

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404090
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Dowell, Jr.; Steven Clay et al.

Storage system

Abstract

A modular container storage system includes multiple container units configured to be assembled to one another in an indefinite expanded state for enabling sheltered access to the stored items through a corridor enclosure, and in a compacted state for convenient transport and/or reduced storage space.

Inventors: Dowell, Jr.; Steven Clay (Moody, TX), Dowell, Sr.; Steven Clay (Moody, TX)

Applicant: Dowell, Jr.; Steven Clay (Moody, TX); Dowell, Sr.; Steven Clay (Moody, TX)

Family ID: 96434044

Appl. No.: 19/082918

Filed: March 18, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250236453 A1	Jul. 24, 2025

Related U.S. Application Data

us-provisional-application US 63622382 20240118

Publication Classification

Int. Cl.: B65D88/02 (20060101); B65D88/00 (20060101); B65D88/52 (20060101); B65D90/02 (20190101); B65D90/18 (20060101)

U.S. Cl.:

CPC **B65D88/005** (20130101); **B65D88/027** (20130101); **B65D88/526** (20130101);
 B65D90/023 (20130101); **B65D90/18** (20130101); B65D2590/0066 (20130101);
 B65D2590/023 (20130101)

Field of Classification Search

CPC: B65D (88/005); B65D (88/027); B65D (88/526); B65D (90/023); B65D (2590/0066);
 B65D (88/022); B65D (21/02); B65D (21/0201); B65D (21/0204)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6039527	12/1999	Myllari	414/812	B65D 88/022
2019/0257073	12/2018	Ledoux	N/A	B65D 88/027
2021/0237967	12/2020	Havener	N/A	B65D 19/06
2021/0339943	12/2020	Austrheim	N/A	B65D 21/0201
2022/0169440	12/2021	Zacharia	N/A	B65D 21/0209
2024/0140692	12/2023	Nylund	N/A	B65D 88/022

Primary Examiner: Anderson; Don M
Attorney, Agent or Firm: Plager Schack LLP

Background/Summary

RELATED APPLICATION (1) This application claims benefit to U.S. Application No. 63/622,382 filed Jan. 18, 2024, which is incorporated by reference herein in its entirety.

BACKGROUND

- (1) The present disclosure relates generally to storage systems and more specifically to storage systems that allow for convenient transport.
- (2) Maintaining a large number of items in an organized fashion may be challenging, especially when such items need to be transported, e.g., upon moving or traveling. As such, an improved system for conveniently storing multiple items in a manner which allows for easy access and transport is desirable.

SUMMARY

- (3) According to various embodiments, disclosed is a storage system, comprising multiple container units configured to assemble to one another, wherein the container assembly can be switched between an expanded (i.e., open) state for enabling access to stored items and a compacted (i.e., closed or collapsed) state for convenient transport and/or reduced storage space. Additionally, in the expanded state, the multiple container units form an enclosed structure including a central walk-in corridor.
- (4) In certain embodiments, the storage system may comprise a pair of container units; a pair of corridor panels; and at least one door, wherein the pair of container units, the pair of corridor panels, and the door are configured to switch between an expanded state of assembly and a collapsed state of assembly. In further embodiments, each container unit in the pair of container units includes a casing providing an interior compartment with a front facing opening in each of the

container units, each casing being formed from a top wall, a bottom wall opposite the top wall, a first side wall extending vertically between a first side of the top wall and a first side of the bottom wall, a second side wall extending vertically between a second side of the top wall and a second side of the bottom wall, and a rear wall extending vertically between a rear side of the top wall and a rear side of the bottom wall. In certain embodiments, the pair of container units are positioned opposite one another such that the front facing opening in a first container unit of the pair of container units faces the front facing opening in a second container unit of the pair of container units. In the expanded state of assembly the pair of container units are separated at a distance allowing for attachment of the pair of corridor panels between the pair of container units, and wherein one of the pair of corridor panels is coupled between a front edge in the top wall of the first container unit and a front edge in the top wall of the second container unit to form a ceiling structure between pair of container units; the other one of the pair of corridor panels is coupled between a front edge in the bottom wall of the first container unit and a front edge in the bottom wall of the second container unit to form a floor structure between pair of container units; and the door is rotationally coupled proximate a front edge in the first side wall of the first container unit via interlocking hinge components, the door further configured to shut against a front edge in the second side wall of the second container unit. In the collapsed state of assembly, the pair of container units are adjoined to close said distance separating the container units in the expanded state, the adjoined container units having a top enclosure formed by the joinder of the top walls of the first container unit and the second container unit, a bottom enclosure opposite the top enclosure formed by the joinder of the bottom wall of the first container unit and the bottom wall of the second container unit, a first side enclosure formed by the joinder of the first side wall of the first container unit and the second side wall of the second container unit, a second side enclosure opposite the first side enclosure and formed by the joinder of the second side wall of the first container unit and the first side wall of the second container unit, a third side enclosure formed by the rear wall of the first container unit, and a fourth side enclosure opposite the third side enclosure and formed by the rear wall of the second container unit.

(5) In further embodiments, the first container unit and the second container unit are configured to attach to one another side by side, such that the storage system can be expanded to include a multiple number of container unit pairs, which in the expanded state of assembly comprise a first container unit row of multiple first container units attached side by side to one another, and a second container unit row of an equal number of second container units attached side by side to one another, wherein the first container unit row and the second container unit row are positioned opposite one another such that the front facing opening in each of the first container unit faces the front facing opening in an oppositely disposed second container unit. Additionally, the first container unit row and the second container unit row form a corridor enclosure in the expanded state of assembly, the corridor enclosure including a ceiling and floor structure formed via a multiple pair of corridor panels corresponding to the number of container unit pairs, the system further including two doors which are attached to an entrance side and to an exit side of the corridor enclosure, wherein a user may walk through the corridor enclosure to access any of the container units for placing or removing stored items from the container units.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) The detailed description of some embodiments of the invention will be made below with reference to the accompanying figures, wherein the figures disclose one or more embodiments of the present invention.

(2) FIGS. 1-14 depict a storage system comprising multiple container units according to certain

- embodiments, the multiple container units being configured to assemble and be switched between an expanded state of assembly, and a compacted state of assembly.
- (3) FIG. 1 is a perspective view depicting four assembled container units in the expanded state and with a door component in a closed position, according to certain embodiments.
- (4) FIG. 2 shows the assembly of FIG. 1, but with the door component opened.
- (5) FIG. 3 is an exploded view of the storage system.
- (6) FIG. 4 is a section view along line 4-4 in FIG. 1.
- (7) FIG. 5 is a section view along line 5-5 in FIG. 1.
- (8) FIG. 6 is a front perspective view of depicting a pair of assembled container units in the compacted state.
- (9) FIG. 7 is a rear perspective view of the pair of container units depicted in FIG. 6.
- (10) FIG. 8 is a section view along line 8-8 in FIG. 6.
- (11) FIG. 9 is a side view showing the pair of assembled container units tilted on integrated wheels.
- (12) FIG. 10 is a detailed perspective view of a latch component of the system.
- (13) FIG. 11 is a detailed perspective view of a door hinge component of the system.
- (14) FIG. 12 is a detailed section view of a cam buckle strap component of the system.
- (15) FIG. 13 is a perspective view of the pair container units assembled in the compacted state, and including lift feet.
- (16) FIG. 14 is a plan side view of showing stacking of a first and a second pair of container units, both in the compacted state, and supported on the lift feet.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

(17) According to various embodiments as depicted in FIGS. 1-14, disclosed is a storage method and/or system **100** for storing various items, comprising multiple container units **10** which may be selectively switched between an expanded assembly **100A** for enabling access to the stored items, and a collapsed/compacted assembly **100B** for convenient transport and/or reduced storage space. In certain embodiments, the expanded assembly may comprise a first row **10A** of one or more container units **10** and a second row **10B** of an equal number of container units **10** facing opposite the first row, wherein container units **10** in each row are configured to securely assemble side by side indefinitely. Storage system **100** may further include corridor panels **42** configured to form a floor structure **42A** and ceiling structure **42B** between the oppositely disposed first and second container rows **10A**, **10B**, such that a corridor enclosure is formed between rows **10A** and **10B**. In further embodiments, storage system **100** may provide a pair of doors **31**, wherein one door **31** may be assembled over an entrance opening and the other door may be assembled over an exit opening in the formed corridor enclosure when the assembly is in its expanded state, wherein each door may be opened to allow access into the assembled storage system, or locked shut to securely enclose the assembled storage system. As such, storage system **100** allows a user to assemble an unlimited number of container units **10** for forming a storage system of customizable size, which may be compacted for convenient transport, or set up as an enclosed storage space for various items. In the compacted state, the container units **10** are configured to securely attach in a manner which keeps the stored items in place, so that the items do not need to be removed and repacked. Furthermore, doors **31** and panels **42** are also configured to store compactly with the container units to provide an overall structure which is convenient for transport.

(18) In certain embodiments, each container unit **10** may include a casing **11** generally comprising a top wall **11C**, a bottom wall **11D**, a first side wall **11E**, a second side wall **11G**, and a rear wall **11F**, which together define an interior compartment with a front facing opening. In embodiments, casing **11** is a unitary molded piece. In some embodiments, casing **11** may include top and bottom weatherstripping **13** and compartment weatherstrippings **15** for a protective water seal in the formed corridor unit. In some embodiments, each casing **11** may be about 50 inches to about 100 inches in vertical length, or about 79.8 inches in vertical length. Each casing **11** may further have a depth of about 10 inches to about 40 inches, or about 19.5 inches. Each casing **11** may further have

a width of about 15 inches to about 40 inches, or about 27 inches. It shall be appreciated however that casing **11** may be of any dimensions in alternate embodiments.

(19) In further embodiments, each casing **11** is configured to support a plurality of storage bins **30** that may be slidable into and out of the interior compartment of the casing through the front opening, thus providing storage drawers within casing **11**. In some embodiments, each casing **11** may include horizontal slots **11A** (i.e., tracks) which may be molded within internal surfaces of side walls **11E**, **11G**, for slidably receiving side tabs **11B** in storage bins **30**. In some embodiments, multiple slots **11A** may be incrementally spaced throughout the vertical length of casing **11** (e.g., about 1 inch to about 5 inches apart), to allow multiple alternative placement locations for bins **30** and to further allow bins of a variety of different vertical dimensions to be stored in casing **11**. In one embodiment, storage bins **30** may each comprise a main bin container (also referred to as “bin container **30**”) having a top opening and a bin lid **30A** configured to enclose the top opening. Bin container **30** and bin lid **30A** may each include conforming top side tabs **11B** configured to slide into the horizontal slots **11A** in casing **11**, so that main container **30** may be used with or without lid **30A**. In further embodiments, each bin container **30** may comprise a front finger hole **30B** and/or a drawer pull knob on a front facing side of the bin. In some further embodiments, each bin container **30** may include a vertical rear channel **30C** (e.g., about 1 inch deep) and a bin rear cord cutout **30D** in a rear facing side of the bin which provides unobstructed access from each bin interior to container unit **10** inlet/outlets holes **24**. It shall be appreciated that different bin/drawer configurations may be used in alternate embodiments.

(20) In certain embodiments, container units **10** are configured to secure to one another side by side to form a row of multiple units in the expanded state, using outer draw latches **16** and inner draw latches **18**. In some embodiments, draw latches **16**, **18** may comprise rubber latches configured to insert into corresponding recesses in the casings to effectuate a watertight seal while securing the assembled units. In some embodiments, side walls **11E** and **11G** may comprise mating bumps **17A** and depressions **17B** at corresponding vertical/horizontal locations, configured to puzzle fit together for assisting in the proper alignment and stable securement of container units when connected side by side in the expanded state and when stacked in the compacted state. In further embodiments, a pair of oppositely facing container units **10** may be secured to one another in the compacted state using a latch component **20** provided on first side wall **11E** to securely engage lockable butterfly latches **21** and butterfly latches **22** provided in second side wall **11G** at corresponding vertical locations as depicted. In one embodiment, a latch component **20**, and butterfly latches **21**, **22** may be located within top, middle, and bottom sections of side walls **11E** and **11G**, respectively, and proximate the front side edges **11H** of the casings as depicted, but are not limited to this option. Draw latches **16**, **18**, corridor panels **42**, ratchet straps **48** (i.e., cam buckle straps), latch component **20**, and butterfly latches **21**, **22** all provide a self-contained attachment mechanism for convenient assembly and conversion between the expanded and collapsed states, which does not require extraneous tools or hardware. It shall be appreciated that different attachment systems and elements may be used in alternate embodiments.

(21) In certain embodiments, each container unit **10**/casing **11** may include bottom wheels **12** and handles **26** for facilitating transport. In some embodiments, handles **26** may be provided on the external surfaces of the top and rear walls **11C**, **11F**, as depicted. In further embodiments, lift foot attachment points **52** may be provided for optional attachment to lift feet **54** (i.e., risers **54**) as depicted in FIGS. **13** and **14**. As such, a compacted pair of container units **10** may be transported by one or more persons using handles **26** and wheels **12**, or one or more compacted pairs may be moved using a forklift and/or risers. It shall be appreciated that any number of wheels, handles, and other types of transport/pull elements may be provided within the walls of casing **11** in alternate embodiments.

(22) In certain embodiments, corridor panels **42** are configured to assemble to the front facing edges of bottom walls **11D** and top walls **11C** to form floor structure **42A** and ceiling structure **42B**,

respectively, between oppositely disposed container units **10**. In certain embodiments, each panel **42** may include ratchet anchor pins **44** which may be disposed proximate a remote end within centrally extending lateral channels in each panel **42**, as depicted. Additionally, anchor pins **28** may be disposed within central grooves proximate front facing edges in bottom walls **11D** and top walls **11C**. Thereby, ratchet straps **48** (i.e., cam buckle straps) may be coupled between anchor pins **28** and ratchet anchor pins **44** to couple panels **42** between each pair of opposing container units **10** to form floor and ceiling structures **42A**, **42B**. In further embodiments, system **100** may be configured to compactly store panel **42** in the compacted state. In one embodiment, back walls **11F** may each include a recessed section **42C** configured to receive a panel **42**, and anchor pins **28** above and below recessed section **42C** as shown. As such, each panel **42** may be attached to the back wall of one of casings **11** by using straps **48** coupled between anchor pins **28** in back wall **11F** and ratchet anchor pins **44** in the panel **42** for secure storage in the compacted state. In some embodiments, each panel **42** may include depressions **42D** and tabs **42E** configured to puzzle fit into corresponding tabs and depressions in the top and bottom front facing edges in casing **11** (for attachment in the expanded state), and in the back walls **11F** (for attachment in the collapsed state). In certain embodiments, each panel **42** may include weatherstripping **43** along its edges for providing a protective water seal in the formed corridor unit. In some further embodiments, each panel may include one or more handles **46**. It is noted that the above-described attachment systems for the panels is self-contained, allowing the panels to be assembled in either the expanded or collapsed state without extraneous tools and/or hardware. It shall be appreciated that panels **42** may have different configurations, including attachment and storage mechanisms in alternate embodiments, as well as optional ancillary components for secondary functionality.

(23) In certain embodiments, storage system **100** includes door attachment and locking elements that enable doors **31** to be functionally attached and locked to container units **10** when assembled in the expanded state, so that doors **31** may enclose over the entrance opening and/or the exit opening in the formed corridor enclosure. In one embodiment, a first side edge of each door **31** may be provided with first hinge halves **36** configured to mate and assemble to second hinge halves **14** provided proximate a front side edge in casing **11** in each container unit **10**, the first and second hinge halves being located at corresponding vertical positions along the door and casing edge, respectively. In certain embodiments, first hinge half **36** may comprise a slotted tube **36A** and pins **38** slidably supported within tube **36A**; second hinge half **14** may comprise a sectioned bracketing tube **14A** including top and bottom sections, configured to coaxially assemble to tube **36** as depicted in FIG. **11**. Pins **38** may slide into top and bottom sections of tube **14A** to secure first and second hinge halves **36**, **14**, and may be slid out of tube **14A** to disengage the hinge halves. It shall be appreciated that different door attachment systems may be used in alternate embodiments; for example, squeeze-release quick-disconnect hinges may be provided in alternate embodiments, which enable doors to be spring snapped into receiving holes, which does not require extraneous tools or hardware.

(24) In further embodiments, a door latch **40** may be provided at a front side of door **31** and is configured to lock shut and securely enclose the assembled storage system provided proximate a front side edge in casing **11** at corresponding vertical positions along the door and casing edges. A padlock **50** inserted within a locking slot in door latch **40** to securely lock the door. It shall be appreciated however that different types of door-locking devices and systems may be used in alternate embodiments. In certain embodiments, hinge halves **14** may be provided in first side wall **11E**, and butterfly latch **21** may be in second side **11G** of casing **11**. As such, when container units **10** and/or rows of multiple container units are positioned facing one another (i.e., to form opposing first container unit row **10A** and second container unit row **10B**), the door attachment site is provided on the entrance side in first container unit row **10A** and the lock engagement site is on the entrance side in the second container unit row **10B**; while at the exit side, the door attachment site is in the in second container unit row **10B**, and the lock engagement is in the first container row

10A. As such, system **100** may include 2 doors **31** which may optionally be used to lock the entrance and exit openings in an assembly of units in the expanded state.

(25) In switching to the compacted state, door(s) **31** are disassembled and removed from the expanded assembly. In certain embodiments, each door **31** may be configured to assemble to system **100** when in the compacted/collapsed state, via a door storage system. Specifically, when container units **10** on opposing sides are collapsed together, door storage system enables door **31** to secure against a surface formed by the unity of side walls **11E** and **11G** on both entrance and exit sides of the collapsed container assembly. In certain embodiments, the door storage system may comprise using draw latch **34** coupled to door **31** which securely connect to receiving locking elements **34A** provided within rear walls **11F**. Additionally, door **31** has a width which is approximately twice the depth of each casing **11** (as well as a vertical length approximately equal to that of the casings **11**), such that when the two container units **11** are collapsed together, door **31** substantially covers the combined side walls **11G**, **11E** as best depicted in FIG. **6**. In further embodiments, each door **31** may comprise bumps **17A** and depressions **17B** configured to puzzle mate to the bumps and depressions in side walls **11E** and **11G** when placed over the combined side walls **11G**, **11E**, for assisting in the proper alignment and stable securement of door **31**. As such, doors **31** may be attached against the side walls of the container units when in the collapsed state for convenient packing. Door may further provide reinforcement to holding the container units together, and further covers the butterfly latches and padlock to protect these components from impact. When expanded, the door is removed, then reattached via the hinges. The above-described door attachment and door storage systems are self-contained and require no extraneous tools/hardware. In some embodiments, each door **31** may include weatherstripping **33** along its edges for providing a protective water seal in the formed corridor unit. In some embodiments, doors **31** may include a hook spine **32** as depicted to provide an attachment point for convenient installation of hooks, mounts, brackets, and/or other various wall storage devices, which does not require extraneous drilling or alteration. It shall be appreciated that doors **31**, and the door attachment and storage systems may have different attachment components and configurations in alternate embodiments.

(26) In some embodiments, inlet/outlet holes **24** may be provided, e.g., within rear wall **11F** for enabling electrical, water, and/or air/ventilation lines to run into the container unit assembly. Such lines may run between inlet/outlet holes **24** through the vertical rear channel **30C** and bin rear cord cutout **30D** and front finger hole **30B** into bin(s) **30**, or around/past the bin(s).

(27) According to an exemplary embodiment, components of storage system **100** (i.e., casings **11**, bins **30**, panels **42**, doors **31**) may generally comprise a high-density polyethylene (HDPE) with a thickness of 0.15 inches which may be made via a molding process, such as rotational molding. In one embodiment, casings **11** may each comprise two stainless steel rods with a diameter of 0.25 inches that are over molded into each component during the rotational molding process. An optional foam insulation may be injected into predesigned cavity walls in the components. In further embodiments, other system components such as handles, latches, each may be attached with bolts, rivets, and other appropriate hardware. In some embodiments, wheels **12** may comprise 10 inch plastic wheels, and weatherstripping material may be approximately ½ inch wide. According to an exemplary embodiment, an assembled pair of container units **10** with the HDPE thicknesses described weighs approximately 320.23 pounds and offers a total storage capacity of 18.82 cubic feet with bins installed or 21.5 cubic feet without bins. Such assembly may have packing dimensions of 79.8 inches×38.9 inches×27.0 inches (H×W×L), wherein the width of the assembly increases from 38.9 inches to 70.0 inches in the expanded configuration. It shall be appreciated that the components of system **100** may comprise any alternative known materials in the field and be of any size and/or dimensions. It shall be appreciated that the components of system **100** may be manufactured and assembled using any known techniques in the field.

(28) Hence, system **100** easily converts between the expanded state to the compacted state while

holding the stored items so that the items do not need to be removed and repacked. In the compacted state, attachment elements **20**, **21**, and **22** secure a pair of compartment units against one another to prevent stored items/bins **30** from falling out, and further hold the ceiling/floor panels **42** and doors **31** together with the unit. The pair of compartment units **10** may be placed in the expanded state by disengaging the attachment elements **20**, **21**, and **22** and pulling apart the pair of compartment units **10**. Thereafter, panels **42** are removed from their respective storage locations, i.e., recesses **42C** in compartment units **10**, by undoing cam-buckle-straps **48**. The panels **42** may then be placed between the two storage compartment halves, i.e. **10A** and **10B**, and secured using same cam-buckle-straps **48** to form a roof and floor structure in the expanded assembly. Optionally, one or more pairs of opposite compartment units which are assembled in the same fashion may be attached to the initially assembled compartment unit pairs using draw latches **16** and **18** which may be recessed rubber latches which aid in waterproofing through high pressure connected seals of the top and bottom weatherstripping **13** and compartment weatherstrippings **15** for a protective water seal in the formed corridor unit. As such, the length and storage capacity of the assembled system **100** may be extended indefinitely. Additionally, doors **31** may be installed at exit and entrance openings in the expanded assembly. The installed doors may be locked shut using a padlock **50** inserted within a locking slot **40**. In expanded/open configuration a user can open any one of the doors and walk into the corridor formed between the compartment units. Once standing inside, the user can place or remove items from the storage bins **30** which can be slid in and out of the compartment units along horizontal slots **11A** (i.e., tracks). In some optional embodiments, electrical, water, air, or any various utilities can be run into the container using inlet/outlet holes **42** on the sides of each container units and run through the vertical rear channel **30C** and bin rear cord cutout **30D** and front finger hole **30B** into bin(s) **30**, or around/past the bin(s). When in the collapsed state, each pair of compartment units can then be hand carried, wheeled, or forklifted to the desired transportation device or repositioned indoors or outdoors as needed, without needing to repack or reorganize the stored items/equipment.

(29) As such, the disclosed system provides a storage assembly which may be hand-carried and converts into a walk-in shipping/transport container which may be used both indoors and outdoors. In embodiments, the compacted assembly fits through doorways, windows, stairways, in basements, garages, etc., and is water sealed to withstand adverse weather when placed outdoors. The system includes connecting compartments that enable the storage space to be increased indefinitely to suit all storage needs, with bins that are tightly secured eliminating movement during transport, and expands into an open configuration (allowing the user to walk inside through the detachable/connectable door(s)). In the closed/compacted configuration, one or more individuals may either pickup and roll the system on wheels, or transport the system using a forklift. Furthermore, due to the rectangular configuration, the system is easily stackable for ease of transport in vehicles, aircraft, ships, intermodal containers, and may also be transported as a shipping container itself and palletized. When arriving at the destination(s), the compacted assembly can be expanded and put into use as a walk-in shelter and storage container immediately with all equipment where it was left on departure. Thus, a user may avoid manual repacking as items stay in place during transport and nearly completely replaces the need to reorganize items upon arrival to any destination. The system further eliminates the need to use boxes, and other disposable storage systems that are commonly discarded after moving, thus further being beneficial in reducing operating expenses and waste.

(30) The disclosed system may be particularly useful for professionals with high volumes of specialized equipment and uniforms, providing a highly organized and convenient means of storage and hassle-free transport. Additionally, individuals seeking to move domestically or overseas may easily transport their belongings without cardboard boxes, wooden crates, and other containers which are susceptible to damage due to weather, crushing/smashing, and damage enroute and lastly creates rubbish and debris after being unpacked at the destination.

(31) It shall be appreciated that the disclosed system and/or components of the disclosed system may have different configurations in alternate embodiments. For example, in some alternate embodiments, the system may be configured to include additional accessories or functional components. Additionally, different designs for the bins, doors, walls, inlet/outlets, latches, handles, etc. may be used in alternate embodiments. In some alternate embodiments, system **100** may be configured to include additional inlet/outlets, internal separating doors, insulation installed into the wall cavities, etc. It shall be appreciated that the disclosed system may be adapted for other uses in alternate embodiments. Such alternate uses may include, but are not limited to an indoor farming/gardening system (e.g., for hydro/aquaponic and vertical farm growing/harvesting), a mobile modular home system, a secured long term storage system, a medical storage system (e.g., for blood and human specimens), a food storage system, amongst others. Additionally, the disclosed system may be beneficial for use in disaster relief, first responder readiness/response, combat ready force deployments in conflict or training, and expeditionary/exploratory missions in austere or off-world environments.

(32) It shall be understood that the orientation or positional relationship indicated by terms such as “upper”, “lower”, “front”, “rear”, “left”, “right”, “top”, “bottom”, “inside”, “outside” is based on the orientation or positional relationship shown in the accompanying drawings, which is only for convenience and simplification of describing the disclosed subject matter, rather than indicating or implying that the indicated device or element must have a specific orientation or are constructed and operated in a specific orientation, and therefore should not be construed as a limitation of the present invention.

(33) As used herein, the articles “a” and “an” are intended to include one or more items, and may be used interchangeably with “one or more.” Where only one item is intended, the term “one” or similar language is used. Also, as used herein, the terms “has”, “have”, “having”, “with” or the like are intended to be open-ended terms. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

(34) The constituent elements of the disclosed device and system listed herein are intended to be exemplary only, and it is not intended that this list be used to limit the device of the present application to just these elements. Persons having ordinary skill in the art relevant to the present disclosure may understand there to be equivalent elements that may be substituted within the present disclosure without changing the essential function or operation of the device. Terms such as ‘approximate,’ ‘approximately,’ ‘about,’ etc., as used herein indicate a deviation of within $\pm 10\%$. Relationships between the various elements of the disclosed device as described herein are presented as illustrative examples only, and not intended to limit the scope or nature of the relationships between the various elements. Persons of ordinary skill in the art may appreciate that numerous design configurations may be possible to enjoy the functional benefits of the inventive systems. Thus, given the wide variety of configurations and arrangements of embodiments of the present invention the scope of the invention is reflected by the breadth of the claims below rather than narrowed by the embodiments described above.

Claims

1. A storage system, comprising: a pair of container units; a pair of corridor panels; and a door, wherein the pair of container units, the pair of corridor panels, and the door are configured to switch between an expanded state of assembly and a collapsed state of assembly, wherein each container unit in the pair of container units includes a casing providing an interior compartment with a front facing opening in each of the container units, each casing being formed from a top wall, a bottom wall opposite the top wall, a first side wall extending vertically between a first side of the top wall and a first side of the bottom wall, a second side wall extending vertically between a second side of the top wall and a second side of the bottom wall, and a rear wall extending

vertically between a rear side of the top wall and a rear side of the bottom wall, wherein the pair of container units are positioned opposite one another such that the front facing opening in a first container unit of the pair of container units faces the front facing opening in a second container unit of the pair of container units, wherein in the expanded state of assembly the pair of container units are separated at a distance allowing for attachment of the pair of corridor panels between the pair of container units, and wherein: one of the pair of corridor panels is coupled between a front edge in the top wall of the first container unit and a front edge in the top wall of the second container unit to form a ceiling structure between pair of container units, the other one of the pair of corridor panels is coupled between a front edge in the bottom wall of the first container unit and a front edge in the bottom wall of the second container unit to form a floor structure between pair of container units, and the door is rotationally coupled proximate a front edge in the first side wall of the first container unit via interlocking hinge components, the door configured to shut against a front edge in the second side wall of the second container unit, wherein in the collapsed state of assembly, the pair of container units are adjoined to close said distance separating the container units in the expanded state, the adjoined container units having a top enclosure formed by the joiner of the top walls of the first container unit and the second container unit, a bottom enclosure opposite the top enclosure formed by the joiner of the bottom wall of the first container unit and the bottom wall of the second container unit, a first side enclosure formed by the joiner of the first side wall of the first container unit and the second side wall of the second container unit, a second side enclosure opposite the first side enclosure and formed by the joiner of the second side wall of the first container unit and the first side wall of the second container unit, a third side enclosure formed by the rear wall of the first container unit, and a fourth side enclosure opposite the third side enclosure and formed by the rear wall of the second container unit.

2. The storage system of claim 1, wherein in the collapsed state, the door and the pair of corridor panels are configured to store flatly against the adjoined container units, and within dedicated storage spaces therein.

3. The storage system of claim 2, wherein a recess for receiving one of the pair of corridor panels is provided in each rear wall in the first and second container units.

4. The storage system of claim 2, wherein the door is configured to overlay the first side enclosure or the second side enclosure for storing flatly against the adjoined container units, wherein the door and each of the first and second side enclosures include mating bumps and depressions so that the surface of the door is configured to puzzle fit with the surface of the first side enclosure and with the surface of the second side enclosure.

5. The storage system of claim 1, further comprising a second door, which is rotationally coupled proximate a front edge in the second side wall of the first container unit via interlocking hinge components, the second door configured to shut against a front edge in the first side wall of the second container unit.

6. The storage system of claim 1, the system including self-contained attachment components for attachment of the door and corridor panels in both the expanded state of assembly and in the collapsed state of assembly.

7. The storage system of claim 1, wherein the first container unit and the second container unit are configured to attach to one another side by side, such that the storage system can be expanded to include a multiple number of container unit pairs, which in the expanded state of assembly comprise a first container unit row of multiple first container units attached side by side to one another, and a second container unit row of an equal number of second container units attached side by side to one another, wherein the first container unit row and the second container unit row are positioned opposite one another such that the front facing opening in each of the first container unit faces the front facing opening in an oppositely disposed second container unit.

8. The storage system of claim 7, wherein the first container unit row and the second container unit row form a corridor enclosure in the expanded state of assembly, the corridor enclosure including a

ceiling and floor structure formed via a multiple pair of corridor panels corresponding to the number of container unit pairs, the corridor enclosure further enclosed via an entrance side door and an exit side door of the storage system, wherein a user may walk through the corridor enclosure to access any of the container units for placing or removing stored items from the container units.

9. The storage system of claim 1, further comprising storage bins that are slidable into and out of the interior compartment through the front opening in each container unit.

10. The storage system of claim 1, further comprising weatherstripping material in the pair of container units, the pair of corridor panels, and the door for providing a sealed enclosure in both the expanded state of assembly and the collapsed state of assembly.
