

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12404804

Kind Code

B1

Date of Patent

September 02, 2025

Inventor(s)

Owoeye; Eyitayo James et al.

Heat exchangers for gas turbine engines

Abstract

A heat exchanger for a gas turbine engine includes an outer shell extending between a first end and a second end opposite the first end. The outer shell defines a first fluid chamber, a first fluid inlet adjacent the first end, and a first fluid outlet adjacent the second end. The outer shell also defines a first plurality of second fluid inlet openings located between the first end and the second end and a second fluid outlet adjacent the second end. The heat exchanger includes a manifold disposed within the outer shell. The manifold defines a second fluid chamber and a second plurality of second fluid inlet openings. The heat exchanger defines a first fluid pathway and a second fluid pathway.

Inventors: Owoeye; Eyitayo James (Houston, TX), Gerstler; William D. (Niskayuna, NY), Erno; Daniel J. (Clifton Park, NY), Osusky; Lana Maria (Rexford, NY)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 96788228

Assignee: General Electric Company (Evendale, OH)

Appl. No.: 18/586886

Filed: February 26, 2024

Publication Classification

Int. Cl.: F02C7/14 (20060101); F02C6/08 (20060101)

U.S. Cl.:

CPC F02C6/08 (20130101); F02C7/14 (20130101); F05D2250/18 (20130101);
F05D2260/213 (20130101)

Field of Classification Search

CPC: F02C (7/14); F02C (6/08); F28F (1/36); F28F (1/38); F28F (9/22); F28F (2250/04); F28F (2250/10); F28F (9/26); F28F (13/06); F28F (2250/06)

USPC: 165/156; 165/184; 165/139

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10100736	12/2017	Niergarth et al.	N/A	N/A
10539076	12/2019	Niergarth et al.	N/A	N/A
10739077	12/2019	Gerstler et al.	N/A	N/A
10775046	12/2019	Snyder et al.	N/A	N/A
10830147	12/2019	Snyder	N/A	N/A
10830540	12/2019	Sennoun et al.	N/A	N/A
10982553	12/2020	Rathay et al.	N/A	N/A
11118784	12/2020	Sweeney et al.	N/A	N/A
11209222	12/2020	Colson	N/A	N/A
11359864	12/2021	Becene et al.	N/A	N/A
11519332	12/2021	Underwood et al.	N/A	N/A
2010/0038056	12/2009	Ellsworth et al.	N/A	N/A
2014/0076293	12/2013	Gaiser	165/100	F28D 7/0066
2019/0024987	12/2018	Moore	N/A	F28F 3/02
2020/0016704	12/2019	Stewart, Jr. et al.	N/A	N/A
2021/0180885	12/2020	Wiedenhoefer et al.	N/A	N/A
2021/0207897	12/2020	Sabo et al.	N/A	N/A
2022/0026155	12/2021	Zaffetti et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109585035	12/2019	CN	N/A
112833685	12/2020	CN	N/A
2377013	12/1977	FR	N/A

Primary Examiner: Sung; Gerald L

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

FIELD

(1) The present disclosure relates to heat exchangers for gas turbine engines.

BACKGROUND

(2) A gas turbine engine generally includes a turbomachine and a rotor assembly. Gas turbine engines, such as turbofan engines, may be used for aircraft propulsion. In the case of a turbofan engine, the rotor assembly may be configured as a fan assembly.

(3) Gas turbine engines typically incorporate one or more heat exchangers to control thermal

energy of various fluids passing through various components of the gas turbine engine. However, heat exchangers that reduce the weight and complexity of gas turbine engines are desirable.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A full and enabling disclosure of the present disclosure, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:
- (2) FIG. 1 is perspective view of an exemplary aircraft in accordance with an exemplary embodiment of the present disclosure.
- (3) FIG. 2 is a cross-sectional view of a gas turbine engine in accordance with an exemplary aspect of the present disclosure.
- (4) FIG. 3 is a schematic view of a lubrication system in accordance with an exemplary aspect of the present disclosure.
- (5) FIG. 4A is a perspective view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (6) FIG. 4B is a cross-section view of the heat exchanger of FIG. 4A in accordance with an exemplary aspect of the present disclosure.
- (7) FIG. 4C is a partial, top view of the heat exchanger of FIG. 4A in accordance with an exemplary aspect of the present disclosure.
- (8) FIG. 4D is an interior view of the heat exchanger of FIG. 4A in accordance with an exemplary aspect of the present disclosure.
- (9) FIG. 4E is an interior view of the heat exchanger of FIG. 4A in accordance with an exemplary aspect of the present disclosure.
- (10) FIG. 5 is a schematic view of a combustion section of a gas turbine engine in accordance with an exemplary aspect of the present disclosure.
- (11) FIG. 6 is a schematic view of a thermal management system in accordance with an exemplary aspect of the present disclosure.
- (12) FIG. 7A is a perspective, cross-section view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (13) FIG. 7B is a detailed, cross-section view of the heat exchanger of FIG. 7A in accordance with an exemplary aspect of the present disclosure.
- (14) FIG. 8A is an interior view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (15) FIG. 8B is an interior view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (16) FIG. 9 is a perspective, cross-section view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (17) FIG. 10 is a perspective, cross-section view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (18) FIG. 11A is a top view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.
- (19) FIG. 11B is a bottom view of the heat exchanger of FIG. 11A in accordance with an exemplary aspect of the present disclosure.

DETAILED DESCRIPTION

- (20) Reference will now be made in detail to present embodiments of the disclosure, one or more examples of which are illustrated in the accompanying drawings. The detailed description uses numerical and letter designations to refer to features in the drawings. Like or similar designations

in the drawings and description have been used to refer to like or similar parts of the disclosure.

(21) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary.

(22) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

(23) As used herein, the terms “first”, “second”, and “third” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(24) Furthermore, the terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(25) Additionally, the terms “low,” “high,” or their respective comparative degrees (e.g., lower, higher, where applicable) each refer to relative speeds, pressures or temperatures within an engine or thermal management system, unless otherwise specified. For example, a “low-pressure turbine” operates at a pressure generally lower than a “high-pressure turbine.” Alternatively, unless otherwise specified, the aforementioned terms may be understood in their superlative degree. For example, a “low-pressure turbine” may refer to the lowest maximum pressure turbine within a turbine section, and a “high-pressure turbine” may refer to the highest maximum pressure turbine within the turbine section.

(26) The terms “coupled,” “fixed,” “attached to,” and the like refer to both direct coupling, fixing, or attaching, as well as indirect coupling, fixing, or attaching through one or more intermediate components or features, unless otherwise specified herein.

(27) The present disclosure is generally related to heat exchangers for gas turbine engines. Conventional thermal management systems route hot engine fluid to external heat exchangers for cooling. Routing such hot engine fluids requires additional piping and larger pump sizes in order to route the engine fluid, which increases the weight of the gas turbine engine. However, including a heat exchanger directly within a fluid or a fluid pathway may reduce the amount of routing, piping, and pumps required to pass the engine fluid through the heat exchanger for cooling.

(28) Referring now to the drawings, FIG. 1 is a perspective view of an exemplary aircraft 10 in accordance with an exemplary embodiment of the present disclosure.

(29) The aircraft 10 includes a fuselage 12, wings 14 attached to the fuselage 12, and an empennage 16. The aircraft 10 further includes a propulsion system 18 that produces a propulsive thrust to propel the aircraft 10 in flight, during taxiing operations, etc. Although the propulsion system 18 is shown attached to the wings 14, in other example embodiments it may additionally or alternatively include one or more aspects coupled to other parts of the aircraft 10, such as, for example, the empennage 16, the fuselage 12, or both. The configuration of the aircraft 10 described above and shown in FIG. 1 is provided only to place the present subject matter in an exemplary field of use. Thus, the present subject matter may be readily adaptable to any manner of aircraft.

(30) The propulsion system 18 includes at least one engine. In the exemplary embodiment shown, the aircraft 10 includes a pair of gas turbine engines 20. Each gas turbine engine 20 is mounted to the aircraft 10 in an under-wing configuration. Each gas turbine engine 20 is capable of selectively generating a propulsive thrust for the aircraft 10. The gas turbine engines 20 may be configured to burn various forms of fuel including, but not limited to unless otherwise provided, jet fuel/aviation turbine fuel, and hydrogen fuel.

(31) FIG. 2 is a cross-sectional view of a gas turbine engine in accordance with an exemplary aspect of the present disclosure.

(32) In at least one example embodiment, the gas turbine engine 20 is a multi-spool, high-bypass

turbofan jet engine, sometimes also referred to as a “turbofan engine.” As shown in FIG. 2, the gas turbine engine **20** defines an axial direction “A” (extending parallel to a longitudinal centerline **22** provided for reference), a radial direction “R”, and a circumferential direction “C” extending about the longitudinal centerline **22**. In general, the gas turbine engine **20** includes a fan section **24** and a turbomachine **26** disposed downstream from the fan section **24**.

(33) The turbomachine **26** depicted generally includes an engine housing, casing, or core cowl **28** that defines an annular core inlet **30**. The core cowl **28** at least partially encases, in serial flow relationship, a compressor section including a booster or low-pressure compressor (“LPC”) **32** and a high-pressure compressor (“HPC”) **34**, a combustion section **36**, a turbine section including a high-pressure turbine (“HPT”) **38** and a low-pressure turbine (“LPT”) **40**, and at least a portion of a jet exhaust nozzle **42**. Together, these components or sections make up a core engine **46** of the turbomachine **26**.

(34) The turbomachine **26** includes a high-pressure shaft **44** drivingly connecting the high-pressure turbine **38** to the high-pressure compressor **34**, and a low-pressure shaft **43** drivingly connecting the low-pressure turbine **40** to the low-pressure compressor **32**. The compressor section, combustion section **36**, turbine section, and jet exhaust nozzle **42** together define a working gas flow path **50** (also referred to as a core air flow path) through the gas turbine engine **20**.

(35) For the embodiment depicted, the fan section **24** includes a fan **52** having a plurality of fan blades **54** coupled to a disk **56** in a spaced apart manner. As depicted, the fan blades **54** extend outwardly from disk **56** generally along the radial direction R. Each fan blade **54** is rotatable with the disk **56** about a pitch axis P by virtue of the fan blades **54** being operatively coupled to a pitch change mechanism **58** configured to collectively vary the pitch of the fan blades **54**, e.g., in unison. The fan blades **54**, disk **56**, and pitch change mechanism **58** are together rotatable about the longitudinal centerline **22** by the low-pressure shaft **43**.

(36) In an exemplary embodiment, as shown in FIG. 2, the gas turbine engine **20** further includes a power gearbox or gearbox **60**. The gearbox **60** includes a plurality of gears for adjusting a rotational speed of the fan **52** relative to a rotational speed of the low-pressure shaft **43**, such that the fan **52** and the low-pressure shaft **43** may rotate at more efficient relative speeds. The gearbox **60** may be any type of gearbox suitable to facilitate coupling the low-pressure shaft **43** to the fan **52** while allowing each of the low-pressure turbine **40** and the fan **52** to operate at a desired speed. For example, in some embodiments, the gearbox **60** may be a reduction gearbox. Utilizing a reduction gearbox may enable the comparatively higher speed operation of the low-pressure turbine **40** while maintaining fan speeds sufficient to provide for increased air bypass ratios, thereby allowing for efficient operation of the gas turbine engine **20**. Moreover, utilizing a reduction gearbox may allow for a reduction in turbine stages that would otherwise be present (e.g., in direct drive engine configurations), thereby providing a reduction in weight and complexity of the engine.

(37) Referring still to the exemplary embodiment of FIG. 2, disk **56** is connected to the gearbox **60** via a fan shaft **62** of the gas turbine engine **20**. The disk **56** is covered by a front hub **64** of the fan section **24** (sometimes also referred to as a “spinner”). The front hub **64** is aerodynamically contoured to promote an airflow through the plurality of fan blades **54**. Additionally, the fan section **24** includes an annular fan casing or nacelle **66** that circumferentially surrounds the fan **52** and/or at least a portion of the turbomachine **26**. The nacelle **66** is supported relative to the turbomachine **26** by a plurality of circumferentially spaced struts or outlet guide vanes **68** in the embodiment depicted. Moreover, a downstream section **70** of the nacelle **66** extends over an outer portion of the turbomachine **26** to define a bypass airflow passage **72** therebetween.

(38) In at least one example embodiment, such as the exemplary embodiment shown, the aircraft **10** includes a fuel delivery system **200** for providing a fuel flow to a combustor of the combustion section **36** of the turbomachine **26**. The fuel delivery system **200** includes a fuel source, such as a fuel tank **205**, for storing the fuel. Although not depicted, the fuel tank **205** may be positioned in one or both of the wings **14**.

(39) In at least one example embodiment, such as the exemplary embodiment shown, the aircraft **10** may include one or more accessory systems configured to support the operation of the gas turbine engines **20** or the aircraft **10** including the gas turbine engines **20**. For example, the gas turbine engine **20** includes a lubrication system **100** configured to provide a lubricant to, e.g., various bearings and gear meshes in the compressor section (including the low-pressure compressor **32** and high-pressure compressor **34**), the turbine section (including the high-pressure turbine **38** and the low-pressure turbine **40**), the high-pressure shaft **44**, the low-pressure shaft **43**, and the gearbox **60**. The lubricant provided by the lubrication system **100** may increase the useful life of such components and may remove a certain amount of heat from such components.

(40) FIG. **3** is a schematic view of a lubrication system **100** in accordance with an exemplary aspect of the present disclosure. The lubrication system **100** may be configured in a similar manner as the exemplary lubrication system **100** discussed above with reference to FIG. **2**.

(41) In at least one example embodiment, the lubrication system **100** includes a first fluid circuit **302** in fluid communication with a sump **300**, a heat exchanger **305**, one or more thermal loads **310**, and a pump **315**. The sump **300** is configured to store a thermal fluid, and the pump **315** is configured to circulate the thermal fluid through the first fluid circuit **302**. The one or more thermal loads **310** may include engine bearings, an accessory gearbox, a reduction gearbox, or a combination thereof. In at least one example embodiment, the thermal fluid is an oil-based lubricant or lubrication oil. Additionally, the first fluid circuit **302** may be formed of one or more fluid conduits.

(42) In at least one example embodiment, such as the exemplary embodiment depicted, the heat exchanger **305** is disposed within the sump **300**. Accordingly, the heat exchanger **305** is in direct fluid communication with the thermal fluid stored within the sump **300** through the first fluid circuit **302**, as will be discussed in greater detail with respect to FIGS. **4A-4E**, below. Positioning the heat exchanger **305** in direct fluid communication with the sump **300** may reduce the weight and complexity of the gas turbine engine **20**. For example, fluid lines associated with the lubrication system **100** may be reduced such that there are no fluid lines extending through the working gas flow path **50** of the gas turbine engine **20** to the sump **300**.

(43) In at least one example embodiment, a second fluid circuit **320** is in fluid communication with the heat exchanger **305**. The second fluid circuit **320** is fluidly isolated from the first fluid circuit **302**, as will also be discussed in greater detail with respect to FIGS. **4A-4E**, below. The second fluid circuit **320** may be in fluid communication with one or more components of the gas turbine engine **20**. Fluid within the second fluid circuit **320** can be any fluid, or mixture of fluids, flowing in the liquid or gaseous state, or flowing in a mixed two-phase state, suitable for meeting thermal performance needs within the gas turbine engine **20**. For example, cooling air from the low-pressure compressor **32** may flow into the heat exchanger **305** and remove heat from the thermal fluid within the heat exchanger **305**. The cooling air absorbs heat from the thermal fluid and is then directed out of the heat exchanger **305** to the high-pressure compressor **34**, which may improve the thermal efficiency of the high-pressure compressor **34**. Additionally, because heat is removed from the thermal fluid, the cooled thermal fluid is directed to the one or more thermal loads **310** downstream of the heat exchanger **305**.

(44) In other example embodiments, the heat exchanger **305** may be disposed or embedded within the core cowl **28**, such as in an undercowl region of the core cowl **28**, within the bypass airflow passage **72**, or any other suitable location for cooling components of the gas turbine engine **20**. Moreover, the heat exchanger **305** may comprise a gas-to-gas heat exchanger, a gas-to-liquid heat exchanger, or a liquid-to-liquid heat exchanger. In still other example embodiments, the heat exchanger **305** may comprise an air-to-air heat exchanger that is embedded within or in fluid communication with the undercowl region of the core cowl **28** to cool full authority digital engine control (“FADEC”) components.

(45) FIG. **4A** is a perspective view of a heat exchanger **305** in accordance with an exemplary aspect

of the present disclosure. FIG. 4B is a cross-section view of the heat exchanger 305 of FIG. 4A in accordance with an exemplary aspect of the present disclosure. FIG. 4C is a partial, top view of the heat exchanger 305 of FIG. 4A in accordance with an exemplary aspect of the present disclosure. FIG. 4D is an interior view of the heat exchanger 305 of FIG. 4A in accordance with an exemplary aspect of the present disclosure. FIG. 4E is an interior view of the heat exchanger 305 of FIG. 4A in accordance with an exemplary aspect of the present disclosure. The exemplary heat exchanger 305 of FIGS. 4A through 4E may be incorporated into the lubrication system 100 described above with respect to FIG. 3 (e.g., as the heat exchanger 305 depicted).

(46) In at least one example embodiment, the heat exchanger 305 includes an outer shell 400 extending between a first end 401 and a second end 402 opposite the first end 401. The outer shell 400 defines a first fluid chamber 403 (see FIG. 4B), a first fluid inlet 405 adjacent the first end 401 (see FIGS. 4A, 4B), and a first fluid outlet 410 adjacent the second end 402 (see FIGS. 4A, 4B). The first fluid inlet 405 and the first fluid outlet 410 are in fluid communication with the first fluid chamber 403. The outer shell 400 also defines at least a portion of a second fluid outlet 412. For example, the second fluid outlet 412 may extend from at least a portion of the outer shell 400 adjacent the second end 402, as shown in FIG. 4A. In at least one example embodiment, such as the exemplary embodiment depicted, the outer shell 400 has a cylindrical shape.

(47) In other example embodiments, however, the outer shell 400 may have a triangular, rectangular, or other polygonal shape.

(48) In at least one example embodiment, such as the exemplary embodiment depicted, the outer shell 400 defines a first plurality of second fluid inlet openings 415 between the first end 401 and the second end 402. The first plurality of second fluid inlet openings 415 may be spaced about a circumference of the outer shell 400. In some example embodiments, such as the exemplary embodiment depicted, the first plurality of second fluid inlet openings 415 may be evenly spaced about the outer shell 400.

(49) It will be appreciated, however, that in other example embodiments, the first plurality of second fluid inlet openings 415 may be unevenly spaced about the outer shell 400. In some additional example embodiments, the first plurality of second fluid inlet openings 415 may be staggered about the outer shell 400. For example, a row or column of the first plurality of second fluid inlet openings 415 may be offset from an adjacent row or column of the first plurality of second fluid inlet openings 415. In still other example embodiments, a row or column of the first plurality of second fluid inlet openings 415 may be aligned with an adjacent row or column of the first plurality of second fluid inlet openings 415.

(50) In at least one example embodiment, the heat exchanger 305 further includes a manifold 420 disposed within the first fluid chamber 403 of the heat exchanger 305 such that the first fluid chamber 403 is defined between the outer shell 400 and the manifold 420. The manifold 420 defines a second fluid chamber 425 and a second plurality of second fluid inlet openings 430 in fluid communication with the second fluid chamber 425. In at least one example embodiment, an end of the manifold 420 adjacent the first end 401 of the outer shell 400 is sealed and an opposite end of the manifold 420 is in fluid communication with the second fluid outlet 412, as shown in FIG. 4B. In at least one example embodiment, such as the exemplary embodiment depicted, the manifold 420 includes a cylindrical shape.

(51) It will be appreciated, however, that in other example embodiments, the manifold 420 comprises a conical shape. For example, a diameter of the manifold may increase or decrease from the end adjacent the first end 401 to the opposite end adjacent the second end 402.

(52) In at least one example embodiment, the second plurality of second fluid inlet openings 430 may be arranged about the manifold 420 in a helical pattern, as shown in FIGS. 4D-4E. The heat exchanger 305 may also include a plurality of tubes 435. The plurality of tubes 435 may fluidly couple the first plurality of second fluid inlet openings 415 to the second plurality of second fluid inlet openings 430. In at least one example embodiment, the plurality of tubes 435 comprise a

cylindrical shape extending between the first plurality of second fluid inlet openings **415** and the second plurality of second fluid inlet openings **430**.

(53) In other example embodiments, one or more of the plurality of tubes **435** may comprise a tortuous, twisted, coiled, or zig-zag shape.

(54) In at least one example embodiment, the heat exchanger **305** includes a plurality of baffles **440**. Each of the plurality of baffles **440** are coupled between each of the plurality of tubes **435**. Accordingly, the plurality of tubes **435** and the plurality of baffles **440** may also be arranged in a helical pattern, as shown in FIGS. **4D-4E**. Moreover, the plurality of baffles **440** coupled between each of the plurality of tubes **435** act as tube fins to increase heat transfer surface area, which increases the efficiency of the heat exchanger **305**.

(55) In at least one example embodiment, the heat exchanger **305** defines a first fluid pathway **445** defining at least a portion of the second fluid circuit **320**. The first fluid pathway **445** extends from the first fluid inlet **405**, through the first fluid chamber **403**, and to the first fluid outlet **410**. Moreover, the first fluid pathway **445** extends through the first fluid chamber **403** following the helical path defined by the plurality of tubes **435** and the plurality of baffles **440**, as shown in FIG. **4D**. In at least one example embodiment, the first fluid pathway **445** may make two or more turns about the manifold **420**, as shown in FIGS. **4D-4E**. In additional example embodiments, each of the plurality of tubes **435** and the plurality of baffles **440** may be coupled such that the first fluid pathway **445** is continuous about the manifold **420**. In other example embodiments, the first fluid pathway **445** may be non-continuous such that one or more of the plurality of tubes **435** are not coupled to one or more of the plurality of baffles **440**.

(56) The heat exchanger **305** also defines a second fluid pathway **450** defining at least a portion of the first fluid circuit **302**. The second fluid pathway **450** is fluidly isolated from the first fluid pathway **445**. The second fluid pathway **450** extends from the first plurality of second fluid inlet openings **415**, through the second plurality of second fluid inlet openings **430**, and to the second fluid outlet **412**. More specifically, the second fluid pathway **450** is defined by the first plurality of second fluid inlet openings **415**, the plurality of tubes **435**, the second plurality of second fluid inlet openings **430**, and the second fluid outlet **412**.

(57) In at least one example embodiment, the first fluid pathway **445** is configured to receive a first fluid and the second fluid pathway **450** is configured to receive a second fluid. The first fluid may comprise a gas and the second fluid may comprise a liquid. For example, the second fluid pathway **450** may be configured to receive the thermal fluid through the first plurality of second fluid inlet openings from the sump **300** via the first fluid circuit **302** and the first fluid pathway **445** may be configured to receive a flow of the cooling air into the first fluid inlet **405** from the low-pressure compressor **32** via the second fluid circuit **320**. The flow of cooling air is configured to circulate through the heat exchanger **305** in the helical pattern defined by the first fluid pathway **445**. The helical pattern of the first fluid pathways **445** enables the flow of cooling air to contact a greater surface area of the manifold **420**, the plurality of tubes **435**, and the plurality of baffles **440**, which also act as tube fins, as discussed above, maximizing heat transfer between the cooling air and the thermal fluid. For example, the flow of cooling air is able to absorb a greater amount of heat from the thermal fluid flowing through the second fluid pathway **450** as the cooling air flows along the plurality of tubes **435** and the plurality of baffles **440** from the first fluid inlet **405** to the first fluid outlet **410**. Additionally, heat transfer effectiveness also increases by increasing the number of turns of the helical pattern of the first fluid pathway **445**. Accordingly, a temperature of the cooling air increases as it flows through the heat exchanger **305** such that the air exiting via the first fluid outlet **410** has a higher temperature than the air that entered via the first fluid inlet **405**.

(58) Referring now to FIG. **5**, a schematic view is provided of a heat exchanger and a combustion section of a gas turbine engine in accordance with another exemplary aspect of the present disclosure. The heat exchanger **305** may be configured in a similar manner as the exemplary heat exchanger **305** discussed above with reference to FIGS. **3** through **4E**, and the gas turbine engine

may be configured in a similar manner as the exemplary gas turbine engine **20** described above with reference to FIG. **2**.

(59) For example, the gas turbine engine includes a combustion section **36** operable with a fuel delivery system **200** of, e.g., an aircraft incorporating the gas turbine engine. For the example embodiment depicted in FIG. **5**, the heat exchanger **305** is disposed in fluid communication with the fuel delivery system **200**. In particular, the combustion section **36** includes one or more fuel nozzles, such as a fuel injector **500**, configured to receive a flow of liquid fuel from a fuel tank **205** through the fuel delivery system and provide the liquid fuel to a combustion chamber **505** of the combustion section **36** for combustion, as indicated by arrow **503**. The fuel injector **500** may be any appropriate type of fuel injector, nozzle, fuel/air mixer, or other liquid fuel dispensing device, atomizing device, or mixing device. In at least one example embodiment, the heat exchanger **305** is in direct fluid communication with the fuel injector **500**, as will be discussed in greater detail with respect to FIG. **6**. Positioning the heat exchanger **305** in direct fluid communication with the fuel injector **500** may reduce the weight and complexity of the gas turbine engine **20**. For example, fluid lines associated with the fuel delivery system **200** may be reduced such that there are fewer fluid lines extending through the working gas flow path **50** of the gas turbine engine **20** to the fuel tank **205**.

(60) In at least one example embodiment, the combustion section **36** includes an inner liner **510** and an outer liner **515**. The inner liner **510** may at least partially define the combustion chamber **505** and a fluid pathway may be defined between the inner liner **510** and the outer liner **515**. For example, the fluid pathway between the inner liner **510** and the outer liner **515** may be configured to receive compressed air, indicated by arrows **518**, from the high-pressure compressor **34**. The inner liner **510** defines a plurality of openings **520** in fluid communication with the combustion chamber **505** such that at least a portion of the compressed air may enter the combustion chamber **505** through the plurality of openings **520**.

(61) Referring still to FIG. **5**, combustion gases **530** flow from the combustion chamber **505** into the turbine section of the gas turbine engine **20**. For example, the combustion gases **530** flow into the high-pressure turbine **38** and the low-pressure turbine **40**, as shown in FIG. **2**.

(62) FIG. **6** is a schematic view of a thermal management system in accordance with an exemplary aspect of the present disclosure. The exemplary thermal management system of FIG. **6** may be configured in a similar manner as the exemplary system of FIG. **5**.

(63) For example, in the exemplary embodiment depicted, the thermal management system includes a heat exchanger **305** and is operable with a fuel delivery system **200** and a gas turbine engine (not shown). The fuel delivery system **200** includes a first fluid pathway **600** and a second fluid pathway **605**. The first fluid pathway **600** is in fluid communication with a high-pressure compressor **34** of the gas turbine engine, the heat exchanger **305**, a first pump **610**, and the combustion chamber **505**. The first fluid pathway **600** may also be in fluid communication with the high-pressure turbine **38**, as is indicated by the phantom lines in FIG. **6**. The first pump **610** is configured to move air from the heat exchanger **305** to one or both of the combustion chamber **505** and the high-pressure turbine **38**.

(64) In at least one example embodiment, the second fluid pathway **605** is in fluid communication with the fuel tank **205**, a second pump **615**, one or more secondary heat exchangers **620**, the heat exchanger **305**, and the combustion chamber **505**. The second pump **615** is configured to provide a flow of fuel from the fuel tank **205** to the combustion chamber **505**. In at least one example embodiment, the flow of fuel may pass through the one or more secondary heat exchangers **620** before entering the heat exchanger **305**. The one or more secondary heat exchangers **620** are configured to increase a temperature of the fuel as it travels along the second fluid pathway **605** to the heat exchanger **305**.

(65) In at least one example embodiment, the heat exchanger **305** is disposed in direct fluid communication with the fuel injector **500**. For example, the heat exchanger **305** may be integrated

with a fuel injector stem and immersed in the working gas flow path **50**. As will be appreciated, the heat exchanger **305** of FIG. **6** may be configured in substantially the same manner as the exemplary heat exchanger discussed above with reference to FIGS. **4A-4E**. In such an exemplary embodiment, with reference back to FIGS. **4A-4E**, the first fluid inlet **405** may be configured to receive the flow of fuel through the first fluid inlet **405**. The fuel may flow into the first fluid chamber **403** from the first fluid inlet **405** and travel along the helical path of the first fluid pathway **445**. For example, fuel may flow through the first fluid inlet **405**, along the helical path defined by the plurality of tubes **435** and the plurality of baffles **440** within the first fluid chamber **403**, and out of the first fluid outlet **410** to the combustion chamber **505**.

(66) Still referring to FIGS. **4A-4E**, the first plurality of second fluid inlet openings **415** of the heat exchanger **305** may be configured to receive the compressed air from the high-pressure compressor **34** via the first fluid pathway **600** (FIG. **6**). The compressed air may travel along the second fluid pathway **450**. For example, the compressed air may enter the second fluid chamber **425** defined by the manifold **420** through the first plurality of second fluid inlet openings **415**, the plurality of tubes **435**, and the second plurality of second fluid inlet openings **430**. The compressed air then exits the heat exchanger through second fluid outlet **412**.

(67) In at least one example embodiment, the fuel traveling along the first fluid pathway **445** within the first fluid chamber **403** absorbs heat from the compressed air flowing along the second fluid pathway in the second fluid chamber **425**. Accordingly, the fuel acts as a heat sink and absorbs heat from the compressed air before it is discharged from the gas turbine engine **20**. Moreover, the temperature of the fuel is increased before the fuel reaches the combustion chamber **505**, increasing the efficiency of combustion.

(68) Referring now to FIGS. **7A** and **7B**, FIG. **7A** is a perspective, cross-section view of a heat exchanger in accordance with another exemplary aspect of the present disclosure. FIG. **7B** is a detailed, cross-section view of the heat exchanger of FIG. **7A** in accordance with an exemplary aspect of the present disclosure.

(69) In at least one example embodiment, a heat exchanger **700** includes a core **705**, a first fluid inlet manifold **710**, a first fluid outlet manifold **715**, a second fluid inlet manifold **720**, and a second fluid outlet manifold **725**. Each of the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725** may have a helical shape extending about a core axis **730** between a first end **701** and a second end **702** of the heat exchanger **700**. In at least one example embodiment, the heat exchanger **700** may comprise a substantially cylindrical shape.

(70) In at least one example embodiment, the core **705** includes a plurality of unit cells. The plurality of unit cells of the core **705** may define a first fluid flow path **735** and a second fluid flow path **740**. The first fluid flow path **735** may be fluidly isolated from the second fluid flow path **740**. For example, the first fluid flow path **735** may be defined by the first fluid inlet manifold **710**, at least a portion of the core **705**, and the first fluid outlet manifold **715**. The second fluid flow path **740** may be defined by the second fluid inlet manifold **720**, at least a portion of the core **705**, and the second fluid outlet manifold **725**.

(71) In at least one example embodiment, the heat exchanger **700** includes a second fluid inlet nozzle **755** adjacent to the first end **701** and a second fluid outlet nozzle **750** adjacent to the second end **702**. In at least one example embodiment, the second fluid inlet nozzle **755** is fluidly coupled to the second fluid inlet manifold **720** and the second fluid outlet nozzle **750** is fluidly coupled to the second fluid outlet manifold **725**. For example, the second fluid inlet manifold **720** may be configured to receive a second fluid via the second fluid inlet nozzle **755** and the second fluid outlet manifold **725** may be configured to discharge the second fluid via the second fluid outlet nozzle **750**. In at least one example embodiment, the second fluid comprises a gas. For example, the gas may include bleed air from one or both of the low-pressure compressor **32** and the high-pressure compressor **34**.

(72) In at least one example embodiment, the first fluid inlet manifold **710** defines a plurality of first fluid inlets **728**. For example, an outer circumferential end of the first fluid inlet manifold **710** defines the plurality of first fluid inlets **728** extending to an outer casing of the heat exchanger **700**. The plurality of first fluid inlets **728** may comprise a plurality of perforations or openings. In at least one example embodiment, the heat exchanger **700** also includes a first fluid outlet nozzle **733** adjacent the first end **701**. For example, the first fluid outlet nozzle **733** is fluidly coupled to the first fluid outlet manifold **715**. In at least one example embodiment, the first fluid inlet manifold **710** receives the first fluid via the plurality of first fluid inlets **728** and the first fluid outlet nozzle **733** is configured to discharge the first fluid from the first fluid inlet manifold **710**. The first fluid may comprise a liquid. For example, the first fluid may include fuel from the fuel tank **205** or a thermal fluid, such as oil, from the sump **300**. In at least one example embodiment, the first fluid inlet manifold **710** includes a first plurality of tubes **760** and the first fluid outlet manifold **715** includes a second plurality of tubes **765**. The first plurality of tubes **760** and the second plurality of tubes **765** extended substantially perpendicular to a length of the first fluid inlet manifold **710** and the first fluid outlet manifold **715**, respectively. The first plurality of tubes **760** and the second plurality of tubes **765** are configured to fluidly couple the second fluid flow path **740** to the core **705**. For example, the first plurality of tubes **760** fluidly couple the second fluid inlet manifold **720** to the core **705** and the second plurality of tubes **765** fluidly couple the core **705** to the second fluid outlet manifold **725**. Accordingly, the second fluid flow path **740** is configured to flow through the second fluid inlet manifold **720**, the first plurality of tubes **760**, the core **705**, the second plurality of tubes **765**, and the second fluid outlet manifold **725**.

(73) Additionally, the first plurality of tubes **760** and the second plurality of tubes **765** fluidly isolate the first fluid flow path **735** from the second fluid flow path **740**. For example, the first fluid flow path **735** is defined between the first plurality of tubes **760** within the first fluid outlet manifold **715** and between the second plurality of tubes **765** within the first fluid inlet manifold **710**. While the first fluid flow path **735** is fluidly isolated from the second fluid flow path **740**, the first fluid flow path **735** and the second fluid flow path **740** are in thermal communication through the first plurality of tubes **760** and the second plurality of tubes **765**. Such thermal communication increases the surface area for heat transfer and may reduce the size and weight of the heat exchanger **305**. For example, the size, wall thickness, and material type of the first plurality of tubes **760** and the second plurality of tubes **765** can be engineered to determine the desired thermal resistance between the first fluid flow path **735** and the second fluid flow path **740** that occurs through the first plurality of tubes **760** and the second plurality of tubes **765**.

(74) In at least one example embodiment, the heat exchanger **700** may be disposed in a sump, such as the sump **300** discussed above with respect to FIG. **3**. In such embodiments, the second fluid inlet manifold **720** receives the second fluid, such as a cooling airflow from the compressor section of the gas turbine engine **20**, such as from the high-pressure compressor **34** or the low-pressure compressor **32**, via the second fluid inlet nozzle **755**. The second fluid flows along the second fluid flow path **740** from the second fluid inlet manifold **720**, through the first plurality of tubes **760**, and to the core **705**. Additionally, the first fluid inlet manifold **710** is configured to receive the first fluid. For example, the first fluid may be a thermal fluid or oil received from the sump **300**, as discussed with respect to FIG. **3**. The thermal fluid or oil flows along the first fluid flow path **735** from the first fluid inlet manifold **710** and into the core **705**, via the plurality of first fluid inlets **728**. Within the core **705**, the second fluid (or the cooling airflow) is configured to absorb heat from the first fluid. The helical patterns of the first fluid flow path **735** and the second fluid flow path **740** about the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold, **720**, the second fluid outlet manifold **725**, and the core **705** maximizes heat transfer as the flow of cooling air contacts a greater surface of the second fluid within the core **705** of the heat exchanger **700**. For example, the cooling air flow is able to absorb a greater amount of heat from the first fluid. Accordingly, a temperature of the cooling air increases such that the second

fluid has a greater temperature as it flows from the core **705**, through the second fluid outlet manifold **725**, and out of the heat exchanger **700** via the second fluid outlet nozzle **750**. Moreover, a temperature of the first fluid decreases as it flows out of the core **705**, through the first fluid outlet manifold **715**, and out of the heat exchanger **700** via the first fluid outlet nozzle **733**.

(75) In other example embodiments, the heat exchanger **700** may be in fluid communication with the fuel injector **500** and immersed in the working gas flow path **50**, as discussed with respect to FIG. **6**. In such embodiments, the second fluid inlet manifold **720** may be configured to receive fuel from the fuel tank **205** via the second fluid inlet nozzle **755**. The fuel may flow along the second fluid flow path **740** from the second fluid inlet manifold **720** and into the core **705**. Additionally, the first fluid inlet manifold **710** may be configured to receive compressed air from the high-pressure compressor **34**. The compressed air may flow from the first fluid inlet manifold **710** into the core **705** via the plurality of first fluid inlets **728**. Within the core **705**, the fuel absorbs heat from the compressed air. Accordingly, the fuel acts as a heat sink and absorbs heat from the compressed air before it is discharged from the gas turbine engine **20**. Moreover, the temperature of the fuel is increased before the fuel reaches the combustion chamber **505**, increasing the efficiency of combustion.

(76) From the core **705**, the fuel flows along the second fluid flow path **740** to the second fluid outlet manifold **725**, where the fuel is then discharged from the heat exchanger **700** via the second fluid outlet nozzle **750**. The compressed air, which has now been cooled by the fuel, exits the core **705** and flows along the first fluid flow path **735** to the first fluid outlet manifold **715**, where the compressed air is discharged from the heat exchanger **700** via the first fluid outlet nozzle **733**.

(77) In at least one example embodiments, the first fluid flow path **735** is configured to flow in a first direction and the second fluid flow path **740** is configured to flow in a second direction. The second direction may be opposite from the first direction such that the first fluid flow path **735** and the second fluid flow path **740** are in a counter-flow arrangement. For example, the first fluid flow path **735** may flow in a helical pattern about the core axis **730** from the second end **702** to the first end **701** of the heat exchanger **700**. The second fluid flow path **740** may flow in a helical pattern about the core axis **730** from the first end **701** to the second end **702** of the heat exchanger **700**.

(78) In other example embodiments (not shown), the second direction may be the same as the first direction, such as in a co-flow arrangement. For example, the first fluid flow path **735** may flow in a helical pattern about the core axis **730** from the first end **701** to the second end **702** of the heat exchanger **700**. The second fluid flow path **740** may flow in a helical pattern about the core axis **730** from the first end **701** to the second end **702** of the heat exchanger **700**.

(79) In at least one example embodiment, the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725** are arranged in a stacked relationship. For example, the first fluid inlet manifold **710** may be adjacent a second side **712** of the core **705** and the first fluid outlet manifold **715** may be adjacent a first side **711** of the core **705**. Additionally, the second fluid inlet manifold **720** may be adjacent the first fluid outlet manifold **715** and the second fluid outlet manifold **725** may be adjacent the first fluid inlet manifold **710**. For example, the first fluid inlet manifold **710** may be between the core **705** and the second fluid outlet manifold **725** and the first fluid outlet manifold **715** may be positioned between the core **705** and the second fluid inlet manifold **720**. In such embodiments, the first fluid outlet manifold **715** and the second fluid inlet manifold **720** may be stacked from the first side **711** of the core **705** and the first fluid inlet manifold **710** and the second fluid outlet manifold **725** may be stacked from the second side **712** of the core **705**.

(80) In at least one example embodiment, the heat exchanger **700** includes a plurality of modules **770**. For example, each of the plurality of modules **770** may include the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725**. As shown in FIG. **7A**, each of the plurality of modules **770** may be stacked to form the heat exchanger **700**. Additionally, the core **705**, the first fluid inlet manifold

710, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725** of each of the plurality of modules **770** may be fluidly coupled such that the first fluid flow path **735** and the second fluid flow path **740** are continuous through each of the plurality of modules **770**. The plurality of modules **770** allow a size of the heat exchanger **700** to be customizable to suit a particular need and based on a desired position of the heat exchanger **700** within the gas turbine engine **20**. For example, a size of the heat exchanger **700** may be modified based on whether the heat exchanger **700** is disposed in the sump **300** (as discussed with respect to FIG. **3**) or disposed in a fluid communication with the working gas flow path **50** (as discussed with respect to FIG. **6**).

(81) FIG. **8A** is an interior view of a heat exchanger in accordance with an exemplary aspect of the present disclosure. FIG. **8B** is an interior view of a heat exchanger in accordance with an exemplary aspect of the present disclosure.

(82) In at least one example embodiment, a heat exchanger **800** may be similar or analogous to the heat exchanger **700** discussed above with respect to FIGS. **7A-7B**. For example, the heat exchanger **800** includes the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725**. However, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725** of FIGS. **8A-8B** may be positioned differently relative to the core **705** compared to the heat exchanger **700** discussed with respect to FIGS. **7A-7B**.

(83) In at least one example embodiment, the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725** are arranged in a stacked relationship. For example, the second fluid outlet manifold **725** and the first fluid inlet manifold **710** may be adjacent the first side **711** of the core **705**, and the first fluid outlet manifold **715** and the second fluid inlet manifold **720** are adjacent the second side **712** of the core **705**. Moreover, the second fluid outlet manifold **725** may be between the core **705** and the first fluid inlet manifold **710**. The first fluid outlet manifold **715** may be between the core **705** and the second fluid inlet manifold **720**. In such embodiments, the second fluid outlet manifold **725** and the first fluid inlet manifold **710** may be stacked from the first side **711** of the core and the first fluid outlet manifold **715** and the second fluid inlet manifold **720** may be stacked from the second side **712** of the core **705**. In other example embodiments, the second fluid inlet manifold **720** may be adjacent the first side **711** of the core **705**, such as between the core **705** and the first fluid inlet manifold **710**, and the second fluid outlet manifold **725** may be adjacent the second side **712** of the core **705**, such that the first fluid outlet manifold **715** is between the core **705** and the second fluid outlet manifold **725**.

(84) In at least one example embodiment, the heat exchanger **800** includes a plurality of modules **870**. Each of the plurality of modules **870** include the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725**. As shown in FIG. **8B**, each of the plurality of modules **770** may be stacked to form the heat exchanger **800**. Additionally, the core **705**, the first fluid inlet manifold **710**, the first fluid outlet manifold **715**, the second fluid inlet manifold **720**, and the second fluid outlet manifold **725** of each of the plurality of modules **870** may be fluidly coupled such that the first fluid flow path **735** and the second fluid flow path **740** are continuous through each of the plurality of modules **870**. The plurality of modules **870** allow a size of the heat exchanger **800** to be customizable to suit a particular need and based on a desired position of the heat exchanger **800** within the gas turbine engine **20**. For example, a size of the heat exchanger **800** may be modified based on whether the heat exchanger **800** is disposed in the sump **300** (as discussed with respect to FIG. **3**) or disposed in a fluid communication with the working gas flow path **50** (as discussed with respect to FIG. **6**).

(85) In at least one example embodiment (not shown), the heat exchanger **700** may be disposed or embedded within the core cowl **28**, such as in an undercowl region of the core cowl **28**, within the bypass airflow passage **72**, or any other suitable location for cooling components of the gas turbine

engine **20**. Moreover, the heat exchanger **700** may comprise a gas-to-gas heat exchanger, a gas-to-liquid heat exchanger, or a liquid-to-liquid heat exchanger. In other example embodiments, the heat exchanger **700** may comprise an air-to-air heat exchanger that is embedded within or in fluid communication with the undercowl region of the core cowl **28** to cool full authority digital engine control (“FADEC”) components.

(86) Referring now to FIG. **9**, FIG. **9** is a perspective, cross-section view of a heat exchanger **900** in accordance with another exemplary aspect of the present disclosure. The heat exchanger **900** may be used in place of the heat exchanger **700**, as shown in FIGS. **7A-8B**, in some example embodiments.

(87) In at least one example embodiment, the heat exchanger **900** is similar to the heat exchanger **700**, as shown in FIGS. **7A-7B**. However, the heat exchanger **900** includes a first end nozzle **955** adjacent the first end **701** and a second end nozzle **950** adjacent the second end **702**. The first end nozzle **955** and the second end nozzle **950** may each include a divider **903**. For example, the divider **903** may extend along the core axis **730** within each of the first end nozzle **955** and the second end nozzle **950**.

(88) In at least one example embodiment, the second end nozzle **950** includes a first fluid inlet side **905** on one side of the divider **903** and a second fluid outlet side **910** on another side of the divider **903**. The first fluid inlet side **905** and the second fluid outlet side **910** may be fluidly isolated by the divider **903**. The first fluid inlet side **905** may be configured to receive the first fluid and supply the first fluid to the first fluid inlet manifold **710**. The second fluid outlet side **910** may be configured to receive the second fluid from the second fluid outlet manifold **725** and discharge the second fluid from the heat exchanger **900**.

(89) In at least one example embodiment, the first end nozzle **955** includes a first fluid outlet side **915** on one side of the divider **903** and a second fluid inlet side **920** on another side of the divider **903**. The first fluid outlet side **915** and the second fluid inlet side **920** may be fluidly isolated by the divider **903**. The first fluid outlet side **915** may be configured to receive the first fluid from the first fluid outlet manifold **715** and discharge the first fluid from the heat exchanger **900**. The second fluid inlet side **920** may be configured to receive the second fluid and supply the second fluid to the second fluid inlet manifold **720**.

(90) In other example embodiments, the first fluid inlet side **905** may discharge the first fluid received from the first fluid outlet manifold **715** and discharge the first fluid from the heat exchanger **900**, and the second fluid outlet side **910** may be configured to receive the second fluid and supply the second fluid to the second fluid inlet manifold **720**. In such embodiments, the first fluid outlet side **915** may be configured to supply the first fluid to the first fluid inlet manifold **710**, and the second fluid inlet side **920** may be configured to receive the second fluid from the second fluid outlet manifold **725** and discharge the second fluid from the heat exchanger **900**.

(91) In at least one example embodiment, the first fluid flow path **735** is configured to flow in a first direction and the second fluid flow path **740** is configured to flow in a second direction through the heat exchanger **900** in a similar manner as the heat exchanger **700** discussed above with respect to FIGS. **7A-8B**. For example, the second direction may be opposite the first direction.

(92) In other example embodiments, the first direction and the second direction may be the same. For example, the first fluid flow path **735** and the second fluid flow path **740** are configured to flow in parallel or in the same direction. In such a parallel flow arrangement of the heat exchanger **900**, the first fluid inlet side **905** of the second end nozzle **950** is configured to supply the first fluid to the first fluid inlet manifold **710** and the second fluid outlet side **910** of the second end nozzle **950** is configured to supply the second fluid to the second fluid inlet manifold **720**. Additionally, the first fluid outlet side **915** of the first end nozzle **955** may be configured to receive the first fluid from the first fluid outlet manifold **715** and discharge the first fluid from the heat exchanger **900**, and the second fluid inlet side **920** of the first end nozzle **955** may be configured to receive the second fluid from the second fluid outlet manifold **725** and discharge the second fluid from the heat

exchanger **900**.

(93) In other example embodiments, the parallel flow arrangement may flow in an opposite direction such that the first fluid outlet side **915** of the first end nozzle **955** is configured to supply the first fluid to the first fluid inlet manifold **710** and the second fluid inlet side **920** of the first end nozzle **955** is configured to supply the second fluid to the second fluid inlet manifold **720**. Additionally, the first fluid inlet side **905** of the second end nozzle **950** may be configured to receive the first fluid from the first fluid outlet manifold **715** and discharge the first fluid from the heat exchanger **900**, and the second fluid outlet side **910** of the second end nozzle **950** may be configured to receive the second fluid from the second fluid outlet manifold **725** and discharge the second fluid from the heat exchanger **900**.

(94) Referring now to FIG. **10**, a perspective, cross-section view of a heat exchanger **1000** in accordance with another exemplary aspect of the present disclosure is depicted. The heat exchanger **1000** may be used in place of the heat exchanger **700**, as shown in FIGS. **7A-8B**, in some example embodiments.

(95) In at least one example embodiment, the heat exchanger **1000** is similar to the heat exchanger **900**, as shown in FIG. **9**. However, the heat exchanger **1000** includes two distinct tubes in place of the first fluid inlet side **905** and the second fluid inlet side **920** of the second end nozzle **950**, as shown in FIG. **10**. Similarly, the first fluid outlet side **915** and the second fluid inlet side **920** of the first end nozzle **955** may comprise two distinct tubes, as shown in FIG. **10**. The first fluid inlet side **905**, the second fluid inlet side **920**, the first fluid outlet side **915**, and the second fluid inlet side **920** of the heat exchanger **1000** may function in a similar or analogous manner as the first fluid inlet side **905**, the second fluid inlet side **920**, the first fluid outlet side **915**, and the second fluid inlet side **920** of the heat exchanger **900** discussed above with respect to FIG. **9**.

(96) FIG. **11A** is a top view of a heat exchanger **1100** in accordance with an exemplary aspect of the present disclosure. FIG. **11B** is a bottom view of the heat exchanger **1100** of FIG. **11A** in accordance with an exemplary aspect of the present disclosure. The heat exchanger **1100** may be similar or analogous to the heat exchanger **700**, as shown in FIGS. **7A-8B**, with differences that will be discussed below. Moreover, the heat exchanger **1100** may be used in place of the heat exchanger **700**, as shown in FIGS. **7A-8B**, in some example embodiments.

(97) In at least one example embodiment, a surface of the heat exchanger **1100** adjacent the first end **701** defines a first opening **1105** and a surface of the heat exchanger **1100** adjacent the second end **702** defines a second opening **1110**. The first opening **1105** may be in fluid communication with the second fluid inlet manifold **720** and the second opening **1110** may be in fluid communication with the second fluid outlet manifold **725**. In at least one example embodiment, the first fluid inlet manifold **710** receives the first fluid via the second fluid outlet nozzle **750**. The first fluid flows from the first fluid inlet manifold **710**, through the core **705**, through the first fluid outlet manifold **715**, and out of the heat exchanger **1100** through the second fluid inlet nozzle **755**. The second fluid inlet manifold **720** receives the second fluid via the first opening **1105**. The second fluid flows from the second fluid inlet manifold **720**, through the first plurality of tubes **760**, through the core **705**, through the second plurality of tubes **765**, through the second fluid outlet manifold **725**, and exits the heat exchanger **1100** through the second opening **1110**. In such embodiments, the first fluid and the second fluid are in a counter-flow arrangement, as described above with respect to FIGS. **7A-7B**. In other example embodiments (not shown), the first fluid and the second fluid may flow through the heat exchanger **1100** in a parallel or co-flow arrangement.

(98) Alternatively, the second fluid outlet nozzle **750** and the second fluid inlet nozzle **755** may be in fluid communication with the second fluid inlet manifold **720** and the second fluid outlet manifold **725**. In such embodiments, the first opening **1105** and the second opening **1110** may be in fluid communication with the first fluid inlet manifold **710** and the first fluid outlet manifold **715**.

(99) In additional example embodiments, the first opening **1105** may be in fluid communication with the first fluid outlet manifold **715** and the second opening **1110** may be in fluid

communication with the first fluid inlet manifold **710**. For example, the heat exchanger **1100** may include a plurality of tubes, ducts, or conduits extending through the second fluid inlet manifold **720** and the second fluid outlet manifold **725** for fluidly coupling the first opening **1105** to the first fluid outlet manifold **715** and fluidly coupling the second opening **1110** to the first fluid inlet manifold **710**. The plurality of tubes, ducts, or conduits may be similar or analogous to the first plurality of tubes **760** and the second plurality of tubes **765**. In such embodiments, the plurality of tubes, ducts, or conduits extending through the second fluid inlet manifold **720** and the second fluid outlet manifold **725** are fluidly isolated from the second fluid inlet manifold **720** and the second fluid outlet manifold **725** to allow for fluid communication within the second fluid inlet manifold **720** and the second fluid outlet manifold **725** between the plurality of tubes, ducts, or conduits.

(100) In such example embodiments, the first fluid enters the first fluid inlet manifold **710** via the second fluid outlet nozzle **750**, flows through the core **705** and the first fluid outlet manifold **715**, and exits the heat exchanger **1100** through the first opening **1105**. The second fluid enters the second fluid inlet manifold **720** through the second fluid inlet nozzle **755**, flows through the first plurality of tubes **760**, the core **705**, the second plurality of tubes **765**, and the second fluid outlet manifold **725**, and exits the heat exchanger **1100** through the second opening **1110**. In such embodiments, the first fluid and the second fluid are in a counter-flow arrangement, as described above with respect to FIGS. 7A-7B. In other example embodiments (not shown), the first fluid and the second fluid may flow through the heat exchanger **1100** in a co-flow arrangement.

(101) Alternatively, the second fluid outlet nozzle **750** and the first opening **1105** may be in fluid communication with the second fluid inlet manifold **720** and the second fluid outlet manifold **725**. In such embodiments, the second opening **1110** and the second fluid inlet nozzle **755** may be in fluid communication with the first fluid inlet manifold **710** and the first fluid outlet manifold **715**.

(102) In at least one example embodiment, the first opening **1105** and the second opening **1110** may include a slit. For example, one or both of the first opening **1105** and the second opening **1110** may include a rectangular or pie-shaped slit in a surface of the heat exchanger **1100** adjacent the first end **701** and the second end **702**, respectively. In other example embodiments, one or both of the first opening **1105** and the second opening **1110** may include a plurality of openings or slits.

(103) Further aspects are provided by the subject matter of the following clauses:

(104) A heat exchanger for a gas turbine engine, comprising: an outer shell extending between a first end and a second end opposite the first end, the outer shell defining a first fluid chamber, a first fluid inlet adjacent the first end, and a first fluid outlet adjacent the second end, the outer shell further defining a first plurality of second fluid inlet openings located between the first end and the second end, and a second fluid outlet adjacent the second end; and a manifold disposed within the outer shell, the manifold defining a second fluid chamber, and a second plurality of second fluid inlet openings; wherein the heat exchanger defines a first fluid pathway extending from the first fluid inlet, through the first fluid chamber, and to the first fluid outlet; and wherein the heat exchanger further defines a second fluid pathway extending from the first plurality of second fluid inlet openings, through the second plurality of second fluid inlet openings, through the second fluid chamber, and to the second fluid outlet.

(105) The heat exchanger of any preceding clause, wherein the first fluid chamber is defined between the outer shell and the manifold.

(106) The heat exchanger of any preceding clause, wherein: the first fluid pathway is configured to receive a first fluid; and the second fluid pathway is configured to receive a second fluid.

(107) The heat exchanger of any preceding clause, wherein the first fluid comprises a flow of cooling air from the gas turbine engine and the second fluid comprises lubrication oil when the heat exchanger is installed in the gas turbine engine.

(108) The heat exchanger of any preceding clause, wherein the first fluid comprises fuel and the second fluid comprises compressed air.

(109) The heat exchanger of any preceding clause, wherein the first fluid pathway is fluidly

isolated from the second fluid pathway.

(110) The heat exchanger of any preceding clause, wherein the first fluid pathway is helical.

(111) The heat exchanger of any preceding clause, wherein: the manifold extends between the first end and the second end; the first end of the manifold is sealed; and the second end of the manifold defines at least a portion of the second fluid outlet.

(112) The heat exchanger of any preceding clause, wherein the second plurality of second fluid inlet openings are arranged in a helical pattern about the manifold.

(113) The heat exchanger of any preceding clause, further comprising a plurality of tubes fluidly coupling the first plurality of second fluid inlet openings and second plurality of second fluid inlet openings, the plurality of tubes defining at least a portion of the second fluid pathway.

(114) The heat exchanger of any preceding clause, wherein the plurality of tubes comprise a straight shape, a tortuous shape, a twisted shape, a coiled shape, a zig-zag shape, or a combination thereof.

(115) The heat exchanger of any preceding clause, further comprising a plurality of baffles coupled between each of the plurality of tubes and defining at least a portion of the first fluid pathway.

(116) The heat exchanger of any preceding clause, wherein the plurality of baffles comprise tube fins for increasing a surface area of the first fluid pathway.

(117) The heat exchanger of any preceding clause, wherein the plurality of tubes and the plurality of baffles are arranged in a helical pattern about the manifold.

(118) The heat exchanger of any preceding clause, wherein the plurality of tubes and the plurality of baffles are arranged to form the first fluid pathway with a plurality of turns about the manifold.

(119) The heat exchanger of any preceding clause, wherein the heat exchanger is configured to be disposed in a sump of a lubrication system of the gas turbine engine when the heat exchanger is installed in the gas turbine engine.

(120) A gas turbine engine, comprising: a fan; a turbomachine operably coupled to the fan for driving the fan, the turbomachine comprising a compressor section, a combustion section, and a turbine section in serial flow order and together defining a working gas flow path; a sump disposed in the turbomachine and configured to receive a lubrication oil; and the heat exchanger of any preceding clause disposed in the sump; wherein the first fluid pathway is in fluid communication with the compressor section; and wherein the second fluid pathway is in fluid communication with the sump.

(121) The gas turbine engine of any preceding clause, wherein the second fluid pathway is in fluid communication with a bearing or gearbox assembly of the gas turbine engine.

(122) A gas turbine engine, comprising: a fan; a turbomachine operably coupled to the fan for driving the fan, the turbomachine comprising a compressor section, a combustion section, and a turbine section in serial flow order and together defining a working gas flow path; a fuel delivery system including a fuel source configured to deliver fuel from the fuel source to the combustion section; and the heat exchanger v disposed in fluid communication with the fuel delivery system; wherein the first fluid pathway is in fluid communication with the fuel source; and wherein the second fluid pathway is in fluid communication with the compressor section.

(123) The gas turbine engine of any preceding clause, wherein: the first fluid pathway is in fluid communication with the combustion section; and the second fluid pathway is in fluid communication with the combustion section or the turbine section.

(124) The gas turbine engine of any preceding clause, further comprising one or more secondary heat exchangers in fluid communication with the first fluid pathway.

(125) A heat exchanger for a gas turbine engine, comprising: a core including a plurality of unit cells, the core defining a core axis and having a helical shape extending about the core axis between a first end and a second end, the core including a first side adjacent the first end and a second side adjacent the second end, each unit cell of the plurality of unit cells defining a first fluid flow path and a second fluid flow path; a first fluid inlet manifold in fluid communication with the

first fluid flow path; a first fluid outlet manifold in fluid communication with the first fluid flow path; a second fluid inlet manifold in fluid communication with the second fluid flow path, the second fluid inlet manifold defining a plurality of second fluid inlets adjacent the first end or the second end; a second fluid outlet manifold in fluid communication with the second fluid flow path; and a second fluid inlet nozzle adjacent the first end and in fluid communication with the second fluid inlet manifold; and a second fluid outlet nozzle adjacent the second end and in fluid communication with the second fluid outlet manifold; wherein the first fluid inlet manifold, the first fluid outlet manifold, the second fluid inlet manifold, and the second fluid outlet manifold each have a helical shape extending about the core axis between the first end in and the second end.

(126) The heat exchanger of any preceding clause, wherein the second fluid outlet manifold defines a second fluid outlet opening opposite the plurality of second fluid inlets.

(127) The heat exchanger of any preceding clause, wherein: the first fluid inlet manifold is adjacent the second side of the core; the first fluid outlet manifold is adjacent the first side of the core; the second fluid inlet manifold is adjacent the first side of the core; and the second fluid outlet manifold is adjacent the second side of the core.

(128) The heat exchanger of any preceding clause, wherein: the first fluid inlet manifold is between the core and the second fluid outlet manifold; and the first fluid outlet manifold is between the core and the second fluid inlet manifold.

(129) The heat exchanger of any preceding clause, wherein: the first fluid inlet manifold is adjacent the first side of the core; the first fluid outlet manifold is adjacent the second side of the core; the second fluid inlet manifold is adjacent the second side of the core; and the second fluid outlet manifold is adjacent the first side of the core.

(130) The heat exchanger of any preceding clause, wherein: the second fluid outlet manifold is between the core and the first fluid inlet manifold; and the first fluid outlet manifold is between the core and the second fluid inlet manifold.

(131) The heat exchanger of any preceding clause, wherein the first fluid flow path and the second fluid flow path are fluidly isolated.

(132) The heat exchanger of any preceding clause, wherein: the first fluid inlet manifold includes a first plurality of tubes; the first fluid outlet manifold includes a second plurality of tubes; and the first plurality of tubes and the second plurality of tubes define at least a portion of the second fluid flow path.

(133) The heat exchanger of any preceding clause, wherein: the first fluid flow path is configured to flow in a first direction; the second fluid flow path is configured to flow in a second direction; and the first direction is opposite the second direction.

(134) The heat exchanger of any preceding clause, wherein: the first direction is about the core axis from the first end to the second end; and the second direction is about the core axis from the second end to the first end.

(135) The heat exchanger of any preceding clause, wherein: the first fluid flow path is configured to flow in a first direction; the second fluid flow path is configured to flow in a second direction; and the first direction is the same as the second direction.

(136) The heat exchanger of any preceding clause, further comprising: a plurality of modules; wherein each of the plurality of modules include the core, the first fluid inlet manifold, the first fluid outlet manifold, the second fluid inlet manifold, and the second fluid outlet manifold.

(137) The heat exchanger of any preceding clause, wherein the plurality of modules are arranged in a stacked relationship.

(138) The heat exchanger of any preceding clause, wherein: the first fluid inlet manifold defines a plurality of first fluid inlets adjacent an outer circumferential end of the first fluid inlet manifold configured to receive a first fluid; and the second fluid inlet manifold is configured to receive a second fluid via the second fluid inlet nozzle.

(139) The heat exchanger of any preceding clause, wherein: the first fluid outlet manifold is

configured to discharge a first fluid via a first fluid outlet nozzle; and the second fluid outlet manifold is configured to receive a second fluid via the second fluid outlet nozzle.

(140) The heat exchanger of any preceding clause, wherein: the first fluid inlet manifold is configured to receive a first fluid via a first fluid inlet nozzle; and the second fluid inlet manifold is configured to receive a second fluid via the second fluid inlet nozzle.

(141) This written description uses examples to disclose the present disclosure, including the best mode, and also to enable any person skilled in the art to practice the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A heat exchanger for a gas turbine engine, comprising: an outer shell extending between a first end and a second end opposite the first end, the outer shell defining a first fluid chamber, a first fluid inlet adjacent the first end, and a first fluid outlet adjacent the second end, the outer shell further defining a first plurality of second fluid inlet openings located between the first end and the second end, and a second fluid outlet adjacent the second end; a manifold disposed within the outer shell, the manifold defining a second fluid chamber, and a second plurality of second fluid inlet openings; a plurality of tubes fluidly coupling the first plurality of second fluid inlet openings and the second plurality of second fluid inlet openings; and a plurality of baffles, each baffle of the plurality of baffles coupled between adjacent ones of the plurality of tubes; wherein the heat exchanger defines a first fluid pathway extending from the first fluid inlet, through the first fluid chamber, and to the first fluid outlet; and wherein the heat exchanger further defines a second fluid pathway extending from the first plurality of second fluid inlet openings, through the second plurality of second fluid inlet openings, through the second fluid chamber, and to the second fluid outlet; and wherein the plurality of tubes and the plurality of baffles define a helical surface defining the first fluid pathway about the manifold.
2. The gas turbine engine of claim 1, wherein the first plurality of second fluid inlet openings are disposed along a length of the outer shell defined between the first end and the second end, and wherein each of the first plurality of second fluid inlet openings are in fluid communication with a sump of the gas turbine engine.
3. The heat exchanger of claim 1, wherein the first fluid chamber is defined between the outer shell and the manifold.
4. The heat exchanger of claim 1, wherein: the first fluid pathway is configured to receive a first fluid; and the second fluid pathway is configured to receive a second fluid.
5. The heat exchanger of claim 4, wherein the first fluid comprises a flow of cooling air from the gas turbine engine and the second fluid comprises lubrication oil when the heat exchanger is installed in the gas turbine engine.
6. The heat exchanger of claim 4, wherein the first fluid comprises fuel and the second fluid comprises compressed air.
7. The heat exchanger of claim 1, wherein the first fluid pathway is fluidly isolated from the second fluid pathway.
8. The heat exchanger of claim 1, wherein the first fluid pathway is helical.
9. The heat exchanger of claim 1, wherein: the manifold extends between the first end and the second end; the first end of the manifold is sealed; and the second end of the manifold defines at least a portion of the second fluid outlet.

10. The heat exchanger of claim 1, wherein the second plurality of second fluid inlet openings are arranged in a helical pattern about the manifold.
11. The heat exchanger of claim 1, wherein the plurality of tubes define at least a portion of the second fluid pathway.
12. The heat exchanger of claim 1, wherein the plurality of tubes comprise a straight shape, a tortuous shape, a twisted shape, a coiled shape, a zig-zag shape, or a combination thereof.
13. The heat exchanger of claim 1, wherein the plurality of baffles comprise tube fins for increasing a surface area of the first fluid pathway.
14. The heat exchanger of claim 1, wherein the plurality of tubes and the plurality of baffles are arranged to form the first fluid pathway with a plurality of turns about the manifold.
15. The heat exchanger of claim 1, wherein the heat exchanger is configured to be disposed in a sump of a lubrication system of the gas turbine engine.
16. A gas turbine engine, comprising: a fan; a turbomachine operably coupled to the fan for driving the fan, the turbomachine comprising a compressor section, a combustion section, and a turbine section in serial flow order and together defining a working gas flow path; a sump disposed in the turbomachine and configured to receive a lubrication oil; and a heat exchanger disposed in the sump, the heat exchanger comprising: an outer shell extending between a first end and a second end opposite the first end, the outer shell defining a first fluid chamber, a first fluid inlet adjacent the first end, and a first fluid outlet adjacent the second end, the outer shell further defining a first plurality of second fluid inlet openings located between the first end and the second end, and a second fluid outlet adjacent the second end, a manifold disposed within the outer shell, the manifold defining a second fluid chamber, and a second plurality of second fluid inlet openings, a plurality of tubes fluidly coupling the first plurality of second fluid inlet openings and the second plurality of second fluid inlet openings, and a plurality of baffles, each baffle of the plurality of baffles coupled between adjacent ones of the plurality of tubes, wherein the heat exchanger defines a first fluid pathway extending from the first fluid inlet, through the first fluid chamber, and to the first fluid outlet and in fluid communication with the compressor section, and wherein the heat exchanger further defines a second fluid pathway extending from the first plurality of second fluid inlet openings, through the second plurality of second fluid inlet openings, through the second fluid chamber, and to the second fluid outlet and in fluid communication with the sump, and wherein the plurality of tubes and the plurality of baffles define a helical surface defining the first fluid pathway about the manifold.
17. The gas turbine engine of claim 16, wherein the second fluid pathway is in fluid communication with a bearing or gearbox assembly of the gas turbine engine.
18. A gas turbine engine, comprising: a fan; a turbomachine operably coupled to the fan for driving the fan, the turbomachine comprising a compressor section, a combustion section, and a turbine section in serial flow order and together defining a working gas flow path; a fuel delivery system including a fuel source configured to deliver fuel from the fuel source to the combustion section; and a heat exchanger disposed in fluid communication with the fuel delivery system, the heat exchanger comprising: an outer shell extending between a first end and a second end opposite the first end, the outer shell defining a first fluid chamber, a first fluid inlet adjacent the first end, and a first fluid outlet adjacent the second end, the outer shell further defining a first plurality of second fluid inlet openings located between the first end and the second end, and a second fluid outlet adjacent the second end, a manifold disposed within the outer shell, the manifold defining a second fluid chamber, and a second plurality of second fluid inlet openings, a plurality of tubes fluidly coupling the first plurality of second fluid inlet openings and the second plurality of second fluid inlet openings, and a plurality of baffles, each baffle of the plurality of baffles coupled between adjacent ones of the plurality of tubes, wherein the heat exchanger defines a first fluid pathway extending from the first fluid inlet, through the first fluid chamber, and to the first fluid outlet and in fluid communication with the fuel source, and wherein the heat exchanger further defines a

second fluid pathway extending from the first plurality of second fluid inlet openings, through the second plurality of second fluid inlet openings, through the second fluid chamber, and to the second fluid outlet and in fluid communication with the compressor section, and wherein the plurality of tubes and the plurality of baffles define a helical surface defining the first fluid pathway about the manifold.

19. The gas turbine engine of claim 18, wherein: the first fluid pathway is in fluid communication with the combustion section; and the second fluid pathway is in fluid communication with the combustion section or the turbine section.
