

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404864
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Zhu; Xueping

Neck fan

Abstract

A neck fan includes a first fan main body and a second fan main body. The second fan main body connected to the first fan main body. The first fan main body and the second fan main body are configured to blow air towards a user respectively, the first fan main body and the second fan main body are respectively provided with a control switch, and the control switch is configured to control an operation of the first fan main body and/or the second fan main body.

Inventors:	Zhu; Xueping (Guangdong, CN)
Applicant:	Guangdong Aoyun Technology Co., Ltd. (Guangdong, CN)
Family ID:	96433181
Appl. No.:	19/010416
Filed:	January 06, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250237222 A1	Jul. 24, 2025

Related U.S. Application Data

continuation-in-part parent-doc US 18933625 20241031 PENDING child-doc US 19010416
continuation-in-part parent-doc US 18421213 20240124 ABANDONED child-doc US 19010416

Publication Classification

Int. Cl.: **F04D27/00** (20060101); **F04D25/06** (20060101); **F04D25/08** (20060101); **F04D29/52** (20060101); **H02J7/00** (20060101)

U.S. Cl.:

CPC **F04D27/004** (20130101); **F04D25/0673** (20130101); **F04D25/08** (20130101);
F04D29/522 (20130101); H02J7/0029 (20130101); H02J7/0047 (20130101);
H02J2207/20 (20200101)

Field of Classification Search

CPC: H02J (7/00302); H02P (2201/07); H02P (2201/09); F04D (19/002); F04D (25/0606);
F04D (25/0673); F04D (25/084); F04D (27/004); F04D (29/24); F04D (29/441); H02K
(5/22)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2010/0164421	12/2009	Dishman	318/471	F04D 27/004
2017/0302093	12/2016	Petersen	N/A	H02M 3/158
2017/0370596	12/2016	Lee	N/A	A42B 3/286
2019/0222038	12/2018	Chen	N/A	H01M 10/0525
2021/0190344	12/2020	Pille	N/A	F24F 8/10
2023/0006512	12/2022	Ji	N/A	H02K 9/06
2024/0229809	12/2023	Zheng	N/A	F04D 29/547

Primary Examiner: Hansen; Kenneth J
Attorney, Agent or Firm: Hemisphere Law, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation-in-Part of the U.S. application Ser. No. 18/933,625 filed on Oct. 31, 2024, and entitled “NECK FAN”, which is also a Continuation-in-Part of the U.S. application Ser. No. 18421213, filed on Jan. 24, 2024, and entitled “NECK FAN” now pending, the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present invention relates to the field of fans, and in particular, to a neck fan.

BACKGROUND

(2) As portable cooling equipment, a fan main body has received widespread attentions and been widely applied in hot seasons in recent years, especially a neck fan. The neck fan can be carried around and free the hands, and are favored by the majority of users.

(3) However, as people continue to pursue comfortable experiences, they have gradually increasing expectations for the performance of the neck fan. In the scorching summer, users hope to achieve a faster and more direct cooling effect in a high-temperature environment, but the design of the traditional neck fan fails to fully meet this demand.

(4) For this purpose, the present invention provides a neck fan that allows air from the fan to be blown more directly and centrally towards a user, thereby providing a more comfortable user experience in a hot environment. According to this design, the cooling effect of the neck fan is improved while the portability is achieved, so that the growing demand of the user for personalized

and efficient cooling equipment is met.

SUMMARY

(5) In order to overcome the shortcomings of the prior art, the present invention provides a neck fan.

(6) The present invention provides a neck fan, which includes a first fan main body and a second fan main body.

(7) The second fan main body connected to the first fan main body.

(8) The first fan main body and the second fan main body are configured to blow air towards a user respectively, the first fan main body and the second fan main body are respectively provided with a control switch, and the control switch is configured to control an operation of the first fan main body and/or the second fan main body.

(9) In one embodiment, the second fan main body and the first fan main body are oppositely arranged and are respectively positioned on two sides of the user's neck; and the second fan main body and the first fan main body have the same structure.

(10) In one embodiment, the first fan main body includes a first main body portion, a first fan assembly, a first power supply assembly and a first switch, the first main body portion is provided with a first mounting cavity, the first power supply assembly is arranged within the first mounting cavity and is electrically connected to the first fan assembly, the first power supply assembly includes a first battery and a first circuit board, the first switch and the first battery are electrically connected to the first circuit board, the first circuit board is provided with a first main control module, the first switch is mounted on the first main body portion and is electrically connected to the first main control module, and the first switch is configured to turn on or turn off the first fan assembly.

(11) In one embodiment, the first fan main body further includes a first charging interface and a first charging control module, and the first charging interface and the first charging control module are configured to charge the first battery; the first fan main body further includes a first status indication module, and the first status indication module is configured to display at least one of a startup status, a shutdown status, a charging status, and an output wind level of the first fan main body or the neck fan.

(12) In one embodiment, the first fan main body further includes a first battery protection module, the first battery protection module is electrically connected to the first main control module and the first charging control module, and is configured to perform charging protection for the first battery.

(13) In one embodiment, the first switch includes a stepless adjustment key configured to perform stepless adjustment and control the rotation speed of the first fan main body; and the stepless adjustment key is a potentiometer with variable electric resistance or an encoder.

(14) In one embodiment, the stepless adjustment key includes a plurality of connection terminals and at least one adjustment pin, one of the plurality of connection terminals is grounded, and at least one adjustment pin is configured for the user to operate so that the other connection terminals output corresponding stepless adjustment signals.

(15) In one embodiment, the first fan main body further includes a first boost module; the first switch is configured to send out a first fan working signal; the first main control module, when receiving the first fan working signal, is configured to drive the first boost module to receive and boost the output voltage of the first battery, thereby driving the first fan assembly to operate; and the first main control module is also configured to control the output voltage of the first boost module to achieve control over the rotation speed of the first fan assembly.

(16) In one embodiment, the first boost module includes an inductor and a switching element, a control terminal of a MCU of the first main control module is connected to a control terminal of the switching element, a first conducting terminal of the switching element is connected to the first battery via the inductor, a second conducting terminal of the switching element is grounded, the first conducting terminal of the switching element is connected to the first fan assembly, the MCU

of the first main control module controls the on-off state of the switching element, thereby controlling the voltage from the first battery to be boosted through the inductor, and provides the boosted voltage to the first fan assembly to drive the first fan assembly to blow air.

(17) In one embodiment, the second fan main body further includes a second main body portion, a second fan assembly, a second power supply assembly and a second switch, the second power supply assembly includes a second battery and a second circuit board, the second switch and the second battery are electrically connected to the second circuit board, the second circuit board is provided with a second main control module, the second switch is mounted on the second main body portion and is electrically connected to the second main control module, the second switch is configured to turn on or turn off the second fan main body, the second fan main body further includes a second boost module, the second switch is configured to send out a second fan working signal, the second main control module, when receiving the second fan working signal, is configured to drive the second boost module to receive and boost the output voltage of the second battery, thereby driving the second fan assembly to operate, and the second main control module is also configured to control the output voltage of the second boost module to achieve control over the rotation speed of the second fan assembly.

(18) In one embodiment, the first main body portion is provided with a first conductive end, the second main body portion is provided with a second conductive end, when the first fan main body and the second fan main body are connected together, consequently, the first conductive end is communicated with the second conductive end, the first switch is electrically connected to the first main control module and the second main control module respectively, and the second switch is also electrically connected to the first main control module and the second main control module respectively, such that at least one of the first switch and the second switch can send out a third fan working signal; the first main control module is configured to receive the third fan working signal and drive the first boost module to boost the output voltage of the first battery, thereby driving the first fan assembly to operate, and the second main control module is configured to receive the third fan working signal and drive the second boost module to boost the output voltage of the second battery, thereby driving the second fan assembly to operate.

(19) In one embodiment, the first fan main body and the second fan main body are manufactured independently and then connected together through an assembly process.

(20) In one embodiment, the first fan main body and the second fan main body are detachably connected, so that the first fan main body and the second fan main body are able to operate and be used independently.

(21) In one embodiment, the neck fan further includes a connection member, the connection member includes a flexible connection portion, the flexible connection portion is provided with at least one installation hole, the at least one installation hole is configured to be sleeved and fixed on one end of the first fan main body and one end of the second fan main body, so that the first fan main body and the second fan main body are connected through the flexible connection portion.

(22) In one embodiment, an inner sidewall of the at least one installation hole is provided with a first anti-detachment structure and a second anti-detachment structure, the first anti-detachment structure is configured to engage with a first buckle on an outer surface of one end of the first fan main body, the second anti-detachment structure is configured to engage with a second buckle on one end of the second fan main body, and at least one of the first anti-detachment structure and the first buckle is provided with a plurality of concave-convex structures arranged in sequence along an extending direction of the connection member.

(23) In one embodiment, the first anti-detachment structure includes a plurality of first buckle slots arranged along an extending direction of the connection member, the plurality of first buckle slots are configured to engage with a plurality of protrusions arranged along an extending direction of the first buckle; the second anti-detachment structure includes a plurality of second buckle slots arranged along the extending direction, the plurality of second buckle slots are configured to

engage with a plurality of protrusions arranged along an extending direction of the second buckle; the first anti-detachment structure is configured to be detachably connected with the first buckle, and the second anti-detachment structure is configured to be detachably connected with the second buckle; the flexible connection portion is also provided with a first fixing structure and a second fixing structure, the first fixing structure and the second fixing structure are respectively arranged at two ends of the flexible connection portion, the first fixing structure is configured to connect with a third fixing structure at one end of the first fan main body, and the second fixing structure is configured to connect with a fourth fixing structure at one end of the second fan main body; the first fixing structure is configured to be detachably connected with the third fixing structure, and the second fixing structure is configured to be detachably connected with the fourth fixing structure.

(24) In one embodiment, the connection member further includes at least one neck support portion, the at least one neck support portion is connected to an inner side of the flexible connection portion adjacent to the human neck, the at least one neck support portion is configured to form at least one air inlet gap with the first fan main body or the second fan main body, so that air from the first fan main body or the second fan main body can enter the air inlet gap.

(25) In one embodiment, the first fan main body includes a first main body portion, the first main body portion has an arc-shaped structure, and includes a concave first air guide path positioned on a surface of one side of the first main body portion and extended along an extending direction of the arc-shaped structure; the first fan assembly is arranged at one end of the first main body portion and is configured to blow air towards the first air guide path, and the first air guide path is configured to guide air of the first fan assembly to one side of the first main body portion and one end of the first main body portion away from the first fan assembly.

(26) In one embodiment, the first fan assembly includes a first fan shell, a first motor, and a first fan blade mounted on a rotating shaft of the first motor, the first motor and the first fan blade are arranged within the first fan shell; the first fan shell includes a shell main body and an air outlet hood, the air outlet hood is arranged on one side of the shell main body; the air outlet hood includes a plurality of air gathering rings and an annular wall structure connected to a periphery of the plurality of air gathering rings, a plurality of air outlet holes are formed among the plurality of air gathering rings, and the air gathering rings are configured to cooperate with an inner side surface of the annular wall structure to pressurize wind from the shell main body and then blow it out.

(27) In one embodiment, the inner side surface of the annular wall structure is an inclined surface or an arc-shaped surface, so that an inner diameter of the annular wall structure gradually decreases along a direction from the shell main body to the air outlet hood; the shell main body includes an annularly arranged sidewall structure, an mounting portion positioned at one end inside the sidewall structure and an air guiding portion connected between the mounting portion and the sidewall structure, the air guiding portion includes a plurality of air guiding blades arranged at intervals and is configured to guide wind from the first fan blade based on a preset direction, the first fan blade and the first motor are arranged within the sidewall structure and are positioned on one side of the mounting portion, and the first motor is mounted on the mounting portion; the first fan shell further includes a metal barrier net, the metal barrier net is arranged on one side of the sidewall structure away from the air outlet hood, the metal barrier net is made of metal material and is provided with a plurality of air inlet holes, and an inner diameter of each air inlet holes ranges from 0.5 mm to 4 mm; the air inlet hole is in a regular hexagon shape, a surrounding wall is arranged between two adjacent air inlet holes, and a width of the surrounding wall ranges from 0.05 mm to 2 mm.

(28) The beneficial effects of the present invention are as follows: the present invention provides a neck fan, which includes two fan main bodies, and each fan main body is provided with a control switch, facilitating the user to control the neck fan and improving the user experience. In addition, the two fan main bodies can also form a modular design, which not only facilitates assembly but

also reduces the costs of assembly and maintenance. Moreover, users can also detach, assemble, store by themselves and conduct DIY designs and so on, thereby improving the user experience.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to explain the technical solutions of the embodiments of the present invention more clearly, the following will briefly introduce the accompanying drawings used in the embodiments. The drawings in the following description are only some embodiments of the present invention. Those of ordinary skill in the art can obtain other drawings based on these drawings without creative work.
- (2) The present invention is further described below in detail in combination with the accompanying drawings and embodiments.
- (3) FIG. 1 is a schematic diagram of an entire structure of a neck fan according to Embodiment I of the present invention;
- (4) FIG. 2 is a schematic diagram of an entire structure of another viewing angle of the neck fan according to Embodiment I of the present invention;
- (5) FIG. 3 is a sectional view of the neck fan according to Embodiment I of the present invention;
- (6) FIG. 4 is an exploded view of the neck fan according to Embodiment I of the present invention;
- (7) FIG. 5 is a partial enlarged structural diagram of a portion V of FIG. 3;
- (8) FIG. 6 is a partial enlarged structural diagram of a portion VI of FIG. 4;
- (9) FIG. 7 is a schematic block diagram of the neck fan according to Embodiment I of the present invention;
- (10) FIG. 8 is a circuit diagram of a first charging interface of the neck fan of the present invention;
- (11) FIG. 9 is a circuit diagram of a first charging control module of the neck fan of the present invention;
- (12) FIG. 10 is a circuit diagram of a first battery of the neck fan of the present invention;
- (13) FIG. 11 is a circuit diagram of a first main control module of the neck fan of the present invention;
- (14) FIG. 12 is a circuit diagram of a first boost module and a first motor of the neck fan of the present invention;
- (15) FIG. 13 is a circuit diagram of a first main control module, a first boost module and a first motor of the neck fan according to an alternative embodiment of the present invention;
- (16) FIG. 14 is a circuit diagram of a first main control module, a first boost module and a first motor of a neck fan according to another modified embodiment of the present invention;
- (17) FIG. 15 is a circuit diagram of the first main control module, the first boost module and the first motor of the neck fan according to another modified embodiment of the present invention;
- (18) FIG. 16 is a schematic diagram of an entire structure of the neck fan according to Embodiment II of the present invention;
- (19) FIG. 17 is a schematic block diagram of a first main body portion of the neck fan according to Embodiment II of the present invention;
- (20) FIG. 18 is a schematic block diagram of a second main body portion of the neck fan according to Embodiment II of the present invention;
- (21) FIG. 19 is a schematic diagram of an entire structure of the neck fan according to Embodiment III of the present invention;
- (22) FIG. 20 is an exploded view of the neck fan according to Embodiment III of the present invention;
- (23) FIG. 21 is another exploded view of the neck fan according to Embodiment III of the present invention;

- (24) FIG. 22 is a cross-sectional view of the neck fan according to Embodiment III of the present invention;
- (25) FIG. 23 is an exploded view of a fan main body of the present invention;
- (26) FIG. 24 is an exploded view of FIG. 23 from another angle;
- (27) FIG. 25 is a schematic structural diagram of an outer side of a first main body portion of the fan main body shown in FIG. 23;
- (28) FIG. 26 is a schematic structural diagram of an inner side of a first outer cover body of the fan main body shown in FIG. 23; and
- (29) FIG. 27 is a schematic structural diagram of a metal screen of a first fan assembly of the fan main body according to a modified embodiment of Embodiment III of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Embodiment I

(30) Referring to FIG. 1 to FIG. 13, a neck fan includes a hanging main body 1 and a first fan assembly 3. A straight-tube-shaped first air guide chamber 2 is arranged at a lower end portion of the hanging main body 1 in a protruding manner; the first air guide chamber 2 includes a first air inlet 22 arranged at the lower end portion of the hanging main body 1 and a first air outlet 23 opposite to the first air inlet 22; the hanging main body 1 includes an inner end portion 11 that is in contact with the neck of a user; the first air outlet 23 faces the inner end portion 11; the first fan assembly 3 is located in the first air guide chamber 2; and the first fan assembly 3 is configured to drive an air flow to flow from the first air inlet 22 to the inner end portion 11 via the first air outlet 23. Through the above structure, due to the straight-tube shape of the first air guide chamber 2, the neck fan forms a vertical blowing type fan capable of blowing air in a vertical direction. The first fan assembly 3 can drive the air flow to be blown from the first air inlet 22 to the inner end portion 11 through the first air outlet 23, greatly improving the air blowing efficiency. A user can directly feel the cool air blown directly to the neck when using the neck fan. This improves the overall performance of the fan. Furthermore, since the first air guide chamber 2 is a straight-tube-shaped cavity integrally protruding out of the hanging main body 1, this design improves the overall sense of beauty and sense of design of the product, helps to improve the wearing comfort of the neck fan, and improves the overall quality and user experience of the product.

(31) In this embodiment, a hanging main body 1 is U-shaped, the hanging main body 1 includes a first main body portion 101, a second main body portion 102 and a connection member 103. The first main body portion 101 and the second main body portion 102 are detachably connected through the connection member 103. Furthermore, the connection member 103, which is flexible, can be a silica gel connection member, a plastic connection member or a rubber connection member. Moreover, the first fan assembly 3 is arranged on the first main body portion 101.

(32) In this embodiment, the neck fan (such as the first main body portion 101) is provided with a first air guide path 12 that is inwards sunken; the first air guide path 12 extends from the first air outlet 23 to the inner end portion 11; and the first fan assembly 3 drives the air flow to be blown out from the first air outlet 23 towards the inner end portion 11 along the first air guide path 12. Further, a flexible first neck support 111 is connected to the inner end portion 11; a first air inlet gap 121 is formed between the first neck support 111 and the inner end portion 11; the first fan assembly 3 drives the air flow to be blown out from the first air outlet 23 towards the first air inlet gap 121 along the first air guide path 12. The first neck support 111 can be a silica gel neck support, a plastic neck support, a rubber neck support, or the like. Through the above structure, when the air flow is blown out from the first air outlet 23, under the guidance of the first air guide path 12 that is inwards sunken, the air flow will be blown towards the inner end portion 11 along the first air guide path 12. Due to the first air inlet gap 121, the air flow can be blocked in the gap, so that when a user wears the neck fan, the user can have a stronger feeling about the air flow at the inner end portion 11, and the heat dissipation effect is enhanced; and furthermore, the flexible neck support provides a more comfortable supporting effect for the user, which improves the user experience.

(33) In this embodiment, a width of the first air guide path gradually decreases towards the inner end portion along the first air outlet; a width range of the first air guide path is 1 to 5 cm; a length range of the first air guide path is 8 to 16 cm; and a depth range of the first air guide path is 0 to 3 cm.

(34) In this embodiment, the first main body portion **101** a first outer shell **1011** and a first inner shell **1012**; the first air guide path **12** is arranged on the first inner shell **1012**; and the first inner shell **1012** is detachably connected to the first outer shell **1011** through a buckle. It is convenient for a user to open and mount the first main body portion **101** for maintenance.

(35) In this embodiment, a diameter of the first air inlet **22** is within a range of 30 mm to 60 mm, and a diameter of the first air outlet **23** is within a range of 30 mm to 60 mm. Through the above structure, an appropriate diameter range helps to achieve a balanced air flowrate, so that the fan can provide a sufficient air flow and maintain a good cooling effect. Furthermore, it helps to rationalize the overall structure, and the neck fan is convenient to carry and use.

(36) In this embodiment, a straight-tube-shaped second air guide chamber **4** is further arranged at a lower end portion of the neck fan in a protruding manner; the second air guide chamber **4** includes a second air inlet **42** arranged at the lower end portion of the hanging main body **1** and a second air outlet **43** opposite to the second air inlet **42**; the second air outlet **43** faces the inner end portion **11**; the neck fan further includes a second fan assembly **5**. The second fan assembly **5** is arranged in the second air guide chamber **4**; and the second fan assembly **5** is configured to drive the air flow to be blown out from the second air inlet **42** towards the inner end portion **11** via the second air outlet **43**. Through the above structure, due to the straight-tube shape of the second air guide chamber **4**, the neck fan forms a vertical blowing type fan capable of blowing air in a vertical direction, so that the second fan assembly **5** can drive the air flow to be blown from the second air inlet **42** to the inner end portion **11** through the second air outlet **43**, greatly improving the air blowing efficiency. A user can directly feel the cool air when using the neck fan. This improves the overall performance of the fan. Furthermore, since the second air guide chamber **4** is a straight-tube-shaped cavity integrally protruding out of the hanging main body **1**, this design improves the overall sense of beauty and sense of design of the product, helps to improve the wearing comfort of the neck fan, and improves the overall quality and user experience of the product. It can be understood that the second fan assembly **5** is arranged in the second main body portion **102**.

(37) In this embodiment, the neck fan (such as the second main body portion **102**) is provided with a second air guide path **13** that is inwards sunken; the second air guide path **13** extends from the second air outlet **43** to the inner end portion **11**; and the second fan assembly **5** drives the air flow to be blown out from the second air outlet **43** towards the inner end portion **11** along the second air guide path **13**. Further, a flexible second neck support **112** is connected to the inner end portion **11**; a second air inlet gap **131** is formed between the second neck support **112** and the inner end portion **11**; the second fan assembly **5** drives the air flow to be blown out from the second air outlet **43** towards the second air inlet gap **131** along the second air guide path **13**. The second neck support **112** can be a silica gel neck support, a plastic neck support, a rubber neck support, or the like. Through the above structure, when the air flow is blown out from the second air outlet **43**, under the guidance of the second air guide path **13** that is inwards sunken, the air flow will be blown towards the inner end portion **11** along the second air guide path **13**. Due to the second air inlet gap **131**, the air flow can be blocked in the gap, so that when a user wears the neck fan, the user can have a stronger feeling about the air flow at the inner end portion **11** more strongly, and the heat dissipation effect is enhanced; and furthermore, the flexible neck support provides a more comfortable supporting effect for the user, which improves the user experience.

(38) In this embodiment, the second main body portion **102** includes a second outer shell **1021** and a second inner shell **1022**; the second air guide path **13** is arranged on the second inner shell **1022**; and the second inner shell **1022** is detachably connected to the second outer shell **1021** through a buckle. It is convenient for a user to open and mount the second main body portion **102** for

maintenance.

(39) In this embodiment, the neck fan further includes a first power supply assembly **8**; the first power supply assembly **8** is located inside the hanging main body **1**; the first power supply assembly **8** is electrically connected to the first fan assembly **3** to supply power to the first fan assembly **3**; the first power supply assembly **8** includes a first battery **81** and a first circuit board **82**; and the first battery **81** is electrically connected to the first circuit board **82** to supply power to the first circuit board **82**. The neck fan further includes a second power supply assembly **9**; the second power supply assembly **9** is located inside the hanging main body **1**; the second power supply assembly **9** is electrically connected to the second fan assembly **5** to provide power to the second fan assembly **5**; the second power supply assembly **9** includes a second battery **91** and a second circuit board **92**; and the second battery **91** is electrically connected to the second circuit board **92** to supply power to the second circuit board **92**. Through the above structure, the first power supply assembly **8** is arranged inside the hanging main body **1**. This design can improve the overall appearance of the neck fan and effectively supply power to the first fan assembly **3**, to ensure the reliability of the product. The second power supply assembly **9** is arranged inside the hanging main body **1**. This design can improve the overall appearance of the neck fan and effectively supply power to the second fan assembly **5**, to ensure the reliability of the product.

(40) In this embodiment, the first fan assembly **3** includes a first fan shell **31**, a first motor **32** fixedly mounted inside the first fan shell **31**, and a first fan blade **33** mounted on a rotating shaft of the first motor **32**; the first fan shell **31** is provided with a third air inlet **311**, a first air duct **312**, and a third air outlet **313**; and the first air inlet **22**, the third air inlet **311**, the first air duct **312**, the third air outlet **313**, the first air guide chamber **2**, and the first air outlet **23** are connected to each other in sequence. Through the above structural design, the first fan assembly **3** in this embodiment is provided with the independent outer shell, which facilitates independent mounting and replacement of the fan.

(41) In another implementation, the first fan assembly **3** includes a first motor **32** and a first fan blade **33** mounted on a rotating shaft of the first motor **32**; the first air inlet **22** is connected with a first air inlet hood **221**; the first air inlet hood **221** is provided with several first air inlet holes **222**; the first air outlet **23** is connected to a first air outlet hood **231**; and the first air outlet hood **231** is provided with several first air outlet holes **232**. Through the above structure, the design of a fan shell is omitted in this case, which saves the cost. Furthermore, a direction of the air flow is effectively achieved. The design of the first air inlet hood **221** and the first air outlet hood **231** is conducive to preventing other debris, such as hairs and paper scraps, from being sucked into the fan, which is conducive to maintaining the safety of the fan.

(42) In this embodiment, the second fan assembly **5** includes a second fan shell **51**, a second motor **52** fixedly mounted inside the second fan shell **51**, and a second fan blade **53** mounted on a rotating shaft of the second motor **52**; the second fan shell **51** is provided with a fourth air inlet **511**, a second air duct **512**, and a fourth air outlet **513**; and the second air inlet **42**, the fourth air inlet **511**, the second air duct **512**, the fourth air outlet **513**, the second air guide chamber **4**, and the first air outlet **23** are connected to each other in sequence. Through the above structural design, the first fan assembly **3** in this embodiment is provided with the independent outer shell, which facilitates independent mounting and replacement of the fan.

(43) In some other embodiments, the second fan assembly **5** includes a second motor **52** and a second fan blade **53** mounted on a rotating shaft of the second motor **52**; the second air inlet **42** and a fourth air inlet **511** are connected with a second air inlet hood **421**; the second air inlet hood **421** is provided with several second air inlet holes **422**; the second air outlet **43** and a fourth air outlet **513** are connected with a second air outlet hood **431**; and the second air outlet hood **431** is provided with several second air outlet holes **432**. Through the above structure, the design of a fan shell is omitted in this case, which saves the cost. Furthermore, a direction of the air flow is effectively achieved. The design of the second air inlet hood **421** and the second air outlet hood **431** is

conductive to preventing other debris, such as hairs and paper scraps, from being sucked into the fan, which is conducive to maintaining the safety of the fan.

(44) In this embodiment, the connector **103** is provided with a installation hole **1031**; the first main body portion **101** is provided with a first connection end **1013** connected to the connector **103**; the first connection end **1013** is detachably inserted into one end of the installation hole **1031**; the second main body portion **102** is provided with a second connection end **1023** connected to the connector **103**; and the second connection end **1023** is detachably inserted into the other end of the installation hole **1031**.

(45) Further, a concave-convex first buckle **10131** is arranged at the first connection end **1013**; the connector **103** is provided with a first buckle slot **1032** that cooperates with the first buckle **10131**; a concave-convex second buckle **10331** is arranged at the second connection end **1023**; and the connector **103** is provided with a second buckle slot **10231** that cooperates with the second buckle **10331**. Through the above structure, the connector **103** is a flexible silica gel connector. After the connector **103** is bent to an angle, the first main body portion **101** and the second main body portion **102** can be easily inserted into the installation hole **1031**. The first main body portion **101** is in clamping fit with the first buckle slot **1032** on an inner wall of the connector **103** through the concave-convex first buckle **10131** arranged at the first connection end **1013**, and the second main body portion **102** is in clamping fit with the second buckle slot **10231** on the inner wall of the connector **103** through the concave-convex second buckle **10331** arranged at the second connection end **1023**, so that it is convenient to mount and connect the first main body portion **101** to the second main body portion **102** to form a complete neck fan.

(46) Referring to FIG. 3 to FIG. 6, the connection member **103** can be divided into a flexible connection portion **103a**, and the flexible connection portion **103a** can be provided with at least one installation hole **1031**. The at least one installation hole **1031** is configured to extend along an extending direction D1 from the first connection end **1013** of the first main body portion **101** to the second connection end **1023** of the second main body portion **102**, and the at least one installation hole **1031** is further configured to be sleeved and fixed onto the first connection end **1013** and the second connection end **1023**, so that the first main body portion **101** and the second main body portion **102** are connected through the flexible connection portion **103a**. The first main body portion **101** and the second main body portion **102** are connected through the flexible connection portion **103a**, so that a flexible connection is formed between the first main body portion **101** and the second main body portion **102**, thereby facilitating the wearing by users.

(47) In this embodiment, the flexible connection portion **103a** is provided with a through installation through hole which is arranged along the extending direction D1, each of two ends of the installation hole **1031** is respectively configured to sleeve and fix the first connection end **1013** and the second connection end **1023**. Adopting one installation through hole is simple in process and offers flexible assembly space. However, in an alternative embodiment, the flexible connection portion **103a** may also have two blind holes (i.e., non-through holes) which are arranged oppositely. The two blind holes are respectively configured to sleeve and fix the first connection end **1013** and the second connection end **1023**.

(48) In an embodiment, an inner sidewall of the at least one installation hole **1031** is provided with a first anti-detachment structure (such as a first buckle slot) and a second anti-detachment structure (such as a second buckle slot), the first anti-detachment structure is configured to be snap-fitted and connected to the first buckle **10131** on an outer surface of the first connection end **1013**, the second anti-detachment structure is configured to be snap-fitted and connected to the second buckle **10331** on an outer surface of the second connection end **1023**, and at least one of the first anti-detachment structure and the first buckle **10131** includes a plurality of convex-concave structures arranged in sequence along the extending direction D1.

(49) Specifically, in this embodiment, the first anti-detachment structure includes a plurality of first buckle slots **1023a** arranged along the extending direction, and the first buckle slot **1023a** is

configured to be meshed and connected to a plurality of projections arranged along the extending direction on the first buckle **10131**; the second anti-detachment structure includes a plurality of second buckle slots **1023b** arranged along the extending direction, and the second buckle slot **1023b** is configured to be meshed and connected to a plurality of projections arranged along the extending direction on the second buckle **10331**; the first anti-detachment structure is configured to be detachably connected to the first buckle **10131**, and the second anti-detachment structure is configured to be detachably connected to the second buckle **10331**.

(50) In an embodiment, the flexible connection portion **103a** is in an arc-shaped and provided with an inner side adjacent to a human neck and an outer side away from the human neck, the first anti-detachment structure is arranged on an inner sidewall of one side of the at least one installation hole **1031** adjacent to the outer side, and the second anti-detachment structure is arranged on an inner sidewall of the other side of the at least one installation hole **1031** adjacent to the outer side.

(51) In an embodiment, the flexible connection portion **103a** is provided with a first fixing structure **103b** and a second fixing structure **103c**, the first fixing structure **103b** and the second fixing structure **103c** are respectively arranged on each of two ends of the flexible connection portion **103a**, the first fixing structure **103b** is configured to connect to a third fixing structure **1013a** of the first connection end **1013**, the second fixing structure **103c** is configured to connect to a fourth fixing structure **1023a** of the second connection end **1023**; the first fixing structure **103b** is configured to detachably connect to the third fixing structure **1013a**, and the second fixing structure **103c** is configured to detachably connect to the fourth fixing structure **1023a**.

(52) In an embodiment, one of the first fixing structure **103b** and the third fixing structure **1013a** is a first fixing post **141**, one of the first fixing structure **103b** and the third fixing structure **1013a** is a first fixing hole **142**; one of the second fixing structure **103c** and the fourth fixing structure **1023a** is a second fixing post **143**, one of the second fixing structure **103c** and the fourth fixing structure **1023a** is a second fixing hole **144**, the first fixing structure **103b** extends along a direction D2 of a first tangent line perpendicular to the extending direction, and the second fixing structure **103c** extends along a direction D3 of a second tangent line perpendicular to the extending direction.

(53) In an embodiment, the first fixing post **141** includes a first post body **1411** and a first buckle hook portion **1412** connected to one end of the first post body **1411** away from the flexible connection portion **103a**, and an outer diameter of the first buckle hook portion **1412** is greater than an outer diameter of the first post body **1411** to prevent the first fixing post **141** from detaching from the first fixing hole **142**; the second fixing post **143** includes a second post body **1431** and a second buckle hook portion **1432** connected to one end of the second post body **1431** away from the flexible connection portion **103a**, and an outer diameter of the second buckle hook portion **1432** is greater than an outer diameter of the second post body **1431** to prevent the second fixing post **143** from detaching from the second fixing hole **144**.

(54) In an embodiment, the first fixing hole **142** includes a first portion **1421** corresponding to the first post body **1411** and a second portion **1422** corresponding to the first buckle hook portion **1412**, and a hole diameter of the second portion **1422** is greater than a hole diameter of the first portion **1421**; the second fixing hole **144** includes a third portion **1441** corresponding to the second post body **1431** and a fourth portion **1442** corresponding to the second buckle hook portion **1432**, and a hole diameter of the fourth portion **1442** is greater than a hole diameter of the third portion **1441**.

(55) In an embodiment, the connection member **103** includes at least one neck support (such as a first neck support portion **111** and a second neck support portion **112**), the at least one neck support is connected to the inner side of the flexible connection portion **103a** adjacent to the human neck, and the at least one neck support is configured to form at least one air inlet gap with the first main body portion **101** or the second main body portion **102**, so that air of the first main body portion **101** or the second main body portion **102** can enter the air inlet gap (such as **121**, **131**). Thereby preventing the human neck from directly contacting with the first main body portion **101** or the second main body portion **102**, and avoiding the situation that wind cannot be provided to a surface

of the neck skin.

(56) As shown previously, in this embodiment, the at least one neck support includes the first neck support portion **111** and the second neck support portion **112**, the first neck support portion **111** is positioned adjacent to the first main body portion **101** and is configured to form a first air inlet gap **121** with the first main body portion **101**, and the second neck support portion **112** is positioned adjacent to the second main body portion **102** and is configured to form a second air inlet gap **131** with the second main body portion **102**.

(57) In an embodiment, a plurality of projections **103m** are arranged on surfaces of the first neck support portion **111** and the second neck support portion **112** away from the flexible connection portion **103a**, and the plurality of projections **103m** are configured to form a gap between the at least one neck support and the human neck skin. The plurality of projections **103m** are further configured to avoid the situation that the human neck directly contacts the first main body portion **101** or the second main body portion **102**, resulting in the inability to supply wind to the surface of the neck skin.

(58) It can be seen that the surfaces of the first neck support portion **111** and the second neck support portion **112** away from the flexible connection portion **103a** are arc-shaped. A size of the plurality of projections gradually decreases from a middle to two ends along a vertical direction **D4** perpendicular to the extending direction **D1**. Thereby achieving a comfortable wearing effect.

(59) In this embodiment, the flexible connection portion **103a**, the first neck support portion **111** and the second neck support portion **112** are made of a flexible material, such as the same flexible material (such as a flexible silica gel material), and they are integrally formed. Thereby achieving a comfortable wearing effect.

(60) Furthermore, the flexible connection portion **103a** includes a main body portion **103b**, a first extending portion **103e** and a second extending portion **103f**, the main body portion **103d** is provided with the at least one installation hole **1031**, the first extending portion **103e** and the second extending portion **103f** are respectively connected to each of two ends of the main body portion **103b**, the first extending portion **103e** and the second extending portion **103f** protrude from the main body portion **103b** along the extending direction **D1**, the first extending portion **103e** and the second extending portion **103f** are respectively configured to cover and connect to an inner surface of the first connection end **1013** adjacent to the human neck and an inner surface of the second connection end **1023** adjacent to the human neck. The first fixing structure and the second fixing structure are respectively arranged on the first extending portion **103e** and the second extending portion **103f**, thereby the first fixing structure and the second fixing structure being adjacent to an inner side of the human neck. The first anti-detachment structure and the second anti-detachment structure are positioned away from an outer side of the human neck, and the internal and external cooperation enables the connection member **103** to reliably connect the first main body portion **101** and the second main body portion **102**, preventing the connection parts from easily getting detached.

(61) In this embodiment, the first air guide chamber **2** is located inside the first main body portion **101**; the first main body portion **101** is further provided with a first mounting chamber **1014**; and the first power supply assembly **8** is located inside the first mounting chamber **1014**. The second air guide chamber **4** is located inside the second main body portion **102**; the second main body portion **102** is further provided with a second mounting chamber **1024**; and the second power supply assembly **9** is located inside the second mounting chamber **1024**.

(62) In this embodiment, the first main body portion **101** is further provided with a first switch **1015**, a first charging interface **1016**, and a first indication module **1017**; and the first switch **1015**, the first charging interface **1016**, and the first indication module **1017** are all electrically connected to the first power supply assembly **8**. The second main body portion **102** is further provided with a second switch **1025**, a second charging interface **1026**, and a second indication module **1027**; and the second switch **1025**, the second charging interface **1026**, and the second indication module

1027 are all electrically connected to the second power supply assembly **9**. Through the above structure, both the first switch **1015** and the second switch **1025** are configured to turn on or turn off the neck fan. The first charging interface **1016** and the second charging interface **1026** are configured to charge the first battery **81** and the second battery **91**, respectively. The first indication module **1017** and the second indication module **1027** can be configured to: display whether the fan is in an ON or OFF state and display a wind rating of the fan.

(63) In this embodiment, referring to FIG. 7 to FIG. 13, the neck fan further includes a first charging control module **811**, a first battery protection module **812**, a first charging indication module **813**, a first main control module **814** and a first boost module **815**; and the first charging control module **811**, the first battery protection module **812**, the first charging indication module **813**, the first main control module **814** and the first boost module **815** can be arranged on the first circuit board **82**.

(64) The first charging interface **1016** and the first charging control module **811** are both electrically connected to the first battery **81**; the first charging indication module **813** is connected to the first charging control module **811**; the first charging interface **1016** and the first charging control module **811** are configured to charge the first battery **81**; the first battery level indication module **813** is configured to display a state of charging; and the first battery protection module **812** is electrically connected to the first charging control module **811** and the first battery **81** to protect the first battery **81**.

(65) The first main control module **814**, the first boost module **815**, and a first motor **32** are all electrically connected to the first battery **81**; the first switch **1015** and the first indication module **1017** are electrically connected to the first main control module **814**; and the first indication module **1017** is configured to display turning on or turning off of the neck fan. It can be understood that the first indication module **1017** and the first charging indication module **813** constitute a first status indication module, which is used to display at least one of the startup status, shutdown status, charging status, and output wind level of the first fan main body or the neck fan. In this embodiment, both the first indication module **1017** and the first charging indication module **813** are indication modules. However, in other embodiments, the first status indication module may also be one or more display screens, such as an LED display screen, a liquid crystal display screen, or an electronic ink display screen.

(66) In this embodiment, the neck fan further includes a second charging control module **921**, a second battery protection module **922**, a second charging indication module **923**, a second main control module **924** and a second boost module **925**; and the second charging control module **921**, the second battery protection module **922**, the second charging indication module **923**, the second main control module **924** and the second boost module **925** can be arranged on the second circuit board **92**.

(67) The second charging interface **1026** and the second charging control module **921** are both electrically connected to the second battery **91**; the second charging indication module **913** is connected to the second charging control module **921**; the second charging interface **1026** and the second charging control module **921** are configured to charge the second battery **91**; the second charging indication module **923** is configured to display a state of charging; and the second battery protection module **922** is electrically connected to the second charging control module **921** and the second battery **91** to protect the second battery **91**.

(68) The second main control module **924**, the first boost module **925**, and a second motor **52** are all electrically connected to the second battery **91**; the second switch **1025** and the second indication module **1027** are electrically connected to the second main control module **924**; and the second indication module **1027** is configured to display turning on or turning off of the neck fan. It can be understood that the second indication module **1027** and the second charging indication module **923** constitute a second status indication module, which is used to display at least one of the startup status, shutdown status, charging status, and output wind level of the second fan main

body or the neck fan. In this embodiment, both the second indication module **1027** and the second charging indication module **923** are indication modules. However, in other embodiments, the second status indication module may also be one or more display screens, such as an LED display screen, a liquid crystal display screen, or an electronic ink display screen.

(69) In this embodiment, the first main body portion **101** is provided with a first conductive end **1018**; the second main body portion **102** is provided with a second conductive end **1019**; when the first conductive end **1018** is communicated to the second conductive end **1019**, the first switch **1015** is electrically connected to the first main control module **814** and the second main control module **924** respectively, and the second switch **1025** is electrically connected to the first main control module **814** and the second main control module **924** respectively; and the first switch **1015** or the second switch **1025** is configured to send a third fan working signal.

(70) The first main control module **814** is configured to: receive the third fan working signal and drive the first boost module **815** to receive and boost the output voltage of the first battery **81**, to drive the first motor **32** to work; and

(71) the second main control module **924** is configured to: receive the third fan working signal and drive the second boost module **925** to receive and boost the output voltage of the second battery **91**, to drive the second motor **52** to work.

(72) It can be understood that, referring to FIG. **14**, in one embodiment, when any one of the first switch **1015** and the second switch **1025** is operated by the user, a third fan working signal can be sent, so that both the first motor **32** and the second motor **52** work. Specifically, the first conductive end **1018** of the first main body portion **101** may have a connector **J1** for connecting with the connector **J1** of the second conductive end **1019** of the second main body portion **102**, thereby realizing the electrical connection between the first main control module **814** and the second main control module **924**, and further realizing that when any one of the first switch **1015** and the second switch **1025** is operated by the user, a third fan working signal can be sent out. Specifically, the connector **J1** may have two signal terminals, but it is not limited to the above.

(73) It can be understood that when the connector **J1** of the first conductive end **1018** of the first main body portion **101** is not connected to the connector **J1** of the second conductive end **1019** of the second main body portion **102**, that is, when the first main body portion **101** and the second main body portion **102** are independent of each other, the first switch **1015** and the second switch **1025** can independently control the operation of the two fan assemblies respectively, and they do not affect each other.

(74) In addition, in some other embodiments, through preset program control, which one of the first switch **1015** and the second switch **1025** dominates the control of the two fan assemblies can be determined according to the need. Specifically, in another embodiment, only when one of the first switch **1015** and the second switch **1025** (such as the first switch) is operated by the user, will the third fan working signal be sent out to make the first motor **32** and the second motor **52** work simultaneously.

(75) Specifically, referring to FIG. **13** and FIG. **14**, the first switch **1015** and the second switch **1025** may include a key switch **S1**. In other embodiments, referring to FIG. **15**, the first switch **1015** and the second switch **1025** may also include a stepless adjustment key **P1** (such as a knob or a slide adjustment key) that enables stepless adjustment. Through the stepless adjustment key **P1**, the rotational speed of the fan assembly can be controlled, thereby controlling the wind force. The stepless adjustment key **P1** includes, but is not limited to, stepless adjustment devices such as a potentiometer with variable electric resistance and an encoder. In one embodiment, the stepless adjustment key **P1** may include a plurality of connection terminals and at least one adjustment pin. One of the plurality connection terminals can be grounded, and at least one adjustment pin position can be operated by the user so that the other connection terminals output corresponding stepless adjustment signals. In other embodiments, a plurality of stepless adjustment pins can be provided, thus increasing more adjustment ranges and functions. It can be understood that the stepless

adjustment key **P1** enables the user to control the wind force of the neck fan according to their own needs, improving the user experience.

(76) In this embodiment, the first main body portion **101** and the second main body portion **102** can be regarded as two independent fans electrically connected to each other to form the neck fan. The circuit diagrams of various circuit modules included in the two independent fans are the same.

(77) Through the above structure, the first main body portion **101** and the second main body portion **102** are combined and spliced to form the complete U-shaped neck fan. At this time, the first conductive end **1018** is in conductive connection with the second conductive end **1019**. When the user presses the first switch **1015** or the second switch **1025**, the third fan working signal can be sent. At this time, after receiving the third fan working signal, the first main control module **814** drives the first boost module **815** to receive and boost the output voltage of the first battery **81**, thereby driving the first motor **32** to work. The rotation of the first motor **32** can drive a first fan blade **33** to rotate, achieving the air blowing effect of the first fan assembly. After receiving the third fan working signal, the second main control module **924** drives the second boost module **925** to receive and boost the output voltage of the second battery **91**, thereby driving the second motor **52** to operate. The rotation of the second motor **52** can drive a second fan blade **53** to rotate, achieving the air blowing effect of the second fan assembly.

(78) It can be understood, the first main control module **814** of FIG. **11** and the first boost module **815** may have other embodiments. Referring to FIG. **12**, in other embodiment, a boost control chip **U2** of the first boost module **815** can be omitted. Specially, in the embodiment of FIG. **13**, the first boost module **815** includes an inductor **L1** and a switch element **Q2**, a control terminal of an MCU of the first main control module **814** is electrically connected to a control terminal of the switch element **Q2**, a first connection terminal of the switch element **Q2** is electrically connected to the battery **BAT** via the first inductor **L1**, and a second connection terminal of the switch element **Q2** is grounded. The first connection terminal of the switch element **Q2** is also electrically connected to the first motor **MG1**, in detail, the first connection terminal of the switch element **Q2** is also electrically connected to the first motor **MG1** via a diode **D4**. The MCU of the first main control module **814** is configured to turn on/turn off the switch element **Q2**, such that a voltage of the battery **BAT** can boost, and a boosted voltage can be provided to the first motor **MG1** to drive the first fan blade **33**. Further, the second main control module **924** and the second boost module **925** of FIG. **5** also can have the same structure of the first boost module **815** and the first main control module **814** of FIG. **13**, such that another boosted voltage can be provided to the second motor to drive the second fan blade **53**.

Embodiment II

(79) Referring to FIG. **16** to FIG. **18**, a difference between Embodiment II and Embodiment I is only that the first main body portion **101** and the second main body portion **102** of the neck fan are removed to form two independent fans, so that the first main body portion **101** and the second main body portion **102** are two small fans capable of working alone.

(80) In this embodiment, the first main body portion **101** includes a first charging control module **811**, a first battery protection module **812**, a first charging indicator module **813**, a first main control module **814**, and a first boost module **815** which are electrically connected to the first circuit board **82**.

(81) The first charging interface **1016**, the first charging control module **811**, and the first charging indication module **813** are all electrically connected to the first battery **81**; the first charging interface **1016** and the first charging control module **811** are configured to charge the first battery **81**; the first charging indication module **813** is configured to display a battery level of the first battery **81**; and the first battery protection module **812** is electrically connected to the first charging control module **811** and the first battery **81** to protect the first battery **81**.

(82) The first main control module **814**, the first boost module **815**, and a first motor **32** are all electrically connected to the first battery **81**; the first switch **1015** and the first indication module

1017 are electrically connected to the first main control module **814**; the first switch **1015** is configured to send a first fan working signal; the first main control module **814** is configured to: receive the first fan working signal and drive the first boost module **815** to receive and boost an output voltage of the first battery **81**, to drive the first motor **32** to work; and the first indication module **1017** is configured to display turning on or turning off of the neck fan.

(83) Through the above structure, the first charging interface **1016** is configured to charge the first battery **81**; the first charging control module **811** is configured to control the charging of the first battery **81**; when the first switch **1015** is turned on, the first fan working signal is sent; when receiving the first fan working signal, the first main control module **814** is configured to drive the first boost module **815** to receive and boost the output voltage of the first battery **81**, to drive the first motor **32** to work; and the first main control module **814** can further adjust the speed of the first motor **32** by controlling the output voltage of the first boost module **815**.

(84) In this embodiment, the second main body portion **102** includes a second charging control module **921**, a second battery protection module **922**, a second charging indicator module **923**, a second main control module **924**, and a second boost module **925** which are electrically connected to the second circuit board **92**.

(85) The second charging interface **1026**, the second charging control module **921**, and the second charging indication module **923** are all electrically connected to the second battery **91**; the second charging interface **1026** and the second charging control module **921** are configured to charge the second battery **91**; the first charging indication module **923** is configured to display a battery level of the second battery **91**; and the second battery protection module **922** is electrically connected to the second charging control module **921** and the second battery **91** to protect the second battery **91**.

(86) The second main control module **924**, the second boost module **925**, and a second motor **52** are all electrically connected to the second battery **91**; the second switch **1025** and the second indication module **1027** are electrically connected to the second main control module **924**; the second switch **1025** is configured to send a second fan working signal; the second main control module **924** is configured to: receive the second fan working signal and drive the second boost module **925** to receive and boost an output voltage of the second battery **91**, to drive the second motor **52** to work; and the second indication module **1027** is configured to display turning on or turning off of the neck fan.

(87) Through the above structure, the second charging interface **1026** is configured to charge the second battery **91**; the second charging control module **921** is configured to control the charging of the second battery **91**; when the second switch **1025** is turned on, the second fan working signal is sent; when receiving the second fan working signal, the second main control module **924** is configured to drive the second boost module **925** to receive and boost the output voltage of the second battery **91**, to drive the second motor **52** to work; and the second main control module **924** can further adjust the speed of the second motor **52** by controlling the output voltage of the second boost module **925**. This structural design achieves an effect of using independent portions as independent fans after the neck fan is disassembled, bringing higher flexibility, and a user can select an appropriate usage method according to a specific need.

Embodiment III

(88) Referring to FIG. 19 to FIG. 26, Embodiment III of the present invention provides a neck fan. It can be understood that the descriptions of Embodiment I and Embodiment II mentioned previously are basically applicable to the neck fan of Embodiment III. Moreover, the following mainly describes the key contents of Embodiment III and the difference from Embodiment I and Embodiment II.

(89) The neck fan includes a hanging main body **1**. The hanging main body **1** includes a first main body portion **101**, a second main body portion **102**, a connection member **103** connecting the first main body portion **101** and the second main body portion **102**, a first fan assembly **3** arranged at one end of the first main body portion **101** away from the connection member **103**, and a second

fan assembly **5** arranged at one end of the second main body portion **102** away from the connection member **103**.

(90) The connection member **103** is detachably connected to both the first main body portion **101** and the second main body portion **102**; the first main body portion **101** is detachably connected to the first fan assembly **3**; and the second main body portion **102** is detachably connected to the second fan assembly **5**. Thus, all five portions of the neck fan are detachably connected, forming a modular design. This not only facilitates assembly but also reduces the costs of assembly and maintenance. Furthermore, users can disassemble, assemble, store by themselves and conduct DIY designs and so on, thereby improving the user experience.

(91) The first main body portion **101** has an arc-shaped structure, and includes a concave first air guide path **12** positioned on a surface of one side of the first main body portion **101** and extended along an extending direction of the arc-shaped structure. Moreover, the first fan assembly **3** is arranged at one end of the first main body portion **101** and is configured to blow air towards the first air guide path **12**. The first air guide path is configured to guide air of the first fan assembly **3** to one side of the first main body portion **101** (one side of the user's neck) and one end of the first main body portion **101** away from the first fan assembly **3** (such as the back of the user's neck).

(92) The second main body portion **102** has an arc-shaped structure, and includes a concave second air guide path **13** positioned on a surface of one side of the second main body portion **102** and extended along an extending direction of the arc-shaped structure. Moreover, the second fan assembly **5** is arranged at one end of the second main body portion **102** and is configured to blow air towards the second air guide path **13**. The second air guide path is configured to guide air of the second fan assembly **5** to one side of the second main body portion **102** (the other side of the user's neck) and one end of the second main body portion **102** away from the second fan assembly **5** (such as the back of the user's neck).

(93) Furthermore, the first main body portion **101** and the first fan assembly **3** can also be assembled into one to form a first fan main body, and the second main body portion **102** and the second fan assembly **5** can also be assembled into one to form a second fan main body. Thus, a neck fan can be disassembled into two fan main bodies for use according to users' needs. It can be understood that when used as a neck fan, one fan main body and the other fan main body are respectively arranged on both sides of the user's neck. Moreover, the fact that a neck fan can be disassembled into two fan main bodies for use according to users' needs can enrich usage scenarios, facilitate storage and improve the user experience.

(94) In some embodiments, the first fan main body and the second fan main body are manufactured independently and then connected together through an assembly process. Through the above arrangements, the two fan main bodies can also form a modular design. This not only facilitates assembly but also reduces the costs of assembly and maintenance. Moreover, users can disassemble, assemble, repair, store by themselves and conduct DIY designs and so on, thereby improving the user experience.

(95) The first fan assembly **3** includes a straight-tube-shaped first fan shell **31**, and the first fan shell **31** is detachably connected to the hanging main body **1** and is located within a first accommodating chamber **15**, and the first fan shell **31** is provided with a third air inlet **311** and a third air outlet **313**.

(96) Through the above structure, due to the straight-tube shape of the first fan shell **31**, the neck fan is formed into a vertical blowing type fan capable of blowing air in a vertical direction. The first fan assembly **3** can drive the air flow to be blown from the third air inlet **311** towards the user's neck via the third air outlet **313** along the first air guide path **12**, greatly improving the air—blowing efficiency. The user can directly feel the cool air blown to the neck when using the neck fan, thereby improving the overall performance of the fan. Furthermore, the first fan shell **31** is detachably connected to the hanging main body **1**, so that separate mold—opening, machining, and assembling can be achieved during production. The production efficiency is improved, the

production cost is reduced. Moreover, it is also convenient for storage and transportation, and the portability of the product is improved.

(97) In this embodiment, a plurality of connection buckle slots **151** are provided in an inner side of the first main body portion **101** of the hanging main body **1** adjacent to the first accommodating chamber **15**; a plurality of connection buckles **315** matched and clamped with the connection buckle slots **151** are arranged on an outer wall of the first fan shell **31**; and the first fan shell **31** is in detachably buckled connection to the hanging main body **1**. Specifically, the connection buckle slots **151** are symmetrically distributed on an inner side of the hanging main body **1**. There are six groups of connection buckle slots **151**. Each group includes two connection buckle slots **151**. The connection buckles **315** are symmetrically located on the outer wall of the first fan shell **31**. There are six groups of connection buckles **315**, and each group includes two connection buckles **315**. Through the above structure, users can manually install or remove the first fan shell **31** from the hanging main body **1**. The six-group buckle-matching structure ensures the firmness of the splicing, preventing the first fan shell from detaching during the wearing and use process, and improving the safety and convenience of the neck fan.

(98) In this embodiment, the first main body portion **101** of the hanging main body **1** is detachably connected with a first outer cover **16** on an outer side away from the first accommodating chamber **15**. As in Embodiment I, the first main body portion **101** of the hanging main body **1** is provided with a first mounting chamber **1014**, and the first power supply assembly **8** is located inside the first mounting chamber **1014**. The first mounting chamber **1014** has an opening, and the first outer cover **16** is detachably covered at the opening.

(99) In this embodiment, the first fan assembly **3** also includes a first motor **32** and a first fan blade **33** mounted on a rotating shaft of the first motor **32**.

(100) The first fan shell **31** can include a shell main body **31a**, an air inlet cover **31b**, a metal barrier net **3111** and an air outlet hood **31c**.

(101) The first fan blade **33** and the first motor **32** are arranged within the shell main body **31a**. Specifically, the shell main body includes a cylindrical sidewall structure **310a**, a mounting portion **310b** positioned at one end inside the sidewall structure **310a** and an air guiding portion **310c** connected between the mounting portion **310b** and the sidewall structure **310a**. The first fan blade **33** and the first motor **32** are arranged within the sidewall structure **310a**, on one side of the mounting portion **310b**, and the first motor **32** is mounted on the mounting portion **310b**.

(102) The air guiding portion **310c** includes a plurality of air guiding blades **310d** arranged at intervals and is configured to guide wind from the first fan blade **33** based on a preset direction. Specifically, the thickness of each air guiding blade **310d** can gradually increase along a direction from the first fan blade **33** to the third air outlet **313**, thus achieving a better air guiding effect. The air inlet cover **31b** can be annular, and the air inlet cover **31b** is sleeved on one end of the shell main body **31a**. Specifically, an outer side surface of one end of the shell main body **31a** can be provided with a stepped groove **31f**, and the air inlet cover **31b** is sleeved on the stepped groove **31f**. After mounting, the outer side surface of the air inlet cover **31b** is flush with the outer side surface of the shell main body **31a**. The metal barrier net **3111** is mounted on the inner side of the air inlet cover **31b**.

(103) The metal barrier net **3111** is provided with the third air inlet **311**. The third air inlet **311** includes a plurality of air inlet holes. Each air inlet hole **311a** can be circular, and the diameters of the plurality of air inlet holes **311a** can be the same. Each air inlet hole **311a** can have a diameter ranging from 0.5 mm to 4 mm. Such a size can prevent hair or debris from being sucked into the interior of the first fan assembly **3**. It can be understood that the metal barrier net **3111** is relatively thin and lightweight. This is conducive to the miniaturization and light weighting of the product. In addition, since it is made of metal material, the size of the air inlet holes of the metal barrier net **3111** can be arranged to be relatively small, thereby effectively preventing foreign objects from entering the first fan assembly **3**.

(104) The third air outlet **313** includes a plurality of air outlet holes **3130** arranged on the air outlet hood **31c**. Specifically, the air outlet hood **31c** includes an annular wall structure **31g**, a mounting structure **31h** and a plurality of air gathering rings **3131**. The plurality of air gathering rings **3131** are connected between the annular wall structure **31g** and the mounting structure **31h**. Moreover, the plurality of air outlet holes **3130** are defined as the spaces between the plurality of air gathering rings **3131**.

(105) The inner side surface of the annular wall structure **31g** is an inclined surface or an arc-shaped surface, so that an inner diameter of the annular wall structure **31g** gradually decreases along a direction from the third air inlet **311** to the third air outlet **313**. Thus, the blowing wind has a pressurizing effect and the outlet wind intensity is improved. The mounting structure **31h** includes an annular mounting wall **31i**, a cover plate **31j** connected to the annular mounting wall **31i** and a mounting column **31k** connected to an inner side of the cover plate **31j**, and the mounting column **31k** is connected to the mounting portion **310b**. Specifically, the mounting column **31k** can be detachably inserted into a mounting hole of the mounting portion **310b**, so that a detachable connection is formed between the air outlet hood **31c** and the shell main body **31a**. Moreover, the cover plate **31j** is circular and is positioned in the middle of the plurality of air outlet holes **3130**, and a groove is arranged on an outer surface of the cover plate **31j** for converging the outlet air.

(106) The metal barrier net **3111** can prevent hair or debris from being sucked into the first fan shell, thereby avoiding damage to the fan assembly and reducing the fan's blowing wind force. The air gathering rings **3131** can gather the air blown towards the neck, thereby improving the blowing performance.

(107) The first main body portion **101** further includes at least one air guiding vane **101h**, and at least one air guiding vane **101h** is arranged within the first air guide path **12** adjacent to the first fan assembly **3**, and is configured to guide the wind from the first fan assembly **3**.

(108) In this embodiment, the number of air guiding vanes **101h** is two. The two air guiding vanes **101h** are respectively arranged on two sides of the first air guide path **12**. Moreover, a distance between the two air guiding vanes **101h** gradually increases along an air outlet direction of the first air guide path **12**.

(109) In this embodiment, a first conductive through hole **152** is provided in an inner side of the hanging main body adjacent to the first accommodating chamber **15**. The first conductive through hole **152** is configured to allow a wire of the first fan assembly **3** to pass through to be communicated with a first power supply assembly **8**. Moreover, the mounting portion **310b** can be provided with an opening **310e**. The wire connected to the motor can pass through the opening **310e** and then be connected to the first power supply assembly **8** via the first conductive through hole **152**.

(110) Through the above structure, when the neck fan needs to be assembled, the first outer cover **16** is first opened, and then the wire of the first fan assembly **3** is communicated with the first power supply assembly **8** in the first mounting chamber **1014** through the first conductive through hole **152**. Then, the first outer cover **16** is closed. After the wire of the first fan assembly **3** is connected, the first fan shell **31** is assembled with the hanging main body **1** through the buckling between the connection buckles **315** and the connecting buckle slots **151**, and finally a vertical blowing type neck fan that is conductive with the hanging main body **1** and easy to mount is obtained.

(111) In this embodiment, a second accommodating chamber **17** is further inwards sunken in one side, opposite to the first accommodating chamber **15**, of the lower end portion of the second main body portion **102** of the hanging main body. The neck fan further includes a second fan assembly **5**. The second fan assembly **5** includes a straight-tube-shaped second fan shell **51**. The second fan shell **51** is detachably connected to the hanging main body and is located in the second accommodating chamber **17**. The second fan shell **51** is provided with a fourth air inlet **511** and a fourth air outlet **513**. The second fan assembly **5** is configured to drive an air flow to be blown from

the fourth air inlet **511** towards the inner end portion via the fourth air outlet **513**. Through the above structure, similarly, due to the straight-tube shape of the second fan shell **51**, the neck fan is formed into a vertical blowing type fan capable of blowing air in a vertical direction. The second fan assembly **5** can drive the air flow to be blown from the fourth air inlet **511** towards the inner end portion **11** via the fourth air outlet **513**, greatly improving the air-blowing efficiency. A user can directly feel the cool air blown to the neck when using the neck fan, thereby improving the overall performance of the fan. Furthermore, the second fan shell **51** is detachably connected and assembled with the hanging main body **1**, so that separate mold-opening, machining, and assembling can be achieved during production. The production efficiency is improved, the production cost is reduced, it is also convenient for storage and transportation, and the portability of the product is improved.

(112) In this embodiment, a plurality of connection buckle slots **151** are provided in an inner side of the second main body portion **102** of the hanging main body adjacent to the second accommodating chamber **17**; the plurality of connection buckles **315** matched and clamped with the connection buckle slots **151** are arranged on an outer wall of the second fan shell **51**; and the second fan shell **51** is in detachably buckled connection to the hanging main body **1**. Specifically, the connection buckle slots **151** are symmetrically distributed on an inner side of the second main body portion **102** of the hanging main body. There are six groups of connection buckle slots **151**. Each group includes two connection buckle slots **151**. The connection buckles **315** are symmetrically located on the outer wall of the second fan shell **51**. There are six groups of connection buckles **315**, and each group includes two connection buckles **315**.

(113) In this embodiment, a second outer cover **18** is detachably connected to the second main body portion **102** of the hanging main body on an outer side away from the second accommodating chamber **17**. As in Embodiment I, the second main body portion **102** of the hanging main body **1** is provided with a second mounting chamber **1024**, and the second power supply assembly **9** is located inside the second mounting chamber **1024**. The second mounting chamber **1024** has an opening, and the second outer cover **18** is detachably covered at the opening.

(114) Further, the specific structure of the second fan assembly **5** can be identical to the first fan assembly **3**. The second fan assembly **5** further includes a second motor **52** and a second fan blade **53** mounted on a rotating shaft of the second motor. The second fan shell **51** can be structurally similar to the first fan shell **31**. For example, it can include a shell main body **31a**, an air inlet cover **31b**, a metal barrier net **3111** and an air outlet hood **31c**. The fourth air inlet **511** can also include a plurality of air inlet holes **311a** arranged on the metal barrier net **3111** of the second fan shell **51**. The fourth air outlet can also include a plurality of air outlet holes **3130** arranged on the air outlet hood **31c** of the second fan shell **51**. The specific structure of the second main body portion **102** can be the same as that of the first main body portion **101**, and the second main body portion **102** and the first main body portion **101** can be arranged symmetrically. The second fan assembly **5** and the first fan assembly **3** can also be arranged symmetrically. Therefore, the specific structures of the second fan shell **51** and the second main body portion **102** will not be introduced repeatedly here.

(115) In this embodiment, a second conductive through hole **171** is provided in an inner side of the hanging main body adjacent to the second accommodating chamber **17**. The second conductive through hole **171** allows a wire of the second fan assembly **5** to pass through to be communicated with the second power supply assembly **9**.

(116) Through the above structure, after the assembling of the first fan shell **31** is completed, the second fan shell **51** is installed in the same manner. The second outer cover **18** is first opened, and then the wire of the second fan assembly **5** is communicated with the second power supply assembly **9** in the second mounting chamber **1024** through the second conductive through hole **171**. Then, the second outer cover **18** is closed. After the wire of the second fan assembly **5** is connected, the second fan shell **51** is assembled with the hanging main body **1** through the buckling between the connection buckles **315** and the connecting buckle slots **151**, and finally a vertical blowing type

neck fan that is conductive with the hanging main body **1** and easy to mount is obtained.

(117) It can be understood that the inner sides of the first outer cover **16** and the second outer cover **18** are provided with at least one first snap-fit member **160**, and the outer sides of the first main body portion **101** and the second main body portion **102** are provided with at least one second snap-fit member **1010**. The first snap-fit member **160** and the second snap-fit member **1010** are snap-fitted to enable the assembly of the first outer cover **16** and the first main body portion **101** as well as the assembly of the second outer cover **18** and the second main body portion **102**.

Specifically, the number of the first snap-fit member **160** and the second snap-fit member **1010** can be multiple, such as **160a**, **160b**, **160c**, **160d** and **101a**, **101b**, **101c**, **101d**. Moreover, the structures of the multiple first snap-fit members **160a**, **160b**, **160c**, **160d** can be different, and the multiple second snap-fit members **101a**, **101b**, **101c**, **101d** are of the structures that match and cooperate with the multiple first snap-fit members.

(118) It can be understood that both the first fan assembly **3** and the second fan assembly **5** are vertical blowing type fan assemblies with the air inlet and the air outlet on the same axis. In the first fan assembly **3**, the air inlet cover **31b**, the first fan blade **33**, the first motor **32**, the shell main body **31a** and the air outlet hood **31c** are all arranged in a straight line. In the second fan assembly **5**, the air inlet cover **31b**, the second fan blade **53**, the second motor **52**, the shell main body **31a** and the air outlet hood **31c** are all arranged in a straight line. In this way, the first fan assembly **3** and the second fan assembly **5** can generate relatively strong wind and achieve a better air outlet effect.

(119) Furthermore, according to Embodiment I and Embodiment II, it can be seen that the fan main body and the other fan main body can be respectively provided with corresponding and independent key switches **1015** and **1025**, so that the turning on and off of the fan main body and the other fan main body can be independently controlled by the corresponding key switches **1015** and **1025**.

(120) Furthermore, referring to FIG. 27, in a modified embodiment of Embodiment III, the air inlet holes **3110** of the metal barrier net **311** can also be in a regular hexagon. The plurality of air inlet holes **3110** are arranged in a honeycomb shape, and a surrounding wall **311a** is arranged between two adjacent air inlet holes **3110**. Such a design can make the air inlet area of the metal barrier net **311** the largest, minimize its weight, wind resistance, and maximize its air inlet volume. Specifically, the width of the surrounding wall ranges from 0.05 mm to 2 mm.

(121) One or more implementation modes are provided above in combination with specific contents, and it is not deemed that the specific implementation of the present invention is limited to these specifications. Any technical deductions or replacements approximate or similar to the method and structure of the present invention or made under the concept of the present invention shall fall within the scope of protection of the present invention.

Claims

1. A neck fan, comprising: a first fan main body; and a second fan main body connected to the first fan main body, wherein the first fan main body and the second fan main body are configured to blow air towards a user respectively, the first fan main body and the second fan main body are respectively provided with a control switch, and the control switch is configured to control an operation of the first fan main body and/or the second fan main body; wherein the first fan main body comprises a first main body portion, a first fan assembly, and a first power supply assembly, and the control switch comprises a first switch, the first main body portion is provided with a first mounting cavity, the first power supply assembly is arranged within the first mounting cavity and is electrically connected to the first fan assembly, the first power supply assembly comprises a first battery and a first circuit board, the first switch and the first battery are electrically connected to the first circuit board, the first circuit board is provided with a first main control module, the first

switch is mounted on the first main body portion and is electrically connected to the first main control module, and the first switch is configured to turn on or turn off the first fan assembly; wherein the first fan main body further comprises a first boost module; wherein the second fan main body comprises a second main body portion, a second fan assembly, and a second power supply assembly, and the control switch further comprises a second switch, the second power supply assembly comprises a second battery and a second circuit board, the second switch and the second battery are electrically connected to the second circuit board, the second circuit board is provided with a second main control module, the second switch is mounted on the second main body portion and is electrically connected to the second main control module, the second switch is configured to turn on or turn off the second fan main body, the second fan main body further comprises a second boost module; and wherein the first main body portion is provided with a first conductive end, the second main body portion is provided with a second conductive end, when the first fan main body and the second fan main body are connected together, consequently, the first conductive end is communicated with the second conductive end, the first switch is electrically connected to the first main control module and the second main control module respectively, and the second switch is also electrically connected to the first main control module and the second main control module respectively, such that at least one of the first switch and the second switch can send out a fan working signal; the first main control module is configured to receive the fan working signal and drive the first boost module to boost the output voltage of the first battery, thereby driving the first fan assembly to operate, and the second main control module is configured to receive the fan working signal and drive the second boost module to boost the output voltage of the second battery, thereby driving the second fan assembly to operate.

2. The neck fan according to claim 1, wherein the second fan main body and the first fan main body are oppositely arranged and are configured to be positioned on two sides of the user's neck; and the second fan main body and the first fan main body are the same.

3. The neck fan according to claim 1, wherein the first fan main body further comprises a first charging interface and a first charging control module, and the first charging interface and the first charging control module are configured to charge the first battery; the first fan main body further comprises a first status indication module, and the first status indication module is configured to display at least one of a startup status, a shutdown status, a charging status, and an output wind level of the first fan main body or the neck fan.

4. The neck fan according to claim 1, wherein the first fan main body further comprises a first battery protection module, the first battery protection module is electrically connected to the first main control module and the first charging control module, and is configured to perform charging protection for the first battery.

5. The neck fan according to claim 1, wherein the first switch comprises a stepless adjustment key configured to perform stepless adjustment and control the rotation speed of the first fan main body; and the stepless adjustment key is a potentiometer with variable electric resistance or an encoder.

6. The neck fan according to claim 5, wherein the stepless adjustment key comprises a plurality of connection terminals and at least one adjustment pin, one of the plurality of connection terminals is grounded, and at least one adjustment pin is configured for the user to operate so that the other connection terminals output corresponding stepless adjustment signals.

7. The neck fan according to claim 1, wherein the first boost module comprises an inductor and a switching element, a control terminal of a MCU of the first main control module is connected to a control terminal of the switching element, a first conducting terminal of the switching element is connected to the first battery via the inductor, a second conducting terminal of the switching element is grounded, the first conducting terminal of the switching element is connected to the first fan assembly, the MCU of the first main control module controls the on-off state of the switching element, thereby controlling the voltage from the first battery to be boosted through the inductor, and provides the boosted voltage to the first fan assembly to drive the first fan assembly to blow

air.

8. The neck fan according to claim 1, wherein the first fan main body and the second fan main body are detachably connected, so that the first fan main body and the second fan main body are able to operate and be used independently.

9. A neck fan, comprising: a first fan main body; and a second fan main body connected to the first fan main body, wherein the first fan main body and the second fan main body are configured to blow air towards a user respectively, the first fan main body and the second fan main body are respectively provided with a control switch, and the control switch is configured to control an operation of the first fan main body and/or the second fan main body, wherein the neck fan further comprises a connection member, the connection member comprises a flexible connection portion, the flexible connection portion is provided with at least one installation hole, the at least one installation hole is configured to be sleeved and fixed on one end of the first fan main body and one end of the second fan main body, so that the first fan main body and the second fan main body are connected through the flexible connection portion; and wherein an inner sidewall of the at least one installation hole is provided with a first anti-detachment structure and a second anti-detachment structure, the first anti-detachment structure is configured to engage with a first buckle on an outer surface of one end of the first fan main body, the second anti-detachment structure is configured to engage with a second buckle on one end of the second fan main body, and at least one of the first anti-detachment structure and the first buckle is provided with a plurality of concave-convex structures arranged in sequence along an extending direction of the connection member.

10. The neck fan according to claim 9, wherein the first anti-detachment structure comprises a plurality of first buckle slots arranged along an extending direction of the connection member, the plurality of first buckle slots are configured to engage with a plurality of protrusions arranged along an extending direction of the first buckle; the second anti-detachment structure comprises a plurality of second buckle slots arranged along the extending direction, the plurality of second buckle slots are configured to engage with a plurality of protrusions arranged along an extending direction of the second buckle; the first anti-detachment structure is configured to be detachably connected with the first buckle, and the second anti-detachment structure is configured to be detachably connected with the second buckle; the flexible connection portion is also provided with a first fixing structure and a second fixing structure, the first fixing structure and the second fixing structure are respectively arranged at two ends of the flexible connection portion, the first fixing structure is configured to connect with a third fixing structure at one end of the first fan main body, and the second fixing structure is configured to connect with a fourth fixing structure at one end of the second fan main body; the first fixing structure is configured to be detachably connected with the third fixing structure, and the second fixing structure is configured to be detachably connected with the fourth fixing structure.

11. The neck fan according to claim 9, wherein the connection member further comprises at least one neck support portion, the at least one neck support portion is connected to an inner side of the flexible connection portion and configured to rest adjacent to a user's neck, the at least one neck support portion is configured to form at least one air inlet gap with the first fan main body or the second fan main body, so that air from the first fan main body or the second fan main body can enter the air inlet gap.

12. The neck fan according to claim 1, wherein the first fan main body comprises a first main body portion, the first main body portion has an arc-shaped structure, and comprises a concave first air guide path positioned on a surface of one side of the first main body portion and extended along an extending direction of the arc-shaped structure; the first fan assembly is arranged at one end of the first main body portion and is configured to blow air towards the first air guide path, and the first air guide path is configured to guide air of the first fan assembly to one side of the first main body portion and one end of the first main body portion away from the first fan assembly.

13. The neck fan according to claim 12, wherein the first fan assembly comprises a first fan shell, a

first motor, and a first fan blade mounted on a rotating shaft of the first motor, the first motor and the first fan blade are arranged within the first fan shell; the first fan shell comprises a shell main body and an air outlet hood, the air outlet hood is arranged on one side of the shell main body; the air outlet hood comprises a plurality of air gathering rings and an annular wall structure connected to a periphery of the plurality of air gathering rings, a plurality of air outlet holes are formed among the plurality of air gathering rings, and the air gathering rings are configured to cooperate with an inner side surface of the annular wall structure to pressurize wind from the shell main body and then blow it out.

14. The neck fan according to claim 13, wherein the inner side surface of the annular wall structure is an inclined surface or an arc-shaped surface, so that an inner diameter of the annular wall structure gradually decreases along a direction from the shell main body to the air outlet hood; the shell main body comprises an annularly arranged sidewall structure, an mounting portion positioned at one end inside the sidewall structure and an air guiding portion connected between the mounting portion and the sidewall structure, the air guiding portion comprises a plurality of air guiding blades arranged at intervals and is configured to guide wind from the first fan blade based on a preset direction, the first fan blade and the first motor are arranged within the sidewall structure and are positioned on one side of the mounting portion, and the first motor is mounted on the mounting portion; the first fan shell further comprises a metal barrier net, the metal barrier net is arranged on one side of the sidewall structure away from the air outlet hood, the metal barrier net is made of metal material and is provided with a plurality of air inlet holes, and an inner diameter of each air inlet holes ranges from 0.5 mm to 4 mm; the air inlet hole is in a regular hexagon shape, a surrounding wall is arranged between two adjacent air inlet holes, and a width of the surrounding wall ranges from 0.05 mm to 2 mm.
