

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12405995

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Chaudhary; Vishrav et al.

Using large generative models with improved grounding to improve image context queries

Abstract

The disclosure describes utilizing an image query system to improve response accuracy and reduce computational steps resources in responding to natural language queries of input images. In various implementations, the image query system utilizes grounding information from one or more sources to determine accurate information for an input image. For example, the image query system uses a single comprehensive image prompt to obtain extensive visual image grounding information for the input image from a visual-based large generative model. Additionally, or in alternative implementations, the image query system obtains reverse image search grounding information for the input image. The image query system then cleverly utilizes the grounding information with a large generative language model to generate text query responses to image-based queries of the input image more accurately and efficiently.

Inventors: Chaudhary; Vishrav (Covington, WA), Abrams; Bradley Moore (Palo Alto, CA), Ginotra; Kamal (Kirkland, WA), Mohammed; Owais Khan (Bellevue, WA), Patra; Barun (Vancouver, CA), Valenzuela; Michael Lawrence (Yelm, WA)

Applicant: Microsoft Technology Licensing, LLC (Redmond, WA)

Family ID: 95860423

Assignee: Microsoft Technology Licensing, LLC (Redmond, WA)

Appl. No.: 18/527923

Filed: December 04, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20250181631 A1

Jun. 05, 2025

Publication Classification

Int. Cl.: G06F16/532 (20190101); G06F16/242 (20190101)

U.S. Cl.:

CPC G06F16/532 (20190101); G06F16/243 (20190101);

Field of Classification Search

CPC: G06F (16/532); G06F (16/243)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0357779	12/2020	Kabra	N/A	G06N 5/04
2023/0016082	12/2022	Kabra	N/A	G06N 5/04
2024/0127085	12/2023	Kabra	N/A	G06N 20/00

Primary Examiner: To; Baoquoc N

Attorney, Agent or Firm: Ray Quinney & Nebeker P.C.

Background/Summary

BACKGROUND

(1) Search engine services have significantly enhanced the ability to explore websites across the vast expanse of the Internet. More recently, advanced chat services utilizing artificial intelligence (AI), known as large generative models (LGMs), including large language models (LLMs), have emerged. In some cases, LGMs use machine-learning models to provide information about user-submitted images. Despite these and other recent advancements, LGMs still suffer from various shortcomings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The following detailed description provides specific and detailed implementations accompanied by drawings. Additionally, each of the figures listed below corresponds to one or more implementations discussed in this disclosure.
- (2) FIG. 1 illustrates an example overview of implementing the image query system that uses one or more large generative models to accurately and efficiently generate one or more text query responses to image-based queries for an input image.
- (3) FIG. 2 illustrates an example computing environment in which the image query system is implemented in a cloud computing system.
- (4) FIGS. 3A-3B illustrate example workflow diagrams for efficiently generating multiple text query responses using a large generative language model and a visual-based large generative

model.

(5) FIGS. 4A-4B illustrate example workflow diagrams for efficiently generating multiple text query responses using a large generative language model, a visual-based large generative model, and reverse image search grounding information.

(6) FIGS. 5A-5B illustrate example workflow diagrams for efficiently generating multiple text query responses using a large generative language model and reverse image search grounding information and selectively using the visual-based large generative model.

(7) FIG. 6 illustrates an example graphical user interface for interacting with the image query system to generate text query responses to image-based queries for an input image.

(8) FIGS. 7A-7B illustrates an example series of acts in a computer-implemented method for providing text, audio, or other forms of user query responses to image-based queries.

(9) FIG. 8 illustrates example components included within a computer system.

DETAILED DESCRIPTION

(10) This disclosure describes utilizing an image query system to generate responses to natural language queries regarding input images in a way that improves response accuracy and reduces computational resources. In various implementations, the image query system utilizes grounding information from one or more sources to determine accurate information for an input image. For example, the image query system uses a single comprehensive image prompt to obtain extensive visual image grounding information for the input image from a visual-based large generative model. Additionally, or in alternative implementations, the image query system obtains reverse image search grounding information for the input image. The image query system then utilizes the grounding information with a large generative language model to more accurately and efficiently generate text query responses to image-based queries of the input image.

(11) In particular, implementations of the present disclosure provide benefits and solve problems in the art with systems, computer-readable media, and computer-implemented methods using an image query system that improves accuracy and reduces computing operations using a combination of large generative models and dynamic grounding information. Indeed, as further explained below, the image query system provides improved accuracy and efficiency compared to existing systems.

(12) As mentioned above, LGMs still suffer from various shortcomings. For instance, some existing computer systems that use LGMs to provide image-based information suffer from several inaccuracies and inefficiencies. For example, LGMs often provide unsatisfactory results when describing images, especially newer images for which the LGM was not trained. Furthermore, these existing computer systems perform many expensive and unnecessary computer operations.

(13) In contrast to existing systems, the image query system provides several technical benefits. To illustrate, in one or more implementations, based on receiving an input image and a corresponding natural language query, the image query system obtains reverse image search grounding information for the input image. In some implementations, the image query system provides a comprehensive image prompt and the input image to a visual-based large generative model to generate visual image grounding information. Using the grounding information (e.g., the visual image grounding information and/or the reverse image search grounding information), the image query system generates a text query response to the natural language query using a large generative language model. The image query system then provides the text query response to the user to answer the natural language query.

(14) As another illustration, in some implementations, based on receiving an input image and a corresponding natural language query, the image query system obtains reverse image search grounding information for the input image and generates a text query response to the natural language query using a large generative language model based on the reverse image search grounding information. If the image query system determines that the text query response meets a threshold confidence value, the image query system provides the text query response to the user without prompting a visual-based large generative model. Otherwise, to ensure an accurate answer

when the threshold confidence value is not met, the image query system may prompt the visual-based large generative model for additional image context information that may be used to answer the user query.

(15) Regarding the shortcomings of existing systems, as mentioned above, while some existing systems provide information about user-submitted images, such as answering questions about an input image, these systems often produce incorrect and unsatisfactory text query responses. This problem worsens when the input image is unique (e.g., not frequently found online) or recently posted online. In these instances, even large generative models struggle to provide accurate answers regarding these input images. More commonly, the large generative model provides a response seeking more information from the user (e.g., asking the user to answer their own question) or indicating that an accurate response is unavailable.

(16) In contrast to existing systems, as described in this disclosure, the image query system delivers several significant technical benefits in terms of computing accuracy and efficiency. Moreover, the image query system provides several practical applications that address problems related to accurately and efficiently generating multiple text query responses using various large generative models and grounding information.

(17) To elaborate, in some examples, the image query system improves computing efficiency by using a comprehensive image prompt. For example, by using a single comprehensive image prompt to the visual-based large generative model, which is separate from any specific natural language query, the image query system obtains extensive visual image grounding information that the large generative language model uses to answer multiple natural language queries for the input image. Indeed, because calls to the visual-based large generative model are even more computationally expensive than to inference or run the large generative language model, the image query system saves a significant amount of memory and processing resources by not calling the visual-based large generative model more than once per input image regardless of the number of corresponding natural language queries.

(18) Additionally, by using visual image grounding information obtained from the comprehensive image prompt, the large generative language model has more context regarding the input image and generates text query responses with improved accuracy. Further, in various implementations, the image query system provides reverse image search grounding information to the visual-based large generative model, which allows the visual-based large generative model to generate even more accurate versions of the visual image grounding information. Likewise, by using the reverse image search grounding information, the large generative language model also generates more accurate text query responses. Moreover, obtaining the reverse image search grounding information is computationally inexpensive compared to executing the large generative language model and almost trivial compared to executing the visual-based large generative model.

(19) In some implementations, the image query system further improves computing efficiency by not calling the visual-based large generative model. In these instances, the image query system uses the reverse image search grounding information in the large generative language model to generate an initial text query response. If the initial text query response is sufficiently accurate, the image query system provides it to the user. Otherwise, if the initial text query response does not meet a threshold confidence value for accuracy, the image query system calls the visual-based large generative model for visual image grounding information to generate an accurate text query response.

(20) As a further technical benefit, the image query system flexibly operates with unique and recently published images. For example, by gathering reverse image search grounding information based on identifying identical and/or similar images to the input image, the image query system can obtain and implement the reverse image search grounding information, as provided above, to generate accurate text query responses.

(21) As illustrated in the foregoing discussion, this disclosure utilizes a variety of example terms to

describe the features and advantages of one or more implementations. For instance, this disclosure describes the image query system in the context of a cloud computing system. As an example, the term “cloud computing system” refers to a network of interconnected computing devices that provide various services and applications to computing devices (e.g., server devices and client devices) inside or outside of the cloud computing system. Additional terms are defined throughout the document in different examples and contexts.

(22) As another example, the term “large generative model” (LGM) refers to an artificial intelligence system with billions or trillions of parameters that uses deep learning to produce coherent and contextually relevant text based on patterns learned from large amounts of training data. In various implementations, a generative learning model, such as a multi-modal generative model, refers to an advanced computational system that uses natural language processing, machine learning, and/or image processing to generate coherent and contextually relevant human-like responses.

(23) As mentioned above, large generative models have a large number of parameters (e.g., in the billions or trillions) and are trained on a vast dataset to produce fluent, coherent, and topic-specific outputs (e.g., text and/or images). Large generative models have applications, including natural language understanding, content generation, text summarization, dialog systems, language translation, creative writing assistance, and image generation. A single large generative model performs a wide range of tasks based on different inputs, such as prompts (e.g., input instructions, rules, example inputs, example outputs, and/or tasks), data, and/or access to data. In response, the large generative model generates various output formats ranging from one-word answers to long narratives, images and videos, labeled datasets, documents, tables, and presentations.

(24) Large generative models include large generative language models (LGLMs) (a.k.a. simply “large language models” (LLMs)), which are primarily based on transformer architectures to understand, generate, and manipulate human language. LLMs can also use a recurrent neural network (RNN) architecture, long short-term memory (LSTM) model architecture, convolutional neural network (CNN) architecture, or other architecture types. Examples of LLMs include generative pre-trained transformer (GPT) models such as GPT-3.5 and GPT-4, bidirectional encoder representations from transformers (BERT) model, text-to-text transfer transformer models such as T5, conditional transformer language (CTRL) models, and Turing-NLG. Other types of large generative models include sequence-to-sequence models (Seq2Seq), vanilla RNNs, and LSTM networks.

(25) Large generative models include visual-based large generative models (LGM-V). Visual-based large generative models generate visual image grounding information from an input image. For instance, a visual-based large generative model uses a combination of convolutional neural networks (CNNs) and transformers to generate high-quality visual content and/or extract visual features from the input image.

(26) As an example, the term “prompt” refers to a query or input provided to a large generative model that provides instructions, directions, guidelines, and/or parameters for generating an answer or result. A prompt may include carefully selected parameters determined based on various factors, such as available input information and desired output data format. In some implementations, a prompt includes and/or references additional information being provided to a large generative model. Additional examples of prompts, including user-generated prompts (e.g., natural language query) and system-generated prompts are provided below.

(27) As another example, the term “grounding information” refers to a set of visual information associated with an image (e.g., an input image provided by a user). Grounding information provides context for an image based on processing and analyzing the image. In some instances, grounding information is extracted directly from an image, such as visual image grounding information. For example, grounding information includes the most relevant identified objects or regions in an image text, image metadata, and/or other image information. In some

implementations, grounding information is indirectly obtained for the image by using external content associated with identical or similar instances of an input image (e.g., reverse image search grounding information). For instance, reverse image search grounding information includes text from a website that includes an image similar or identical to the input image.

(28) Additionally, as an example, a “network” refers to one or more data links that enable electronic data transport between computer systems and/or modules and/or other electronic devices. A network may include public networks such as the Internet as well as private networks. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a computer, the computer properly views the connection as a transmission medium. Transmission media can include a network and/or data links that can be used to carry needed program code means in the form of computer-executable instructions or data structures and which can be accessed by a general-purpose or special-purpose computer. Combinations of the above are also included within the scope of computer-readable media.

(29) Additional example implementations and details of the image query system are discussed in connection with the accompanying figures, which are described next. For example, FIG. 1 illustrates an example overview of implementing the image query system using large generative models to accurately and efficiently generate one or more text query responses to image-based queries for an input image according to some implementations. As shown, FIG. 1 illustrates a series of acts **100** performed by the image query system within a cloud computing system.

(30) As shown, the series of acts **100** includes act **101** of receiving an input image and a natural language query seeking information about the input image. For instance, the image query system receives a request that includes the input image and a corresponding natural language query requesting information about the input image. In some instances, the request is provided as part of a search or chat service that answers queries and requests from users.

(31) In one or more implementations, the image query system obtains reverse image search grounding information for the input image, as shown in act **102**. For instance, in various implementations, the image query system provides the input image to a reverse image search model to generate image search grounding information. Additional details about reverse image search grounding information are provided below in connection with FIG. 4A. In some instances, the image query system skips act **102** and does not obtain reverse image search grounding information.

(32) As shown, the series of acts **100** includes act **103** of providing a comprehensive image prompt to a visual-based large generative model to generate visual image grounding information. In many instances, the image query system provides the input image to a visual-based large generative model along with a comprehensive image prompt with directions to generate visual image grounding information for the input image. The comprehensive image prompt is independent of the natural language query and is designed to cover a wide range of potential natural language queries. In some instances, the image query system may provide the image search grounding information to the visual-based large generative model.

(33) The image query system uses the comprehensive image prompt to task the visual-based large generative model to provide as much grounding information as possible about the input image. Additional details about generating visual image grounding information are provided below in connection with FIG. 3A. In a few implementations, the image query system bypasses act **103** of using the visual-based large generative model, as described below in connection with FIG. 5A.

(34) As shown, the series of acts **100** includes act **104** of generating a text query response to the natural language query using a large generative model and the grounding information. For instance, the image query system provides the natural language query along with one or more pieces of grounding information to a large generative model, such as a large language model, to generate a text query response to the natural language query. Depending on the grounding information obtained, the image query system provides the visual image grounding information and/or the

image search grounding information to the large generative model to assist it in generating an accurate text query response. Additional details about generating text query responses using a large generative model are provided below in connection with FIG. 3A, FIG. 4A, and FIG. 5A.

(35) In addition, as shown, the series of acts **100** includes act **105** of generating additional text query responses to additional natural language queries using the large generative model and the grounding information without again calling the visual-based large generative model. For instance, upon providing the first text query response to a user, the image query system may receive additional natural language queries. For each query, the image query system utilizes the previously received grounding information and the large generative model to answer the additional queries. This way, the image query system significantly saves computer resources by not calling the visual-based large generative model, which is much more computationally expensive than calling the large generative model. Furthermore, by using the comprehensive grounding information previously received, the image query provides highly accurate text query responses to the additional queries. Additional details about generating additional text query responses without making additional calls to the visual-based large generative model are provided below in connection with FIG. 3B, FIG. 4B, and FIG. 5B.

(36) With a general overview in place, the next figure provides a general overview of the components, features, and elements of the image query system. To illustrate, FIG. 2 shows an example computing environment where the image query system is implemented in a cloud computing system according to some implementations. In particular, FIG. 2 shows an example of a computing environment **200** of various computing devices within a cloud computing system **202** associated with an image query system **206**. While FIG. 2 shows example arrangements and configurations of the computing environment **200**, the cloud computing system **202**, the image query system **206**, and associated components, other arrangements and configurations are possible.

(37) As shown, the computing environment **200** includes a cloud computing system **202** and a client device **250** connected via a network **260**. The cloud computing system **202** includes a content management system **204**, a reverse image search model **228**, a visual-based large generative model **230**, and a large generative language model **240**. Each of these components may be implemented on one or more computing devices, such as on a set of one or more server devices. Further details regarding computing devices are provided below in connection with FIGS. 7A-7B along with Additional details about networks, such as the network **260** shown.

(38) The content management system **204** performs a variety of functions. For example, in one or more implementations, the content management system **204** facilitates user interactions with various machine-learning models including the large generative language model **240**. For example, the content management system **204** provides text query responses within a search service to natural language queries that do not include input images.

(39) As shown, the content management system **204** includes the image query system **206**. In some implementations, the content management system **204** is located on a separate computing device from the content management system **204** within the cloud computing system **202**. For example, the image query system **206** is on another server device, or the image query system **206** is located wholly or in part on the client device **250**.

(40) As mentioned earlier, the image query system **206** generates text query responses to natural language queries about input images. As shown, the image query system **206** includes various components and elements, which are implemented in hardware and/or software. For example, the image query system **206** includes an image manager **210**, a reverse image search manager **212**, a large generative model manager **214**, a grounding information manager **216**, a natural language query manager **218**, and a storage manager **220** having input images **222**, a comprehensive image prompt **224**, and grounding information **226**.

(41) As mentioned above, the image query system **206** includes the image manager **210**, which manages receiving, accessing, and handling input images **222**. The image manager **210** directly or

indirectly obtains input images **222** corresponding to a natural language query. For example, a user may directly provide an input image or may provide access (e.g., a link) to an input image.

(42) The image query system **206** also includes the reverse image search manager **212**, which generates image search grounding information by providing input images **222** to the reverse image search model **228**, which generates and returns the image search grounding information. The reverse image search manager **212** may provide the image search grounding information to the storage manager **220** to store it as grounding information **226**.

(43) As shown, the image query system **206** includes the large generative model manager **214**, which provides prompts to large generative models. For example, the large generative model manager **214** provides a comprehensive image prompt **224** to the visual-based large generative model **230**. In some instances, the large generative model manager **214** generates other prompts (e.g., large generative model-based prompts) to provide to the large generative language model **240** to generate text query responses, as further described below.

(44) The image query system **206** also includes the grounding information manager **216**, which communicates with the visual-based large generative model **230** to generate visual image grounding information. In some instances, the grounding information manager **216** works with the reverse image search manager **212** to obtain the image search grounding information. When grounding information is received, the grounding information manager **216** may provide it to the storage manager **220** to be stored as the grounding information **226**. The grounding information manager **216** can also access stored grounding information when it is needed by components of the image query system **206**.

(45) As shown, the image query system **206** includes the natural language query manager **218**, which receives, stores, provides, and manages natural language queries received from users. In some instances, the natural language query manager **218** provides generated text query responses back to users in response to a natural language query.

(46) As shown, the cloud computing system **202** includes the client device **250**. In various implementations, the client device **250** is associated with a user (e.g., a user client device), such as a user who interacts with the image query system **206** to request and receive text query responses to natural language queries. For example, the client device **250** includes a client application **252**, such as a web browser or another form of computer application for accessing and/or interacting with the image query system **206** via the network **260**.

(47) The next set of figures includes example workflows of the image query system efficiently generating accurate text query responses by providing dynamically obtained grounding information to a large generative model. For example, FIGS. 3A-3B illustrate generating text query responses based on visual image grounding information, FIG. 4A-4B illustrate generating text query responses based on image search grounding information and visual image grounding information; FIG. 5A-5B illustrate generating text query responses based on at least image search grounding information.

(48) To elaborate, FIGS. 3A-3B illustrate example workflow diagrams of efficiently generating multiple text query responses using a large generative language model and a visual-based large generative model. In these figures, the image query system **206** generates text query responses based on visual image grounding information alone and not image search grounding information. In other words, in some implementations, the image query system **206** utilizes a visual-based large generative model but not a reverse image search model in generating text query responses.

(49) As shown, FIG. 3A includes user input **302**, a visual-based large generative model **330**, the image query system **206**, a large generative language model **340**, and a text query response **342**. The user input **302** includes an input image **304** and a natural language query **306**. The image query system **206** includes an LLM prompt generator **318**, a comprehensive image prompt **312**, and visual image grounding information **314**. Each of these components and elements is described below.

(50) In many implementations, the image query system **206** receives user input **302** corresponding to a user search request or user chat query. More particularly, the image query system **206** receives an input image **304** and a natural language query **306**, which corresponds to the input image **304**. While FIG. **3A** shows the image query system **206** receiving only the natural language query **306** from the user input **302**, the image query system **206** receives both, but processes the pieces of information differently, as described next.

(51) As mentioned above, FIG. **3A** includes the visual-based large generative model **330**. As shown, the visual-based large generative model **330** receives the input image **304** from the user input **302**. While illustrated differently for clarity, in many implementations, the image query system **206** receives the input image **304** and then provides it to the visual-based large generative model **330** (along with the comprehensive image prompt **312**) to generate the visual image grounding information **314**.

(52) In various implementations, the image query system **206** provides the comprehensive image prompt **312** to the visual-based large generative model **330**, which includes or references the input image **304**. For example, the comprehensive image prompt **312** is a set of contexts, parameters, and examples for instructing the visual-based large generative model **330** on what to include when generating the visual image grounding information. In many instances, the comprehensive image prompt **312** is the same as or similar to the input image **304**.

(53) In addition, as shown, the comprehensive image prompt **312** is independent of the natural language query **306**. As mentioned above, to determine the context of an input image, the comprehensive image prompt **312** includes queries of different scopes about the visual information included in an input image. For example, the comprehensive image prompt **312** includes questions about what the image is of, whether a theme is present, whether the image appears real or synthetic; whether people are included, information about identified people, what the people are doing; whether any text is included, what does the text say, what language the text is in; whether objects are present, object types, the size and position of each object, object properties, how the objects relate to each other).

(54) The comprehensive image prompt **312** may also include prompts about the metadata of an image. For example, the comprehensive image prompt **312** includes questions about the origin of the image, such as how and where the image was captured or created, and location information associated with the image, including a geographic location as well as an online location (e.g., URL). The comprehensive image prompt **312** may also include metadata questions, such as those relating to the size and color palettes present in the image, pixel density, and hash keys. The comprehensive image prompt **312** may include additional metadata questions.

(55) Furthermore, the comprehensive image prompt **312** may provide parameters, such as input and output parameters. For instance, the comprehensive image prompt **312** includes system-level and/or metadata-level context information directing the visual-based large generative model on the perspective to use when analyzing the input image, output styles (e.g., casual or formal, output formats (e.g., bullet point, paragraphs, XML, tabular), the target audience, and output size limits. Additionally, the comprehensive image prompt **312** may include responsible artificial intelligence (AI) requirements that the large generative language model must follow to prevent it from processing and providing malicious, inappropriate, and unauthorized content.

(56) Regarding responsible AI, the image query system **206** may include various checkpoints to ensure non-malicious and appropriate content. For example, upon receiving the input image **304**, the image query system **206** ensures that the image passes a content audit. If not, the image query system **206** provides an error message back to the user. In addition, the image query system **206** may verify that any text query response provided to the user also passes a responsible AI verification check before returning the text query response.

(57) Additionally, the comprehensive image prompt **312** may include output templates and/or output examples. Indeed, the comprehensive image prompt **312** may cover all aspects of analyzing

and extracting visual information from an input image and how to report back the information as grounding information to the image query system **206**. The comprehensive image prompt **312** may also include directions for providing the visual image grounding information as a single output or as separate outputs (e.g., one output for the image as a whole and additional outputs for each detected person, object, and/or theme).

(58) Notably, calling the visual-based large generative model **330** is computationally expensive in terms of memory and processing power. For instance, the visual-based large generative model **330** is roughly twice as expensive as the large generative language model **340**. However, the processing costs for the visual-based large generative model **330** are similar for both simple calls and complex calls. For example, providing a simplified prompt corresponding to the natural language query **306** costs roughly the same as providing the comprehensive image prompt **312**, which anticipates answering queries corresponding to hundreds or thousands of queries. Accordingly, sending a single complex, comprehensive image prompt is much more efficient than sending multiple simple image prompts.

(59) As shown, the visual-based large generative model **330** generates the visual image grounding information **314** from the input image **304** and the comprehensive image prompt **312**. In various implementations, the visual image grounding information **314** includes a bullet point list of grounding information corresponding to the input image **304**. As noted, this grounding information is not restricted to the natural language query **306** but rather covers a wide array of visual information about the input image **304**.

(60) In various implementations, the image query system **206** generates the first LLM prompt **320** from the visual image grounding information **314** and the natural language query **306** using the LLM prompt generator **318**. In particular, the image query system **206** provides the natural language query **306** to the LLM prompt generator **318** along with the visual image grounding information **314**. The LLM prompt generator **318** generates an LLM prompt to provide to the large generative language model **340** that directs the model to answer the natural language query **306** given the grounding information from the visual image grounding information **314**. For example, the first LLM prompt **320** includes the prompt “Please answer the natural language query of <<natural language query>> using the provided information.”

(61) As illustrated, the large generative language model **340** generates the text query response **342** in response to the first LLM prompt **320**. Because the large generative language model **340** was trained on large amounts of data, it efficiently processes the visual image grounding information **314**, even if it includes a large amount of visual information about the input image **304**.

Furthermore, by having large amounts of visual information as image grounding information, the large generative language model **340** generates a highly accurate text query response to the natural language query **306**.

(62) In addition to the improvements in efficiency and accuracy achieved using the comprehensive image prompt **312** to generate the text query response **342**, the image query system **206** achieves significant additional efficiency improvements when generating additional text query responses. In particular, when providing text query responses for additional natural language queries corresponding to the input image **304**, the image query system **206** does not need to call the visual-based large generative model **330**, which is computationally expensive. This concept is further described next.

(63) To illustrate, FIG. **3B** shows a workflow diagram of efficiently generating multiple text query responses using a large generative language model, but not the visual-based large generative model according to some implementations. FIG. **3B** includes many of the same components and elements as FIG. **3A**. In addition, FIG. **3B** includes an additional natural language query **308** in place of the input image **304** and the natural language query **306**. Notably, FIG. **3B** does not include the input image **304** and the comprehensive image prompt **312**. Further, while the visual-based large generative model **330** is shown, it is crossed out to emphasize its non-use for answering additional

natural language queries.

(64) As shown, the image query system **206** receives the additional natural language query **308**. To be clear, the additional natural language query **308** corresponds to the input image **304** previously provided to the image query system **206**. For example, the additional natural language query **308** is a follow-up question received upon providing the text query response **342** to a user within a search or chat service interface.

(65) Upon receiving the additional natural language query **308**, the image query system **206** utilizes the LLM prompt generator **318** again to generate a second LLM prompt **322** based on the additional natural language query **308** and the previously visual image grounding information **316**. Indeed, the image query system **206** reuses the same visual image grounding information previously generated by the visual-based large generative model **330**, which includes comprehensive information about the input image **304**. This way, the image query system **206** saves significant processing resources by not calling the visual-based large generative model **330** again.

(66) In some implementations, the second LLM prompt **322** is different from the first LLM prompt **320**. For example, the LLM prompt generator **318** generates the second LLM prompt **322** based on the additional natural language query **308** but with the same visual image grounding information (e.g., the previously visual image grounding information **316**). In particular, the second LLM prompt **322** prompts the large generative language model **340** to generate a text query response to answer the additional natural language query **308** given the visual image grounding information. For instance, the second LLM prompt **322** includes the prompt “Please answer the natural language query of additional natural language query using the provided grounding information.”

(67) Upon receiving the additional text query response **344** from the large generative language model **340**, the image query system **206** provides it to the user. The image query system **206** may continue to receive natural language queries regarding the input image **304** and repeat the workflow shown in FIG. **3B** to quickly and efficiently provide text query responses using the previously visual image grounding information **316** and without sending additional calls to the visual-based large generative model **330**.

(68) Turning to the next set of figures, FIGS. **4A-4B** expand on the concepts described in FIGS. **3A-3B** by introducing the use of reverse image search grounding information. In particular, FIG. **4A-4B** illustrate example workflow diagrams that show how to efficiently generate multiple text query responses using a large generative language model, a visual-based large generative model, and reverse image search grounding information according to some implementations.

(69) As shown, FIG. **4A** includes many of the components and elements introduced earlier in FIG. **3A**. For instance, FIG. **4A** includes the user input **302** having the input image **304** and the natural language query **306**; the visual-based large generative model **330**; the image query system **206** with the comprehensive image prompt **312**, the visual image grounding information **314**, and the LLM prompt generator **318**; the large generative language model **340**; and the text query response **342**. In addition, FIG. **4A** includes a reverse image search model **420** that provides reverse image search grounding information **422** to the image query system **206**.

(70) In one or more implementations, the image query system **206** uses the reverse image search model **420** to generate reverse image search grounding information **422** for the input image **304**. The reverse image search model **420** may utilize a variety of approaches (e.g., matching, feature extraction, indexing, ranking) to identify the input image **304** at external locations across different websites and/or external sources. The reverse image search model **420** may identify locations that include copies of the input image **304** (e.g., identical images) and/or similar images as the input image **304**. The reverse image search model **420** may weigh the influence of information obtained from sources based on how close the identified image is to the input image **304** as well as the credibility of the source.

(71) In various implementations, once the location of a matching or similar image is identified, the

reverse image search model **420** extracts content corresponding to the identified image. For example, the reverse image search model **420** extracts texts, metadata, captions, comments, other images, and/or videos from these locations to generate reverse image search grounding information. In some cases, the reverse image search model **420** scrapes a webpage or a website that includes an identified image. In some cases, the reverse image search model **420** extracts only a portion of the content from a corresponding location.

(72) For instance, if the input image **304** is of a recent event, the image may be included in various news articles, blogs, and forums. However, the reverse image search model **420** identifies news articles that include the image and/or similar images and obtains valuable and relevant grounding information about the image. Furthermore, if the same information is found at multiple locations or sources, the reverse image search model **420** may more confidently provide this information as the reverse image search grounding information **422**.

(73) As mentioned above, the image query system **206** may use the reverse image search model **420** to improve the accuracy of the text query response **342**. For example, in some implementations, the visual-based large generative model **330** uses the reverse image search grounding information **422** to generate an improved version of the visual image grounding information **314**. This is particularly useful when the input image **304** is unique (e.g., not frequently found online) or has been recently posted online.

(74) As shown, the image query system **206** provides the reverse image search grounding information **422** to the LLM prompt generator **318**. As before, the LLM prompt generator **318** generates the first LLM prompt **320** based on the natural language query **306** and grounding information. In the illustrated example, the grounding information includes both the visual image grounding information **314** and the reverse image search grounding information **422**.

(75) By providing the first LLM prompt **320** to the large generative language model **340**, the model generates the text query response **342** as described above. By using both versions of grounding information, the large generative language model **340** further improves the accuracy of the text query response **342**.

(76) In FIG. 3A, the reverse image search model **420** is shown to run in parallel with the visual-based large generative model **330**, and the LLM prompt generator **318** uses both types of grounding information to generate the first LLM prompt **320**. In some implementations, the reverse image search model **420** runs before the visual-based large generative model **330** and provides the reverse image search grounding information **422** to the visual-based large generative model **330**, as explained above. In general, the reverse image search model **420** is a computationally inexpensive model that quickly generates the reverse image search grounding information **422**.

(77) As explained earlier, the image query system **206** further improves processing efficiency when providing additional text query responses. To illustrate, FIG. 4B shows a workflow diagram of efficiently generating multiple text query responses using a large generative language model without using the visual-based large generative model or the reverse image search model **420** according to some implementations.

(78) FIG. 4B includes many of the same components and elements introduced above. For example, FIG. 4B includes the additional natural language query **308** in place of the input image **304** and the natural language query **306**, as introduced in FIG. 3B. Further, while the visual-based large generative model **330** and the reverse image search model **420** are shown, they are crossed out to emphasize their non-use for answering the additional natural language queries.

(79) As shown, the image query system **206** receives the additional natural language query **308**, which corresponds to the input image **304** provided to the image query system **206** with the previous natural language query. In many instances, the additional natural language query **308** is a follow-up question received upon providing the text query response **342** to a user within a search or chat service interface.

(80) Upon receiving the additional natural language query **308**, the image query system **206** utilizes

the LLM prompt generator **318** again to generate a second LLM prompt **322** based on the additional natural language query **308**, the previously visual image grounding information **316**, and the previously generated versions of the reverse image search grounding information **424**. The image query system **206** reuses the same visual image grounding information and reverse image search grounding information previously generated by the visual-based large generative model **330** and the reverse image search model **420**. As shown, the large generative language model **340** generates an additional text query response **344** based on the second LLM prompt **322**. Again, the image query system **206** saves significant processing resources by not calling the visual-based large generative model **330** or the reverse image search model **420** again.

(81) As described above, the image query system **206** may continue to receive natural language queries regarding the input image **304** and repeat the workflow shown in FIG. **4B** to quickly, efficiently, and accurately provide text query responses using the previously visual image grounding information **316** and the reverse image search grounding information **424** without sending additional calls to the visual-based large generative model **330** or the reverse image search model **420**.

(82) Turning to the next set of figures, FIGS. **5A-5B** provide an alternative approach for using the visual-based large generative model **330**, the reverse image search model **420**, and the large generative language model **340** to generate a text query response **342**. In particular, FIG. **5A-5B** illustrate example workflow diagrams for efficiently generating multiple text query responses using a large generative language model and reverse image search grounding information, and selectively using the visual-based large generative model, according to some implementations.

(83) While FIGS. **5A-5B** include many of the components and elements introduced above, the workflow performed by the image query system **206** differs from the workflows previously discussed. In particular, the workflow in FIGS. **5A-5B** correspond to determining when to selectively use the visual-based large generative model **330**. As described next, in FIG. **5A**, the image query system **206** determines not to call the visual-based large generative model **330**, thus saving a significant amount of bandwidth without sacrificing accuracy. In FIG. **5B**, the image query system **206** determines to call the visual-based large generative model **330** to ensure accurate results, as described further below.

(84) In FIG. **5A**, upon receiving the user input **302**, the image query system **206** provides the input image **304** to the reverse image search model **420** to generate the reverse image search grounding information **422** as previously described in connection with FIG. **4A**. In addition, the image query system **206** utilizes the LLM prompt generator **318** to generate the first LLM prompt **320** using the natural language query **306** and the reverse image search grounding information **422**. Unlike other workflows previously described, the LLM prompt generator **318** initially uses the grounding information from the reverse image search without using any visual image grounding information.

(85) As shown, the image query system **206** provides the first LLM prompt **320** to the large generative language model **340**, which generates an initial text query response **542**. In these instances, the large generative language model **240** answers the natural language query **306** using only the reverse image search grounding information **422** and the other resources available to the large generative language model **340**.

(86) The image query system **206** uses a response evaluator **510** to determine whether the initial text query response **542** meets or satisfies a threshold confidence value. In various implementations, the threshold confidence value indicates whether a text query response is sufficiently accurate to provide to a user or whether the text query response is inadequate. In various implementations, the threshold confidence value is quantitative. In some implementations, the threshold confidence value is qualitative.

(87) The response evaluator **510** may use various means to compare the initial text query response **542** to the threshold confidence value. For example, the large generative language model **340** may provide confidence values for each token (e.g., word) generated in the initial text query response

542. If the average token value is at or above the threshold confidence value of the response evaluator **510**, the image query system **206** determines to provide the initial text query response **542** to the user as the text query response **342**. Otherwise, the image query system **206** determines not to provide the initial text query response **542** to the user in response to the natural language query **306**.

(88) As another example, the response evaluator **510** uses a large generative model to determine whether the initial text query response **542** meets the threshold confidence value. For example, the response evaluator **510** generates a prompt that includes the natural language query **306** and the initial text query response **542** along with a query about how related or correlated the two inputs are. The large generative model then indicates whether the initial text query response **542** meets the threshold confidence value.

(89) As shown in FIG. 5A, the image query system **206** determines that the initial text query response **542** meets the threshold confidence value, indicating that the initial text query response **542** is sufficiently accurate (e.g., the “yes” option is circled). Accordingly, the image query system **206** determines to provide the initial text query response **542** to the user as the text query response **342**. In these implementations, the image query system **206** accurately answers the natural language query **306** without needing to call the visual-based large generative model **330**, as indicated in FIG. 5A by this component being crossed out, which saves significant processing and memory resources.

(90) In some implementations, the image query system **206** determines that the initial text query response **542** is inaccurate and does not meet the threshold confidence value. To illustrate, in FIG. 5B, the response evaluator **510** shows that the image query system **206** determined that the initial text query response **542** did not meet the threshold confidence value (e.g., the “no” option is circled). As a result, the image query system **206** may need to call the visual-based large generative model **330** to generate a more accurate text query response.

(91) Based on the initial text query response **542** not meeting the threshold confidence value, the image query system **206** generates an updated text query response based on additional grounding information. In particular, the image query system **206** determines to obtain visual image grounding information to generate the updated text query response with improved accuracy.

(92) To illustrate, as shown in FIG. 5B, the image query system **206** provides the input image **304** to the visual-based large generative model **330** to generate the visual image grounding information **314**. The image query system **206** then provides the LLM prompt generator **318**, the visual image grounding information **314**, and the reverse image search grounding information **422** to the LLM prompt generator **318**, which generates the second LLM prompt **322**.

(93) In addition, the image query system **206** provides the second LLM prompt **322**, which references the visual image grounding information **314** and the reverse image search grounding information **422**, to the large generative language model **340** to generate the text query response **342**. Furthermore, the image query system **206** provides the text query response **342** to the user in response to the natural language query **306**.

(94) As shown in FIG. 5B, in various implementations, the image query system **206** selectively calls the visual-based large generative model **330** only after determining that generating a text query response without visual image grounding information is inadequate. Thus, when the visual image grounding information is not needed, the image query system **206** provides the text query response **342** with significantly fewer computing resources. However, when visual image grounding information is needed to provide a sufficiently accurate text query response, the image query system **206** may appropriately call on the visual-based large generative model **330** to generate the visual image grounding information, as described above.

(95) In some implementations, the image query system **206** generates an LLM prompt that instructs the large generative language model **340** to determine a confidence score for a generated text query response. Additionally, the LLM prompt includes directions for the large generative language

model **340** to obtain visual image grounding information from the visual-based large generative model **330** when the confidence score for the text query response is below the threshold confidence value. For example, the LLM prompt includes “Can you confidently answer the natural language query with all the provided information?” and “If not, call the visual-based large generative model for visual image grounding information to accurately answer the natural language query.”

(96) FIG. **6** illustrates an example graphical user interface for interacting with the image query system to generate text query responses to image-based queries for an input image, according to some implementations. As illustrated, FIG. **6** includes a computing device **600** with a display showing a graphical user interface **602**. For example, the graphical user interface **602** is displayed as part of a client application that allows access to functions of the image query system **206**, such as via a content management system. Specifically, the graphical user interface **602** includes a client application **604** that enables an advanced chat service (e.g., a large generative model-based chat service) displayed on the computing device **600**. In some implementations, the client application **604** is a web browser, dedicated mobile application, or another type of application.

(97) The client application **604** shows the advanced chat service where a user can provide natural language queries and receive text responses. In addition, the user can provide an input image (or a link to an input image) and ask a question about the image. To illustrate, the client application **604** includes a user request with a natural language prompt **610** and an input image **612** corresponding to the prompt. In response, the image query system **206** provides a text query response **614** that accurately responds to the natural language prompt **610**. The image query system **206** provides the text query response **614** using grounding information and a large generative language model as described above.

(98) In addition, upon receiving the text query response **614**, the user may provide additional natural language queries about the input image **612**. In particular, without re-providing the input image **612**, the user submits natural language queries about the image. As described above, the image query system **206** uses the previously generated grounding information (e.g., the reverse image search grounding information and/or the visual image grounding information) to generate text query responses without needing to again call the reverse image search model and/or visual-based large generative model, respectively.

(99) Turning now to FIGS. **7A-7B**, these figures each illustrate an example flowchart that includes a series of acts for using the image query system. In particular, FIGS. **7A-7B** each illustrates an example series of acts for providing text query responses to image-based queries according to some implementations.

(100) While FIGS. **7A-7B** each illustrates acts according to one or more implementations, alternative implementations may omit, add to, reorder, and/or modify any of the acts shown. Furthermore, the acts of FIGS. **7A-7B** can each be performed as part of a method (e.g., a computer-implemented method). Alternatively, a computer-readable medium can include instructions that, when executed by a processing system having a processor, cause a computing device to perform each of the acts of FIGS. **7A-7B**. In some implementations, a system (e.g., a processing system having a processor and a computer memory including instructions that, when executed by the processing system, cause the system to perform various actions or steps) can perform each of the acts of FIGS. **7A-7B**.

(101) As shown in FIG. **7A**, the series of acts **700** includes act **710** of obtaining reverse image search grounding information for an input image. For instance, in example implementations, act **710** involves obtaining reverse image search grounding information for an input image based on receiving the input image and a natural language query corresponding to the input image.

(102) In some implementations, act **710** includes obtaining the reverse image search grounding information for the input image by generating an initial text response to the natural language query using the large generative language model based on the reverse image search grounding information, determining that the initial text response does not meet a threshold confidence value,

and providing the reverse image search grounding information and the comprehensive image prompt to the visual-based large generative model based on the initial text response not meeting the threshold confidence value (e.g., the initial text response did not meet the threshold confidence value).

(103) In some implementations, act **710** includes obtaining the reverse image search grounding information for the input image by providing the input image to a reverse image search model and receiving the reverse image search grounding information from the reverse image search model. In some instances, the reverse image search model includes context information and metadata information for the input image. In some implementations, act **710** includes obtaining the reverse image search grounding information for the input image based on identifying the input image within an external online source, extracting text content from the external online source, and generating the reverse image search grounding information from the text content. In some implementations, act **710** includes obtaining the reverse image search grounding information for the input image based on identifying images similar to the input image within an external online source, extracting text content from the external online source, and generating the reverse image search grounding information from the text content.

(104) As further shown in FIG. 7A, the series of acts **700** includes act **720** of providing a comprehensive image prompt and the input image to a visual-based large generative model. For instance, in some implementations, act **720** involves providing a comprehensive image prompt and the input image to a visual-based large generative model to generate visual image grounding information. In some implementations, act **720** includes obtaining reverse image search grounding information for the input image and providing the reverse image search grounding information to the visual-based large generative model along with the input image and the comprehensive image prompt.

(105) In some instances, the large generative language model also uses the reverse image search grounding information to generate the text response to the natural language query. In some implementations, act **720** includes receiving the input image and the natural language query from a computing device. In some instances, the comprehensive image prompt is different from the natural language query, and/or the comprehensive image prompt does not include content from the natural language query. In some instances, the comprehensive image prompt provides instructions to the visual-based large generative model to identify context information for the input image, and/or the same version of the comprehensive image prompt is provided to the visual-based large generative model for different input images.

(106) As further shown in FIG. 7A, the series of acts **700** includes act **730** of generating a response to the natural language query using a large generative language model based on the grounding information. For instance, in some implementations, act **730** involves generating a text response to the natural language query corresponding to the input image using a large generative language model based on the reverse image search grounding information and the visual image grounding information.

(107) In some implementations, act **730** includes generating a prompt to provide to the large generative language model that includes the natural language query, the reverse image search grounding information, the visual image grounding information, and instructions to answer the natural language query based on the provided grounding information. In some implementations, act **730** includes receiving the visual image grounding information from the visual-based large generative model in response to providing the comprehensive image prompt and the input image to the visual-based large generative model. In some instances, the large generative language model is less computationally expensive to execute than the visual-based large generative model.

(108) As further shown in FIG. 7A, the series of acts **700** includes act **740** of providing the response. For instance, in example implementations, act **740** involves providing the text response in response to the natural language query. In some implementations, act **740** includes receiving an

additional natural language query corresponding to the input image and generating an additional text response using the large generative language model without sending additional prompts to the visual-based large generative model. In some implementations, the large generative language model generates the additional text response using the additional natural language query, the visual image grounding information previously generated by the visual-based large generative model, and the reverse image search grounding information previously obtained.

(109) In some implementations, act **740** includes receiving an additional natural language query corresponding to the input image and generating an additional text response using the large generative language model without sending additional prompts to the visual-based large generative model. In some instances, the large generative language model generates the additional text response using the additional natural language query and the visual image grounding information previously generated by the visual-based large generative model. In some implementations, act **740** includes providing the text response to the computing device in response to the natural language query.

(110) In various implementations, the series of acts **700** includes fewer acts. For example, the series of acts includes providing the input image and a comprehensive image prompt to a visual-based large generative model based on receiving an input image and a natural language query corresponding to the input image, generating a text response to the natural language query corresponding to the input image using a large generative language model based on visual image grounding information from the visual-based large generative model, and providing the text response in response to the natural language query. In these instances, reverse image search grounding information may not be used, only the visual image grounding information, to generate the text response.

(111) As shown in FIG. 7B, the series of acts **750** includes act **760** of obtaining image grounding information for an input image. For instance, in some implementations, act **760** involves obtaining reverse image search grounding information for an input image based on receiving the input image and a natural language query corresponding to the input image.

(112) As further shown in FIG. 7B, the series of acts **750** includes act **770** of generating a response to an image query using a large generative language model based on the image grounding information. For instance, in some implementations, act **770** involves generating a text response to the natural language query using a large generative language model based on the reverse image search grounding information.

(113) As further shown in FIG. 7B, the series of acts **750** includes act **780** of determining that the response meets a threshold. For instance, in some implementations, act **780** involves determining that the text response meets a threshold confidence value.

(114) As further shown in FIG. 7B, the series of acts **750** includes act **790** of providing the response without prompting a visual-based large generative model. For instance, in some implementations, act **790** involves providing the text response in response to the natural language query without prompting a visual-based large generative model, based on the text response meeting the threshold confidence value.

(115) In some implementations, the series of acts **750** includes additional acts. For example, in one or more implementations, the series of acts **750** includes obtaining additional reverse image search grounding information for the additional input image based on receiving an additional input image and an additional natural language query corresponding to the additional input image, generating an additional text response to the additional natural language query using the large generative language model based on the additional reverse image search grounding information, determining that the additional text response does not meet the threshold confidence value, providing a comprehensive image prompt to the visual-based large generative model based on the text response not meeting the threshold confidence value, generating a new text response to the additional natural language query using the large generative language model based on the additional reverse image

search grounding information and visual image grounding information received from the visual-based large generative model, and/or providing the new text response in response to the additional natural language query. In some implementations, the series of acts **750** includes providing the reverse image search grounding information and the comprehensive image prompt to the visual-based large generative model based on the text response not meeting the threshold confidence value.

(116) FIG. **8** illustrates certain components that may be included within a computer system **800**. The computer system **800** may be used to implement the various computing devices, components, and systems described herein (e.g., by performing computer-implemented instructions). As used herein, a “computing device” refers to electronic components that perform a set of operations based on a set of programmed instructions. Computing devices include groups of electronic components, client devices, server devices, etc.

(117) In various implementations, the computer system **800** represents one or more of the client devices, server devices, or other computing devices described above. For example, the computer system **800** may refer to various types of network devices capable of accessing data on a network, a cloud computing system, or another system. For instance, a client device may refer to a mobile device such as a mobile telephone, a smartphone, a personal digital assistant (PDA), a tablet, a laptop, or a wearable computing device (e.g., a headset or smartwatch). A client device may also refer to a non-mobile device such as a desktop computer, a server node (e.g., from another cloud computing system), or another non-portable device.

(118) The computer system **800** includes a processing system including a processor **801**. The processor **801** may be a general-purpose single- or multi-chip microprocessor (e.g., an Advanced Reduced Instruction Set Computer (RISC) Machine (ARM)), a special-purpose microprocessor (e.g., a digital signal processor (DSP)), a microcontroller, a programmable gate array, etc. The processor **801** may be referred to as a central processing unit (CPU) and may cause computer-implemented instructions to be performed. Although the processor **801** shown is just a single processor in the computer system **800** of FIG. **8**, in an alternative configuration, a combination of processors (e.g., an ARM and DSP) could be used.

(119) The computer system **800** also includes memory **803** in electronic communication with the processor **801**. The memory **803** may be any electronic component capable of storing electronic information. For example, the memory **803** may be embodied as random-access memory (RAM), read-only memory (ROM), magnetic disk storage media, optical storage media, flash memory devices in RAM, on-board memory included with the processor, erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), registers, and so forth, including combinations thereof.

(120) The instructions **805** and the data **807** may be stored in the memory **803**. The instructions **805** may be executable by the processor **801** to implement some or all of the functionality disclosed herein. Executing the instructions **805** may involve the use of the data **807** that is stored in the memory **803**. Any of the various examples of modules and components described herein may be implemented, partially or wholly, as instructions **805** stored in memory **803** and executed by the processor **801**. Any of the various examples of data described herein may be among the data **807** that is stored in memory **803** and used during the execution of the instructions **805** by the processor **801**.

(121) A computer system **800** may also include one or more communication interface(s) **809** for communicating with other electronic devices. The one or more communication interface(s) **809** may be based on wired communication technology, wireless communication technology, or both. Some examples of the one or more communication interface(s) **809** include a Universal Serial Bus (USB), an Ethernet adapter, a wireless adapter that operates according to an Institute of Electrical and Electronics Engineers (IEEE) 802.11 wireless communication protocol, a Bluetooth® wireless communication adapter, and an infrared (IR) communication port.

(122) A computer system **800** may also include one or more input device(s) **811** and one or more output device(s) **813**. Some examples of the one or more input device(s) **811** include a keyboard, mouse, microphone, remote control device, button, joystick, trackball, touchpad, and light pen. Some examples of the one or more output device(s) **813** include a speaker and a printer. A specific type of output device that is typically included in a computer system **800** is a display device **815**. The display device **815** used with implementations disclosed herein may utilize any suitable image projection technology, such as liquid crystal display (LCD), light-emitting diode (LED), gas plasma, electroluminescence, or the like. A display controller **817** may also be provided, for converting data **807** stored in the memory **803** into text, graphics, and/or moving images (as appropriate) shown on the display device **815**.

(123) The various components of the computer system **800** may be coupled together by one or more buses, which may include a power bus, a control signal bus, a status signal bus, a data bus, etc. For clarity, the various buses are illustrated in FIG. **8** as a bus system **819**.

(124) This disclosure describes a subjective data application system in the framework of a network. In this disclosure, a “network” refers to one or more data links that enable electronic data transport between computer systems, modules, and other electronic devices. A network may include public networks such as the Internet as well as private networks. When information is transferred or provided over a network or another communication connection (either hardwired, wireless, or both), the computer correctly views the connection as a transmission medium. Transmission media can include a network and/or data links that carry required program code in the form of computer-executable instructions or data structures, which can be accessed by a general-purpose or special-purpose computer.

(125) In addition, the network described herein may represent a network or a combination of networks (such as the Internet, a corporate intranet, a virtual private network (VPN), a local area network (LAN), a wireless local area network (WLAN), a cellular network, a wide area network (WAN), a metropolitan area network (MAN), or a combination of two or more such networks) over which one or more computing devices may access the various systems described in this disclosure. Indeed, the networks described herein may include one or multiple networks that use one or more communication platforms or technologies for transmitting data. For example, a network may include the Internet or other data link that enables transporting electronic data between respective client devices and components (e.g., server devices and/or virtual machines thereon) of the cloud computing system.

(126) Further, upon reaching various computer system components, program code means in the form of computer-executable instructions or data structures can be transferred automatically from transmission media to non-transitory computer-readable storage media (devices), or vice versa. For example, computer-executable instructions or data structures received over a network or data link can be buffered in random-access memory (RAM) within a network interface module (NIC), and then it is eventually transferred to computer system RAM and/or to less volatile computer storage media (devices) at a computer system. Thus, it should be understood that computer-readable storage media (devices) can be included in computer system components that also (or even primarily) utilize transmission media.

(127) Computer-executable instructions include instructions and data that, when executed by a processor, cause a general-purpose computer, special-purpose computer, or special-purpose processing device to perform a certain function or group of functions. In some implementations, computer-executable and/or computer-implemented instructions are executed by a general-purpose computer to turn the general-purpose computer into a special-purpose computer implementing elements of the disclosure. The computer-executable instructions may include, for example, binaries, intermediate format instructions such as assembly language, or even source code. Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is

not necessarily limited to the described features or acts described above. Rather, the described features and acts are disclosed as example forms of implementing the claims.

(128) Those skilled in the art will appreciate that the disclosure may be practiced in network computing environments with many types of computer system configurations, including, personal computers, desktop computers, laptop computers, message processors, hand-held devices, multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, mobile telephones, PDAs, tablets, pagers, routers, switches, and the like. The disclosure may also be practiced in distributed system environments where local and remote computer systems, which are linked (either by hardwired data links, wireless data links, or a combination of hardwired and wireless data links) through a network, both perform tasks. In a distributed system environment, program modules may be located in both local and remote memory storage devices.

(129) The techniques described herein may be implemented in hardware, software, firmware, or any combination thereof unless specifically described as being implemented in a specific manner. Any features described as modules, components, or the like may also be implemented together in an integrated logic device or separately as discrete but interoperable logic devices. If implemented in software, the techniques may be realized at least in part by a non-transitory processor-readable storage medium, including instructions that, when executed by at least one processor, perform one or more of the methods described herein (including computer-implemented methods). The instructions may be organized into routines, programs, objects, components, data structures, etc., which may perform particular tasks and/or implement particular data types, and which may be combined or distributed as desired in various implementations.

(130) Computer-readable media can be any available media that can be accessed by a general-purpose or special-purpose computer system. Computer-readable media that store computer-executable instructions are non-transitory computer-readable storage media (devices). Computer-readable media that carry computer-executable instructions are transmission media. Thus, by way of example, implementations of the disclosure can include at least two distinctly different kinds of computer-readable media: non-transitory computer-readable storage media (devices) and transmission media.

(131) As used herein, computer-readable storage media (devices) may include RAM, ROM, EEPROM, CD-ROM, solid-state drives (SSDs) (e.g., based on RAM), Flash memory, phase-change memory (PCM), other types of memory, other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store desired program code means in the form of computer-executable instructions or data structures and which can be accessed by a general-purpose or special-purpose computer.

(132) The steps and/or actions of the methods described herein may be interchanged with one another without departing from the scope of the claims. In other words, unless a specific order of steps or actions is required for the proper operation of the method that is being described, the order and/or use of specific steps and/or actions may be modified without departing from the scope of the claims.

(133) The term “determining” encompasses a wide variety of actions and, therefore, “determining” can include calculating, computing, processing, deriving, investigating, looking up (e.g., looking up in a table, a data repository, or another data structure), ascertaining, and the like. Also, “determining” can include receiving (e.g., receiving information), accessing (e.g., accessing data in a memory), and the like. Also, “determining” can include resolving, selecting, choosing, establishing, and the like.

(134) The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to “one implementation” or “implementations” of the present disclosure are not intended to be interpreted as excluding the existence of additional implementations that also

incorporate the recited features. For example, any element or feature described concerning an implementation herein may be combinable with any element or feature of any other implementation described herein, where compatible.

(135) The present disclosure may be embodied in other specific forms without departing from its spirit or characteristics. The described implementations are to be considered illustrative and not restrictive. The scope of the disclosure is indicated by the appended claims rather than by the foregoing description. Changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A computer-implemented method for providing text responses to image-based queries: based on receiving an input image and a natural language query corresponding to the input image, obtaining reverse image search grounding information for the input image; providing a comprehensive image prompt and the input image to a visual-based large generative model to generate visual image grounding information; generating a text response to the natural language query corresponding to the input image using a large generative language model based at least in part on the reverse image search grounding information and the visual image grounding information; and providing the text response in response to the natural language query.
2. The computer-implemented method of claim 1, further comprising: receiving an additional natural language query corresponding to the input image; and generating an additional text response using the large generative language model without sending additional prompts to the visual-based large generative model.
3. The computer-implemented method of claim 2, wherein the large generative language model generates the additional text response using the additional natural language query, the visual image grounding information previously generated by the visual-based large generative model, and the reverse image search grounding information previously obtained.
4. The computer-implemented method of claim 1, wherein: the comprehensive image prompt is different from the natural language query; and the comprehensive image prompt does not include content from the natural language query.
5. The computer-implemented method of claim 1, wherein: the comprehensive image prompt provides instructions to the visual-based large generative model to identify context information for the input image; and a same version of the comprehensive image prompt is provided to the visual-based large generative model for different input images.
6. The computer-implemented method of claim 1, further comprising generating a prompt to provide to the large generative language model that includes the natural language query, the reverse image search grounding information, the visual image grounding information, and instructions to answer the natural language query based on provided grounding information.
7. The computer-implemented method of claim 1, further comprising obtaining the reverse image search grounding information for the input image by: generating an initial text response to the natural language query using the large generative language model based on the reverse image search grounding information; determining the initial text response does not meet a threshold confidence value; and based on the initial text response not meeting the threshold confidence value, providing the reverse image search grounding information and the comprehensive image prompt to the visual-based large generative model.
8. The computer-implemented method of claim 1, further comprising obtaining the reverse image search grounding information for the input image by: providing the input image to a reverse image search model; and receiving the reverse image search grounding information from the reverse image search model, wherein the reverse image search model includes context information and metadata information for the input image.

9. The computer-implemented method of claim 1, further comprising obtaining the reverse image search grounding information for the input image based on: identifying the input image within an external online source; extracting text content from the external online source; and generating the reverse image search grounding information from the text content.
10. The computer-implemented method of claim 1, further comprising obtaining the reverse image search grounding information for the input image based on: identifying images similar to the input image within an external online source; extracting text content from the external online source; and generating the reverse image search grounding information from the text content.
11. A system for providing text responses to image-based queries, the system comprising: a processing system; and a computer memory comprising instructions that, when executed by the processing system, cause the system to perform operations of: based on receiving an input image and a natural language query corresponding to the input image, providing the input image and a comprehensive image prompt to a visual-based large generative model; generating a text response to the natural language query corresponding to the input image using a large generative language model based on visual image grounding information from the visual-based large generative model; and providing the text response in response to the natural language query.
12. The system of claim 11, further comprising: receiving an additional natural language query corresponding to the input image; and generating an additional text response using the large generative language model without sending additional prompts to the visual-based large generative model.
13. The system of claim 12, wherein the large generative language model generates the additional text response using the additional natural language query and the visual image grounding information previously generated by the visual-based large generative model.
14. The system of claim 11, further comprising: obtaining reverse image search grounding information for the input image; and providing the reverse image search grounding information to the visual-based large generative model along with the input image and the comprehensive image prompt, wherein the large generative language model also uses the reverse image search grounding information to generate the text response to the natural language query.
15. The system of claim 11, wherein: the comprehensive image prompt providing instructions to the visual-based large generative model to identify context information for the input image; and the comprehensive image prompt does not include content from the natural language query.
16. The system of claim 11, further comprising: receiving the visual image grounding information from the visual-based large generative model in response to providing the comprehensive image prompt and the input image to the visual-based large generative model, wherein the large generative language model is less computationally expensive to execute than the visual-based large generative model.
17. The system of claim 11, further comprising: receiving the input image and the natural language query from a computing device; and providing the text response to the computing device in response to the natural language query.
18. A computer-implemented method for providing text responses to image-based queries: based on receiving an input image and a natural language query corresponding to the input image, obtaining reverse image search grounding information for the input image; generating a text response to the natural language query using a large generative language model based on the reverse image search grounding information; determining the text response meets a threshold confidence value; and based on the text response meeting the threshold confidence value, providing the text response in response to the natural language query without prompting a visual-based large generative model.
19. The computer-implemented method of claim 18, further comprising: based on receiving an additional input image and an additional natural language query corresponding to the additional input image, obtaining additional reverse image search grounding information for the additional input image; generating an additional text response to the additional natural language query using

the large generative language model based on the additional reverse image search grounding information; determining the additional text response does not meet the threshold confidence value; based on the text response not meeting the threshold confidence value, providing a comprehensive image prompt to the visual-based large generative model; generating a new text response to the additional natural language query using the large generative language model based on the additional reverse image search grounding information and visual image grounding information received from the visual-based large generative model; and providing the new text response in response to the additional natural language query.

20. The computer-implemented method of claim 19, further comprising providing the reverse image search grounding information and the comprehensive image prompt to the visual-based large generative model based on the text response not meeting the threshold confidence value.
