

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398692
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Fukagawa; Tateru et al.

Aquatic wind power generation system

Abstract

An aquatic wind power generation system includes: a hull that navigates on water; a power generation system that includes a kite connected to the hull via a tether, and repeats between a power generation mode, in which wind power is generated by an unwinding operation of the tether due to flight of the kite, and retraction mode, in which the tether is retracted by a winding operation of the tether; and a controller that performs control to direct a bow of the hull in a leeward direction in the retraction mode.

Inventors: Fukagawa; Tateru (Fujisawa, JP), Masuki; Hayato (Fuji, JP), Kimura; Kazutaka (Mishima, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Family ID: 1000008780728

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Appl. No.: 18/439868

Filed: February 13, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240337243 A1	Oct. 10, 2024

Foreign Application Priority Data

JP	2023-061556	Apr. 05, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: F03D5/00 (20060101); B63B35/44 (20060101); B63H25/04 (20060101); F03D13/25 (20160101)

U.S. Cl.:

CPC F03D5/015 (20230801); B63B35/44 (20130101); B63H25/04 (20130101); F03D13/256 (20230801); B63B2035/446 (20130101); F05B2240/9176 (20200801)

Field of Classification Search

CPC: F03D (5/015); F03D (13/256); F03D (5/00); F03D (9/32); B63B (35/44); B63B (2035/446); B63H (25/04); B63H (9/00); F05B (2240/9176)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9416770	12/2015	Paulig et al.	N/A	N/A
2008/0210826	12/2007	Ockels et al.	N/A	N/A
2011/0272527	12/2010	Larson	N/A	N/A
2022/0389904	12/2021	Reiners	N/A	F03D 5/06

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
211116407	12/2019	CN	N/A
2014-184936	12/2013	JP	N/A
2021/094987	12/2020	WO	N/A

Primary Examiner: Ortega; Joseph

Attorney, Agent or Firm: Oliff PLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to Japanese Patent Application No. 2023-061556 filed on Apr. 5, 2023, incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

(2) The disclosure relates to an aquatic wind power generation system.

2. Description of Related Art

(3) WO2021/094987 discloses a marine wind power generation system that generates wind power by flying a kite using an engine from a floating structure on the sea, such as a hull equipped with a propulsion device. The marine wind power generation system alternates between a power generation mode, in which wind power is generated by unwinding a tether connected to a kite, and a retraction mode, in which the tether is retracted by winding the tether.

SUMMARY

(4) In the above marine wind power generation system that alternates between the power

generation mode and the retraction mode, when the kite is retracted against the wind direction during the retraction mode, the energy required to wind the tether increases. This leads to decreased cost efficiency, indicating room for improvement.

(5) Considering the above facts, it is an object of the disclosure to provide an aquatic wind power generation system capable of improving the overall power generation efficiency.

(6) An aquatic wind power generation system according to a first aspect of the disclosure includes: a hull that navigates on water; a power generation system that includes a kite connected to the hull via a tether, and alternates between a power generation mode, in which wind power is generated by the unwinding operation of the tether due to the flight of the kite, and a retraction mode, in which the tether is retracted by the winding operation of the tether, and a controller that performs control to direct the bow of the hull in a leeward direction in the retraction mode.

(7) The aquatic wind power generation system according to the first aspect of the disclosure alternates between the power generation mode, in which wind power is generated by the unwinding operation of the tether due to the flight of the kite, and a retraction mode, in which the tether is retracted by the winding operation of the tether, and performs control to direct the bow of the hull in the leeward direction in the retraction mode. Thus, the bow of the hull faces the leeward direction when the tether is retracted, and hence the relative wind velocity with respect to the kite can be reduced. This allows for a reduction in the energy consumption required for the winding operation of the tether, thereby improving the overall power generation efficiency.

(8) In an aquatic wind power generation system according to a second aspect of the disclosure, in the configuration according to the first aspect, in the retraction mode, when the advancing direction of the hull is angled with respect to the wind direction of natural wind, the controller controls the advancing velocity of the hull so that a relative velocity with respect to the hull is orthogonal to the advancing velocity of the hull, the relative velocity being a composite velocity of the advancing velocity of the hull and a wind velocity of the natural wind. Note that the term “orthogonal” here includes a slight allowable range in addition to being completely orthogonal.

(9) In the aquatic wind power generation system according to the second aspect of the disclosure, when the advancing direction of the hull is angled with respect to the wind direction of the natural wind, the advancing velocity of the hull is controlled so that the relative velocity with respect to the hull is orthogonal to the advancing velocity of the hull, thus enabling the relative velocity with respect to the hull to reach the minimum velocity. Therefore, by the relative velocity with respect to the hull reaching the minimum velocity, the relative wind velocity with respect to the kite can be minimized, and the energy consumption required for the winding operation of the tether can also be minimized. Accordingly, it is possible to further improve the overall power generation efficiency.

(10) In an aquatic wind power generation system according to a third aspect of the disclosure, in the configuration according to the first aspect, in the retraction mode, the controller controls the direction of the bow so that the vector direction of the tension of the kite matches an advancing direction of the hull when viewed from above the hull. Note that the term “match” here includes a slight allowable range in addition to a perfect match.

(11) In the aquatic wind power generation system according to the third aspect of the disclosure, when the tether is retracted, the hull advances in the vector direction of the tension of the kite, and hence the relative wind velocity with respect to the kite can be efficiently reduced. This also allows for an efficient reduction in the energy consumption required for the winding operation of the tether, thereby efficiently improving the overall power generation efficiency.

(12) In an aquatic wind power generation system according to a fourth aspect of the disclosure, in the configuration according to any one of the first to third aspects, in the power generation mode, the controller performs control to direct the bow of the hull to the windward direction.

(13) In the aquatic wind power generation system according to the fourth aspect of the disclosure, when wind power is generated by the kite, since the bow of the hull faces the windward direction, the hull moves against the natural wind. This allows for an increase in the relative wind velocity

with respect to the kite, leading to a faster unwinding speed of the tether and thus an increase in power output.

(14) In an aquatic wind power generation system according to a fifth aspect of the disclosure, in the configuration according to the fourth aspect, in the power generation mode, the controller controls the direction of the bow so that the wind direction of natural wind and an advancing direction of the hull are orthogonal to each other when viewed from above the hull. Note that the term “orthogonal” here includes a slight allowable range in addition to being completely orthogonal.

(15) In the aquatic wind power generation system according to the fifth aspect of the disclosure, by making the advancing direction of the hull orthogonal to the wind direction of the natural wind, the advancing direction of the hull can be set to a direction abeam to the wind, resulting in a faster advancing velocity of the hull. This increases the propulsive force of the hull, thereby increasing the lateral force applied to the hull and enabling a reduction in the tension of the kite. Therefore, it is possible to efficiently increase the relative velocity with respect to the kite, leading to a faster unwinding speed of the tether and thus an increase in power output.

(16) As described above, the aquatic wind power generation system according to the disclosure has an excellent effect in enabling an improvement in overall power generation efficiency.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Features, advantages, and technical and industrial significance of exemplary embodiments of the disclosure will be described below with reference to the accompanying drawings, in which like signs denote like elements, and wherein:

(2) FIG. 1 is a schematic configuration diagram schematically illustrating a configuration of an aquatic wind power generation system according to a first embodiment of the disclosure;

(3) FIG. 2 is a route chart illustrating a movement trajectory of a hull when the hull moves leeward;

(4) FIG. 3 is a diagram illustrating in three dimensions a line of maximum flight range within which the kite can fly;

(5) FIG. 4 is a diagram illustrating in two dimensions a line of maximum flight range within which the kite can fly;

(6) FIG. 5 is a plan view illustrating the relationship between a wind direction and a force applied to a hull in a power generation mode;

(7) FIG. 6 is a diagram illustrating the relationship among a relative wind velocity with respect to the hull, an advancing velocity, and a wind velocity;

(8) FIG. 7 is a plan view illustrating in coordinates the relationship between the relative wind velocity and a propulsive force with respect to a sail angle;

(9) FIG. 8 is a graph illustrating the relationship between a relative angle between an X₀ axis and the relative wind velocity, and an aerodynamic coefficient for each sail angle;

(10) FIG. 9 is a plan view illustrating the relationship between the wind direction and the force applied to the hull in a retraction mode;

(11) FIG. 10 is a diagram illustrating the relationship among the relative wind velocity with respect to the hull, the advancing velocity, and the wind velocity;

(12) FIG. 11 is a route chart illustrating a movement trajectory of the hull when the hull moves while maintaining its position;

(13) FIG. 12 is a route chart illustrating a movement trajectory of the hull when the hull moves windward; and

(14) FIG. 13 is a route chart illustrating a movement trajectory of the hull when the hull moves laterally to the natural wind.

DETAILED DESCRIPTION OF EMBODIMENTS

(15) An aquatic wind power generation system **10** according to an embodiment of the disclosure will be described below with reference to FIGS. **1** to **13**. An arrow UP and an arrow FR, shown as appropriate in the drawings, indicate the upper side of a hull-height direction and the front of a hull front-rear direction, respectively. An arrow W indicates a hull-width direction. In the drawings, only some of the reference numerals are shown and the others are omitted to prioritize the clarity of the drawings.

(16) As illustrated in FIG. **1**, an aquatic wind power generation system **10** is equipped with: a sailboat **12** including a hull **16** that is operated on a sea, lake, river, or the like; a power generation system **20** that generates electric power; and a control device **30** that controls the steering of the sailboat **12**, the drive of the power generation system **20**, and the like. Although not illustrated, the control device **30** serving as a controller includes various electric devices (electric components), a control unit, and the like. The control unit includes a central processing unit (CPU: processor), a read-only memory (ROM), a random-access memory (RAM), a storage device, a communication interface (communication I/F), and an input-output interface (input-output I/F). A generator **22A** and the like, which will be described later, are connected to the input-output I/F.

(17) Configuration of Power Generation System **20**

(18) The power generation system **20** includes, for example, a power generation device **22** disposed on the hull **16**, and a kite **26** connected to the hull **16** via a tether **24**. The kite **26** is composed of a kite body and is moored on the hull **16** by a tether **24**.

(19) The power generation device **22** includes a generator **22A** and a winch **22B**. To the rotating shaft of the generator **22A**, a rotating shaft body **22C** is connected, and the generator **22A** rotates the rotating shaft body **22C** based on a command from the control device **30**. The winch **22B** has the rotating shaft body **22C** as its rotating shaft, and the tether **24** is wound around the rotating shaft body **22C**. In the power generation device **22**, the rotating shaft body **22C** is rotated clockwise or counterclockwise to unwind the tether **24** from the winch **22B** or wind the tether **24** onto the winch **22B**.

(20) In the power generation system **20**, in a case where the kite **26** ascends, the tether **24** is unwound from the winch **22B** as the kite **26** ascends. The rotating shaft body **22C** is rotated by the unwinding operation of the tether **24**, and the rotating shaft of the generator **22A** is rotated in conjunction with the rotation of the rotating shaft body **22C**, thereby generating electric power. A power output Q due to the rise of the kite **26** is a value obtained by multiplying the tension of the tether **24** by the unwinding speed of the tether **24**.

(21) After the tether **24** is unwound to a predetermined length or after a predetermined time has elapsed, the rotating shaft body **22C** is rotated in the opposite direction, that is, in the direction to wind the tether **24**, by a motor **23**, for example, via the generator **22A** based on a command from the control device **30**. Thereby, the tether **24** is wound, and the kite **26** thus descends.

(22) As illustrated in FIG. **2**, the power generation system **20** alternates and repeats between a power generation mode A, in which wind power is generated by the unwinding operation of the tether **24** due to the flight of the kite **26**, and a retraction mode B, in which the tether **24** is retracted by the winding operation of the tether **24**. In the present embodiment, in the power generation system **20**, the time required for the power generation mode A is set to be longer than the time required for the retraction mode B. Further, the power output Q in the power generation mode A is set to be larger than the amount of electric power consumed by the retraction mode B. As illustrated in FIG. **2**, in the power generation system **20**, the wind power generation in the power generation mode A and the retraction of the tether **24** in the retraction mode B are performed while the sailboat **12** is caused to execute movement F to increase the power generation efficiency. Note that the movement F will be described in detail later.

(23) Configuration of Sailboat **12**

(24) As illustrated in FIG. **1**, the sailboat **12** includes the hull **16** equipped with the sail **14**. The hull **16** is a body of a floating structure configured to float on a water surface S of the sea, lake, river, or

the like, and generates buoyancy, which is an upward force equal to the weight of the water displaced by the bottom of the hull **16** positioned in the water. The hull **16** includes a rudder **18** serving as a steering device. The hull **16** also includes, at the its bottom positioned below the water surface S, a lateral force generating portion **40** that generates a lateral force, which will be described later.

(25) The sail **14** is made of a membrane material, and is composed of a soft sail formed using an elastic material that inflates with wind. In the present embodiment, the sail **14** has been composed of a soft sail as an example, but the disclosure is not limited thereto, and may be composed of a hard sail formed using a hard material with an airfoil shape, for example. The number of sails **14** is not limited to one, and a plurality of sails **14** may be provided.

(26) The sail **14** is fixed to the hull **16** via a mast **15**, and the base portion of the mast **15** is made rotatable with respect to the hull **16**. By rotating the base portion of the mast **15** with respect to the hull **16**, a sail angle as to be described later can be set to any angle. The mast **15** is driven and controlled by the control device **30** described above. When the mast **15** is configured for manual operation, the control device **30** informs a user of the required amount of rotation or the like to set the sail angle as to the desired angle, and the like, using informing means (not illustrated) such as a display or a vocal sound. In the present embodiment, as an example, the sail angle as is changed by rotating the base portion of the mast **15** with respect to the hull **16**. However, the disclosure is not limited thereto, and the manner of changing the sail angle as can be varied as appropriate.

(27) As illustrated in FIG. **1**, the rudder **18** has a flat surface and is provided on the rear side of the bottom surface of the hull **16** to control the direction of a bow **16A** of the hull **16**. Specifically, the rudder **18** is configured to be rotatable, and rotates to change the direction of the flow in the water, and the direction of the bow **16A** changes due to the change in the flow in the water. The rudder **18** is drive-controlled by the control device **30** described above. When the rudder **18** is configured for manual operation, the control device **30** informs of the required amount of movement to move the bow **16A** of the hull **16** in the desired direction, and the like, using the informing means (not illustrated).

(28) Note that the method for controlling the direction of the bow **16A** of the hull **16** is not limited to using the rudder **18**, and it is possible to use a known technique such as a thruster (propulsion device) that generates a moment in the direction of the bow **16A**.

(29) As illustrated in FIG. **1**, the lateral force generating portion **40** is provided on the bottom surface of the hull **16**. In the present embodiment, the lateral force generating portion **40** includes a board **42** as a plate material fixed to extend in the front-rear direction at the center of the width of the hull **16**. The board **42** generates a lateral force F_b to be described later in a direction substantially orthogonal to the advancing direction of the hull **16**.

(30) As described above, in the power generation system **20**, the wind power generation in the power generation mode A and the retraction of the tether **24** in the retraction mode B are performed while the sailboat **12** is caused to execute the movement F to increase the power generation efficiency.

(31) Leeward Movement Pattern

(32) Here, a leeward movement pattern will be described, where electric power is generated while the sailboat **12** as a whole is caused to execute the movement F in the leeward direction. As illustrated in FIG. **2**, in the power generation mode A, the control device **30** moves the hull **16** in a direction that crosses a wind direction WD of the natural wind, that is, a direction abeam to the wind, and in the retraction mode B, the control device **30** moves the hull **16** in a direction substantially the same as the wind direction WD.

(33) Power Generation Mode A

(34) Generally, the kite **26** has its flyable range for generating electric power. As illustrated in FIG. **3**, in the present embodiment, the flyable range is represented by an angle ψ formed between a wind axis W and the tether **24** (cf. FIGS. **1** and **4**). The angle ψ is an angle with respect to the

average position of the tether **24** during the flight of the kite **26** in the wind power generation mode A. In FIG. 3, an arc denoted by K indicates a flight trajectory of the kite **26**, and a range shown in color indicates the flyable range. Note that the flyable range, that is, the value of the angle ψ , depends on the inherent performance of the kite **26**.

(35) As illustrated in FIG. 4, when the flyable range shown in color in FIG. 3 is projected onto an azimuth plane, the maximum flight azimuth is the azimuth at which the kite **26** can be caused to fly closest to the direction of the bow **16A** of the hull **16**, that is, the azimuth at the position of the tether **24** illustrated in FIG. 4. In the present embodiment, in the power generation mode A, the control device **30** maintains the position of the kite **26** so that the tether **24** is positioned in the maximum flight azimuth direction. However, the control device **30** causes the kite **26** to fly with a margin within the flyable range because the kite **26** may unintentionally be positioned outside the flyable range. That is, the control device **30** causes the kite **26** to fly in such a manner that the tether **24** is positioned slightly inward of the maximum flight azimuth direction within the flyable range.

(36) Movement Direction of Hull **16**

(37) As illustrated in FIG. 5, in the power generation mode A, the sail **14** generates propulsive force by utilizing the wind force of the natural wind. In FIGS. 5 and 6, the direction of the vector represents the wind direction, and the magnitude of the vector represents the velocity. As illustrated in FIG. 6, a relative velocity V_w with respect to the hull **16**, indicated by the single-dotted line, is expressed as a composite velocity of a wind velocity V_{wd} of the natural wind, indicated by the solid line, and an advancing velocity V of the hull **16**, indicated by the dotted line. The relative velocity V_w is detected by a wind direction and velocity sensor (not illustrated) mounted on the hull **16**. Specifically, the wind direction and velocity sensor detects a relative angle γ_w , which is the wind direction relative to the hull **16**, and the relative velocity V_w .

(38) As illustrated in FIG. 5, a propulsive force P_s due to the sail **14** changes with a change in the sail angle α_s , which is an angle of attack between the sail **14** and the relative velocity V_w . The propulsive force P_s increases as the sail angle α_s increases, and the movement velocity of the sailboat **12** increases as the propulsive force P_s increases.

(39) Further, the lateral force F_b is generated on the hull **16** by the board **42** in a direction substantially orthogonal to the advancing direction of the hull **16**. The control device **30** generates the lateral force F_b in a direction to cancel tension T caused by the kite **26**. In the present embodiment, as an example, the control device **30** changes a rudder angle α_r so that the lateral force F_b acts in a direction opposite to the tension T caused by the kite **26**. Note that the means for generating the lateral force F_b is not limited thereto, and for example, a known technique such as making the board **42** movable can be used.

(40) The lateral force F_b generated by the board **42** increases as the movement velocity of the hull **16** increases. In other words, the lateral force F_b increases as the propulsive force P_s increases. In the present embodiment, the control device **30** controls the sail angle α_s to maximize the propulsive force P_s . Here, the sail angle α_s at which the maximum propulsive force P_s can be obtained will be described.

(41) When the coordinates are defined as illustrated in FIG. 7, a lift force L_s and a drag force D_s change with a change in the sail angle α_s , which is an angle of attack between the sail **14** and the relative velocity V_w . The lift force L_s is generated in a direction orthogonal to the relative velocity V_w , and the drag force D_s is generated in the same direction as the relative velocity V_w . Here, the values of the lift force L_s and the drag force D_s with respect to the sail angle α_s are inherent characteristics of each sailboat **12**. Accordingly, the values of the lift force L_s and the drag force D_s with respect to the sail angle α_s are obtained in advance through wind tunnel tests and computational fluid dynamics (CFD) for fluid analysis.

(42) The propulsive force P_s with respect to the relative angle γ_w of an X_o axis and the relative velocity V_w is illustrated in the graph of FIG. 8 for each sail angle α_s . In FIG. 8, an aerodynamic coefficient C_x is a dimensionless coefficient of the propulsive force P_s in the X_o axis direction of

the hull **16**. As illustrated in FIG. **8**, in a case where the relative angle γ_w is 140° or less, the propulsive force P_s reaches its maximum when the sail angle α_s , at which the lift force L_s is at its maximum, is 15° . In a case where the relative angle γ_w exceeds 140° , the propulsive force P_s reaches its maximum when the sail angle α_s , at which the drag force D_s is at its maximum, is 90° . Note that the threshold value of 140° for the relative angle γ_w and the maximum sail angle α_s may vary depending on the shape of the sail **14**, but generally become values around the values described above.

(43) Retraction Mode B

(44) Movement Direction of Hull **16**

(45) As illustrated in FIGS. **2** and **9**, in the retraction mode B, the hull **16** is moved in a direction substantially the same as the wind direction WD. Specifically, the control device **30** performs control to direct the bow **16A** of the hull **16** in the leeward direction by rotating the rudder **18** to change the rudder angle α_r .

(46) As illustrated in FIG. **9**, in the present embodiment, since an advancing direction D of the hull **16** is a direction substantially the same as the wind velocity V_{wd} direction of the natural wind, the vector direction of the advancing velocity V of the hull **16** is also a direction substantially the same as the wind velocity V_{wd} direction. When the wind velocity V_{wd} is constant, the relative velocity V_w of the hull **16** is changed according to the advancing velocity V. That is, as the advancing velocity V increases, the relative velocity V_w decreases, and hence the control device **30** controls the sail angle α_s so that the propulsive force P_s becomes smaller. Specifically, since the relative angle γ_w is 180° , the control device **30** controls the sail angle α_s so that the sail angle α_s is 90° with reference to the graph of FIG. **8**.

(47) As illustrated in FIG. **9**, the control device **30** causes the kite **26** to fly so that the tether **24** is in a direction substantially the same as the wind velocity V_{wd} direction when viewed from above the hull **16**. Note that the control device **30** winds the tether **24** at an appropriate winding speed V_t that maximizes the average power output.

(48) In the above leeward movement pattern, the movement direction has been set as described above because the advancing direction D of the hull **16** is the same direction as the wind velocity V_{wd} direction of the natural wind. However, as illustrated in FIG. **10**, in a case where the advancing direction D of the hull **16** is angled with respect to the wind velocity V_{wd} of the natural wind, there exists an advancing velocity V of the hull **16** that minimizes the relative velocity V_w of the hull **16** when the hull **16** is navigated in the leeward direction. This is a case specifically when the vector of the advancing velocity V of the hull **16** and the vector of the relative velocity V_w are orthogonal to each other. Next, the movement pattern of the hull **16** when the advancing direction D of the hull **16** is angled with respect to the wind velocity V_{wd} of the natural wind will be described.

(49) In the following pattern, in both the power generation mode A and the retraction mode B, the azimuth and the sail angle α_s of the tether **24** of the kite **26** are the same as those in the leeward movement pattern described above. The azimuth for the advancement of the hull **16** in the windward or leeward direction is determined in view of the need for the movement, considering the maximum wind velocity of the natural wind with respect to the azimuth and the performance such as the power output.

(50) Position Maintaining Movement Pattern

(51) As illustrated in FIG. **11**, when wind power generation is conducted while the hull **16** stays within a predetermined range, the advancing direction of the hull **16** in the power generation mode A is opposite to the advancing direction of the hull **16** in the retraction mode B.

(52) Windward Movement Pattern

(53) As illustrated in FIG. **12**, when wind power generation is conducted while the hull **16** as a whole moves in the leeward direction, the hull **16** is moved so that the amount of movement of the hull **16** in the windward direction in the power generation mode A exceeds the amount of

movement of the hull **16** in the leeward direction in the retraction mode B.

(54) Horizontal Movement Pattern

(55) As illustrated in FIG. **13**, when wind power generation is conducted while the hull **16** as a whole moves laterally to (in a direction orthogonal to) the wind direction of the natural wind WD, in the power generation mode A, the hull **16** moves only in the set advancing direction while moving in the windward direction. In the retraction mode B, the hull **16** is moved in a direction substantially the same as the leeward direction and is also moved to a position in the wind direction from which the hull **16** started navigation in the power generation mode A.

(56) Case of Deteriorating External Environment

(57) In the case of deteriorating external environment, such as worsening weather, the control device **30** performs one or more processes of (1) to (3) below. (1) The advancing velocity V of the hull **16** is reduced. Specifically, the control device **30** reduces the advancing velocity V of the hull **16** by increasing or decreasing the sail angle α_s . (2) The flight motion of Kite **26** is stopped. (3) The kite **26** is retracted.

Case of Rapid Change in External Environment

(58) In the case of a rapid change in the external environment, such as a rapid change in the weather, the control device **30** performs one or more processes of (4) to (7) below. (4) The tension strength of the kite **26** and the tether **24** is maintained by increasing the unwinding speed of the tether **24**. (5) The advancing direction of the hull **16** is changed to the leeward side. (6) The advancing velocity V of the hull **16** is reduced. Note that (6) is the same process as (1) above. (7) The flight motion of Kite **26** is stopped. Note that (7) is the same process as (2) above.

Operation and Effect of the Above Embodiment

(59) Next, the effects of the above embodiment will be described.

(60) The aquatic wind power generation system **10** according to the above embodiment alternates between a power generation mode A, in which wind power is generated by the unwinding operation of the tether **24** due to the flight of the kite **26**, and a retraction mode B, in which the tether **24** is retracted by the winding operation of the tether **24**. In the retraction mode B, control is performed to direct the bow **16A** of the hull **16** in the leeward direction. Thus, the bow **16A** of the hull **16** faces the leeward direction when the tether **24** is retracted, and hence the relative wind velocity with respect to the kite **26** can be reduced. This allows for a reduction in the energy consumption required for the winding operation of the tether **24**, thereby improving the overall power generation efficiency.

(61) In the aquatic wind power generation system **10** according to the above embodiment, when the advancing direction D of the hull **16** is a direction substantially the same as the wind direction of the natural wind, the propulsive force P_s of the hull **16** and the tension T of the tether **24** are aligned in the same direction. The winding speed V_t of the tether **24** is set to be slower than the unwinding speed of the tether **24** in the power generation mode A, as much as possible. The power output Q_r required to retract the kite **26** is a value obtained by multiplying the tension T of the tether **24** by the winding speed V_t of the tether **24**. Therefore, by aligning the propulsive force P_s of the hull **16** and the tension T of the tether **24** in the same direction, the tension T is used to pull the hull **16**, and the tension T can thus be reduced. Accordingly, the power output Q_r can be reduced by decreasing the winding speed V_t while reducing the tension T .

(62) In the aquatic wind power generation system **10** according to the above embodiment, when the tether **24** is retracted, the hull **16** advances in the vector direction of the tension T of the kite **26**, and hence the relative wind velocity with respect to the kite **26** can be efficiently reduced. This also allows for an efficient reduction in the energy consumption required for the winding operation of the tether **24**, thereby efficiently improving the overall power generation efficiency.

(63) In the aquatic wind power generation system **10** according to the above embodiment, when the advancing direction D of the hull **16** is angled with respect to the wind direction of the natural wind, the advancing velocity V of the hull **16** is controlled so that the relative velocity V_w with

respect to the hull **16** is orthogonal to the advancing velocity V of the hull **16**, thus enabling the relative velocity V_w with respect to the hull **16** to reach the minimum velocity. Therefore, by the relative velocity V_w with respect to the hull **16** reaching the minimum velocity, the relative wind velocity with respect to the kite **26** can be minimized, and the energy consumption required for the winding operation of the tether **24** can also be minimized. Accordingly, it is possible to further improve the overall power generation efficiency.

(64) In the aquatic wind power generation system **10** according to the above embodiment, when wind power is generated by the kite **26**, since the bow **16A** of the hull **16** faces the windward direction, the hull **16** moves against the natural wind. This allows for an increase in the relative wind velocity with respect to the kite **26**, leading to a faster unwinding speed of the tether **24** and thus an increase in power output.

(65) In the aquatic wind power generation system **10** according to the above embodiment, by making the advancing direction D of the hull **16** orthogonal to the wind direction of the natural wind, the advancing direction D of the hull **16** can be set to a direction abeam to the wind, resulting in a faster advancing velocity V of the hull **16**. This increases the propulsive force P_s of the hull **16**, thereby increasing the lateral force F_b applied to the hull **16** and enabling a reduction in the tension T of the kite **26**. Therefore, it is possible to efficiently increase the relative velocity with respect to the kite **26**, leading to a faster unwinding speed of the tether **24** and thus an increase in power output.

(66) In the embodiment described above, the sailboat **12** includes one hull **16**, but the disclosure is not limited thereto. For example, the sailboat **12** may include a multi-hulled vessel, such as a catamaran or trimaran, with two or more hulls connected in parallel on deck. The lateral force generating portion **40** of the embodiment described above can also be applied to the shape of the multi-hulled vessel.

(67) In the aquatic wind power generation system **10** according to the embodiment described above, in the power generation mode A, the control device **30** controls the rudder angle α_r so that the vector direction of the tension T of the kite **26** and the advancing direction D of the hull **16** are substantially orthogonal to each other when viewed from above the hull **16**, but the disclosure is not limited thereto. For example, the rudder angle α_r may be controlled to fall within a range of approximately $\pm 10^\circ$ from a direction in which the vector direction of the tension T of the kite **26** and the advancing direction D of the hull **16** are substantially orthogonal to each other when viewed from above the hull **16**. However, the range varies depending on the area of the kite **26** and the magnitude of the wind velocity V_{wd} , and the larger the area of the kite **26** and the higher the wind velocity V_{wd} , the narrower the above range becomes. In the disclosure, the control device **30** only needs to be able to control the rudder angle α_r so that the lateral force F_b can be generated in a direction to cancel the tension T of the kite **26**.

(68) In the embodiment described above, the rudder angle α_r is controlled in order to change the advancing direction D of the hull **16**, but the disclosure is not limited thereto. For example, the advancing direction D of the hull **16** may be changed by controlling the sail angle α_s to increase the propulsive force P_s and generate a larger lateral force F_b . The advancing direction D of the hull **16** may be changed by controlling both the rudder angle α_r and the sail angle α_s .

(69) In the present embodiment, the sailboat **12** equipped with the sail **14** has been described, but the disclosure is not limited thereto, and known means capable of generating the propulsive force P_s may be used instead of the sail **14**.

(70) One embodiment of the disclosure has been described above, but the disclosure is not limited to such an embodiment. The disclosure may be used in combination with various modifications as appropriate, and may be implemented in various forms within the scope not departing from the gist of the disclosure.

Claims

1. An aquatic wind power generation system comprising: a hull that navigates on water; a power generation system that includes a kite connected to the hull via a tether, and alternates between a power generation mode in which wind power is generated by an unwinding operation of the tether due to flight of the kite, and a retraction mode in which the tether is retracted by a winding operation of the tether; and a controller that performs control: (a) during retraction mode: (i) to direct a bow of the hull in a leeward direction in the retraction mode so that a vector direction of tension of the kite matches an advancing direction of the hull when viewed from above the hull, and a sail angle of a sail, which is an angle of attack between the sail and a vector of a composite velocity of a wind velocity of a natural wind and an advancing velocity of the hull, to be 90° , and (b) during power generation mode controls a direction of the bow so that a wind direction of natural wind and an advancing direction of the hull are orthogonal to each other when viewed from above the hull.
