

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399580
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Munakata; Hiroshi et al.

Three-dimensional position indicator and three-dimensional position detection system including grip part and tracker

Abstract

A position indicator indicates a position in a three-dimensional (3D) space. The position indicator includes an elongated casing; a position indicating part which is disposed at one end of the elongated casing and which, in operation, indicates the position; a grip part configured to be gripped with a palm of a user in a state in which the elongated casing is gripped between fingers of the user; and a tracker which, in operation, causes an external device to detect a tracker position of the tracker in the 3D space, wherein the tracker is disposed so as to be not covered by the user's hand when the user palm-grips the grip part. The tracker position of the tracker and a position of the position indicating part are in a specific positional relation.

Inventors: Munakata; Hiroshi (Saitama, JP), Tamano; Hiroshi (Saitama, JP), Chen; Yuanhao (Saitama, JP)

Applicant: Wacom Co., Ltd. (Saitama, JP)

Family ID: 1000008780721

Assignee: Wacom, Co., Ltd. (Saitama, JP)

Appl. No.: 18/423011

Filed: January 25, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240192788 A1	Jun. 13, 2024

Foreign Application Priority Data

JP	2018-055544	Mar. 23, 2018
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17681666 20220225 US 11934592 child-doc US 18423011
continuation parent-doc US 17010652 20200902 US 11294478 20220405 child-doc US 17681666
continuation parent-doc WO PCT/JP2018/046976 20181220 PENDING child-doc US 17010652

Publication Classification

Int. Cl.: G06F3/0354 (20130101); G06F3/0346 (20130101); G06F3/038 (20130101); G06F3/044 (20060101); G06F3/046 (20060101)

U.S. Cl.:

CPC G06F3/03545 (20130101); G06F3/0346 (20130101); G06F3/0383 (20130101); G06F3/044 (20130101); G06F3/046 (20130101);

Field of Classification Search

CPC: G06F (3/03545); G06F (3/0346); G06F (3/0383); G06F (3/044); G06F (3/046)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4991148	12/1990	Gilchrist	N/A	N/A
5488204	12/1995	Mead	345/179	G06F 3/0446
9367169	12/2015	Tan	N/A	N/A
11934592	12/2023	Munakata	N/A	G06F 3/03545
2002/0051359	12/2001	Hisasue	463/47	B43K 29/10
2005/0073508	12/2004	Pittel	345/175	G06F 3/03542
2005/0190163	12/2004	Sarasmu	345/179	G06F 3/03545
2008/0166175	12/2007	Pittel	401/131	B43K 23/02
2010/0021022	12/2009	Pittel	206/320	G06F 3/03545
2010/0091112	12/2009	Veesser et al.	N/A	N/A
2011/0007037	12/2010	Ogawa	345/179	G06F 3/046
2012/0229384	12/2011	Nakane	345/158	G06F 3/03545
2014/0354553	12/2013	Dai	345/173	G06F 3/044
2015/0116289	12/2014	Stern	345/179	G06F 3/03545
2015/0116290	12/2014	Wheaton	345/179	B43K 7/12

2016/0041632	12/2015	Ono	345/175	G06F 3/03542
2016/0253043	12/2015	Narikawa	348/744	G06F 3/0425
2017/0168599	12/2016	Zenghui	N/A	G06F 3/0393
2017/0177099	12/2016	Tamura	N/A	G06F 3/0446
2017/0185233	12/2016	Ono	N/A	G06F 3/0386
2017/0308184	12/2016	Kato	N/A	G06F 3/0383
2017/0357334	12/2016	Balan et al.	N/A	N/A
2021/0048897	12/2020	Munakata et al.	N/A	N/A
2021/0072847	12/2020	Ide	N/A	G06F 3/03545
2021/0278293	12/2020	Kinokuni	N/A	G06F 3/0447

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1 228 480	12/2001	EP	N/A
4053227	12/2021	EP	C09D 11/17
2001-344060	12/2000	JP	N/A
2010-509582	12/2009	JP	N/A
5723499	12/2014	JP	G06F 1/3206
WO-0135329	12/2000	WO	G06F 3/0346
WO-2008056180	12/2007	WO	G01B 11/002
2016158418	12/2015	WO	N/A
WO-2019220803	12/2018	WO	G06F 3/011
WO-2019225170	12/2018	WO	G06F 3/011

OTHER PUBLICATIONS

Extended European Search Report, dated May 12, 2021, for European Application No. 18910270.0-1216, 14 pages. cited by applicant

International Search Report, mailed Mar. 5, 2019, for International Application No. PCT/JP2018/046976, 4 pages. (With English translation). cited by applicant

Poupyrev et al., "Virtual Notepad: Handwriting in Immersive VR," *IEEE*, 1998. (7 pages). cited by applicant

Primary Examiner: Davis; David D

Attorney, Agent or Firm: Seed Intellectual Property Law Group LLP

Background/Summary

BACKGROUND

Technical Field

(1) The disclosure relates to a three-dimensional position indicator and a three-dimensional position detection system suitable to be used for three-dimensional rendering (3D rendering), for example.

Description of the Related Art

(2) Known is a rendering system with which an animation image or the like is created by continuously carrying out position indication to a coordinate input device called a digitizer and carrying out rendering by an electronic pen. In this case, the operator carries out a position indication operation for generating a rendering image in a state in which a pen tip of the electronic pen is brought into contact with an input surface of a tablet device that incorporates the digitizer, or in a state in which the pen tip is put in an upper-side region in which position detection is possible while the pen tip is not in contact with the input surface of the tablet device (hover state). The digitizer detects the position indicated by the electronic pen and generates a rendering image as the detection result thereof to display the rendering image on a display screen. The operator carries out rendering while checking the rendering image displayed on the display screen.

(3) Recently, rendering systems and applications that allow a rendering image displayed on a two-dimensional display screen to be rendered and expressed like a three-dimensional image visually have appeared. In this case, many of the rendering systems and applications detect, using a motion sensor, a motion operation (gesture) for rendering an image generated using a digitizer, which is indicated by motion of a hand or finger of the operator, and perform three-dimensional rendering expression processing based on the detected motion operation (gesture).

(4) Incidentally, a user interface with which both position indication input and operation input of gesture and so forth as the above-described ones can be carried out has been provided. For example, in Patent Document 1 (U.S. Pat. No. 9,367,169), disclosed is a touch controller that is one that uses a device including a touch sensor configured to detect a finger touch by an operator and a motion sensor configured to detect motion and that is configured to switch the touch sensor from a hover event detection mode to a gesture event detection mode in response to a signal from the motion sensor.

PRIOR ART DOCUMENT

Patent Document

(5) Patent Document 1: U.S. Pat. No. 9,367,169

BRIEF SUMMARY

Technical Problems

(6) However, in Patent Document 1, switching between the hover event detection mode and the gesture event detection mode is carried out in a hover region that is a spatial region in a distance range limited from an input surface of the touch sensor, and the operator needs to make gesture while keeping the hover state with respect to the touch sensor. Thus, the operator needs to make gesture in the limited spatial region and therefore, there is a problem that it is difficult to carry out work for 3D rendering. Furthermore, in Patent Document 1, operation with fingers of the operator is assumed and therefore, there is also a problem that it is difficult to carry out more detailed indication operation. Moreover, in Patent Document 1, switching between the hover event detection mode and the gesture event detection mode is carried out in response to a signal from the motion sensor. Therefore, there is a problem that the tilt of the device needs to be changed for the switching each time.

(7) The disclosure intends to provide a three-dimensional position indicator and a three-dimensional position detection system configured to be capable of solving the above-described

problems.

Technical Solution

(8) In order to solve the above-described problems, there is provided a three-dimensional position indicator that indicates a position on an input surface of a position detecting sensor in a three-dimensional space. The three-dimensional position indicator includes: a casing, a position indicating part that is disposed at one end of the casing, wherein and the position indicating part, in operation, indicates a the position on the input surface of the position detecting sensor, and a tracker for causing which, in operation, causes an external device to detect a the position in the three-dimensional space, wherein the a position of the tracker and the a position of the position indicating part are in a specific positional relation.

(9) Furthermore, in order to solve the above-described problems, there is provided a three-dimensional position detection system including a position indicator, a position detecting sensor, and a spatial position detecting device. The position indicator includes: a casing, a position indicating part that is disposed at one end of the casing. The position indicating part, in operation, indicates a position on an input surface of the position detecting sensor, a tracker which, in operation, causes the spatial position detecting device to detect a position in the three-dimensional space, a position of the tracker and a position of the position indicating part being in a specific positional relation, and a communication circuit which, in operation, communicates with the position detecting sensor and causes the position detecting sensor to detect the position on the input surface of the position detecting sensor indicated by the position indicating part. The spatial position detecting device includes a circuit which, in operation, calculates a position of the position indicating part in the three-dimensional space, based on the position in the three-dimensional space detected by interaction of the spatial position detecting device with the tracker and the specific positional relation

(10) The three-dimensional position indicator with the above-described configuration causes the position indicated by the position indicating part on the one end of the casing to be detected by the position detecting sensor, by carrying out interaction with the position detecting sensor by the interaction part.

(11) Furthermore, the three-dimensional position indicator includes the tracker that causes the external device to detect the position in the three-dimensional space. Therefore, in the above-described three-dimensional position detection system, the spatial position detecting device can detect the position in the three-dimensional space irrespective of the positional relation between the three-dimensional position indicator and the position detecting sensor.

(12) According to this configuration, in the above-described three-dimensional position detection system, the operator can carry out fine rendering by position indication performed by the tip part of the bar-shaped part of the three-dimensional position indicator on the input surface of the position detecting sensor. In addition, the operator can carry out input operation with respect to a 3D rendering image by making gesture based on motion of the position of the three-dimensional position indicator in the three-dimensional space free from limitation on the positional relation with the position detecting sensor.

(13) Here, because the position of the tracker of the three-dimensional position indicator is at a position different from the position indicating part, a difference arises between the position detected by the position detecting sensor and the position in the three-dimensional space detected by the spatial position detecting device. In this case, in the case of carrying out work with switching between rendering operation with the position detecting sensor and gesture operation with the spatial position detecting device as a series of operation, by use of the three-dimensional position indicator, the position indicated by the three-dimensional position indicator differs depending on the operation. Thus, possibly, continuous position indication operation becomes impossible and it becomes impossible to smoothly carry out the work.

(14) However, in the three-dimensional position indicator with the above-described configuration,

the position indicating part is disposed to be in the specific positional relation with the position and the direction detected by interaction between the tracker and the spatial position detecting device. Accordingly, in the spatial position detecting device, the position of the position indicating part detected as the indicated position, based on the position detected by the interaction with the tracker and the specific positional relation.

(15) Therefore, the user can employ the position indicating part as the indicated position not only in the input surface of the position detecting sensor but also in the three-dimensional space based on the spatial position detecting device. Thus, consistency is kept in the operation work, and it becomes possible to smoothly carry out three-dimensional rendering work.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) FIG. 1 is a diagram for explaining the outline of a spatial position detection system according to a first embodiment of the disclosure.

(2) FIG. 2 is a block diagram for explaining a configuration example of the spatial position detection system according to the first embodiment of the disclosure.

(3) FIG. 3 is a diagram for explaining a spatial coordinate system in a spatial position indication system according to the first embodiment of the disclosure.

(4) FIG. 4 is a diagram for explaining switching of a coordinate system for position detection of an electronic pen in the spatial position indication system according to the first embodiment of the disclosure.

(5) FIG. 5 is a perspective view illustrating the appearance of a three-dimensional position indicator according to the first embodiment of the disclosure.

(6) FIGS. 6A, 6B, and 6C depict diagrams for explaining a configuration example of the three-dimensional position indicator according to the first embodiment of the disclosure.

(7) FIG. 7 is a diagram for explaining the configuration example of the three-dimensional position indicator according to the first embodiment of the disclosure.

(8) FIG. 8 is a diagram for explaining another configuration example of the three-dimensional position indicator according to the first embodiment of the disclosure.

(9) FIG. 9 is a diagram for explaining a configuration example of a three-dimensional position indicator according to a second embodiment of the disclosure.

(10) FIG. 10 is a block diagram for explaining a configuration example of the spatial position detection system according to the second embodiment of the disclosure.

(11) FIGS. 11A, 11B, and 11C depict diagrams for explaining a configuration example of the three-dimensional position indicator according to another embodiment of the disclosure.

DETAILED DESCRIPTION

(12) Several embodiments of a spatial position detection system according to the disclosure will be described below with reference to the drawings.

First Embodiment

(13) A spatial position detection system according to a first embodiment of the disclosure is an example in which a configuration of a head-mounted display is employed as a display part and a space of virtual reality (including VR (Virtual Reality), MR (Mixed Reality), AR (Augmented Reality), and so forth hereinafter abbreviated as VR) is employed as a 3D rendering space.

(14) FIG. 1 is a diagram illustrating the outline of the overall configuration of the spatial position detection system of this first embodiment in which a space of VR is employed as the 3D rendering space. Further, FIG. 2 is a block diagram illustrating a detailed configuration example of functions of the respective parts of the spatial position detection system of this first embodiment.

(15) As depicted in FIG. 1, the spatial position detection system of this first embodiment is

configured to include a three-dimensional position indicator, a digitizer **20**, a unit **30** for spatial position detection, a spatial rendering information generating device **40**, and a head-mounted display (hereinafter, referred to as HMD) **50**. As depicted in FIG. 2, in this example, the spatial rendering information generating device **40** has functions of an input information processing part **41** and a display image generating part **42** and includes a personal computer, for example. The input information processing part **41** has functions of a spatial position detecting device. As depicted in FIG. 2, in this specification, each of processing functions performed by executing a program of the personal computer is depicted as each “circuit” block for convenience of explanation. For example, the spatial rendering information generating device **40** includes a processor and a memory storing instructions that, when executed by the processor, cause the spatial rendering information generating device **40** to perform the functions of the various circuits of the spatial rendering information generating device **40** shown in FIG. 2.

(16) In the spatial position detection system of this first embodiment, the spatial rendering information generating device **40** including the input information processing part **41** and the display image generating part **42** is used. However, as the spatial position detection system of the disclosure, a configuration composed of the three-dimensional position indicator, the digitizer **20**, the unit **30** for spatial position detection, and the input information processing part **41** may be employed, and the display image generating part **42** may be configured to be disposed separately.

(17) A three-dimensional position indicator **10** has a function of causing the position of a tip on one end side of a bar-shaped part in the axis center direction to be an indicated position in an input surface of the digitizer **20** and causing the position of the tip to be an indicated position in a three-dimensional space detected by a spatial position detection function of the input information processing part **41** by use of the unit **30** for spatial position detection.

(18) As depicted in FIG. 1, in this example, the bar-shaped part of the three-dimensional position indicator **10** is formed of an electronic pen **11** allowed to be inserted and removed. In this example, a tip **11a** (hereinafter, referred to as a pen tip **11a**) of a core body that protrudes from an opening of one end part of a tubular casing of the electronic pen **11** in the axis center direction serves as the tip on the one end side of the bar-shaped part in the axis center direction. As the electronic pen **11**, in this first embodiment, an electronic pen of the electromagnetic induction system is used as an example. However, the electronic pen **11** is not limited to those of the electromagnetic induction system and may be an electronic pen of the capacitive coupling system.

(19) The electronic pen **11** may of course be disposed to be monolithic with or fixed to the three-dimensional position indicator **10** without being allowed to be inserted and removed. That is, the bar-shaped part may be disposed to be monolithic with or fixed to the three-dimensional position indicator **10**. A detailed description of a configuration example of the three-dimensional position indicator **10** will be made later.

(20) In this example, the digitizer **20** includes a casing **21** with a thin rectangular parallelepiped shape, and a surface thereof is used as an input surface **21S** for position indication by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10**. In addition, the digitizer **20** includes a position detecting sensor **22** and a position detecting circuit **23** (see FIG. 2).

(21) Although diagrammatic representation is omitted, the position detecting sensor **22** is configured through disposing of each of plural loop coils in the horizontal direction of the casing of the digitizer **20** (X-axis direction) and the vertical direction of the casing (Y-axis direction).

Although diagrammatic representation is omitted, the electronic pen **11** of the three-dimensional position indicator **10** includes a resonant circuit (diagrammatic representation is omitted) including a coil and a capacitor, on the side of the pen tip **11a**. Through electromagnetic induction coupling between the loop coils of the position detecting sensor **22** of the digitizer **20** and the resonant circuit of the electronic pen **11**, interaction is carried out between the electronic pen **11** and the position detecting sensor **22** of the digitizer **20** and transfer of signals is carried out. In this example, the digitizer **20** of the electromagnetic induction system is used in conformity with the

electronic pen **11**. However, in the case of the capacitive coupling system, the digitizer **20** carries out interaction with the electronic pen by capacitive coupling.

(22) The position detecting circuit **23** of the digitizer **20** supplies a signal to the electronic pen **11** through the loop coil of the position detecting sensor **22**. In addition, the position detecting circuit **23** receives a signal fed back from the electronic pen **11** through the loop coil and detects the position indicated by the pen tip **11a** of the electronic pen **11** in the detection region of the position detecting sensor **22**, based on the received signal. In this embodiment, the digitizer **20** is configured to detect the position indicated by the pen tip **11a** of the electronic pen **11** as the indicated position of the electronic pen **11**.

(23) In the digitizer **20** of this example, the plural loop coils of the sensor **22** are disposed to cover almost the whole area of the input surface **21S**.

(24) Moreover, in this embodiment, the position detection region in which the indicated position of the electronic pen **11** can be detected by the digitizer **20** includes not only a planar region when the pen tip **11a** of the electronic pen **11** is in contact with the input surface **21S** of the digitizer **20** but also a spatial region (hover region of the hover state of the electronic pen **11**) in which the indicated position of the electronic pen **11** can be detected through transfer of signals by electromagnetic coupling although the pen tip **11a** of the electronic pen **11** is not in contact with the input surface **21S** of the digitizer **20** and is separate from the input surface **21S** in the direction orthogonal to this input surface **21S** (Z-axis direction orthogonal to X-axis direction and Y-axis direction).

(25) FIG. **3** is a diagram for explaining the detection spatial region of the indicated position of the electronic pen **11** of the three-dimensional position indicator **10** in the digitizer **20**, and a detection spatial region (three-dimensional spatial region) of a detection-target object (referred to as an object) including the three-dimensional position indicator **10** in the unit **30** for spatial position detection to be described later is also depicted.

(26) For example, when, in FIG. **1**, a position P0 of the upper left corner of the input surface **21S** of the digitizer **20** is defined as coordinates $((X, Y, Z)=(0, 0, 0))$ of the origin in the X-axis direction, the Y-axis direction, and the Z-axis direction, a position detection region DT in which the indicated position of the electronic pen **11** can be detected in the digitizer **20** is a planar region of the input surface **21S** and a rectangular parallelepiped spatial region above this input surface **21S**, depicted by being given hatched lines in FIG. **3**.

(27) Specifically, when, as depicted in FIG. **3**, the length of the input surface **21S** of the digitizer **20** in the X-axis direction is defined as L_x , the length thereof in the Y-axis direction is defined as L_y , and the critical height position in the Z-axis direction at and under which the hover state can be detected is defined as L_z , the region surrounded by the positions of eight coordinate points of P0 (0, 0, 0), P1 ($L_x, 0, 0$), P2 ($L_x, L_y, 0$), P3 (0, $L_y, 0$), P4 (0, 0, L_z), P5 ($L_x, 0, L_z$), P6 (L_x, L_y, L_z), and P7 (0, L_y, L_z) is the position detection region DT of the digitizer **20**, as depicted in FIG. **3**. In this digitizer **20**, information on the indicated position of the electronic pen **11** detected in the position detection region DT is supplied to the input information processing part **41** of the spatial rendering information generating device **40**.

(28) In this example, the unit **30** for spatial position detection is configured to be capable of setting a three-dimensional spatial region in which the digitizer **20** exists and, in this three-dimensional spatial region, detecting the position of the three-dimensional position indicator **10** and the position of the digitizer **20**.

(29) The unit **30** for spatial position detection is configured to set a spatial region including the position detection region DT of the digitizer **20** as a search region and to search for objects that exist in the search region, as depicted in FIG. **3**. In this embodiment, the objects detected by the unit **30** for spatial position detection are the three-dimensional position indicator **10** and the digitizer **20**. In the following description, the three-dimensional spatial region (search region) set by this unit **30** for spatial position detection will be referred to as a motion detection spatial region MD, for convenience.

(30) In this embodiment, the unit **30** for spatial position detection is one that detects the positions of the objects by optical interaction with the objects and, as depicted in FIG. 1 and FIG. 2, is configured to include two light emission tracing devices **31A** and **31B** and light position notifying parts (hereinafter, referred to as trackers) attached to the objects.

(31) The trackers include a light receiving sensor that detects infrared laser light from the light emission tracing devices **31A** and **31B** and a light emitting part that is for notifying the light emission tracing devices **31A** and **31B** of reception of the infrared laser light when the reception of the infrared laser light is detected by the light receiving sensor and that is formed of an LED (Light Emitting Diode), for example. Plural light receiving sensors are disposed in each tracker so that the laser light from any direction can be received.

(32) In this embodiment, the objects to which the trackers are mounted are the three-dimensional position indicator **10** and the digitizer **20**. Specifically, in this example, a tracker **24A** and a tracker **24B** are mounted at the upper left corner and the lower right corner of the casing of the digitizer **20** with the thin rectangular parallelepiped shape, in order to allow notification of the spatial position and orientation of the digitizer **20** (orientation of the input surface **21S**) in the motion detection spatial region MD. Since not only the position but also the direction can be detected by use of the tracker as described above, the tracker attached to the digitizer **20** may be one tracker.

(33) Moreover, in order to give notification of the spatial position and orientation of the three-dimensional position indicator **10** in the motion detection spatial region MD, for the three-dimensional position indicator **10**, a tracker **12** is mounted to the rear end side on the side opposite the side of the pen tip **11a** in the axis center direction of the electronic pen **11**, in this example. The tracker **12** configures a spatial position index part of the three-dimensional position indicator **10**.

(34) Further, in this example, for example, a nine-axis sensor for detecting motion and direction (orientation) is also disposed in the trackers. Further, from each of the trackers, light reception output of the light receiving sensors and output of the nine-axis sensor are supplied to the spatial rendering information generating device **40** in a wired or wireless manner or via the object to which the tracker is attached. In this case, in information from the trackers **12**, **24A**, and **24B**, identification information of each of them is included.

(35) In the spatial rendering information generating device **40**, the posture and motion of the object to which the tracker is mounted in the three-dimensional space are detected from the light reception output of the plural light receiving sensors and/or the output of the nine-axis sensor from the tracker. To detect the posture and motion of the object to which the tracker is mounted in the three-dimensional space, it suffices that either one of the plural light receiving sensors and the nine-axis sensor is disposed in the tracker.

(36) The two light emission tracing devices **31A** and **31B** have the same configuration and each include a laser light emitting part of the infrared laser light, search means that makes a search in the motion detection spatial region MD by the emitted infrared laser light, and light position detecting means that detects light emission of the light emitting parts of the trackers **12**, **24A**, and **24B** that have received the infrared laser light.

(37) In this case, for example, the light emission tracing device **31A** makes a search by the infrared laser light in such a manner as to scan the inside of the motion detection spatial region MD in the horizontal direction and to move the position of the scanning in the horizontal direction sequentially in the vertical direction by a predetermined pitch τX . Moreover, the light emission tracing device **31B** makes a search by the infrared laser light in such a manner as to scan the inside of the motion detection spatial region MD in the vertical direction and to move the position of the scanning in the vertical direction sequentially in the horizontal direction by a predetermined pitch τY .

(38) Each of the trackers **12**, **24A**, and **24B** monitors light reception of the infrared laser light by the light receiving sensors and lights the light emitting part formed of the LED when detecting light reception of the infrared laser light.

(39) The light emission tracing devices **31A** and **31B** detect light emission of the light emitting parts of the trackers **12**, **24A**, and **24B** to thereby detect the positions of the objects to which these trackers **12**, **24A**, and **24B** are mounted in the motion detection spatial region MD. The light emission tracing devices **31A** and **31B** are configured to be capable of, when detecting light emission of the light emitting part of the tracker **12**, **24A**, or **24B**, detecting also the elapsed clock time from the emission clock time of the emitted infrared laser at the time of this detection. In this case, each of the trackers **12**, **24A**, and **24B** carries out different light emission according to its own identification information.

(40) This allows the unit **30** for spatial position detection to detect the positions of the trackers **12**, **24A**, and **24B** attached to the objects (i.e., positions of the objects) in the motion detection spatial region MD with precision according to the predetermined pitch τX and the predetermined pitch τY .

(41) The two light emission tracing devices **31A** and **31B** are connected to the spatial rendering information generating device **40** in a wired or wireless manner and notify the spatial rendering information generating device **40** of spatial position information in the motion detection spatial region MD regarding the detected trackers **12**, **24A**, and **24B**. In this case, in information from the two light emission tracing devices **31A** and **31B**, identification information of each of them is included.

(42) In this example, the spatial position information in the motion detection spatial region MD regarding the trackers **12**, **24A**, and **24B** detected by the two light emission tracing devices **31A** and **31B** is supplied to a spatial position detecting circuit **410** of the input information processing part **41** of the spatial rendering information generating device **40** as depicted in FIG. 2.

(43) As described above, the light reception output of the light receiving sensors and the detection output of the nine-axis sensor from the trackers **12**, **24A**, and **24B** are also supplied to the spatial position detecting circuit **410** of the input information processing part **41** of the spatial rendering information generating device **40**.

(44) In this example, the spatial position detecting circuit **410** includes a position indicator detecting circuit **4101**, an indicated position calculating circuit **4102**, and a digitizer detecting circuit **4103**. In addition, in this example, the spatial position detecting circuit **410** includes an operation information detecting circuit **4104** that detects operation information of an operation part disposed in the three-dimensional position indicator **10**, as described below. The operation information detected by the operation information detecting circuit **4104** is supplied from the three-dimensional position indicator **10** to the spatial position detecting circuit **410** of the spatial rendering information generating device **40** together with the light reception output of the light receiving sensors and the output of the nine-axis sensor.

(45) The position indicator detecting circuit **4101** detects the position of the three-dimensional position indicator **10** in the motion detection spatial region MD by position information detected by the light emission tracing devices **31A** and **31B** through optical interaction with the tracker **12** of the three-dimensional position indicator **10**. In addition, the position indicator detecting circuit **4101** detects the posture of the three-dimensional position indicator **10** including the direction in which the three-dimensional position indicator **10** is oriented in the motion detection spatial region MD from the light reception output of the light receiving sensors and the detection output of the nine-axis sensor from the tracker **12**. In this case, in the posture of the three-dimensional position indicator **10**, the axis center direction of the electronic pen **11** as the bar-shaped part and the rotation direction position (rotation angle) around this axis center direction are included.

(46) The information on the position of the three-dimensional position indicator **10** and the information on the posture of the three-dimensional position indicator **10** including the direction in which the three-dimensional position indicator **10** is oriented, which are detected by the position indicator detecting circuit **4101**, are supplied to the indicated position calculating circuit **4102**. Here, the indicated position of the three-dimensional position indicator **10** is the position of the pen tip **11a** of the electronic pen **11** and is different from the position of the three-dimensional position

indicator **10** detected by the position indicator detecting circuit **4101**. As described later, in the three-dimensional position indicator **10**, the pen tip **11a** of the electronic pen **11** is attached and configured to be in specific positional relation and directional relation with the position and direction of the three-dimensional position indicator **10** detected by the position indicator detecting circuit **4101** of the spatial position detecting circuit **410**.

(47) In the indicated position calculating circuit **4102**, correction information with which the position indicated by the pen tip **11a** of the electronic pen **11** is detected from the information on the position and the information on the direction regarding the three-dimensional position indicator **10** detected by the position indicator detecting circuit **4101** from the above-described specific positional relation and directional relation is stored in a correction memory **4102M**.

(48) The indicated position calculating circuit **4102** calculates and outputs the position indicated by the pen tip **11a** of the electronic pen **11** from the information on the position and the information on the direction regarding the three-dimensional position indicator **10** detected by the position indicator detecting circuit **4101** and the correction information stored in the correction memory **4102M**. Moreover, based on the information on the posture of the three-dimensional position indicator **10** detected by the position indicator detecting circuit **4101**, the indicated position calculating circuit **4102** calculates the orientation of the axis center direction of the electronic pen **11** (tilt of the electronic pen **11**) and calculates the rotation and motion of the electronic pen **11** to output the calculated information as information on the posture of the electronic pen **11**.

(49) Further, the digitizer detecting circuit **4103** of the spatial position detecting circuit **410** detects the position of the digitizer **20** in the motion detection spatial region MD by position information detected by the light emission tracing devices **31A** and **31B** through optical interaction with the trackers **24A** and **24B**. Further, the digitizer detecting circuit **4103** detects the posture of the digitizer **20** including the direction in which the input surface **21S** of the digitizer **20** is oriented in the motion detection spatial region MD from the light reception output of the light receiving sensors and the detection output of the nine-axis sensor from the trackers **24A** and **24B**, and outputs information on the detected posture together with information on the position.

(50) In addition, the operation information detecting circuit **4104** detects and outputs the operation information of the operation part of the three-dimensional position indicator **10**.

(51) In the input information processing part **41**, information to be supplied to the display image generating part **42** is generated from the information on the position indicated by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** in the position detection region DT, which is detected by the digitizer **20** in the above-described manner, and the information on the position (indicated position) of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** in the motion detection spatial region MD, the information on the posture of the electronic pen **11**, the information on the posture of the three-dimensional position indicator **10**, and the operation information, which are detected by the above-described spatial position detecting circuit **410**. Then, the input information processing part **41** supplies the generated information to the display image generating part **42**.

(52) In this embodiment, as depicted in FIG. 2, the display image generating part **42** includes a rendering image generating circuit **421** for generating a 3D rendering image and a VR image generating circuit **422** for generating a VR image to be displayed on the HMD **50**. Hereinafter, processing relating to generation of a 3D rendering image in the rendering image generating circuit **421** will be referred to as 3D rendering-related processing. In addition, processing relating to generation of a VR image in the VR image generating circuit **422** will be referred to as VR image-related processing. In this embodiment, on the HMD **50**, a 3D rendering image rendered in the motion detection spatial region MD including the position detection region DT of the digitizer **20** is displayed as a virtual display image and virtual display images of the electronic pen **11** of the three-dimensional position indicator **10** and the digitizer **20** are displayed.

(53) The rendering image generating circuit **421** generates a 3D rendering image, based on

information on the position indication by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** and the posture of the electronic pen **11**. In addition, the rendering image generating circuit **421** performs processing of deformation, rotation, movement, and so forth of the 3D rendering image, based on gesture made by the operator of the three-dimensional position indicator **10**. In the display image generating part **42**, as depicted in FIG. 2, a gesture detection processing circuit **423** for detecting a gesture made by the operator of the three-dimensional position indicator **10** is disposed. The detection result of the gesture in this gesture detection processing circuit **423** is supplied to the rendering image generating circuit **421**. The gesture detection processing circuit **423** detects the gesture made by the operator of the three-dimensional position indicator **10** from change in the position and change in the posture regarding the three-dimensional position indicator **10**.

(54) The VR image generating circuit **422** of the display image generating part **42** generates a VR image to be displayed on the HMD **50**. As the VR image, in this embodiment, a VR image of the electronic pen **11**, a VR image of the digitizer **20**, and a VR image of the 3D rendering image generated by the rendering image generating circuit **421** are included. A VR image of the three-dimensional position indicator **10** including the electronic pen **11** may be generated.

(55) The input information processing part **41** generates information for the rendering-related processing and information for the VR image-related processing such as the pieces of information described above, from information from the digitizer **20** and information from the unit **30** for spatial position detection, and supplies the pieces of information to the display image generating part **42**.

(56) In this case, when the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** exists in the position detection region DT, the input information processing part **41** supplies, to the VR image generating circuit **422** of the display image generating part **42**, information on the position indicated by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** detected by the digitizer **20**, which can detect the position of the pen tip **11a** of the electronic pen **11** with higher accuracy than the unit **30** for spatial position detection.

(57) Moreover, when the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** exists in a space other than the position detection region DT, the input information processing part **41** supplies information on the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** detected by use of the unit **30** for spatial position detection to the VR image generating circuit **422** of the display image generating part **42**. That is, the input information processing part **41** switches the information on the indicated position of the three-dimensional position indicator **10**, according to which of the position detection region DT and the motion detection spatial region MD the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** exists in, and supplies the information to the display image generating part **42**.

(58) Furthermore, in this embodiment, the input information processing part **41** supplies, to the rendering image generating circuit **421** and the VR image generating circuit **422** of the display image generating part **42**, information on the posture including the tilt and rotation of the electronic pen **11** calculated by the indicated position calculating circuit **4102** from the information on the posture of the three-dimensional position indicator **10** detected by use of the unit **30** for spatial position detection in the above-described manner, irrespective of the spatial position at which the pen tip **11a** of the electronic pen **11** exists.

(59) [Coordinate Transformation Between Spatial Coordinate Systems in which Indicated Position of Three-Dimensional Position Indicator **10** is Detected]

(60) Incidentally, in this embodiment, the spatial coordinate system of the position detection region DT of the digitizer **20** and the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection can independently be set as depicted in FIG. 3.

(61) As described above, in this embodiment, in each of the 3D rendering-related processing and the VR image-related processing, information on the spatial coordinate system of the position detection region DT of the digitizer **20** and information on the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection are mutually used. In this case, there is no problem if the two spatial coordinate systems can completely be made common. However, they can each be independently set as described above and therefore, a point to be described below needs to be taken into consideration.

(62) In FIG. **3**, the three axes of the spatial coordinate system of the motion detection spatial region MD are defined as Xs-axis, Ys-axis, and Zs-axis with use of a suffix s and are depicted with discrimination from X-axis, Y-axis, and Z-axis of the spatial coordinate system of the detection region DT of the digitizer **20**. In FIG. **3**, for convenience, the direction of each of the Xs-axis, the Ys-axis, and the Zs-axis is depicted as the same direction as the direction of a respective one of the X-axis, the Y-axis, and the Z-axis. However, the direction of each of the Xs-axis, the Ys-axis, and the Zs-axis could be different from the direction of the respective one of the X-axis, the Y-axis, and the Z-axis because of the tilt of the input surface **21S** and so forth when the digitizer **20** disposed in the motion detection spatial region MD is set.

(63) However, in this embodiment, the digitizer **20** is disposed in the motion detection spatial region MD of the unit **30** for spatial position detection and the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection is configured to include at least part of the spatial coordinate system of the position detection region DT of the digitizer **20** as a common region. In this embodiment, the configuration is made in such a manner that, for the information on the position indicated by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10**, coordinate transformation is carried out with use of spatial position correction information to be described below, by using a common region between the spatial coordinate system of the position detection region DT and the spatial coordinate system of the motion detection spatial region MD.

(64) In this case, if the direction of each of the Xs-axis, the Ys-axis, and the Zs-axis is the same direction as the direction of the respective one of the X-axis, the Y-axis, and the Z-axis, the spatial coordinate system of the position detection region DT and the spatial coordinate system of the motion detection spatial region MD can be treated as one spatial coordinate system in common, by considering the difference between the origin positions of the two spatial coordinate systems. Specifically, for example, when offset values of the X-axis direction, the Y-axis direction, and the Z-axis direction between the origin position of the spatial coordinate system of the position detection region DT and the origin position of the spatial coordinate system of the motion detection spatial region MD are defined as OFSx, OFSy, and OFSz, respectively, coordinate values (Xs, Ys, Zs) of the spatial coordinate system of the motion detection spatial region MD can be transformed to coordinate values (X, Y, Z) of the spatial coordinate system of the position detection region DT by obtaining $Xs - OFSx (=X)$, $Ys - OFSy (=Y)$, and $Zs - OFSz (=Z)$.

(65) However, in the spatial position indication system of this first embodiment, as described above, the direction of each of the X-axis, the Y-axis, and the Z-axis could be different from the direction of a respective one of the Xs-axis, the Ys-axis, and the Zs-axis between the spatial coordinate system of the position detection region DT of the digitizer **20** and the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection, which are independently set. Moreover, also when the direction of each of the X-axis, the Y-axis, and the Z-axis is the same as the direction of the respective one of the Xs-axis, the Ys-axis, and the Zs-axis, it is difficult to correctly define the offset values of the origin position, and the offset values could differ for each spatial position indication system.

(66) In this case, the coordinate positions in the two spatial coordinate systems differ. As such, when switching is carried out between the two spatial coordinate systems, i.e., the spatial coordinate system of the position detection region DT of the digitizer **20** and the spatial coordinate

system of the motion detection spatial region MD of the unit **30** for spatial position detection, the coordinates of the position of the pen tip **11a** of the electronic pen **11** possibly change in such a manner as jumping in the display screen of the HMD **50**, for example. If this occurs, the user who is trying to input a rendering image is forced to indicate the indicated position again, which is inconvenient.

(67) As such, in this embodiment, by using the fact that at least a partial region of the position detection region DT of the digitizer **20** is a spatial region in common with the motion detection spatial region MD of the unit **30** for spatial position detection, correction information for deviation between the spatial coordinate system of the position detection region DT and the spatial coordinate system of the motion detection spatial region MD is generated to carry out coordinate transformation. In this example, coordinate values resulting from correction of the deviation between the two spatial coordinate systems are allowed to be obtained by transforming the coordinate values (Xs, Ys, Zs) of the spatial coordinate system of the motion detection spatial region MD detected by use of the unit **30** for spatial position detection to the coordinate values (X, Y, Z) of the spatial coordinate system of the position detection region DT of the digitizer **20**. The correction information for the transformation will be described next.

$$(68) \begin{bmatrix} X \\ Y \\ Z \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{bmatrix} \begin{bmatrix} X_s \\ Y_s \\ Z_s \end{bmatrix} \quad (\text{Expression 1})$$

(Expression 1) is an expression with a matrix for linear transformation of the coordinate values (Xs, Ys, Zs) of the spatial coordinate system of the motion detection spatial region MD detected by use of the unit **30** for spatial position detection to the coordinate values (X, Y, Z) of the spatial coordinate system of the position detection region DT of the digitizer **20**. This matrix has three rows and three columns, and elements thereof are represented by a.sub.ij (i, j=1, 2, 3).

(69) In this first embodiment, by using the fact that at least part of the position detection region DT of the digitizer **20** is a spatial region in common with the motion detection spatial region MD of the unit **30** for spatial position detection, the correction information for transformation between the spatial coordinate system of the position detection region DT and the spatial coordinate system of the motion detection spatial region MD is generated.

(70) Specifically, as depicted in FIG. 3, the position is specified regarding at least three points Pa, Pb, and Pc in the spatial region common to the position detection region DT of the digitizer **20** and the motion detection spatial region MD of the unit **30** for spatial position detection, and the coordinate values (X, Y, Z) of the spatial coordinate system of the position detection region DT of the digitizer **20** and the coordinate values (Xs, Ys, Zs) of the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection regarding each point are acquired from each device. Ideally, the coordinate values acquired from these devices are the same values. However, normally these coordinate values do not correspond if calibration is not carried out. In general, the accuracy of position detection by the digitizer **20** is higher than the accuracy of position detection by use of the unit **30** for spatial position detection. Therefore, it is preferable to adjust the coordinate values of the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection to the coordinate values of the spatial coordinate system of the position detection region DT of the digitizer **20**.

(71) Per one point regarding which the position has been specified in the common region, three equations are obtained when the corresponding coordinate values (X, Y, Z) of the spatial coordinate system of the position detection region DT and the corresponding coordinate values (Xs, Ys, Zs) of the spatial coordinate system of the motion detection spatial region MD are substituted into expression 1. By carrying out position specifying of at least three points in the common region, at least nine equations regarding a.sub.11 to a.sub.33 are obtained and therefore, the value of each of a.sub.11 to a.sub.33 can be obtained. Moreover, the transformation between the spatial coordinate

system of the position detection region DT and the spatial coordinate system of the motion detection spatial region MD is not limited to the above-described method. Learning based on machine learning regarding the coordinate values of at least three points in the common region, calibration by the user, and so forth may be used.

(72) In the above-described manner, in the spatial position indication system of this embodiment, deviation between the spatial coordinate system of the position detection region DT of the digitizer **20** and the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection is corrected to allow the spatial coordinate systems to be treated as one common coordinate system. This correction processing is performed in the input information processing part **41**.

(73) Thus, in a displayed image of the HMD **50**, even when information on the indicated position of the electronic pen **10** is switched between the spatial coordinate system of the position detection region DT of the digitizer **20** and the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection, since the two systems are allowed to be treated as one common coordinate system, for example, the state in which the position indicated by the pen tip **11a** of the electronic pen **11** changes does not occur.

(74) [Switching of Spatial Coordinate System in which Indicated Position of Three-Dimensional Position Indicator **10** is Detected]

(75) In the spatial position indication system of the first embodiment, the configuration is made to have at least part of the position detection region DT of the digitizer **20** as a common region in the motion detection spatial region MD of the unit **30** for spatial position detection.

(76) Moreover, in the spatial position indication system of this embodiment, according to the separation distance of the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** in the space of the motion detection spatial region MD from the input surface **21S** of the sensor **22** of the digitizer **20**, switching is carried out regarding whether the coordinates of the indicated position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** detected by the digitizer **20** are used or the coordinates of the indicated position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** detected by the unit **30** for spatial position detection are used.

(77) In this embodiment, a separation distance (separation distance in the Z-axis direction) θ th from the input surface **21S** serving as the switching point is set equal to or shorter than a critical height distance L_z in the Z-axis direction at and under which the digitizer **20** can detect the hover state of the electronic pen **11** of the three-dimensional position indicator **10**. In this example, as depicted in FIG. **4**, the separation distance θ th from the input surface **21S** serving as the switching point is set equal to the critical height distance L_z in the Z-axis direction at and under which the digitizer **20** can detect the hover state of the electronic pen **11** of the three-dimensional position indicator **10**, i.e., the length L_z of the position detection region DT in the Z-axis direction.

(78) Specifically, in the spatial position indication system of this embodiment, as depicted in FIG. **4**, when the separation distance of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the input surface **21S** is equal to or shorter than θ th, information on the position indicated by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** detected by the digitizer **20** in the position detection region DT thereof is used.

(79) Moreover, in the spatial position indication system of this embodiment, as depicted in FIG. **4**, when the separation distance of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the input surface **21S** is longer than θ th, information on the position indicated by the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** detected by use of the unit **30** for spatial position detection is used.

(80) In this embodiment, the signal level (signal intensity) of a received signal from the electronic pen **11** in the sensor **22** of the digitizer **20** becomes a value according to the separation distance and therefore, the separation distance (separation distance in the Z-axis direction) of the position of the

pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the input surface **21S** of the sensor **22** of the digitizer **20** is detected in the input information processing part **41** on the basis of the signal level of the received signal from the electronic pen **11** obtained from the digitizer **20**.

(81) [Switching Processing in Input Information Processing Part **41**]

(82) Next, a configuration example of the input information processing part **41** in FIG. 2 configured to realize the above will be described. Specifically, the position detecting circuit **23** configuring the digitizer **20** supplies detection output of the indicated position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** to a selection circuit **411** as one input signal thereof and supplies the detection output to a selection circuit **412** as one input signal thereof. In this information supplied from the position detecting circuit **23** to the selection circuits **411** and **412**, information on the writing pressure applied to the pen tip **11a** of the electronic pen **11** is included in addition to the detection output of the indicated position of the pen tip **11a** of the electronic pen **11**.

(83) Moreover, the indicated position calculating circuit **4102** of the spatial position detecting circuit **410** supplies detection output of the spatial position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** (indicated position of the electronic pen **11**) to a coordinate transformation circuit **413**. The coordinate transformation circuit **413** stores the elements a.sub.11 to a.sub.33 of the matrix of three rows and three columns in the above-described (Expression 1) and transforms information on the spatial coordinate system of the motion detection spatial region MD of the unit **30** for spatial position detection to information on the spatial coordinate system of the position detection region DT of the digitizer **20** by carrying out arithmetic operation of the above-described (Expression 1). Then, the coordinate transformation circuit **413** supplies coordinate output obtained after the transformation to the selection circuits **411** and **412** as the other input signal thereof.

(84) Further, in this embodiment, the position detecting circuit **23** of the digitizer **20** supplies information on the signal level of the received signal from the electronic pen **10** to a selection control signal generating circuit **414**. The selection control signal generating circuit **414** detects the separation distance of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the input surface **21S** of the digitizer **20** from the signal level of the received signal from the electronic pen **10**, and generates a selection control signal SE on the basis of the detected separation distance from the input surface **21S**. The generated selection control signal SE is supplied to the selection circuits **411** and **412**.

(85) Further, by the selection control signal SE, the selection circuits **411** and **412** are controlled to select the position detection output from the position detecting circuit **23** of the digitizer **20** when the separation distance of the pen tip **11a** of the electronic pen **11** from the input surface **21S** of the digitizer **20** is equal to or shorter than the critical height L_z in the Z-axis direction at and under which the digitizer **20** can detect the hover state of the electronic pen **11**, and are controlled to select the output from the coordinate transformation circuit **413** when the separation distance is longer than the above-described critical height L_z .

(86) Further, the information on the indicated position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the selection circuit **411** is supplied to the rendering image generating circuit **421** for the 3D rendering-related processing and the gesture detection processing circuit **423**. In addition, the information on the indicated position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the selection circuit **412** is supplied to the VR image generating circuit **422** for the VR image-related processing.

(87) Furthermore, information on the posture of the electronic pen **11** from the indicated position calculating circuit **4102** of the spatial position detecting circuit **410** and operation information of the operation part of the three-dimensional position indicator **10** from the operation information detecting circuit **4104** are supplied to each of the rendering image generating circuit **421**, the

gesture detection processing circuit **423**, and the VR image generating circuit **422**. In addition, position information and posture information of the digitizer **20** from the digitizer detecting circuit **4103** are supplied to each of the rendering image generating circuit **421** and the VR image generating circuit **422**. As described below, in the rendering image generating circuit **421**, the posture information of the digitizer **20** is used to transform the information on the posture of the electronic pen **11** to information on the relative posture with respect to the input surface of the digitizer **20**.

(88) [Processing Operation of Display Image Generating Part **42**]

(89) The rendering image generating circuit **421** has a pen rendering function of rendering a fine line drawing and so forth based on the detection output of the indicated position of the pen tip **11a** of the electronic pen **11** and the information on the posture of the electronic pen **11** detected by the unit **30** for spatial position detection from the selection circuit **411**. Moreover, the rendering image generating circuit **421** has a gesture processing function of performing rendering processing based on motion (gesture) detected by the gesture detection processing circuit **423**, on the basis of the information on the spatial position of the electronic pen **11** and the posture of the electronic pen detected by the unit **30** for spatial position detection.

(90) In this example, the selection control signal SE from the selection control signal generating circuit **414** is supplied to the rendering image generating circuit **421** and the gesture detection processing circuit **423**. Accordingly, the rendering image generating circuit **421** operates to perform the pen rendering function when the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** exists in the spatial region of the position detection region DT of the digitizer **20**. Moreover, the gesture detection processing circuit **423** operates to perform gesture processing when the position of the pen tip **11a** of the electronic pen **11** exists outside the spatial region of the position detection region DT of the digitizer **20**.

(91) In this case, in the rendering image generating circuit **421**, the tilt included in the information on the posture of the electronic pen **11** is reflected in the thickness of the rendering line and so forth. As the tilt, the tilt with respect to the input surface **21S** of the digitizer **20** needs to be used, when the position of the pen tip **11a** of the electronic pen **11** exists in the position detection region DT.

(92) However, the information on the posture of the electronic pen **11** from the indicated position calculating circuit **4102** is one that has been detected by use of the unit **30** for spatial position detection. Therefore, the information is not one that illustrates the tilt with respect to the input surface **21S** of the digitizer **20** if the surface direction of the input surface **21S** of the digitizer **20** deviates from the surface direction of the X-Y plane in the motion detection spatial region MD in the unit **30** for spatial position detection.

(93) As such, the rendering image generating circuit **421** of this embodiment has a processing function of correcting the tilt of the electronic pen **11** detected in the coordinate system of the motion detection spatial region MD of the spatial position detecting circuit **410** to the relative tilt with respect to the input surface of the digitizer **20**, by using the posture information of the digitizer **20** from the digitizer position detecting circuit **4103**.

(94) Moreover, the rendering image generating circuit **421** and the gesture detection processing circuit **423** also perform processing based on the operation information of the operation part of the three-dimensional position indicator **10** from the operation information detecting circuit **4104**.

(95) The VR image generating circuit **422** of the display image generating part **42** generates a VR image of the electronic pen **11** by using the information on the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** and the information on the posture of the electronic pen **11** from the selection circuit **412**. This VR image of the electronic pen **11** is generated in such a manner that the position of the pen tip **11a** of the electronic pen **11** is displayed at the detected indicated position.

(96) In this case, the information on the indicated position of the pen tip **11a** of the electronic pen

11 from the spatial position detecting circuit **410** is subjected to coordinate transformation by the coordinate transformation circuit **413** so as to become information on the same indicated position as the digitizer **20**. Thus, the information on the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** from the selection circuit **412** does not change when switching is carried out in the selection circuit **412** based on the selection control signal SE. Therefore, display deviation such as movement of the display position of the VR image of the electronic pen **11** in a jumping manner does not occur.

(97) Further, in this embodiment, the VR image generating circuit **422** generates a VR image of the digitizer **20**, based on the information on the position and posture of the digitizer **20** from the digitizer detecting circuit **4103**, and displays the VR image in the motion detection spatial region MD. Moreover, the VR image generating circuit **422** further accepts the operation information of the operation part of the three-dimensional position indicator **10** from the operation information detecting circuit **4104** to carry out VR displaying of a menu regarding 3D rendering and to display a VR image of operation buttons, for example. In the rendering image generating circuit **421**, the positions of these VR images of the menu and the operation buttons in the motion detection spatial region MD are recognized, and whether or not the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** has indicated (same as click) these VR image positions can be detected so that corresponding processing can be performed.

(98) Furthermore, the 3D rendering image information generated in the rendering image generating circuit **421** in the above-described manner is supplied to the VR image generating circuit **422** and is turned to a VR image. This VR image is supplied to the HMD **50** through a display drive circuit **424** and is displayed together with the above-described VR image.

(99) [Configuration Example of Three-Dimensional Position Indicator **10**]

(100) Next, a configuration example of the three-dimensional position indicator **10** of this embodiment will be described with reference to FIG. 5 to FIG. 7. FIG. 5 is a perspective view illustrating the appearance of the three-dimensional position indicator **10** of this embodiment. In addition, FIGS. 6A, 6B, and 6C depict diagrams for explaining constituent parts of the three-dimensional position indicator **10** of this embodiment and assembly thereof.

(101) The three-dimensional position indicator **10** of this embodiment includes the electronic pen **11** depicted in FIG. 6A and a holder **13** that configures a grip part gripped by a user. The tracker **12** that configures the spatial position index part is mounted to the holder **13**.

(102) In the electronic pen **11** in this example, as depicted in FIG. 6B, the tip part of a core body protrudes as the pen tip **11a** from one opening side of a bar-shaped casing **110** with a circular cylindrical shape in the axis center direction. Although diagrammatic representation is omitted, a coil wound around a ferrite core in a well-known manner is disposed in the vicinity of the pen tip **11a** in a hollow part of the circular cylindrical casing **110** of the electronic pen **11**. In addition, a capacitor connected in parallel to the coil to configure a resonant circuit is disposed on a printed circuit board disposed in the hollow part. Moreover, in the electronic pen **11** in this example, a side switch **11s** that controls the on/off-state of the capacitor for changing the frequency of the resonant circuit is disposed to be exposed from the casing **110** so as to be allowed to be operated by the user.

(103) The holder **13** includes a grip part **131** configured to be covered by a palm part when the user grips the three-dimensional position indicator **10**, an electronic pen mounting part **132**, and a tracker mounting part **133**.

(104) The electronic pen mounting part **132** has a circular cylindrical shape and includes a tubular recessed hole part **132a** configured in such a manner that the electronic pen **11** is inserted in the axis center direction thereof from a rear end part **11b** on the side opposite the side of the pen tip **11a** and is locked to the holder **13**. The tubular recessed hole part **132a** has such a length in the axis center direction that, when the electronic pen **11** is inserted and mounted, the electronic pen **11** is held in the state in which the side of its pen tip **11a** is exposed and the side switch **11s** is exposed on the outside to be operable.

(105) Moreover, in the electronic pen **11** in this example, a ring-shaped recessed groove **11c** is made on the side of the rear end part **11b** in the axis center direction as depicted in FIG. 6A. In addition, in the tubular recessed hole part **132a**, a ring-shaped protrusion **132b** for being fitted to the ring-shaped recessed groove **11c** of the electronic pen **11** to lock the electronic pen **11** in the tubular recessed hole part **132a** is formed.

(106) In this example, a step part **11d** is formed on the side of the rear end part **11b** of the electronic pen **11**, and the configuration is made in such a manner that the ring-shaped recessed groove **11c** of the electronic pen **11** is fitted to the ring-shaped protrusion **132b** in the tubular recessed hole part **132a** and the electronic pen **11** is locked in the tubular recessed hole part **132a** of the electronic pen mounting part **132** when this step part **11d** abuts against an end part of the tubular recessed hole part **132a**. The configuration that locks the electronic pen **11** in the tubular recessed hole part **132a** of the electronic pen mounting part **132** is not limited to the configuration in which the ring-shaped recessed groove **11c** and the ring-shaped protrusion **132b** are disposed as in this example. The configuration may be any configuration as long as it is a configuration that can lock the electronic pen **11** in the tubular recessed hole part **132a** of the electronic pen mounting part **132** when the step part **11d** on the side of the rear end part **11b** of the electronic pen **11** abuts against the end part of the tubular recessed hole part **132a**.

(107) The grip part **131** is extended in a direction orthogonal to the axis center direction from the circumferential side surface of the electronic pen mounting part **132** with the circular cylindrical shape and is configured into a shape that can easily be gripped by the user. In the grip part **131**, operation buttons **131a** and **131b** are disposed at places at which operation by a forefinger or the like is possible when the user grips the grip part **131**. In addition, an operation part **131c** allowed to be subjected to rotational operation and pressing-down operation by the ball of the thumb of the user is disposed. In this example of the three-dimensional position indicator **10** depicted in FIG. 5 and FIGS. 6A, 6B, and 6C, the three-dimensional position indicator **10** is depicted as one for a left-handed user and the circular operation part **131c** is attached to be operable by the thumb of the left hand when the grip part **131** is gripped with the left hand.

(108) Furthermore, the tracker mounting part **133** is attached to be extended in a direction orthogonal to the axis center direction from an angular position that is different by 180 degrees from and is on the side opposite the angular position at which the grip part **131** is formed on the circumferential side surface of the electronic pen mounting part **132** with the circular cylindrical shape. The above-described tracker **12** is set for the tracker mounting part **133**. Therefore, when the user grips the grip part **131** in such a manner as to wrap it by a palm, the tracker **12** attached to the tracker mounting part **133** is located on the upper side of the back of the hand and is in the state of not being covered by the hand.

(109) In this example, the tracker **12** is formed into a shape including three protrusions on an upper surface (flat surface) **12a** of a circular-plate-shaped member as depicted in FIG. 5. In the tracker **12**, as depicted in FIG. 5, FIG. 6B, and FIG. 6C, plural light receiving sensors **121** are disposed on the three protrusions and the circular-plate-shaped member so that an infrared laser can be received whichever direction the infrared laser comes from. Furthermore, on one of the three protrusions of the tracker **12**, an LED **122** as a light emitting element for giving notification of reception of the infrared laser by light emission when the infrared laser is received by any of the light receiving sensors **121** is disposed. The nine-axis sensor is disposed inside the tracker **12**.

(110) Although diagrammatic representation is omitted, in the case of connecting the tracker **12** and the spatial rendering information generating device **40** in a wired manner, a connector to which a cable for connection to the spatial rendering information generating device **40** is connected is disposed in the tracker **12**. Moreover, in the case of a wireless connection, communication means is disposed inside the tracker **12**.

(111) Further, in this example, as depicted in FIGS. 6B and 6C, the tracker **12** is attached in such a manner that the surface direction of the upper surface **12a** of the circular-disc-shaped member

(direction in which the plane including the upper surface **12a** is oriented) is in the state of being orthogonal to the extension direction of the tracker mounting part **133** and is in the state of being parallel to the axis center direction of the electronic pen mounting part **132** with the circular cylindrical shape. In addition, the LED **122** is attached on the extension direction of the tracker mounting part **133**.

(112) As described above, by use of the unit **30** for spatial position detection, in the position indicator detecting circuit **4101** of the spatial position detecting circuit **410**, a position Pt of the LED **122** disposed in the tracker **12** is detected as the position of the tracker **12** in the spatial coordinate system of the motion detection spatial region MD. Moreover, in the position indicator detecting circuit **4101**, as described above, the surface direction of the upper surface **12a** of the tracker **12** (direction in which the plane including the upper surface is oriented) is detected as the orientation (direction) of the three-dimensional position indicator **10**, in this example.

(113) As is apparent from FIG. 5, the position Pt of the tracker **12** detected by the position indicator detecting circuit **4101** of the spatial position detecting circuit **410** is different from a position Pp of the pen tip **11a** of the electronic pen **11** mounted to the holder **13**. However, the position Pt of the tracker **12** (position of the LED **122**) detected by the position indicator detecting circuit **4101** of the spatial position detecting circuit **410** and the position Pp of the pen tip **11a** of the electronic pen **11** mounted to the holder **13** are in a specific positional relation in the three-dimensional position indicator **10**.

(114) Here, a three-dimensional coordinate system that defines the mechanical configuration of the three-dimensional position indicator **10** is configured as follows. As depicted in FIG. 5, the position Pt of the tracker **12** is defined as the origin. The direction that is parallel to the upper surface **12a** of the tracker **12** and is parallel to the axis center direction of the electronic pen mounting part **132** with the circular cylindrical shape is defined as a coordinate axis Zt. The direction that is parallel to the upper surface **12a** of the tracker **12** and is orthogonal to the axis center direction of the electronic pen mounting part **132** with the circular cylindrical shape is defined as a coordinate axis Yt. The direction orthogonal to the upper surface **12a** of the tracker **12** (direction orthogonal to the coordinate axes Zt and Yt) is defined as a coordinate axis Xt. Since the configuration is made in this manner, the position Pt of the tracker **12** detected by the position indicator detecting circuit **4101** of the spatial position detecting circuit **410** and the position Pp of the pen tip **11a** of the electronic pen **11** mounted to the holder **13** are in a positional relation as that depicted in FIG. 7.

(115) Specifically, in the space of the coordinate axes Xt, Yt, and Zt, the position Pp of the pen tip **11a** of the electronic pen **11** mounted to the holder **13** is a position that deviates from the position Pt of the tracker **12** by $-\Delta x$ in the direction of the coordinate axis Xt and deviates therefrom by $+\Delta z$ in the direction of the coordinate axis Zt. Moreover, deviation Δy in the direction of the coordinate axis Yt is 0 ($\Delta y=0$). Therefore, by using these values as correction values COR ($=(-\Delta x, \Delta y (=0), +\Delta z)$), the position Pp of the pen tip **11a** of the electronic pen **11** can be calculated from the position Pt of the tracker **12**.

(116) In this embodiment, because the three-dimensional position indicator **10** is mechanistically configured in the above-described manner, the deviation amount Δx in the above-described Xt-axis direction and the deviation amount Δz in the above-described Zt-axis direction can be prescribed as mechanical dimension values of the three-dimensional position indicator **10**. Specifically, Δx is obtained as the dimension from the position of the LED **122** to the position of the center axis of the electronic pen mounting part **132**, and Δz is obtained as the dimension from the position of the intersection of the position of the LED **122** and the position of the center axis of the electronic pen mounting part **132** to the tip part of the pen tip **11a** of the electronic pen **11**.

(117) In this case, the position Pt of the tracker **12** detected by the spatial position detecting circuit **410** with use of the unit **30** for spatial position detection is the spatial coordinate system (Xs, Ys, Zs) in the spatial position detecting circuit **410**, and that the directions of the coordinate axes of the abovementioned spatial coordinate system do not necessarily correspond with those of the three-

dimensional coordinate system (Xt, Yt, Zt) that defines the above-described mechanical configuration of the three-dimensional position indicator **10** needs to be taken into consideration. This is because the three-dimensional position indicator **10** is used while being oriented in any direction by the user.

(118) However, in this embodiment, the orientation of the three-dimensional position indicator **10** detected by the position indicator detecting circuit **4101**, i.e., the direction in which the upper surface **12a** of the tracker **12** is oriented (direction orthogonal to the upper surface **12a**), is detected by the spatial position detecting circuit **410** by use of the unit **30** for spatial position detection. Then, when this direction in which the upper surface **12a** of the tracker **12** is oriented can be detected, the directions of the respective coordinate axes of the three-dimensional coordinate system (Xt, Yt, Zt) that defines the above-described mechanical configuration of the three-dimensional position indicator **10** can be identified in the spatial coordinate system (Xs, Ys, Zs) in the spatial position detecting circuit **410**.

(119) When the directions of the respective coordinate axes of the three-dimensional coordinate system (Xt, Yt, Zt) that defines the mechanical configuration of the three-dimensional position indicator **10** can be identified in the spatial coordinate system (Xs, Ys, Zs) in the spatial position detecting circuit **410** in this manner, the indicated position of the pen tip **11a** of the electronic pen **11** in the spatial coordinate system (Xs, Ys, Zs) of the spatial position detecting circuit **410** can be calculated from the position Pt of the tracker **12** detected by the position indicator detecting circuit **4101** of the spatial position detecting circuit **410**, by use of the above-described correction values COR.

(120) Based on the above, the above-described correction values COR ($=(-\Delta x, \Delta y (=0), +\Delta z)$) are stored in the correction memory **4102M** included in the indicated position calculating circuit **4102** of the spatial position detecting circuit **410**. Moreover, in the indicated position calculating circuit **4102**, by using the orientation of the three-dimensional position indicator **10** detected by the position indicator detecting circuit **4101** and the above-described correction values COR stored in the correction memory **4102M**, the indicated position of the pen tip **11a** of the electronic pen **11** is calculated from the position Pt of the tracker **12** of the three-dimensional position indicator **10** in the above-described manner.

(121) In the three-dimensional position indicator **10** depicted in FIG. 5 and FIGS. 6A, 6B, and 6C, the configuration is made in such a manner that the positional relation between the tracker **12** and the electronic pen mounting part **132** and the electronic pen **11** becomes as described above, in order to allow the correction values COR to be set easily from mechanical dimension values of the three-dimensional position indicator **10**. However, the tracker **12** may be attached to the holder **13** in any state.

(122) In this case, the correction values COR can be obtained in the following manner and be stored in the correction memory **4102M**.

(123) Specifically, in the space of the motion detection spatial region MD, through adjustment of the orientation of the tracker **12**, the three-dimensional position indicator **10** is set to the state in which the directions of the respective coordinate axes of the three-dimensional coordinate system (Xt, Yt, Zt) that defines the mechanical configuration of the three-dimensional position indicator **10** correspond with the directions of the respective coordinate axes of the spatial coordinate system (Xs, Ys, Zs) in which detection is carried out by the spatial position detecting circuit **410** with use of the unit **30** for spatial position detection.

(124) Then, the position Pp of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** is detected by use of the digitizer **20**, and the detected coordinate values are transformed to coordinate values of the spatial coordinate system (Xs, Ys, Zs) in which detection is carried out by the spatial position detecting circuit **410** with use of the unit **30** for spatial position detection. This transformation is the inverse transformation of the transformation depicted in Expression 1. Moreover, the position Pt of the tracker **12** of the three-dimensional position

indicator **10** is detected as coordinate values of the spatial coordinate system (X_s , Y_s , Z_s) in which detection is carried out by the spatial position detecting circuit **410**.

(125) Then, the deviation amounts (Δx , Δy , Δz) between the coordinate values of the detected position P_t of the tracker **12** and the coordinate values of the position P_p of the pen tip **11a** of the electronic pen **11** are calculated, and the calculated deviation amounts (Δx , Δy , Δz) are stored in the correction memory **4102M** as the correction values COR.

(126) This storing processing of the correction values COR into the correction memory **4102M** may be performed when the spatial position detection system is constructed or may be performed later by the user as appropriate.

(127) As described above, in the spatial position detection system of the above-described embodiment, rendering is carried out in the digitizer **20** by use of the three-dimensional position indicator **10**. In addition, in the case of carrying out gesture operation or the like in the space defined by the unit **30** for spatial position detection, the position of the pen tip **11a** of the electronic pen **11** of the three-dimensional position indicator **10** can always be used as the indicated position. This provides an effect that the user can carry out operation work with consistency kept from rendering to gesture.

(128) Moreover, in the above-described first embodiment, spatial coordinates of the detection region of the digitizer **20** and spatial coordinates of the detection region of the unit **30** for spatial position detection are allowed to be treated as common coordinates. Therefore, there is a characteristic that coordinate deviation does not occur even when switching is carried out between output from the digitizer **20** and output of the unit **30** for spatial position detection, in the 3D rendering-related processing.

(129) Therefore, the operator can carry out operation by gesture from fine rendering seamlessly by only spatially moving the electronic pen **10** over the digitizer **20** without taking heed of switching between the digitizer **20** and the unit **30** for spatial position detection.

(130) Further, in the VR image-related processing in the above-described first embodiment, in the spatial region of the position detection region DT of the digitizer **20**, position detection output of the digitizer **20**, which allows higher accuracy than detection output in the unit **30** for spatial position detection and is also higher in response speed, can be used as position information of the electronic pen **11** (position information of the pen tip **11a**) for generating a VR image of the electronic pen **11** of the three-dimensional position indicator **10**. Thus, the VR image that precisely reacts to operation of the electronic pen **11** by the actual user is obtained.

(131) Since the above-described spatial rendering information generating device **40** includes a computer, it goes without saying that the part of each circuit of the input information processing part **41** and the display image generating part **42** can be configured as a software functional part implemented by a software program.

(132) In the above-described first embodiment, information on the correction values (Δx , Δy , Δz) is stored in advance in the correction memory **4102M** of the indicated position calculating circuit **4102** at the time of factory shipment or the like. However, this correction memory **4102M** may be set as a buffer memory, and information on the correction values may be transmitted thereto from the three-dimensional position indicator **10**.

(133) In this case, the configuration is made in such a manner that, for example, as depicted in FIG. **8**, information on the above-described correction values (Δx , Δy , Δz) is transmitted from the three-dimensional position indicator **10** to the spatial position detecting circuit **410** in addition to information on light reception output of the light receiving sensors of the tracker **12**, output information of the nine-axis sensor, and operation information of the operation buttons **131a** and **131b**. Moreover, in the indicated position calculating circuit **4102** of the spatial position detecting circuit **410**, the position of the pen tip **11a** of the electronic pen **11** is detected as the indicated position of the three-dimensional position indicator **10** by use of the correction values held in the correction memory **4102M** as the buffer memory. In FIG. **8**, "ID" means identification information

of the three-dimensional position indicator **10**.

(134) If the configuration is made as above, it becomes possible to use what are different in the amount of deviation between the position of the tracker **12** and the position of the pen tip **11a** of the electronic pen **11**, as the three-dimensional position indicator used in the spatial position detection system. Further, it also becomes possible to mount plural kinds of electronic pens different in the length in the axis center direction to the three-dimensional position indicator **10**. However, in this case, the correction values corresponding to each of the electronic pens different in the length dimension in the axis center direction are stored in the three-dimensional position indicator **10**. In addition, the user is allowed to carry out selective setting of which correction values in them are used, according to the mounted electronic pen, by operating operation means.

(135) In the three-dimensional position indicator **10** of the above-described first embodiment, the electronic pen **11** is allowed to be inserted and removed. However, the electronic pen **11** may be fixed to the holder **13**. Moreover, instead of using the electronic pen **11** as the bar-shaped part, the bar-shaped part may be configured integrally with the holder **13** by disposing, in the bar-shaped part, the functional parts of the electronic pen **11**, i.e., a coil wound around a ferrite core and a capacitor connected in parallel to this coil to configure a resonant circuit.

Second Embodiment

(136) A second embodiment is a modification example of the above-described first embodiment. The same parts as the respective parts of the above-described first embodiment are given the same reference symbols, and description thereof is omitted.

(137) In the three-dimensional position indicator **10** of the above-described first embodiment, the position of the pen tip **11a** of the electronic pen **11** is always used as the position indicated by the three-dimensional position indicator **10**. However, the configuration may be made in such a manner that the position of the tracker **12** is used as the indicated position and that use for another purpose is enabled when the electronic pen **11** is not mounted to the holder **13**.

(138) Specifically, in a three-dimensional position indicator **10A** of this second embodiment, when the electronic pen **11** is mounted to a holder **13A**, the position of the pen tip **11a** of the mounted electronic pen **11** is used as the indicated position similarly to the first embodiment. However, when the electronic pen **11** is not mounted to the holder **13A**, the position of the tracker **12** is used as the indicated position directly.

(139) FIG. **9** is a diagram for explaining a configuration example of part of the three-dimensional position indicator **10A** of this second embodiment. FIG. **9** illustrates a sectional view of one part of the grip part **131**, the electronic pen mounting part **132**, and the tracker mounting part **133** of the holder **13A** of the three-dimensional position indicator **10A** of this second embodiment.

(140) In this second embodiment, mounting detecting means that detects whether or not the electronic pen **11** is mounted is disposed in the holder **13A** of the three-dimensional position indicator **10A**. Moreover, mounting detection output of the electronic pen **11** in this mounting detecting means is notified to a spatial position detecting circuit **410A** (see FIG. **10**) of a spatial rendering information generating device **40A** in this second embodiment together with light reception output of light receiving sensors and so forth through the tracker **12**, in this example. The configuration may of course be made in such a manner that the mounting detection output of the electronic pen **11** from the mounting detecting means is notified to the spatial position detecting circuit **410A** of the spatial rendering information generating device **40A** not through the tracker **12** but independently.

(141) In this example, as depicted in FIG. **9**, a switch member **134** including a pressing element **134a** capable of being elastically deformed in a direction of an arrow AR is used as the mounting detecting means. The switch member **134** is in a switch-off state, for example, in the state in which the pressing element **134a** is not pressed and protrudes to the outside of a casing of the switch member **134**. The switch member **134** is in a switch-on state in the state in which the pressing element **134a** is pressed to be pushed into the casing of the switch member **134**.

(142) Therefore, when the electronic pen **11** is inserted into a tubular recessed hole part **132Aa** of the electronic pen mounting part **132A** as depicted in FIG. **9**, the pressing element **134a** of the switch member **134** is pressed down by the casing of this electronic pen **11** and the switch state of the switch member **134** changes (in this example, from switch-off to switch-on). Moreover, the switch state in the switch member **134** is supplied to the spatial position detecting circuit **410A** of the spatial rendering information generating device **40A** through the tracker **12**, as the mounting detection output of the electronic pen **11**.

(143) In FIG. **10**, a configuration example of particularly the spatial position detecting circuit **410A** of the spatial rendering information generating device **40A** in the case of this second embodiment is depicted. Also in the example of FIG. **10**, the same part as the spatial rendering information generating device **40** and the spatial position detecting circuit **410** of the above-described first embodiment is given the same reference symbol, and detailed description thereof is omitted.

(144) In the spatial position detecting circuit **410A** of this second embodiment, an electronic pen mounting detecting circuit **4105** and a switch circuit **4106** are disposed in addition to the above-described position indicator detecting circuit **4101**, indicated position calculating circuit **4102**, digitizer detecting circuit **4103**, and operation information detecting circuit **4104**.

(145) The electronic pen mounting detecting circuit **4105** receives and analyzes the mounting detection output of the electronic pen **11** from the three-dimensional position indicator **10A** and detects whether or not the electronic pen **11** is mounted to the electronic pen mounting part **132** to output mounting detection output DP as the detection result thereof.

(146) To one input terminal T of the switch circuit **4106**, information TI on the position of the tracker **12** of the three-dimensional position indicator **10A** detected by the position indicator detecting circuit **4101** is supplied. To the other input terminal P, information PI on the position of the pen tip **11a** of the mounted electronic pen **11** calculated by the indicated position calculating circuit **4102** is supplied.

(147) Further, the mounting detection output DP of the electronic pen mounting detecting circuit **4105** is supplied to the switch circuit **4106**, as a switching control signal. Based on the mounting detection output DP, when the electronic pen **11** is not mounted in the three-dimensional position indicator **10A**, the switch circuit **4106** is switched to the side of the one input terminal T and the information TI on the position of the tracker **12** is output as the output information. When the electronic pen **11** is mounted in the three-dimensional position indicator **10A**, the switch circuit **4106** is switched to the side of the other input terminal P and the information PI on the position of the pen tip **11a** of the electronic pen **11** is output as the output information. Then, the output information of the switch circuit **4106** is supplied to the coordinate transformation circuit **413**.

(148) Further, the mounting detection output DP of the electronic pen mounting detecting circuit **4105** is supplied to a VR image generating circuit **422A**. When determining that the electronic pen **11** is mounted in the three-dimensional position indicator **10A** based on the mounting detection output DP, the VR image generating circuit **422A** generates a VR image of the electronic pen **11** similarly to the above-described first embodiment and displays the VR image on the HMD **50**. Moreover, when determining that the electronic pen **11** is not mounted in the three-dimensional position indicator **10A** based on the mounting detection output DP, in this second embodiment, the VR image generating circuit **422A** does not generate a VR image of the electronic pen **11** but generates, for example, a VR image of the tracker **12** or a predetermined mark at the position of the detected tracker **12** and displays it on the HMD **50**.

(149) In the above-described manner, in the second embodiment, the same operation as in the first embodiment is carried out only when the electronic pen **11** is mounted in the three-dimensional position indicator **10A**. Moreover, when the electronic pen **11** is not mounted in the three-dimensional position indicator **10A**, it is possible to use the three-dimensional position indicator **10A** as another use application using the tracker position.

(150) In the above-described example, the switch member **134** is disposed as the mounting

detecting means for automatically detecting mounting when the electronic pen **11** is mounted to the electronic pen mounting part **132A** of the holder **13** of the three-dimensional position indicator **10A**. However, the mounting detecting means is not limited to the switch member **134**.

(151) Moreover, although the mounting detecting means for automatically detecting mounting when the electronic pen **11** is mounted to the electronic pen mounting part **132A** of the holder **13** of the three-dimensional position indicator **10A** is disposed in the above-described second embodiment, the mounting of the electronic pen **11** may be notified to the spatial position detecting circuit **410A** of the spatial rendering information generating device **40A** not by the mounting detecting means but by operation by the user.

(152) Furthermore, in the case of the example in which the user gives notification of the mounting of the electronic pen **11** in the three-dimensional position indicator by operating the operation part of the three-dimensional position indicator **10**, even when the electronic pen **11** is not actually mounted, a VR image of the electronic pen **11** can be generated in the VR image generating circuit **422A** and be displayed on the HMD **50**, based on the assumption that the electronic pen **11** is virtually mounted in the three-dimensional position indicator **10**.

MODIFICATION EXAMPLES OF ABOVE-DESCRIBED EMBODIMENTS

(153) In the three-dimensional position indicator **10** of the above-described embodiment, the configuration in which the holder **13** includes the grip part **131** is employed. However, as depicted in FIGS. **11A**, **11B**, and **11C**, a three-dimensional position indicator **10B** including a holder **13B** that does not include the grip part **131** but includes the electronic pen mounting part **132** and the tracker mounting part **133** may be configured. The three-dimensional position indicator **10B** has the same configuration as the three-dimensional position indicator **10** described by using FIG. **5** and FIGS. **6A**, **6B**, and **6C** except that the configuration of the holder is changed as depicted by being given the same reference symbols in FIGS. **11A**, **11B**, and **11C**.

(154) In the case of the three-dimensional position indicator **10B**, the operation buttons **131a** and **131b** depicted in FIG. **5** and FIGS. **6A**, **6B**, and **6C** may be disposed in the electronic pen mounting part **132**. Moreover, also in the three-dimensional position indicator **10B**, the electronic pen **11** may be fixed to the holder **13B**. In addition, instead of using the electronic pen **11** as the bar-shaped part, the bar-shaped part may be configured integrally with the holder **13B** by disposing the functional parts of the electronic pen **11** in the bar-shaped part. Furthermore, it goes without saying that the configuration of the three-dimensional position indicator **10B** depicted in FIGS. **11A**, **11B**, and **11C** can also be applied to the case of the second embodiment.

(155) In the above-described embodiments, the unit **30** for spatial position detection is given the configuration including the light emission tracing devices that emit infrared laser light and the trackers. However, it goes without saying that the unit **30** for spatial position detection is not limited to this configuration. For example, a configuration using another invisible light sensor, a visible light beam sensor, or a combination of them may be employed.

(156) In addition, a configuration in which a battery is disposed in an electronic pen, transmitting-receiving means of radio waves is disposed therein, and the spatial position of the electronic pen is detected by transmitting radio waves to the electronic pen from the outside and receiving radio waves from this electronic pen may be employed. Moreover, one that uses magnetic resonance or one that uses ultrasonic waves may be employed. Further, a configuration in which a target object (electronic pen or tablet) with respect to which the spatial position is detected is photographed by one or plural cameras and the spatial position of the target object is detected by using the photographed image thereof may be employed.

(157) Further, in the above-described embodiments, the configuration is made in such a manner that a VR image of the digitizer **20** is generated and the operator recognizes the position of the digitizer **20** on the display screen of the HMD **50**. However, a configuration may of course be made in such a manner that what is compatible with AR (Augmented Reality) is employed as the HMD and the digitizer **20** can be directly viewed.

(158) Further, in the explanation of the above-described embodiments, gesture based on motion of the electronic pen is detected in the spatial region outside the position detection region DT of the digitizer. However, it is also possible to detect not motion of the electronic pen but the position indicated by the pen tip of the electronic pen and use the position for rendering in the outside spatial region as well.

(159) Further, in the above-described embodiments, the separation distance of the position of the pen tip **11a** of the electronic pen **11** from the input surface of the digitizer **20** is detected based on the reception level of a signal between the sensor **22** of the digitizer **20** and the electronic pen **11**. However, the method for detecting the separation distance between the pen tip **11a** of the electronic pen **11** and the input surface of the digitizer **20** is not limited thereto.

(160) For example, in the unit **30** for spatial position detection, the position of the pen tip **11a** of the electronic pen **10** and the position of the input surface **21S** of the digitizer **20** can be detected. Therefore, the separation distance between the position of the pen tip **11a** of the electronic pen **11** and the input surface **21S** of the digitizer **20** may be detected from the detected position of the pen tip **11a** of the electronic pen **11** and the detected position of the input surface **21S** of the digitizer **20**, and the selection control signal of the selection circuit **401** may be generated.

(161) Further, means for displaying a three-dimensional image is not limited to the HMD, and a 3D display, an AI (Aerial Imaging) plate, and a hologram technique may be used. In addition, a display such as an LCD, for example, may be disposed for the digitizer **20**, and 3D displaying may be carried out in the display. These kinds of display means may be used together with the HMD and be employed as one that is for allowing a person other than the person who wears the HMD to view a rendering image displayed on the HMD.

(162) Further, in transformation of coordinates, coordinate values of the pen tip of the electronic pen detected by the unit **30** for spatial position detection are transformed to coordinate values of the coordinate system in the digitizer **20**. However, conversely, coordinate values of the pen tip of the electronic pen detected by the digitizer **20** may be transformed to coordinate values of the coordinate system in the unit **30** for spatial position detection.

(163) Further, in the above-described embodiments, as the electronic pen and the digitizer, ones of the electromagnetic induction system are used. However, they are not limited thereto and it is of course also possible to use electronic pens and digitizers of the capacitive system (including active capacitive coupling system and passive capacitive coupling system) or another system.

(164) Furthermore, the digitizer of the above-described embodiments may be a portable mobile phone terminal referred to as what is generally called a smartphone or may be a personal computer with a digitizer.

(165) In the above explanation, the case of carrying out 3D rendering by the spatial position indication system is described. However, the rendering image as the target of the disclosure may be a 2D rendering image or 2.5D rendering image.

DESCRIPTION OF REFERENCE SYMBOLS

(166) **10** Three-dimensional position indicator **11** Electronic pen **11a** Pen tip of the electronic pen **11** **12** Tracker **13** Holder **20** Digitizer **22** Position detecting sensor **23** Position detecting circuit **24A**, **24B** Tracker **30** Unit for spatial position detection **31A**, **31B** Light emission tracing device **40** Spatial rendering information generating device **41** Input information processing part **42** Display image generating part **50** HMD **131** Grip part **132** Electronic pen mounting part **133** Tracker mounting part **410** Spatial position detecting circuit **413** Coordinate transformation circuit **421** Rendering image generating circuit **422** VR image generating circuit

Claims

1. A position indicator that indicates a position in a three-dimensional (3D) space, the position indicator comprising: an elongated casing; a position indicating part which is disposed at one end

of the elongated casing and which, in operation, indicates the position; a grip part that extends in a first direction intersecting a second direction in which an axis of the elongated casing extends and is configured to be gripped with a palm of a user in a state in which the elongated casing is gripped between fingers of the user; and a tracker which, in operation, causes an external device to detect a tracker position of the tracker in the 3D space, wherein the tracker is disposed so as to be not covered by the user's hand when the user palm-grips the grip part; wherein the tracker position of the tracker and a position of the position indicating part are in a specific positional relation.

2. The position indicator according to claim 1, wherein: the tracker includes a Light Emitting Diode.

3. The position indicator according to claim 1, wherein: the grip part includes an operation part operable by the user, and the position indicator further comprises a communication circuit which, in operation, communicates with the external device in response to operation of the operation part.

4. The position indicator according to claim 1, wherein: the elongated casing includes an operation part operable by the user.

5. The position indicator according to claim 1, wherein: the tracker is disposed so as to face the grip part across the axis of the elongated casing.

6. The position indicator according to claim 1, further comprising: a holder to which the elongated casing is mounted so that the tracker position of the tracker and the position of the position indicating part are in the specific positional relation.

7. The position indicator according to claim 1, wherein: the position indicating part, in operation, indicates the position on an input surface of a position detecting sensor, and the position indicating part, in operation, couples to the position detecting sensor by an electromagnetic induction system.

8. The position indicator according to claim 1, wherein: the position indicating part, in operation, indicates the position on an input surface of a position detecting sensor, and the position indicating part, in operation, couples to the position detecting sensor by a capacitive coupling system.

9. The position indicator according to claim 1, wherein: the position indicating part, in operation, indicates the position in a VR (Virtual Reality) space.

10. A position detection system comprising: a position indicator that indicates a position in a three-dimensional (3D) space; a spatial position detecting circuit; and a computer; wherein the position indicator includes: an elongated casing; a position indicating part which is disposed at one end of the elongated casing and which, in operation, indicates the position; a grip part that extends in a first direction intersecting a second direction in which an axis of the elongated casing extends and is configured to be gripped with a palm of a user in a state in which the elongated casing is gripped between fingers of the user; and a tracker which, in operation, causes the spatial position detecting circuit to detect a tracker position of the tracker in the 3D space, wherein the tracker position of the tracker and a position of the position indicating part are in a specific positional relation, and the tracker is disposed so as to be not covered by the user's hand when the user palm-grips the grip part; wherein the spatial position detecting circuit includes: a position detecting part which, in operation, detects the tracker position of the tracker; and wherein the computer includes: circuitry which, in operation, computes, based on the tracker position of the tracker detected by the spatial position detecting circuit and the specific positional relation, the position in the 3D space indicated by the position indicator.

11. The position detection system according to claim 10, wherein: the computer further includes a memory which, in operation, stores correction values which are generated based on the specific position relation and used to compute the position in the 3D space indicated by the position indicator.

12. The position detection system according to claim 10, further comprising: a position detecting sensor; wherein the circuitry of the computer, in operation, selects either one of the position indicated by the position indicator as detected by the position detecting sensor or the position indicated by the position indicator as computed by the computer.

13. The position detection system according to claim 10, further comprising: a position detecting sensor; wherein the circuitry of the computer, in operation, performs coordinate transformation that causes a first one of a coordinate system of the 3D space and a coordinate system of an input surface of the position detecting sensor to correspond with a second one of the coordinate system of the 3D space and the coordinate system of the input surface of the position detecting sensor.
14. The position detection system according to claim 10, further comprising: a display which, in operation, displays a locus of the position indicated by the position indicator; wherein an image including the locus displayed on the display is a VR (Virtual Reality) image.
-