

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399929
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Clark; John J. et al.

Security event characterization and response

Abstract

Security event characterization and response includes, for each of a plurality of first security data collection events determining that the first event has started. Collecting, in a database, an event data record associated with the first event determined to have started, the event data record comprising gait information of a person associated with the first event. For a given security data collection event later than the plurality of first events, determining that the given event has started. Detecting given event data comprising gait information of a person associated with the given event determined to have started. Determining a similarity meeting a threshold similarity between the query and one or more sets of records of the database. Initiating an action based on the one or more sets of records of the database determined to meet a threshold similarity with the query.

Inventors: Clark; John J. (Boynton Beach, FL), Bergman; Adam S. (Boca Raton, FL)

Applicant: Sensormatic Electronics, LLC (Boca Raton, FL)

Family ID: 1000008780753

Assignee: Sensormatic Electronics, LLC (Boca Raton, FL)

Appl. No.: 18/411854

Filed: January 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240241903 A1	Jul. 18, 2024

Related U.S. Application Data

us-provisional-application US 63479984 20230113

Publication Classification

Int. Cl.: G06F16/43 (20190101); G06V20/52 (20220101); G06V40/20 (20220101)

U.S. Cl.:

CPC G06F16/43 (20190101); G06V20/52 (20220101); G06V40/25 (20220101);

Field of Classification Search

CPC: G06F (16/43); G06V (40/25); G06V (20/52)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9432632	12/2015	Cheng	N/A	H04N 7/18
10290031	12/2018	Reid et al.	N/A	N/A
2007/0263907	12/2006	McMakin	382/107	G06V 40/25
2016/0269411	12/2015	Malachi	N/A	H04L 63/0421
2021/0097832	12/2020	Bergman	N/A	G06V 10/811
2022/0346670	12/2021	Chen	N/A	A61B 5/7282
2023/0048282	12/2022	Hanson	N/A	G06V 20/597
2023/0410616	12/2022	Carlson	N/A	G08B 13/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021067197	12/2020	WO	N/A
2021186149	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report issued in corresponding International Application No. PCT/US2024/011524 dated May 16, 2024. cited by applicant
Otzurk, et al., Gait-based people Identification with Millimeter-Wave Radio, 2021 IEEE 7th World Forum on Internet of Things (WF-IoT) 978-1-6654-4431-6/21. cited by applicant

Primary Examiner: Leroux; Etienne P
Attorney, Agent or Firm: ArentFox Schiff LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application claims the benefit of U.S. Prov. Pat. App. No. 63/479,984, of the same title and filed on Jan. 13, 2023; the entirety of which is incorporated herein by reference.

BACKGROUND

(1) The present disclosure relates generally to security systems, and more particularly, to systems

and methods for characterizing and response to security events.

SUMMARY

(2) This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the DETAILED DESCRIPTION. This summary is not intended to identify key features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(3) In some examples, systems, methods, and computer program products for security event characterization and response are disclosed herein. In some examples, security event characterization and response includes, for each of a plurality of first security data collection events, determining that the first event has started. Collecting, in a database, an event data record associated with the first event determined to have started, the event data record comprising gait information of a person associated with the first event. For a given security data collection event later than the plurality of first events, determining that the given event has started. Detecting given event data comprising gait information of a person associated with the given event determined to have started. Determining a similarity meeting a threshold similarity between the query and one or more sets of records of the database. Initiating an action based on the one or more sets of records of the database determined to meet a threshold similarity with the query.

(4) Further aspects of the present disclosure are described in more details below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosed aspects will hereinafter be described in conjunction with the appended drawings, provided to illustrate and not to limit the disclosed aspects, wherein like designations denote like elements, and in which:

(2) FIG. 1 is a block diagram of an example security system, according to implementations of the present disclosure;

(3) FIG. 2 is a block diagram of an example control system implemented by the security system of FIG. 1, according to implementations of the present disclosure;

(4) FIG. 3 is a block diagram of an example security system of FIG. 1 implemented with other security systems, according to implementations of the present disclosure;

(5) FIG. 4 is an architecture for methods, systems, and computer program products for security event characterization, in accordance with examples of the technology disclosed herein.

(6) FIG. 5 is a flowchart of an example method implemented by the security system of FIG. 1, according to implementations of the present disclosure; and

(7) FIG. 6 is a block diagram of examples components of a computer device that may implement one or more of the features of the security system of FIG. 1.

DETAILED DESCRIPTION

(8) The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well known components may be shown in block diagram form in order to avoid obscuring such concepts.

(9) In many retail stores, there is a need of acting on a detected security event, e.g., identifying persons of interest (POI) in the context of potential theft incidents. Typical electronic article surveillance (EAS) systems merely provide an alarm to notify store clerks of an individual leaving a store without paying for a product. This means the individual may have already performed the

theft and may escape without being caught by law enforcement officials.

(10) In addition, retailers are struggling with organized retail theft from stores. They are looking for a way to proactively identify persons or groups that are participating in organized retail theft so action can be taken before the theft occurs. Examples of the technology disclosed herein can identify those individuals or groups based on associating gait and body biometrics with EAS alarms at a retail store. Using this data to create a system that can be accessed as a service by any retailer regardless of whether the retailer uses EAS exit systems. Examples of the technology disclosed herein do not have the same issues as facial recognition systems that are easy to defeat with facial covering such as medical masks, sunglasses, hats or other disguises. Examples of the technology disclosed herein also may not have the same privacy issues associate with facial recognition system. It is not easy to alter or disguise a person's gait and body biometrics, so it would provide a higher level of function to detect repeat theft offenders with identifying rates up to 97% for this type of technology. Examples of the technology disclosed herein can help retailers (an managers of any other controlled area) identify potential thefts (or other actions) and take actions before the theft takes place as most retailers have policies not to pursue after the theft.

(11) The present disclosure addresses one or more shortcomings of a typical EAS system by providing systems and methods for relating a present event characterized by biometric data including gait with prior similar events. In an example, a system implemented according to the present disclosure may build an index of confidence scores and POIs based on characteristics including gait and wireless (e.g., Wi-Fi or Bluetooth) identifying technologies operating simultaneously. The system may derive a confidence score for associating a present event with prior events based on these technologies. Further, the system may identify an individual as a POI (e.g., potential shoplifting suspect) as the individual enters the store (i.e., before the individual has shoplifted). In other words, the system may identify the individual as a POI based on a confidence score generated from past actions by one or more candidates profiled by characteristics including gait and one or more prior collection events.

(12) The systems and methods described herein may offer a pro-active opportunity to stop potential theft before it happens. One benefit of this solution is that the confidence in a notification according to the present disclosure may be higher than those of a typical EAS system due to a linking of a biometric characteristics including at least gait with prior collection events.

(13) In some examples, the technology includes video and/or other technologies such as millimeter (mm) wave transceivers to detect the physical characteristics of a person's gait and body biometrics. During a collection event (e.g., as a person passes through the exit system and an active AM/RFID EAS tag is detected and alarms the system) the biometrics data of the persons gait and body is associated with that event. That corollary information is stored in a local and/or cloud-based system and a profile is created for that gait/body biometric instance. The system records each collection event (e.g., an instance of an alarm) associated with the same gait/body biometrics data and based on the type and frequency of collection events (e.g., outbound AM/RFID EAS alarms) may identify that profile as a potential repeat theft offender. The system then monitors incoming pedestrian traffic into/near the retail store and determines gait/body biometrics of each person (e.g., entering a store or parking area). Those biometrics are compared to the online profiles. If a profile match meeting a certain threshold level is found with one or more recorded collection events (e.g., AM/RFID EAS alarm events), an action (e.g., the retailer being notified that a possible repeat offender entered the retail store with the entry timestamp) can be taken. The retailer can use the store CCTV system to identify and track the person and perform any preemptive measures to discourage the theft before it takes place. Additionally, the gait/biometric characteristics can be combined with other attributes of the potential repeat offender such as Wi-Fi or Bluetooth associated with the person's device. In combining other attributes, a confidence factor or score can be generated depending on the number of attributes in agreement on a particular repeat offender candidate.

(14) The technology disclosed herein in unlike facial recognition alone, is more difficult to defeat and may not have the same privacy implications. In some examples, the technology disclosed herein does not rely primarily on the detection of electronic devices such as cell phones that could easily uniquely identify a person, which can be simply turned off or left outside the retail store.

(15) In some examples, the technology disclosed herein can both collect data from and monitor not just one facility, but multiple facilities—e.g., including across disparate retailers. In some examples, the collection database and comparison functions can be cloud-based, or offered as software-as-a-service (SaaS).

(16) Turning now to the figures, example aspects are depicted with reference to one or more components described herein, where components in dashed lines may be optional.

(17) Referring to FIG. 1, an example security system **100** deployed at a facility (e.g., store) **102** is depicted. In general, the facility **102** can be any controlled area. The security system **100** may include, for example, one or more outside-facing cameras **104** facing out from an entrance of the facility **102** and one or more inside-facing cameras **106** facing inward from the entrance of the facility **102**. The cameras **104**, **106** may capture an image **117** (e.g., video image or photographic image) of individuals (e.g., individual **110**) entering and/or exiting the facility **102**. The security system **100** may also include, for example, one or more non-camera sensors **107** such as millimeter (MM) wave transceivers that collect data that allows the security system **100** to identify biometric characteristics, such as gait, of a person in the field of view of the non-camera sensor **107**. Examples of a non-camera sensors **107** also include a network sniffer, packet sniffer, packet analyzer, wireless device identification determiners that attempt to identify a wireless device (e.g., wireless device **116** associated with individual **110**) entering and/or exiting the facility **102** and collect a corresponding device identification information **118** or any other device capable of capturing a device identification from a wireless device.

(18) Some examples of the technology disclose herein generate confidence scores of persons of interest (POIs), which can include individuals believed to have engaged in theft of items (e.g., item **112**) from the facility **102** or another establishment, or at least associated with one or more previous security events, based on a combination of the image **117** and biometric information including gait information. Correspondingly, the present implementations provide mechanisms to alert security personal of the entrance of an identified person of interest into the facility **102**.

(19) In an example, an individual **110** may exit the facility **102** by passing through one or more pedestal scanners **108a** and **108b**. When the individual **110** purchases an item **112**, an electronic tag **114** (e.g., a radio frequency identifier (RFID) tag, an acousto-magnetic tag, or any other type of EAS device) on the item **112** may be removed or deactivated so that it will not be detected by the scanners **108a** and **108b**.

(20) In some instances, the individual **110** may steal or not purchase the item **112**, therefore the electronic tag **114** is not deactivated or removed. In this case, when the individual **110** exits from the facility **102**, the pedestal scanners **108a** and **108b** may detect that the item **112** with the electronic tag **114** is located near the scanners, and that the item **112** is being carried out of the facility **102** without having been purchased by the individual **110**. As such, the pedestal scanners **108a** and **108b** and/or the control system **120** may activate one or more notification devices **109**, such as an audio alarm device, a strobe or flashing light device, and/or a notification message sent to security or store personnel to notify the personnel about the security event or potential theft.

(21) Concurrently, as the individual **110** is just prior to exiting the facility **102**, or as they are exiting, or after they have exited, the inside-facing camera **106** and/or the outside-facing camera **104** may capture an image **117** (e.g., via recorded video or photographic image) of the individual **110** exiting the facility **102** and send the image **117** to the control system **120** for processing, as described in further detail herein. Further, the non-camera sensors **107** may concurrently attempt to 1) detect gait, and/or 2) detect the wireless device **116**. For example, the non-camera sensors **107** may attempt to detect a device identification (e.g., media access control (MAC) address, an Internet

Protocol address, or any other type of unique device identifier) of the wireless device **116** by scanning Wi-Fi, Bluetooth, and/or any other wireless protocol. The non-camera sensors **107** may send device identification information **118**, including biometric information such as gait information, and device identification of the wireless device **116**, to the control system **120** for processing, as described in further detail herein. Based on the images **117**, gait information, and the device identification information **118**, the control system **120** may generate a confidence score corresponding to the individual **110** and store the confidence score along with person of interest (POI) information (e.g., image of POI or device identification of wireless device corresponding to POI) for future detections, as described in more detail herein.

(22) In an aspect, the confidence score along with the POI information may be shared with other establishments. Further, when a subsequent security event occurs (at the facility **102** or another establishment) and a second image corresponding to the security event or a second device identification corresponding to the security event matches those of the POI information, the confidence score corresponding to the POI information may be updated based on the subsequent security event. For example, a subsequent confidence score corresponding to subsequent security event may be calculated, and when a feature set (e.g., gait) of the second image or the second device identification match the POI information, the second confidence score may be added to the confidence score and stored as the confidence score corresponding to the POI. This multi-factor (e.g., image plus device identification) confidence score may ultimately be used to proactively notify store or security or law enforcement personnel of a potential POI upon the corresponding individual being detected as entering a store.

(23) Referring to FIG. 2, details of the control system **120** in relation to the individual **110** exiting the facility **102** are depicted as control system **200**. In an example, the control system **200** may generate a security event signal **202** when the item **112** is being carried out of the facility **102** without having been purchased by the individual **110**. The security event signal **202** may signal to the pedestal scanners **108a** and **108b** to send an alert (e.g., via notification devices **109**), to the inside-facing camera **106** and/or the outside-facing camera **104** to capture the image **117**, and to the non-camera sensors **107** to detect i) gait or ii) device identification of the wireless device **116**.

(24) The control system **200** may include an image processor **210** configured to process the image **117**. In an example, the image processor **210** may obtain the image **117** from the cameras **104** and **106**, in response to the security event signal **202**. In an example, one or more of the images **117** may be captured from a timeframe that spans before and after the security event signal **202**, e.g., within a certain threshold time.

(25) The image processor **210** may also include an image recognition model **212** configured to identify a feature set (e.g., facial features, other biometric characteristics including gait) of the image **117** corresponding to the individual **110**. In an example, the image recognition model **212** may include an image comparator **216** configured to compare the feature set of the image **117** with one or more POI feature sets **244** stored in a database **240**.

(26) The control system **200** may include an ID processor **220** configured to process the device identification information **118**. In an example, the ID processor **220** may determine whether the device identification information **118** corresponds to the security event based on the captured time of the device identification information **118**. In an example, the ID processor **220** may include an ID comparator **222** configured to compare the device identification information **118** to POI device identification information **246** stored in the database **240**. In addition, control system **200** may include gait processor (not shown) configured to determine a gait of the individual **110**.

(27) The control system **120** may include a confidence processor **230** configured to generate and/or update a confidence score corresponding to a POI. In an example, if the image comparator **214** or the ID comparator **222** determines a match, a confidence score corresponding to the POI may be updated. Otherwise, the POI is a new POI and a new confidence score is generated.

(28) The confidence processor **230** may include an image/ID score generator configured to

generate an image score (e.g., first score) and an ID score (e.g., second score) corresponding to the security event. In an example, if the image recognition model **212** identifies a feature set of the image **117**, the image score may be scored at a predetermined value (e.g., 1), and if the image recognition model **212** does not identify a feature set of the image **117**, the image score may be scored at second predetermined value (e.g., 0). Further, if the ID processor **220** obtains a device identification of the wireless device **116** from the device identification information **118**, the ID score may be scored at a predetermined value (e.g., 1), and if the ID processor **220** does not obtain the device identification, the ID score may be scored at second predetermined value (e.g., 0).

(29) In some examples, the confidence processor **230** may include a weight generator **234** which weights the image score and/or the ID score. In an example, the weight generator **234** may weight one of the image score or the ID score over the other. For example, the ID score may be weighted at a percentage (e.g., 50%) of the image score such that if both a feature set and a device identification are identified, the image score is, for example, 1 and the ID score is 0.5.

(30) The confidence processor **232** may generate a confidence score based on the image score and the ID score. For example, the confidence score may be the sum of the image score and the ID score. However, other algorithms and calculations may be used, including those considering the weight of the image score and the ID score.

(31) The confidence processor **232** may store the calculated confidence score in the database **240** as the POI confidence score **248**. In an example, the POI list **242** may associate the POI confidence score **248** with the one or more of the POI feature sets **244** or the POI device identification information **246**.

(32) In an example, the security system **100** may also alert personnel when a POI enters the facility **102** based on the POI confidence score **248**. In an example, the security system **100** may maintain a confidence threshold corresponding to the POI confidence score **248**. When the individual **110** and/or the wireless device **116** enters the facility **102**, the security system **100** may determine that the individual **110** is a POI. For example, the inside-facing camera **106** and/or the outside-facing camera **104** may capture an image **117** (e.g., via recorded video or photographic image) of the individual **110** entering the facility **102** and send the image **117** to the control system **200** for comparison to POI information (e.g., gait), as described in further detail herein. Further, the non-camera sensors **107** may concurrently attempt i) to determine a gait of the individual **110** entering the facility **102**, and/or ii) to detect the wireless device **116** entering the facility **102** by scanning Wi-Fi, Bluetooth, and/or any other wireless protocol to determine a device identification (e.g., MAC address) of the wireless device **116**. The non-camera sensors **107** may send the gait information and/or the device identification information **118**, including device identification of the wireless device **116**, to the control system **200** for comparison to the POI information, as described in further detail herein. Based on the images **117** and the device identification information **118**, the control system **200** may determine the individual is a POI when, for example, a feature set of the image **117** or the device identification information **118** matches the POI information. In response to determining that the individual is a POI, the security system **100** may compare the confidence score corresponding to the POI with the confidence threshold. When the confidence score exceeds the confidence threshold, this means the POI (e.g., individual **110**) has been involved in a sufficient number of security events that security personnel should be notified of the POI's presence in the facility **102**. When the confidence score does not exceed the confidence threshold, it may mean that the POI has not been involved in enough security events to warrant a notification to security personnel of the facility **102**.

(33) Referring to FIG. 2, the control system **200** in relation to the individual **110** entering the facility **102** are depicted. In an aspect, the image processor **210** may receive the image **117** corresponding to the individual **110** entering the facility **102**, and the image comparator **214** may compare a feature set of the image **117** to the POI feature sets **244** to determine whether the individual **110** is a POI. Further, the ID processor **220** may receive the device identification

information **118**, and the ID comparator **222** may compare any device identification to the POI device identification information **246** to determine whether the individual **110** is a POI. In other words, if one or more of the image comparator **214** or the ID comparator **222** determines a match, the individual **110** is determined to be a POI.

(34) The confidence processor **230** further includes a confidence comparator **236** configured to determine whether to alert a security personnel based on the POI confidence score **248**. For example, once the individual **110** is determined to be a POI, the confidence comparator **236** compares the POI confidence score **248** (e.g., 10) with a confidence threshold value (e.g., 9). When the POI confidence score **248** is greater than the confidence threshold value, this may indicate that the POI was involved in multiple security events at the facility **102** and/or other establishments. Otherwise, when the POI confidence score **248** is not greater than the confidence threshold value, this may indicate that the POI was not involved in a sufficient number of security events to warrant the involvement of security personnel.

(35) The control system **200** may include a notification component **250** configured to alert a security personnel regarding the POI confidence score **248** of the individual **110** exceeding the confidence threshold value. In an example, the notification component **250** may include a wired or wireless transceiver configured to transmit one or more notifications (e.g., email, text, alarm) to a device used by the security personnel.

(36) Accordingly, the security system **100** may provide mechanisms to build a profile of a POI based on information obtained as the individual **110** exits the facility **102** (or another establishment) and a proactive approach to identify the individual **110** when entering the facility **102** (or another establishment) and to alert security personnel based on the POI information.

(37) Referring to FIG. 3, an example security system **300** configured for multiple establishments is depicted, in accordance with examples of the technology disclosed herein. In an example, the facility **102** may be one of many establishments in the security system **300**. For example, the facility **102** may communicate with one or more additional establishments **302** via a network **310** to share POI information including images **117** and device identification information **118** for security purposes, as described herein. In some examples, the facility **102** may include the control system **320**, which performs all functions of the control system **120**. In another example, the security system **300** may also include a control center **330** which, in conjunction with the control system **320**, performs all functions of the control system **120**.

(38) Referring to FIG. 4, an architecture **400** for methods, systems, and computer program products for security event characterization and response are shown, in accordance with examples of the technology disclosed herein. Referring to FIG. 5, an example method **500** for security event characterization and response is depicted. The operations of the method **500** may be performed by one or more components of the system **100**, **200**, or **300** (referred to below as “system **100**”), as described herein. In such methods **500**, for each of a plurality of first security data collection events, system **100** determines that the first event has started—Block **510**. In a continuing example, system **100** identifies collection events **410** such as an EAS tag alarm, a confirmed theft, or an unauthorized/anomalous entry or exit from facility **102**. However, the first event need not be a tag alarm and need not be from the same facility. First security data collection events can be from one or more different facilities.

(39) The system **100** then collects, in a database such as event database **420**, an event data record **412** associated with the first event determined to have started—Block **520**. In the continuing example, each event data record **412** includes gait information of a person associated with the first event. In some examples, collecting includes collecting gait information using at least one of a video imaging device (e.g., **104**, **106**) and a millimeter wave transceiver (e.g., **107**). Each event data record **412** can include other information such as images, time of collection, location of collection, facility type, facility identifier, and other biometric information. The event data records **412** can be collected from one facility or across a number of facilities.

(40) For a given security data collection event later than the plurality of first events, the system **100** determines that the given event has started—Block **530**. While the given event can be an EAS tag alarm, the given event can be other events, e.g., the presence of an individual near (e.g., outside in a parking lot) or just entering a controlled area (e.g., facility **102**).

(41) The system **100** then detects given event data—Block **540**. The given event data includes gait information of a person associated with the given event determined to have started.

(42) The system **100** then determines a similarity, meeting a threshold similarity, between the query and one or more sets of records of the database—Block **550**. In the continuing example, at least one of the sets of records of the database determined to meet a threshold similarity with the query is a set of records associated with a single individual. However, this does not have to be the case. One or more of the records could be not mapped to a particular individual. In the continuing example, several sets of records determined to meet a threshold similarity to the query are found. The sets of records are presented along with the similarity measure, or in order of decreasing similarity to the query. Where a set of records is associated with an individual, a confidence level (as described elsewhere herein) that the individual is a repeat offender is also returned.

(43) The system **100** then initiates an action based on the one or more sets of records of the database determined to meet a threshold similarity with the query—Block **560**. In the continuing example, initiating an action includes one of more of notifying a party that the given event meets a threshold similarity with one or more sets of records of the database; directing one or more sensors towards one or more of a person or an area associated with the given event; and securing the controlled area.

(44) In a further example, methods include determining a security event has occurred. For example, the control system **120**, **200**, or control center **320** may determine a security event has occurred based on receiving the security event signal **202** from the pedestal scanners **108a** and **108b** when the item **112** having the electronic tag **114** is located near the scanners.

(45) Such examples include obtaining, from a camera, an image corresponding to the security event. For example, one or more of the control system **120**, **200**, or control center **320**, the image processor **210**, or the image recognition model **212** may receive the image **117** (e.g., video image or photographic image) from the one or more of the cameras **104** or **106** corresponding to the security event signal **202** being received. In some such examples, one or more of the control system **120**, **200**, or control center **320**, the image processor **210**, or the image recognition model **212** may transmit instructions to the camera **104/106** to capture the image **117** in response to the security event. The one or more of the control system **120**, **200**, or control center **320**, the image processor **210**, or the image recognition model **212** may receive the image **117** in response to the transmitted instructions.

(46) Such examples include generating a first score corresponding to a POI based on whether an individual is detected in the image. For example, one or more of the control system **120**, **200**, or control center **320**, the confidence processor **230**, the confidence score generator **232**, or the image/ID score generator **233** may generate an image score (e.g., first score) corresponding to one or more of an individual **110** or a feature set of the individual **110** being detected in the image **117**. In some such examples, when the individual **110** and/or a feature set of the individual **110** is identified in the image, the image score may have a value of 1, and when the not identified, the image score may have a value of 0.

(47) Such examples include causing a wireless device identification determiner to search for a device identification of a wireless device corresponding to the security event. For example, one or more of the control system **120**, **200**, or control center **320** or the ID processor **220** may cause the non-camera sensors **107** to search for a device identification information **118** of the wireless device **116** corresponding to the security event. In some such examples, one or more of the control system **120**, **200**, or control center **320**, the image processor **210**, or the image recognition model **212** transmits instructions to the non-camera sensors **107** to search for the device identification

information **118** in response to the security event. The one or more of the control system **120, 200**, or control center **320**, the image processor **210**, or the image recognition model **212** may receive the device identification information **118** in response to the transmitted instructions.

(48) Such examples include generating a second score corresponding to the person of interest based on whether the device identification is identified. For example, one or more of the control system **120, 200**, or control center **320**, the confidence processor **230**, the confidence score generator **232**, or the image/ID score generator **233** may generate an ID score (e.g., second score) corresponding to the POI based on whether the device identification is identified. In some such examples, when the device identification is identified, the ID score may have a value of 1, and when the device identification is not identified, the ID score may have a value of 0.

(49) Such examples may optionally include weighting one or more of the first score or the second score. For example, one or more of the control system **120, 200**, or control center **320**, the confidence processor **230**, the confidence score generator **232**, the image/ID score generator **233**, or the weight generator **234** may weight one or more of the image score or the ID score. In some such examples, the image score may be weighted higher than the ID score. For example, the ID score may be weighted at a percentage (e.g., 50%) of the image score.

(50) Such examples include generating a confidence score corresponding to the POI based on the first score and the second score. For example, one or more of the control system **120, 200**, or control center **320**, the confidence processor **230**, or the confidence score generator **232** may generate a confidence score corresponding to the POI based on the image score and the ID score. In some such examples, the confidence score may be generated by summing the image score and the ID score (with or without the weighting, depending on the example).

(51) Such examples include storing the confidence score in correlation with POI information in a database. For example, one or more of the control system **120, 200**, or control center **320**, the confidence processor **230**, or the confidence score generator **232** may store the confidence score as POI confidence score **248** and associate the confidence score with POI information such as POI feature sets **244** and/or POI device identification information **246** in the database **240**.

(52) In an additional example, the system **100** obtains, from the camera, an image corresponding to an entrance of an individual. For example, one or more of the control system **120, 200**, or control center **320**, the image processor **210**, or the image recognition model **212** may receive the image **117** (e.g., video image or photographic image) from the one or more of the cameras **104** or **106** corresponding to an entrance of the individual **110** at the facility **102**. In some such examples, one or more of the control system **120, 200**, or control center **320**, the image processor **210**, or the image recognition model **212** may transmit instructions to the camera **104/106** to capture the image **117** in response to the entrance. The one or more of the control system **120, 200**, or control center **320**, the image processor **210**, or the image recognition model **212** may receive the image **117** in response to the transmitted instructions.

(53) Such additional examples include causing a wireless device identification determiner to search for a device identification of a wireless device corresponding to the entrance of the individual. For example, one or more of the control system **120, 200**, or control center **320** or the ID processor **220** may cause the non-camera sensors **107** to search for a device identification of the wireless device **116** corresponding to the entrance of the individual **110** into the facility **102**. In an example, one or more of the control system **120, 200**, or control center **320**, the image processor **210**, or the image recognition model **212** may transmit instructions to the non-camera sensors **107** to search for the device identification information **118** in response to the entrance. The one or more of the control system **120, 200**, or control center **320**, the image processor **210**, or the image recognition model **212** may receive the device identification information **118** in response to the transmitted instructions.

(54) Such additional examples include determining whether the individual is a POI based on one or more of the image or the device identification. For example, one or more of the control system **120**,

200, or control center **320**, the image processor **210**, the image recognition model **212**, the image comparator **214**, the ID processor **220**, or the ID comparator may determine whether the individual **110** is a POI. In some such examples, the individual **110** may be a POI based on a match between a feature set of the image **117** to one or more POI feature sets **244**, and/or the individual **110** may be a POI based on a match between a device identification of the wireless device **116** and a POI device identification information **246**.

(55) Such additional examples include determining a confidence score corresponding to the person of interest in response to determining the individual is the person of interest. For example, one or more of the control system **120**, **200**, or control center **320**, the confidence processor **230**, or the confidence comparator **236** may determine a confidence score corresponding to the POI in response to determining the individual **110** is the POI. In an example, one or more of the control system **120**, **200**, or control center **320**, the confidence processor **230**, or the confidence comparator **236** may read the POI confidence score **248** associated with the POI information, including the POI feature set **244** and/or the POI device identification information **246**, stored in the database **240** and/or the POI list **242**.

(56) Such additional examples include transmitting a notification of the POI to a device in response to the confidence score exceeding a confidence threshold. For example, one or more of the control system **120**, **200**, or control center **320** or the notification component **250** may transmit a notification such as an email, text, or alert to a device associated with security personnel when the confidence score exceeds a confidence threshold value. In some such examples, one or more of the control system **120**, **200**, or control center **320** or the confidence comparator **236** may compare the POI confidence score **248** associated with the POI to a confidence threshold value to determine whether to transmit the notification.

(57) Referring to FIG. **6**, a computing device **600** (such as a computing device of system **300**) may implement all or a portion of the functionality described in FIGS. **1-5** and the other examples described above. For example, the computing device **600** may be or may include at least a portion of the control system **120**, **200**, or **320**, the control center **330**, or any other component described herein with reference to FIGS. **1-5**. The computing device **600** may include a processor **602** which may be configured to execute or implement software, hardware, and/or firmware modules that perform some or all of the functionality described herein with reference to FIGS. **1-5**. For example, the processor **602** may be configured to execute or implement software, hardware, and/or firmware modules that perform some or all the functionality described herein with reference to the the control system **120**, **200**, or **320**, the control center **330**, or any other component described herein with reference to FIGS. **1-5**.

(58) The processor **602** may be a micro-controller, an application-specific integrated circuit (ASIC), or a field-programmable gate array (FPGA), and/or may include a single or multiple set of processors or multi-core processors. Moreover, the processor **602** may be implemented as an integrated processing system and/or a distributed processing system. The computing device **600** may further include a memory **604**, such as for storing local versions of applications being executed by the processor **602**, related instructions, parameters, etc. The memory **604** may include a type of memory usable by a computer, such as random access memory (RAM), read only memory (ROM), tapes, magnetic discs, optical discs, volatile memory, non-volatile memory, and any combination thereof. Additionally, the processor **602** and the memory **604** may include and execute an operating system executing on the processor **602**, one or more applications, display drivers, etc., and/or other components of the computing device **600**.

(59) Further, the computing device **600** may include a communications component **606** that provides for establishing and maintaining communications with one or more other devices, parties, entities, etc. utilizing hardware, software, and services. The communications component **606** may carry communications between components on the computing device **600**, as well as between the computing device **600** and external devices, such as devices located across a communications

network and/or devices serially or locally connected to the computing device **600**. In an aspect, for example, the communications component **606** may include one or more buses, and may further include transmit chain components and receive chain components associated with a wireless or wired transmitter and receiver, respectively, operable for interfacing with external devices.

(60) Additionally, the computing device **600** may include a data store **608**, which can be any suitable combination of hardware and/or software, which provides for mass storage of information, databases, and programs. For example, the data store **608** may be or may include a data repository for applications and/or related parameters not currently being executed by processor **602**. In addition, the data store **608** may be a data repository for an operating system, application, display driver, etc., executing on the processor **602**, and/or one or more other components of the computing device **600**.

(61) The computing device **600** may also include a user interface component **610** operable to receive inputs from a user of the computing device **600** and further operable to generate outputs for presentation to the user (e.g., via a display interface to a display device). The user interface component **610** may include one or more input devices, including but not limited to a keyboard, a number pad, a mouse, a touch-sensitive display, a navigation key, a function key, a microphone, a voice recognition component, or any other mechanism capable of receiving an input from a user, or any combination thereof. Further, the user interface component **610** may include one or more output devices, including but not limited to a display interface, a speaker, a haptic feedback mechanism, a printer, any other mechanism capable of presenting an output to a user, or any combination thereof.

(62) The previous description is provided to enable any person skilled in the art to practice the various aspects described herein. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but is to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects. Unless specifically stated otherwise, the term “some” refers to one or more. Combinations such as “at least one of A, B, or C,” “one or more of A, B, or C,” “at least one of A, B, and C,” “one or more of A, B, and C,” and “A, B, C, or any combination thereof” include any combination of A, B, and/or C, and may include multiples of A, multiples of B, or multiples of C. Specifically, combinations such as “at least one of A, B, or C,” “one or more of A, B, or C,” “at least one of A, B, and C,” “one or more of A, B, and C,” and “A, B, C, or any combination thereof” may be A only, B only, C only, A and B, A and C, B and C, or A and B and C, where any such combinations may contain one or more member or members of A, B, or C. All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. The words “module,” “mechanism,” “element,” “device,” and the like may not be a substitute for the word “means.” As such, no claim element is to be construed as a means plus function unless the element is expressly recited using the phrase “means for.”

Claims

1. A method of characterizing security events and responding thereto, comprising: for each of a plurality of first security events: determining that the first security event has started; and collecting,

in a database, an event data record associated with the first security event determined to have started, the event data record comprising gait information of a person associated with the first security event; for a given security event later than the plurality of first security events: determining that the given security event has started; detecting given security event data comprising gait information of a person associated with the given security event determined to have started; determining a similarity meeting a threshold similarity between i) a query comprising the detected given security event data gait information, and ii) gait information of one or more records of the database; and initiating an action based at least in part on determining a similarity meeting the threshold between i) the query and ii) the gait information of one or more records of the database.

2. The method of claim 1, wherein the collecting comprises collecting gait information using at least one of a video imaging device and a millimeter wave transceiver.
3. The method of claim 1, wherein at least one first security event comprises an electronic article surveillance (EAS) alarm.
4. The method of claim 1, wherein the given security event comprises an event other than an electronic article surveillance (EAS) alarm.
5. The method of claim 1, wherein the given security event is a presence of an individual near or entering a controlled area.
6. The method of claim 1, wherein at least one of the plurality of first security events occurs at an area other than the area of the given security event.
7. The method of claim 1, wherein at least one of the records of the database determined to meet a threshold similarity with the query is a set of records associated with a single individual.
8. The method of claim 7, wherein the at least one of the records associated with a single individual is associated with a confidence level that the individual is a repeat offender.
9. The method of claim 1, wherein initiating an action comprises one or more of: notifying a party that the determined similarity meets the threshold; directing one or more sensors towards one or more of a person or an area associated with the given security event; and securing a controlled area.
10. A non-transitory computer-readable medium storing computer executable instructions for identifying a person of interest by a security system, comprising instructions to: for each of a plurality of first security events: determine that the first security event has started; and collect, in a database, an event data record associated with the first security event determined to have started, the event data record comprising gait information of a person associated with the first security event; for a given security event later than the plurality of first security events: determine that the given security event has started; detect given security event data comprising gait information of a person associated with the given security event determined to have started; determine a similarity meeting a threshold similarity between i) a query comprising the detected given security event data gait information, and ii) gait information of one or more of records of the database; and initiate an action based at least in part on determining a similarity meeting the threshold between i) the query and ii) the gait information of one or more records of the database.
11. The non-transitory computer-readable medium of claim 10, wherein the collecting comprises collecting gait information using at least one of a video imaging device and a millimeter wave transceiver.
12. The non-transitory computer-readable medium of claim 10, wherein at least one first security event comprises an electronic article surveillance (EAS) alarm.
13. The non-transitory computer-readable medium of claim 10, wherein the given security event comprises an event other than an electronic article surveillance (EAS) alarm.
14. The non-transitory computer-readable medium of claim 10, wherein the given security event is a presence of an individual near or entering a controlled area.
15. The non-transitory computer-readable medium of claim 10, wherein at least one of the plurality of first security events occurs at an area other than the area of the given security event.
16. A system comprising: one or more processors; memory, in communication with the one or more

processors, containing instructions that when executed by the one or more processors, causes the system to: for each of a plurality of first security events: determine that the first security event has started; and collect, in a database, an event data record associated with the first security event determined to have started, the event data record comprising gait information of a person associated with the first security event; for a given security event later than the plurality of first security events: determine that the given security event has started; detect given security event data comprising gait information of a person associated with the given security event determined to have started; determine a similarity meeting a threshold similarity between i) a query comprising the detected given security event data gait information and ii) gait information of one or more records of the database; and initiating an action based at least in part on determining a similarity meeting the threshold between i) the query and ii) the gait information of one or more records of the database.

17. The system of claim 16, wherein the collecting comprises collecting gait information using at least one of a video imaging device and a millimeter wave transceiver.

18. The system of claim 16, wherein at least one first security event comprises an electronic article surveillance (EAS) alarm.

19. The system of claim 16, wherein the given security event comprises an event other than an electronic article surveillance (EAS) alarm.

20. The system of claim 16, wherein the given security event is a presence of an individual near or entering a controlled area.
