

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400530
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ohtsuji; Taichi et al.

Tracking support apparatus, terminal, tracking support system, tracking support method and program

Abstract

A tracking support system includes a position calculating section connected with a plurality of cameras arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras and configured to calculate a position of the tracking target based on the video images received from the plurality of cameras; a tracker selecting section configured to select a tracker to be instructed to track the tracking target, based on position information of the terminal received from the terminal and the calculated position of the tracking target; and an information transmitting section configured to transmit information of a distance between the tracking target and the terminal during the tracking of the tracking target to the terminal carried by the selected tracker.

Inventors: Ohtsuji; Taichi (Tokyo, JP), Muraoka; Kazushi (Tokyo, JP), Aminaka; Hiroaki (Tokyo, JP), Kanetomo; Dai (Tokyo, JP), Yamagaki; Norio (Tokyo, JP), Yoshinaga; Takashi (Tokyo, JP)

Applicant: NEC Corporation (Tokyo, JP)

Family ID: 1000008780700

Assignee: NEC CORPORATION (Tokyo, JP)

Appl. No.: 18/367586

Filed: September 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240005754 A1	Jan. 04, 2024

Related U.S. Application Data

continuation parent-doc US 18212908 20230622 PENDING child-doc US 18367586
continuation parent-doc US 17148747 20210114 US 11727775 20230815 child-doc US 18212908
continuation parent-doc US 16472688 US 11049374 20210629 WO PCT/JP2017/008263
20170302 child-doc US 17148747
us-provisional-application US 62437742 20161222

Publication Classification

Int. Cl.: **G06T7/292** (20170101); **G06V20/52** (20220101); **G08B13/196** (20060101); **G08B25/00** (20060101)

U.S. Cl.:

CPC **G08B13/19608** (20130101); **G06T7/292** (20170101); **G06V20/52** (20220101);
G08B13/19613 (20130101); **G08B13/19645** (20130101); **G08B25/009** (20130101);
G06T2207/30232 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6970183	12/2004	Monroe	348/143	G08B 7/062
9191633	12/2014	Fujimatsu et al.	N/A	N/A
10162353	12/2017	Hammond	N/A	N/A
10810889	12/2019	Ogawa	N/A	N/A
2003/0202102	12/2002	Shiota et al.	N/A	N/A
2005/0280711	12/2004	Ishii et al.	N/A	N/A
2011/0181712	12/2010	You et al.	N/A	N/A
2014/0169663	12/2013	Han et al.	N/A	N/A
2014/0285659	12/2013	Kim et al.	N/A	N/A
2015/0015718	12/2014	Fujimatsu	348/159	H04N 7/181
2015/0248751	12/2014	Ebiyama et al.	N/A	N/A
2015/0356840	12/2014	Wang et al.	N/A	N/A
2016/0031416	12/2015	Calhou et al.	N/A	N/A
2016/0291593	12/2015	Hammond et al.	N/A	N/A
2016/0304217	12/2015	Fisher et al.	N/A	N/A
2017/0092109	12/2016	Trundle et al.	N/A	N/A
2017/0287301	12/2016	Taylor et al.	N/A	N/A
2017/0352250	12/2016	de Barros Chapiewski et al.	N/A	N/A
2018/0158298	12/2017	Jeong et al.	N/A	N/A
2018/0173220	12/2017	Wang	N/A	N/A
2018/0239953	12/2017	Miwa	N/A	N/A

2020/0310468	12/2019	Liu	N/A	N/A
--------------	---------	-----	-----	-----

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002-290962	12/2001	JP	N/A
2003-289532	12/2002	JP	N/A
2004-328484	12/2003	JP	N/A
2005-086360	12/2004	JP	N/A
2005-348157	12/2004	JP	N/A
2009-003852	12/2008	JP	N/A
2011-018094	12/2010	JP	N/A
2012-078950	12/2011	JP	N/A
2012-104022	12/2011	JP	N/A
2014-031118	12/2013	JP	N/A
2014-199548	12/2013	JP	N/A
2015-002553	12/2014	JP	N/A
2015-019248	12/2014	JP	N/A
2015-207149	12/2014	JP	N/A
5871296	12/2015	JP	N/A
2016-119627	12/2015	JP	N/A
2016-171442	12/2015	JP	N/A
2016-194759	12/2015	JP	N/A
10-2012-0126680	12/2011	KR	N/A
2013/125301	12/2012	WO	N/A

OTHER PUBLICATIONS

U.S. Office Action for U.S. Appl. No. 18/212,908, mailed on Oct. 10, 2024. cited by applicant
JP Official Communication for JP Application No. 2023-001498, mailed on Nov. 28, 2023 with English Translation. cited by applicant
JP Office Action for JP Application No. 2023-212230, mailed on Nov. 26, 2024 with English Translation. cited by applicant
JP Office Action for JP Application No. 2023-212230, mailed on Jun. 25, 2024 with English Translation. cited by applicant
International Search Report for PCT/JP2017/008263 dated May 23, 2019 [PCT/ISA/210]. cited by applicant
Japanese Office Action for JP Application No. 2021-096083 mailed on Jun. 28, 2022 with English Translation. cited by applicant
U.S. Notice of Allowance for U.S. Appl. No. 18/472,888 mailed on Feb. 11, 2021. cited by applicant
U.S. Office Action for U.S. Appl. No. 18/368,618, mailed on Dec. 27, 2024. cited by applicant

Primary Examiner: Findley; Christopher G

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

DESCRIPTION OF RELATED APPLICATION (1) The present application is a continuation of U.S. patent application Ser. No. 18/212,908 (filed on Jun. 22, 2023), which is a continuation of

U.S. patent application Ser. No. 17/148,747 (filed on Jan. 14, 2021), now U.S. Pat. No. 11,727,775, which is a continuation of U.S. patent application Ser. No. 16/472,688 (filed on Jun. 21, 2019), now U.S. Pat. No. 11,049,374, which is National Stage Entry of International Patent Application No. PCT/JP2017/008263 (filed on Mar. 2, 2017), which claims priority based on U.S. Provisional Application 62/437,742 (filed on Dec. 22, 2016), the disclosure of which are incorporated herein by reference.

FIELD

(1) The present invention relates to a tracking support apparatus, a terminal, a tracking support system, a tracking support method and a program, and especially, to a tracking support system, a tracking support method and a program, in which a support is provided for a tracker tracking a tracking target.

BACKGROUND

(2) Patent Literature 1 discloses a security patrol support system in which a security guard who heads for the scene where an extraordinary event occurred can easily specify a suspicious person in a patrol guard service. Specifically, the security patrol support system includes a person monitoring section 100 which detects a person contained in video image data imaged by an imaging section arranged in a predetermined security area and monitors the detected person, a suspicious person detecting section 101 which detects a person satisfying a predetermined detection condition as a suspicious person, a position information calculating section 102 which calculates relative position information between the security guard and the suspicious person detected by the suspicious person detecting section 101, and a suspicious person information transmitting section 103 which transmits predetermined information to a mobile terminal carried by the security guard based on the relative position information calculated by the position information calculating section 102.

(3) Patent Literature 2 discloses a monitoring system which can output an instruction for an object quickly and properly when the object such as a suspicious person and a suspicious thing is detected. Specifically, in Patent Literature 2, a monitoring server 2 of the monitoring system stores a mobile terminal position managing table used to manage the positions of the mobile terminals 3 for every mobile terminal 3. Also, the monitoring server 2 stores an extraordinary state classification table in which there is registered a condition to determine the mobile terminal 3 to which an instruction for the object is to be issued, for every item corresponding to a kind of extraordinary state of the object. When the detection of the object in an extraordinary state is notified from the monitoring camera terminal 1, the monitoring server 2 determines the mobile terminal 3 to which the instruction for the object should be issued, by using the mobile terminal position managing table and the extraordinary state classification table. The monitoring server 2 transmits the instruction for the object in the extraordinary state to the determined mobile terminal 3.

(4) Patent Literature 3 discloses a configuration in which a central monitoring apparatus (20) acquires monitoring information which contain position information outputted from a monitoring terminal (10) at least, sets a monitoring point where the existence of a tracking target to be tracked by a tracker is estimated, selects the monitoring terminal (10) for a moving object which approaches and/or leaves a predetermined monitoring area with respect to the set monitoring point, and output an image transmission instruction to the selected monitoring terminal (10) so as to transmit the monitoring information containing image information.

(5) Patent Literature 4 discloses a detecting apparatus and a detecting method, in which it is possible to detect position information of a specific target and to ask a third party in the neighborhood of the specific object to secure the specific object.

(6) Patent Literature 5 discloses a tracking support apparatus which can reduce the load of a monitoring member carrying out the monitoring at a central control room and a security room.

(7) Patent Literature 6 discloses a configuration in which a security guard G1 takes a sight in the

neighborhood of him by a wearable camera, and asks a managing apparatus 10 to collate a person contained in the image data, and the managing apparatus 10 informs security information if the person contained in the image data is a person H1. [Patent Literature 1] JP2011-18094A [Patent Literature 2] JP2012-104022A [Patent Literature 3] WO2013/125301A1 [Patent Literature 4] JP2009-3852A [Patent Literature 5] JP2015-19248A [Patent Literature 6] JP2016-194759A
SUMMARY

(8) According to the configurations of Patent Literatures 1 to 3, it becomes possible for the security guard and so on to come running to a site to deal with a suspicious person and an extraordinary event. However, often, the suspicious person notices the security guard and runs away. On the other hand, Patent Literature 4 has as a purpose, the search of a lost child, and does not assume the situation that the child runs away. Also, the tracking in Patent Literatures 5 and 6 is to trace a person in video images of a fixed camera with the eyes, and a security guard does not track actually.

(9) The present invention has as an object, to provide a tracking support apparatus, a terminal, a tracking support system, a tracking support method and a program, that can contribute to enrichment of means for supporting a tracker such as a security guard so that the tracker can track in such a manner that a tracking target such as the above suspicious person is difficult to notice the tracking.

(10) According to a first aspect, a tracking support apparatus is provided that has a position calculating section connected with a plurality of cameras which are arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras, and configured to calculate a position of a tracking target based on the video images received from the plurality of cameras. The tracking support apparatus further includes a tracker selecting section configured to select a tracker to be instructed to track the tracking target, based on position information (or data) of a terminal received from the terminal and the calculated position information (or data) of the tracking target. Moreover, the tracking support apparatus further includes an information transmitting section configured to transmit information of a distance between the tracking target and the terminal carried by the tracker tracking the tracking target to the terminal of the selected tracker.

(11) According to a second aspect, a terminal is provided that has an instruction receiving section configured to receive an instruction about a tracking target from a tracking support apparatus, which transmits the instruction to the tracker carrying the terminal, based on information received from a plurality of cameras that are arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras, and an outputting section configured to output information of a distance between its own terminal and the tracking target based on a position of the tracking target received from the tracking support apparatus and a position of its own terminal.

(12) According to a third aspect, there is provided a tracking support method performed by a tracking support apparatus in a tracking support system that has a plurality of cameras arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras, and a tracking support apparatus configured to transmit an instruction to a tracker carrying a terminal based on information received from terminals carried by a plurality of trackers and the cameras. The tracking support method is provided in which the tracking support apparatus calculates a position of a tracking target based on the video images received from the plurality of cameras, selects the tracker to be instructed to track the tracking target, based on position information of the terminal received from the terminal and the calculated position of the tracking target, and transmits information of a distance between the tracking target and the terminal during tracking the tracking target to the terminal of the selected tracker. This method is coupled to a computer to instruct the tracking of the tracking target to the terminal carried by the tracker, as a specific machine.

(13) According to a fourth aspect, a program is provided to make a computer, installed in a tracking support apparatus of a tracking support system which has a plurality of cameras arranged in a

predetermined monitoring area to transmit video images imaged by the plurality of cameras, and the tracking support apparatus configured to transmit an instruction to a tracker carrying a terminal based on information received from the cameras and the terminals carried by a plurality of trackers, execute: processing of calculating a position of the tracking target based on the video images received from the plurality of cameras, processing of selecting the tracker to be instructed to track the tracking target, based on position information of the terminal received from the terminal and the calculated position of the tracking target, and processing of transmitting information of a distance between the tracking target and the terminal during the tracking of the tracking target to the terminal of the selected tracker.

(14) According to a fifth aspect, a program is provided which makes a computer that is installed in a terminal receiving an instruction about a tracking target from a tracking support apparatus which transmits the instruction about the tracking target to a tracker carrying the terminal based on information received from a plurality of cameras arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras, execute: processing of calculating a distance between its own terminal and the tracking target based on a position of the tracking target received from the tracking support apparatus and a position of its own terminal, and processing of outputting information of the calculated distance. The program can be stored in a (non-transitory) storage medium readable by a computer. That is, the present invention can be embodied as a computer program product.

(15) According to a sixth aspect, a tracking support system is provided to include a plurality of cameras arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras and the above tracking support apparatus.

(16) According to the present invention, it becomes possible to support a tracker such as a security guard so as to be able to track in such a manner that a tracking target such as a suspicious person is difficult to notice the tracking.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a diagram showing the configuration of an exemplary embodiment of the present invention.

(2) FIG. 2 is a diagram showing the operation of the exemplary embodiment of the present invention.

(3) FIG. 3 is a diagram showing the configuration of a tracking support system according to a first exemplary embodiment of the present invention.

(4) FIG. 4 is a diagram showing the configuration of a tracking support terminal according to the first exemplary embodiment of the present invention.

(5) FIG. 5 is a diagram showing the configuration of a support server according to the first exemplary embodiment of the present invention.

(6) FIG. 6 is a diagram showing an example of tracker information held by the support server according to the first exemplary embodiment of the present invention.

(7) FIG. 7 is a diagram showing an example of monitoring target information held by the support server according to the first exemplary embodiment of the present invention.

(8) FIG. 8 is a flow chart showing the operation (transmission processing of images to the support server) of a camera according to the first exemplary embodiment of the present invention.

(9) FIG. 9 is a flow chart showing the operation (processing of position notification to the support server) of a tracking support terminal according to the first exemplary embodiment of the present invention.

(10) FIG. 10 is a flow chart showing the operation (change processing of the tracker) of the support

server according to the first exemplary embodiment of the present invention.

(11) FIG. 11 is a flow chart showing the operation (reception processing of an instruction from the support server) of the tracking support terminal according to the first exemplary embodiment of the present invention.

(12) FIG. 12 is a flow chart showing the operation (determination processing of a distance from a tracking target) of the support server according to the first exemplary embodiment of the present invention.

(13) FIG. 13 is a sequence diagram showing a take-over operation to a new tracker according to the first exemplary embodiment of the present invention.

(14) FIG. 14 is a diagram showing an example of approach warning displayed on the tracking support terminal according to the first exemplary embodiment of the present invention.

(15) FIG. 15 is a diagram showing another example of approach warning displayed on the tracking support terminal according to the first exemplary embodiment of the present invention.

(16) FIG. 16 is a diagram showing the configuration of the tracking support terminal according to a second exemplary embodiment of the present invention.

(17) FIG. 17 is a flow chart showing the operation (determination process of a distance from the tracking target) of the tracking support terminal according to the second exemplary embodiment of the present invention.

(18) FIG. 18 is a diagram showing an example of buttons provided for the tracking support terminal according to a third exemplary embodiment of the present invention.

(19) FIG. 19 is a sequence diagram showing a take-over operation to a new tracker according to the third exemplary embodiment of the present invention.

(20) FIG. 20 is a sequence diagram showing the take-over operation to the new tracker according to a fourth exemplary embodiment of the present invention.

(21) FIG. 21 is a sequence diagram showing the operations of a fixation camera and the support server according to an exemplary embodiment.

(22) FIG. 22 is a sequence diagram showing the operations of the tracking support terminal and the support server according to an exemplary embodiment.

(23) FIG. 23 is a flow chart showing the operation of the support server according to the exemplary embodiment.

(24) FIG. 24 is a functional block diagram of the support server according to an exemplary embodiment.

(25) FIG. 25 is a functional block diagram of the tracking support terminal according to an exemplary embodiment.

(26) FIG. 26 is a flow chart showing another operation of the tracking support terminal according to an exemplary embodiment.

(27) FIG. 27 is a flow chart showing another operation of the tracking support terminal according to an exemplary embodiment.

(28) FIG. 28 is a sequence diagram showing the operations of the fixation camera and the support server according to an exemplary embodiment.

(29) FIG. 29 is flow chart showing another operation of the tracking support terminal according to an exemplary embodiment.

(30) FIG. 30 is a sequence diagram showing the operations of a fixation camera and a support server according to an exemplary embodiment.

(31) FIG. 31 is a block diagram exemplifying the configuration of an information processing apparatus according to an exemplary embodiment.

PREFERRED MODES

(32) First, the overview of an exemplary embodiment of the present invention will be described with reference to the attached drawings. Note that reference numerals in the drawings used in this overview are added to elements as an example for convenience to help understanding. The

reference numerals are not used to limit the present invention to the illustrated exemplary embodiments. An interblock connection line in the drawing to be referred to in the following description contains both of a bidirectional line and a mono-directional line. A one-way arrow schematically shows a flow of a main signal (data), but the bidirectional transmission is not excluded.

(33) As shown in FIG. 1, the present invention can be realized by a tracking support system which contains a plurality of cameras **10A** arranged in a predetermined monitoring area to transmit video images imaged by them, terminals (hereinafter, to be also referred to as tracking support terminals) respectively carried by a plurality of tracking mission workers (to be simply referred to as “trackers”, hereinafter), and a tracking support apparatus **20A** which transmits instructions to the trackers carrying the terminals based on information received from the terminals and the cameras **10A**, in an exemplary embodiment.

(34) More specifically, the tracking support apparatus **20A** of the tracking support system has a position calculating section **21A** configured to calculate a position of a tracking target person (to be simply referred to as “a tracking target” or “monitoring target”, hereinafter) based on the video images received from the plurality of cameras, a tracker selecting section **22A** configured to select a tracker tracking the tracking target based on position information (or data) of the terminal received from the terminal and the calculated position of the tracking target, an information transmitting section **23A** configured to transmit to the terminal of the selected tracker, information of a distance between the terminal and the tracking target during tracking of the tracking target. The information of the distance between the terminal and the tracking target may be displayed as a distance simply in a numerical value or may be level-displayed to show the distance in the number of elements, by setting one unit element having a unit of 3 m, etc. Regarding the information of the distance between the terminal and the tracking target, an example may be adopted in which an approach warning is outputted by using images, vibration and so on, when the terminal approaches the tracking target too much, as described later.

(35) By adopting the above-mentioned configuration, as shown in FIG. 2, the tracking support apparatus **20A** of the tracking support system transmits the distance to the tracking target to the terminal of the selected tracker. The tracker carries out the tracking while maintaining an appropriate distance, by referring to the information of the distance displayed on the carried terminal.

(36) As mentioned above, according to the present invention, it is possible to check the distance (a suitable interval) to the tracking target without watching the tracking target. Therefore, it is possible to track the tracking target in such a manner that for the tracking target it is difficult to notice the tracker.

(37) When the tracker selecting section **22A** selects the tracker, a method can be adopted in which the movement of the tracking target and the movements of the trackers are estimated, and the tracker nearest to the tracking target is selected at each time. Of course, at that time, it is possible to totally determine the tracker, taking into account the outer appearance of each tracker (clothes, physique, colors of hair and skin, sexuality and so on), skills (walking speed, language, specialty and so on), machineries and materials carried by the tracker, experience, a fatigue degree and a tracking time until now.

First Exemplary Embodiment

(38) Next, a first exemplary embodiment of the present invention will be described in detail with reference to the drawings. FIG. 3 is a diagram showing the configuration of the tracking support system according to the first exemplary embodiment of the present invention. Referring to FIG. 3, the configuration is shown in which a support server **100** receiving images from a plurality of cameras **200** and tracking support terminals **500** carried by the plurality of trackers are connected through a communication network. In the present exemplary embodiment, the plurality of trackers track the tracking target based on instructions from the support server **100** while taking over the

tracking, in the above configuration.

(39) FIG. 4 is a diagram showing the configuration of the tracking support terminal **500** according to the first exemplary embodiment of the present invention. Referring to FIG. 4, the configuration is shown which includes a time managing section **501**, an own terminal position information acquiring section **503**, a display section **504**, a data transmitting and receiving section **505**, a radio interface (hereinafter, to be referred to as “a radio IF”) **506**, and an operation section **507**.

(40) The time managing section **501** has a clock device (timer) and manages the time. When the position information is transmitted to the support server **100**, time information is transmitted together with the position information.

(41) The own terminal position information acquiring section **503** acquires position information showing the position of the own terminal by positioning by use of a satellite positioning system such as GPS (Global Positioning System).

(42) The display section **504** displays tracking support information and warnings such as an approach warning which are received from the support server **100**. The approach warning is not limited to an example of displaying characters and images. For example, the approach warning can be informed by sound and vibration. In such a case, instead of the display section **504**, the approach warning is outputted by a speaker and a vibrator. Also, the characters and images may be used together with sound and vibration.

(43) The data transmitting and receiving section **505** communicates with the support server **100** through the radio IF **506**. Specifically, the data transmitting and receiving section **505** transmits the position information of the own terminal and messages showing the start and end of tracking to the support server **100**. Also, when receiving instructions and approach warnings from the support server **100**, the data transmitting and receiving section **505** transmits the instructions and the approach warnings to the display section **504**. The radio IF **506** and the data transmitting and receiving section **505** are equivalent to the above-mentioned instruction receiving section, and the data transmitting and receiving section **505** and the display section **504** are equivalent to the above-mentioned output section.

(44) The operation section **507** is configured from a touch-panel and buttons receiving various instructions from an operating tracker.

(45) As the above-mentioned tracking support terminal **500**, a smart phone and various wearable terminals with a position measurement function can be desirably used (reference to FIG. 14 and FIG. 15).

(46) Next, the configuration of the support server **100** will be described that is equivalent to the above tracking support apparatus that supports the tracking by grasping the position of the above tracking support terminal **500** and outputting the tracking instructions and the approach warnings. FIG. 5 is a diagram showing the configuration of the support server **100** according to the first exemplary embodiment of the present invention. Referring to FIG. 5, the configuration is shown that includes a tracker information managing section **101**, a tracking target information managing section **102**, a time managing section **103**, a takeover destination determining section **104**, a tracking target position estimating section **105**, a network interface (hereinafter, to be referred to as “NW IF”) **106**, a data transmitting and receiving section **107**, and a distance determining section **108**.

(47) The tracker information managing section **101** manages information of the trackers which track the tracking target. FIG. 6 is a diagram showing an example of tracker information held by the tracker information managing section **101**. In the example of FIG. 6, the tracker information is shown in which a current position, outer appearance information, skill information of each tracker specified by a tracker ID and an address of a tracking support terminal carried by the tracker and so on are related to each other. In a current position information field and a current time information field, information showing the current position of the tracker (e.g. latitude & longitude information) and a time when the tracker was in the position are stored. Also, as the outer appearance

information, information of clothes, physique, colors of hair and skin, sexuality and so on of the tracker are stored. Also, walking speed, languages, and specialty and so on are stored as the skill information. In the field of address of tracking support terminal, a terminal address used to transmit messages and information to the tracking support terminal is stored. Also, although being omitted in an example of FIG. 6, the machineries and materials held by the tracker, the experience, the fatigue degree, the tracking time until now and so on may be recorded as status information. These pieces of information are referred to when the takeover destination determining section **104** selects the trackers to carry out the tracking. The contents of the above tracker information managing section **101** are enough to be set by an operation person who manages the trackers. Of course, each tracker may update items which are more desirable to be changed in real time.

(48) Also, information of a person and so on as a tracking target is stored in the tracking target information managing section **102**. FIG. 7 is a diagram shows an example of tracking target information held by the tracking target information managing section **102**. In the example of FIG. 7, the following information is recorded for each tracking target specified by a tracking target ID: position information (current position), time information when the tracking target was in the position, and at least one item of feature information of the tracking target. As the feature information, for example, features such as clothes, colors of hair and skin, standing height, sexuality and so on of the tracking target are desirably adopted. Also, information usable as the feature information is not limited to the features of outer appearances of the tracking target. For example, if a terminal ID transmitted in radio from a terminal carried by the tracking target, voice (features of voice) and a used language and so on are known, these types of information can be used supplementary.

(49) Also, the time managing section **103** has a time counting device (a timer) and records and manages a tracking start time, a tracking continuation time and so on of each tracking target.

(50) The takeover destination determining section **104** determines a new tracker to start the tracking newly, instead of the tracker on tracking the tracking target at a predetermined event. More specifically, the takeover destination determining section **104** selects the new tracker to start the tracking newly based on the tracking target information held by the tracking target information managing section **102** and the tracker information held by the tracker information managing section **101**. As the selection reference of the tracker, the outer appearance, skill and status information of the tracker are used in addition to the current position of the tracker showing that the tracker can start the tracking of the tracking target. For example, a person of the clothes and sexuality different from those of the tracker being tracking currently can be selected, and if the moving speed of the tracking target is fast, a person who is fast in walking speed and is low in a fatigue level can be selected as a tracker. Also, if it is known that the tracking target has strong wariness, a tracker having an attribute which is not conspicuous in an area where the tracking is carried out can be selected. Also, the attribute of the tracker may be determined previously based on the attribute of the tracking target.

(51) The tracking target position estimating section **105** acquires the position of the tracking target based on the images received from the camera(s) **200** to output to the distance determining section **108**. For example, the position of the tracking target is possible to calculate based on the position of the camera **200** and the position and size of the tracking target in each imaged image. Also, even when the tracking target has disappeared from the imaged images, the tracking target position estimating section **105** may estimate and output the position of the tracking target, if it can be seen from the imaged images that the tracking target advances in certain direction at a uniform velocity. As a method of detecting the tracking target and estimating the position thereof, various methods can be used. For example, the methods described in the above Patent Literatures (e.g. Patent Literature 6) can be used.

(52) The data transmitting and receiving section **107** transmits a tracking instruction to a tracking support terminal **500** of a new tracker to start the tracking newly through the network IF (NW I/F)

106, and instructs a tracking end to a tracking support terminal **500** of the tracker who ends the tracking. Also, the data transmitting and receiving section **107** receives a tracking start report, a tracking end report, the position information of the tracking support terminal, a tracking start time and so on that are transmitted from the tracking support terminal **500** of the tracker through the radio IF **106**.

(53) The distance determining section **108** transmits the approach warning to a tracking support terminal **500** through the data transmitting and receiving section **107** when it is determined from the position of the tracking target estimated by the tracking target position estimating section **105** and the position of the tracker that the distance between the tracking target and the tracker is less than a predetermined threshold.

(54) Note that each section (a processing section) of the tracking support terminal **500** and support server **100** shown in FIG. 4 and FIG. can be realized by making a processor as hardware loaded into these devices execute a computer program for the above processing.

(55) Subsequently, the operation of the present exemplary embodiment will be described in detail with reference to the drawings. First, a mechanism by which the support server **100** specifies the position of the tracking target will be described. FIG. 8 is a sequence diagram showing an operation of the camera according to the first exemplary embodiment of the present invention (transmission processing of the imaged image to the support server). Referring to FIG. 8, the camera **200** transmits the imaged image to the support server **100** in a predetermined time interval (Step **S001**).

(56) The support server **100** acquires the position information from the imaged image received from the camera **200** (Step **S002**). As mentioned above, the position of the tracking target can be calculated based on the position of the camera **200** and the position and size of the tracking target in the imaged image. Also, when the tracking target has disappeared from the image imaged by the camera, the position of the tracking target may be estimated from the movement of the tracking target in past.

(57) Next, the transmission processing of the position information to the support server **100** from the tracking support terminal **500** will be described. FIG. 9 is a flow chart showing the operation of the tracking support terminal **500** according to the first exemplary embodiment of the present invention. Referring to FIG. 9, the tracking support terminal **500** transmits the position information of the own terminal **500** to the support server **100** (Step **S201**).

(58) Next, the tracking support terminal **500** checks whether or not a predetermined (period of) time passed after the last transmission to the support server **100** (Step **S202**). Until the predetermined time passes, the tracking support terminal **500** stands by (NO at Step **S202**). On the other hand, when the predetermined time passed away, the flow returns to the step **S201** in order for the tracking support terminal **500** to transmit new information to the support server **100**.

(59) As mentioned above, the tracking support terminal **500** transmits its own position information to the support server **100** in a predetermined time interval.

(60) Next, an operation will be described in which the above support server **100** transmits a tracking instruction to the tracking support terminal **500** by using the position of the above tracking target and the position of the tracking support terminal. FIG. 10 is a flow chart showing the operation of the support server **100** according to a first exemplary embodiment of the present invention. Referring to FIG. 10, the support server **100** first specifies the position of the tracking target (may be termed as “monitoring target” herein) from a video image imaged by the camera **200**, as described above with reference to FIG. 8. The support server **100** receives the position information of each tracking support terminal **500** from the tracking support terminal **500**, as described above with reference to FIG. 9 (Step **S101**).

(61) Next, the support server **100** checks whether the predetermined time passed away after the last takeover, that is, whether the tracking time of the current tracker exceeded the predetermined time (Step **S102**).

(62) As the check result, when the tracking time of the current tracker exceeds the predetermined

time (YES at Step S102), the support server **100** determines a new tracker as a takeover destination, and transmits a takeover start instruction, and the position information and feature information of the tracking target to the tracking support terminal **500** carried by the new tracker (Step S103). (63) When receiving a monitoring start notification (to be described later) from the tracking support terminal **500** of the new tracker as the takeover destination, the support server **100** transmits a takeover end instruction to the tracking support terminal **500** of the tracker as a takeover source (Step S104).

(64) At the step S102, when the tracking time of the tracker does not exceed the predetermined time (NO at Step S102), the flow returns to step S101 and the support server **100** continues the reception of new information from the camera **200** and the tracking support terminal **500**.

(65) As mentioned above, the support server **100** carries out the operation of changing the tracker who tracks the tracking target, for every predetermined time. "The predetermined time" at the step S102 does not have to be a fixed time. For example, a time obtained by adding a time determined based on a random number to certain time may be used as the predetermined time. That is, it is possible to change the tracker who carries out the monitoring operation, by using a time randomly determined for every time. Thus, it becomes possible to reduce a possibility that the tracking target notices the monitoring. Also, the determination may be carried out, without changing randomly, taking into account the situation that the tracking target is easy to notice the tracker from the attribute of the tracking target (typically, whether the tracking target is a terrorist or a criminal (attentive)), a time zone, a climate condition of a tracking area, a congestion degree in the neighborhood and so on.

(66) Subsequently, the operation of the tracking support terminal which receives an instruction from the support server **100** will be described. FIG. **11** is a flow chart showing the operation of the tracking support terminal **500** according to the first exemplary embodiment of the present invention (instruction reception processing from the support server **100**). Referring to FIG. **11**, when the tracking support terminal **500** is in a stand-by state, i.e. is not used to monitor the tracking target (YES at Step S301), the tracking support terminal **500** displays a tracking start instruction on the display section **504** (Step S303) if receiving a tracking takeover instruction about the tracking target from the support server **100** (YES at Step S302). The tracker sees this display to start the tracking of the tracking target. Then, the tracking support terminal **500** notifies the start of monitoring to the support server **100** (Step S304).

(67) On the other hand, during the tracker carrying the tracking support terminal **500** is in the tracking state, i.e. in monitoring the tracking target (NO at Step S301), the tracking support terminal **500** displays a tracking end instruction on the display section **504** (Step S306) upon receiving the tracking end instruction of the tracking target from the support server **100** (YES at step S305). The tracker views this display to end the tracking of the tracking target, and carries out a predetermined operation to the operation section **507** of the tracking support terminal. Then, the tracking support terminal **500** notifies the end of the tracking to the support server **100** (Step S307).

(68) As mentioned above, the tracker starts or ends the monitoring of a monitoring target person (to be simply referred to as "a monitoring target") according to the instruction from the support server **100** and notifies such effect to the support server **100**.

(69) Subsequently, warning processing to the tracker by the support server **100**, which processing is carried out independently from the above takeover of the tracking target will be described. FIG. **12** is a flow chart showing an operation of the support server according to the first exemplary embodiment of the present invention (determination processing of a distance to a tracking target). Referring to FIG. **12**, the support server **100** first calculates the position information of the tracking target, and acquires the position information of the tracking support terminal **500** carried by the tracker tracking the tracking target from the tracker information managing section **101** (Step S401).

(70) Next, the support server **100** calculates a distance from the tracking support terminal **500** carried by the tracker tracking the tracking target to the tracking target (Step S402).

(71) Next, the support server **100** checks whether or not the calculated distance is less than a predetermined threshold value (Step **S403**).

(72) When the calculated distance is less than the predetermined threshold value (YES at Step **S403**), the support server **100** transmits an approach warning to the tracking support terminal **500** carried by the tracker tracking the tracking target to indicate that the distance to the tracking target becomes shortening (or is too short) (Step **S404**). When the distance calculated at the step **S403** exceeds the predetermined threshold value (NO at Step **S403**), the control flow returns to the step **S401** and the support server **100** stands by until the next calculation timing.

(73) Next, the takeover operation of the tracking target by the support server **100** and the tracking support terminal **500** operating as mentioned above will be described. FIG. **13** is a sequence diagram showing the takeover operation of the tracker according to the first exemplary embodiment of the present invention. Also, in FIG. **13**, it is supposed as an initial state that an instruction has been issued to a tracking support terminal #1 so as to monitor the tracking target (Step **S501**).

(74) The tracking support terminal #1 held by the tracker tracking the tracking target transmits the position information to the support server **100** in a predetermined interval, as described at the step **S201** of FIG. **9** (Step **S502**).

(75) Also, as described at the step **S201** of FIG. **9**, a tracking support terminal #2 carried by a new tracker in a tracking stand-by state transmits its own position information to the support server **100** in a predetermined interval (Step **S502**).

(76) The support server **100** determines the new tracker to whom the tracking of the tracking target is to be taken over (Step **S503**), when a tracking continuation time of the tracker exceeds the predetermined time, as described at the steps **S101** and **S102** of FIG. **10**. In this case, it is supposed that the support server **100** selects the tracking support terminal #2 of another new tracker as a takeover destination.

(77) Then, the support server **100** transmits the following takeover information to the tracking support terminal #2 to instruct the support start for a support object (Step **S504**):

(78) The tracking start instruction;

(79) Position information of the monitoring target; and

(80) Feature information of the monitoring target.

(81) Receiving the instruction, the tracking support terminal #2 displays the position information and feature information of the tracking target received from the support server **100** on the display section **504** to promote the tracking start to the tracker. When a predetermined tracking start operation is carried out to the operation section **507** of the tracking support terminal #2 by the tracker, the tracking support terminal #2 notifies to the support server **100** that the tracking of the tracking target has been started (Step **S506**).

(82) Upon receiving the notice of the monitoring start from the tracking support terminal #2, the support server **100** instructs the tracking end of the tracking target (shift to a tracking standby state) to the tracking support terminal #1 (Step **S507**). Upon receiving the instruction, the tracking support terminal #1 ends the monitoring of the tracking target based on the instruction from the support server **100**, and notifies the end of monitoring of the monitoring target to the support server **100** (Step **S508**).

(83) As mentioned above, according to the first exemplary embodiment of the present invention, it becomes possible to track the tracking target while changing the trackers sequentially in such a manner that the tracking target is difficult to notice the tracker. In the above exemplary embodiment, a case has been described where the number of the trackers tracking the tracking target at a same time is single. However, the tracking may be instructed to a plurality of tracking support terminals of trackers and the takeover may be made to a plurality of trackers.

(84) Also, the role of complementing a part of the above trackers or a mission of the tracker may be achieved by an unmanned aircraft (called "drone"). In this case, the support server **100** transmits a

tracking instruction containing the position information and feature information of the monitoring target to the unmanned aircraft in place of the tracking support terminal. In this way, even if the tracker in charge is put in the situation that the tracking is difficult, the tracking can be continued. (85) Also, in this exemplary embodiment, as described with reference to FIG. 12, an approach warning is issued to the tracker tracking the tracking target when the distance to the tracking target becomes shorter. This approach warning is carried out in a more preferable mode when the tracking support terminal **500** is a wearable terminal.

(86) For example, as shown in FIG. 14, when the tracking support terminal **500** is the wearable terminal of a glass type, an approach warning **901** can be displayed in an information display area of the lens surface. Also, in an example of FIG. 14, when the tracking target is projected into the eyesight of the tracker, a marker **902** showing the tracking target is displayed in superposition. Therefore, the tracker can move to track the tracking target without moving the sight line. In such a situation, when the approach warning **901** is displayed, the tracker can extend the distance to the tracking target by reducing the walking speed or changing a direction of advancing.

(87) Also, as shown in FIG. 15, when the tracking support terminal **500** is the wearable terminal of a watch type, an approach warning **911** can be displayed in an information display area of a main unit **910**. Also, in case of the wearable terminal of the watch-type, an example in which the approach warning is outputted in the form of vibration of a vibrator may be adopted in place of the display of the approach warning **911** in the information display area. The tracking support terminal **500** is not limited to the above wearable forms and may be used of a ring type or a wristband type. Of course, a smart phone and so on can be used as the tracking support terminal **500**.

Second Exemplary Embodiment

(88) Next, a second exemplary embodiment of the present invention will be described in which an output determination function of the approach warning arranged on the side of the support server **100** in the first exemplary embodiment is arranged on the side of the tracking support terminal. The basic configuration and operation of the second exemplary embodiment are same as those of the first exemplary embodiment. Therefore, difference points between them will be described hereinafter. The support server **100** in the present exemplary embodiment has a function of transmitting the position information of the tracking target that is estimated by the tracking target position estimating section **105**, to the tracking support terminal **500**. Because the second exemplary embodiment is same as the first exemplary embodiment except for the above fact, the description is omitted.

(89) FIG. 16 is a diagram showing the configuration of a tracking support terminal **500a** according to the second exemplary embodiment of the present invention. The difference points from the tracking support terminal **500** according to the first exemplary embodiment shown in FIG. 4 reside in the point that a tracking target position information holding section **502** and a distance determining section **508** are added to the tracking support terminal **500a**.

(90) The tracking target position information holding section **502** holds the position information of the tracking target received from the support server **100** for a predetermined time period.

(91) The distance determining section **508** calculates the distance between the tracking target and its own terminal based on the position information of the tracking target received from the support server **100** and the position information of its own terminal. As a result of calculation, when the distance between them is less than the predetermined threshold value, the distance determining section **508** outputs the approach warning to the display section **504**.

(92) Next, the output processing of the above approach warning in the tracking support terminal **500a** of the present exemplary embodiment will be described. FIG. 17 is a flow chart showing the operation of the tracking support terminal **500a** according to the second exemplary embodiment of the present invention (the determination processing of the distance to the tracking target). First, the tracking support terminal **500a** reads the position information of the tracking target from the tracking target position information holding section **502**. Next, the tracking support terminal **500a**

acquires the position information of the tracking support terminal **500a** carried by the tracker tracking the tracking target from the tracker information managing section **101** (Step **S601**).

(93) Next, the tracking support terminal **500a** calculates the distance between the tracking target and the tracking support terminal **500a** carried by the tracker tracking a tracking target (Step **S602**).

(94) Next, the tracking support terminal **500a** checks whether or not the calculated distance is less than the predetermined threshold value (Step **S603**).

(95) When the calculated distance is less than the predetermined threshold value (YES at Step **S603**), the tracking support terminal **500a** displays on the display section **504**, the approach warning showing that the distance to the tracking target is shortening (too short) (Step **S604**). When the distance calculated at the step **S603** is more than the predetermined threshold value (NO at Step **S603**), the control flow returns to the step **S601** and the tracking support terminal **500a** stands by until the next calculation timing.

(96) As mentioned above, the configuration of the present invention may be modified such that the distance between the tracker and the tracking target is calculated on the side of the tracking support terminal **500a** and the approach warning is outputted according to need.

Third Exemplary Embodiment

(97) Next, a third exemplary embodiment of the present invention will be described in which a search function is added to be used when the tracker loses sight of the tracking target (hereinafter, this situation is called a “monitoring failure”, containing a case of the tracking target escaping from the tracker and a case of the tracker noticing tracking of a wrong tracking target). The basic configuration and operation of the third exemplary embodiment are same as those of the first and second exemplary embodiments. Therefore, the different points will be mainly described hereinafter.

(98) The tracking support terminal of the present exemplary embodiment has a function of informing the monitoring failure of the tracking target by the tracker to the support server **100**. FIG. **18** is a diagram showing an example of operation section **507** provided for the tracking support terminal of a watch type in the third exemplary embodiment of the present invention. In the example of FIG. **18**, a “target lost” button **912** indicating the loss of sight of the target and a “takeover request” button **913** which requests a takeover to another tracker based on some reason are independently provided. For example, when the tracker clicks the “target lost” button **912**, a message showing that the tracker lost the sight of the target is transmitted to the support server. In the same way, when the tracker clicks the “takeover request” button **913**, a message showing that the tracker requests the takeover of the tracking to a new tracker is transmitted to the support server. In an example of FIG. **18**, the “target lost” button **912** and the “takeover request” button **913** are displayed separately (independently) on a touch panel of the tracking support terminal of the watch type. However, by integrating both of functions of the buttons, a new button may be provided to request a type of support to the support server. Also, functions corresponding to these buttons may be allocated to mechanical buttons provided for the wearable terminal.

(99) FIG. **19** is a sequence diagram showing a function added to the third exemplary embodiment of the present invention. The sequence of FIG. **19** shows a search operation of the tracking target carried out when the support server **100** having received a monitoring failure report from the tracker cannot find the tracking target from video image data from the camera **200**. Referring to FIG. **19**, when noticing loss of sight of the tracking target, the tracker first clicks the “target lost” button **912** of FIG. **18** (Step **S701**), to report the monitoring failure to the support server **100** (Step **S702**). The position information (monitoring failure position) and time (monitoring failure time) in which the tracking target was confirmed last, or the feature information may be contained in this report (monitoring failure report).

(100) Receiving the monitoring target report, the support server **100** selects a new tracker based on the position information where the tracker confirmed the tracking target last, and transmits the search request of the tracking target to the tracking support terminals #2 of these trackers (Step

S703). The position information where the tracking target was last confirmed and past feature information showing a disguise history may be included in the search request of tracking target in addition to the feature information of the tracking target. In case of receiving the monitoring failure report at the step **S702**, when the support server **100** can find the tracking target from the video image data from the camera **200**, the steps **S703** to **S705** can be omitted. In this case, the support server **100** transmits the tracking target position information specified by the camera **200** and so on to the tracking support terminal #1, and requests re-monitoring of the tracking target (Step **S706**).

(101) Receiving the search request of the tracking target, the tracker searches the tracking target based on the feature information of the tracking target contained in the search request of the tracking target (Step **S704**). In the example of FIG. **19**, as a result of the search of the tracking target, it is supposed that the tracker(s) holding the tracking support terminal(s) #2 discovers the tracking target.

(102) Discovering the tracking target, the tracker operates the tracking support terminal #2 to notify the discovering of the tracking target to the support server **100** (Step **S705**). The position information showing the position where the tracking target has been discovered and the feature information are contained in the notice according to need.

(103) Receiving the position information of the tracking target and so on, the support server **100** transmits the position information of the tracking target and so on to the tracking support terminal #1 to request the re-monitoring of the tracking target (Step **S706**). When discovering the tracking target again (Step **S707**), the tracker operates the tracking support terminal #1 to notify the discovery of the tracking target and the re-start of the tracking to the support server **100** (Step **S708**).

(104) As mentioned above, according to the present exemplary embodiment, it becomes possible for the tracker to deal with a case of losing sight of the tracking target, from the reasons that the tracking target changes clothes, disguises oneself and disappears intentionally from the eyesight of the unmanned aircraft. Especially, as shown in FIG. **18**, by providing the “target lost” button **912** independently, it is possible to report the loss of sight to the support server **100** promptly after losing the sight of the tracking target.

(105) In the above exemplary embodiment, the description is made in which the support server **100** selects the tracking support terminal based on the position information where the tracker carrying the tracking support terminal #1 confirmed the tracking target last. However, a modification may be made so that the support server **100** broadcasts a search request of the tracking target to all the subordinate tracking support terminals. Even in this case, the position information where the tracker #1 confirmed the tracking target last may be contained in the search request of the tracking target. In this way, each tracker can search the tracking target again based on a position and a feature when the tracker #1 confirmed the tracking target last.

(106) In the above exemplary embodiment, the support server **100** instructs the tracker carrying the tracking support terminal #1 to restart the tracking. However, when the position relation between the tracker #1 and the tracking target is not appropriate as the result that the tracking target moves greatly, the control flow advances to the step **S103** of FIG. **10**, and the selection of the tracker to which the takeover is to be carried out may be made.

Fourth Exemplary Embodiment

(107) Next, a fourth exemplary embodiment of the present invention will be described in which a function of requesting to stop the tracking is added to the tracking support terminal. The basic configuration and operation of the fourth exemplary embodiment are same as those of the first and second exemplary embodiments. Therefore, the difference points are mainly described hereinafter.

(108) FIG. **20** is a sequence diagram showing the function added to the fourth exemplary embodiment of the present invention. Referring to FIG. **20**, when the reason that the tracking of the tracking target should be stopped occurs (Step **S1001**), the tracker carrying the tracking support terminal #1 first transmits a tracking stop request (tracking end request) to the support server **100**

(Step S1002). The position information where the tracking target has been confirmed last and the reason that the tracking of the tracking target should be stopped may be included in the tracking stop request (the tracking end request).

(109) As the reasons that the tracking of the tracking target should be stopped, the following reasons are thought of: a case where the tracking target notices the tracking; a case where the tracking target enters an area where it is difficult for the tracker to track the tracking target; a case where a different command is received; and a case where the safety of the tracker should be secured for the reason of the fatigue or injury of the tracker.

(110) Upon receiving the tracking stop request (the tracking end request), the support server **100** determines a new tracker to take over the tracking of the tracking target (Step S1003). In this case, it is supposed that the support server **100** selects the tracker carrying the tracking support terminal #2 as the takeover destination.

(111) The support server **100** transmits the following information to the tracking support terminal #2 to instruct a tracking start of the tracking target (Step S1004): A takeover start instruction; Position information of the tracking target; and Feature information of the tracking target.

(112) The tracker having the tracking support terminal #2 which has received the instruction, starts the tracking of the tracking target based on the position information and feature information of the tracking target which have been received from the support server **100** (Step S1005). The tracking support terminal #2 notifies a start of the monitoring of the tracking target to the support server **100** (Step S1006). The notification of the start of the monitoring of the tracking target may be transmitted in response to an explicit operation from the tracker having the tracking support terminal #2, or may be transmitted automatically based on the start of the monitoring the tracking target by the tracking support terminal #2.

(113) Receiving the notification of the monitoring start from the tracking support terminal #2, the support server **100** instructs the tracking end of the tracking target (a shift to the tracking standby state) to the tracking support terminal #1 (Step S1007). Receiving the instruction, the tracker having the tracking support terminal #1 ends the tracking of the tracking target based on the instruction received from the support server **100**, and notifies the end of the tracking of the tracking target to the support server **100** (Step S1008).

(114) As mentioned above, according to the present exemplary embodiment, when a situation to stop the tracking has occurred on the side of tracker, it is possible for the monitoring to be promptly taken over to another tracker.

(115) As described above, each exemplary embodiment of the present invention has been described. However, the present invention is not limited to the above exemplary embodiments, and further modification, substitution and adjustment can be applied in a range which does not deviate from the basic technical thought of the present invention. For example, a network configuration, the configuration of each element, the expression form of information element and so on shown in each drawing are only an example to help the understanding of the present invention, and are not limited to the configuration shown in these drawings.

(116) Lastly, preferred modes of the present invention are summarized as follows:

(117) [First Mode]

(118) (Reference to a tracking support apparatus according to the above first aspect.)

(119) [Second Mode]

(120) In the above tracking support apparatus, it is preferred that information relating to a distance between the terminal and the tracking target is an approach warning to be transmitted when the distance between the terminal and the tracking target becomes shorter than a predetermined threshold value.

[Third Mode]

(121) In the above tracking support apparatus, a configuration can be adopted in which, when a tracking time of the tracking target by a tracker exceeds a predetermined time, a tracker selecting

section selects another tracker from among the plurality of trackers, and instructs the tracking of the tracking target to a terminal of the selected another tracker, and instructs an end of the tracking of the tracking target to the tracker.

[Fourth Mode]

(122) In the above tracking support apparatus, a time determined randomly at any occurrence can be used as the predetermined time.

[Fifth Mode]

(123) The above tracking support apparatus can adopt a configuration in which the tracker selecting section selects another tracker from among the plurality of trackers when receiving a tracking end request from the tracker, and the information transmitting section instructs the tracking of the tracking target to a terminal of the other tracker and instructs the end of the tracking of the tracking target to the terminal of the tracker.

(124) [Sixth Mode]

(125) In the above tracking support apparatus, when the tracking end request from the tracker is based on a monitoring failure, it is preferred to transmit information of the tracking target to the plurality of trackers and to instruct search of the tracking target.

(126) [Seventh Mode]

(127) (Reference to the terminal according to the above second aspect.)

(128) [Eighth Mode]

(129) It is preferred that the terminal has a button(s) to transmit a tracking end request to the tracking support apparatus.

(130) [Ninth Mode]

(131) In the above terminal, it is preferred that a button used to notify a monitoring failure to the tracking support apparatus and a button used to notify that the tracking target noticed the tracking, to the tracking support apparatus are provided independently as the buttons.

(132) [Tenth Mode]

(133) (Reference to the tracking support method according to above third aspect.)

(134) [Eleventh Mode]

(135) A program which makes a computer installed in a tracking support apparatus which is connected with a plurality of cameras arranged in a predetermined monitoring area to transmit video images imaged by the plurality of cameras, and configured to transmit instructions to a tracker carrying a terminal based on information received from the plurality of cameras and terminals respectively carried by a plurality of trackers, execute: processing of calculating a position of a tracking target based on the video images received from the plurality of cameras; processing of selecting a tracker tracking the tracking target, based on position information of the terminal received from the terminal and the calculated position of the tracking target; and processing of transmitting information of a distance between the tracking target and the terminal carried by the tracker tracking the tracking target, to the terminal of the selected tracker.

[Twelfth Mode]

(136) A program which makes a computer, which is loaded in a terminal configured to receive an indication of a tracking target from a support apparatus which transmits an instruction to a tracker carrying the terminal, based on information received from a plurality of cameras which are arranged in a predetermined monitoring area and transmit video images by the cameras, to execute: processing of calculating a distance between the terminal and the tracking target based on a position of the tracking target received from the support apparatus and a position of the terminal, and processing of outputting information of the calculated distance.

(137) Note that the above-mentioned seventh and tenth to twelfth modes can be developed into the second to sixth modes, like the first mode.

(138) In the disclosure of the present invention, the following modes, too, are possible.

Solutions

(139) A tracking support system that provides a support when tracking a monitoring target while changing the tracker(s) among a plurality of trackers, includes: a plurality of cameras which take a monitoring area, a tracking support terminal which is carried by a tracker, and a support server which is connected with the plurality of cameras and a plurality of tracking support terminals through a communication network, the cameras transmit video images in the monitoring area to the support server through the communication network, the tracking support terminal transmits position information of its own terminal to the support server through the communication network, and the support server selects a next tracker to carry out the tracking to notify to the tracking support terminal based on the position information of the tracking support terminal and position information of the monitoring target specified based on the video images of the cameras or position information of the monitoring target estimated from history records.

Advantages

(140) The monitoring target becomes difficult to notice the monitoring so that a possibility to take an action running away from the monitoring reduces since it is difficult for the tracker to lose sight of the monitoring target at a change of a tracker, and the recovery upon losing sight is easy, or it becomes possible to carry out the tracking in an appropriate distance.

(141) In FIG. 22, as an example of a method of determining a new tracker to take over the monitoring, the following methods are given: a new tracker is randomly selected from among trackers having support terminals moving within a predetermined radius from a current position of the monitoring target; and a new tracker is randomly selected from among trackers having support terminals moving within a predetermined radius from a place where the monitoring target estimated as likely to move in a predetermined time based on action history records of the monitoring target.

(142) Upon selecting, personal features of the tracker e.g., physiognomy such as sexuality, physique, clothes, ornament and wear or the like, walking speed of the tracker and a periphery situation (degree of congestion) may be taken into account. When the tracker changes from an office worker style to an old person style, tracking of the tracking target becomes difficult to be noticed. The moving speed reduces if crowded.

(143) Also, in a determination block of FIG. 26, the predetermined distance may be changed according to a periphery situation. For example, when a degree of congestion is high, it is thought that a possibility that the monitoring target notices the monitoring is low, even if approaching the monitoring target.

(144) Also, in FIG. 30, there are a photograph, physique and clothes of the monitoring target as an example of the monitoring target information.

(145) FIG. 31 is a block diagram which exemplifies a configuration of an information processing apparatus. An analysis server according to an exemplary embodiment may have an information processing apparatus shown in the above figure. The information processing apparatus has a central processing unit (CPU) and a memory. The information processing apparatus may realize part or whole of function of each section of the analysis server by the CPU executing a program stored in the memory.

(146) Mode 1:

(147) A tracking support system that provides a support when tracking a monitoring target while changing a tracker among a plurality of trackers, includes: a plurality of cameras which take a monitoring area, a tracking support terminal which is carried by a tracker, and a support server which is connected with the plurality of cameras and a plurality of tracking support terminals through a communication network, wherein the cameras transmit video images in the monitoring area to the support server through the communication network, wherein the tracking support terminal transmits position information of its own terminal to the support server through the communication network, and wherein the support server selects a next tracker tracking the monitoring target to notify to the tracking support terminal based on the position information of the

tracking support terminal and position information of the monitoring target specified based on the video images from the cameras or position information of the monitoring target estimated from records.

Mode 2:

(148) The tracking support system of mode 1, characterized in that the support server has a NW IF, a data transmitting and receiving section, a monitoring target position estimating section, a tracking target information storing section, a tracker information managing section, a time managing section, and a takeover destination determining section.

(149) Mode 3:

(150) The tracking support system of mode 1 or 2, characterized in that each of the plurality of tracking support terminals includes a radio IF, a display section, an own terminal position information acquiring section, a monitoring target position information holding section, a time managing section, a position relation determining section, a data transmitting and receiving section and an operating section.

(151) Mode 4:

(152) The tracking support system according to any one of modes 1 to 3, characterized in that the plurality of tracking support terminals report provision requests of the position information of the monitoring target to the support server, when receiving an input of having missed the monitoring target to the operation section, that the support server notifies the position information of the monitoring target to the tracking support terminal of a requesting source, and that the tracking support terminal of the requesting source displays the notified position information of the monitoring target on the display section.

Mode 5:

(153) The tracking support system according to any one of modes 1 to 4, characterized in that the plurality of tracking support terminals calculate the position relation of the tracker and the monitoring target based on the position information of its own terminal and the position information of the monitoring target, and displays a warning on the display section of the tracking support terminal when the distance exceeds a predetermined distance (an upper limit and a lower limit).

(154) It is possible to modify and adjust the exemplary embodiments and exemplifications in a range of the whole disclosure of the present invention (containing claims) based on the basic technical thought. Also, it is possible to combine and select various disclosed elements (containing each element of each claim, each element of each exemplary embodiment or each exemplification and each element of each drawing and so on) in the disclosure of the present invention. That is, of course, the present invention contains various modifications and changes which will be possible to be attained by a skilled person according to the entire disclosure including claims and the technical thought. Especially, a numerical value range described in the Description and Claims should be interpreted as being specifically described even when an optional numerical value or a small range is not specified particularly.

REFERENCE SIGNS LIST

(155) **10A**, **200**: camera **20A**: tracking support apparatus **21A**: position calculating section **22A**: tracker selecting section **23A**: information transmitting section **100**: support server **101**: tracker information managing section **102**: tracking target information managing section **103**: time managing section **104**: takeover destination determining section **105**: tracking target position estimating section **106**: network interface (network IF) **107**: data transmitting and receiving section **108**: distance determining section **500**, **500a**: tracking support terminal **501**: time managing section **502**: tracking target position information holding section **503**: own terminal position information acquiring section **504**: display section **505**: data transmitting and receiving section **506**: radio interface (radio IF) **507**: operation section **508**: distance determining section **900**, **910**: (wearable terminal) main unit **902**: marker **901**, **911**: approach warning **912**, **913**: button

Claims

1. A tracking support apparatus comprising: a receiver configured to receive a notification of a monitoring failure from a terminal of a current tracker instructed to track a tracking target; and an information transmitting section configured to transmit a search request to search the tracking target to a plurality of terminals, each one of the plurality of terminals being carried by a tracker, wherein the receiver is configured to receive, from the terminal, a notification that the tracker requests takeover of the tracking of the tracking target to a new tracker, independently from notification of the monitoring failure.
2. The tracking support apparatus according to claim 1, wherein the receiver is configured to receive confirmation information from the terminal of the current tracker, the confirmation information including information on a position where the current tracker confirms the tracking target, and wherein the information transmitting section is configured to transmit the search request including information on the position where the current tracker confirms the tracking target in the last confirmation information.
3. The tracking support apparatus according to claim 2, wherein the receiver is configured to receive a discovery notification including position information of the tracking target from at least one of the plurality of terminals, and wherein the information transmission section is further configured to transmit the position information of the tracking target included in the discovery notification to the terminal of the current tracker, when the discovery notification is received.
4. The tracking support apparatus according to claim 3, wherein the discovery information includes feature information of the tracking target.
5. The tracking support apparatus according to claim 3, wherein the tracker selecting section is configured to select a new takeover tracker instructed to track the tracking target, using position information of the plurality of terminals and the position information of the tracking target in the discovery notification, when the discovery information is received and a position relation between the selected tracker and a target position is determined to be not appropriate, the target position being indicated by the position information of the tracking target in the discovery notification.
6. The tracking support apparatus according to claim 1, the apparatus further comprising a position calculating section configured to calculate a position of the tracking target using video images received from a plurality of cameras, the position calculating section being connected with the plurality of cameras arranged in a predetermined monitoring area to transmit video images taken by the plurality of cameras, wherein the receiver is configured to receive the position information of the plurality of terminals, each one of the plurality of terminals being carried by a tracker, wherein the tracking support apparatus comprises a tracker selecting section configured to select the current tracker instructed to track the tracking target, using the position information of the plurality of terminals and the calculated position of the tracking target, and wherein the information transmitting section is configured to transmit information of a distance between the tracking target and the terminal during tracking of the tracking target to the terminal of the selected current tracker.
7. A tracking support method by a tracking support apparatus, the method comprising: receiving a notification of a monitoring failure from a terminal of a current tracker instructed to track a tracking target; transmitting a search request to search the tracking target to a plurality of terminals, each one of the plurality of terminals being carried by a tracker; and receiving, from the terminal, a notification that the tracker requests takeover of the tracking of the tracking target to a new tracker, independently from notification of the monitoring failure.
8. The tracking support method according to claim 7, the method further comprising: receiving confirmation information from the terminal of the current tracker, the confirmation information including information on a position where the current tracker confirms the tracking target; and transmitting the search request including information on the position where the current tracker

confirms the tracking target in the last conformation information.

9. The tracking support method according to claim 8, the method further comprising: receiving a discovery notification including position information of the tracking target from at least one of the plurality of terminals; and transmitting the position information of the tracking target included in the discovery notification to the terminal of the current tracker, when the discovery notification is received.

10. The tracking support method according to claim 9, wherein the discovery information includes feature information of the tracking target.

11. The tracking support method according to claim 9, the method further comprising selecting a new takeover tracker instructed to track the tracking target, using position information of the plurality of terminals and the position information of the tracking target in the discovery notification, when the discovery information is received and a position relation between the selected tracker and a target position is determined to be not appropriate, the target position being indicated by the position information of the tracking target in the discovery notification.

12. The tracking support method according to claim 7, the method further comprising: calculating a position of the tracking target using video images received from a plurality of cameras, the position calculating section being connected with the plurality of cameras arranged in a predetermined monitoring area to transmit video images taken by the plurality of cameras; receiving the position information of the plurality of terminals, each one of the plurality of terminals being carried by a tracker; selecting the current tracker instructed to track the tracking target, using the position information of the plurality of terminals and the calculated position of the tracking target; and transmitting information of a distance between the tracking target and the terminal during tracking of the tracking target to the terminal of the selected current tracker.

13. A non-transitory computer readable medium storing a program causing a computer to execute processing comprising: receiving a notification of a monitoring failure form a terminal of a current tracker instructed to track a tracking target; transmitting a search request to search the tracking target to a plurality of terminals, each one of the plurality of terminals being carried by a tracker; and receiving, from the terminal, a notification that the tracker requests takeover of the tracking of the tracking target to a new tracker, independently from notification of the monitoring failure.

14. The non-transitory computer readable medium according to claim 13, storing the program causing the computer to execute processing comprising: receiving confirmation information from the terminal of the current tracker, the confirmation information including information on a position where the current tracker confirms the tracking target; and transmitting the search request including information on the position where the current tracker confirms the tracking target in the last conformation information.

15. The non-transitory computer readable medium according to claim 14, storing the program causing the computer to execute processing comprising: receiving a discovery notification including position information of the tracking target from at least one of the plurality of terminals; and transmitting the position information of the tracking target included in the discovery notification to the terminal of the current tracker, when the discovery notification is received.

16. The non-transitory computer readable medium according to claim 15, wherein the discovery information includes feature information of the tracking target.

17. The non-transitory computer readable medium according to claim 15, storing the program causing the computer to execute processing comprising: selecting a new takeover tracker instructed to track the tracking target, using position information of the plurality of terminals and the position information of the tracking target in the discovery notification, when the discovery information is received and a position relation between the selected tracker and a target position is determined to be not appropriate, the target position being indicated by the position information of the tracking target in the discovery notification.

18. The non-transitory computer readable medium according to claim 13, storing the program

causing the computer to execute processing comprising: calculating a position of the tracking target using video images received from a plurality of cameras, the position calculating section being connected with the plurality of cameras arranged in a predetermined monitoring area to transmit video images taken by the plurality of cameras; receiving the position information of the plurality of terminals, each one of the plurality of terminals being carried by a tracker; selecting the current tracker instructed to track the tracking target, using the position information of the plurality of terminals and the calculated position of the tracking target; and transmitting information of a distance between the tracking target and the terminal during tracking of the tracking target to the terminal of the selected current tracker.
