

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402384
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Wang; Sheng-Hsiung et al.

Standard cell design with dummy padding

Abstract

A semiconductor structure includes a substrate; a first column of active regions over the substrate; a second column of active regions over the substrate; and a dummy padding disposed between the first and the second columns from a top view. The dummy padding includes multiple dummy regions. A first dummy region of the multiple dummy regions is disposed between a first active region in the first column of active regions and a second active region in the second column of active regions. An outer boundary line tracing an edge of the first active region, an edge of the first dummy region, and an edge of the second active region includes at least two substantially 90-degree bends from a top view. The first and the second active regions include a semiconductor material doped with a same dopant.

Inventors: Wang; Sheng-Hsiung (Zhubei, TW), Lin; Chun-Yen (Hsinchu, TW), Lin; Yen-Hung (Hsinchu, TW), Hou; Yuan-Te (Hsinchu, TW), Hsieh; Tung-Heng (Hsinchu County, TW)

Applicant: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Family ID: 1000008780739

Assignee: TAIWAN SEMICONDUCTOR MANUFACTURING COMPANY, LTD.
(Hsinchu, TW)

Appl. No.: 17/749842

Filed: May 20, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230253477 A1	Aug. 10, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **H10D64/01** (20250101); **B82Y10/00** (20110101); **H10D30/01** (20250101); **H10D30/43** (20250101); **H10D30/62** (20250101); **H10D30/67** (20250101); **H10D30/69** (20250101); **H10D62/10** (20250101); **H10D62/822** (20250101); **H10D84/01** (20250101); **H10D84/03** (20250101); **H10D84/83** (20250101); **H10D84/85** (20250101); **H10D89/10** (20250101)

U.S. Cl.:

CPC **H10D64/017** (20250101); **H10D62/115** (20250101); **H10D84/856** (20250101);

Field of Classification Search

CPC: H01L (29/66545); H01L (27/0922); H01L (29/0649); H01L (21/823412); H01L (21/823481); H01L (27/0207); H01L (27/088); H01L (29/0673); H01L (27/0886); H01L (21/823431); H01L (29/165); H01L (29/42392); H01L (29/66439); H01L (29/775); H01L (29/7848); H01L (27/092); H01L (29/0638); H01L (27/0924); H01L (29/785); B82Y (10/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6838713	12/2004	Gheewala et al.	N/A	N/A
8759885	12/2013	Jain et al.	N/A	N/A
10423078	12/2018	Shen et al.	N/A	N/A
2005/0254280	12/2004	Yamauchi	N/A	N/A
2011/0049575	12/2010	Tanaka	N/A	N/A
2018/0240890	12/2017	Yang et al.	N/A	N/A
2020/0035705	12/2019	Kim	N/A	H01L 21/823481
2020/0050728	12/2019	Kim et al.	N/A	N/A
2020/0105761	12/2019	Liaw	N/A	H01L 21/823821
2020/0176303	12/2019	Yang et al.	N/A	N/A
2021/0265481	12/2020	Huang et al.	N/A	N/A
2021/0336004	12/2020	Huang et al.	N/A	N/A
2021/0391421	12/2020	Chu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2009130167	12/2008	JP	N/A
2005-0063674	12/2004	KR	N/A
2020-0089052	12/2004	KR	N/A
20150034506	12/2014	KR	N/A
201916367	12/2018	TW	N/A
202141638	12/2020	TW	N/A

OTHER PUBLICATIONS

Primary Examiner: Assouman; Herve-Louis Y

Attorney, Agent or Firm: HAYNES AND BOONE, LLP

Background/Summary

PRIORITY (1) This claims the benefits of U.S. Prov. App. Ser. No. 63/308,831, filed Feb. 10, 2022, the entire disclosure of which is incorporated herein by reference.

BACKGROUND

(1) The semiconductor integrated circuit (IC) industry has experienced exponential growth. Technological advances in IC materials and design have produced generations of ICs where each generation has smaller and more complex circuits than the previous generation. In the course of IC evolution, functional density (i.e., the number of interconnected devices per chip area) has generally increased while geometry size (i.e., the smallest component (or line) that can be created using a fabrication process) has decreased. This scaling down process generally provides benefits by increasing production efficiency and lowering associated costs. Such scaling down has also increased the complexity of processing and manufacturing ICs and, for these advancements to be realized, similar developments in IC processing and manufacturing are needed.

(2) For example, when implementing ICs using standard cells, it is desirable to reduce leakage current between active regions, between an active region and adjacent wells, and between an active region and adjacent source/drain contacts.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure is best understood from the following detailed description when read with the accompanying figures. It is emphasized that, in accordance with the standard practice in the industry, various features are not drawn to scale and are used for illustration purposes only except explicitly disclosed. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1A illustrates a fragmentary top view of a semiconductor structure, such as an integrated circuit having standard cells, according to various aspects of the present disclosure.

(3) FIGS. 1A-1 and 1A-2 illustrate another semiconductor structure for comparison with embodiments of the present disclosure.

(4) FIGS. 1B-1, 1B-2, and 1B-3 illustrate fragmentary cross-sectional views of the semiconductor structure in FIG. 1A taken along line B-B as shown in FIG. 1A, according to embodiments of the present disclosure.

(5) FIGS. 1C-1 and 1C-2 illustrate fragmentary cross-sectional views of the semiconductor structure in FIG. 1A taken along line C-C as shown in FIG. 1A, according to embodiments of the present disclosure.

(6) FIGS. 2, 3, 4, 5, 6A, 7, 8, 9, 10, 11, 12, 13, and 14 illustrate fragmentary top views of the semiconductor structure of FIG. 1A, according to alternative embodiments of the present disclosure.

(7) FIGS. 6B-1 and 6B-2 illustrate fragmentary cross-sectional views of the semiconductor structure in FIG. 6A taken along line B-B as shown in FIG. 6A, according to embodiments of the present disclosure.

DETAILED DESCRIPTION

(8) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(9) Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(10) Further, when a number or a range of numbers is described with “about,” “approximate,” and the like, the term is intended to encompass numbers that are within a reasonable range considering variations that inherently arise during manufacturing as understood by one of ordinary skill in the art. For example, the number or range of numbers encompasses a reasonable range including the number described, such as within $\pm 10\%$ of the number described, based on known manufacturing tolerances associated with manufacturing a feature having a characteristic associated with the number. For example, a material layer having a thickness of “about 5 nm” can encompass a dimension range from 4.25 nm to 5.75 nm where manufacturing tolerances associated with depositing the material layer are known to be $\pm 15\%$ by one of ordinary skill in the art.

(11) The present disclosure relates to semiconductor structures and methods thereof, and more particularly to providing dummy paddings between adjacent active regions of standard cells (e.g., standard CMOS cells) in a semiconductor structure such as an integrated circuit (IC). The standard cells may include NPN cells, PNP cells, NPPN cells, PNPN cells, and/or other types of cells. Here, “N” refers to an n-type doped active region, and “P” refers to a p-type doped active region. For example, an NPN cell refers to a cell having an n-type doped active region adjacent to a p-type doped active region that is adjacent to another n-type doped active region. The dummy paddings help increase design margin and reduce leakage current among active regions, between active regions and nearby source/drain contacts, and between active regions and nearby wells. Using the disclosed dummy paddings can increase the maximum operating frequency of the standard cells, thereby increasing the operational speed of the semiconductor structure incorporating such standard cells.

(12) FIG. 1A illustrates a fragmentary top view of a semiconductor structure **200**, such as an integrated circuit having standard cells, according to various aspects of the present disclosure. Referring to FIG. 1A, the semiconductor structure **200** includes various active regions **104** (including active regions **104-1** and **104-2**) arranged into a column along the Y direction and various active regions **105** (including active regions **105-1** and **105-2**) arranged into a column along the Y direction. The active regions **104** and **105** are oriented lengthwise along the X direction and widthwise along the Y direction. The active regions **104-1** and **105-1** are doped with the same type

of dopant(s). The active regions **104-2** and **105-2** are doped with the same type of dopant(s). Essentially, the active regions **104-1** and **105-1** may be same (though they may have different widths), and the active regions **104-2** and **105-2** may be same (though they may have different widths). They are labeled differently for the simplicity of referencing. The dopants in the active regions **104-1** and **105-1** and the dopants in the active regions **104-2** and **105-2** are of opposite conductivity types. For example, the dopants in the active regions **104-1** and **105-1** are of n-type conductivity and the dopants in the active regions **104-2** and **105-2** are of p-type conductivity, or vice versa. For example, the active regions **104-1**, **104-2**, **105-1**, and **105-2** may include silicon, silicon germanium, or other semiconductor material(s) doped with appropriate dopants, such as phosphorus or arsenic for n-type conductivity or boron for p-type conductivity.

(13) In the present embodiment, the active regions **104** and **105** are formed over wells **103**. For example, the active regions **104-1** and **105-1** are formed over wells **103-1** and the active regions **104-2** and **105-2** are formed over wells **103-2**. In an embodiment, the wells **103-1** and the active regions **104-1** and **105-1** are doped with dopants of opposite conductivity types, and the wells **103-2** and the active regions **104-2** and **105-2** are doped with dopants of opposite conductivity types. FIG. 1A also illustrates boundary lines **112** between each well **103-2** and adjacent wells **103-1**.

(14) The active regions **104** are isolated from each other along the Y direction by an isolation structure **107** (see FIGS. 1C-1, 1C-2), such as shallow trench isolation (STI). Similarly, the active regions **105** are isolated from each other along the Y direction by the isolation structure **107** (see FIGS. 1C-1, 1C-2).

(15) In the illustrated embodiment, the top two active regions **104-1** and **104-2** form a standard CMOS cell **102-1**, the bottom two active regions **104-1** and **104-2** form another standard CMOS cell **102-2**, and the two active regions **105-1** and the active region **105-2** form a standard CMOS cell **102-3**. In an embodiment, the two cells **102-1** and **102-2** are both NP cells and the cell **102-3** is an NPN cell (i.e., the active regions **104-1** and **105-1** are n-type doped and the active regions **104-2** and **105-2** are p-type doped). In an alternative embodiment, the two cells **102-1** and **102-2** are both PN cells and the cell **102-3** is a PNP cell (i.e., the active regions **104-1** and **105-1** are p-type doped and the active regions **104-2** and **105-2** are n-type doped).

(16) The active region **105-1** is wider than the active region **104-1** along the Y direction. The active region **105-2** is wider than each active region **104-2** along the Y direction. By having active regions **105-1** and **105-2** wider than the active region **104-1** and **104-2**, the cell **102-3** is provided with more current capability than each cell **102-1** and **102-2**. The well **103-1** is wider in the column having active regions **105** than in the column having active regions **104**. The well **103-2** is narrower in the column having active regions **105** than in the column having active regions **104**. As illustrated in FIG. 1A, a boundary line **112** between a well **103-1** and a well **103-2** has two 90-degree (or near 90-degree) bends (or angles or jogs) at where the widths of the wells **103-1** and **103-2** change.

(17) Still referring to FIG. 1A, the semiconductor structure **200** includes various dummy regions **106** (including dummy regions **106-1** and **106-2**) in a column (also referred to as a dummy padding **106**) that is disposed between the column of active regions **104** and the column of active regions **105**. Specifically, a dummy region **106-1** is disposed laterally (along the X direction) between the top active region **104-1** and the top active region **105-1**, another dummy region **106-1** is disposed laterally between the bottom active region **104-1** and the bottom active region **105-1**. Further, a dummy region **106-2** is disposed laterally between the active regions **104-2** and the active region **105-2**.

(18) In an embodiment, dummy regions **106-1** include the same semiconductor material(s) as in the active regions **104-1** and **105-1** and are doped with the same dopant(s) as in the active regions **104-1** and **105-1**. Also, dummy regions **106-2** include the same semiconductor material(s) as in the active regions **104-2** and **105-2** and are doped with the same dopant(s) as in the active regions **104-2** and **105-2**. What makes the regions **106** “dummy” is that there are no functional transistors

formed in these regions. For example, there may be no functional gates formed over dummy regions **106**, or that there may be no contacts formed over dummy regions **106** such that dummy regions **106** are not electrically connected to other parts of the semiconductor structure **200**. In contrast, there are functional transistors formed in the active regions **104** and **105**. In another embodiment, dummy regions **106** include one or more dielectric materials. Thus, they are not conductive or semiconductive.

(19) In various embodiments, FIGS. **1A**, **2-5**, **6A**, and **7-14** illustrate layout views (or layouts) of the semiconductor structure **200**. In such embodiments, the dummy regions **106** may be implemented in a different CAD (Computer Aided Design) layer than the active regions **104** and **105** such that CAD tools may process the dummy regions **106** differently than the active regions **104** and **105**. For example, CAD tools may perform OPC (Optical Proximity Correction) to the active regions **104** and **105** so that the shapes of the active regions **104** and **105** can be manufactured as close to their original design as possible (such as rectangular or substantially rectangular), even if such OPC would change or distort the shapes of the dummy regions **106**. This provides benefits that there are increased design margin and reduced leakage between adjacent active regions **104** and **105** and between active regions **104** and **105** and nearby source/drain contacts, as will be discussed below with reference to FIG. **1A-2**.

(20) Still referring to FIG. **1A**, the semiconductor structure **200** further includes isolation structures **235** that are oriented lengthwise along the Y direction and disposed between the dummy regions **106** and the active regions **104** and **105**. In an embodiment, the isolation structures **235** may be dielectric gates or CPODE (Continuous Poly On Diffusion Edge). The isolation structures **235** include one or more dielectric materials such as silicon oxide and silicon nitride.

(21) The benefits of having the dummy regions **106** are explained below by comparing the semiconductor structure **200** with a semiconductor structure **200'** illustrated in FIGS. **1A-1** and **1A-2**. The semiconductor structure **200'** is similar to the semiconductor structure **200**, but without the dummy regions **106**. The semiconductor structure **200'** shown in FIGS. **1A-1** and **1A-2** is not prior art and is merely used to explain the benefits of having the dummy regions **106** in the semiconductor structure **200**.

(22) Referring to FIG. **1A-1**, the bends in the boundary line **112** coincide with the isolation structure **235**. The smallest distance between the active region **104-2** and the well **103-1** is the distance **d2** from a corner of the active region **104-2** to a corner of the well **103-1**, illustrated by a double arrow in FIG. **1A-1**. The distance **d2** may or may not meet the manufacturer's design rules. In contrast, by having the dummy regions **106**, the bends in the boundary line **112** are disposed into the space between the isolation structures **235** as shown in FIG. **1A**. As a result, any distance from an edge of the active region **104-2** and an edge of the well **103-1** in FIG. **1A** is greater than **d2**, which beneficially reduces potential leakage between the active region **104-2** and the well **103-1**.

(23) Referring to FIG. **1A-2**, a source/drain contact **275** is disposed on the active region **104-2**. Although not shown, source/drain contacts are also disposed on various active regions **104** and **105** in the embodiment in FIG. **1A**. The source/drain contact **275** may include a conductive barrier layer and a metal fill layer over the conductive barrier layer. The conductive barrier layer may include titanium (Ti), tantalum (Ta), tungsten (W), cobalt (Co), ruthenium (Ru), or a conductive nitride such as titanium nitride (TiN), titanium aluminum nitride (TiAlN), tungsten nitride (WN), tantalum nitride (TaN), or combinations thereof. The metal fill layer may include tungsten (W), cobalt (Co), molybdenum (Mo), ruthenium (Ru), or other metals.

(24) As shown in FIG. **1A-2**, the source/drain contact **275** is disposed on the active region **104-2** and extends beyond the active region **104-2** along the Y direction from a top view. FIG. **1A-2** also illustrates peripheries **113** of the active regions **104-2** after fabrication. The peripheries **113** extend substantially straight except in the vicinity where the active regions **104-2** meet the active region **105-2**. In this vicinity, the peripheries **113** become curved due to optical proximity effects and/or other manufacturing effects (such as etching). As a result, the two active regions **104-2** become

closer to each other after fabrication than they are originally designed (for example, in the design layout), which might increase leakage between the two active regions **104-2**. Further, the bottom active region **104-2** becomes closer to the source/drain contact **275** than it is originally designed, which might increase leakage between the active region **104-2** and the source/drain contact **275**.

(25) In contrast, in the semiconductor structure **200** shown in FIG. **1A**, the shapes of the active regions **104** and **105** can be manufactured as close to their original shape as possible (e.g., rectangular or substantially rectangular), for example, by curving the edge of the dummy region **106-2** inwards during design or during OPC. Since the dummy region **106-2** does not provide any functional transistors, such change to the dummy region **106-2** does not have any adverse effects, while providing design margin for the active regions **104** and **105**. Advantageously, the semiconductor structure **200** shown in FIG. **1A** can have reduced leakage between the active regions **104**, **105**, and between an active region **104** or **105** and adjacent source/drain contacts than the semiconductor structure **200'** shown in FIG. **1A-2**.

(26) Referring to FIG. **1A**, in the present embodiment, a height (or width) **H1** of the active region **104-1** is greater than a height (or width) **H4** of the dummy region **106-1** and is smaller than a height (or width) **H3** of the active region **105-1** (i.e., $H4 < H1 < H3$). An outer boundary line **110** tracing an edge of the active region **104-1**, an edge of the dummy region **106-1**, and an edge of the active region **105-1** has four 90-degree or substantially 90-degree bends from a top view. Further, a height (or width) **H2** of the active region **105-2** is less than a height (or width) **H5** of the dummy region **106-2** that is less than a distance **D1** from the top edge of the top active region **104-2** to the bottom edge of the bottom active region **104-2** (i.e., $H2 < H5 < D1$). Also, a height (or width) **H0** of the active region **104-2** is less than the height **H2**. In an embodiment, the height **H0** is equal to or substantially equal to the height **H1**. Further, **H3** is less than **H2**, and half of **H3** is less than **H4**. The design of these dimensions helps increase the design margin associated with the active regions (**104-1**, **104-2**, **105-1**, **105-2**) and the wells (**103-1**, **103-2**) as well as between the active regions and nearby source/drain contacts (not illustrated in FIG. **1A**, but see FIG. **1A-2**).

(27) FIGS. **1B-1** and **1B-2** illustrate fragmentary cross-sectional views of the semiconductor structure **200** taken along line B-B shown in FIG. **1A**, according to embodiments of the present disclosure where the dummy regions **106** include doped or undoped semiconductor material(s). In the embodiment shown in FIG. **1B-1**, each of the active regions **104** and **105** includes two source/drain regions **218** and a semiconductor channel region **208** connecting the two source/drain regions **218**. The semiconductor channel region **208** may be in the shape of a semiconductor fin (e.g., for FinFETs). In the embodiment shown in FIG. **1B-2**, each of the active regions **104** and **105** includes two source/drain regions **218** and a semiconductor channel region **208** connecting the two source/drain regions **218**. The semiconductor channel region **208** includes a stack of nano-sized channels **210** (e.g., for gate-all-around FETs). In each of the FIGS. **1B-1** and **1B-2**, the dummy regions **106** may be formed in the same processes as for the source/drain regions **218**. For example, the dummy regions **106** may be formed by etching into semiconductor fins to form trenches and epitaxially growing semiconductor materials in the trenches. Further, the dummy regions **106** may be doped in the same way as for the source/drain regions **218**.

(28) The semiconductor structure **200** includes a substrate **201**, the wells **103**, source/drain regions **218**, the dummy regions **106**, channel regions **208**, gate structures **242**, dielectric layers **268**, and other elements (such as source/drain contacts **275** and other structures) not shown in FIGS. **1B-1** and **1B-2**. The various elements of the semiconductor structure **200** are further discussed below.

(29) In an embodiment, the substrate **201** is a bulk silicon substrate (i.e., including bulk single-crystalline silicon). The substrate **201** may include other semiconductor materials in various embodiments, such as germanium, silicon carbide, gallium arsenide, gallium phosphide, indium phosphide, indium arsenide, indium antimonide, SiGe, GaAsP, AlInAs, AlGaAs, GaInAs, GaInP, GaInAsP, or combinations thereof. In an alternative embodiment, substrate **201** is a semiconductor-on-insulator substrate, such as a silicon-on-insulator (SOI) substrate, a silicon germanium-on-

insulator (SGOI) substrate, or a germanium-on-insulator (GOI) substrate. The wells **103** (such as the wells **103-1** and **103-2**) are formed in and/or on the substrate **201** by doping portions of the substrate **201** with appropriate dopants.

(30) The source/drain regions **218** include epitaxially grown semiconductor material(s) with proper n-type or p-type dopants. For example, each of the source/drain regions **218** may include silicon and may be doped with carbon, phosphorous, arsenic, other n-type dopant, or combinations thereof (for example, forming Si:C epitaxial source/drain features, Si:P epitaxial source/drain features, or Si:C:P epitaxial source/drain features). Alternatively, each of the source/drain regions **218** may include silicon germanium or germanium and may be doped with boron, other p-type dopant, or combinations thereof (for example, forming Si:Ge:B epitaxial source/drain features). The source/drain regions **218** may be formed by etching trenches on both sides of the respective channel region **208**, and epitaxially growing semiconductor material(s) in the trenches. In an embodiment, the semiconductor channel regions **208** may include silicon and may be portions of a semiconductor fin. Alternatively, the semiconductor channel regions **208** may include other suitable semiconductor material(s).

(31) As discussed above, the dummy regions **106** may be formed using the same processes as for the source/drain regions **218**. Thus, the dummy regions **106** may include silicon and may be doped with carbon, phosphorous, arsenic, other n-type dopant, or combinations thereof. Alternatively, the dummy regions **106** may include silicon germanium or germanium and may be doped with boron, other p-type dopant, or combinations thereof. Further, the top surface of the dummy regions **106** may be above, below, or substantially coplanar with the top surface of the semiconductor channel regions **208**, depending on the epitaxial growth process that forms the dummy regions **106**. The bottom surface of the dummy regions **106** may be curved or flat depending on the etching process(es) that etches trenches into a semiconductor fin and the substrate **201**.

(32) The isolation structures **235** may be formed by removing dummy gates formed at the boundary of the active regions **104**, **105** and the dummy regions **106** to form isolation trenches, optionally extending the isolation trenches into the substrate **201**, and filling the isolation trenches with one or more dielectric materials. The one or more dielectric materials may include silicon oxide, silicon nitride, silicon oxynitride, fluoride-doped silicate glass (FSG), a low-k dielectric material, and/or other suitable insulating material. In an embodiment, the isolation structures **235** are formed after the source/drain regions **218** have been formed. Further, the isolation structures **235** may be formed before, during, or after a replacement gate process that forms gate structures **242**. In the embodiments shown in FIGS. **1B-1** and **1B-2**, the isolation structures **235** extends above the top surface of the dummy regions **106**.

(33) The gate structures **242** engage the respective channel regions **208** and may include one or more gate dielectric layers, one or more work function metal layers, a bulk metal layer, and gate spacers. For simplicity, these elements are not individually illustrated. The one or more gate dielectric layers may include a dielectric material, such as SiO₂, HfSiO, SiON, a high-k dielectric material such as HfO₂, HfSiO, HfSiO₂, HfSiON, HfLaO, HfTaO, HfTiO, HfZrO, HfAlO_x, ZrO, ZrO₂, ZrSiO₂, AlO, AlSiO, Al₂O₃, TiO, TiO₂, LaO, LaSiO, Ta₂O₃, Ta₂O₅, Y₂O₃, SrTiO₃, BaZrO, BaTiO₃ (BTO), (Ba,Sr)TiO₃ (BST), Si₃N₄, hafnium dioxide-alumina (HfO₂—Al₂O₃) alloy, other suitable high-k dielectric material, or combinations thereof. The one or more work function metal layers may include a p-type work function material and/or an n-type work function material. A p-type work function material may include TiN, TaN, TaSN, Ru, Mo, Al, WN, WCN, ZrSi₂, MoSi₂, TaSi₂, NiSi₂, other p-type work function material, or combinations thereof. An n-type work function material may include Ti, Al, Ag, Mn, Zr, TiAl, TiAlC, TiAlSiC, TaC, TaCN, TaSiN, TaAl, TaAlC, TaSiAlC, TiAlN, other n-type work function material, or combinations thereof. The bulk metal layer includes a suitable conductive material, such as Co, Al, W, and/or Cu. The bulk metal layer may additionally or collectively include other

metals, metal oxides, metal nitrides, other suitable materials, or combinations thereof. The gate spacers may include a suitable dielectric material such as silicon oxide and silicon nitride.

(34) The dielectric layers **268** may include one or more contact etch stop layers (CESL) and one or more interlayer dielectric (ILD) layers. The CESL may include silicon and nitrogen, such as silicon nitride or silicon oxynitride. The ILD layer(s) may include a dielectric material such as silicon oxide, silicon nitride, silicon oxynitride, TEOS formed oxide, phosphosilicate glass (PSG), low-k dielectric material, other suitable dielectric material, or combinations thereof.

(35) FIG. **1B-2** illustrate the semiconductor structure **200** in another embodiment. The embodiment shown in FIG. **1B-2** is similar to the embodiment shown in FIG. **1B-1** except the differences in the channel region. In the embodiment shown in FIG. **1B-2**, the channel region **208** includes a stack of nano-sized channels **210**. Each channel **210** is wrapped around by the gate structure **242**, thereby forming gate-all-around FETs. The semiconductor structure **200** further includes dielectric spacers **216** between the gate structure **242** and the source/drain regions **218**. The dielectric spacers **216** may include a suitable dielectric material such as silicon oxide and silicon nitride.

(36) FIG. **1B-3** illustrates a fragmentary cross-sectional view of the semiconductor structure **200** taken along line B-B shown in FIG. **1A**, according to an embodiment of the present disclosure where the dummy regions **106** include one or more dielectric materials. In this embodiment, the dummy regions **106** are formed as an isolation structure, such as shallow trench isolation (STI). For example, the dummy regions **106** may be formed by etching trenches into semiconductor fins and the substrate **201**, filling the trenches with one or more dielectric materials such as silicon oxide, silicon nitride, silicon oxynitride, fluoride-doped silicate glass (FSG), a low-k dielectric material, and/or other suitable insulating material. The top surface of the dummy regions **106** may be substantially co-planar with the top surface of the channel regions **208** in an embodiment or may be formed lower than the top surface of the channel regions **208** in an alternative embodiment. The bottom surface of the dummy regions **106** may be curved or flat depending on the etching process(es) that forms the isolation trenches. The embodiment in FIG. **1B-3** has the channel regions **208** in the form of semiconductor fins. Alternatively, the channel regions **208** may include a stack of nano-sized channels **210**, such as shown in FIG. **1B-2**.

(37) FIG. **1C-1** illustrates a fragmentary cross-sectional view of the semiconductor structure **200** taken along line C-C shown in FIG. **1A**, according to an embodiment of the present disclosure where the dummy regions **106** include doped or undoped semiconductor material(s) (such as illustrated in FIGS. **1B-1** and **1B-2** above). As illustrated in FIG. **1C-1**, wells **103-1** and **103-2** are formed in the substrate **201**. The dummy regions **106** are formed over the wells **103-1** and **103-2**. The dummy regions **106** are isolated from each other by isolation structures **107**. Isolation structures **107** may comprise silicon oxide, silicon nitride, silicon oxynitride, fluoride-doped silicate glass (FSG), a low-k dielectric material, and/or other suitable insulating material. Isolation structures **107** may be shallow trench isolation (STI) features or other isolation structure such as field oxide and Local Oxidation of Silicon (LOCOS). In this embodiment, the top surface of the dummy regions **106** extend above the isolation structures **107**.

(38) FIG. **1C-2** illustrates a fragmentary cross-sectional view of the semiconductor structure **200** taken along line C-C shown in FIG. **1A**, according to an embodiment of the present disclosure. In this embodiment, the dummy regions **106** include one or more dielectric material(s) (such as illustrated in FIG. **1B-3** above). The top surface of the dummy regions **106** and the top surface of the isolation structures **107** are co-planar or substantially co-planar. The dummy regions **106** and the isolation structures **107** may be formed by the same process or by different processes. The boundary between the dummy regions **106** and the isolation structures **107** may be visible or invisible depending on the processes of forming the dummy regions **106** and the isolation structures **107** and/or the materials used in the dummy regions **106** and the isolation structures **107**.

(39) FIG. **2** illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. **2** is similar to the

embodiment in FIG. 1A. Some differences between the two embodiments are discussed below. In FIG. 1A, the top edge of the top dummy region **106-1** is aligned with the top edge of the top active region **104-1** and the top edge of the top active region **105-1**. In FIG. 2, the top edge of the top dummy region **106-1** is misaligned with and is lower than the top edge of the top active region **104-1** and the top edge of the top active region **105-1**. In FIG. 1A, the bottom edge of the bottom dummy region **106-1** is aligned with the bottom edge of the bottom active region **104-1** and the bottom edge of the bottom active region **105-1**. In FIG. 2, the bottom edge of the bottom dummy region **106-1** is misaligned with and is higher than the bottom edge of the bottom active region **104-1** and the bottom edge of the bottom active region **105-1**.

(40) FIG. 3 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. 3 is similar to the embodiment in FIG. 1A. Some differences between the two embodiments are discussed below. In FIG. 1A, the dummy region **106-2** is wider than the active region **105-2**. The wide dummy region **106-2** in FIG. 1A is replaced with two narrower dummy regions **106-2** in FIG. 3. Each dummy region **106-2** is narrower than the active region **104-2** which is narrower than the active region **105-2**. Further, the bottom edge of the top dummy region **106-2** is aligned with the bottom edge of the top active region **104-2**, and the top edge of the bottom dummy region **106-2** is aligned with the top edge of the bottom active region **104-2**.

(41) The semiconductor structure **200** in FIG. 3 provides advantages over the semiconductor structure **200'** in FIG. 1A-2. As discussed above, the semiconductor structure **200'** in FIG. 1A-2 might have increased leakage between the two active regions **104-2** and between the active region **104-2** and the source/drain contact **275**. In contrast, in the semiconductor structure **200** shown in FIG. 3, the bottom edge of the top active region **104-2** and the top edge of the bottom active region **104-2** can be well preserved through the manufacturing processes due to the presence of the dummy regions **106-2**, and thus remain substantially straight even after fabrication.

Advantageously, the semiconductor structure **200** shown in FIG. 3 does not have the leakage discussed above with respect to the semiconductor structure **200'** in FIG. 1A-2. Additionally, the semiconductor structure **200** shown in FIG. 3 provides advantages over the semiconductor structure **200'** in FIG. 1A-1 for the same reasons discussed above for the embodiment in FIG. 1A.

(42) FIG. 4 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The active regions **104** include three active regions **104-1** and three active regions **104-2** arranged into three cells **102-1**, **102-2**, and **102-4** in a column. The active regions **105** include two active regions **105-1** and two active regions **105-2** arranged in a column. The middle two active regions **105-2** and **105-1** form a cell **102-5**. The dummy regions **106** include two dummy regions **106-1** and two dummy regions **106-2** arranged in a column. The active region **105-1** has a height $H7$. The active region **105-2** has a height $H6$. The top dummy region **106-2** has a height $H8$. The bottom dummy region **106-1** has a height $H9$. Each of the active regions **104** has a height $H1$. The top dummy region **106-1** and the bottom dummy region **106-2** each have a height $H4$. $H4$ is less than $H1$ which is less than $H6$ and $H7$. $H8$ is greater than $H6$. $H9$ is greater than $H7$. The two adjacent active regions **104-2** and the isolation structure in between collectively have a height $D2$. The two adjacent active regions **104-1** and the isolation structure in between collectively have a height $D3$. $D2$ is greater than $H8$. $D3$ is greater than $H9$. The design of these dimensions helps increase the design margin associated with the active regions **104** and **105** and the wells and between the active regions and nearby source/drain contacts.

(43) The top dummy region **106-1** is disposed between the top active region **104-1** and the top active region **105-1**. The top edge of the top dummy region **106-1** is aligned with the top edge of the top active region **104-1** and the top edge of the top active region **105-1**. The bottom edge of the top dummy region **106-1**, the bottom edge of the top active region **104-1**, and the bottom edge of the top active region **105-1** are misaligned, with four 90-degree bends.

(44) The bottom dummy region **106-2** is disposed between the bottom active region **104-2** and the

bottom active region **105-2**. The bottom edge of the bottom dummy region **106-2** is aligned with the bottom edge of the bottom active region **104-2** and the bottom edge of the bottom active region **105-2**. The top edge of the bottom dummy region **106-2**, the top edge of the bottom active region **104-2**, and the top edge of the bottom active region **105-2** are misaligned, with four 90-degree bends.

(45) The top dummy region **106-2** is disposed between the top two active regions **104-2** and the top active region **105-2**. The top edge of the top dummy region **106-2**, the top edge of the top active region **104-2**, and the top edge of the top active region **105-2** are misaligned, with four 90-degree bends. The bottom edge of the top dummy region **106-2**, the bottom edge of the second-from-the-top active region **104-2**, and the bottom edge of the top active region **105-2** are misaligned, with four 90-degree bends.

(46) The bottom dummy region **106-1** is disposed between the bottom two active regions **104-1** and the bottom active region **105-1**. The top edge of the bottom dummy region **106-1**, the top edge of the second-from-the-top active region **104-1**, and the top edge of the bottom active region **105-1** are misaligned, with four 90-degree bends. The bottom edge of the bottom dummy region **106-1**, the bottom edge of the third-from-the-top active region **104-1**, and the bottom edge of the bottom active region **105-1** are misaligned, with four 90-degree bends.

(47) FIG. 5 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. 5 is similar to the embodiment in FIG. 4. Some differences between the two embodiments are discussed below. In FIG. 4, the dummy regions **106-2** and **106-1** in the middle are wider than the active regions **105-2** and **105-1**, respectively. The wide dummy region **106-2** in FIG. 4 is replaced with two narrower dummy regions **106-2** in FIG. 5, each having a height **H10**. The wide dummy region **106-1** in FIG. 4 is replaced with two narrower dummy regions **106-1** in FIG. 5, each having a height **H11**. Each dummy region **106** in FIG. 5 is narrower than each active region **104**. The bottom edge of the top dummy region **106-2** is aligned with the bottom edge of the top active region **104-2**, and the top edge of the second-from-the-top dummy region **106-2** is aligned with the top edge of the second-from-the-top active region **104-2**. The bottom edge of the second-from-the-top dummy region **106-1** is aligned with the bottom edge of the second-from-the-top active region **104-1**, and the top edge of the third-from-the-top dummy region **106-1** is aligned with the top edge of the third-from-the-top active region **104-1**. Advantageously, the semiconductor structure **200** shown in FIG. 5 reduces the leakage discussed above with respect to the semiconductor structure **200'** in FIG. 1A-2. Additionally, the semiconductor structure **200** shown in FIG. 5 provides advantages over the semiconductor structure **200'** in FIG. 1A-1 for the same reasons discussed above for the embodiment in FIG. 1A.

(48) FIG. 6A illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. In this embodiment, the dummy regions **106** are disposed between two cells **102-3**. Each cell **102-3** includes an active region **105-2** between two active regions **105-1**. Each active region **105-2** is wider than each active region **105-1**. Further, the dummy region **106-2** has the same height (or width) as the active region **105-2**, and the dummy region **106-1** is narrower than the active region **105-1**. The top edge of the top dummy region **106-1** and the top edges of the top active regions **105-1** are aligned. The bottom edge of the top dummy region **106-1** and the bottom edges of the top active regions **105-1** are misaligned, with four 90-degree bends. The bottom edge of the bottom dummy region **106-1** and the bottom edges of the bottom active regions **105-1** are aligned. The top edge of the bottom dummy region **106-1** and the top edges of the bottom active regions **105-1** are misaligned, with four 90-degree bends. The top edges of the active regions **105-2** and the dummy region **106-2** are aligned. The bottom edges of the active regions **105-2** and the dummy region **106-2** are aligned. Advantageously, the semiconductor structure **200** shown in FIG. 6A reduces the leakage discussed above with respect to the semiconductor structure **200'** in FIG. 1A-2. Additionally, the semiconductor structure **200**

shown in FIG. 6A provides advantages over the semiconductor structure **200'** in FIG. 1A-1 for the same reasons discussed above for the embodiment in FIG. 1A.

(49) Further, the dummy regions **106** in the embodiment in FIG. 6A is wider than the dummy regions **106** in the embodiments in FIGS. 1A, 2, 3, 4, and 5, along the X direction. In the embodiments in FIGS. 1A, 2, 3, 4, and 5, the width of the dummy regions **106** is about one poly-to-poly pitch (referred to as poly-pitch). In the embodiment in FIG. 6A, the width of the dummy regions **106** is about two poly-pitches. As a result, a gate structure **242'** may be formed over the dummy regions **106**. The gate structure **242'** is a dummy gate (e.g., it is a dielectric gate or it is a high-k metal gate that is not connected to other parts of the semiconductor structure **200**).

(50) FIG. 6B-1 illustrates a fragmentary cross-sectional view of the semiconductor structure **200** taken along line B-B shown in FIG. 6A, according to an embodiment of the present disclosure where the dummy regions **106** include doped or undoped semiconductor material(s). In the embodiment shown in FIG. 6B-1, each of the active regions **105** includes two source/drain regions **218** and a semiconductor channel region **208** connecting the two source/drain regions **218**. The semiconductor channel region **208** may be in the shape of a semiconductor fin (e.g., for FinFETs) as shown in FIG. 6B-1 or may include a stack of nano-sized channels (not shown) similar to FIG. 1B-2. As illustrated in FIG. 6B-1, dummy regions **106-1**, dummy channel **208'**, and dummy gate structure **242'** are formed between the isolation structures **235**. The dummy regions **106-1** may be formed in the same processes as for the source/drain regions **218**, as discussed with respect to FIG. 1B-1. The dummy channel **208'** may include the same material as the channel region **208**.

(51) FIG. 6B-2 illustrates a fragmentary cross-sectional view of the semiconductor structure **200** taken along line B-B shown in FIG. 6A, according to an embodiment of the present disclosure where the dummy regions **106** include one or more dielectric materials. For example, the dummy regions **106** may be formed as an isolation structure, such as shallow trench isolation (STI), as discussed with respect to FIG. 1B-3. As illustrated in FIG. 6B-2, dummy region **106-1** and dummy gate structure **242'** are formed between the isolation structures **235**.

(52) FIG. 7 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. 7 is similar to the embodiment in FIG. 6A. Some differences between the two embodiments are discussed below. In FIG. 6A, the dummy region **106-2** has the same height (or width) as the active region **105-2**. The dummy region **106-2** in FIG. 6A is replaced with two narrower dummy regions **106-2** in FIG. 7. Each dummy region **106-2** is narrower than the active region **105-1** which is narrower than the active region **105-2**. Further, the dummy regions **106-1** and **106-2** have about the same height along the Y direction. Further, the top and bottom edges of the dummy regions **106-2** are misaligned with the top and bottom edges of the active regions **105-2**.

(53) FIG. 8 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. 8 is similar to the embodiment in FIG. 6A. The dummy regions **106** are 2 poly-pitch wide. Each cell **102-5** includes a wide active region **105-1** and a wide active region **105-2**. There are other, narrower active regions **105** in the columns. The middle two dummy regions **106-2**, **106-1** have the same height (or width) as the middle two active regions **105-2** and **105-1**. Their respective top edges are aligned. Their respective bottom edges are also aligned. The top edge of the top dummy region **106-1** and the top edges of the top active regions **105-1** are aligned. The bottom edge of the top dummy region **106-1** and the bottom edges of the top active regions **105-1** are misaligned, with four 90-degree bends. The bottom edge of the bottom dummy region **106-2** and the bottom edges of the bottom active regions **105-2** are aligned. The top edge of the bottom dummy region **106-2** and the top edges of the bottom active regions **105-2** are misaligned, with four 90-degree bends.

(54) FIG. 9 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. 9 is similar to the embodiment in FIG. 8. Some differences between the two embodiments are discussed below. In

FIG. 8, the middle two dummy regions **106-2**, **106-1** have the same height (or width) as the active region **105-2**, **105-1**, respectively. Each of the two middle dummy regions **106** in FIG. 8 is replaced with two narrower dummy regions **106** in FIG. 9. The top and bottom edges of the narrower dummy regions **106** in FIG. 9 may or may not be aligned with the active regions **105**.

(55) FIG. 10 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The semiconductor structure **200** includes a cell **102-6** that includes an active region **105-1** and two active regions **105-2** where the active region **105-1** is taller (or wider) than each of the two active regions **105-2**. The cell **102-5** includes an active region **105-1** and an active region **105-2** that have about the same height. There are other active regions **105** in the columns. The dummy regions **106** includes a wide dummy region **106-1** that has its top and bottom edges aligned with the respective top and bottom edges of the active regions **105-1** in the cells **102-5** and **102-6**. Other dummy regions **106** are narrower. The dummy regions **106** are 2 poly-pitch wide.

(56) FIG. 11 illustrates a fragmentary top view of the semiconductor structure **200**, according to another embodiment of the present disclosure. The embodiment in FIG. 11 is similar to the embodiment in FIG. 10. The wide dummy region **106-1** in FIG. 10 is replaced with two narrower dummy regions **106-1** in FIG. 11 and are disposed between the active regions **105-1** of the cells **102-5** and **102-6**.

(57) FIGS. 12, 13, and 14 illustrate fragmentary top views of the semiconductor structure **200**, according to three embodiments of the present disclosure, respectively. In the three embodiments, the width **W3** of the dummy regions **106** are different from each other. In the embodiment shown in FIG. 12, the width **W3** of the dummy regions **106** is about one poly-pitch (i.e., it is about equal to one pitch of the gate structures **242**). In the embodiment shown in FIG. 13, the width **W3** of the dummy regions **106** is about two poly-pitches (i.e., it is about equal to two pitches of the gate structures **242**). In the embodiment shown in FIG. 14, the width **W3** of the dummy regions **106** is about three poly-pitches (i.e., it is about equal to three pitches of the gate structures **242**). As shown in the three embodiments, the bends in the boundary line **112** are disposed in the column of dummy regions **106**. There may be two bends in the boundary line **112**, such as show in FIG. 12, or there may be four bends in the boundary line **112**, such as show in FIGS. 13 and 14. In alternative embodiments, the four bends in the boundary line **112** in FIGS. 13-14 may be replaced with two bends such as shown in FIG. 12. When the width **W3** is greater than one poly-pitch, dummy gate structures **242**'s may be implemented in the column of dummy regions **106**.

(58) In various embodiments, the disclosed dummy regions **106** may be inserted during a design phase, such as during automatic place and route. The dummy regions **106** may be inserted between two columns of active regions when the lateral space (e.g., along the X direction in FIG. 1A) between the two columns of active regions is less than four poly-pitches. In the embodiments in FIGS. 12, 13, and 14, the lateral space between the two columns of active regions is one poly-pitch, two poly-pitches, and three poly-pitches, respectively. When the lateral space between the two columns of active regions is equal to or greater than four poly-pitches, a column of active regions may be inserted (because an active cell is at least two poly-pitch wide).

(59) Although not intended to be limiting, one or more embodiments of the present disclosure provide many benefits to a semiconductor structure and the formation thereof. For example, the present disclosure provides embodiments of a semiconductor structure or a layout thereof which implement a dummy padding between two columns of active regions. The dummy padding provides various benefits to the semiconductor structure, including increased design margin and reduced leakage between an active region and an adjacent well, increased design margin and reduced leakage between two adjacent active regions, and increased design margin and reduced leakage between an active region and an adjacent source/drain contact.

(60) In an example aspect, the present disclosure is directed to a semiconductor structure that includes a substrate; a first column of active regions over the substrate; a second column of active

regions over the substrate; and a dummy padding disposed between the first and the second columns from a top view. The dummy padding includes multiple dummy regions. A first dummy region of the multiple dummy regions is disposed between a first active region in the first column of active regions and a second active region in the second column of active regions. An outer boundary line tracing an edge of the first active region, an edge of the first dummy region, and an edge of the second active region includes at least two substantially 90-degree bends from a top view. The first and the second active regions include a semiconductor material doped with a same dopant.

(61) In an embodiment of the semiconductor structure, the first and the second active regions and the first dummy region are at a same vertical level above the substrate. In another embodiment, the first dummy region includes the semiconductor material doped with the same dopant. In yet another embodiment, the first dummy region includes a dielectric material.

(62) In an embodiment of the semiconductor structure, the second active region is wider than the first active region along a first direction parallel to the first and the second columns from a top view. In a further embodiment, an edge of the first active region and an edge of the second active region are substantially aligned along a second direction perpendicular to the first direction. In another further embodiment, the first dummy region is narrower than both the first and the second active regions along the first direction.

(63) In another embodiment, the semiconductor structure further includes a first isolation structure between the first column and the dummy padding and a second isolation structure between the second column and the dummy padding.

(64) In another example aspect, the present disclosure is directed to a semiconductor structure that includes a substrate, a first cell comprising a first active region of a first conductivity type and a second active region of a second conductivity type that is opposite to the first conductivity type, and a second cell comprising a third active region of the first conductivity type and a fourth active region of the second conductivity type. From a top view, the first, the second, the third, and the fourth active regions are disposed in a first column and the second and the fourth active regions are disposed between the first and the third active regions in the first column. The semiconductor structure further includes a third cell comprising fifth and seventh active regions of the first conductivity type and a sixth active region of the second conductivity type. From a top view, the fifth, the sixth, and the seventh active regions are disposed in a second column and the sixth active region is disposed between the fifth and the seventh active regions in the second column. The semiconductor structure further includes a dummy padding disposed between the first and the second columns from a top view. The dummy padding includes a first dummy region between the first active region and the fifth active region, a second dummy region between the second active region and the sixth active region, and a third dummy region between the third active region and the seventh active region. The first through seventh active regions and the first through third dummy regions are at a same vertical level above the substrate.

(65) In an embodiment, the semiconductor structure further includes a first well formed in the substrate and being of the second conductivity type and a second well formed in the substrate and being of the first conductivity type. The first and the fifth active regions and the first dummy region are over the first well. the second, the fourth, and the sixth active region are over the second well. From a top view, a boundary line between the first well and the second well includes two bends that are disposed between the first column and the second column.

(66) In an embodiment of the semiconductor structure, from a top view, the fifth active region is wider than the first active region and an edge of the first active region and an edge of the fifth active region are substantially aligned. In a further embodiment, from a top view, an edge of the first dummy region is substantially aligned with the edge of the first active region and the edge of the fifth active region.

(67) In an embodiment, the second dummy region is also between the fourth active region and the

sixth active region. In another embodiment, each of the first dummy region and the first and the fifth active regions includes a semiconductor material doped with dopants of the first conductivity type. In yet another embodiment, each of the first through third dummy regions includes a dielectric material.

(68) In an embodiment, the semiconductor structure further includes a first isolation structure between the first column and the dummy padding and a second isolation structure between the second column and the dummy padding. Each of the first and the second isolation structures is oriented lengthwise parallel to the first and the second columns.

(69) In yet another example aspect, the present disclosure is directed to an integrated circuit layout that includes a first CMOS cell, a second CMOS cell, a third CMOS cell, and a dummy padding. The first CMOS cell includes a first active region of a first conductivity type and a second active region of a second conductivity type that is opposite to the first conductivity type. The second CMOS cell includes a third active region of the first conductivity type and a fourth active region of the second conductivity type. From a top view, the first, the second, the third, and the fourth active regions are disposed in a first column and the second and the fourth active regions are disposed between the first and the third active regions in the first column. The third CMOS cell includes a fifth active region of the first conductivity type, a sixth active region of the second conductivity type, and a seventh active region of the first conductivity type. From a top view, the fifth, the sixth, and the seventh active regions are disposed in a second column and the sixth active region is disposed between the fifth and the seventh active regions in the second column. Each of the fifth and the seventh active regions is wider than each of the first and the third active regions. The sixth active region is wider than each of the second and the fourth active regions. The dummy padding is disposed between the first and the second columns from a top view. The dummy padding includes a first dummy region between the first and the fifth active regions, a second dummy region between each of the second and the fourth active regions and the sixth active region, and a third dummy region between the third and the seventh active regions.

(70) In an embodiment of the integrated circuit layout, a top edge of the first active region, a top edge of the first dummy region, and a top edge of the fifth active region are substantially aligned.

(71) In an embodiment, the integrated circuit layout further includes a first well of the second conductivity type and a second well of the first conductivity type. The first active region, the first dummy region, and the fifth active region are in the first well from a top view. The second and the fourth active regions and the sixth active region are in the second well from a top view. A boundary line between the first well and the second well includes two bends that are disposed between the first column and the second column.

(72) In another embodiment, a width of the second dummy region is greater than a width of the sixth active region and is smaller than a distance from a top edge of the second active region to a bottom edge of the fourth active region.

(73) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A semiconductor structure, comprising: a substrate; a first column of active regions over the substrate; a second column of active regions over the substrate; and a dummy padding disposed

- between the first column of active regions and the second column of active regions from a top view, wherein the dummy padding includes multiple dummy regions, a first dummy region of the multiple dummy regions is disposed between a first active region in the first column of active regions and a second active region in the second column of active regions, an outer boundary line tracing an edge of the first active region, an edge of the first dummy region, and an edge of the second active region includes at least two substantially 90-degree bends from a top view, wherein the first and the second active regions include a semiconductor material doped with a same dopant, wherein, the first active region extends lengthwise along a first direction and has a first dimension along a second direction different from the first direction, the first dummy region has a second dimension along the second direction, the second dimension is less than the first dimension.
2. The semiconductor structure of claim 1, wherein the first and the second active regions and the first dummy region are at a same vertical level above the substrate.
 3. The semiconductor structure of claim 1, wherein the first dummy region includes the semiconductor material doped with the same dopant.
 4. The semiconductor structure of claim 1, wherein the first dummy region includes a dielectric material.
 5. The semiconductor structure of claim 1, wherein the second active region has a third dimension along the second direction, the third dimension is greater than the second dimension.
 6. The semiconductor structure of claim 5, wherein an edge of the first active region and an edge of the second active region are substantially aligned along the first direction.
 7. The semiconductor structure of claim 5, wherein the first dimension is less than the third dimension.
 8. The semiconductor structure of claim 1, further comprising: a first isolation structure between the first column of active regions and the dummy padding; and a second isolation structure between the second column of active regions and the dummy padding.
 9. A semiconductor structure, comprising: a substrate; a first cell comprising a first active region of a first conductivity type and a second active region of a second conductivity type that is opposite to the first conductivity type; a second cell comprising a third active region of the first conductivity type and a fourth active region of the second conductivity type, wherein from a top view, the first, the second, the third, and the fourth active regions are disposed in a first column and the second and the fourth active regions are disposed between the first and the third active regions in the first column; a third cell comprising fifth and seventh active regions of the first conductivity type and a sixth active region of the second conductivity type, wherein from a top view, the fifth, the sixth, and the seventh active regions are disposed in a second column and the sixth active region is disposed between the fifth and the seventh active regions in the second column; and a dummy padding disposed between the first and the second columns from a top view, wherein the dummy padding includes a first dummy region between the first active region and the fifth active region, a second dummy region between the second active region and the sixth active region, and a third dummy region between the third active region and the seventh active region, wherein the first through seventh active regions and the first through third dummy regions are at a same vertical level above the substrate.
 10. The semiconductor structure of claim 9, further comprising: a first well formed in the substrate and being of the second conductivity type; and a second well formed in the substrate and being of the first conductivity type, wherein the first and the fifth active regions and the first dummy region are over the first well, wherein the second, the fourth, and the sixth active region are over the second well, wherein from a top view, a boundary line between the first well and the second well includes two bends that are disposed between the first column and the second column.
 11. The semiconductor structure of claim 9, wherein from a top view, the fifth active region is wider than the first active region and an edge of the first active region and an edge of the fifth active region are substantially aligned.

12. The semiconductor structure of claim 11, wherein from a top view, an edge of the first dummy region is substantially aligned with the edge of the first active region and the edge of the fifth active region.
 13. The semiconductor structure of claim 9, wherein the second dummy region is also between the fourth active region and the sixth active region.
 14. The semiconductor structure of claim 9, wherein each of the first dummy region and the first and the fifth active regions includes a semiconductor material doped with dopants of the first conductivity type.
 15. The semiconductor structure of claim 9, wherein each of the first through third dummy regions includes a dielectric material.
 16. The semiconductor structure of claim 9, further comprising: a first isolation structure between the first column and the dummy padding; and a second isolation structure between the second column and the dummy padding, wherein each of the first and the second isolation structures is oriented lengthwise parallel to the first and the second columns.
 17. An integrated circuit layout, comprising: a first CMOS cell comprising a first active region of a first conductivity type and a second active region of a second conductivity type that is opposite to the first conductivity type; a second CMOS cell comprising a third active region of the first conductivity type and a fourth active region of the second conductivity type, wherein from a top view, the first, the second, the third, and the fourth active regions are disposed in a first column and the second and the fourth active regions are disposed between the first and the third active regions in the first column; a third CMOS cell comprising a fifth active region of the first conductivity type, a sixth active region of the second conductivity type, and a seventh active region of the first conductivity type, wherein from a top view, the fifth, the sixth, and the seventh active regions are disposed in a second column and the sixth active region is disposed between the fifth and the seventh active regions in the second column, wherein each of the fifth and the seventh active regions is wider than each of the first and the third active regions, wherein the sixth active region is wider than each of the second and the fourth active regions; and a dummy padding disposed between the first and the second columns from a top view, wherein the dummy padding includes a first dummy region between the first and the fifth active regions, a second dummy region between each of the second and the fourth active regions and the sixth active region, and a third dummy region between the third and the seventh active regions.
 18. The integrated circuit layout of claim 17, wherein a top edge of the first active region, a top edge of the first dummy region, and a top edge of the fifth active region are substantially aligned.
 19. The integrated circuit layout of claim 17, further comprising a first well of the second conductivity type and a second well of the first conductivity type, wherein the first active region, the first dummy region, and the fifth active region are in the first well from a top view, the second and the fourth active regions and the sixth active region are in the second well from a top view, and a boundary line between the first well and the second well includes two bends that are disposed between the first column and the second column.
 20. The integrated circuit layout of claim 17, wherein a width of the second dummy region is greater than a width of the sixth active region and is smaller than a distance from a top edge of the second active region to a bottom edge of the fourth active region.
-