

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418144
Kind Code	B1
Date of Patent	September 16, 2025
Inventor(s)	Baldwin; Jeffrey P. et al.

Gripping electrical receptacle

Abstract

An electrical receptacle with a receptacle body, at least one friction pad within the receptacle body between two plug prongs when the electrical plug is coupled with the electrical receptacle, a cam within the receptacle body and having a cam body with an oval-shaped cross section configured to force the friction pad towards a plug prong while a cam lever is in an engaged position, and release the force when the cam lever is in a disengaged position. An actuator is exposed on a surface of the receptacle body and operatively coupled to the cam lever to manually rotate the cam lever to the engaged position. When the cam lever is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam lever is in the disengaged position.

Inventors:	Baldwin; Jeffrey P. (Anthem, AZ), Brown; Austin Steven (Addison, TX)
Applicant:	Baldwin; Jeffrey P. (Anthem, AZ); Brown; Austin Steven (Addison, TX)
Family ID:	1000006778405
Assignee:	Titan3 Technology LLC (Tempe, AZ)
Appl. No.:	17/989535
Filed:	November 17, 2022

Related U.S. Application Data

us-provisional-application US 63294665 20211229

Publication Classification

Int. Cl.: H01R13/639 (20060101); H01R13/512 (20060101); H01R13/629 (20060101)

U.S. Cl.:

Field of Classification Search**CPC:** H01R (13/639); H01R (13/629); H01R (13/6395); H01R (13/512)**USPC:** 439/372; 439/346; 439/373**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1933592	12/1932	Hubbell, Jr.	N/A	N/A
2239653	12/1940	O'Brien	N/A	N/A
2524250	12/1949	Bierce	N/A	N/A
3478297	12/1968	Gimpel	N/A	N/A
3891289	12/1974	Hanke	439/106	H01R 13/20
4037901	12/1976	Kaszuba	N/A	N/A
4600258	12/1985	Hu	N/A	N/A
4659161	12/1986	Holcomb	N/A	N/A
4722693	12/1987	Rose	N/A	N/A
4909749	12/1989	Long	N/A	N/A
4971571	12/1989	Puerner	439/372	H01R 13/627
5277602	12/1993	Yi	N/A	N/A
5350310	12/1993	Chen	N/A	N/A
5484299	12/1995	Schlessinger	N/A	N/A
5551884	12/1995	Burkhart, Sr.	439/140	H01R 13/44
5551893	12/1995	Johnson	N/A	N/A
5791931	12/1997	Burkhart, Sr.	N/A	N/A
5934931	12/1998	Castaldo	N/A	N/A
5967815	12/1998	Schlessinger	N/A	N/A
5975941	12/1998	Castaldo	N/A	N/A
5984700	12/1998	Chang	N/A	N/A
6056588	12/1999	Castaldo	N/A	N/A
6193539	12/2000	Chang	N/A	N/A
6196851	12/2000	Gerard	N/A	N/A
6224401	12/2000	Yu	N/A	N/A
6332794	12/2000	Tzeng Jeng	N/A	N/A
6461176	12/2001	Haas	439/133	H01R 31/065
6537089	12/2002	Montague	N/A	N/A
6695639	12/2003	Castaldo	N/A	N/A
6805578	12/2003	Chiou	N/A	N/A
6893275	12/2004	Ng	N/A	N/A
6984141	12/2005	Beski, Sr.	N/A	N/A
7041918	12/2005	Wu	N/A	N/A
7101218	12/2005	Castaldo	N/A	N/A
7121834	12/2005	Gerard	N/A	N/A
7125256	12/2005	Gerard	N/A	N/A
7156682	12/2006	Lai	439/270	H01R 13/639

7182615	12/2006	Liu	439/263	H01R 24/22
7238028	12/2006	Gerard	N/A	N/A
7381894	12/2007	Shotey	N/A	N/A
7753682	12/2009	Gerard	N/A	N/A
7794283	12/2009	Wang	N/A	N/A
7902458	12/2010	Eshelman	N/A	N/A
7931484	12/2010	Chen	N/A	N/A
7967620	12/2010	Baldwin	N/A	N/A
8007283	12/2010	Gerard	N/A	N/A
8210853	12/2011	Gerard	N/A	N/A
8344251	12/2012	Eshelman	N/A	N/A
8475175	12/2012	Gerard	N/A	N/A
8808014	12/2013	Hsu	439/373	H01R 13/41
8840418	12/2013	Chien	N/A	N/A
8951059	12/2014	Chang	439/346	H01R 13/633
9450365	12/2015	Baldwin	N/A	H01R 24/76
9502808	12/2015	Jeffrey	N/A	N/A
9728908	12/2016	Baldwin	N/A	N/A
9769620	12/2016	Khider	N/A	N/A
9905969	12/2017	Baldwin	N/A	H01R 24/76
10170872	12/2018	Baldwin	N/A	N/A
10424871	12/2018	Baldwin	N/A	H01R 13/20
10756495	12/2019	Baldwin	N/A	N/A
10916899	12/2020	Baldwin	N/A	H01R 13/4538
11011878	12/2020	Baldwin	N/A	H01R 13/4538
2002/0068474	12/2001	Davidson	439/346	H01R 13/6392
2002/0097546	12/2001	Weinberger	N/A	N/A
2008/0064248	12/2007	Huang	439/346	H01R 13/639
2010/0197156	12/2009	Chen	439/188	H01R 13/20
2014/0106601	12/2013	Matsumoto	N/A	N/A
2014/0259651	12/2013	Fletcher	N/A	N/A
2015/0226925	12/2014	Lambourn	N/A	N/A
2018/0006403	12/2017	Dong	N/A	H01R 4/184
2018/0198235	12/2017	Huang	N/A	H01R 13/6395

Primary Examiner: Paumen; Gary F

Attorney, Agent or Firm: Booth Udall, PLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of the filing date of U.S. Provisional Patent Application 63/294,665 entitled “GRIPPING ELECTRICAL RECEPTACLE” to Baldwin, et. al. that was filed on Dec. 29, 2021, the disclosure of which is hereby incorporated herein by this reference.

TECHNICAL FIELD

(1) Aspects of this document relate generally to electrical receptacles, and more specifically to electrical receptacles configured to grip the plug blades.

BACKGROUND

(2) Electrical receptacles provide power to electrical devices through the device's plug. In many instances, the plug of an electrical device easily comes free from the electrical receptacle because the plug is sized to be inserted into and removed from electrical receptacles without a significant withdrawal force. Occasionally, electrical plugs are bumped, pulled or moved to become partially removed from a receptacle, exposing live electrical prongs that become an environmental hazard through dangers such as electrical shock, electrical arc or fire. Thus, in some instances, it is desirable to have a higher withdrawal force, such as to prevent accidental removal of the plug from the electrical receptacle or to prevent young children from removing the plug from the electrical receptacle.

SUMMARY

(3) Aspects of this document relate to an electrical receptacle comprising a receptacle body having at least two plug apertures extending into the receptacle body, wherein the at least two plug apertures are configured to receive at least two plug prongs of an electrical plug, at least two friction pads positioned within the receptacle body, wherein each friction pad of the at least two friction pads is associated with a different plug aperture of the at least two plug apertures and is positioned to sit between two plug prongs of the at least two plug prongs when the electrical plug is coupled with the electrical receptacle, a cam positioned within the receptacle body and having a cam body and a cam lever, wherein the cam body has an oval-shaped cross section and is positioned between the at least two friction pads and is configured to force the at least two friction pads towards the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam lever is in an engaged position and release the at least two friction pads when the cam lever is in a disengaged position rotated away from the engaged position, and an actuator exposed on a surface of the receptacle body and operatively coupled to the cam lever, wherein the actuator is configured to enable a user to manually rotate the cam lever to the engaged position, wherein, when the cam lever is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam lever is in the disengaged position.

(4) Particular embodiments may comprise one or more of the following features. The actuator may have a plurality of ridges configured to facilitate rotating the actuator. The actuator may be a dial surrounding the at least two plug apertures of the receptacle body. The withdrawal force may be between 15 lbs and 50 lbs when the cam lever is in the engaged position.

(5) According to an aspect of the disclosure, an electrical receptacle may comprise a receptacle body having at least two plug apertures extending into the receptacle body, wherein the at least two plug apertures are configured to receive at least two plug prongs of an electrical plug, at least two friction pads positioned within the receptacle body, wherein each friction pad of the at least two friction pads is associated with a different plug aperture of the at least two plug apertures, and a cam positioned within the receptacle body and having a cam body and a cam lever, wherein the cam body is positioned between the at least two friction pads and is configured to force the at least two friction pads towards the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam lever is in an engaged position, wherein, when the cam lever is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam lever is in a disengaged position rotated away from the engaged position.

(6) Particular embodiments may comprise one or more of the following features. The at least two friction pads may be positioned to sit between two plug prongs of the at least two plug prongs when the electrical plug is coupled with the electrical receptacle. The cam body may comprise an oval-shaped cross section. An actuator may be exposed on a surface of the receptacle body and operatively coupled to the cam lever, wherein the actuator is configured to enable a user to manually rotate the cam lever to the engaged position. The actuator may include a plurality of

ridges configured to facilitate rotating the actuator. The actuator may be a dial surrounding the at least two plug apertures of the receptacle body. The withdrawal force may be between 15 lbs and 50 lbs when the cam lever is in the engaged position.

(7) According to an aspect of the disclosure, an electrical receptacle may comprise a receptacle body having at least two plug apertures extending into the receptacle body, wherein the at least two plug apertures are configured to receive at least two plug prongs of an electrical plug, and a cam positioned within the receptacle body and having a cam body, wherein the cam body is configured to apply a force to the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam is in an engaged position, wherein, when the cam is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam is in a disengaged position rotated away from the engaged position.

(8) Particular embodiments may comprise one or more of the following features. At least two friction pads positioned within the receptacle body, wherein each friction pad of the at least two friction pads is associated with a different plug aperture of the at least two plug apertures. The cam body may be positioned between the at least two friction pads and is configured to force the at least two friction pads towards the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam lever is in an engaged position. The at least two friction pads may be positioned to sit between two plug prongs of the at least two plug prongs when the electrical plug is coupled with the electrical receptacle. The cam body may be positioned between the at least two plug prongs when the electrical plug is coupled with the electrical receptacle. An actuator may be exposed on a surface of the receptacle body and operatively coupled to the cam, wherein the actuator is configured to enable a user to manually rotate the cam to the engaged position. The actuator may include a plurality of ridges configured to facilitate rotating the actuator. The actuator may be a dial surrounding the at least two plug apertures of the receptacle body. The withdrawal force may be between 15 lbs and 50 lbs when the cam is in the engaged position.

(9) The foregoing and other aspects, features, applications, and advantages will be apparent to those of ordinary skill in the art from the specification, drawings, and the claims. Unless specifically noted, it is intended that the words and phrases in the specification and the claims be given their plain, ordinary, and accustomed meaning to those of ordinary skill in the applicable arts. The inventors are fully aware that they can be their own lexicographers if desired. The inventors expressly elect, as their own lexicographers, to use only the plain and ordinary meaning of terms in the specification and claims unless they clearly state otherwise and then further, expressly set forth the “special” definition of that term and explain how it differs from the plain and ordinary meaning. Absent such clear statements of intent to apply a “special” definition, it is the inventors' intent and desire that the simple, plain and ordinary meaning to the terms be applied to the interpretation of the specification and claims.

(10) The inventors are also aware of the normal precepts of English grammar. Thus, if a noun, term, or phrase is intended to be further characterized, specified, or narrowed in some way, then such noun, term, or phrase will expressly include additional adjectives, descriptive terms, or other modifiers in accordance with the normal precepts of English grammar. Absent the use of such adjectives, descriptive terms, or modifiers, it is the intent that such nouns, terms, or phrases be given their plain, and ordinary English meaning to those skilled in the applicable arts as set forth above.

(11) Further, the inventors are fully informed of the standards and application of the special provisions of 35 U.S.C. § 112 (f). Thus, the use of the words “function,” “means” or “step” in the Detailed Description or Description of the Drawings or claims is not intended to somehow indicate a desire to invoke the special provisions of 35 U.S.C. § 112 (f), to define the invention. To the contrary, if the provisions of 35 U.S.C. § 112 (f) are sought to be invoked to define the inventions, the claims will specifically and expressly state the exact phrases “means for” or “step for”, and will

also recite the word “function” (i.e., will state “means for performing the function of [insert function]”), without also reciting in such phrases any structure, material or act in support of the function. Thus, even when the claims recite a “means for performing the function of . . .” or “step for performing the function of . . .,” if the claims also recite any structure, material or acts in support of that means or step, or that perform the recited function, then it is the clear intention of the inventors not to invoke the provisions of 35 U.S.C. § 112 (f). Moreover, even if the provisions of 35 U.S.C. § 112 (f) are invoked to define the claimed aspects, it is intended that these aspects not be limited only to the specific structure, material or acts that are described in the preferred embodiments, but in addition, include any and all structures, materials or acts that perform the claimed function as described in alternative embodiments or forms of the disclosure, or that are well known present or later-developed, equivalent structures, material or acts for performing the claimed function.

(12) The foregoing and other aspects, features, and advantages will be apparent to those of ordinary skill in the art from the specification, drawings, and the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Implementations will hereinafter be described in conjunction with the appended drawings, where like designations denote like elements, and:

(2) FIG. 1 is a perspective view of the gripping electrical receptacle;

(3) FIG. 2 is a front view of the gripping electrical receptacle shown in FIG. 1;

(4) FIG. 3 is a top view of the gripping electrical receptacle shown in FIG. 1;

(5) FIG. 4 is a right-side view of the gripping electrical receptacle shown in FIG. 1;

(6) FIG. 5 is a left-side view of the gripping electrical receptacle shown in FIG. 1;

(7) FIG. 6 is an exploded view of the gripping electrical receptacle shown in FIG. 1;

(8) FIG. 7A is a perspective view of the gripping electrical receptacle shown in FIG. 1 with an electrical plug removed and the cam in the disengaged position;

(9) FIG. 7B is a perspective view of the gripping electrical receptacle shown in FIG. 7A with the plug coupled with the electrical receptacle and the cam in the disengaged position;

(10) FIG. 7C is perspective view of the gripping electrical receptacle shown in FIG. 7A with the plug coupled with the electrical receptacle and the cam in the engaged position;

(11) FIG. 8A is a side view of the gripping electrical receptacle shown in FIG. 1 with the cam in the disengaged position;

(12) FIG. 8B is a cross section of the gripping electrical receptacle taken along line 8B-8B in FIG. 8A;

(13) FIG. 8C is a cross section of the gripping electrical receptacle taken along line 8C-8C in FIG. 8A;

(14) FIG. 9A is a side view of the gripping electrical receptacle shown in FIG. 1 with the cam in the engaged position;

(15) FIG. 9B is a cross section of the gripping electrical receptacle taken along line 9B-9B in FIG. 9A; and

(16) FIG. 9C is a cross section of the gripping electrical receptacle taken along line 9C-9C in FIG. 9A.

(17) Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of implementations.

DETAILED DESCRIPTION

(18) This disclosure, its aspects and implementations, are not limited to the specific material types, components, methods, or other examples disclosed herein. Many additional material types, components, methods, and procedures known in the art are contemplated for use with particular implementations from this disclosure. Accordingly, for example, although particular implementations are disclosed, such implementations and implementing components may comprise any components, models, types, materials, versions, quantities, and/or the like as is known in the art for such systems and implementing components, consistent with the intended operation.

(19) The word “exemplary,” “example,” or various forms thereof are used herein to mean serving as an example, instance, or illustration. Any aspect or design described herein as “exemplary” or as an “example” is not necessarily to be construed as preferred or advantageous over other aspects or designs. Furthermore, examples are provided solely for purposes of clarity and understanding and are not meant to limit or restrict the disclosed subject matter or relevant portions of this disclosure in any manner. It is to be appreciated that a myriad of additional or alternate examples of varying scope could have been presented, but have been omitted for purposes of brevity.

(20) While this disclosure includes a number of implementations that are described in many different forms, there is shown in the drawings and will herein be described in detail particular implementations with the understanding that the present disclosure is to be considered as an exemplification of the principles of the disclosed methods and systems, and is not intended to limit the broad aspect of the disclosed concepts to the implementations illustrated.

(21) In the following description, reference is made to the accompanying drawings which form a part hereof, and which show by way of illustration possible implementations. It is to be understood that other implementations may be utilized, and structural, as well as procedural, changes may be made without departing from the scope of this document. As a matter of convenience, various components will be described using exemplary materials, sizes, shapes, dimensions, and the like. However, this document is not limited to the stated examples and other configurations are possible and within the teachings of the present disclosure. As will become apparent, changes may be made in the function and/or arrangement of any of the elements described in the disclosed exemplary implementations without departing from the spirit and scope of this disclosure.

(22) The present disclosure is related to a gripping electrical receptacle **100**, illustrated in FIGS. 1-6. The electrical receptacle **100** is configured to selectively grip an electrical plug **10** that is coupled with the electrical receptacle **100**. When in an engaged configuration, the electrical receptacle **100** increases a withdrawal force required to remove the electrical plug **10** from the electrical receptacle **100** as compared to the withdrawal force required when the electrical receptacle **100** is in a disengaged configuration. Instead of locking the electrical plug **10** in the electrical receptacle **100**, the electrical receptacle **100** creates a frictional force that increases the withdrawal force required to remove the electrical plug **10** from the electrical receptacle **100**. Although the drawings illustrate a particular embodiment of the electrical receptacle **100**, it will be clear to one of skill in the art that the electrical receptacle **100** disclosed herein can be applied to any NEMA (National Electrical Manufacturer's Association) receptacle to increase the withdrawal force required and reduce the likelihood of a plug coming unintentionally loosened from an electrical receptacle.

(23) In specific relation to FIG. 6, the electrical receptacle **100** has a receptacle body **102** and a cam **104** positioned within the receptacle body **102**. The electrical receptacle **100** may also have friction pads **106** positioned within the receptacle body **102** and an actuator **108** exposed on a surface **110** of the receptacle body **102**. The receptacle body **102** has at least two plug apertures **112** extending into the receptacle body **102**. In some embodiments, the receptacle body **102** has three plug apertures **112** extending into the receptacle body **102**. The plug apertures **112** are configured to receive the plug prongs **12** of the electrical plug **10**. When the plug prongs **12** of the electrical plug **10** are coupled with the plug apertures **112** of the receptacle body **102**, the electrical receptacle **100** is configured to provide electrical power to the electrical plug **10**. The plug apertures **112** may each include a raised border **113** surrounding the plug aperture **112**. When the electrical plug **10** is

coupled with the electrical receptacle **100**, the raised border **113** of each plug aperture **112** may compress against the electrical plug **10** and may be configured to restrict the intrusion of water into the receptacle body **102**, thus reducing the chance of an electrical short or shock.

(24) As mentioned above, the cam **104** is positioned within the receptacle body **102**. The cam **104** is movable between an engaged position and a disengaged position. FIGS. 7A-7C illustrate the progression of plugging in the electrical plug **10** and then moving the cam **104** to the engaged position. When the cam **104** is in the engaged position and the electrical plug **10** is coupled with the electrical receptacle **100**, a withdrawal force required to move the electrical plug **10** from the electrical receptacle **100** is greater than when the cam **104** is in the disengaged position. When the cam **104** is in the engaged position, the likelihood of the electrical plug **10** coming unintentionally loosened from the electrical receptacle **100** is reduced. The withdrawal force may be between 15 lbs and 30 lbs. In some embodiments, the withdrawal force may be as high as 50 lbs or between 15 lbs and 50 lbs. In some embodiments, the cam **104** is configured to rotate between the engaged position and the disengaged position. The cam **104** has a cam body **114** which is configured to apply a force to the plug prongs **12** when the electrical plug **10** is coupled with the electrical receptacle **100** and the cam **104** is in an engaged position. By applying a force to the plug prongs **12**, the cam **104** increases a frictional force between the plug prongs **12** and the electrical receptacle **100**, thus increasing the withdrawal force.

(25) FIGS. 8A-9C illustrate the internal components of the electrical receptacle **100** when the cam **104** is in the disengaged position (FIGS. 8A-8C) and in the engaged position (FIGS. 9A-9C). The cam body **114** may apply the force directly to the plug prongs **12**, or indirectly through other components. For example, the friction pads **106** may be positioned between the cam body **114** and the plug prongs **12** when the electrical plug **10** is coupled with the electrical receptacle **100**. In such an embodiment, when the cam **104** is moved to the engaged position, the cam body **114** exerts a force on the friction pads **106**, pushing the friction pads **106** against the plug prongs **12** and creating the frictional force discussed above. Each friction pad **106** may be associated with a different plug aperture **112**, positioned to contact a different plug prong **12** when the cam **104** is moved to the engaged position. Thus, similar to the plug apertures **112**, the friction pads **106** may be at least two friction pads **106**. Each friction pad **106** may be positioned to sit between two plug prongs **12** when the electrical plug **10** is coupled with the electrical receptacle **100**. In embodiments of the electrical receptacle **100** with friction pads **106**, the cam body **114** may be configured to force the friction pads **106** towards the plug prongs **12** while the electrical plug **10** is coupled with the electrical receptacle **100** and the cam **104** is in the engaged position as shown in FIG. 9C. Similarly, the cam body **114** may be configured to release the friction pads **106** when the cam **104** is in the disengaged position, as shown in FIG. 8C. The friction pads **106** may be formed of a material that is selected for creating higher frictional forces with other materials. For example, the friction pads **106** may be formed of a rubber material, a plastic material, or a silicon material. Other contemplated materials include Delrin®, Teflon®, and vinyl. The material used for the friction pads **106** may have a durometer measurement within the range of Shore A **20** to Shore C **70**.

(26) The cam body **114** may have an oval-shaped cross section and may be positioned between the plug prongs **12** of the electrical plug **10**. As shown in FIG. 8C, when the cam body **114** is in the disengaged position, the cam body **114** may fit between the plug prongs **12** without making significant contact with the plug prongs **12** or any component positioned between the plug prongs **12** and the cam body **114**, such as the friction pads **106**. However, when the cam body **114** is moved to the engaged position, the size of the cam body **114** is larger along the line between the plug prongs **12** due to the oval shape of the cam body **114**, as shown in FIG. 9C, thus increasing the contact between the cam body **114** and the plug prongs **12** or any component positioned between the plug prongs **12** and the cam body **114**. This increased contact is what creates the frictional force discussed above.

(27) The cam **104** may also have a cam lever **116** extending away from the cam body **114**. The cam

lever **116** is configured to facilitate moving the cam **104** between the engaged position and the disengaged position (see FIGS. **8B** and **9B**). In some embodiments, the cam lever **116** is accessible to the user to manually move the cam **104** between the engaged position and the disengaged position. In some embodiments, the cam lever **116** is operatively coupled with the actuator **108** (see FIGS. **8B** and **9B**). As mentioned above, the actuator **108** is exposed on the surface **110** of the receptacle body **102**. The surface **110** may be a front surface, a top surface, a bottom surface, or a side surface of the electrical receptacle **100**. Thus, even in embodiments in which the cam lever **116** is not directly accessible to the user, the actuator **108** allows the user to manually rotate the cam lever **116** between the engaged position and the disengaged position.

(28) The actuator **108** may have a plurality of ridges **118** that are configured to facilitate rotating the actuator **108** by improving the grip of the user on the actuator **108**. In some embodiments, the actuator **108** is formed as a dial surrounding the plug apertures **112** of the receptacle body **102**. In embodiments of the electrical receptacle **100** that are positioned on the end of a power cord, the actuator **108** may extend around a circumference of the electrical receptacle **100**. In embodiments that are on a wall plate, the actuator **108** may be positioned on a front surface of the wall plate and allow the user to manually adjust the cam **104** through the front surface of the wall plate. Thus, the actuator **108** may be adapted to different embodiments of the electrical receptacle **100** while still serving the same purpose. The actuator **108** may include a position indicator **120** that is configured to provide a visual indication of whether the cam **104** is in the engaged position or in the disengaged position. Thus, the user can easily see the current position of the cam **104**, and thus rotate the actuator **108** to move the cam **104** between the engaged position and the disengaged position as desired. The actuator **108** may also be configured to produce audible or tactical feedback to indicate when the cam **104** has moved from the engaged position to the disengaged position or vice versa.

(29) All of the specific examples and embodiments of the components illustrated herein are intended to be non-limiting examples of a particular way of forming the electrical receptacle **100**. Other components, materials, shapes, sizes, and the like may be used and would be needed when applying this disclosure to other receptacles and other designs, as will be apparent to one of skill in the art.

(30) It will be understood that implementations of a gripping electrical receptacle are not limited to the specific assemblies, devices and components disclosed in this document, as virtually any assemblies, devices and components consistent with the intended operation of a gripping electrical receptacle may be used. Accordingly, for example, although particular gripping electrical receptacles, and other assemblies, devices and components are disclosed, such may include any shape, size, style, type, model, version, class, measurement, concentration, material, weight, quantity, and/or the like consistent with the intended operation of gripping electrical receptacles. Implementations are not limited to uses of any specific assemblies, devices and components; provided that the assemblies, devices and components selected are consistent with the intended operation of a gripping electrical receptacle.

(31) Accordingly, the components defining any gripping electrical receptacle may be formed of any of many different types of materials or combinations thereof that can readily be formed into shaped objects provided that the materials selected are consistent with the intended operation of a gripping electrical receptacle. For example, the components may be formed of: polymers such as thermoplastics (such as ABS, Fluoropolymers, Polyacetal, Polyamide; Polycarbonate, Polyethylene, Polysulfone, and/or the like), thermosets (such as Epoxy, Phenolic Resin, Polyimide, Polyurethane, Silicone, and/or the like), any combination thereof, and/or other like materials; glasses (such as quartz glass), carbon-fiber, aramid-fiber, any combination thereof, and/or other like materials; composites and/or other like materials; metals, such as zinc, magnesium, titanium, copper, lead, iron, steel, carbon steel, alloy steel, tool steel, stainless steel, brass, nickel, tin, antimony, pure aluminum, 1100 aluminum, aluminum alloy, any combination thereof, and/or other

like materials; alloys, such as aluminum alloy, titanium alloy, magnesium alloy, copper alloy, any combination thereof, and/or other like materials; any other suitable material; and/or any combination of the foregoing thereof. In instances where a part, component, feature, or element is governed by a standard, rule, code, or other requirement, the part may be made in accordance with, and to comply under such standard, rule, code, or other requirement.

(32) Various gripping electrical receptacles may be manufactured using conventional procedures as added to and improved upon through the procedures described here. Some components defining a gripping electrical receptacle may be manufactured simultaneously and integrally joined with one another, while other components may be purchased pre-manufactured or manufactured separately and then assembled with the integral components. Various implementations may be manufactured using conventional procedures as added to and improved upon through the procedures described here.

(33) Accordingly, manufacture of these components separately or simultaneously may involve extrusion, pultrusion, vacuum forming, injection molding, blow molding, resin transfer molding, casting, forging, cold rolling, milling, drilling, reaming, turning, grinding, stamping, cutting, bending, welding, soldering, hardening, riveting, punching, plating, and/or the like. If any of the components are manufactured separately, they may then be coupled with one another in any manner, such as with adhesive, a weld, a fastener (e.g. a bolt, a nut, a screw, a nail, a rivet, a pin, and/or the like), wiring, any combination thereof, and/or the like for example, depending on, among other considerations, the particular material forming the components.

(34) It will be understood that methods for manufacturing or assembling gripping electrical receptacles are not limited to the specific order of steps as disclosed in this document. Any steps or sequence of steps of the assembly of a gripping electrical receptacle indicated herein are given as examples of possible steps or sequence of steps and not as limitations, since various assembly processes and sequences of steps may be used to assemble gripping electrical receptacles.

(35) The implementations of a gripping electrical receptacle described are by way of example or explanation and not by way of limitation. Rather, any description relating to the foregoing is for the exemplary purposes of this disclosure, and implementations may also be used with similar results for a variety of other applications employing a gripping electrical receptacle.

Claims

1. An electrical receptacle, comprising: a receptacle body having at least two plug apertures extending into the receptacle body, wherein the at least two plug apertures are configured to receive at least two plug prongs of an electrical plug; at least two friction pads positioned within the receptacle body, wherein each friction pad of the at least two friction pads is associated with a different plug aperture of the at least two plug apertures and is positioned to sit between two plug prongs of the at least two plug prongs when the electrical plug is coupled with the electrical receptacle; a cam positioned within the receptacle body and having a cam body and a cam lever, wherein the cam body has an oval-shaped cross section and is positioned between the at least two friction pads and is configured to force the at least two friction pads towards the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam lever is in an engaged position and release the at least two friction pads when the cam lever is in a disengaged position rotated away from the engaged position; and an actuator exposed on a surface of the receptacle body and operatively coupled to the cam lever, wherein the actuator is configured to enable a user to manually rotate the cam lever to the engaged position and wherein the actuator is a dial surrounding the at least two plug apertures of the receptacle body; wherein, when the cam lever is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam lever is in the disengaged position.

2. The electrical receptacle of claim 1, wherein the actuator has a plurality of ridges configured to facilitate rotating the actuator.
3. The electrical receptacle of claim 1, wherein the withdrawal force is between 15 lbs and 50 lbs when the cam lever is in the engaged position.
4. An electrical receptacle, comprising: a receptacle body having at least two plug apertures extending into the receptacle body, wherein the at least two plug apertures are configured to receive at least two plug prongs of an electrical plug; at least two friction pads positioned within the receptacle body, wherein each friction pad of the at least two friction pads is associated with a different plug aperture of the at least two plug apertures; a cam positioned within the receptacle body and having a cam body and a cam lever, wherein the cam body is positioned between the at least two friction pads and is configured to force the at least two friction pads towards the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam lever is in an engaged position; and an actuator exposed on a surface of the receptacle body and operatively coupled to the cam lever, wherein the actuator is configured to enable a user to manually rotate the cam lever to the engaged position, wherein the actuator is a dial surrounding the at least two plug apertures of the receptacle body; wherein, when the cam lever is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam lever is in a disengaged position rotated away from the engaged position.
5. The electrical receptacle of claim 4, wherein the at least two friction pads are positioned to sit between two plug prongs of the at least two plug prongs when the electrical plug is coupled with the electrical receptacle.
6. The electrical receptacle of claim 4, wherein the cam body has an oval-shaped cross section.
7. The electrical receptacle of claim 4, wherein the actuator has a plurality of ridges configured to facilitate rotating the actuator.
8. The electrical receptacle of claim 4, wherein the withdrawal force is between 15 lbs and 50 lbs when the cam lever is in the engaged position.
9. An electrical receptacle, comprising: a receptacle body having at least two plug apertures extending into the receptacle body, wherein the at least two plug apertures are configured to receive at least two plug prongs of an electrical plug; a cam positioned within the receptacle body and having a cam body, wherein the cam body is configured to apply a force to the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam is in an engaged position; and an actuator exposed on a surface of the receptacle body and operatively coupled to the cam, wherein the actuator is configured to enable a user to manually rotate the cam to the engaged position, wherein the actuator is a dial surrounding the at least two plug apertures of the receptacle body; wherein, when the cam is in the engaged position and the electrical plug is coupled with the electrical receptacle, a withdrawal force required to remove the electrical plug from the electrical receptacle is greater than when the cam is in a disengaged position rotated away from the engaged position.
10. The electrical receptacle of claim 9, further comprising at least two friction pads positioned within the receptacle body, wherein each friction pad of the at least two friction pads is associated with a different plug aperture of the at least two plug apertures.
11. The electrical receptacle of claim 10, wherein the cam body is positioned between the at least two friction pads and is configured to force the at least two friction pads towards the at least two plug prongs while the electrical plug is coupled with the electrical receptacle and the cam lever is in an engaged position.
12. The electrical receptacle of claim 10, wherein the at least two friction pads are positioned to sit between two plug prongs of the at least two plug prongs when the electrical plug is coupled with the electrical receptacle.
13. The electrical receptacle of claim 9, wherein the cam body is positioned between the at least

two plug prongs when the electrical plug is coupled with the electrical receptacle.

14. The electrical receptacle of claim 9, wherein the actuator has a plurality of ridges configured to facilitate rotating the actuator.

15. The electrical receptacle of claim 9, wherein the withdrawal force is between 15 lbs and 50 lbs when the cam is in the engaged position.
