

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12418608

Kind Code

B1

Date of Patent

September 16, 2025

Inventor(s)

Koslosky; Frank

Multiple cell phone holder utilizing a magnet mounted vertical and horizontal support

Abstract

A multiple cell phone holder is provided for retaining a first cell phone and a second cell phone perpendicular to the first cell phone. The multiple cell phone holder generally includes a primary cell phone holder, a secondary cell phone holder and connector assembly for holding the secondary cell phone holder perpendicular to the primary cell phone holder. The connector assembly is rotatably mounted relative to the primary cell phone holder. The primary cell phone holder includes one or more magnets to secure a first cell phone to the primary cell phone holder. The secondary cell phone holder includes a clamp assembly having a primary clamp and a secondary clamp and an adjustment mechanism to move the secondary clamp relative to the primary clamp to secure a second cell phone therebetween.

Inventors: Koslosky; Frank (Gallatin, TN)

Applicant: Koslosky; Frank (Gallatin, TN)

Family ID: 1000007403743

Appl. No.: 18/116515

Filed: March 02, 2023

Related U.S. Application Data

us-provisional-application US 63315167 20220301

Publication Classification

Int. Cl.: H04M1/00 (20060101); H04B1/3877 (20150101); H04M1/60 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: H04M (1/6075); H04B (1/3877)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8827341	12/2013	Sofield	296/37.12	B60R 7/06
9699285	12/2016	Lundsgaard	N/A	H04M 1/6075
10933815	12/2020	Khubani	N/A	B60R 11/0241
11297917	12/2021	Malach	N/A	A45F 5/1516
2009/0294617	12/2008	Stacey	248/316.1	H04M 1/04
2013/0075285	12/2012	Peng	206/216	A45C 13/005

Primary Examiner: Fang; Pakee

Attorney, Agent or Firm: John Rizvi, P.A.—The Patent Professor

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates generally to cell phone holders and cases, and more particularly, to a multiple cell phone holder for releasably holding two cell phones together.

BACKGROUND OF THE INVENTION

(2) Cellular phones or cell phones are common electronic communications devices used for contacting other individuals. Newer or smart phones also can contain various programs such as, for example, accounting programs, navigational programs, games, etc. The cell phones are often carried in cases or cell phone holders for ease of transport and use.

(3) Cell phone technology is constantly improving often requiring a user to upgrade or get a newer model cell phone. This can pose a problem where the user has valuable information on a first cell phone that is difficult or inconvenient to copy over onto a newer second cell phone. Thus, the user often needs to carry two cell phones with them.

(4) Additionally, in many professions, it is often necessary to carry two separate cell phones. For example, it is often necessary to carry one cell phone for business and another cell phone for personal use. This requires the user to carry two separate cell phone cases or holders.

(5) Still further, a user may wish to simultaneously use one cell phone for communication with a first party and a second cell phone for viewing data on a cell phone program. Often these programs are best viewed on a cell phone screen horizontally or in landscape mode and the communication with the first party is best viewed on the other cell phone vertically in portrait mode.

(6) Accordingly, there is need for a solution to at least one of the aforementioned problems. For instance, there is an established need for a cell phone holder that can carry multiple phones. There is a further established need for a multiple cell phone holder that can hold one cell phone at an angle relative to another cell phone.

SUMMARY OF THE INVENTION

- (7) The present invention is directed to a multiple cell phone holder for retaining a first cell phone and a second cell phone perpendicular to the first cell phone. The multiple cell phone holder generally includes a primary cell phone holder, a secondary cell phone holder and connector assembly for holding the secondary cell phone holder perpendicular to the primary cell phone holder. The connector assembly is rotatably mounted relative to the primary cell phone holder. The primary cell phone holder includes one or more magnets to secure a first cell phone to the primary cell phone holder. The secondary cell phone holder includes a clamp assembly having a primary clamp and a secondary clamp and an adjustment mechanism to move the secondary clamp relative to the primary clamp to secure a second cell phone therebetween.
- (8) In a first implementation of the invention, a multiple cell phone holder is provided for carrying two cell phones, the multiple cell phone holder comprising: a primary cell phone holder including a vertical support, a horizontal support attached to said vertical support and at least one magnet mounted on said vertical support for engagement with a first cell phone; a secondary cell phone holder including a primary clamp, a secondary clamp, and an adjustment mechanism for moving said secondary clamp relative to said primary clamp to retain a second cell phone therebetween; and a connector assembly for movably mounting said secondary cell phone holder to said primary cell phone holder, wherein said secondary cell phone holder is mounted perpendicular to said primary cell phone holder.
- (9) In a second aspect, the secondary cell phone holder is rotatably mounted relative to said primary cell phone holder.
- (10) In another aspect, said connector assembly includes an attachment pin rotatably mounted to said primary cell phone holder.
- (11) In another aspect, said attachment pin is rotatably mounted in a housing on said vertical support of said primary cell phone holder.
- (12) In another aspect, said attachment pin is removable from said housing on said vertical support.
- (13) In another aspect, said secondary cell phone holder is mounted to a connector plate of said connector assembly.
- (14) In another aspect, said secondary cell phone holder is mounted to said connector plate with at least one magnet positioned on said connector plate.
- (15) In another aspect, said adjustment mechanism includes an adjustment bolt extending between said primary clamp and said secondary clamp, wherein rotation of said adjustment bolt moves said secondary clamp towards and away from said primary clamp.
- (16) In another aspect, said adjustment bolt has a threaded shaft rotatably mounted in said primary clamp.
- (17) In another aspect, said adjustment mechanism further includes at least one guide rod affixed to said secondary clamp and slidably mounted within said primary clamp.
- (18) In another aspect, said primary clamp includes a compressible pad for engagement with the second cell phone.
- (19) In another aspect, said secondary clamp includes a compressible pad for engagement with the second cell phone.
- (20) In another aspect, said connector assembly includes an attachment plate pivotally mounted to said primary cell phone holder.
- (21) In another aspect, said attachment plate is pivotally mounted to said primary cell phone holder by a pivot pin.
- (22) These and other objects, features, and advantages of the present invention will become more readily apparent from the attached drawings and the detailed description of the preferred embodiments, which follow.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The preferred embodiments of the invention will hereinafter be described in conjunction with the appended drawings provided to illustrate and not to limit the invention, where like designations denote like elements, and in which:
- (2) FIG. 1 presents a front isometric view of a multiple cell phone holder, for use in holding a pair of cell phones, in accordance with an illustrative embodiment of the present invention;
- (3) FIG. 2 presents a rear isometric view of the multiple cell phone holder in accordance with the illustrative embodiment of the present invention;
- (4) FIG. 3 presents front plan view of the multiple cell phone holder in accordance with the illustrative embodiment of the present invention;
- (5) FIG. 4 presents a front isometric view, with parts separated, of the multiple cell phone holder in accordance with the illustrative embodiment of the present invention including a primary cell phone holder and a secondary cell phone holder;
- (6) FIG. 5 presents a front isometric view of the of the multiple cell phone holder illustrated in FIG. 1 in accordance with the illustrative embodiment of the present invention with a first cell phone positioned in the primary cell phone holder of the multiple cell phone holder and a second cell phone positioned in the secondary cell phone holder of the multiple cell phone holder;
- (7) FIG. 6 presents a front isometric view, similar to FIG. 5, with the secondary cell phone holder of the multiple cell phone holder rotated relative to the primary cell phone holder of the multiple cell phone holder to position the secondary cell phone at an angle relative to the primary cell phone;
- (8) FIG. 7 presents a front plane view of the multiple cell phone holder incorporating an alternative embodiment of a connector assembly for pivotally connecting the primary cell phone holder to the secondary cell phone holder; and
- (9) FIG. 8 presents a side plane view of the multiple cell phone holder with the secondary cell phone holder pivoted forward relative to the primary cell phone holder.
- (10) Like reference numerals refer to like parts throughout the several views of the drawings.

DETAILED DESCRIPTION

(11) The following detailed description is merely exemplary in nature and is not intended to limit the described embodiments or the application and uses of the described embodiments. As used herein, the word “exemplary” or “illustrative” means “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” or “illustrative” is not necessarily to be construed as preferred or advantageous over other implementations. All of the implementations described below are exemplary implementations provided to enable persons skilled in the art to make or use the embodiments of the disclosure and are not intended to limit the scope of the disclosure, which is defined by the claims. For purposes of description herein, the terms “upper”, “lower”, “left”, “rear”, “right”, “front”, “vertical”, “horizontal”, and derivatives thereof shall relate to the invention as oriented in FIG. 1. Furthermore, there is no intention to be bound by any expressed or implied theory presented in the preceding technical field, background, brief summary or the following detailed description. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification, are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

(12) Shown throughout the figures, the present invention is directed toward a multiple cell phone holder for retaining a pair of cell phones perpendicular to each other.

(13) Referring to FIGS. 1-4, and initially with regard to FIGS. 1 and 2, a multiple cell phone holder for use in retaining a pair of cell phones, hereinafter multiple cell phone holder **100**, is illustrated in

accordance with an exemplary embodiment of the present invention. The multiple cell phone holder **100** generally includes a primary cell phone holder **110** and a secondary cell phone holder **112**. The secondary cell phone holder **112** is rotatably mounted to the primary cell phone holder **110** in order to position two cell phones in different orientations relative to a user as discussed in more detail hereinbelow. The secondary cell phone holder **112** is also removably attached to the primary cell phone holder **110** to allow individual use of a cell phone without having to remove a cell phone from the multiple cell phone holder **110**.

(14) The primary cell phone holder **110** of the multiple cell phone holder **100** generally includes an elongated rectangular vertical support **114** and a shorter rectangular horizontal support **116**. The secondary cell phone holder **112** of the multiple cell phone holder **100** is rotatably attached to the primary cell phone holder **110** at a top end **118** of the vertical support **114** of the primary cell phone holder **110**. The primary cell phone holder **110** includes multiple magnets **120** (FIG. **1**) for releasably securing a first cell phone (not shown) to the primary cell phone holder **110**.

(15) The horizontal support **116** of the primary cell phone holder **110** is attached to the vertical support **114** of the primary cell phone holder **110** at a bottom end **122** of the vertical support **114**. Specifically, the bottom end **122** of the vertical support **114** is attached to a middle portion **124** of the horizontal support **116**.

(16) The vertical support **114** and the horizontal support **116** may be formed from a variety of materials, such as, for example, polymeric material, metallic materials, etc. The horizontal support **116** can be formed integrally with the vertical support **114** or may be attached to the vertical support **114** by a variety of methods, such as, for example, welding, gluing, attaching using bolts or screws, etc.

(17) The magnets **120**, holding a first cell phone on the primary cell phone holder **110**, are positioned on a front surface **126** of the vertical support **114** of the primary cell phone holder **110**. The magnets **120** may be attached to the vertical support **114** by gluing, welding, attaching using screws or bolts, etc. The first cell phone is held on the primary cell phone holder **110** by the magnets **120** and is supported on the front surface **126** of the vertical support **114** of the primary cell phone holder **110** and a top surface **128** of the horizontal support **116** of the primary cell phone holder **110** in a manner discussed in more detail hereinbelow.

(18) The secondary cell phone holder **112** includes a clamp assembly **130** having an L-shaped primary clamp **132** including a rectangular base block **134** and first and second support legs **136** and **138** extending perpendicularly from the base block **134**. The clamp assembly **130** additionally includes an adjustable secondary clamp **140** movably attached to the primary clamp **132** by an adjustment mechanism **142**. The secondary clamp **140** generally includes a secondary clamp block **144** having first and second support legs **146** and **148** extending perpendicularly from the secondary clamp block **144**. A second cell phone (not shown) is secured on the secondary cell phone holder **112** between the primary clamp **132** and the adjustable secondary clamp **140** of the clamp assembly **130** of the secondary cell phone holder **112**.

(19) The secondary cell phone holder **112** is rotatably mounted to the primary cell phone holder **110** by a connector assembly **150**. The connector assembly **150** includes a connector plate **152** and an attachment pin **154** extending perpendicularly from the connector plate **152**. The attachment pin **154** is rotatably mounted in a housing **156** formed on a rear surface **158** of the vertical support **114** of the primary cell phone holder **110** adjacent the top end **118** of the vertical support **114**. This allows the secondary cell phone holder **112** to be rotated relative to the primary cell phone holder **110**.

(20) The secondary cell phone holder **112** is releasably connected to the connector plate **152** of the connector assembly **150** by one or more magnets (not shown) similar to those used in the primary cell phone holder **110**. This allows the secondary cell phone holder **112** to be easily removed from the connector plate **152** of the connector assembly **150** and thus from the primary cell phone holder **110**.

(21) The adjustment mechanism **142** of the clamp assembly **130** is provided to clamp a second cell phone between the primary clamp **132** and the secondary clamp **140** of the secondary cell phone holder **112**. The adjustment mechanism **142** includes an adjustment bolt **160** and a pair of guide rods **162** and **164** extending parallel to the adjustment bolt **160**. The adjustment bolt **160** is rotatably mounted in the adjustable secondary clamp **140** and includes a threaded shaft **166** and an adjustment knob **168** affixed to the threaded shaft **168**. The threaded shaft **168** is rotatably mounted within a threaded bore **170** (FIG. 1) of the base block **134** of the primary clamp **132** such that rotation of the adjustment bolt **160** in a first direction draws the secondary clamp **140** towards the primary clamp **132** to secure a cell phone therebetween and rotation of the adjustment bolt **160** in the opposite direction moves the secondary clamp **140** away from the primary clamp **132** to release the cell phone from the secondary cell phone holder **112**.

(22) The threaded bolt **160** is rotatably supported through the secondary clamp block **144** of the secondary clamp **140** by a support collar **172** fitted in a bore **174** extending through the secondary clamp block **144**. Thus, the threaded bolt **160** is free to rotate within the secondary clamp block **144** without rotating or torquing the secondary clamp block **144**.

(23) The guide rods **162** and **164** are fixedly mounted within the secondary clamp block **144** and extend outward there from. The guide rods **162** and **164** are slidably mounted within respective bores **176** and **178** formed longitudinally through the base block **134** of the primary clamp **132**. As the secondary clamp **140** is moved towards and away from the primary clamp **132**, the guide rods **162** and **164** slide within the bores **176** and **178** in the base block **132** to prevent the secondary clamp **140** from twisting or rotating relative to the first clamp **132**.

(24) In order to prevent any inadvertent crushing of a second cell phone as it is clamped between the primary clamp **132** and the secondary clamp **140** of the secondary cell phone holder **112**, the primary clamp **132** includes a pair of compressible pads **180** and **182**. The compressible pads **180** and **182** are mounted on the first and second legs **136** and **138** of the primary clamp **132**. The compressible pads **180** and **182** are formed of a foam, rubber or other compressible substance and may also have a relatively high coefficient of friction to prevent the second cell phone from sliding off of the primary clamp **132** in the event that the primary clamp **132** becomes slightly loosened from the secondary clamp **140**.

(25) Likewise, the secondary clamp **140** may also include a pair of compressible pads **184** and **186** affixed to the first and second legs **146** and **148** of the secondary clamp **140**. Tightening the adjustment bolt **160** firmly clamps a second cell phone between the compressible pads **180** and **182** of the primary clamp **132** and the compressible pads **184** and **186** of the secondary clamp **140**.

(26) Turning specifically to FIG. 3, the distance "L" between the first and second legs **136** of the primary clamp **132** and the first and second legs **146** and **148** of the secondary clamp **140** is adjusted by rotation of the adjustment bolt **160** in the direction of arrow "A". This moves the secondary clamp **140** of the secondary cell phone holder **112** in the direction of arrow "B" relative to the primary clamp **132** of the secondary cell phone holder **112** to clamp the second cell phone therebetween as well as accommodating cell phones of various lengths. As noted hereinabove, the guide rods **162** and **164** slide in and out of the base block **134** of the primary clamp **132** to prevent twisting of the secondary clamp **140** during the rotation of the adjustment bolt **160**.

(27) Referring for the moment to FIG. 4, as noted hereinabove, in addition to being rotatable relative to the primary cell phone holder **110**, the secondary cell phone holder **112** is removable from the primary cell phone holder **110**. This can be accomplished in two separate ways. As described hereinabove, the secondary cell phone holder **112** may be releasably attached to the connector plate **152** of the connector assembly **150** by a magnets (not shown) mounted on the connector plate **152** in a manner similar to that used on the primary cell phone holder **110**. Pulling the secondary cell phone holder **112** away from the magnets on the connector plate **152** releases the secondary cell phone holder **112** from the connector assembly **150** and thus from the primary cell phone holder **110**.

(28) Alternatively, the connector plate **152** and the attachment pin **154** of the connector assembly **150**, along with the secondary cell phone holder **112**, may be removed from the housing **156** of the connector assembly **150** affixed to the vertical support **114** of the primary cell phone holder **110**. As shown, the attachment pin **154** is rotatably mounted within a bore **188** of the housing **156** mounted on the primary cell phone holder **110** for rotation of the secondary cell phone holder **112** relative to the primary cell phone holder **110** in the direction of arrow “C”. Drawing the attachment pin **154** out of the bore **188** of the housing **156** in the direction of arrow “D” also releases the secondary cell phone holder **112** from the primary cell phone holder **110**.

(29) Referring now to FIGS. **3**, **5** and **6**, the use of the multiple cell phone holder **100**, including the primary cell phone holder **110**, the secondary cell phone holder **112** and the connector assembly **150**, to retain a pair of cell phones will now be described. The multiple cell phone holder **110** is provided to hold a pair of cell phones, such as, for example, first and second cell phones **300** and **400**, respectively, as a single unit and allow the first and second cell phones **300** and **400** to be rotated relative to each other.

(30) To assemble the first cell phone **300** to the primary cell phone holder **110** of the multiple cell phone holder **100**, the first cell phone **300** is positioned on the primary cell phone holder **110** such that a bottom end **310** of the first cell phone **300** rests on the top surface **128** of the horizontal support **116** of the primary cell phone holder **110** and a back surface **312** of the first cell phone **300** rests against the front surface **126** of the vertical support **114** of the primary cell phone holder **110**. The first cell phone **300** is releasably secured to the primary cell phone holder **110** by the magnets **120** (FIG. **3**) on the vertical support **114** of the primary cell phone holder **110**.

(31) In order to secure the second cell phone **400** to the secondary cell phone holder **112**, the adjustment mechanism **142** is used to separate the primary clamp **132** from the secondary clamp **140** a sufficient length **L** (FIG. **3**) to allow the second cell phone **400** to be positioned between the primary and secondary clamps **132** and **140**, respectively. A first or bottom end **410** of the second cell phone **400** is initially positioned against the first and second legs **136** and **138** of the primary clamp **132**. More specifically, the bottom end **410** of the second cell phone **400** is positioned against the compressible pads **180** and **182** on the first and second legs **136** and **138**, respectively. A back surface **412** of the second cell phone **400** is positioned against a front surface **190** of the base block **134** of the primary clamp **132** and the adjustment bolt **160** is rotated by turning the adjustment knob **168** in the direction of arrow “A” to draw the secondary clamp **140** towards the primary clamp **132** in the direction of arrow “B” (FIG. **3**).

(32) As the adjustment bolt **160** draws the secondary clamp **140** towards the primary clamp **132**, the compressible pads **184** and **186** on the first and second legs **146** and **148** of the secondary clamp **140** engage a second or top end **414** of the second cell phone **400** such that the second cell phone **400** is captured within the clamp assembly **130** of the secondary cell phone holder **112**. As noted above, the compressible pads **180**, **182**, **184** and **186** are provided to prevent crushing of the second cell phone **400** as the adjustment bolt **160** is operated to secure the second cell phone **400** within the secondary cell phone holder **112**.

(33) As best shown in FIG. **5**, when the first and second cell phones **300** and **400** are releasably secured to the multiple cell phone holder **110**, the second cell phone **400** is held orthogonal or perpendicular to the first cell phone **300**. This allows a user to easily operate two cell phones in close proximity on a single cell phone holder. For example, a user may wish to retain an older cell phone containing programs, photos, contact lists, for example the second cell phone **400**, for ease of access while simultaneously utilizing features on a newer cell phone for example the first cell phone **300**. Alternatively, it allows a user to easily communicate over two cell phones at the same time. For example, the first cell phone **300** may be used for secure communications with a relative, friend, client, etc. while the second cell phone is being used for a zoom meeting, consultation with other persons, etc. Thus, the multiple cell phone holder **100** permits a user to easily carry two cell phones together for simultaneous use.

(34) With specific reference to FIG. 6, should a user wish to share a conversation with an accompanying second user, the second cell phone **400** can be rotated relative in the direction of arrow “C” relative to the first cell phone **300** to better position the second cell phone **400** to the second user. Additionally, the ability of the multiple cell phone holder **100** to rotate one cell phone holder, for example, the second cell phone holder **112** relative to the other allows the user to use one cell phone, for example the first cell phone **300**, for communications while taking pictures with the other cell phone, for example the second cell phone **400**.

(35) Finally, the ability of the multiple cell phone holder **100** to easily retain two cell phones and subsequently detach them from each other by separating the second cell phone holder **112** from the first cell phone holder **110** allows the user to carry one or both cell phones at a time. Both the first and second cell phones **300** and **400**, may also be held by the multiple cell phone holder **100** at a single location for ease of charging.

(36) Referring now to FIGS. 7 and 8, and initially with regard to FIG. 7, there is disclosed an alternative connector assembly **200** for use in the multiple cell phone holder **100**. The connector assembly **200** allows the secondary cell phone holder **112** to pivot or rotate forward and back relative to the primary cell phone holder **100**. As shown, the connector assembly **200** generally includes a connector plate **202** for supporting the secondary cell phone holder **112** and an attachment pin or plate **204** affixed to and extending from the connector plate **202**.

(37) In this embodiment of the connector assembly **200**, the connector assembly **200** includes a housing **204** affixed to or formed integrally with the vertical support **114** of the primary cell phone holder **110**. Specifically, the housing **204** is provided at the top end **118** (FIG. 8) of the vertical support **114** of the primary cell phone holder **110**. The connector assembly **200** further includes a pair of semi-circular ears **208a** and **208b** extending upward from the housing **104**. The semi-circular ears **208a** and **208b** may be attached to the housing **204** in known manner or may be formed integrally therewith.

(38) The connector plate **202** supporting the secondary cell phone holder **112** is pivotally connected to the housing **204** extending from the primary cell phone holder **110** by a pivot pin **210**. This allows the secondary cell phone holder **112** to pivot forward and back relative to the primary cell phone holder **110**. The pivot pin **210** extends through a bore **212** in the connector plate **204** and through respective holes **214a** and **214b** formed through the semi-circular ears **208a** and **208b**.

(39) With reference to FIG. 8, the secondary cell phone holder **112** can pivot forward and back about the pivot pin **210** in the direction of arrow “E” relative to the primary cell phone holder **110**. This allows a user to point the secondary cell phone **400** (FIG. 6) mounted on the second cell phone holder **112** up or down relative to the first cell phone **300** retained on the primary cell phone holder **110**.

(40) Since many modifications, variations, and changes in detail can be made to the described preferred embodiments of the invention, it is intended that all matters in the foregoing description and shown in the accompanying drawings be interpreted as illustrative and not in a limiting sense. Thus, the scope of the invention should be determined by the appended claims and their legal equivalents.

Claims

1. A multiple cell phone holder for carrying two cell phones, the multiple cell phone holder comprising: a primary cell phone holder including a vertical support, a horizontal support attached to said vertical support and at least one magnet mounted on said vertical support for engagement with a first cell phone; a secondary cell phone holder including a primary clamp, a secondary clamp, and an adjustment mechanism for moving said secondary clamp relative to said primary clamp to retain a second cell phone therebetween; a connector assembly for movably mounting said secondary cell phone holder to said primary cell phone holder, wherein said secondary cell phone

holder is mounted perpendicular to said primary cell phone holder; wherein said secondary cell phone holder is mounted to said connector plate with at least one magnet positioned on said connector plate; wherein said adjustment mechanism includes an adjustment bolt extending between said primary clamp and said secondary clamp; wherein rotation of said adjustment bolt moves said secondary clamp towards and away from said primary clamp; wherein said adjustment bolt has a threaded shaft rotatably mounted in said primary clamp; and wherein said adjustment mechanism further includes at least one guide rod affixed to said secondary clamp.

2. The multiple cell phone holder of claim 1, wherein said secondary cell phone holder is rotatably mounted relative to said primary cell phone holder.
 3. The multiple cell phone holder of claim 1, wherein said connector assembly includes an attachment pin rotatably mounted to said primary cell phone holder.
 4. The multiple cell phone holder of claim 3, wherein said attachment pin is rotatably mounted in a housing on said vertical support of said primary cell phone holder.
 5. The multiple cell phone holder of claim 3, wherein said attachment pin is removable from said housing on said vertical support.
 6. The multiple cell phone holder of claim 1, wherein said secondary cell phone holder is mounted to a connector plate of said connector assembly.
 7. The multiple cell phone holder of claim 1, wherein said at least one guide rod is slidably mounted within said primary clamp.
 8. The multiple cell phone holder of claim 1, wherein said primary clamp includes a compressible pad for engagement with the second cell phone.
 9. The multiple cell phone holder of claim 1, wherein said secondary clamp includes a compressible pad for engagement with the second cell phone.
 10. The multiple cell phone holder of claim 1, wherein said primary clamp includes a pair of compressible pads.
 11. The multiple cell phone holder of claim 10, wherein said compressible pads are mounted on a first leg and a second leg of said primary clamp.
 12. The multiple cell phone holder of claim 11, wherein said compressible pads are formed of a foam, rubber or other compressible substance.
 13. The multiple cell phone holder of claim 12, wherein said compressible pads may have a relatively high coefficient of friction to prevent said second cell phone from sliding off of said primary clamp.
 14. The multiple cell phone holder of claim 10, wherein said secondary clamp includes a pair of compressible pads.
 15. The multiple cell phone holder of claim 14, wherein an adjustment bolt firmly clamps said second cell phone between said pair of compressible pads of said primary clamp and said pair of compressible pads of said secondary clamp.
-