

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414837
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Li; Shugang

Needle clamping device and leg support device

Abstract

The present application discloses a needle clamping device and a leg support device. The needle clamping device includes a first component having a shaft portion; a second component hinged with the shaft portion, the second component includes a first portion and a second portion whose relative position is variable, the first portion and the second portion are arranged to clamp the shaft portion when the relative position changes; a clamping mechanism for clamping the needle, the clamping mechanism is connected to the second component, and the clamping mechanism is arranged so that at least part of the structure further clamps the first portion and the second portion, and drives the first portion and the second portion to change their relative position so that the second component clamps the shaft portion in the process of clamping the orthopaedic needle.

Inventors: Li; Shugang (Beijing, CN)

Applicant: BEIJING HURWA ROBOT MEDICAL TECHNOLOGY CO., LTD. (Beijing, CN); BEIJING HURWA ROBOT TECHNOLOGY CO., LTD. (Beijing, CN)

Family ID: 1000008819519

Assignee: Beijing Hurwa Robot Medical Tehnology Co., Ltd. (Beijing, CN); Beijing Hurwa Robot Technology Co., Ltd. (Beijing, CN)

Appl. No.: 17/709232

Filed: March 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220218436 A1	Jul. 14, 2022

Foreign Application Priority Data

CN	202010885394.9	Aug. 28, 2020
CN	202022330951.9	Oct. 16, 2020
CN	202110120633.6	Jan. 28, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/109000 20210728 PENDING child-doc US 17709232

Publication Classification

Int. Cl.: A61B90/57 (20160101); A61B17/34 (20060101)

U.S. Cl.:

CPC A61B90/57 (20160201); A61B17/3472 (20130101); A61B2090/571 (20160201)

Field of Classification Search

CPC: A61B (90/57); A61B (17/3472); A61B (2090/571)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4220146	12/1979	Cloutier	606/90	A61B 17/6425
5167223	12/1991	Koros et al.	N/A	N/A
5439465	12/1994	Tumibay	606/105	A61B 17/6408
5792046	12/1997	Dobrovolny	N/A	N/A
5921985	12/1998	Ross, Jr. et al.	N/A	N/A
6074401	12/1999	Gardiner et al.	N/A	N/A
6206894	12/2000	Thompson et al.	N/A	N/A
9717530	12/2016	Ross	N/A	A61B 17/645
2003/0199738	12/2002	Yager	600/227	A61B 90/57
2004/0144905	12/2003	Ropertz et al.	N/A	N/A
2012/0150183	12/2011	Dorawa	606/59	A61B 17/6466
2016/0278875	12/2015	Crawford	N/A	N/A
2020/0008889	12/2019	Ho	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2588947	12/2002	CN	N/A
2659361	12/2003	CN	N/A
2744307	12/2004	CN	N/A
101998842	12/2010	CN	N/A
203647498	12/2013	CN	N/A
205964137	12/2016	CN	N/A
108553255	12/2017	CN	N/A

109330813	12/2018	CN	N/A
109640862	12/2018	CN	N/A
109674612	12/2018	CN	N/A
109717938	12/2018	CN	N/A
111803199	12/2019	CN	N/A
111803200	12/2019	CN	N/A
111956441	12/2019	CN	N/A
213190924	12/2020	CN	N/A
213217541	12/2020	CN	N/A
213217542	12/2020	CN	N/A
0972491	12/1999	EP	N/A
3225224	12/2016	EP	N/A
3 409 231	12/2017	EP	N/A
559219	12/1943	GB	N/A
H05208023	12/1992	JP	N/A
2011517998	12/2010	JP	N/A
2015065989	12/2014	JP	N/A
2015511501	12/2014	JP	N/A
WO02083020	12/2001	WO	N/A
2018/102926	12/2017	WO	N/A
2018/220050	12/2017	WO	N/A

OTHER PUBLICATIONS

The first office action dated Feb. 8, 2022 for Chinese application No. 202010885394.9. cited by applicant

International Search Report dated Oct. 26, 2021 for PCT application No. PCT/CN2021/109000. cited by applicant

The Extended European Search Report for European Patent Application No. 21765820.2, dated Jun. 7, 2022. cited by applicant

The Extended European Search Report dated Mar. 7, 2023 for European Application No. 21860031.0. cited by applicant

Notice of Refusal dated Feb. 14, 2023 for Japanese Patent Application No. 2022-525474. cited by applicant

The First Examination Opinion dated Aug. 2, 2022 for Chinese Application No. 202110120633.6. cited by applicant

Primary Examiner: McGrath; Erin

Background/Summary

CROSS-REFERENCE OF RELATED APPLICATIONS (1) The present application is a continuation of International Application No. PCT/CN2021/109000, filed on Jul. 28, 2021, which claims priority of the Chinese patent application 202010885394.9 filed on Aug. 28, 2020 and entitled “Needle Clamping Device and Fixing Device”, the Chinese patent application 202022330951.9 filed on Oct. 16, 2020 and entitled “Leg Support Device” and the Chinese patent application 202110120633.6 filed on Jan. 28, 2021 and entitled “Leg Support Device”, all of which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present application relates to the technical field of medical devices, in particular to a needle clamping device and a leg support device.

BACKGROUND

(2) In scenarios such as knee arthroplasty, it is often necessary to keep the patient's limb fixed to facilitate the surgical operation. Taking knee arthroplasty as an example, at least the femur needs to be kept immobilized during the osteotomy of the femur. Traditional knee arthroplasty relies on an assistant to hold the patient's leg by hand to keep the leg fixed. The fixed way of holding the leg by hand increases the labor intensity of the assistant, and the accuracy and standardization depend on the physical strength level of the operator, and the stability is poor.

(3) The fixed device can effectively reduce the physical exertion of the doctor and reduce the instability of manual operation. The fixing method of the fixing device may be to bind the affected limb to the support, or to establish a rigid connection with the bone of the affected limb through instruments such as threaded needles, and to fix the threaded needle on the support. However, the use of fixing devices increases the operation steps involved in the surgery, increases the duration of the surgery, and results in increased exposure time of the affected area. Especially in the fixing method of instruments using threaded needles, it is necessary to adjust the access of the threaded needle in multiple directions before implanting the threaded needle. After implanting, it is necessary to fix the threaded needle on the fixing device and lock the parts of the fixing device itself. The above operations are not conducive to reducing the complicated degree of surgery.

SUMMARY

(4) The present application provides a needle clamping device and a leg support device so as to at least partially solve the above technical problems.

(5) In a first aspect, the present application provides a needle clamping device for clamping an orthopedic needle, the needle clamping device comprises: a first component having a shaft portion; a second component hinged with the shaft portion, the second component includes a first portion and a second portion whose relative position is variable, the first portion and the second portion are arranged to clamp the shaft portion when the relative position changes; a clamping mechanism for clamping the needle, the clamping mechanism is connected to the second component, the clamping mechanism is arranged so that at least part of the structure further clamps the first portion and the second portion and drives the first portion and the second portion to change the relative position so that the second component clamps the shaft portion in the process of clamping the orthopaedic needle.

(6) In a first possible implementation manner, the first portion and the second portion of the second component are a first clamping arm and a second clamping arm arranged side by side, a first end portion of the first clamping arm is connected to a first end portion of the second clamping arm, a predetermined distance is formed between a second end portion of the first clamping arm and a second end portion of the second clamping arm, and a shaft hole is formed between the first clamping arm and the second clamping arm; the second component is rotatably connected with the shaft portion of the first component through the shaft hole.

(7) In combination with the above possible implementation manners, in a second possible implementation, the clamping mechanism includes: an inner shaft that penetrates through the second end portion of the first clamping arm and the second end portion of the second clamping arm, a first end and a second end of the inner shaft are distributed on both sides of the second component, and the first end is provided with a first limiting surface; a handle member movably arranged on the second end of the inner shaft, when the handle member is movable relative to the inner shaft, at least part of the structure can move in an axial direction of the inner shaft; a locking sleeve having a through hole, the locking sleeve is sleeved on the outside of the first end of the inner shaft, the locking sleeve can move relative to the inner shaft, the locking sleeve has a second

limiting surfaces, the second limiting surface and the first limiting surface of the inner shaft are arranged face to face or diagonally opposite to each other; wherein, the second component forms limit for the handle member and the locking sleeve in the axial direction of the inner shaft.

(8) In combination with the above possible implementation manners, in a third possible implementation manner, a first radial hole is provided on the first end of the inner shaft along the radial direction, a hole wall portion of the first radial hole facing away from an end surface of the first end is the first limiting surface, the locking sleeve is provided with a second radial hole along the radial direction, and a hole wall portion of the second radial hole that has the same direction as the end surface of the first end of the inner shaft is the second limiting surface. The first limiting surface is arranged diagonally opposite to the second limiting surface.

(9) In combination with the above possible implementation manners, in a fourth possible implementation manner, the first end of the inner shaft is located in the locking sleeve, and the locking sleeve is provided with a limiting rod.

(10) In combination with the above possible implementation manners, in a fifth possible implementation manner, the first end of the inner shaft is provided with a flange protruding radially, the flange is located on a side portion of an end of the locking sleeve facing away from the second component, a gap is formed between the flange and the end of the locking sleeve facing away from the second component, a side surface of the flange facing the locking sleeve is the first limiting surface, and an end surface of the first end facing the flange is the second limiting surface.

(11) In combination with the above possible implementations, in a sixth possible implementation, the handle member includes a cylinder portion and a handle portion, the cylinder portion is connected with the handle portion, the handle portion radially protrudes out of the cylinder portion, the cylinder portion and the handle portion are sleeved outside the second end of the inner shaft and are threadedly connected with the second end of the inner shaft, an end of the handle portion is in contact with the second end portion of the first clamping arm. When the handle portion is rotated, it can drive the inner shaft to move the axial direction and drive the locking sleeve to squeeze the second end portion of the second clamping arm.

(12) In combination with the above possible implementations, in a seventh possible implementation, the handle member is a cam handle, the cam handle includes a cam portion and a handle portion, the cam portion is connected with the handle portion, the cam portion is rotatably connected with the second end of the inner shaft. When the handle portion rotates to drive the cam portion to rotate, it can drive the inner shaft to move in the axial direction and drive the locking sleeve to squeeze the second end portion of the second clamping arm.

(13) In combination with the above possible implementation manners, in an eighth possible implementation manner, the inner shaft is connected with the locking sleeve in a manner of circumferential limit.

(14) In combination with the above possible implementation manners, in a ninth possible implementation manner, an outer peripheral surface of the inner shaft at least includes a plane area parallel to the inner shaft, an inner peripheral surface of the through hole of the locking sleeve is provided with a matching surface matched with the plane area. The matching surface is fitted with the plane area to form the circumferential limit.

(15) In combination with the above possible implementation manners, in a tenth possible implementation manner, an elastic member is further provided between the first end of the inner shaft and the locking sleeve, and the elastic member acts on the inner shaft and enables that the inner shaft have a tendency of protruding toward the outside of the sleeve.

(16) In a second aspect, the present application provides a leg support device having the needle clamping device provided by any of the implementations of the first aspect. The leg support device includes: a base; a support rod assembly connected to the base; the needle clamping device is provided on the upper portion of the support rod assembly.

(17) In a first possible implementation manner, the support rod includes a first support rod

assembly and a second support rod assembly respectively disposed on two sides of the base, and at least one of the first support rod assembly and the second support rod assembly can be detachably connected to the base.

(18) In combination with the above possible implementation manners, in a second possible implementation manner, the position of the support rod and the base relative to each other along a length direction of the side of the base is adjustable.

(19) Compared with the prior art, embodiments of the present application have at least the following advantages:

(20) In the needle clamping device provided in embodiments of the present application, the clamping structure in the needle clamping device can make the second component clamp the shaft portion of the first component while clamping the orthopaedic needle, or make the second component release the shaft portion of the first component while releasing the orthopaedic needle. The complicated degree of the operation in the process of locking and releasing orthopedic needles (such as threaded needles) is reduced, the operation is convenient, and time and effort are saved.

(21) In addition, in the leg support device provided by the embodiment of the present application, at least one of the first support rod assembly and the second support rod assembly is detachably connected to the base respectively, and the needle clamping device mounted on the left or right can be selected according to the leg under surgery, which reduces the occupation of the surgery space and facilitates the operation around the knee joint of the human body. What more, the need for sterilization of instruments prior to surgery is reduced because only the support rod assembly that needs to be mounted on the base needs to be sterilized. In addition, the first support rod assembly and the second support rod assembly are located on both sides of the base, and the space between the two and the upper surface of the base can be used to lay the affected limb straight and flat to check the tension of the joint ligament during the surgery or after the surgery is completed, it is not necessary to remove the leg support device from the surgery table to make room for the affected limb to lay flat. Moreover, the leg is positioned by the first support rod assembly, which avoids the problems of poor stability and poor accuracy of the hand-holding fixation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The features, advantages and technical effects of the exemplary embodiments of the present application will be described below with reference to the accompanying drawings.

(2) FIG. 1 is a structural schematic diagram of a leg support device according to an embodiment of the present application;

(3) FIG. 2 is a structural schematic diagram of the base in FIG. 1;

(4) FIG. 3 is a schematic diagram of the structure of the vertical cylinder in FIG. 1 connecting with the base;

(5) FIG. 4 is a structural schematic diagram between the vertical cylinder and the upright column in FIG. 1;

(6) FIG. 5 is a structural schematic diagram of the needle clamping device in FIG. 1;

(7) FIG. 6 is a cross-sectional view schematically showing the structure of the needle clamping device of FIG. 5;

(8) FIG. 7 is a cross-sectional view schematically showing the structure of the needle clamping device in another embodiment;

(9) FIG. 8 is a cross-sectional view schematically showing the structure of the needle clamping device in another embodiment;

(10) FIG. 9 shows a structural schematic diagram of the foot support positioning device in FIG. 1 and the cross-sectional view of the foot support;

- (11) FIG. 10 is an enlarged view of the foot support positioning device in FIG. 9;
(12) FIG. 11 is a perspective view of the foot support positioning device in FIG. 1;
(13) FIG. 12 is a structural schematic diagram of the locking block in FIG. 1;
(14) FIG. 13 is a structural schematic diagram of the locking block driver in FIG. 1;
(15) FIG. 14 is a structural schematic diagram of a locking block and a locking block driver in another embodiment;
(16) In the drawings, the drawings are not necessarily drawn according to actual scale.

DETAILED DESCRIPTION

(17) Embodiments of the present application will be described in further detail below with reference to the accompanying drawings and examples. The following detailed description of the embodiments and the accompanying drawings are used to illustrate the principles of the present application by way of example, but should not be used to limit the scope of the present application, that is, the present application is not limited to the described embodiments.

(18) In the description of this application, it should be noted that, unless otherwise specified, the meaning of “plurality” is two or more; The orientation or positional relationship indicated by the terms “upper”, “lower”, “left”, “right”, “inner”, “outside” etc. is only for the convenience of describing the present application and simplifying the description, rather than indicating or implying that the indicated device or element must have a specific orientation, be constructed and operated in a specific orientation, and therefore should not be construed as restrictions to the present application. Furthermore, the terms “first”, “second” etc. are used for descriptive purposes only and should not be construed to indicate or imply relative importance. “Vertical” is not strictly vertical, but within the allowable range of errors. “Parallel” is not strictly parallel, but within the allowable range of errors.

(19) In the description of the present application, it should also be noted that, unless otherwise expressly specified and limited, the terms “install”, “connect” and “connect” should be understood in a broad sense, for example, it may be a fixed connection, a detachable connection, or an integral connection; it can be direct connection or indirect connection through an intermediate medium. For those of ordinary skill in the art, the specific meanings of the above terms in the present application can be understood according to specific circumstances.

(20) For a better understanding of the present application, embodiments of the present application are described below with reference to FIGS. 1 to 14.

(21) Referring to FIG. 1, FIG. 1 is a structural schematic diagram of a leg support device in an embodiment disclosed in the present application. The leg brace device can be used in surgical operations to support and fix an affected limb such as a leg, for example, to fix the femur in total knee arthroplasty.

(22) In the first aspect, embodiments of the present application provide a leg support device, which includes: a base **90d**, a first support rod assembly **10d**, a second support rod assembly **20d**, a first needle clamping device and a second needle clamping device. The structure of the first needle clamping device and the structure of the second needle clamping device can be the same.

(23) The base **90d** is used as the installation and support base of the device, and the first support rod assembly **10d** and the second support rod assembly **20d** are mounted on the base **90d**.

(24) Referring to FIG. 1, in some optional embodiments, the support bases of the two needle clamping devices are two independent support rod structures, namely a first support rod assembly **10d** and a second support rod assembly **20d**. The first support rod assembly **10d** and the second support rod assembly **20d** are detachably connected to the base **90d** respectively, so that needle clamping device mounted on the left or right side can be selected according to the leg under operation. This can reduce the occupation of the surgical space and facilitate the operation around the knee joint of the human body. Also, the need for sterilization of instruments prior to surgery can be reduced, as only the support rod assembly that needs to be mounted on the base **90d** needs to be sterilized.

(25) There is no beam between the first support rod assembly **10d** and the second support rod assembly **20d**, so during or after the surgery, the doctor can directly lay the patient's leg flat for joint flexion and extension observation without removing the leg support device. In addition, the doctor can choose to install only the first support rod assembly **10d** or the second support rod assembly **20d** according to the convenience of operation, without having to install both, reducing operation steps and occupied operation space near the knee joint. The position of the support rod assembly on the slide rail can also be adjusted through the slider at the bottom, which can adapt to more clinical conditions.

(26) The first support rod assembly **10d** and the second support rod assembly **20d** can be slidably connected with the base **90d**, the first support rod assembly **10d** and the second support rod assembly **20d** can slide relative to the base **90d**, and the position of the legs can be fine-tuned; A locking mechanism may also be provided between the first support rod assembly **10d**, the second support rod assembly **20d** and the base **90d** for locking the relative positions of the first support rod assembly **10d**, the second support rod assembly **20d** and the base **90d**.

(27) Referring to FIG. 2, specifically, the base **90d** is an I-shaped bottom plate with a first slide rail **91d** in the middle, and a second slide rail **92d** and a third slide rail **93d** are respectively provided on both sides of one end of the first slide rail **91d**.

(28) The first support rod assembly **10d** and the second support rod assembly **20d** are symmetrically arranged on both sides of the first sliding rail **91d**, and the two needle clamping devices are also symmetrically arranged.

(29) Referring to FIG. 1, FIG. 3 and FIG. 4, the structural composition of the first support rod assembly **10d** are taken as an example to describe below.

(30) The lower end of the vertical cylinder **11d** is connected to the second sliding rail **92d** of the base **90d** through the second sliding block **100e**, and is controlled by the locking block **300e**, the locking block driver **400e** and the pin **500e** to be locked with the second sliding rail **92d**. The structures and their connection relationships of the second sliding block **100e**, the locking block **300e**, the locking block driving member **400e** and the pin **500e** are the same as the structure and its deformation of the sliding block **100m**, the locking block **300m**, the locking block driving member **400m** and the pin **500m**.

(31) The upper end of the vertical cylinder **11d** is provided with a clamping device, and the clamping device can lock the upright column **12d** inserted into the vertical cylinder **11d**. The clamping device includes a cam handle **13d**, a first clamping arm **14d**, a second clamping arm **15d** and a locking screw **16d**. One end of the first clamping arm **14d** is hingedly connected with one end of the second clamping arm **15d**, an arc-shaped clamping portion is provided in the middle of the two, and a gap is formed between the other ends. The cam handle **13d** is provided at the position where the two clamping arms are provided with a gap, and the distance between the clamping arms is changed by the cam portion to realize the clamping effect. The cam handle **13d**, the nut, the rotating shaft and the like constitute a cam handle assembly for realizing the clamping of the clamping arm. The locking screw **16d** can also lock the vertical column **12d** in the vertical cylinder **11d** from the radial direction. Of course, the above locking mechanism is not unique, for example, the locking screw **16d** may not be provided, or only the locking screw **16d** may be provided, or the clamping structure in the needle clamping device may be used.

(32) The upright column **12d** is inserted into the upright cylinder **11d**, and the cam handle **13d** can be released when needed to adjust the insertion depth, thereby changing the height of the needle clamping device at the top of the upright post **12d** relative to the base **90d**.

(33) In some optional embodiments, the first support rod assembly **10d** can also be replaced with a support rod/arm with a fixed length, that is, the vertical cylinder **11d** is fixedly connected with the vertical column **12d**, and the lengths of the vertical cylinder **11d** and the vertical column **12d** are not adjustable in the axial direction.

(34) In some optional embodiments, the first support rod assembly **10d** and the second support rod

assembly **20d** may also be connected to the base **90d** in other ways. For example, it is directly fixed on the base **90d** with screws, bolts or other fastening structures.

(35) In some optional embodiments, only the first support rod assembly **10d** or the second support rod assembly **20d** may also be provided. In use, the first support rod assembly **10d** can be installed on the first slide rail **91d** or the second slide rail **92d** on the base **90d** according to actual needs. Specifically, the first support rod assembly **10d** can be installed on the third slide rail **93d** in the attitude shown in FIG. 1; or the first support rod assembly **10d** can be rotated 180 degrees around its long axis relative to the attitude shown in FIG. 1, and then installed on the third sliding rail **93d**, so that the needle clamping device is still located outside, which is convenient for operation.

(36) The first needle clamping device and the second needle clamping device are disposed on the top of the first support rod assembly **10d** and the second support rod assembly **20** respectively. The first needle clamping device is capable of clamping the first threaded needle **1**. Before clamping the first threaded needle **1**, the first needle clamping device has two rotational degrees of freedom relative to the first support rod assembly **10d**, and the operator can flexibly adjust the direction of the first threaded needle **1** as required. After the first threaded needle **1** is implanted in the affected limb, the first threaded needle **1** can be clamped and locked between the first needle clamping device and the first support rod assembly **10d** by only one tightening, which is easy and convenient to operate. The second needle clamping device also has the above-mentioned connection relationship with the second threaded needle.

(37) In some optional embodiments, the second needle clamping device can also be replaced with other form of needle clamping devices; in some other optional embodiments, the second needle clamping device can also be replaced with a fastening mechanism such as a bandage. As long as the first needle clamping device is provided, the complicated degree of the operation in the process of locking and releasing the threaded needle can be reduced to a certain extent.

(38) The inventors of the present application have found that the fixing manner of the threaded needle used in the related art requires that the access of the threaded needle needs to be adjusted in multiple directions before implanting the threaded needle, and after implanting the threaded needle needs to be fixed on the fixing device and the parts of the fixing device itself needs to be locked. The above operations are not conducive to reducing the complicated degree of the surgery.

(39) In view of the above findings, embodiments of the present application also provide a needle clamping device for clamping an orthopedic needle, which can at least reduce the complicated degree of operations in the process of locking and releasing the threaded needle. In order to facilitate the understanding of the needle clamping device of embodiments of the present application, the needle clamping device, the first needle-clamping device, and the second needle-clamping device of embodiments of the present application are described further in combination with FIG. 5 and FIG. 6, taking the first needle-clamping device as an example. FIG. 5 is a structural schematic diagram of the first needle clamping device in FIG. 1; FIG. 6 is a cross-sectional view of the first needle clamping device, wherein the cutting plane passes through the centerline of the first threaded needle **1** and is perpendicular to the first support rod assembly.

(40) The first needle clamping device includes a first component **100**, a second component **200** and a clamping mechanism **300**. The first component **100** is provided on the first support rod assembly **10d**. In the unlocked state, the second component **200** can be rotated relative to the first component **100**, the clamping mechanism **300** as a whole can be rotated relative to the second component **200**, and the axes of the two rotational movements are in a spatially vertical relationship. The above connection relationship is convenient for adjusting the implanted device to a proper implantation orientation before the implantation operation.

(41) The first component **100** includes a shaft portion **110**. The shaft portion **110** is disposed at the top end of the first support rod assembly **10d**. The peripheral surface of the tail end of the shaft portion **110** is provided with a ring groove for installing a snap ring to limit axially.

(42) The second component **200** is hinged with the shaft portion **110**, the second component **200**

includes a first portion and a second portion whose relative positions are variable, and the first portion and the second portion are arranged to clamp the shaft portion **110** when the relative position changes. In some embodiments, the first and second portions of the second component are first and second clamping arms **210** and **220** disposed side by side. The first end portion **211** of the first clamping arm **210** is connected to the first end portion **221** of the second clamping arm **220**. There is a predetermined distance, that is, a gap **240**, between the second end portion **212** of the first clamping arm **210** and the second end portion **222** of the second clamping arm **220**. A shaft hole **230** is further provided between the first clamping arm **210** and the second clamping arm **220**. (43) In the illustrated embodiments, the second component **200** is an open ring structure, which can be made by milling holes and slitting on a roughly cuboid blank, and the slit is arranged on the solid structure around the hole along the radial direction of the hole and is in communication with the hole. The solid structure around the hole is the main ring body, and the solid structures on both sides of the slit can be regarded as extension portions of the two tail ends of the main ring body respectively pointing to the outside of the ring body (the second end portion **212** and the second end portion **222**). The first clamping arm **210** is a half structure of the open ring structure (the left half portion of the dotted line m in FIG. 6), including half of the main ring body and its extension portion (the second end portion **212**). The second clamping arm **220** is the other half structure of the open ring structure (the right half portion of the dotted line m in FIG. 6), including the other half of the main ring body and its extension portion (the second end portion **222**). The shaft hole **230** is a ring hole of the open ring structure. The open ring structure is an integral structure, and the first end portion **211** of the first clamping arm **210** is fixedly connected with the first end portion **221** of the second clamping arm **220**.

(44) The second end portion **212** of the first clamping arm **210** is provided with a through hole **213**, and the through hole **213** is perpendicular to the shaft hole **230**. The second end portion **222** of the second clamping arm **220** is provided with a through hole **223**, and the through hole **223** is coaxially aligned with the through hole **213**.

(45) The shaft hole **230** of the second component **200** has the same diameter as the shaft portion **110** of the first component **100**, and the two form a rotational connection through the shaft hole engagement. When the second end portion **212** and the second end portion **222** are brought close to each other, the diameter of the shaft hole **230** tends to decrease, so the first clamping arm **210** and the second clamping arm **220** can clamp the shaft portion **110** to achieve locking function.

(46) The clamping mechanism **300** is used for clamping the needle, the clamping mechanism **300** is connected to the second component **200**, the clamping mechanism **300** is configured that at least part of the structure clamps the first portion and the second portion, and in the process of clamping the orthopaedic needle the first portion and the second portion are driven to change the relative position so that the second component **200** clamps the shaft portion **110**. In some embodiments, the clamping mechanism **300** may include an inner shaft **310**, a handle member **320**, a locking sleeve **330**, a limit pin **340** and a spring **350**.

(47) The inner shaft **310** penetrates through the second end portion **212** and the second end portion **222** of the second component. The first end **311** and the second end **312** of the inner shaft **310** are distributed on both sides of the second component **200**, and the first end **311** is provided with a first limiting surface **314**. The outer circumferential surface of the second end **312** is provided with threads.

(48) Specifically, the inner shaft **310** is inserted into the second end portion **212** and the second end portion **222** through the through hole **213** and the through hole **223**, the first end **311** protrudes from one side of the second end portion **222**, and the second end **312** protrudes from one side of the second end portion **212**. The tail end section of the first end **311** is a square shaft, the outer peripheral surface of this section is four planes, and a transition step is further provided between this section and the second end **312**. The square shaft is further provided with a first radial hole **313**. The first limiting surface **314** is the hole wall portion of the first radial hole **313** facing the

second end **312**, that is, the right half portion of the hole wall of the first radial hole **313** in the figure. When the first threaded needle **1** is locked, the hole wall portion contacts and presses the first threaded needle **1**, so it is defined as the first limiting surface. Part of the wall surface of the round hole is an implementation manner of the first limiting surface, and in some optional embodiments, the first radial hole **313** may also be a recessed structure arranged radially such as a waist-shaped hole, a square hole, or a groove. The first limiting surface is the hole wall portion facing the second end **312** in the above structure, and the hole wall portion may be a plane or a curved surface.

(49) The handle member **320** is movably disposed on the second end **312** of the inner shaft **310**, and the handle member **320** can move axially on the inner shaft **310** as a whole when the handle member **320** moves relative to the inner shaft **310**. Specifically, the handle member **320** includes a cylinder portion **321**, a handle portion **323** and a threaded hole **322**. The handle portion **323** protrudes from the outer surface of the cylinder portion **321** in the radial direction. The threaded hole **322** penetrates the cylinder portion **321**. The handle member **320** forms a nut-screw mechanism through the threaded hole **322** and the external thread of the inner shaft **310**. When the handle member **320** rotates on the inner shaft **310**, the handle member **320** can move axially on the inner shaft **310** at the same time.

(50) The center of the locking sleeve **330** is provided with a through hole **331**, and the through hole **331** is a stepped hole. The locking sleeve **330** has a second limiting surface **333** and a second limiting surface **334**, which are arranged diagonally opposite to the first limiting surface **314** of the inner shaft **310**. Specifically, the through hole **331** is a square hole at the maximum diameter thereof (the right half portion of FIG. 6), whose size matches the square shaft of the first end **311** of the inner shaft **310** and forms a circumferential limiting engagement with the square shaft. The locking sleeve **330** is provided with a second radial hole **332** penetrating in the radial direction. The hole is divided into two sections by the through hole **331**. The second limiting surface **333** and the second limiting surface **334** are the hole wall portions of the two sections having the same direction as the end surface of the first end **311**. When the first threaded needle **1** is locked, the hole wall portions will contact and press against the first threaded needle **1**, so it is defined as the second limiting surface. Part of the wall surface of the round hole is only an implementation manner of the second limiting surface, and in some optional embodiments, the second radial hole **332** may also be a recessed structure arranged radially such as a waist-shaped hole, a square hole, or a groove, etc. The second limiting surface is the hole wall portion of the recessed structure that has the same direction as the end surface of the first end **311** (the hole wall portion facing away from the second component **200**), and the hole wall portion may be a plane or a curved surface. The locking sleeve **330** is sleeved outside the first end **311** of the inner shaft **310**. The locking sleeve **330** is axially movable relative to the inner shaft **310**.

(51) The locking sleeve **330** is also provided with a radial hole for installing a limiting pin **340**, and the radial hole is located outside the second radial hole **332** (the right side of the second radial hole **332** in FIG. 6). The limiting pin **340** is inserted into the radial hole of the locking sleeve **330** and is located outside the end surface of the first end **311** to form a structure of limiting the axial direction of the inner shaft **310**.

(52) The spring **350** is sleeved on the inner shaft **310** and is located in the through hole **331** of the locking sleeve **330**. One end of the spring **350** abuts against a step of the through hole **331**, and the other end abuts against the shoulder of the transition step of the inner shaft **310**. The spring **350** causes the first end **311** has tendency to protrude outward (rightward in FIG. 6) from the through hole **331** (the tendency to move the locking sleeve **330** toward the side of the second end **312** of the inner shaft **310**).

(53) The handle member **320** and the locking sleeve **330** are located on two sides of the second component **200** respectively. Both the handle member **320** and the locking sleeve **330** can move along the axial direction of the inner shaft **310**. When the handle member **320** and the locking

sleeve **330** are close to each other, the second component **200** can clamp the shaft portion **110** under the clamping of the handle member **320** and the locking sleeve **330**, eliminating the two rotational degrees of freedom of the first needle clamping device.

(54) Embodiments of the present application only need to drive the handle to realize the locking of the threaded needle and the locking of the two rotational degrees of freedom of the needle clamping device, which is convenient to operate and saves time and effort.

(55) Instructions for use:

(56) The handle member **320** is rotated so that the distance from the locking sleeve **330** becomes larger. In this process, under the action of the spring **350**, the first end **311** of the inner shaft **310** approaches the limit pin **340** and finally abuts against the limit pin **340**. At this time, the second radial hole **332** is aligned with the first radial hole **313** and the first threaded needle **1** is inserted.

(57) The orientation of the first threaded needle **1** is adjusted until an appropriate implantation path is reached, and a tool is used to drive the first threaded needle **1** into the patient's bone.

(58) The handle member **320** is rotated so that it is close to the locking sleeve **330**. In this process, the inner shaft **310** will pull the first threaded needle **1** and the locking sleeve **330** to approach the handle member **320** together. The locking sleeve **330** acts on the second end portion **222** of the second component **200**, and the handle member **320** acts on the second end portion **212**, so that the first clamping arm **210** and the second clamping arm **220** clamp the shaft portion **110**. In addition, the first limiting surface **314** of the inner shaft **310** and the second limiting surface **334** and the second limiting surface **333** of the locking sleeve **330** jointly clamp the first threaded needle **1**, so that the first threaded needle **1** cannot move or turn. In some other embodiments, the handle member **302** can also be a nut, the nut is connected with the second end **312** of the inner shaft **310** by a thread, and the nut can drive the first clamping arm **210** and the second clamping arm **220** to clamp the shaft portion **110** of the first component when the nut moves along the inner shaft **310** and approaches the locking sleeve **330**.

(59) In the above operation process, the clamping mechanism **300** has two rotational degrees of freedom relative to the first component **100**, so the adjustment range of the threaded needle is relatively large. The first threaded needle **1** can be clamped between the inner shaft **310** and the locking sleeve **330** only by turning the handle member **320**, so that the inner shaft **310** and the handle member **320** are also locked with the second component **200** and the second component **200** is locked with the first component **100**, which is convenient to operate and saves time and effort. In addition, in the process of driving the first threaded needle **1** into the patient's bone, the first radial hole **313** and the second radial hole **332** in the clamping mechanism **300** can further guide and support the first threaded needle **1**, and the operator can grip the clamping mechanism **300** to prevent the first threaded needle **1** from being offset. The cooperation of the limiting pin **340** and the spring **350** can further automatically align the second radial hole **332** with the first radial hole **313**, so as to facilitate the rapid insertion of the first threaded needle **1**. The contact line between the first threaded needle **1** and the first radial hole **313** is parallel to the contact line between the first threaded needle **1** and the second radial hole **332** and the contact line is long, so that the first threaded needle **1** is evenly stressed and locked reliable. In some optional embodiments, the spring **350** may not be provided. During the operation, the operator can move the locking sleeve **330** to make the limiting pin **340** abut against the end surface of the first end **311**, and manually align the second radial hole **332** with the first radial hole **313**.

(60) In some optional embodiments, the limiting pin **340** and the spring **350** may not be provided. The second radial hole **332** is manually aligned with the first radial hole **313** during operation.

(61) In some optional embodiments, no circumferential limit may be provided between the inner shaft **310** and the locking sleeve **330**, and the second radial hole **332** and the first radial hole **313** may be manually rotated and aligned during operation.

(62) In some optional embodiments, the circumferential limit between the inner shaft **310** and the locking sleeve **330** may be the cooperation of a guide groove along the axial direction of the inner

shaft **310** and a key provided on the locking sleeve **330**; or, one or two flat surfaces are provided on the peripheral surface of the first end **311**, and corresponding matching structures are provided on the locking sleeve **330**. The matching structure of the locking sleeve **330** may be formed by machining, or additional parts may be provided on the locking sleeve **330**, and part of the surface of the part forms a matching structure (such as the end surface or the outer peripheral surface of a pin or a nail, the flat surface of a key).

(63) Referring to FIG. 7, FIG. 7 is a schematic structural diagram of a needle clamping device in another embodiment. The structure of the needle clamping device in the present embodiment is basically the same as the structure and principle of the first needle clamping device shown in FIG. 6, the difference include the second component **200a** is a split structure, and the second component **200** is an integral structure; the inner shaft **310a** and the locking sleeve **330a** are not provided with radial holes, but the first threaded needle **1** is clamped by the gap between them; and there is no limit pin between the inner shaft **310a** and the locking sleeve **330a** to perform axial limit. The structural differences of the second component **200a**, the inner shaft **310a** and the locking sleeve **330a** will be specifically described below.

(64) The second component **200a** is formed by connecting two separate clamping arms, and the two clamping arms are the first clamping arm **210a** and the second clamping arm **220a** in the figure. The first clamping arm **210a** includes a half ring body in the middle and a first end portion **211a** and a second end portion **212a** at both ends of the half ring body, and the second end portion **212a** is longer than the first end portion **211a**. The second clamping arm **220a** includes a half ring body in the middle and a first end portion **221a** and a second end portion **222a** at both ends of the half ring body, and the second end portion **222a** is longer than the first end portion **221a**. The first clamping arm **210a** and the second clamping arm **220a** are fastened together, the two half ring bodies form an open ring body, and the center of the ring body is the shaft hole **230a**. The first end portion **211a** is fixedly connected to the first end portion **221a**. The second end portion **212a** is provided with a through hole **213a**. The second end portion **222a** is provided with a through hole **223a**. A gap **240a** is formed between the second end portion **212a** and the second end portion **222a**.

(65) In some optional embodiments, the first end portion **211a** may also be hingedly connected to the first end portion **221a**.

(66) The inner shaft **310a** is different from the inner shaft **310** in that the first radial hole **313** is not provided, but a flange **313a** is formed at the tail end of the first end **311a**. The side surface of the flange **313a** facing the second end **312a** is the first limiting surface **314a**. In the assembly body, the flange **313a** protrudes out of the end surface of the locking sleeve **330a**, the first limiting surface **314a** faces the second limiting surface **334a**, and a ring groove is formed therebetween.

(67) The difference between the locking sleeve **330a** and the locking sleeve **330** is that the second radial hole **332** and the radial hole for installing the limiting pin **340** are not provided. The end surface of the locking sleeve **330a** that is not adjacent to the second component **200a** is the second limiting surface **334a**.

(68) When the handle member **320** is rotated, there is an axial relative displacement between the inner shaft **310a** and the locking sleeve **330a**, so that the first threaded needle **1** can be clamped or released. A recessed groove can also be provided on the side of the flange **313a** to prevent the first threaded needle **1** from coming out in the radial direction.

(69) In some optional embodiments, the inner shaft **310a** and the second component **200a** cannot rotate relative to each other. The position of the first threaded needle **1** in the annular groove formed by the first limiting surface **314a** and the second limiting surface **334a** is adjustable, so there is no need for rotational freedom between the inner shaft **310a** and the second component **200a**.

(70) In some optional embodiments, the inner shaft **310a** and the second component **200a** cannot rotate relative to each other, there is no circumferential limit between the locking sleeve **330a** and the inner shaft **310a**, and the locking sleeve **330a** and the inner shaft **310a** can rotate relative to

each other. In some other optional embodiments, the inner shaft **310a** and the second component **200a** cannot rotate relative to each other, there is no circumferential limit between the locking sleeve **330a** and the inner shaft **310a**, and the locking sleeve **330a** and the inner shaft **310a** can rotate relative to each other, and a recessed groove is provided on the end surface of the locking sleeve **330a**. When the first threaded needle **1** is located in the recessed groove, the locking sleeve **330a** can follow the rotation of the first threaded needle **1** around the inner shaft **310a**. This can not only ensure that the position of the first threaded needle **1** can be adjusted, but also prevent the first threaded needle **1** from coming out.

(71) Referring to FIG. 8, FIG. 8 is a schematic structural diagram of a needle clamping device in another embodiment. Compared with the first needle clamping device shown in FIG. 6, the needle clamping device in the present embodiment uses the cam handle **320b** instead of the handle member **320** to realize the locking function. Specifically, a cam handle **320b** and a sleeve **360** are disposed on the second end **312b** of the inner shaft **310b**, and the sleeve **360** is located between the second component **200** and the cam handle **320b**. When the cam handle **320b** rotates, the sleeve **360** can be driven to squeeze the second component **200** so as to achieve locking. The cam handle **320b** includes a cam portion and a handle portion, the cam portion is rotatably disposed on the second end **312b**, and the rotation center line is perpendicular to the inner shaft **310b**. When the cam handle **320b** is toggled, the contour surface of the cam portion rotates along with it, and its rotational motion can be decomposed into the movement along the axial direction of the inner shaft **310b**, the movement and rotation along the radial direction of the inner shaft **310b**, which is equivalent to the movement of part of the structure of the cam handle **320b** along the axial direction of the inner shaft **310b**.

(72) In some optional embodiments, the sleeve **360** may not be provided, and the cam handle **320b** may directly act on the second component **200**. In some other optional embodiments, a cylindrical cam can also be used to replace the cam handle **320b**. The cylindrical cam and the inner shaft **310b** are coaxially arranged and can rotate relative to each other. The cam surface of the cylindrical cam is located on the end surface of the cylinder and faces the sleeve **360** in the assembly body, and the sleeve **360** is provided with a protrusion facing the cam surface. When the cylindrical cam is rotated, the interaction between the cam surface and the sleeve **360** causes an axial displacement therebetween, thereby compressing the second component **200**.

(73) The leg support device of embodiments of the present application may further include a foot support **30**, and the foot support **30** is installed on the base **90d**. The foot support **30** can accommodate the foot of the patient, and the foot support **30** is slidably connected with the base **90d**, and the position of the foot support **30** relative to the base **90d** can be adjusted.

(74) Specifically, the foot support **30** is connected to the first sliding rail **91d** by the foot support positioning device. The structures of the foot support **30**, the foot support positioning device and the connection between them are the same as those shown in FIGS. 9 to 14, and the specific structures can refer to the drawings and their descriptions, which will not be repeated here.

(75) Referring to FIGS. 9 to 13, FIG. 9 is a cross-sectional view of the foot support positioning device and the foot support **30** in FIG. 1; FIG. 10 is an enlarged view of the foot support positioning device in FIG. 9; FIG. 11 is a perspective view of the foot support positioning device in FIG. 1; FIG. 12 is a schematic structural diagram of the locking block **300m** in FIG. 1; FIG. 13 is a schematic structural diagram of the locking block driver **400m** in FIG. 1.

(76) The foot support positioning device includes a sliding block **100m**, a foot support connecting mechanism **200m**, a locking block **300m**, a locking block driver **400m**, and a pin **500m**. The sliding block **100m** is the base for bearing and installation, and the foot support connection mechanism **200m**, the locking block **300m**, the locking block driver **400m** and the pin **500m** are all disposed on the sliding block **100m**.

(77) The sliding block **100m** is a rectangular plate structure. The bottom **120m** of the sliding block **100m** is provided with a chute **121m**, and the chute **121m** is a dovetail slot. The upper surface of the

sliding block **100m** is the load surface **110m**, the load surface **110m** is provided with a threaded hole **130m** and a boss, and the boss is provided with a pin hole and a recessed portion. Both the pin hole and the threaded hole **130m** are perpendicular to the plate body, and the threaded hole **130m** is a through hole. The sliding block **100m** is movably disposed on the sliding rail **12** of the base **90d** through the chute **121m**.

(78) The foot support connecting mechanism **200m** includes a first tong arm **210m**, a second tong arm **220m**, a locking screw **230m** and a pin **250m**, and an accommodating cavity **240m** is provided between the first tong arm **210m** and the second tong arm **220m**. The second tong arm **220m** is fixedly connected to the sliding block **100m**, and in the present embodiment, they are integral structure. The first tong arm **210m** is hingedly connected with the pin **250m**, and is connected in the pin hole of the boss through the pin **500m**. The accommodating cavity **240m** corresponds to the recessed portion on the boss of the sliding block **100m**. The other ends of the first tong arm **210m** and the second tong arm **220m** are both provided with through holes, the through hole of the first tong arm **210m** is a waist-shaped hole, and the through hole of the second tong arm **220m** is a threaded hole. The threaded hole of the second tong arm **220m** is a threaded hole of a nut embedded in the second tong arm **220m**, and the material of the nut can be a wear-reducing material. One end of the locking screw **230m** is provided with a nut, the other end is provided with a radial through hole, and a thread is provided in the middle. The locking screw **230m** is inserted into the through holes of the first tong arm **210m** and the tong clamp arm **220m**, and the threaded section of the locking screw **230m** and the threaded hole of the second tong arm **220m** constitute a nut screw pair. The radial hole of the locking screw **230m** is provided with a lever, and the lever is used to rotate the locking screw **230m**. In some optional embodiments, the second tong arm **220m** is a separate part, one end of each of the first tong arm **210m** and the second tong arm **220m** is hinged into one body through a pin **250m**, and connected to the sliding block **100m** through a pin **250m**.

(79) The connection structure for clamping the foot support **30** is disposed in the accommodating cavity **240m** of the foot support connecting mechanism **200m**. In the present embodiment, the connection structure of the foot support **30** is a foot support connecting rod **600m**, and the tail end of the foot support connecting rod **600m** is provided with a ball head **610m**.

(80) The locking block **300m** includes a locking portion **310m**, an external thread portion **320m** and a drive interface portion **330m**. The locking block **300m** is a cylinder, the locking portion **310m** and the external thread portion **320m** are provided at both ends of the cylinder, and the external thread portion **320m** is provided on the outer peripheral surface of the cylinder. A through hole is further provided in the center of the cylinder. The locking portion **310m** is the end surface of the cylinder, and the end surface is used to abut the upper surface of the base **90d**. The drive interface portion **330m** is a quincunx groove on the other end surface of the cylinder. The quincunx groove has an annular array of torque transmission portions **331m**, and the torque transmission portions **331m** are recessed grooves along the radial direction of the cylinder, which can generate a torque of **300m** on the locking block when the side wall of the recessed groove is forced. In the present embodiment, the number of recessed grooves of the quincunx groove is nine and the array angle interval of the recessed grooves is 40 degrees. The nine recessed grooves can be regarded as a set of torque transmission portions. The locking block **300m** is disposed in the threaded hole **130m** of the sliding block **100m** through the external thread portion **320m**.

(81) The locking block driver **400m** includes a torque output portion **410m** and a handle portion **420m**. Specifically, one tail end of the handle portion **420m** is provided with a disc, and an end surface of the disc is provided with the torque output portion **410m**. The torque output portion **410m** is a gear-shaped structure having an annular array of teeth **411m**. A through hole is provided in the center of the gear-shaped structure. The outer contour of the torque output portion **410m** is the same as that of the drive interface portion **330m**, the torque output portion **410m** is embedded in the drive interface portion **330m**, and the teeth **411m** of the torque output portion **410m** are

embedded in the recessed grooves of the quincunx groove of the drive interface portion **330m**. The through hole **340m** is coaxial with the through hole of the locking block driver **400m**.

(82) The pin **500m** is inserted into the through hole of the locking block **300m** and the locking block driver **400m**, and limits the radial displacement between the locking block **300m** and the locking block driver **400m** together with the shaft snap ring.

(83) When the locking block **300m** is driven to rotate by the locking block driver **400m**, the locking block **300m** can move axially relative to the sliding block **100m** and abut against the base **90d**, so that the sliding block **100m** is fixed on the base **90d**.

(84) Upon assembly, the azimuth relationship between the locking block driver **400m** and the locking block **300m** can be set according to actual needs. For example, during the locking operation, the handle needs to be rotated, and the required force is the largest just before reaching the locking position. If the operating space of the handle is relatively small near the locking position, it will cause inconvenience in operation. It is therefore necessary to set the handle to have sufficient space between the handle and the surrounding structure in the locked state. Specifically, in the present solution, the locking block driver **400m** is located below the foot support **30**, so the position of the locking block driver **400m** shown in FIG. **11** is in a locked state for convenient operation. Upon assembly, the foot support **30** is not installed first, the locking block **300m** is screwed into the threaded hole **130m** of the sliding block **100m**, the pin **500m** is inserted into the through hole **340m** of the locking block **300m**, and then the sliding block **100m** is installed on the slide rail **12**. The locking block driver **400m** is used to rotate the locking block **300m** to lock the sliding block **100m**. At this time, the position of the locking block driver **400m** relative to the sliding block **100m** can be arbitrary. The locking block driver **400m** is taken out, the locking block driver **400m** at the position shown in FIG. **10** is installed, and then the locking block driver **400m** is turned to release the locking block **300m** from the base **90d**, the sliding block **100m** is removed, such that the pin **500m** protrudes from the through hole of the locking block driver **400m** and a snap ring is used to achieve axial limit.

(85) In some optional embodiments, the torque output portion **410m** may be provided with a smaller number of teeth **411m**, such as three which are evenly distributed. In this case, the torque transmission portion **331m** in the drive interface portion **330m** is equivalent to three groups, and each group has three annular recessed grooves which are evenly distributed.

(86) In some optional embodiments, the torque output portion **410m** may be provided with a smaller number of teeth **411m**, such as one, two, three or four, and the angular interval between the teeth **411m** is 40 degrees (equivalent to removing some adjacent teeth **411m** of torque output **410m** in FIG. **12**).

(87) The foot support **30** is an “L”-shaped structure, which is similar to the shape of the foot and lower leg of a human body. The foot support **30** includes an “L”-shaped bottom plate and two side plates **31** on both sides of the bottom plate, and the space between the two side plates **31** is used for accommodating feet. The edge of the side plate **31** is provided with a notch **32**, and the outer side of the side plate **31** is provided with a limiting protrusion **33**. When the patient's foot is bound, the limiting protrusion **33** can prevent the bandage from slipping off. When the patient's foot is relatively thin, the bandage can pass through the notch **32**, which can effectively fix the foot. The bottom of the foot support **30** is provided with a foot support connecting rod **600m**, and the tail end of the foot support connecting rod **600m** is provided with a ball head **610m**. The foot support **30** is installed in the accommodating cavity **240m** of the foot support connecting mechanism **200m** through the ball head **610m**, and the ball head **610m** is clamped by the first tong arm **210m** and the second tong arm **220m**.

(88) Referring to FIG. **14**, FIG. **14** is a schematic structural diagram of a locking block and a locking block driver in another embodiment.

(89) In the present embodiment, the locking block driver **400n** includes a torque output portion **410n**, a handle portion **420n**, a cylindrical base **430n** and a positioning column **440n**. The

cylindrical base **430n** is provided at the tail end of the handle portion **420n**. The torque output portion **410n** is provided on the outer circumferential surface of the cylindrical base **430n**. The positioning column **440n** is disposed on the lower end surface of the cylindrical base **430n**. The drive interface portion **330n** of the locking block **300n** is a recessed groove on the end surface of the locking block **300n**, and the side wall of the recessed groove includes an arc surface portion **350n** and a plurality of torque transmission portions **331n**. The torque transmission portion **331n** is a recessed groove in the radial direction, and the shape is adapted to the torque output portion **410n**. The locking block **300n** is further provided with a through hole **340n** coaxial with the arc surface portion **350n**. The positioning post **440n** can form a shaft hole matching with the through hole **340n**. The cylindrical base **430n** and the arc surface portion **350n** are also cylindrical surface matching, so in some embodiments, the positioning column **440n** may not be provided. Four torque transmission portions **331n** are provided, so there are four relative positional relationships between the locking block driver **400n** and the locking block **300n**, which can be selected during assembly according to actual needs.

(90) Although the present application has been described with reference to preferred embodiments, various modifications may be made and equivalents may be substituted for parts thereof without departing from the scope of the application, particularly, provided that no structural conflict exists, each technical feature mentioned in each embodiment can be combined in any manner. The present application is not limited to the specific embodiments disclosed herein, but includes all technical solutions falling within the scope of the claims.

Claims

1. A needle clamping device for clamping an orthopedic needle, wherein the needle clamping device comprises: a first component comprising a shaft portion; a second component hinged with the shaft portion, wherein the second component comprises a first portion and a second portion whose relative position is variable, and the first portion and the second portion are arranged to clamp the shaft portion when the relative position changes; and a clamping mechanism for clamping the needle, wherein the clamping mechanism is connected to the second component, the clamping mechanism is arranged so that at least part of the clamping mechanism further clamps the first portion and the second portion, and drives the first portion and the second portion to change their relative position so that the second component clamps the shaft portion in the process of clamping the orthopedic needle, wherein the first portion and the second portion of the second component are a first clamping arm and a second clamping arm arranged side by side, a first end portion of the first clamping arm is connected with a first end portion of the second clamping arm, a predetermined distance is formed between a second end portion of the first clamping arm and a second end portion of the second clamping arm, a shaft hole is formed between the first clamping arm and the second clamping arm; the second component is rotatably connected with the shaft portion of the first component through the shaft hole, wherein the clamping mechanism comprises: an inner shaft, wherein the inner shaft passes through the second end portion of the first clamping arm and the second end portion of the second clamping arm, a first end and a second end of the inner shaft are distributed on both sides of the second component, and the first end is provided with a first limiting surface; a handle member, wherein the handle member is movably disposed on the second end of the inner shaft, and when the handle member moves relative to the inner shaft, at least part of the handle member can move in an axial direction of the inner shaft; and a locking sleeve with a through hole, wherein the locking sleeve is sleeved on the outside of the first end of the inner shaft, the locking sleeve can move relative to the inner shaft, the locking sleeve comprises a second limiting surface, and the second limiting surface and the first limiting surface of the inner shaft are arranged face-to-face or diagonally opposite to each other, wherein the second component forms a limit for the handle member and the locking sleeve in the axial direction of the inner shaft,

- and wherein an elastic member is further provided between the first end of the inner shaft and the locking sleeve, and the elastic member acts on the inner shaft and configures the inner shaft to have a tendency to protrude toward a side of the locking sleeve facing away from the second component.
2. The needle clamping device according to claim 1, wherein the first end of the inner shaft is provided with a first radial hole in a radial direction, a hole wall portion of the first radial hole facing away from an end surface of the first end is the first limiting surface, the locking sleeve is provided with a second radial hole in the radial direction, a hole wall portion of the second radial hole which has the same direction as the end surface of the first end of the inner shaft is the second limiting surface, and the first limiting surface and the second limiting surface are arranged diagonally opposite to each other.
 3. The needle clamping device according to claim 2, wherein the first end of the inner shaft is located in the locking sleeve, and a limiting rod is arranged in the locking sleeve.
 4. The needle clamping device according to claim 1, wherein the first end of the inner shaft is provided with a flange protruding along the radial direction, the flange is located on a side portion of an end of the locking sleeve facing away from the second component, a gap is formed between the flange and the end of the locking sleeve facing away from the second component, a side surface of the flange facing the locking sleeve is the first limiting surface, and an end surface of the first end facing the flange is the second limiting surface.
 5. The needle clamping device according to claim 1, wherein the handle member comprises a cylinder portion and a handle portion, the cylinder portion is connected with the handle portion, the handle portion protrudes radially out of the cylinder portion, the cylinder portion and the handle portion are sleeved outside the second end of the inner shaft, and are threadedly connected with the second end of the inner shaft, an end of the handle portion is contacted with the second end portion of the first clamping arm, and when the handle portion is rotated, the handle portion can drive the inner shaft to move in the axial direction, and drive the locking sleeve to squeeze the second end portion of the second clamping arm.
 6. The needle clamping device according to claim 1, wherein the handle member is a cam handle, the cam handle comprises a cam portion and a handle portion, the cam portion is connected with the handle portion, the cam portion is rotatably connected to the second end of the inner shaft, and when the handle portion rotates to drive the cam portion to rotate, the handle portion can drive the inner shaft to move in the axial direction and drive the locking sleeve to squeeze the second end portion of the second clamping arm.
 7. The needle clamping device according to claim 1, wherein the inner shaft is connected to the locking sleeve in a manner of circumferential limit.
 8. The needle clamping device according to claim 7, wherein an outer peripheral surface of the inner shaft comprises at least a plane area parallel to the inner shaft, an inner peripheral surface of the through hole of the locking sleeve is provided with a matching surface matched with the plane area, the matching surface is fitted with the plane area to form the circumferential limit.
 9. A leg support device comprising a needle clamping device of claim 1, wherein the leg support device further comprises: a base; a support rod assembly connected to the base; the needle clamping device is arranged on an upper portion of the support rod assembly.
 10. The leg support device according to claim 9, wherein the support rod assembly comprises a first support rod assembly and a second support rod assembly respectively disposed on two sides of the base, and at least one of the first support rod assembly and the second support rod assembly is detachably connected to the base.
 11. The leg support device according to claim 9, wherein the position of the support rod assembly and the base relative to each other along a length direction of a side of the base is adjustable.
-