

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415041
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Brereton; Simon Francis et al.

Auto-injector methods

Abstract

An auto-injector for administering a dose of a liquid medicament (M) is present having a tubular chassis telescopable in a tubular case, a carrier subassembly comprising a tubular carrier slidably arranged relative to the chassis inside the case, where the carrier is adapted to contain a syringe with a hollow injection needle. The injector also has a drive spring and a plunger for forwarding load of the drive spring to a stopper of the syringe, wherein the syringe is lockable for joint axial translation with the carrier. A control spring is arranged around the carrier for translating the carrier in a proximal direction (P) for insertion of the needle through the chassis into an injection site.

Inventors: Brereton; Simon Francis (Cambridge, GB), Kemp; Thomas (Ashwell, GB), Burnell; Rosie (Cambridge, GB), Ekman; Matthew (Cheshire, GB)

Applicant: Sanofi-Aventis Deutschland GMBH (Frankfurt am Main, DE)

Family ID: 1000008819439

Assignee: Sanofi-Aventis Deutschland GMBH (Frankfurt am Main, DE)

Appl. No.: 19/018513

Filed: January 13, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250144309 A1	May. 08, 2025

Foreign Application Priority Data

EP	11155040	Feb. 18, 2011
----	----------	---------------

Related U.S. Application Data

continuation parent-doc US 18487215 20231016 PENDING child-doc US 18755814
continuation parent-doc US 17126962 20201218 US 11819670 20231121 child-doc US 18487215
continuation parent-doc US 15897872 20180215 US 10894132 20210119 child-doc US 17126962
continuation parent-doc US 13983809 US 9925344 20180327 WO PCT/EP2012/052647 20120216
child-doc US 15897872
division parent-doc US 18755814 20240627 US 12214171 child-doc US 19018513

Publication Classification

Int. Cl.: **A61M5/315** (20060101); **A61M5/20** (20060101); **A61M5/32** (20060101); **A61M5/46** (20060101)

U.S. Cl.:

CPC **A61M5/31501** (20130101); **A61M5/20** (20130101); **A61M5/2033** (20130101); **A61M5/3157** (20130101); **A61M5/3158** (20130101); **A61M5/322** (20130101); **A61M5/326** (20130101); **A61M5/46** (20130101); A61M2005/206 (20130101); A61M2005/208 (20130101); A61M2205/581 (20130101); A61M2205/582 (20130101); A61M2205/583 (20130101)

Field of Classification Search

CPC: A61M (5/31501); A61M (5/20); A61M (5/2033); A61M (5/3157); A61M (5/3158); A61M (5/326); A61M (5/46); A61M (2005/206); A61M (2005/208); A61M (2205/581); A61M (2205/582); A61M (2205/583)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3656480	12/1971	Rubricius	N/A	N/A
3712301	12/1972	Sarnoff	N/A	N/A
RE32922	12/1988	Levin et al.	N/A	N/A
4964866	12/1989	Szwarc	N/A	N/A
5042977	12/1990	Bechtold et al.	N/A	N/A
5137516	12/1991	Rand	N/A	N/A
5300030	12/1993	Crossman et al.	N/A	N/A
5320609	12/1993	Haber	N/A	N/A
5358489	12/1993	Wyrick	604/157	A61M 5/2033
5391157	12/1994	Harris et al.	N/A	N/A
5478316	12/1994	Bitdinger et al.	N/A	N/A
5480387	12/1995	Gabriel et al.	N/A	N/A
5540664	12/1995	Wyrick	N/A	N/A
5559309	12/1995	Zabler et al.	N/A	N/A
5599309	12/1996	Marshall et al.	N/A	N/A
5681291	12/1996	Galli	N/A	N/A
5746215	12/1997	Manjarrez	N/A	N/A

5779677	12/1997	Frezza	N/A	N/A
5961495	12/1998	Walters et al.	N/A	N/A
6004297	12/1998	Steenfeldt-Jensen et al.	N/A	N/A
6159181	12/1999	Crossman et al.	N/A	N/A
6221046	12/2000	Burroughs	N/A	N/A
6270479	12/2000	Bergens et al.	N/A	N/A
6277099	12/2000	Strowe et al.	N/A	N/A
6371939	12/2001	Bergens et al.	N/A	N/A
6454743	12/2001	Weber	N/A	N/A
6620137	12/2002	Kirchhofer et al.	N/A	N/A
6743205	12/2003	Nolan, Jr. et al.	N/A	N/A
7195616	12/2006	Diller et al.	N/A	N/A
7291132	12/2006	DeRuntz et al.	N/A	N/A
7297135	12/2006	Jeffrey	N/A	N/A
7341575	12/2007	Rice et al.	N/A	N/A
7361160	12/2007	Hommann et al.	N/A	N/A
7407494	12/2007	Bostrom	N/A	N/A
7442185	12/2007	Amark et al.	N/A	N/A
7597685	12/2008	Olson	N/A	N/A
7678085	12/2009	Graf	N/A	N/A
7717877	12/2009	Lavi et al.	N/A	N/A
7749195	12/2009	Hommann	N/A	N/A
7758550	12/2009	Bollenbach	N/A	N/A
7771398	12/2009	Knight et al.	N/A	N/A
7901377	12/2010	Harrison et al.	N/A	N/A
7918824	12/2010	Bishop et al.	N/A	N/A
7976494	12/2010	Kohlbrenner et al.	N/A	N/A
8038649	12/2010	Kronestedt	N/A	N/A
8048037	12/2010	Kohlbrenner et al.	N/A	N/A
8062255	12/2010	Brunnberg et al.	N/A	N/A
8083711	12/2010	Enggaard	N/A	N/A
8308695	12/2011	Laiosa	N/A	N/A
8313465	12/2011	Harrison	N/A	N/A
8323238	12/2011	Cronenberg et al.	N/A	N/A
8357125	12/2012	Grunhut et al.	N/A	N/A
8361025	12/2012	Lawlis et al.	N/A	N/A
8366680	12/2012	Raab	N/A	N/A
8376993	12/2012	Cox et al.	N/A	N/A
8376997	12/2012	Hogdahl et al.	N/A	N/A
8403883	12/2012	Fayyaz et al.	N/A	N/A
8409138	12/2012	James et al.	N/A	N/A
8409141	12/2012	Johansen et al.	N/A	N/A
8409148	12/2012	Fiechter et al.	N/A	N/A
8439864	12/2012	Galbraith et al.	N/A	N/A
8491538	12/2012	Kohlbrenner et al.	N/A	N/A
8568359	12/2012	Carrel et al.	N/A	N/A
8617109	12/2012	Kronestedt et al.	N/A	N/A
8617124	12/2012	Wieselblad et al.	N/A	N/A
8632507	12/2013	Bartha	N/A	N/A

8647299	12/2013	Stamp	N/A	N/A
8684969	12/2013	Moller et al.	N/A	N/A
8708973	12/2013	Holmqvist	N/A	N/A
8734394	12/2013	Adams et al.	N/A	N/A
8734402	12/2013	Sharp et al.	N/A	N/A
8758292	12/2013	Tschirren et al.	N/A	N/A
8808250	12/2013	Ekman et al.	N/A	N/A
8808251	12/2013	Raab et al.	N/A	N/A
8821451	12/2013	Daniel	N/A	N/A
8834431	12/2013	Kohlbrener et al.	N/A	N/A
8840591	12/2013	Raab et al.	N/A	N/A
8882723	12/2013	Smith et al.	N/A	N/A
8911411	12/2013	Nielsen	N/A	N/A
8939934	12/2014	Brereton et al.	N/A	N/A
8945063	12/2014	Wotton et al.	N/A	N/A
8956331	12/2014	Johansen et al.	N/A	N/A
8961473	12/2014	Heald	N/A	N/A
8968256	12/2014	Raab	N/A	N/A
8968258	12/2014	Nzike et al.	N/A	N/A
8992484	12/2014	Radmer et al.	N/A	N/A
8992487	12/2014	Eich et al.	N/A	N/A
9005160	12/2014	Karlsson et al.	N/A	N/A
9011386	12/2014	Kronstedt et al.	N/A	N/A
9011387	12/2014	Ekman et al.	N/A	N/A
9022991	12/2014	Moeller	N/A	N/A
9022994	12/2014	Moser et al.	N/A	N/A
9044548	12/2014	Miller et al.	N/A	N/A
9044553	12/2014	James et al.	N/A	N/A
9057369	12/2014	Kohlbrener et al.	N/A	N/A
9061104	12/2014	Daniel	N/A	N/A
9067024	12/2014	Roberts et al.	N/A	N/A
9089652	12/2014	Nzike et al.	N/A	N/A
9108002	12/2014	Markussen	N/A	N/A
9125988	12/2014	Karlsson	N/A	N/A
9132235	12/2014	Holmqvist	N/A	N/A
9155844	12/2014	Brereton et al.	N/A	N/A
9199038	12/2014	Daniel	N/A	N/A
9205199	12/2014	Kemp et al.	N/A	N/A
9216256	12/2014	Olson et al.	N/A	N/A
9233213	12/2015	Olson et al.	N/A	N/A
9233214	12/2015	Kemp et al.	N/A	N/A
9233215	12/2015	Hourmand et al.	N/A	N/A
9242044	12/2015	Markussen	N/A	N/A
9242047	12/2015	Brereton et al.	N/A	N/A
9272098	12/2015	Hourmand et al.	N/A	N/A
9283326	12/2015	Kemp et al.	N/A	N/A
9283327	12/2015	Hourmand et al.	N/A	N/A
9283328	12/2015	Dasbach	N/A	N/A
9308327	12/2015	Marshall et al.	N/A	N/A
9333304	12/2015	Brereton et al.	N/A	N/A

9339607	12/2015	Langley et al.	N/A	N/A
9352088	12/2015	Ekman et al.	N/A	N/A
9352090	12/2015	Brereton et al.	N/A	N/A
9358345	12/2015	Brereton et al.	N/A	N/A
9358351	12/2015	Ekman et al.	N/A	N/A
9393368	12/2015	Nzike et al.	N/A	N/A
9402957	12/2015	Adams et al.	N/A	N/A
9408976	12/2015	Olson et al.	N/A	N/A
9408977	12/2015	Butler et al.	N/A	N/A
9408979	12/2015	Veasey et al.	N/A	N/A
9415165	12/2015	Cowe	N/A	N/A
9421336	12/2015	Ekman et al.	N/A	N/A
9427525	12/2015	Barrow-Williams et al.	N/A	N/A
9446196	12/2015	Hourmand et al.	N/A	N/A
9446201	12/2015	Holmqvist	N/A	N/A
9457149	12/2015	Kemp et al.	N/A	N/A
9457152	12/2015	Raab et al.	N/A	N/A
9492622	12/2015	Brereton et al.	N/A	N/A
9604003	12/2016	Brereton et al.	N/A	N/A
9623181	12/2016	Brereton et al.	N/A	N/A
9636459	12/2016	Brereton et al.	N/A	N/A
9656021	12/2016	Brereton et al.	N/A	N/A
9662452	12/2016	Daniel	N/A	N/A
9687607	12/2016	Brereton et al.	N/A	N/A
9724472	12/2016	Hourmand et al.	N/A	N/A
9789225	12/2016	Bagga et al.	N/A	N/A
9789255	12/2016	Brereton et al.	N/A	N/A
9867940	12/2017	Holmqvist et al.	N/A	N/A
9872961	12/2017	Fourt et al.	N/A	N/A
9950123	12/2017	Brereton et al.	N/A	N/A
10118001	12/2017	Fourt et al.	N/A	N/A
10314981	12/2018	Sampson et al.	N/A	N/A
10350362	12/2018	Dennis, Jr. et al.	N/A	N/A
10363377	12/2018	Atterbury et al.	N/A	N/A
10376642	12/2018	Brereton et al.	N/A	N/A
10384015	12/2018	Brereton et al.	N/A	N/A
10384016	12/2018	Brereton et al.	N/A	N/A
10413668	12/2018	Brereton et al.	N/A	N/A
10420898	12/2018	Daniel	N/A	N/A
10471210	12/2018	Brereton et al.	N/A	N/A
10518041	12/2018	Brereton et al.	N/A	N/A
10556064	12/2019	Brereton et al.	N/A	N/A
10569019	12/2019	Hirschel et al.	N/A	N/A
RE47903	12/2019	Hourmand et al.	N/A	N/A
10729853	12/2019	Hourmand et al.	N/A	N/A
10799647	12/2019	Hostettler et al.	N/A	N/A
10960142	12/2020	Brereton et al.	N/A	N/A
RE48593	12/2020	Hourmand et al.	N/A	N/A
11298462	12/2021	Atterbury et al.	N/A	N/A

11383044	12/2021	Tschirren et al.	N/A	N/A
11400217	12/2021	Hourmand et al.	N/A	N/A
11452821	12/2021	Lafever et al.	N/A	N/A
11458252	12/2021	Hourmand et al.	N/A	N/A
11471601	12/2021	Hourmand et al.	N/A	N/A
11484655	12/2021	Brereton et al.	N/A	N/A
11559630	12/2022	Brereton et al.	N/A	N/A
11607495	12/2022	Hourmand et al.	N/A	N/A
11612691	12/2022	Hourmand et al.	N/A	N/A
11833331	12/2022	Hourmand et al.	N/A	N/A
12208247	12/2024	Brereton et al.	N/A	N/A
12208248	12/2024	Brereton et al.	N/A	N/A
12214170	12/2024	Brereton et al.	N/A	N/A
12214171	12/2024	Brereton et al.	N/A	N/A
12214172	12/2024	Brereton et al.	N/A	N/A
12214176	12/2024	Brereton et al.	N/A	N/A
12220563	12/2024	Brereton et al.	N/A	N/A
12220564	12/2024	Brereton et al.	N/A	N/A
12220567	12/2024	Brereton et al.	N/A	N/A
2001/0005781	12/2000	Bergens	N/A	N/A
2002/0007154	12/2001	Hansen et al.	N/A	N/A
2002/0009520	12/2001	Clayton et al.	N/A	N/A
2002/0095120	12/2001	Larsen et al.	N/A	N/A
2002/0123675	12/2001	Trautman et al.	N/A	N/A
2002/0133122	12/2001	Giambattista et al.	N/A	N/A
2002/0161386	12/2001	Halseth et al.	N/A	N/A
2003/0105430	12/2002	Lavi et al.	N/A	N/A
2003/0212362	12/2002	Roser	N/A	N/A
2004/0039336	12/2003	Amark et al.	N/A	N/A
2004/0097883	12/2003	Roe	N/A	N/A
2005/0027255	12/2004	Lavi et al.	N/A	N/A
2005/0101919	12/2004	Brunnberg	N/A	N/A
2005/0165363	12/2004	Judson	604/209	A61M 5/31551
2005/0222539	12/2004	Gonzales et al.	N/A	N/A
2005/0272551	12/2004	Oates et al.	N/A	N/A
2005/0273061	12/2004	Hommann et al.	N/A	N/A
2005/0277885	12/2004	Scherer	N/A	N/A
2006/0153693	12/2005	Fiechter et al.	N/A	N/A
2006/0224124	12/2005	Scherer	N/A	N/A
2006/0258990	12/2005	Weber	N/A	N/A
2006/0270984	12/2005	Hommann	N/A	N/A
2006/0270985	12/2005	Hommann et al.	N/A	N/A
2006/0270986	12/2005	Hommann et al.	N/A	N/A
2006/0287630	12/2005	Hommann	N/A	N/A
2007/0005021	12/2006	Kohlbrenner et al.	N/A	N/A
2007/0027430	12/2006	Hommann	N/A	N/A
2007/0112310	12/2006	Lavi et al.	N/A	N/A
2007/0129686	12/2006	Daily et al.	N/A	N/A
2007/0197975	12/2006	Burren et al.	N/A	N/A

2008/0009807	12/2007	Hommann	N/A	N/A
2008/0015520	12/2007	Hommann et al.	N/A	N/A
2008/0051713	12/2007	Kohlbrenner et al.	N/A	N/A
2008/0210890	12/2007	Fago	N/A	N/A
2008/0228143	12/2007	Stamp	N/A	N/A
2008/0228147	12/2007	David-Hegerich et al.	N/A	N/A
2008/0262427	12/2007	Hommann	N/A	N/A
2008/0262438	12/2007	Bollenbach et al.	N/A	N/A
2008/0262443	12/2007	Hommann	N/A	N/A
2008/0269692	12/2007	James et al.	N/A	N/A
2008/0281271	12/2007	Griffiths et al.	N/A	N/A
2008/0312591	12/2007	Harrison	N/A	N/A
2008/0312606	12/2007	Harrison et al.	N/A	N/A
2009/0012471	12/2008	Harrison	N/A	N/A
2009/0012479	12/2008	Moller et al.	N/A	N/A
2009/0088688	12/2008	Barrow-Williams et al.	N/A	N/A
2009/0131875	12/2008	Green	N/A	N/A
2009/0259178	12/2008	Brechbuehler et al.	N/A	N/A
2009/0270804	12/2008	Mesa et al.	N/A	N/A
2009/0292246	12/2008	Slate et al.	N/A	N/A
2009/0312705	12/2008	Grunhut et al.	N/A	N/A
2010/0016795	12/2009	McLoughlin	N/A	N/A
2010/0049125	12/2009	James et al.	N/A	N/A
2010/0087799	12/2009	Galbraith et al.	N/A	N/A
2010/0137798	12/2009	Streit et al.	N/A	N/A
2010/0137801	12/2009	Streit et al.	N/A	N/A
2010/0185178	12/2009	Sharp et al.	N/A	N/A
2010/0191217	12/2009	Hommann	N/A	N/A
2010/0256570	12/2009	Maritan	N/A	N/A
2010/0262083	12/2009	Grunhut et al.	N/A	N/A
2010/0268170	12/2009	Carrel et al.	N/A	N/A
2010/0286612	12/2009	Cirillo et al.	N/A	N/A
2010/0292653	12/2009	Maritan	N/A	N/A
2010/0298780	12/2009	Laiosa	N/A	N/A
2010/0312195	12/2009	Johansen et al.	N/A	N/A
2011/0034878	12/2010	Radmer et al.	N/A	N/A
2011/0034902	12/2010	Markussen	N/A	N/A
2011/0054414	12/2010	Shang	604/218	A61M 5/31578
2011/0077599	12/2010	Wozencroft	N/A	N/A
2011/0092915	12/2010	Olson et al.	N/A	N/A
2011/0218500	12/2010	Grunhut et al.	N/A	N/A
2011/0270161	12/2010	Harrison et al.	N/A	N/A
2012/0010575	12/2011	Jones et al.	N/A	N/A
2012/0041387	12/2011	Bruggemann et al.	N/A	N/A
2012/0053528	12/2011	Bollenbach et al.	N/A	N/A
2012/0116319	12/2011	Grunhut et al.	N/A	N/A
2012/0172817	12/2011	Bruggemann et al.	N/A	N/A

2012/0184917	12/2011	Bom et al.	N/A	N/A
2012/0209192	12/2011	Alexandersson	N/A	N/A
2012/0253274	12/2011	Karlsson et al.	N/A	N/A
2012/0310156	12/2011	Karlsson et al.	N/A	N/A
2013/0035642	12/2012	Daniel	N/A	N/A
2013/0035647	12/2012	Veasey et al.	N/A	N/A
2013/0041328	12/2012	Daniel	N/A	N/A
2013/0123710	12/2012	Ekman et al.	N/A	N/A
2013/0190722	12/2012	Kemp et al.	N/A	N/A
2013/0261556	12/2012	Jones et al.	N/A	N/A
2013/0274662	12/2012	Hourmand et al.	N/A	N/A
2013/0274666	12/2012	Brereton et al.	N/A	N/A
2013/0274677	12/2012	Ekman et al.	N/A	N/A
2013/0289525	12/2012	Kemp et al.	N/A	N/A
2013/0310739	12/2012	Galbraith et al.	N/A	N/A
2013/0310744	12/2012	Brereton et al.	N/A	N/A
2013/0310745	12/2012	Latham et al.	N/A	N/A
2013/0310757	12/2012	Brereton et al.	N/A	N/A
2013/0317427	12/2012	Brereton et al.	N/A	N/A
2013/0317428	12/2012	Brereton et al.	N/A	N/A
2013/0317479	12/2012	Brereton	N/A	N/A
2013/0324924	12/2012	Brereton et al.	N/A	N/A
2013/0324925	12/2012	Brereton et al.	N/A	N/A
2013/0324935	12/2012	Brereton et al.	N/A	N/A
2013/0324938	12/2012	Brereton et al.	N/A	N/A
2013/0324939	12/2012	Brereton et al.	N/A	N/A
2013/0345643	12/2012	Hourmand et al.	N/A	N/A
2015/0273157	12/2014	Kohlbrenner et al.	N/A	N/A
2016/0089498	12/2015	Daniel	N/A	N/A
2016/0106923	12/2015	Brereton et al.	N/A	N/A
2016/0129194	12/2015	Brereton et al.	N/A	N/A
2017/0197036	12/2016	Brereton et al.	N/A	N/A
2017/0216526	12/2016	Brereton et al.	N/A	N/A
2017/0246397	12/2016	Brereton et al.	N/A	N/A
2017/0246398	12/2016	Brereton et al.	N/A	N/A
2017/0326298	12/2016	Hourmand et al.	N/A	N/A
2018/0001026	12/2017	Brereton et al.	N/A	N/A
2018/0064875	12/2017	Holmqvist	N/A	N/A
2018/0200445	12/2017	Brereton et al.	N/A	N/A
2019/0358405	12/2018	Brereton et al.	N/A	N/A
2019/0374717	12/2018	Swanson et al.	N/A	N/A
2020/0078524	12/2019	Brereton et al.	N/A	N/A
2020/0316298	12/2019	Hourmand et al.	N/A	N/A
2021/0213206	12/2020	Brereton et al.	N/A	N/A
2022/0211947	12/2021	Hourmand et al.	N/A	N/A
2022/0218906	12/2021	Hourmand et al.	N/A	N/A
2022/0313915	12/2021	Hourmand et al.	N/A	N/A
2023/0019806	12/2022	Hourmand et al.	N/A	N/A
2023/0082328	12/2022	Brereton et al.	N/A	N/A
2023/0086760	12/2022	Hourmand et al.	N/A	N/A

2023/0140568	12/2022	Brereton et al.	N/A	N/A
2024/0148979	12/2023	Brereton et al.	N/A	N/A
2024/0226438	12/2023	Brereton et al.	N/A	N/A
2024/0226450	12/2023	Brereton et al.	N/A	N/A
2024/0226451	12/2023	Brereton et al.	N/A	N/A
2024/0342385	12/2023	Brereton et al.	N/A	N/A
2024/0342386	12/2023	Brereton et al.	N/A	N/A
2024/0342387	12/2023	Brereton et al.	N/A	N/A
2024/0350742	12/2023	Brereton et al.	N/A	N/A
2025/0135117	12/2024	Brereton et al.	N/A	N/A
2025/0135118	12/2024	Brereton et al.	N/A	N/A
2025/0144303	12/2024	Brereton et al.	N/A	N/A
2025/0144304	12/2024	Brereton et al.	N/A	N/A
2025/0144305	12/2024	Brereton et al.	N/A	N/A
2025/0144306	12/2024	Brereton et al.	N/A	N/A
2025/0144307	12/2024	Brereton et al.	N/A	N/A
2025/0144308	12/2024	Brereton et al.	N/A	N/A
2025/0144310	12/2024	Brereton et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
705345	12/2012	CH	N/A
705992	12/2012	CH	N/A
1849148	12/2005	CN	N/A
1901957	12/2006	CN	N/A
101264360	12/2007	CN	N/A
102665801	12/2009	CN	N/A
101854965	12/2009	CN	N/A
101868272	12/2009	CN	N/A
102821801	12/2010	CN	N/A
19819409	12/1998	DE	N/A
202007000578	12/2006	DE	N/A
102005052502	12/2006	DE	N/A
102007013836	12/2007	DE	N/A
0308192	12/1988	EP	N/A
0382015	12/1989	EP	N/A
0666084	12/1994	EP	N/A
0824923	12/1997	EP	N/A
0693946	12/2000	EP	N/A
0991441	12/2002	EP	N/A
1932558	12/2007	EP	N/A
1997852	12/2007	EP	N/A
2399634	12/2010	EP	N/A
2468334	12/2011	EP	N/A
2468335	12/2011	EP	N/A
2675510	12/2012	EP	N/A
2675511	12/2012	EP	N/A
2675502	12/2014	EP	N/A
3381490	12/2019	EP	N/A

2899482	12/2006	FR	N/A
2905273	12/2007	FR	N/A
2438592	12/2006	GB	N/A
2443606	12/2007	GB	N/A
2451663	12/2008	GB	N/A
2467637	12/2009	GB	N/A
2469672	12/2009	GB	N/A
H11-503637	12/1989	JP	N/A
H08-505543	12/1995	JP	N/A
H09-507416	12/1996	JP	N/A
H11-347121	12/1998	JP	N/A
2001-521792	12/2000	JP	N/A
2002-528182	12/2001	JP	N/A
2005-177503	12/2004	JP	N/A
2006-507061	12/2005	JP	N/A
2006-526446	12/2005	JP	N/A
2007-500530	12/2006	JP	N/A
2007-504867	12/2006	JP	N/A
2007-509659	12/2006	JP	N/A
2007-313372	12/2006	JP	N/A
2008-528144	12/2007	JP	N/A
2008-521482	12/2007	JP	N/A
2008-229344	12/2007	JP	N/A
2009-533124	12/2008	JP	N/A
2010-501295	12/2009	JP	N/A
2010-520786	12/2009	JP	N/A
2010-523183	12/2009	JP	N/A
2010-532243	12/2009	JP	N/A
2010-535564	12/2009	JP	N/A
4578484	12/2009	JP	N/A
2010-540057	12/2009	JP	N/A
2010-540059	12/2009	JP	N/A
2012-504008	12/2011	JP	N/A
5180956	12/2012	JP	N/A
2108116	12/1997	RU	N/A
2203688	12/2002	RU	N/A
WO 1994/011041	12/1993	WO	N/A
WO 1994/021316	12/1993	WO	N/A
WO 1996/032974	12/1995	WO	N/A
WO 1999/022790	12/1998	WO	N/A
WO 1999/022792	12/1998	WO	N/A
WO 1999/053979	12/1998	WO	N/A
WO 2000/024441	12/1999	WO	N/A
WO 2000/035060	12/1999	WO	N/A
WO 2002/047746	12/2001	WO	N/A
WO 2003/062672	12/2002	WO	N/A
WO 2004/108194	12/2003	WO	N/A
WO 2005/070481	12/2004	WO	N/A
WO 2005/097238	12/2004	WO	N/A
WO 2005/115507	12/2004	WO	N/A

WO 2005/115508	12/2005	WO	N/A
WO 2006/052737	12/2005	WO	N/A
WO 2006/057604	12/2005	WO	N/A
WO 2006/079481	12/2005	WO	N/A
WO 2006/111862	12/2005	WO	N/A
WO 2007/002052	12/2006	WO	N/A
WO 2007/083115	12/2006	WO	N/A
WO 2007/099044	12/2006	WO	N/A
WO 2007/129106	12/2006	WO	N/A
WO 2007/129324	12/2006	WO	N/A
WO 2007/132353	12/2006	WO	N/A
WO 2008/029280	12/2007	WO	N/A
WO 2008/059385	12/2007	WO	N/A
WO 2008/112472	12/2007	WO	N/A
WO 2008/116688	12/2007	WO	N/A
WO 2009/007305	12/2008	WO	N/A
WO 2009/022132	12/2008	WO	N/A
WO 2009/040602	12/2008	WO	N/A
WO 2009/040605	12/2008	WO	N/A
WO 2009/040607	12/2008	WO	N/A
WO 2009/040672	12/2008	WO	N/A
WO 2009/062508	12/2008	WO	N/A
WO 2009/095701	12/2008	WO	N/A
WO 2009/141650	12/2008	WO	N/A
WO 2010/035056	12/2009	WO	N/A
WO 2010/035057	12/2009	WO	N/A
WO 2010/035059	12/2009	WO	N/A
WO 2010/035060	12/2009	WO	N/A
WO 2010/063707	12/2009	WO	N/A
WO 2010/122323	12/2009	WO	N/A
WO 2010/136077	12/2009	WO	N/A
WO 2011/012903	12/2010	WO	N/A
WO 2011/109205	12/2010	WO	N/A
WO 2011/111006	12/2010	WO	N/A
WO 2011/117592	12/2010	WO	N/A
WO 2011/123024	12/2010	WO	N/A
WO 2011/126439	12/2010	WO	N/A
WO 2012/000939	12/2011	WO	N/A
WO 2012/045350	12/2011	WO	N/A
WO 2012/085021	12/2011	WO	N/A
WO 2012/085024	12/2011	WO	N/A
WO 2012/110577	12/2011	WO	N/A
WO 2013/016832	12/2012	WO	N/A
WO 2019/074788	12/2018	WO	N/A
WO 2020/190529	12/2019	WO	N/A
WO 2021/008839	12/2020	WO	N/A
WO 2021/160540	12/2020	WO	N/A
WO 2021/197804	12/2020	WO	N/A
WO 2022/069617	12/2021	WO	N/A
WO 2022/184388	12/2021	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability in International Appln. No. PCT/EP2011/073502, mailed on Jul. 4, 2013, 8 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052639, mailed on Aug. 21, 2013, 9 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052640, mailed on Aug. 21, 2013, 6 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052642, mailed on Aug. 21, 2013, 7 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052643, mailed on Aug. 21, 2013, 8 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052645, mailed on Aug. 21, 2013, 6 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052646, mailed on Aug. 21, 2013, 6 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052647, mailed on Aug. 21, 2013, 8 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052648, mailed on Aug. 21, 2013, 6 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052649, mailed on Aug. 21, 2013, 8 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052652, mailed on Aug. 21, 2013, 7 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/052653, mailed on Aug. 21, 2013, 6 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2011/073502, mailed on Mar. 26, 2012, 9 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052639, mailed on May 11, 2012, 10 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052640, mailed on May 14, 2012, 8 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052642, mailed on May 18, 2012, 11 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052645, mailed on May 14, 2012, 8 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052646, mailed on Nov. 5, 2012, 9 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052647, mailed on May 8, 2012, 10 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052648, mailed May 18, 2012, 8 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/052649, mailed on May 14, 2012, 10 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2012/059758, mailed on Aug. 13, 2012, 12 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/EP2013/052653, mailed on May 11, 2012, 10 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/GB2010/050619, mailed on Sep. 6, 2011, 9 pages. cited by applicant

International Search Report in International Appln. No. PCT/EP2012/052643, mailed on Apr. 25, 2012, 3 pages. cited by applicant
International Search Report in International Appln. No. PCT/EP2012/052652, mailed on May 10, 2012, 4 pages. cited by applicant
International Search Report in International Appln. No. PCT/EP2012/052653, mailed on May 11, 2012, 3 pages. cited by applicant
International Search Report in International Appln. No. PCT/SE1999/001922, mailed on Mar. 28, 2000, 6 pages. cited by applicant
Merriam-Webster Dictionary, 2015, Simple Definition, 1 page. cited by applicant
U.S. Appl. No. 14/000,113, filed Aug. 16, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 14/879,805, filed Oct. 9, 2015, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/983,808, filed Aug. 6, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 15/480,026, filed Apr. 5, 2017, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/985,253, filed Aug. 13, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 14/982,555, filed Dec. 29, 2015, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 15/919,389, filed Mar. 13, 2018, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 17/213,115, filed Mar. 25, 2021, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/983,805, filed Aug. 6, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 16/538,969, filed Aug. 13, 2019, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 18/145,564, filed Dec. 22, 2022, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/985,520, filed Aug. 14, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/984,849, filed Aug. 10, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 15/433,523, filed Feb. 15, 2017, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/985,021, filed Aug. 12, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 15/452,346, filed Mar. 7, 2017, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 16/667,008, filed Oct. 29, 2019, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 17/935,237, filed Sep. 26, 2022, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/983,810, filed Aug. 6, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 15/706,131, filed Sep. 15, 2017, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/983,807, filed Aug. 6, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 13/983,811, filed Aug. 6, 2013, Simon Francis Brereton. cited by applicant
U.S. Appl. No. 15/471,926, filed Mar. 28, 2017, Simon Francis Brereton. cited by applicant

Primary Examiner: Ponton; James D

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. patent application Ser. No. 18/755,814, filed Jun. 27, 2024, which is a continuation of U.S. patent application Ser. No. 18/487,215, filed Oct. 16, 2023, which is a continuation of U.S. patent application Ser. No. 17/126,962, filed Dec. 18, 2020, now U.S. Pat. No. 11,819,670, which is a continuation of U.S. patent application Ser. No. 15/897,872, filed Feb. 15, 2018, now U.S. Pat. No. 10,894,132, which is a continuation of U.S. patent application Ser. No. 13/983,809, filed Aug. 6, 2013, now U.S. Pat. No. 9,925,344, which is a U.S. National Phase Application pursuant to 35 U.S.C. § 371 of International Application No. PCT/EP2012/052647 filed Feb. 16, 2012, which claims priority to European Patent Application No. 11155040.6 filed Feb. 18, 2011. The entire

disclosure contents of these applications are herewith incorporated by reference into the present application.

TECHNICAL FIELD

(1) The invention relates to an auto-injector for administering a dose of a liquid medicament.

BACKGROUND

(2) Administering an injection is a process which presents a number of risks and challenges for users and healthcare professionals, both mental and physical.

(3) Injection devices (i.e. devices capable of delivering medicaments from a medication container) typically fall into two categories—manual devices and auto-injectors.

(4) In a manual device—the user must provide the mechanical energy to drive the fluid through the needle. This is typically done by some form of button/plunger that has to be continuously pressed by the user during the injection. There are numerous disadvantages to the user from this approach. If the user stops pressing the button/plunger then the injection will also stop. This means that the user can deliver an underdose if the device is not used properly (i.e. the plunger is not fully pressed to its end position). Injection forces may be too high for the user, in particular if the patient is elderly or has dexterity problems.

(5) The extension of the button/plunger may be too great. Thus it can be inconvenient for the user to reach a fully extended button. The combination of injection force and button extension can cause trembling/shaking of the hand which in turn increases discomfort as the inserted needle moves.

(6) Auto-injector devices aim to make self-administration of injected therapies easier for patients. Current therapies delivered by means of self-administered injections include drugs for diabetes (both insulin and newer GLP-1 class drugs), migraine, hormone therapies, anticoagulants etc.

(7) Auto-injectors are devices which completely or partially replace activities involved in parenteral drug delivery from standard syringes. These activities may include removal of a protective syringe cap, insertion of a needle into a patient's skin, injection of the medicament, removal of the needle, shielding of the needle and preventing reuse of the device. This overcomes many of the disadvantages of manual devices. Injection forces/button extension, hand-shaking and the likelihood of delivering an incomplete dose are reduced. Triggering may be performed by numerous means, for example a trigger button or the action of the needle reaching its injection depth. In some devices the energy to deliver the fluid is provided by a spring.

(8) US 2002/0095120 A1 discloses an automatic injection device which automatically injects a pre-measured quantity of fluid medicine when a tension spring is released. The tension spring moves an ampoule and the injection needle from a storage position to a deployed position when it is released. The content of the ampoule is thereafter expelled by the tension spring forcing a piston forward inside the ampoule. After the fluid medicine has been injected, torsion stored in the tension spring is released and the injection needle is automatically retracted back to its original storage position.

(9) High viscosity medicaments require high forces for expelling them through the relatively thin injection needle. To achieve these forces strong drive springs are needed. This can lead to a high impact felt by the user when inserting the needle into the skin and to high forces felt by the user when triggering the injection.

SUMMARY

(10) It is an object of the present invention to provide an improved auto-injector.

(11) The object is achieved by an auto-injector according to claim 1.

(12) Preferred embodiments of the invention are given in the dependent claims.

(13) In the context of this specification the term proximal refers to the direction pointing towards the patient during an injection while the term distal refers to the opposite direction pointing away from the patient. The term inwards refers to a radial direction pointing towards a longitudinal axis of the auto-injector whereas the term outwards refers to the opposite direction radially pointing away from the longitudinal axis.

(14) According to the invention an auto-injector for administering a dose of a liquid medicament, comprises: a tubular chassis telescopable in a tubular case, a carrier subassembly comprising a tubular carrier slidably arranged relative to the chassis inside the case, the carrier adapted to contain a syringe with a hollow injection needle, a drive spring and a plunger for forwarding load of the drive spring to a stopper of the syringe, wherein the syringe is lockable for joint axial translation with the carrier, a control spring arranged around the carrier for translating the carrier in a proximal direction for insertion of the needle through the chassis into an injection site.

(15) The control spring is arranged to bias the case against the chassis in a distal direction so as to extend the chassis out of a proximal end of the case. An insertion depth of the needle is defined by the carrier abutting the chassis in a predefined position. The case is arranged to release or allow release of the control spring for needle insertion on translation of the case in the proximal direction relative to the chassis against the bias into an advanced position.

(16) In the context of this specification the chassis is generally considered as being fixed in position so motion of other components is described relative to the chassis.

(17) The needle insertion depth is defined by the carrier relative to the chassis not relative to the case, so if the user flinches or fails to hold the auto-injector hard against the injection site, only the case will move in the distal direction while the injection depth remains constant as the chassis is still being pressed against the injection site by the control spring. Maintaining the insertion depth is thought to avoid unnecessary pain to a patient as opposed to the needle being translated back and forth if the user flinches, e.g. due to tremor.

(18) The carrier may be arranged to be translated in the distal direction for retracting the inserted needle when the case is moved in the distal direction relative to the chassis by a predefined distance. Retraction may be achieved by the control spring being released from the carrier at its proximal end and switched to the chassis or case instead and by the distal end of the control spring being switched from the case to the carrier. As long as the case motion does not exceed the predefined distance the case does not yet switch the control spring for needle retraction, i.e. the user may move the case below this distance without triggering retraction or altering the insertion depth.

(19) The auto-injector may furthermore comprise: a trigger button arranged distally or laterally in or on the case, a needle insertion control mechanism for coupling a proximal end of the control spring to either the carrier for advancing it for needle insertion or to the chassis for needle retraction depending on the relative axial position of the carrier and the chassis, a plunger release mechanism arranged for releasing the plunger for injection when the carrier has at least almost reached an injection depth during needle insertion, a detent mechanism arranged for coupling the chassis to the carrier for joint axial translation relative to the case, wherein the detent mechanism is arranged to decouple the chassis from the carrier upon actuation of the trigger button thus allowing the carrier to move relative to the chassis so as to cause the needle insertion control mechanism to switch the proximal end of the control spring to the carrier for needle insertion, a syringe retraction control mechanism arranged for coupling a distal end of the control spring to either the carrier for needle retraction or to the case otherwise.

(20) The carrier subassembly with the integrated drive spring allows for employing a strong drive spring without any impact on the user when triggering the auto-injector or during needle insertion since these actions are achieved or opposed by the control spring which can be specified considerably weaker than the drive spring. This allows for delivering highly viscous medicaments.

(21) There are a number of significant benefits of separating the functions between the drive spring and the control spring in this way. The auto-injector is always needle safe, i.e. the needle can be retracted before the injection is complete. The reliability of the auto-injector is improved as the components for needle advance and retraction are not loaded by the high impact of a freely expanding high force drive spring. The auto-injector is well suited to serve as a platform as the drive spring can be swapped to deliver different viscosity drugs without affecting the insertion or

retraction functions. This is particularly advantageous for high viscosity fluids.

(22) Releasing the drive spring upon the needle reaching the insertion or injection depth avoids a so called wet injection, i.e. medicament leaking out of the needle which is a problem in conventional art auto-injectors, where both needle insertion and injection are achieved by pushing on the stopper. The auto-injector solves the wet injection problem by the separate springs for translation of the carrier and for drug delivery.

(23) The auto-injector has a particularly low part count compared to most conventional auto-injectors thus reducing manufacturing costs. The arrangement with separate control spring and drive spring for fluid injection allows for using one design for different viscosity liquids by just changing the drive spring, and for different volumes just by changing the length of the plunger. This is an advantage over conventional art designs where the main spring also powers needle insertion and/or retraction.

(24) In an initial as delivered state of the auto-injector the proximal end of the control spring is coupled to the chassis by the needle insertion control mechanism while the distal end is coupled to the case by the syringe retraction control mechanism, release of the drive spring is prevented by the plunger release mechanism, decoupling of the chassis from the carrier is prevented by the detent mechanism.

(25) In order to trigger an injection the auto-injector has to be pressed against an injection site, e.g. a patient's skin. A user, e.g. the patient or a caregiver, grabs the case with their whole hand and pushes the chassis protruding from the proximal end against the injection site.

(26) When pushed against the injection site, the case translates in the proximal direction relative to the chassis against the force of the control spring. When the case has at least almost reached an advanced position the detent mechanism is unlocked thereby allowing translation of the carrier relative to the chassis.

(27) The carrier can now be translated, preferably manually by depressing the trigger button forcing the carrier in the proximal direction. The carrier translates in the proximal direction relative to the case and to the chassis thereby switching the needle insertion control mechanism depending on the relative position of the carrier in the chassis so as to decouple the proximal end of the control spring from the chassis and couple it to the carrier, thereby releasing the control spring for advancing the carrier for needle insertion.

(28) Alternatively the control spring could initially be coupled to the carrier by the needle insertion control mechanism so that the carrier would be immediately advanced when the detent mechanism is unlocked by translation of the case into the advanced position.

(29) As the needle translated with the carrier subassembly at least almost reaches an injection depth the drive spring is released by the plunger release mechanism thereby allowing the drive spring to advance the plunger and the stopper for at least partially delivering the medicament. The release of the drive spring is preferably triggered by the carrier reaching a predefined relative position within the case.

(30) If the auto-injector is removed from the injection site after the stopper has bottomed out in the syringe or mid injection, the case is translated in the distal direction under load of the control spring relative to the carrier subassembly.

(31) As the case reaches a defined position relative to the carrier during that motion the proximal end of the control spring is decoupled from the carrier and coupled to the chassis by the needle insertion control mechanism. Furthermore the distal end of the control spring is decoupled from the trigger sleeve and coupled to the carrier by the syringe retraction control mechanism. As the control spring now pushes against the chassis in the proximal direction and against the carrier in the distal direction the carrier subassembly is retracted into the chassis into a needle safe position by the control spring.

(32) According to one embodiment the needle insertion control mechanism may comprise a first collar biased by the control spring in the proximal direction, wherein at least one resilient beam is

proximally arranged on the first collar, wherein respective recesses are arranged in the carrier and case, wherein a transversal extension of a head of the resilient beam is wider than a gap between the carrier and the chassis causing the head of the resilient beam to abut a distal face on the recess in the chassis while being prevented from deflecting in an inward direction by the carrier or to abut a distal face on the recess in the carrier while being prevented from deflecting in an outward direction by the chassis thereby forwarding load from the control spring to the carrier for needle insertion, wherein the resilient beam is arranged to be switched between the chassis and the carrier by ramped engagement of the head to the distal faces under load of the control spring depending on the relative longitudinal position between the chassis and the carrier. As the head of the resilient beam may be inwardly and outwardly ramped it may be referred to as an arrowhead.

(33) The plunger release mechanism may comprise at least one resilient arm on the carrier arranged to be in a ramped engagement to the plunger so as to disengage them under load of the drive spring, wherein a peg protrudes from a distal end face of the trigger button in the proximal direction in a manner to support the resilient arm preventing disengagement of the carrier from the plunger and thus release of the drive spring when the carrier is in a distal position. The trigger button is arranged to remain in position relative to the case when the carrier is translated for advancing the needle. That means, the trigger button, initially coupled to the carrier, pushes the carrier in the proximal direction when depressed. As soon as the control spring takes over further advancing the carrier the trigger button may abut the case and decouple from the carrier, staying in position as the carrier moves on. Hence the resilient arm is pulled away from the peg thus allowing deflection of the resilient arm due to the ramped engagement under load of the drive spring for disengaging the plunger from the carrier and releasing the drive spring for drug delivery when the carrier has reached a predefined position during needle advancement.

(34) The detent mechanism may be arranged to provide a resistive force which has to be overcome to advance the carrier in the proximal direction for needle insertion. Once the user applies a force on the trigger button which exceeds a pre-determined value the detent mechanism releases, initiating the injection cycle. If the pre-determined value is not overcome the detent mechanism pushes the carrier and trigger button back into their prior position. This ensures that the auto-injector is always in a defined state, either triggered or not triggered, not half triggered by the user hesitating.

(35) The detent mechanism may also be arranged to provide a resistive force resisting translation of the carrier in the distal direction relative to the chassis for keeping the carrier in a defined position in a transitional state with both ends of the control spring decoupled from the carrier. This transitional state may be required for retracting the needle on removal from the injection site. As the carrier is biased against the injection site by the control spring before removal from the injection site it has to be decoupled from the proximal end of the control spring and coupled to the distal end for retraction. The sequencing of this switching is critical as retraction will fail if both ends of the control spring are attached to the carrier at the same time. This is overcome by separating the switching of the ends by a significant displacement of the case, which moves in the distal direction relative to the chassis on removal of the injection site under load of the control spring. As the switching of the distal end of the control spring to the carrier depends on the relative position of the case to the carrier the carrier has to be fixed in the transitional state which is achieved by the detent mechanism.

(36) In one embodiment the detent mechanism comprises a resilient beam on the chassis and a rhomboid ramp member on the carrier, the resilient beam being essentially straight when relaxed and having a first beam head arranged to interact in a ramped engagement with a proximal fourth ramp or a distal fifth ramp on the rhomboid ramp member in such a manner that application of a translative force on the carrier relative to the chassis in the proximal direction with the first beam head engaged to the fourth ramp deflects the resilient beam in one transversal direction, e.g. outwards when a predetermined value of the translative force, at least depending on the resilience

of the resilient beam, is overcome so as to allow the first beam head to travel along one transversal side of the rhomboid ramp member on continued relative translation of the components. The beam head may protrude transversally from the resilient beam in a manner to distort the resilient beam by lever action when pushed against the rhomboid ramp member thereby also defining the predetermined value of the translative force to be overcome by the carrier. Furthermore, the contacting faces of the first beam head and the rhomboid ramp member may have their friction adapted to define the required force by appropriately choosing their shape and material properties. The resilient beam is allowed to relax when the first beam head has reached the fifth ramp thereby engaging it in a manner that application of a translative force on the carrier in the distal direction deflects the resilient beam in the other transversal direction, e.g. inwards when a predetermined value of the translative force, at least depending on the resilience of the resilient beam, is overcome so as to allow the first beam head to travel along the other transversal side of the rhomboid ramp member on continued translation of the carrier. The first beam head may also be allowed to relax behind the fourth ramp at the end of this motion for preventing the carrier from being advanced again, e.g. when the auto-injector is being heavily shaken after use.

(37) It goes without saying that the positions of the resilient beam on the chassis and the rhomboid ramp member on the carrier may be switched without altering the function of the detent mechanism.

(38) When the auto-injector or the syringe is assembled a protective needle sheath may be attached to the needle for keeping the needle sterile and preventing both, damage to the needle during assembly and handling and access of a user to the needle for avoiding finger stick injuries. Removal of the protective needle sheath prior to an injection usually requires a relatively high force for pulling the protective needle sheath off the needle and needle hub in the proximal direction. In order to maintain pre injection needle safety and prevent exposure of the needle translation of the syringe in the proximal direction due to this force has to be avoided. For this purpose the case may be arranged to lock the detent mechanism prior to being translated in the proximal direction relative to the chassis when the chassis is being pressed against the injection site so as to avoid translation of the carrier. This may be achieved by a rib in the case preventing deflection of the resilient beam of the detent mechanism by supporting it outwardly. Translation of the case is translated into the advanced position in the proximal direction on contact to the injection site is arranged to unlock the detent mechanism rendering it operable. This may be achieved by the rib being moved with the case so as to no longer outwardly supporting the resilient beam of the detent mechanism. In order to ensure that the case is not moved in the proximal direction unlocking the detent mechanism before the protective needle sheath is removed a cap may be attached to the proximal end of the case so as to make the chassis inaccessible before the cap is removed. The cap preferably engages the protective needle sheath by means of a barb in a manner to remove the protective needle sheath when the cap is being pulled off the auto-injector. In order to facilitate removal of the cap it may have a profiled surface mating with a surface on the case so that the cap is pulled off when rotated. The barb may be connected to the cap in a manner allowing them to rotate independently so as to avoid torque on the protective needle sheath when the cap is rotated in order not to distort the needle inside the protective needle sheath.

(39) The distally arranged trigger button may be at least initially coupled to the carrier, wherein the case is arranged to abut the trigger button in the initial state preventing depression of the trigger button. On translation of the case into the advanced position when the chassis is being pressed against the injection site the trigger button remains coupled to the carrier thus emerging from the case which has been moved relative to the chassis, carrier and trigger button so as to allow depression of the trigger button for starting an injection cycle. Thus a sequence of operation is defined for the auto-injector to be actuated, first pressing it against the injection site and then to push the trigger button. This reduces the risk of finger stick injuries particularly if the user were to be confused which end of the auto-injector to apply against their skin. Without a sequence the user

would risk inserting the needle into their thumb which is significantly less probable with the forced sequence.

(40) The syringe retraction control mechanism may comprise a second collar bearing against the distal end of the control spring and having a resilient proximal beam with a second beam head having an inward boss. The second beam head is arranged to be in a ramped engagement with a second case detent in the case in a manner ramping the second beam head in the inward direction under load of the control spring in the distal direction. The inward boss is arranged to inwardly abut the carrier for preventing inward deflection of the second beam head and keep the second collar locked to the case. A third recess is arranged in the carrier for allowing the inward boss to be inwardly deflected on translation of the case in the distal direction relative to the carrier on removal of the auto-injector from the injection site.

(41) In an alternative embodiment the first collar and/or the second collar may also be threaded to one of the components which they are intended to couple to the control spring wherein the case would be arranged to prevent the threads from decoupling in some relative longitudinal positions while allowing the collar to rotate out of the threaded engagement in other relative longitudinal positions so as to allow the collars to switch to the respective other component to be coupled to the control spring.

(42) In an alternative embodiment the trigger button may be arranged distally, wherein the case is arranged as a wrap-over sleeve trigger having a closed distal end face covering the trigger button. In an initial state a clearance is provided between the distal end face of the sleeve trigger and the trigger button allowing for some travel of the sleeve trigger against the bias of the control spring in the proximal direction in a first phase before abutting the trigger button. As soon as the sleeve trigger has contacted the trigger button the trigger button is pushed by the sleeve trigger on further translation in a second phase. This embodiment allows for keeping the majority of the components of the auto-injector while only the described features need modification allowing to customize a platform device to particular requirements. An auto-injector with a sleeve trigger is particularly well suited for people with dexterity problems since, as opposed to conventional art auto-injectors, triggering does not require operation of small buttons by single fingers. Instead, the whole hand is used.

(43) Retraction of the needle requires the user to lift the auto-injector far enough from the injection site to allow the case or sleeve trigger to translate back in the distal direction to switch the control spring. As it may be difficult for the user to know if the injection is finished or not a releasable noise component may be provided, capable of, upon release, generating an audible and/or tactile feedback to the user, wherein the noise component is arranged to be released when the plunger reaches a position relative to the syringe in which the stopper is located in proximity of a proximal end of the syringe, i.e. when the injection is at least almost finished. The released noise component then impacts on a housing component, such as the case, sleeve trigger or trigger button indicating the end of the injection. Impacting a directly accessible component allows for high perceptibility of the noise and direct access to the user's hand or finger for generating the tactile feedback. Preferably the noise component may impact the trigger button which may be shaped as a drum for providing a loud noise.

(44) The auto-injector may be operated by a number of key mechanical operations: The case is advanced relative to the chassis compressing the control spring giving the user the impression of depressing a skin interlock sleeve. All other components remain in the same place during case advance resulting in the trigger button appearing from the distal end of the case. The user pushes the trigger button which can now be operated. Button depression directly moves the carrier and hence the drive sub-assembly in the proximal direction a set distance until the control spring takes over via the first collar and inserts the needle into the injection site. The trigger button stops on the distal end of the case as the carrier continues translating in the proximal direction. The motion of the carrier relative to the trigger button is used to release the drive spring just before full insertion

depth is reached, e.g. by pulling a peg on the trigger button out of the carrier thus allowing the plunger to move. The drive spring drives the plunger down the syringe barrel expelling the medicament. A noise mechanism is released when the plunger is near the end of travel shortly before the stopper bottoms out in the syringe, indicating the end of injection to the user. The needle remains fully inserted until the user moves the case back a set distance at which point the second collar decouples from the case and couples to the carrier while the first collar decouples from the carrier and couples to the chassis thus allowing the control spring to retract the carrier and hence the needle.

(45) The auto-injector may preferably be used for subcutaneous or intra-muscular injection, particularly for delivering one of an analgetic, an anticoagulant, insulin, an insulin derivate, heparin, Lovenox, a vaccine, a growth hormone, a peptide hormone, a proteine, antibodies and complex carbohydrates.

(46) The term “medicament”, as used herein, means a pharmaceutical formulation containing at least one pharmaceutically active compound, wherein in one embodiment the pharmaceutically active compound has a molecular weight up to 1500 Da and/or is a peptide, a proteine, a polysaccharide, a vaccine, a DNA, a RNA, an antibody, an enzyme, an antibody, a hormone or an oligonucleotide, or a mixture of the above-mentioned pharmaceutically active compound, wherein in a further embodiment the pharmaceutically active compound is useful for the treatment and/or prophylaxis of diabetes mellitus or complications associated with diabetes mellitus such as diabetic retinopathy, thromboembolism disorders such as deep vein or pulmonary thromboembolism, acute coronary syndrome (ACS), angina, myocardial infarction, cancer, macular degeneration, inflammation, hay fever, atherosclerosis and/or rheumatoid arthritis, wherein in a further embodiment the pharmaceutically active compound comprises at least one peptide for the treatment and/or prophylaxis of diabetes mellitus or complications associated with diabetes mellitus such as diabetic retinopathy, wherein in a further embodiment the pharmaceutically active compound comprises at least one human insulin or a human insulin analogue or derivative, glucagon-like peptide (GLP-1) or an analogue or derivative thereof, or exedin-3 or exedin-4 or an analogue or derivative of exedin-3 or exedin-4.

(47) Insulin analogues are for example Gly(A21), Arg(B31), Arg(B32) human insulin; Lys(B3), Glu(B29) human insulin; Lys(B28), Pro(B29) human insulin; Asp(B28) human insulin; human insulin, wherein proline in position B28 is replaced by Asp, Lys, Leu, Val or Ala and wherein in position B29 Lys may be replaced by Pro; Ala(B26) human insulin; Des(B28-B30) human insulin; Des(B27) human insulin and Des(B30) human insulin.

(48) Insulin derivates are for example B29-N-myristoyl-des(B30) human insulin; B29-N-palmitoyl-des(B30) human insulin; B29-N-myristoyl human insulin; B29-N-palmitoyl human insulin; B28-N-myristoyl LysB28ProB29 human insulin; B28-N-palmitoyl-LysB28ProB29 human insulin; B30-N-myristoyl-ThrB29LysB30 human insulin; B30-N-palmitoyl-ThrB29LysB30 human insulin; B29-N—(N-palmitoyl-Y-glutamyl)-des(B30) human insulin; B29-N—(N-lithocholyl-Y-glutamyl)-des(B30) human insulin; B29-N-(ω -carboxyheptadecanoyl)-des(B30) human insulin and B29-N-(ω -carboxyheptadecanoyl) human insulin.

(49) Exendin-4 for example means Exendin-4(1-39), a peptide of the sequence H-His-Gly-Glu-Gly-Thr-Phe-Thr-Ser-Asp-Leu-Ser-Lys-Gln-Met-Glu-Glu-Glu-Ala-Val-Arg-Leu-Phe-Ile-Glu-Trp-Leu-Lys-Asn-Gly-Gly-Pro-Ser-Ser-Gly-Ala-Pro-Pro-Ser-NH₂.

(50) Exendin-4 derivatives are for example selected from the following list of compounds: H-(Lys)4-des Pro36, des Pro37 Exendin-4(1-39)-NH₂, H-(Lys)5-des Pro36, des Pro37 Exendin-4(1-39)-NH₂, des Pro36 [Asp28] Exendin-4(1-39), des Pro36 [IsoAsp28] Exendin-4(1-39), des Pro36 [Met(O)14, Asp28] Exendin-4(1-39), des Pro36 [Met(O)14, IsoAsp28] Exendin-4(1-39), des Pro36 [Trp(O2)25, Asp28] Exendin-4(1-39), des Pro36 [Trp(O2)25, IsoAsp28] Exendin-4(1-39), des Pro36 [Met(O)14 Trp(O2)25, Asp28] Exendin-4(1-39), des Pro36 [Met(O)14 Trp(O2)25, IsoAsp28] Exendin-4(1-39); or des Pro36 [Asp28] Exendin-4(1-39), des Pro36 [IsoAsp28]

Exendin-4(1-39), des Pro36 [Met(O)14, Asp28] Exendin-4(1-39), des Pro36 [Met(O)14, IsoAsp28] Exendin-4(1-39), des Pro36 [Trp(O2)25, Asp28] Exendin-4(1-39), des Pro36 [Trp(O2)25, IsoAsp28] Exendin-4(1-39), des Pro36 [Met(O)14 Trp(O2)25, Asp28] Exendin-4(1-39), des Pro36 [Met(O)14 Trp(O2)25, IsoAsp28] Exendin-4(1-39), wherein the group-Lys6-NH2 may be bound to the C-terminus of the Exendin-4 derivative; or an Exendin-4 derivative of the sequence H-(Lys)6-des Pro36 [Asp28] Exendin-4(1-39)-Lys6-NH2, des Asp28 Pro36, Pro37, Pro38 Exendin-4(1-39)-NH2, H-(Lys)6-des Pro36, Pro38 [Asp28] Exendin-4(1-39)-NH2, H-Asn-(Glu)5des Pro36, Pro37, Pro38 [Asp28] Exendin-4(1-39)-NH2, des Pro36, Pro37, Pro38 [Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-Asn-(Glu)5-des Pro36, Pro37, Pro38 [Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-(Lys)6-des Pro36 [Trp(O2)25, Asp28] Exendin-4(1-39)-Lys6-NH2, H-des Asp28 Pro36, Pro37, Pro38 [Trp(O2)25] Exendin-4(1-39)-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Trp(O2)25, Asp28] Exendin-4(1-39)-NH2, H-Asn-(Glu)5-des Pro36, Pro37, Pro38 [Trp(O2)25, Asp28] Exendin-4(1-39)-NH2, des Pro36, Pro37, Pro38 [Trp(O2)25, Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Trp(O2)25, Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-Asn-(Glu)5-des Pro36, Pro37, Pro38 [Trp(O2)25, Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-(Lys)6-des Pro36 [Met(O)14, Asp28] Exendin-4(1-39)-Lys6-NH2, des Met(O)14 Asp28 Pro36, Pro37, Pro38 Exendin-4(1-39)-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Met(O)14, Asp28] Exendin-4(1-39)-NH2, H-Asn-(Glu)5-des Pro36, Pro37, Pro38 [Met(O)14, Asp28] Exendin-4(1-39)-NH2, des Pro36, Pro37, Pro38 [Met(O)14, Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Met(O)14, Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-Asn-(Glu)5 des Pro36, Pro37, Pro38 [Met(O)14, Asp28] Exendin-4(1-39)-(Lys)6-NHpb 2, H-Lys6-des Pro36 [Met(O)14, Trp(O2)25, Asp28] Exendin-4(1-39)-Lys6-NH2, H-des Asp28 Pro36, Pro37, Pro38 [Met(O)14, Trp(O2)25] Exendin-4(1-39)-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Met(O)14, Asp28] Exendin-4(1-39)-NH2, H-Asn-(Glu)5-des Pro36, Pro37, Pro38 [Met(O)14, Trp(O2)25, Asp28] Exendin-4(1-39)-NH2, des Pro36, Pro37, Pro38 [Met(O)14, Trp(O2)25, Asp28] Exendin-4(1-39)-(Lys)6-NH2, H-(Lys)6-des Pro36, Pro37, Pro38 [Met(O)14, Trp(O2)25, Asp28] Exendin-4(S1-39)-(Lys)6-NH2, H-Asn-(Glu)5-des Pro36, Pro37, Pro38 [Met(O)14, Trp(O2)25, Asp28] Exendin-4(1-39)-(Lys)6-NH2; or a pharmaceutically acceptable salt or solvate of any one of the afore-mentioned Exedin-4 derivative.

(51) Hormones are for example hypophysis hormones or hypothalamus hormones or regulatory active peptides and their antagonists as listed in Rote Liste, ed. 2008, Chapter 50, such as Gonadotropine (Follitropin, Lutropin, Choriongonadotropin, Menotropin), Somatropine (Somatropin), Desmopressin, Terlipressin, Gonadorelin, Triptorelin, Leuprorelin, Buserelin, Nafarelin, Goserelin.

(52) A polysaccharide is for example a glucosaminoglycane, a hyaluronic acid, a heparin, a low molecular weight heparin or an ultra low molecular weight heparin or a derivative thereof, or a sulphated, e.g. a poly-sulphated form of the above-mentioned polysaccharides, and/or a pharmaceutically acceptable salt thereof. An example of a pharmaceutically acceptable salt of a poly-sulphated low molecular weight heparin is enoxaparin sodium.

(53) Pharmaceutically acceptable salts are for example acid addition salts and basic salts. Acid addition salts are e.g. HCl or HBr salts. Basic salts are e.g. salts having a cation selected from alkali or alkaline, e.g. Na⁺, or K⁺, or Ca²⁺, or an ammonium ion N⁺(R1)(R2)(R3)(R4), wherein R1 to R4 independently of each other mean: hydrogen, an optionally substituted C1-C6-alkyl group, an optionally substituted C2-C6-alkenyl group, an optionally substituted C6-C10-aryl group, or an optionally substituted C6-C10-heteroaryl group. Further examples of pharmaceutically acceptable salts are described in "Remington's Pharmaceutical Sciences" 17. ed. Alfonso R. Gennaro (Ed.), Mark Publishing Company, Easton, Pa., U.S.A., 1985 and in Encyclopedia of Pharmaceutical Technology.

(54) Pharmaceutically acceptable solvates are for example hydrates.

(55) The drive spring and control spring may be compression springs. However, they may likewise

be any kind of stored energy means such as torsion springs, gas springs etc.

(56) Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus, are not limitative of the present invention, and wherein:

(2) FIGS. 1A and 1B show two longitudinal sections of an auto-injector in different section planes in a state prior to use,

(3) FIGS. 2A and 2B show two longitudinal sections of the auto-injector after removal of a cap and a protective needle sheath,

(4) FIGS. 3A and 3B show shows two longitudinal sections of the auto-injector with a proximal end pressed against an injection site,

(5) FIGS. 4A and 4B show two longitudinal sections of the auto-injector with a trigger button depressed,

(6) FIGS. 5A and 5B show two longitudinal sections of the auto-injector during needle insertion into the injection site,

(7) FIGS. 6A and 6B show two longitudinal sections of the auto-injector with the needle fully inserted,

(8) FIGS. 7A and 7B show two longitudinal sections of the auto-injector during injection near the end of dose,

(9) FIGS. 8A and 8B show two longitudinal sections of the auto-injector at the end of dose,

(10) FIGS. 9A and 9B show two longitudinal sections of the auto-injector removed from the injection site,

(11) FIGS. 10A and 10B show two longitudinal sections of the auto-injector with the needle retracted into a needle safe position,

(12) FIGS. 11A, 11B, 11C and 11D show schematic views of a detent mechanism for controlling movement of a carrier relative to a chassis of the auto-injector in four different states,

(13) FIGS. 12A, 12B, 12C, 12D, 12E and 12F show schematic views of a needle insertion control mechanism for controlling movement of a first collar in six different states,

(14) FIGS. 13A, 13B and 13C show schematic views of a syringe retraction control mechanism in three different states,

(15) FIGS. 14A, 14B and 14C show schematic views of a noise release mechanism for audibly indicating the end of injection in three different states,

(16) FIGS. 15A, 15B and 15C show schematic views of a plunger release mechanism in three different states,

(17) FIGS. 16A, 16B and 16C show schematic views of a button release mechanism in three different states,

(18) FIG. 17 is an isometric view of an alternative embodiment of the plunger release mechanism,

(19) FIG. 18 is a longitudinal section of an alternative embodiment of the button release mechanism,

(20) FIGS. 19A and 19B show longitudinal sections of an alternative embodiment of the detent mechanism,

- (21) FIG. 20 is a longitudinal section of a third embodiment of the detent mechanism,
- (22) FIG. 21 is a longitudinal section of an alternative embodiment of the noise release mechanism,
- (23) FIGS. 22A and 22B show longitudinal sections of an alternative embodiment of the needle insertion control mechanism, also arranged to perform the function of the detent mechanism on needle retraction and needle insertion,
- (24) FIG. 23 is an isometric view of the needle insertion control mechanism of FIG. 22,
- (25) FIGS. 24A and 24B show longitudinal sections of a third embodiment of the needle insertion control mechanism, also arranged to perform the functions of the detent mechanism,
- (26) FIG. 25 is an isometric view of the needle insertion control mechanism of FIG. 24,
- (27) FIGS. 26A and 26B show longitudinal sections of a third embodiment of the noise release mechanism, and
- (28) FIGS. 27A and 27B show another embodiment of the auto-injector having a wrap-over sleeve trigger instead of a trigger button.
- (29) Corresponding parts are marked with the same reference symbols in all figures.

DETAILED DESCRIPTION

- (30) A ramped engagement in the terminology of this specification is an engagement between two components with at least one of them having a ramp for engaging the other component in such a manner that one of the components is flexed aside when the components are axially pushed against each other provided this component is not prevented from flexing aside.
- (31) FIGS. 1A and 1B show two longitudinal sections of an auto-injector 1 in different section planes, the different section planes approximately 90° rotated to each other, wherein the auto-injector 1 is in an initial state prior to starting an injection. The auto-injector 1 comprises a chassis 2. In the following the chassis 2 is generally considered as being fixed in position so motion of other components is described relative to the chassis 2. A syringe 3, e.g. a Hypak syringe, with a hollow injection needle 4 is arranged in a proximal part of the auto-injector 1. When the auto-injector 1 or the syringe 3 is assembled a protective needle sheath 5 is attached to the needle 4. A stopper 6 is arranged for sealing the syringe 3 distally and for displacing a liquid medicament M through the hollow needle 4. The syringe 3 is held in a tubular carrier 7 and supported at its proximal end therein. The carrier 7 is slidably arranged in the chassis 2.
- (32) A drive spring 8 in the shape of a compression spring is arranged in a distal part of the carrier 7. A plunger 9 serves for forwarding the force of the drive spring 8 to the stopper 6.
- (33) The drive spring 8 is loaded between a distal carrier end face 10 of the carrier 7 and a thrust face 11 arranged distally on the plunger 9.
- (34) The carrier 7 is a key element housing the syringe 3, the drive spring 8 and the plunger 9, which are the components required to eject the medicament M from the syringe 3. These components can therefore be referred to as a drive sub-assembly.
- (35) The chassis 2 and the carrier 7 are arranged within a tubular case 12. A trigger button 13 is arranged at a distal end of the case 12. In a plunger release mechanism 27 a peg 14 protrudes from a distal end face of the trigger button 13 in the proximal direction P between two resilient arms 15 originating from the distal carrier end face 10 thus preventing them from flexing towards each other in an initial state A illustrated in FIG. 15A. In FIG. 15A only one of the resilient arms 15 is shown to illustrate the principle. Outwardly the resilient arms 15 are caught in respective first recesses 16 in a distal plunger sleeve 17 attached distally to the thrust face 11 and arranged inside the drive spring 8. The engagement of the resilient arms 15 in the first recesses 16 prevents axial translation of the plunger 9 relative to the carrier 7. The resilient arms 15 are ramped in a manner to flex them inwards on relative motion between the plunger 9 and the carrier 7 under load of the drive spring 8, which is prevented by the peg 14 in the initial state A.
- (36) The carrier 7 is locked to the chassis 2 for preventing relative translation by a detent mechanism 18 illustrated in more detail in FIGS. 11A to 11D.
- (37) The trigger button 13 is initially engaged to the case 12 by a button release mechanism 26 and

cannot be depressed. The button release mechanism **26** is illustrated in detail in FIGS. **16A** to **16C**. Referring now to FIG. **16A** the button release mechanism **26** comprises a resilient proximal beam **13.1** on the trigger button **13**, the proximal beam **13.1** having an outward first ramp **13.2** and an inward second ramp **13.3**. In an initial state A illustrated in FIG. **16A** the outward first ramp **13.2** is engaged in a ramped first case detent **12.1** preventing the trigger button **13** from moving out of the distal end D. The trigger button **13** proximally abuts both the case **12** and the carrier **7** hence being prevented from being depressed in the proximal direction P.

(38) Referring again to FIGS. **1A** and **1B** a control spring **19** in the shape of another compression spring is arranged around the carrier **7** and acts between a proximal first collar **20** and a distal second collar **21**. The control spring **19** is used to move the carrier **7** and hence the drive sub-assembly in the proximal direction P for needle insertion or in the distal direction D for needle retraction.

(39) In the state as delivered as shown in FIGS. **1a** and **1b** a cap **22** is attached to the proximal end of the case **12** and the protective needle sheath **5** is still in place over the needle **4** and the needle hub. An inner sleeve **22.1** of the cap **22** is arranged inside the chassis **2** and over the protective needle sheath **5**. In the inner sleeve **22.1** a barb **23** is attached. The barb **23** is engaged to the protective needle sheath **5** for joint axial translation.

(40) A sequence of operation of the auto-injector **1** is as follows:

(41) A user pulls the cap **22** from the proximal end of the case **12**. The barb **23** joins the protective needle sheath **5** to the cap **22**. Hence, the protective needle sheath **5** is also removed on removal of the cap **22**. FIGS. **2A** and **2B** show the auto-injector **1** with the cap **22** and needle sheath **5** removed. The carrier **7** and syringe **3** are prevented from moving in the proximal direction P by the detent mechanism **18** being in a state A as in FIG. **11A**. Referring now to FIG. **11A**, the detent mechanism **18** comprises a resilient beam **2.1** on the chassis **2** with an inwardly protruding first beam head **2.2**. The first beam head **2.2** has a proximal third ramp **2.3**. The detent mechanism **18** further comprises a rhomboid ramp member **7.1** on the carrier **7** having a proximal fourth ramp **7.2** and a distal fifth ramp **7.3**. In state A a rounded off distal side of the first beam head **2.2** abuts the ramp member **7.1** in the distal direction D resisting movement of the carrier **7** in the proximal direction P relative to the chassis **2**. A rib on the case **12** is provided for preventing outward deflection of the resilient beam **2.1** thereby also preventing motion of the carrier **7** relative to the chassis **2**.

(42) Referring again to FIGS. **2A** and **2B** the user grabs the case **12** and places the chassis **2** protruding from the case **12** at the proximal end P against an injection site, e.g. a patient's skin. As the auto-injector **1** is pressed against the injection site the case **12** translates in the proximal direction P relative to the chassis **2** into an advanced position as illustrated in FIGS. **3A** and **3B**. The second collar **21** is locked to the case **12** and is moved with the case **12** relative to the chassis **2** and relative to nearly all other components of the auto-injector **1** thus slightly compressing the control spring **19** against the first collar **20** which is prevented from moving in the proximal direction P by the chassis **2** due to a needle insertion control mechanism **24** being in a state A illustrated in detail in FIG. **12A**. Referring now to FIG. **12A**, a resilient member in the shape of an arrowhead **20.1** is proximally arranged on the first collar **20**. The first collar **20** with the arrowhead **20.1** is being forced in the proximal direction P under load of the compressed control spring **19**. An outward sixth ramp **20.2** on the arrowhead **20.1** interacts with a second distal seventh ramp **2.4** on the chassis **2** ramping the arrowhead **20.1** in an inward direction I which is prevented by the arrowhead **20.1** inwardly abutting the carrier **7**. Hence, the first collar **20** cannot translate in the proximal direction P.

(43) Referring again to FIGS. **3A** and **3B** the second collar **21** is locked to the case due to a syringe retraction control mechanism **25** being in a state A illustrated in detail in FIG. **13A**. Referring now to FIG. **13A**, the syringe retraction control mechanism **25** comprises a resilient proximal beam **21.1** on the second collar **21**, the proximal beam **21.1** having a second beam head **21.2** having an inward

boss **21.3** and a distal outward eighth ramp **21.4**. The distal outward eighth ramp **21.4** is engaged in a ramped second case detent **12.2** in a manner ramping the second beam head **21.1** in the inward direction I with the second collar **21** under load of the control spring **19** in the distal direction D which is prevented by the inward boss **21.3** inwardly abutting the carrier **7**.

(44) Referring again to FIGS. **3A** and **3B**, if the user was to move the case **12** away from the injection site, the control spring **19** expands returning the auto-injector **1** to the initial condition after removal of the cap **22** as illustrated in FIGS. **2A** and **2B**.

(45) In the state as in FIGS. **3A** and **3B** the carrier **7** continues to be prevented from moving in the proximal direction P by the detent mechanism **18**, however with the case **12** in its advanced position the detent mechanism **18** is unlocked as the rib on the case **12** has also moved and no longer prevents outward deflection of the resilient beam **2.1**. Movement of the case **12** relative to the carrier **7**, which is locked to the chassis **2** by the detent mechanism **18**, causes the button release mechanism **26** to switch to a state B illustrated in FIG. **16B**. The trigger button **13** cannot translate with the case **12** in the proximal direction P as it is abutted against the carrier **7**. The ramp on the first case detent **12.1** interacts with the outward first ramp **13.2** on the proximal beam **13.1** on the trigger button **13** deflecting the proximal beam **13.1** in the inward direction I thus engaging the inward second ramp **13.3** on the proximal beam **13.1** in a ramped carrier detent **7.4** arranged in the carrier **7**. As the case **12** is translated further in the proximal direction P it supports the proximal beam **13.1** outwardly thus locking the trigger button **13** to the carrier **7**. The trigger button **13** now protrudes from the distal end D of the chassis **12** and is ready to be pressed.

(46) In the state as in FIGS. **3A** and **3B** the user depresses the trigger button **13** in the proximal direction P. As the trigger button **13** abuts against the carrier **7** the carrier **7** is pushing in the proximal direction P against the chassis **2**, the carrier **7** and the chassis **2** interacting in the detent mechanism **18**. The force exerted by the user pressing the trigger button **13** is resolved through the chassis **2** onto the injection site, not between the trigger button **13** and the case **12**. The detent mechanism **18** provides a resistive force when the user pushes the trigger button **13**. Once the user applies a force which exceeds a pre-determined value the detent mechanism **18** releases, initiating the injection cycle. Referring now to FIG. **11B** showing the detent mechanism **18** in a state B, the resilient beam **2.1** on the chassis **2** begins to bow under load from the rhomboid ramp member **7.1** on the carrier **7**, storing elastic energy. Despite the proximal fourth ramp **7.2** on the ramp member **7.1** friction between the contacting faces of the first beam head **2.2** and the proximal fourth ramp **7.2** prevents movement of the first beam head **2.2** in the outward direction O until the straightening force in the resiliently deformed beam **2.1** is sufficiently large to overcome it. At this point the resilient beam **2.1** is deflected in the outward direction O moving out of the way of the carrier **7** thus allowing the carrier **7** to translate in the proximal direction P. When the carrier **7** travels sufficiently far in the proximal direction P the rhomboid ramp member **7.1** on the carrier **7** passes under the first beam head **2.2** thus allowing it to relax and move back in the inward direction I distally behind the rhomboid ramp member **7.1** in a state C illustrated in FIG. **11C** at the same time constraining translation of the carrier **7** in the distal direction D relative to the chassis **2**.

(47) Once the carrier **7** slides far enough in the proximal direction P relative to the first collar **20** the needle insertion control mechanism **24** is switched to a state B as illustrated in FIG. **12B**. In FIG. **12B** the carrier **7** has been translated in the proximal direction P in such a manner that the arrowhead **20.1** on the first collar **20** is no longer inwardly supported. This may be achieved by a second recess **7.5** in the carrier **7**. The arrowhead **20.1** is now deflected in the inward direction I into the second recess **7.5** under load of the control spring **19** arriving at a state C as illustrated in FIG. **12C**. The first collar **20** is now decoupled from the chassis **2**. Instead, the arrowhead **20.1** couples the first collar **20** to the carrier **7** by an inward ninth ramp **20.3** engaging a distal tenth ramp **7.6** on the carrier **7** at the proximal end of the second recess **7.5**. Hence, the control spring **19** continues moving the carrier **7** in the proximal direction P from this point. Whilst the user advances the needle **4** by a proportion of its travel, the control spring **19** takes over insertion before the

needle **4** protrudes from the proximal end P. Therefore the user experience is that of pressing a button, rather than manually inserting a needle.

(48) The detent mechanism **18** relies on the user applying a force rather than a displacement. Once the force applied exceeds the force required to switch the detent the user will push the trigger button **13** fully, ensuring that the first collar **20** will always switch. If the user fails to pass the detent, the trigger button **13** returns to its unused state ready for use as illustrated in FIGS. **3A** and **3B**. This feature avoids the auto-injector **1** arriving in an undefined state.

(49) FIGS. **4A** and **4B** show the auto-injector **1** with the trigger button **13** depressed sufficiently for the control spring **19** to couple on to the carrier **7** and continue moving the carrier **7** forwards, but not yet abutting the case **12**.

(50) The carrier **7** coupled to the first collar **20** is translated in the proximal direction P driven by the control spring **19**. As the syringe **3** is arranged for joint axial translation with the carrier **3** the syringe **3** and needle **4** are also translated resulting in the needle **4** protruding from the proximal end P and being inserted into the injection site. The trigger button **13** returns to its initial position relative to the case **12** and latches back to the case **12** from the carrier **7** as in state A in FIG. **16A**. The carrier **7** translates further in the proximal direction P preventing inward deflection of the proximal beam **13.1** so the outward first ramp **13.2** cannot disengage from the first case detent **12.1**.

(51) Immediately prior to the needle **4** reaching full insertion depth as illustrated in FIGS. **5A** and **5B** the peg **14** on the trigger button **13** is completely pulled out from between the resilient arms **15** on the carrier **7**. Hence, the plunger release mechanism **27** arrives in a state B shown in FIG. **15B** with the resilient arms **15** no longer inwardly supported by the peg **14**. Due to the ramped engagement of the resilient arms **15** in the first recess **16** they are deflected in the inward direction I under load of the drive spring **8** arriving in a state B illustrated in FIG. **15C**. Hence, the plunger **9** is released from the carrier **7** and driven in the proximal direction P by the drive spring **8**, ready to inject the medicament M. The force to pull the peg **14** out from between the resilient arms **15** is provided by the control spring **19** while the force required to deflect the resilient arms **15** out of engagement to the plunger **9** is provided by the drive spring **8**.

(52) While the plunger **9** moves and closes a gap to the stopper **6** the movement of the carrier **7** in the proximal direction P is completed by the control spring **19** pushing the first collar **20**. As the carrier **7** moves with respect to the chassis **2** during needle insertion the needle insertion mechanism **24** arrives in a state D illustrated in FIG. **12D**. The arrowhead **20.1** has moved with the carrier **7** and is still kept inwardly deflected by the chassis **2** thus preventing the first collar **20** from disengaging the carrier **7**. The arrowhead **20.1** must be able to deflect in the outward direction O to allow retraction which will be discussed below. In order to allow outward deflection the arrowhead **20.1** travels proximally beyond the part of the chassis **2** shown in FIGS. **12A** to **12F** next to an aperture **2.5** in the chassis **2**. However, as long as the case **12** is being kept pressed against the injection site and not allowed to return in the distal direction D beyond a predefined distance under load of the control spring **19** the arrowhead **20.1** will be kept from deflecting in the outward direction O by a first rib **12.3** on the case **12** (not illustrated in FIGS. **12A** to **F**, see FIGS. **5A** to **8A**) during about the second half of its motion for needle insertion.

(53) The needle **4** is now fully inserted into the injection site as illustrated in FIGS. **6A** and **6B**. The time between the trigger button **13** pressed and the needle **4** being fully inserted is very short, however several mechanical operations take place in this time. The needle insertion depth is defined by the carrier **7** relative to the chassis **2** not relative to the case **12**, so if the user flinches or fails to hold the auto-injector **1** hard against the skin, only the case **12** will move in the distal direction D while the injection depth remains constant.

(54) As soon as the plunger **9** has closed the gap to the stopper **6** under force of the drive spring **8** the stopper **6** is pushed in the proximal direction P within the syringe **3** displacing the medicament M through the needle **4** into the injection site.

(55) Immediately prior to the end of injection with the stopper **6** having almost bottomed out in the syringe **3** as illustrated in FIGS. **7A** and **7B** a noise component **28** is released. The stack up of tolerances, most notably due to the syringe **3** requires that the noise must always be released prior to the end of injection. Otherwise, with certain combinations of parts, the noise would not always release. The noise component **28** comprises an elongate portion **28.1** arranged within the distal plunger sleeve **17** and a distal end plate **28.2** arranged between the carrier end face **10** and an end face of the trigger button **13**. Two second resilient arms **30** originate from the distal carrier end face **10** and extend in the proximal direction P. A noise spring **29** is arranged to bias the noise component **28** in the distal direction D relative to the carrier **7** by proximally bearing against a rib on the second resilient arms **30** and distally against the noise component **28** (not illustrated).

(56) Note: the noise component **28** is not illustrated in FIGS. **16A**, **B** and **C** for clarity since it does not affect the function of the button release mechanism **26**. A noise release mechanism **31** for releasing the noise component **28** is schematically illustrated in FIGS. **14A**, **14B** and **14C**. Referring now to FIG. **14A**, the noise release mechanism **31** comprises the second resilient arms **30**. A ramped inward boss **30.1** is arranged on each second resilient arm **30** which is engaged to a respective outward eleventh ramp **28.3** on the elongate portion **28.1** of the noise component **28** in such a manner that the second resilient arm **30** is deflected in the outward direction O under load of the noise spring **29**. In an initial state A of the noise release mechanism **31** the second resilient arms **30** are prevented from being outwardly deflected by outward support of the distal plunger sleeve **17** thus preventing translation of the noise component **28** relative to the carrier **7**. The noise release mechanism **31** remains in state A until immediately prior to the end of injection with the stopper **6** having almost bottomed out in the syringe **3** as illustrated in FIGS. **7A** and **7B**. At this point the plunger **9** has been translated in the proximal direction P relative to the carrier **7** to such an extent that the second resilient arms **30** are no longer supported by the distal plunger sleeve **17**. The noise release mechanism **31** has thus arrived in a state B illustrated in FIG. **14B**. Due to the ramped engagement between the ramped inward boss **30.1** and the outward eleventh ramp **28.3** the second resilient arm **30** is outwardly deflected under load of the noise spring **29** thus disengaging the noise component **28** from the carrier **7** and allowing the noise component **28** to move in the distal direction D driven by the noise spring **29** in a state C illustrated in FIG. **14C**. Hence, the noise component **28** is accelerated in the distal direction D and the distal end plate **28.2** impacts on the inside of the trigger button **13** producing audible and tactile feedback to the user that the injection is about finished.

(57) FIGS. **8A** and **8B** show the auto-injector **1** with the stopper **6** having entirely bottomed out in the syringe **3**.

(58) As mentioned above the user is able to let the case **12** move by a few millimetres in the distal direction D under the force of the control spring **19** without affecting the position of the needle **4** as long as that motion is below a predefined distance. If the user wishes to end the injection, at any time, they must allow the case **12** to move in the distal direction D beyond that distance. FIGS. **9A** and **9B** show the auto-injector **1** lifted from the injection site with the case **12** moved all the way in the distal direction D so that the chassis **2** protrudes from the proximal end of the case **12**. As the case **12** is moved the first collar **20** releases the carrier **7** and then the second collar **21** releases from the case **12** and pulls the carrier **7** in the distal direction D. The sequencing of this switching is critical as retraction will fail if both collars **20**, **21** are attached to the carrier **7** at the same time. This is overcome by separating the switching of the collars **20**, **21** by a significant displacement of the case **12**.

(59) The switching of the first collar **20** is illustrated in FIGS. **12E** and **F**. In FIG. **12E** the case **12** has been allowed to move in the distal direction D under load of the control spring **19** during removal of the auto-injector **1** from the injection site. The first rib **12.3** (not illustrated, see FIG. **9A**) is removed from outwardly behind the arrowhead **20.1**. The first collar **20** is still being pushed in the proximal direction P by the control spring **19**. Due to the engagement of the inward ninth

ramp **20.3** on the arrowhead **20.1** with the distal tenth ramp **7.6** on the carrier **7** the arrowhead **20.1** is deflected in the outward direction **O** into the aperture **2.5** of the chassis **2** (illustrated in FIGS. **12A** to **12F**), the needle insertion control mechanism **24** arriving in a state **E** as illustrated in FIG. **12E**, decoupling the first collar **20** from the carrier **7** and latching it to the chassis **2**.

(60) As the case **12** is moving further in the distal direction **D** on removal from the injection site the syringe retraction control mechanism **25** switches from its state **A** (cf. FIG. **13A**) into a state **B** illustrated in FIG. **13B**. The case **12** and the second collar **21** locked to the case **12** move together in the distal direction **D** while the carrier **7** is held in place by the detent mechanism **18** in its state **C** as described above (cf. FIG. **11C**). Due to this motion the inward boss **21.3** on the second beam head **21.2** of the proximal beam **21.1** on the second collar **21** no longer inwardly abuts the carrier **7**. Instead the inward boss **21.3** is deflected in the inward direction **I** into a third recess **7.7** in the carrier **7** due to the ramped engagement of the second beam head **21.1** to the ramped second case detent **12.2** under load of the control spring **19**. The syringe retraction control mechanism **25** thus arrives in a state **C** as illustrated in FIG. **13C** with the second collar **21** decoupled from the case **12** and coupled to the carrier **7**. The detent mechanism **18** applies a small retarding force to the movement of the carrier **7** before the syringe retraction control mechanism **25** switches to state **C** as there is a small sliding force, applied by the second collar **21**, pulling the carrier **7** in the distal direction **D** on translation of the case **12** in the distal direction **D** when the needle insertion control mechanism **24** has already been switched into state **E**. If the carrier **7** moves too far in the distal direction **D** before the second collar **21** switches, the case **12** runs out of travel before the inward boss **21.3** can deflect into the third recess **7.7** preventing retraction.

(61) Starting from the position **C** of the detent mechanism **18** (cf. FIG. **11C**) the carrier **7** and hence the rhomboid ramp member **7.1** are translated in the distal direction **D** under load of the control spring **19**. Hence, the distal fifth ramp **7.3** of the rhomboid ramp member **7.1** engages the proximal third ramp **2.3** on the first beam head **2.2** of the resilient beam **2.1** in a manner deflecting the resilient beam **2.1** in the inward direction **I**. This applies the small retarding force to the movement of the carrier **7** required for ensuring the switching of the second collar **21** to the carrier **7**. The resilient beam **2.1** and the rhomboid ramp member **7.1** are offset sideways to allow the resilient beam **2.1** to pass without contacting the rhomboid ramp member **7.1** as soon as the first beam head **2.2** is entirely inwardly from the ramp member **7.1** in a state **D** illustrated in FIG. **11D**.

(62) The control spring **19** is grounded at its proximal end in the case by the first collar **20** being abutted against the chassis **2**. The distal end of the control spring **19** moves the second collar **21** in the distal direction **D** taking with it the carrier **7** and hence the syringe **3** with the needle **4** overcoming the detent mechanism **18** as illustrated in FIG. **11D**. Note that the needle **4** is retracted out of the skin by the auto-injector **1** as soon as the user allows the case **12** to translate sufficiently far as opposed to auto-injectors with needle shields which require the user to remove the auto-injector from the injection site thereby themselves pulling the needle out of the skin for allowing the needle shield to advance.

(63) As the movement allowed of the noise component **28** is limited relative to the carrier **7** it is no longer in contact with the trigger button **13** which has moved in the distal direction **D** with the case **12** on removal from the injection site. When the retraction begins the noise spring **29** does not provide any retarding force. Once the noise component **28** hits the trigger button **13** again on retraction of the carrier **7** the noise spring **29** must be recompressed, reducing the force driving the final part of retraction. In order to ensure a reliable retraction despite this reducing force the control spring **19** must be appropriately dimensioned.

(64) The retraction ends when the distal collar **21** meets a first back stop **12.4** on the case **12** as in FIGS. **10A** and **10B**. The arrowhead **20.1** on the first collar **20** is inwardly supported by the carrier **7** in a state **F** illustrated in FIG. **12F** and thus prevented from deflecting in the inward direction **I**. The outward sixth ramp **20.2** of the arrowhead **20.1** is engaged behind the first rib **12.3** on the case **12** preventing the case **12** from being pushed in the proximal direction **P** again. A clearance may be

provided between the arrowhead **20.1** and the first rib **12.3** to allow for tolerances.

(65) The detent mechanism **18** returns to state A as in FIG. **11A** locking the carrier **7** in position relative to the chassis **2** as it did initially, however it cannot be unlocked now as the case **12** cannot move relative to the chassis **2**.

(66) A tab **20.4** on the first collar **20** is now visible through an indicator window **32** in the case **12**—indicating the auto-injector **1** has been used.

(67) FIG. **17** is an isometric view of an alternative embodiment of the plunger release mechanism **27**. The plunger release mechanism **27** prevents movement of the plunger **9** in the proximal direction P relative to the carrier **7** until the carrier **7** is moved in the proximal direction P for needle insertion. As opposed to the plunger release mechanism **27** of FIG. **15**, where relative movement of the carrier **7** and trigger button **13** are used to trigger the release of the plunger **9**, the alternative embodiment of FIG. **17** releases the plunger **9** by movement of the carrier **7** relative to the second collar **21**. FIG. **17** illustrates the plunger release mechanism **27** prior to plunger release. The second collar **21** is shown transparent to improve clarity. The plunger **9** is being pushed in the proximal direction P by the drive spring **8**. In order for the plunger **9** to advance, it must rotate around a twelfth ramp **7.8** on the carrier **7**. A ramp member **9.1** on the plunger **9** is arranged to engage this twelfth ramp **7.8**. Rotation of the ramp member **9.1** is blocked by an inward longitudinal rib **21.5** on the second collar **21** splined in a longitudinal aperture **7.9** in the carrier **7**. The case **12** and the second collar **21** remain in the same position, i.e. coupled to each other for joint axial translation. On depression of the trigger button **13** the carrier **13** and the plunger **9** being part of the drive sub-assembly are moved in the proximal direction P, first by the user pressing the trigger button **13** and then by the control spring **19** taking over via the first collar **20** as described above. Once the carrier **7** moves sufficiently far in the proximal direction P relative to the second collar **21** the ramp member **9.1** on the collar **9** comes clear of the longitudinal rib **21.5** on the second collar **21** and can rotate past the proximal end of the longitudinal rib **21.5** due to its ramped engagement to the twelfth ramp **7.8** under load of the drive spring **8**. Hence, the drive spring **8** advances the plunger **9** in the proximal direction P for injecting the medicament M.

(68) FIG. **18** is a longitudinal section of an alternative embodiment of the button release mechanism **26**. Other than the button release mechanism **26** of FIG. **16** which gives the appearance of a revealing trigger button **13** on skin contact by switching the ground of the trigger button **13** between the carrier **7** and the case **12**, the button release mechanism **26** of FIG. **18** starts with the trigger button **13** locked but protruding from the distal end of the case **12**. Once the carrier **7** has moved in the distal direction D on skin contact of the chassis **2**, it is possible to depress the trigger button **13** and activate the auto-injector **1**. This ensures a sequenced operation.

(69) In the embodiment of FIG. **18** the trigger button **13** has two proximal beams **13.1**, each of them having a ramped outward boss **13.4**. In the initial state shown in FIG. **18** the ramped outward bosses **13.4** are engaged in respective fourth recesses **12.5** in the case **12**. Disengaging the ramped outward bosses **13.4** from the fourth recesses **12.5** is prevented by the carrier **7** inwardly supporting the proximal beams **13.1** in a manner to keep the proximal beams **13.1** from deflecting inwardly. Inward protrusions **13.5** on the proximal beams **13.1** abut against a second rib **7.10** on the carrier **7** in a manner preventing the carrier **7** from moving further in the proximal direction P in the initial state. Once the carrier **7** has moved in the distal direction D on skin contact of the chassis **2** a first window **7.11** in the carrier **7** is moved behind the inward protrusion **13.5** so as to allow the proximal beams **13.1** to be inwardly deflected due to their ramped engagement in the fourth recesses **12.5** on depression of the trigger button **13**. The proximal beams **13.1** are now outwardly supported by the case **12** and remain engaged to the carrier **7** even on retraction of the needle **4**. The trigger button **13** does therefore not return to its initial position, indicating that the auto-injector **1** has been used.

(70) The button release mechanism **26** illustrated in FIG. **18** may preferably be combined with the plunger release mechanism **27** illustrated in FIG. **17**.

(71) FIGS. **19A** and **19B** show two longitudinal sections of an alternative embodiment of the detent mechanism **18**. The detent mechanism **18** of FIGS. **11A** to **11D**, which may be referred to as a “race track” mechanism because of the first beam head **2.2** travelling around the rhomboid ramp member **7.1** has multiple functions which control the movement of the carrier **7** relative to the chassis **2**. The alternative detent mechanism **18** of FIGS. **19A** and **19B** uses three clips **7.12**, **7.13**, **2.6** to produce the same effect.

(72) The first clip **7.12** is arranged as an outwardly biased resilient beam on the carrier **7** extending from the carrier **7** in the proximal direction **P**. the first clip **7.12** is arranged to prevent the carrier **7** from being moved in the proximal direction **P** prior to the chassis **2** being depressed or rather the case **12** being translated on skin contact. The first clip **7.12** is composed of two sections side by side. A first section **7.14** prevents movement of the carrier **7** in the proximal direction **P** by abutting the chassis **2** in a recess. A second section **7.15** is arranged as an outwardly protruding clip head arranged to be ramped inwards by a ramp feature **12.6** on the chassis **12** for releasing the first clip **7.12** thereby unlocking the carrier **7** from the chassis **2** when the case **12** is being translated in the proximal direction **P** on skin contact. A longitudinal slot **2.7** in the chassis **2** is arranged for allowing the second section **7.15** to slide in the proximal direction **P** once the lock has been released. A slight friction force between the first clip **7.12** and the chassis **2** provides the retarding force required to ensure retraction.

(73) The second clip **7.13** is arranged as a resilient beam on the carrier **7** extending in the distal direction **D** having an outwardly protruding third beam head **7.16** with a proximal ramp. The third beam head **7.16** serves as a back stop against a third rib **2.9** on the chassis **2** for preventing the carrier **7** moving in the distal direction **D** from its initial position. The carrier **7** and chassis **2** are assembled with the second clip **7.13** in this position prior to inserting the syringe **3** into the carrier **7** which is facilitated by the proximal ramp on the third beam head **7.16**. The syringe **3** locks the clip in place by preventing inward deflection thus creating a fixed stop.

(74) The third clip **2.6** is a resilient beam on the chassis **2** extending in the distal direction **D**. A ramped fourth beam head **2.8** on the third clip **2.6** is arranged to inwardly engage in a fifth recess **7.17** in the carrier **7**. Once the first clip **7.12** is unlocked, the user can load the third clip **2.6** by pressing the carrier **7** in the proximal direction **P** on depression of the trigger button **13**. The third clip **2.6** is loaded in compression, i.e. it will bend outwards and release suddenly due to its ramped engagement to the carrier **7** providing the detent functionality similar to that illustrated in FIG. **11B**.

(75) FIG. **20** is a longitudinal section of a third embodiment of the detent mechanism **18** which is a variation on the embodiment of FIGS. **19A** and **19B**. In this embodiment the detent function of the third clip **2.6** has been added into the first clip **7.12**. The lock between the case **12** and the carrier **7** is released in the same way, but the detent is provided by deflecting the first clip **7.12** inwards a second level which is achieved by the chassis **2** not having a slot **2.7** for the second section **7.15**. Instead the second section **7.15**, once ramped inwards by the ramp feature **12.6** on the case **12** has to be further ramped inwards inside the chassis **2** on axial load between the chassis **2** and the carrier **7**, suddenly releasing their engagement.

(76) FIG. **21** is a longitudinal section of an alternative embodiment of the noise release mechanism **31**. As opposed to the noise release mechanism **31** of FIG. **14** where the noise spring **29** acts between the carrier **7** and the noise component **28**, in the embodiment illustrated in FIG. **21** the noise spring **29** acts between the case **12** and the noise component **28**. During needle insertion the noise spring **29** is compressed as the noise component **28** moves with the carrier **7** relative to the case **12**. When the noise component **28** is released by the plunger **9** shortly before the end of dose, the noise component **28** moves in the distal direction **D** and impacts the trigger button **13**. Other than in FIG. **14** the noise spring **29** is not being recompressed during needle retraction since it is grounded in the case **12** not in the carrier **7**.

(77) FIGS. **22A** and **22B** show longitudinal sections of an alternative embodiment of the needle insertion control mechanism **24** which is also arranged to perform the detent function of the detent

mechanism **18** on needle retraction and needle insertion. FIG. **23** shows a corresponding isometric view. A fourth clip **20.5** on the first collar **20** is arranged as a resilient beam with a beam head having an inward proximal thirteenth ramp **20.6** for engaging a fourth rib **7.18** on the carrier **7** and outwardly supported by the case **12** so as to keep the first collar **20** engaged to the carrier **7** prior to use, during needle insertion and during injection. When the user lifts the case **12** away from the injection site at the end of injection, a sixth recess **12.7** in the case **12** is moved outwardly behind the fourth clip **20.5** allowing the fourth clip **20.5** to release when the carrier **7** is pulled in the distal direction **D** by the second collar **21**. Since the fourth clip **20.5** has to be ramped outwards a small force is required to release the fourth clip **20.5**, providing the retraction detent.

(78) A fifth clip **2.10** on the chassis **2** abuts a block **20.7** on the first collar **20** prior to use preventing the first collar **20** and hence the carrier **7** engaged to the first collar **20** from moving in the proximal direction **P**. In order to release, the fifth clip **2.10** must be deflected outwards and over the block **20.7**. Outward deflection of the fifth clip **2.10** is initially prevented by the case **12**. Once the case **12** has moved on skin contact a second window **12.8** in the case **12** appears outwardly from the fifth clip **2.10** allowing outward deflection. The fifth clip **2.10** is then deflected by a fourteenth ramp **7.19** on the carrier **7** when the carrier **7** is pushed in the proximal direction **P** on button depression as the fourth clip **20.5** does allow translation of the carrier **7** in the proximal direction **P** relative to the first collar **20** but not the other way round. The detent for needle insertion is provided by having to deflect the fifth clip **2.10** when it is loaded by the control spring **19**.

(79) FIGS. **24A** and **24B** show longitudinal sections of a third embodiment of the needle insertion control mechanism **24**, also arranged to perform the functions of the detent mechanism **18**. FIG. **25** is an isometric view of the needle insertion control mechanism **24** of FIG. **24**. The embodiment is similar to that illustrated in FIGS. **22A**, **22B** and **23**. The difference is that the fifth clip **2.10** is arranged on the first collar **20** and the block **20.7** is arranged on the chassis **2**, i.e. their position has been switched, so there are two clips **2.10** and **20.5** on the first collar **20**.

(80) The fourth clip **20.5** is identical to that in FIG. **22B**. It keeps the first collar **20** connected to the carrier **7** until the needle retraction is triggered, ensuring full injection depth is reached and maintained until the retraction cycle is initiated by removing the auto-injector **1** from the skin.

(81) The fifth clip **2.10** provides the detent for needle insertion and releases the first collar **20** from the chassis **2**, initiating needle insertion. The fifth clip **2.10** prevents the first collar **20** and hence the carrier **7** engaged to the first collar **20** from moving in the proximal direction **P** prior to use by abutting the block **20.7** on the chassis **2**. In order to release, the fifth clip **2.10** must be deflected outwards and over the block **20.7**. Outward deflection of the fifth clip **2.10** is initially prevented by the case **12**. Once the case **12** has moved on skin contact the second window **12.8** in the case **12** appears outwardly from the fifth clip **2.10** allowing outward deflection. The fifth clip **2.10** is then deflected by the fourteenth ramp **7.19** on the carrier **7** when the carrier **7** is pushed in the proximal direction **P** on button depression as the fourth clip **20.5** does allow translation of the carrier **7** in the proximal direction **P** relative to the first collar **20** but not the other way round. The detent for needle insertion is provided by having to deflect the fifth clip **2.10** when it is loaded by the control spring **19**.

(82) FIGS. **26A** and **26B** show a longitudinal section of a third embodiment of the noise release mechanism **31**. This embodiment works without the need for a dedicated noise spring. The plunger **9** comprises a proximally ramped rib **9.2** arranged to splay two seventh clips **7.21** on the carrier **7** immediately prior to the end of dose. When the proximally ramped rib **9.2** has travelled past the seventh clips **7.21** they snap back and impact the plunger **9** generating a sound. The tubular shape of the carrier **7** helps to transmit the sound. FIG. **26A** shows the noise release mechanism **31** before release. FIG. **26B** shows the noise release mechanism **31** after release. Proximal faces of the seventh clips **7.21** on the carrier **7** are axially offset to facilitate assembly by lifting the seventh clips **7.21** over the distal side of the proximally ramped rib **9.2** one by one.

(83) FIGS. **27A** and **27B** show longitudinal sections of another embodiment of the auto-injector **1**

in different section planes, the different section planes approximately 90° rotated to each other, wherein the auto-injector **1** is in an initial state prior to starting an injection. The auto-injector **1** is essentially identical to the one described in FIGS. **1** to **16**. However, other than the auto-injector of FIGS. **1** to **16** the auto-injector **1** of this embodiment has a wrap-over sleeve trigger instead of a trigger button.

(84) The wrap-over sleeve trigger **12** is the same component as the case **12** which has a closed distal end face **12.10** other than the one in FIGS. **1** to **16**. An internal trigger button **13** is arranged at the distal end inside the sleeve trigger **12**. Other than in FIGS. **1** to **16** the trigger button **13** is not visible nor does it protrude from the case **12** in any state. In the initial state a clearance **33** is provided between the distal end face **12.10** of the sleeve trigger **12** and the internal trigger button **13** allowing for some travel of the sleeve trigger **12** without interfering with the trigger button **13**.

(85) As the auto-injector **1** does not differ from the auto-injector of FIGS. **1** to **16** in other respects it is essentially operated in the same way with the following exceptions:

(86) As the chassis **2** is placed against the injection site the sleeve trigger **12** translates in the proximal direction P relative to the chassis **2** into the advanced position in a first phase of sleeve travel removing the clearance **33** between the distal end face **12.10** of the sleeve trigger **12** and the internal trigger button **13**. As in the embodiment of FIGS. **1** to **16** this motion unlocks the detent mechanism **18** and the trigger button **13**. As the user continues to depress the sleeve trigger **12** in a second phase of sleeve travel thereby further advancing it in the proximal direction P the distal end face **12.10** hits the internal trigger button **13** thereby depressing it until the first collar **20** is released from the chassis **2** and the control spring force is coupled on to the carrier **7**. The carrier **7** then advances until the internal trigger button **13** stops on another rib in the case **12** and the plunger release mechanism **27** is released (note the peg **14** is shorter in this embodiment).

(87) From a user perspective, the detent mechanism **18** is arranged to provide a resistive force when the user reaches the second phase of sleeve travel. Internally, there is no difference to the embodiment of FIGS. **1** to **16** at this point.

(88) Needle insertion is triggered by the user fully advancing the sleeve trigger **12** in the second phase of sleeve travel thereby fully depressing the internal trigger button **13** and overcoming the detent mechanism as in the embodiment of FIGS. **1** to **16**.

(89) As the control spring **19** takes over on button depression fully advancing the carrier **7** for needle insertion the internal trigger button **13** bottoms out on an internal fifth rib **12.11** in the sleeve trigger **12** and the internal trigger button **13** switches back to being locked to the sleeve trigger **12** as in FIG. **16C**.

(90) The embodiment of FIGS. **27A** and **27B** may also be combined with the alternative features illustrated in FIGS. **17** to **26**.

(91) It goes without saying that in all ramped engagements between two components described in the above embodiments there may be just one ramp on one or the other component or there may be ramps on both components without significantly influencing the effect of the ramped engagement.

Claims

1. A method comprising: proximally moving a button relative to a housing of an auto-injector to disengage a first opening of a plunger rod of the auto-injector from a sleeve of the auto-injector by a radially inward deflection, the first opening being formed on a distal portion of the plunger rod and extending radially inward from an outer surface of the distal portion of the plunger rod, the plunger rod comprising (i) a transverse portion in from which the distal portion extends-from, and (ii) a proximal portion that extends proximally from the transverse portion, wherein an axial length of the proximal portion is greater than an axial length of the distal portion, and the distal portion defines a second opening such that, when the plunger rod is viewed in isolation, an inner portion of a distal side of the transverse portion that is radially inward of the distal portion of the plunger rod

is viewable from a distal end of the plunger rod along a longitudinal axis of the plunger rod; and after the first opening of the plunger rod has disengaged from the sleeve, proximally moving the plunger rod relative to the sleeve by a proximally-directed biasing force of a first compression spring that is disposed around the distal portion of the plunger rod and engaged to the transverse portion such that the proximal portion of the plunger rod pushes a stopper within a syringe to dispense a medicament from the auto-injector, wherein a radial gap between the first compression spring and a central region of the distal portion of the plunger rod is substantially constant along the central region of the distal portion, the central region is proximal of the first opening, and the central region spans at least one third of the axial length of the distal portion of the plunger rod.

2. The method of claim 1, comprising distally moving the sleeve relative to the housing to retract a needle of the syringe into the housing after the medicament has been dispensed from the auto-injector.
3. The method of claim 2, comprising using a second compression spring of the auto-injector to distally move the sleeve relative to the housing to retract the needle of the syringe into the housing, wherein a diameter of the second compression spring is greater than a diameter of the first compression spring.
4. The method of claim 1, wherein a thickness of a sidewall of the distal portion of the plunger rod is substantially constant throughout the central region of the distal portion.
5. The method of claim 1, wherein the plunger rod is configured such that, when the plunger rod is viewed in a cross-sectional plane, the distal portion of the plunger rod comprises two distally-extending members that are spaced apart from one another in a direction perpendicular to the longitudinal axis of the housing plunger rod.
6. The method of claim 1, wherein the first opening extends completely through a sidewall of the distal portion.
7. The method of claim 1, wherein the medicament comprises a glucagon-like peptide-1 (GLP-1) or an analogue or derivative thereof from the syringe.
8. A method comprising: proximally moving a button relative to a housing of an auto-injector to deflect one or more flexible arms radially inward to disengage a distal portion of a plunger rod of the auto-injector from a sleeve of the auto-injector, the plunger rod comprising (i) a transverse portion in from which the distal portion extends and (ii) a proximal portion that extends proximally from the transverse portion, wherein a thickness of a sidewall of the distal portion of the plunger rod is substantially constant throughout a central region of the distal portion of the plunger rod, the central region spans at least one third of an axial length the distal portion, an axial length of the proximal portion is greater than the axial length of the distal portion, and the plunger rod is configured such that, when the plunger rod is viewed in a cross-sectional plane, the distal portion of the plunger rod comprises two distally-extending members that are spaced apart from one another in a direction perpendicular to a longitudinal axis of the housing; and after the distal portion of the plunger rod has disengaged from the sleeve, proximally moving the plunger rod relative to the sleeve by a proximally-directed biasing force of a first compression spring that is disposed around the distal portion of the plunger rod and engaged to the transverse portion such that the proximal portion of the plunger rod pushes a stopper within a syringe to dispense a medicament from the auto-injector, wherein a radial gap between the first compression spring and the central region of the distal portion of the plunger rod is substantially constant along the central region.
9. The method of claim 8, comprising distally moving the sleeve relative to the housing to retract a needle of the syringe into the housing after the medicament has been dispensed from the auto-injector.
10. The method of claim 9, comprising using a second compression spring of the auto-injector to distally move the sleeve relative to the housing to retract the needle of the syringe into the housing, wherein a diameter of the second compression spring is greater than a diameter of the first compression spring.

11. The method of claim 8, wherein the distal portion defines a second opening such that, when the plunger rod is viewed in isolation, an inner portion of a distal side of the transverse portion that is radially inward of the distal portion of the plunger rod is viewable from a distal end of the plunger rod along a longitudinal axis of the plunger rod.
12. The method of claim 8, wherein a distal region of the distal portion of the plunger rod comprises a first opening that extends radially inward from an outer surface of the distal portion of the plunger rod, and the sleeve is configured to releasably engage a wall of the first opening to releasably hold the plunger rod in an initial position relative to the sleeve.
13. The method of claim 12, wherein the first opening extends completely through the sidewall of the distal portion.
14. The method of claim 8, wherein the medicament comprises a glucagon-like peptide-1 (GLP-1) or an analogue or derivative thereof from the syringe.
15. A method comprising: removing a cap from a proximal end of an auto-injector to uncover a needle of a syringe of the auto-injector while the syringe remains in an initial position within the auto-injector; after removing the cap, proximally moving a button relative to a housing of the auto-injector to disengage a distal portion of a plunger rod of the auto-injector from a sleeve of the auto-injector, the plunger rod comprising (i) a transverse portion from which the distal portion extends and (ii) a proximal portion that extends proximally from the transverse portion, wherein the distal portion defines an axially-extending opening such that when the plunger rod is viewed in isolation a radially-inward portion of a distal side of the transverse portion that is radially inward of the distal portion is viewable from a distal end of the plunger rod, an axial length of the proximal portion is greater than an axial length of the distal portion, a distal region of the distal portion of the plunger rod comprises a transverse opening that extends radially inward from an outer surface of the distal portion of the plunger rod, and the sleeve is configured to releasably engage a wall of the transverse opening to releasably hold the plunger rod in a first position relative to the sleeve; and after the distal portion of the plunger rod has disengaged from the sleeve, proximally moving the plunger rod relative to the sleeve by a proximally-directed biasing force of a first compression spring that is disposed around the distal portion of the plunger rod and engaged to the transverse portion such that the proximal portion of the plunger rod pushes a stopper within the syringe to dispense a medicament from the auto-injector, wherein a radial gap between the first compression spring and a central region of the distal portion of the plunger rod is substantially constant along the central region, the central region spanning at least one third of the axial length of the distal portion of the plunger rod.
16. The method of claim 15, comprising distally moving the sleeve relative to the housing to retract the needle of the syringe into the housing after the medicament has been dispensed from the auto-injector.
17. The method of claim 16, comprising using a second compression spring of the auto-injector to distally move the sleeve relative to the housing to retract the needle of the syringe into the housing, wherein a diameter of the second compression spring is greater than a diameter of the first compression spring.
18. The method of claim 15, wherein a thickness of a sidewall of the distal portion of the plunger rod is substantially constant throughout the central region of the distal portion of the plunger rod.
19. The method of claim 15, wherein the transverse opening extends completely through the distal portion.
20. The method of claim 15, wherein the medicament comprises a glucagon-like peptide-1 (GLP-1) or an analogue or derivative thereof.
21. A method comprising: proximally moving a button relative to a housing of an auto-injector to allow a distal portion of a plunger rod of the auto-injector to disengage from a sleeve of the auto-injector by a radially inward deflection, the distal portion of the plunger rod extending distally from a transverse portion of the plunger rod; after the distal portion of the plunger rod has disengaged

from the sleeve, proximally moving the plunger rod relative to the sleeve by a proximally-directed biasing force of a first compression spring such that a proximal portion of the plunger rod pushes a stopper within a syringe of the auto-injector to dispense a medicament from the auto-injector, the proximal portion extending proximally from the transverse portion of the plunger rod; and using a second compression spring to retract a needle of the syringe into the housing after the medicament has been dispensed from the auto-injector, wherein the first compression spring is disposed around the distal portion and engaged to the transverse portion to proximally bias the plunger rod relative to the sleeve such that a radial gap between an inner surface of the first compression spring and an outer surface of the distal portion of the plunger rod is substantially constant along a central region of the distal portion of the plunger rod, the central region spanning at least one third of an entire axial length of the distal portion of the plunger rod.

22. The method of claim 21, comprising distally moving the sleeve relative to the housing to retract the needle of the syringe into the housing after the medicament has been dispensed from the auto-injector.

23. The method of claim 21, wherein a thickness of a sidewall of the distal portion of the plunger rod is substantially constant throughout the central region of the distal portion of the plunger rod.

24. The method of claim 21, wherein a distal region of the distal portion of the plunger rod comprises a first opening, and the sleeve is configured to releasably engage the first opening to releasably hold the plunger rod in an initial position relative to the sleeve.

25. The method of claim 24, wherein the first opening extends completely through the distal portion.

26. The method of claim 21, wherein the medicament comprises a glucagon-like peptide-1 (GLP-1) or an analogue or derivative thereof.

27. The method of claim 21, wherein a diameter of the second compression spring is greater than a diameter of the first compression spring.

28. The method of claim 21, comprising removing a cap from a proximal end of the auto-injector to uncover the needle of the syringe of the auto-injector while the syringe remains in an initial position within the auto-injector.

29. The method of claim 21, wherein the plunger rod is configured such that, when the plunger rod is viewed in a cross-sectional plane, the distal portion of the plunger rod comprises two distally-extending members that are spaced apart from one another in a direction perpendicular to a longitudinal axis of the plunger rod, and each of the two distally-extending members are configured to releasably engage the sleeve to hold the plunger rod in an initial position relative to the sleeve.
