

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415402
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Stoia; Jonathan et al.

Infotainment system with air-vent control

Abstract

An air vent assembly includes a cover member having an inlet for allowing a flow of air to enter the cover member. The cover member also has a vent extending from the inlet for allowing a flow of air to exit the cover member. The vent includes a first vent portion, and a second vent portion located adjacent to the first vent portion. The first vent portion has a first set of flow guiding vanes disposed therein. The second vent portion has a second set of flow guiding vanes disposed therein. Each of the vanes is spaced apart from one another and pivotally coupled to a pair of opposing walls of the cover member. The first and second sets of flow guiding vanes are independently moveable with respect to each other using an actuating mechanism for providing a variety of flow-guiding positions one of which includes a split flow-guiding position.

Inventors: Stoia; Jonathan (Santa Clara, CA), Berthelet; Christopher (Berkeley, CA)

Applicant: Tesla, Inc. (Palo Alto, CA)

Family ID: 1000008819501

Assignee: Tesla, Inc. (Austin, TX)

Appl. No.: 17/001523

Filed: August 24, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200384831 A1	Dec. 10, 2020

Related U.S. Application Data

division parent-doc US 15374035 20161209 US 10752088 child-doc US 17001523

Publication Classification

Int. Cl.: B60H1/00 (20060101); B60H1/34 (20060101)

U.S. Cl.:

CPC B60H1/00985 (20130101); B60H1/00757 (20130101); B60H1/00871 (20130101); B60H1/3421 (20130101); B60H1/345 (20130101); B60H2001/3471 (20130101)

Field of Classification Search

CPC: B60H (1/00985); B60H (1/00757); B60H (1/00871); B60H (1/3421); B60H (1/345); B60H (2001/3471)

USPC: 454/155

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2293065	12/1941	Kiczales	454/335	F24F 13/15
5080002	12/1991	Soethout	454/313	B60H 1/00871
5364303	12/1993	Terry	N/A	N/A
5470276	12/1994	Burnell	454/319	F24F 13/075
5520579	12/1995	Saida	N/A	N/A
5766069	12/1997	Baek	454/153	B60H 1/345
9283829	12/2015	Waller	N/A	N/A
10752088	12/2019	Stoia et al.	N/A	N/A
2002/0094744	12/2001	Cheng	N/A	N/A
2002/0094774	12/2001	Demerath	N/A	N/A
2003/0050001	12/2002	Kamio	454/155	B60H 1/345
2007/0037505	12/2006	Wang	N/A	N/A
2010/0163633	12/2009	Barrett	N/A	N/A
2012/0330507	12/2011	Auner	701/36	B60H 1/00985
2015/0094862	12/2014	Choi et al.	N/A	N/A
2016/0259351	12/2015	Barrett et al.	N/A	N/A
2016/0313025	12/2015	Nemoto	N/A	F24F 13/1426
2017/0291469	12/2016	Romero Regalado	N/A	B60H 1/00985
2018/0162199	12/2017	Stoia et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1924735	12/2006	CN	N/A
102231076	12/2010	CN	N/A

203110886	12/2012	CN	N/A
105358202	12/2015	CN	N/A
105711374	12/2015	CN	N/A
105745101	12/2015	CN	N/A
106183812	12/2015	CN	N/A
110049889	12/2018	CN	N/A
114590109	12/2021	CN	N/A
19943822	12/2000	DE	N/A
20100740	12/2000	DE	N/A
10121909	12/2001	DE	N/A
10130951	12/2002	DE	N/A
102004053212	12/2005	DE	N/A
202011050523	12/2011	DE	N/A
102012021519	12/2013	DE	B60H 1/00871
102014209247	12/2013	DE	N/A
202016103388	12/2015	DE	N/A
1223061	12/2001	EP	N/A
3551487	12/2022	EP	N/A
4279303	12/2022	EP	N/A
40067597	12/2024	HK	N/A
61-63641	12/1985	JP	N/A
61-98940	12/1985	JP	N/A
H0482647	12/1991	JP	N/A
04-82647	12/1991	JP	N/A
05-40007	12/1992	JP	N/A
11-83152	12/1998	JP	N/A
2002-293133	12/2001	JP	N/A
2003-083601	12/2002	JP	N/A
2007-170693	12/2006	JP	N/A
2008-265675	12/2007	JP	N/A
2014-069770	12/2013	JP	N/A
2015-009615	12/2014	JP	N/A
2016-032958	12/2015	JP	N/A
2013045004	12/2012	WO	N/A
2018106351	12/2017	WO	N/A

OTHER PUBLICATIONS

Annex to the invitation to pay additional fees and provisional opinion; International Application No. PCT/US2017/058015; Jan. 31, 2018; 6 pgs. cited by applicant

International Search Report and Written Opinion; International Application No. PCT/US2017/058015; Mar. 21, 2018; 14 pgs. cited by applicant

“Chinese Application Serial No. 202210369577.4, Office Action mailed Mar. 5, 2024”, w English Translation, 20 pgs. cited by applicant

“European Application Serial No. 23200500.9, Extended European Search Report mailed Mar. 11, 2024”, 7 pgs. cited by applicant

“International Application Serial No. PCT US2017 058015, International Preliminary Report on Patentability mailed Jun. 20, 2019”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Restriction Requirement mailed Jun. 13, 2018”, 7 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Response filed Jul. 30, 2018 to Restriction Requirement mailed Jun. 13, 2018”, 9 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Non Final Office Action mailed Nov. 29, 2018”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Response filed Mar. 22, 2019 to Non Final Office Action mailed Nov. 29, 2018”, 16 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Final Office Action mailed May 2, 2019”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Response filed Jul. 2, 2019 to Final Office Action mailed May 2, 2019”, 16 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Advisory Action mailed Jul. 15, 2019”, 3 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Non Final Office Action mailed Nov. 1, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Response filed Feb. 28, 2020 to Non Final Office Action mailed Nov. 1, 2019”, 13 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Notice of Allowance mailed Apr. 16, 2020”, 8 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Notice of Allowance mailed Jun. 15, 2020”, 5 pgs. cited by applicant

“U.S. Appl. No. 15/374,035, Notice of Allowance mailed Jun. 25, 2020”, 3 pgs. cited by applicant

“Chinese Application Serial No. 202210369577.4, Response filed May 6, 2024 to Office Action mailed Mar. 5, 2024”, w current English claims, 19 pgs. cited by applicant

“Chinese Application Serial No. 202210369577.4, Office Action mailed May 18, 2023”, W English Translation, 30 pgs. cited by applicant

“Chinese Application Serial No. 202210369577.4, Office Action mailed Nov. 13, 2023”, W English Translation, 25 pgs. cited by applicant

“Chinese Application Serial No. 202210369577.4, Response filed Sep. 21, 2023 to Office Action mailed May 18, 2023”, WO English Claims, 10 pgs. cited by applicant

“Chinese Application Serial No. 202210369577.4, Response filed Jan. 29, 2024 to Office Action mailed Nov. 13, 2023”, WO English Claims, 12 pgs. cited by applicant

“European Application Serial No. 17794592.0, Response to Communication pursuant to Rules 161(1) and 162 EPC filed Jan. 23, 2020”, 17 pgs. cited by applicant

“European Application Serial No. 17794592.0, Communication Pursuant to Article 94(3) EPC mailed Apr. 15, 2021”, 6 pgs. cited by applicant

“European Application Serial No. 17794592.0, Response filed Aug. 12, 2021 to Communication Pursuant to Article 94(3) EPC mailed Apr. 15, 2021”, 43 pgs. cited by applicant

“European Application Serial No. 17794592.0, Communication Pursuant to Article 94(3) EPC mailed Jan. 25, 2022”, 6 pgs. cited by applicant

“European Application Serial No. 17794592.0, Response filed May 17, 2022 to Communication Pursuant to Article 94(3) EPC mailed Jan. 25, 2022”, 44 pgs. cited by applicant

“European Application Serial No. 17794592.0, Notification Pursuant to Rule 79(1) mailed Sep. 25, 2024”, 3 pgs. cited by applicant

“European Application No. 17794592.0, Communication of a notice of opposition dated Jul. 22, 2024”, (Jul. 24, 2024), 73 pgs. cited by applicant

“European Application Serial No. 23200500.9, Response filed Oct. 10, 2024 Extended European Search Report mailed Mar. 11, 2024”, 54 pgs. cited by applicant

“European Application Serial No. 17794592.0, Summons to Attend Oral Proceedings mailed Feb. 20, 2025”, 13 pgs. cited by applicant

“”, Machine translation of JP 2002-293133 A. cited by applicant

“”, machine translation of JP 2008-265675 A. cited by applicant

Background/Summary

(1) This application is a divisional application of U.S. application Ser. No. 15/374,035, entitled “Infotainment System with Air-Vent Control”, filed on Dec. 9, 2016, and issued as U.S. Pat. No. 10,752,088, each of which are hereby incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates to an infotainment system that controls operation of an HVAC system in order to control air flow within a cabin space of a vehicle. More particularly, the present disclosure relates to an air vent assembly of an HVAC system that can be electronically controlled using an infotainment system.

BACKGROUND

(2) It is well known in the art to provide an air vent assembly for delivering air from an HVAC system to a cabin space of a vehicle. In many cases, conventional air vent assemblies lack choices of desired air flow to ensure driver and passenger comfort when seated within the cabin space of the vehicle. Also, in other cases, many traditionally known air vent assemblies are typically controlled with input devices including, but not limited to, physical buttons and/or knobs thus making operation of the air vent assembly dependent upon a proper working condition of such input devices. However, as air flow within the vehicle is an important aspect to creating a comfortable environment for the driver and passengers of the vehicle, ensuring the reliability of the HVAC system, and in particular, a reliability of the air vent assembly may be desired. In addition, traditionally, vehicles have multiple vents for each of the driver and/or passenger. However, dashboard space is often at a premium due to other considerations, such as a larger windshield or room for meters.

(3) Hence, there is a need for an air vent assembly that overcomes one or more of the aforementioned drawbacks. Further, there is need for improved control of the air vent assembly through an infotainment system which allows for easy and intuitive control to facilitate the desired condition of the cabin space within the vehicle.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1 illustrates an interior of a vehicle showing the air vent assembly of an HVAC system that is capable of being controlled by an infotainment system according to certain embodiments of the invention.

(2) FIG. 2 illustrates an interface of the infotainment system showing a variety of high-level menu options according to certain embodiments of the invention.

(3) FIG. 3 illustrates an interface of the infotainment system showing a variety of low-level menu options for controlling the HVAC system according to certain embodiments of the invention.

(4) FIG. 4 illustrates an exploded top perspective view of an air vent assembly of the HVAC system according to certain embodiments of the invention.

(5) FIG. 5 illustrates an assembled top perspective view of the air vent assembly according to certain embodiments of the invention.

(6) FIG. 6 illustrates a partially assembled top perspective view of the air vent assembly without a cover member according to certain embodiments of the invention.

(7) FIG. 7 illustrates a side perspective view of the air vent assembly without the cover member

according to certain embodiments of the invention.

(8) FIG. 8 illustrates a top view of the air vent assembly showing vanes disposed in a vane closeout position according to certain embodiments of the invention.

(9) FIG. 9 illustrates a bottom view of the air vent assembly showing vanes disposed in a rightward flow-guiding position according to certain embodiments of the invention.

(10) FIG. 10 illustrates a bottom view of the air vent assembly showing vanes disposed in an onward flow-guiding position according to certain embodiments of the invention.

(11) FIG. 11 illustrates a bottom view of the air vent assembly showing vanes disposed in a leftward flow-guiding position according to certain embodiments of the invention.

(12) FIG. 12 illustrates a bottom view of the air vent assembly showing vanes disposed in an onward flow-guiding position according to certain embodiments of the invention.

(13) FIG. 13 illustrates a bottom view of the air vent assembly showing vanes disposed in a split flow-guiding position according to certain embodiments of the invention.

(14) FIG. 14A illustrates a cam-groove geometries for the first and second actuating members of the air vent assembly according to certain embodiments of the invention.

(15) FIG. 14B illustrates a cam-groove geometries for the first and second actuating members pursuant to the air vent assembly of FIG. 4 according to certain embodiments of the invention.

(16) Embodiments of the present disclosure and their advantages are best understood by referring to the detailed description that follows. It should be appreciated that like reference numerals are used to identify like elements illustrated in one or more of the figures, wherein showings therein are for purposes of illustrating embodiments of the present disclosure and not for purposes of limiting the same.

DETAILED DESCRIPTION

(17) The present disclosure relates to air vent assemblies. More particularly, the present disclosure relates to a particular air vent assembly and an infotainment system that controls an HVAC system, including the air vent assembly, in order to control air flow within a cabin space of a vehicle.

(18) The air vent assembly according to the present disclosure introduces a new way of delivering airflow to a user. According to certain embodiments, the air vent assembly includes a first vent portion placed in front of the driver and a second vent portion that is placed in front of the passenger. These vent portions may be elongated as compared to traditionally known designs of air vent assemblies in that they have longer, more linear vents instead of more circular or boxy vents. Also, each of the vent portions from the air vent assembly of the present disclosure typically includes more than one vent for each of the driver and passenger.

(19) Embodiments of the present disclosure enhance the capabilities of this air vent assembly to provide air flow in a leftward, rightward, onward, and a split configuration using a single rotary actuator. In certain embodiments, the user interface may also allow a user to define the degree to which the vents may cause air to flow in the rightward, leftward, or split direction. In certain other embodiments, the infotainment display may be configured to provide pre-defined degrees of movement to the vents for causing air to flow around the driver or passenger.

(20) According to certain embodiments, the driver and/or the passenger may control the vents using menu options provided on the user interface of the infotainment device. Some of the menu options provided on the user interface when actuated may configure the rotary actuator to close the vents, or cause the vents to accomplish a rightward air flow, a leftward air flow, an onward air flow, or a split air flow.

(21) According to certain embodiments, the air vent assembly includes an actuating mechanism having a single rotary actuator therein for controlling a pair of actuating members—a first actuating member and a second actuating member. Each actuating member can control half of the vanes, although in certain other embodiments, each actuating member may control more or less than half of the vanes provided in the vent portions of the air vent assembly. Using the pair of actuating members together with the single rotary actuator, the vanes can be rotated about their respective

rotational axes to close, or cause air to flow in the leftward, rightward, onward, or a split flow configuration in which flow of air is directed around the driver and/or the passenger of the vehicle. In certain embodiments, the user customizes the airflow, for example, the specific direction of the airflow. This can allow for a more comfortable experience for the occupants of a vehicle. For example, certain occupants may desire for air to be directed towards themselves while other occupants may desire the temperature of the vehicle cabin to be set to a certain value without having air directly impinging on themselves.

(22) According to certain embodiments, the actuating mechanism includes a cam member that is rotatively driven by the rotary actuator in a range of 180 degrees, which in other embodiments could include other ranges of angular motion for accomplishing a movement of the vanes in their respective vane-closeout position, leftward flow guiding position, onward flow guiding position, rightward flow-guiding position, and a split flow-guiding position.

(23) Reference will now be made in detail to specific aspects or features, examples of which are illustrated in the accompanying drawings. Wherever possible, corresponding or similar reference numbers will be used throughout the drawings to refer to the same or corresponding parts.

(24) FIG. 1 illustrates an interior **102** of a vehicle **100** according to certain embodiments of the invention. As shown, a dash console **104** is disposed in an anterior region **106** of the vehicle **100**. The dash console **104** is configured to provide a host of spaces for fitment of various devices including, but not limited to, an infotainment device **108**, an air vent assembly **112** of an HVAC system **110**, a speedometer **114**, an odometer **116**, a stereo system **118**, and other like devices provided to the vehicle **100** depending on specific requirements of a vehicular application. Embodiments of the present disclosure are directed to the air vent assembly **112** of the HVAC system **110** and the infotainment device **108** that is configured to operatively control, amongst other things, the movement of vanes **120** in the air vent assembly **112** of the HVAC system **110**.

(25) FIG. 2 illustrates an interface **206** of the infotainment device **108** showing a variety of high-level menu options **202** according to certain embodiments of the invention. Each of the menu options **202** is provided on the user interface **206** of a display **204** associated with the infotainment device **108**. This way, a user may select an appropriate menu option **202** on the user interface **206** of the infotainment device **108**. Consequently, a processor **208** of the infotainment device **108** detects the menu option **202** that is being selected by the user and provides appropriate control signals to a desired device present in the vehicle **100** and corresponding with the selected menu option **202** so that an operation of the desired device is controlled. As disclosed earlier in this embodiment, the user input is provided by selecting from the menu options **202** listed on the user interface **206**. According to certain other embodiments of this invention, the user can provide a voice command to the user interface **206** in lieu of physically selecting a menu option to control the air flow in vehicle **100**.

(26) As shown in the illustrated embodiment of FIG. 2, a host of high-level menu options **202** are shown provided on the user interface **206** of the infotainment device **108**. Each of these high-level menu options **202** are user selectable for controlling an operation of the desired device. For example, as shown in FIG. 2, a menu option **202a** when selected may be configured to direct the processor **208** to turn ON the stereo system **118**. Likewise, a menu option **202b** when selected may be configured to direct the processor **208** to turn ON a Bluetooth device while a menu option **202c** when selected by the user would direct the processor **208** to open a rear boot lid of the vehicle **100**. Similarly, a menu option **202d** when selected may configure the processor **208** to turn ON the HVAC system **110** of the vehicle **100**. Other menu options including, but not limited to, the menu options **202e** and **202f** may, additionally or optionally, be provided on the user interface **206** to facilitate AUX input at the stereo system **118** and enable navigation maps at the user interface **206** itself respectively.

(27) It may be noted that the processor **208** may be a single microprocessor or multiple microprocessors that include components for performing functions consistent with the present

disclosure. Numerous commercially available microprocessors can be configured to perform the functions of the processor **208** disclosed herein. It should be appreciated that the processor **208** could readily be embodied in a general purpose microprocessor capable of controlling numerous functions associated with each of the devices present in the vehicle **100**. The processor **208** may also include a memory, a secondary storage device, and any other components for running an application. Various circuits may be associated with the processor **208** such as power supply circuitry, a solenoid driver circuitry, a signal conditioning circuitry for e.g., an analog-to-digital converter circuitry, and other types of circuitry. Various routines, algorithms, and/or programs can be programmed within the processor **208** for execution thereof. Moreover, it should be noted that the processor **208** disclosed herein may be a stand-alone processor **208** or may be configured to co-operate with existing processor/s, for example, an electronic control module (ECM) (not shown) provided to the vehicle **100** to perform functions that are consistent with the present disclosure.

(28) Referring to FIG. **3**, a host of low-level menu options **302** are displayed on the user interface **206** of the infotainment device **108** in accordance with certain embodiments of the invention. In particular, the low-level menu options **302** shown in FIG. **3** may be displayed on the user interface **206** in response to the user having previously selected the HVAC menu option **202d** listed in the high-level menu options **202** from FIG. **2**. As shown in FIG. **3**, the low-level menu options **302** may include, but are not limited to, a temperature setting menu option **302f**, a menu option **302g** for enabling a recirculation mode of air conditioning in the vehicle **100**, a menu option **302h** for enabling climate control in the vehicle **100**.

(29) According to specific embodiments of this invention, at least some low-level menu options **302** are additionally provided to a user for particularly controlling the vanes **120** of the air vent assembly **112**. As shown in FIG. **3**, these low-level menu options **302** include a menu option **302a** for directing the vanes **120** to move to a vane closeout position, a menu option **302b** for directing the vanes **120** to move to a leftward flow-guiding position, a menu option **302c** for directing the vanes **120** to move to an onward flow-guiding position, a menu option **302d** for directing the vanes **120** to a rightward flow-guiding position, a menu option **302e** for directing the vanes **120** of the air vent assembly **112** to a partially-split flow-guiding position, and another menu option **302i** for directing the vanes **120** of the air vent assembly **112** to a fully-split flow-guiding position.

(30) Referring back to FIG. **1**, an air vent assembly **112** is shown typically disposed in front of the driver seat and front-passenger seat on the dash console **104**. Therefore, references to the flow-guiding positions of the vanes **120** such as closeout, leftward, rightward, onward, and split are to be construed as being taken in relation to the seats or occupants of the vehicle **100** who would typically be located in a front portion **124** of the vehicle **100**. Additional detail for each of the aforementioned flow-guiding positions appears below in the detailed description of the other figures.

(31) Moreover, although it is disclosed in the illustrated embodiment of FIG. **1** that two air vent assemblies are disposed on the dash console **104**—one in front of the driver seat and one in front of the passenger seat—it may be noted that the number and position of the air vent assembly **112** or assemblies within the interior **102** of the vehicle **100** is non-limiting of this invention. Other alternative positions within the interior **102** of the vehicle **100** may include, but is not limited to, the center of the console, a right inner side of the vehicle **100**, a left inner side of the vehicle **100**, a top inner side of the vehicle **100**, or stretching from the right side of the vehicle **100** to the left side of the vehicle **100**. Such alternative positions may be contemplated depending on specific requirements of a vehicular application.

(32) FIG. **4** shows an exploded top perspective view of the air vent assembly **112** in accordance with certain embodiments of this invention. As shown, the air vent assembly **112** includes a cover member **402**. An outer shape and size of the cover member **402** may be selected so as to correspond with a size and shape of a space provided by the dash console **104** of the vehicle **100** (refer to FIG. **1**). In instances where the air vent assembly **112** is to be installed in a location other than the space

provided by the dash console **104**, for example, the left inner side, the right inner side, or the top inner side of the vehicle **100**, the outer size and shape of the cover member **402** may be suitably selected to correspond with a size and shape of that space.

(33) With continued reference to FIG. **4**, the cover member **402** has a pair of elongated walls **404a** and **404b** disposed in an opposing relation to one another. The cover member **402** has an inlet **406** defined on an aft side **408** thereof. The inlet **406** allows a flow of air to enter the cover member **402**, particularly, when the HVAC system **110** is turned ON in response to the user input at the interface being indicative of the HVAC menu option **202d**.

(34) The cover member **402** also has a vent **410** extending from the inlet **406** toward a fore side **412** of the cover member **402**. The vent **410** is configured to allow a flow of air to exit the cover member **402**. The vent **410** consists of a first vent portion **410a** and a second vent portion **410b** located adjacent to the first vent portion **410a**. As shown, the first vent portion **410a** has vanes **120** disposed therein. For purposes of simplicity, the vanes **120** from the first vent portion **410a** are hereinafter referred to as ‘the first set of flow-guiding vanes’ and denoted with like alpha-numeral ‘**120a**’. Likewise, the second vent portion **410b** has a second set of flow-guiding vanes disposed therein, which for purposes of simplicity and differentiation from the first set of flow-guiding vanes **120a** is denoted with like alpha-numeral ‘**120b**’.

(35) In the illustrated embodiment of FIG. **4**, the first set of flow-guiding vanes **120a** is shown to consist of five vanes **120**. Likewise, the second set of flow-guiding vanes **120b** consists of five vanes **120** therein. It may be noted that a number and distribution of vanes **120** between the first and second sets of flow-guiding vanes **120a**, **120b** is merely a matter of design choice and hence, the number and distribution of vanes **120** between the first and second sets of flow-guiding vanes **120a**, **120b** may vary from one application to another depending on specific requirements of an application. Moreover, although the number of vanes **120** in the air vent assembly **112** of the present disclosure is limited to five in each of the first and second sets of flow-guiding vanes **120a**, **120b**, it will be acknowledged by persons skilled in the art that an unequal number of vanes **120** may be present in the first and second sets of flow-guiding vanes **120a**, **120b** depending on specific requirements of an application.

(36) Further, each of the vanes **120** from the first and second set of flow-guiding vanes **120b** are spaced apart from one another. Moreover, the vanes **120** from the first and second vent portions **410a**, **410b** extend at least partially between the aft and fore sides **408**, **412** of the cover member **402**. Furthermore, each vane **120** from the first and second sets of flow-guiding vanes **120a**, **120b** are pivotally coupled to the pair of mutually opposing elongated walls **404a**, **404b** of the cover member **402**. In the illustrated embodiment of FIGS. **4-7**, three sets of cover plates **418** are provided to establish a pivotal connection of each vane **120** from the first and second sets of flow-guiding vanes **120a**, **120b** with the pair of mutually opposing elongated walls **404a**, **404b** of the cover member **402**. As best shown in FIG. **4**, each pair of mutually opposing cover plates **418** defines multiple corresponding recesses **420**. Each of the recesses **420** on the cover plates **418** receives a pivot pin **422** associated with the vane from either the first or second set of flow-guiding vanes **120b**.

(37) According to certain embodiments of this invention, the first set of flow-guiding vanes **120a** and the second set of flow-guiding vanes **120b** are independently moveable with respect to each other using an actuating mechanism **424** that is coupled to each of the first and second sets of flow-guiding vanes **120a**, **120b**. The actuating mechanism **424** includes a first actuating member **426**. The first actuating member **426** has a first base portion **428**, and a first link member **430** extending from the first base portion **428**. The first link member **430** is engaged with each vane **120** from the first set of flow-guiding vanes **120a**. The first link member **430** is operable to pivot each vane **120** from the first set of flow-guiding vanes **120a** about its corresponding rotational axis AA’.

(38) Referring to FIGS. **4-7**, the actuating mechanism **424** further includes a second actuating member **434** located adjacent to the first actuating member **426**. The second actuating member **434**

has a second base portion **436** that is disposed below the first base portion **428** of the first actuating member **426**. The second actuating member **434** also has a second link member **438** extending from the second base portion **436**. The second link member **438** is pivotally engaged with each vane **120** from the second set of flow-guiding vanes **120b**. The second link member **438** is selectively operable to pivot each vane **120** from the second set of flow-guiding vanes **120b** about its corresponding rotational axis AA'.

(39) Additionally, the first base portion **428** of the first actuating member **426** defines a first cam groove **440** therein. The first cam groove **440** includes a first portion **442**, a second portion **444** spaced-apart from the first portion **442**, and a mid-portion **446** disposed between the first and second portions **442**, **444**. As shown, the mid-portion **446** of the first cam groove **440** is curved away from an axis BB' connecting the first and second portions **442**, **444** of the first cam groove **440**.

(40) The second base portion **436** of the second actuating member **434** defines a second cam groove **448** therein. The second cam groove **448** includes a first portion **450**, a second portion **452** spaced-apart from the first portion **450**, and a mid-portion **454** disposed between the first and second portions **450**, **452**. As shown, the mid-portion **454** of the second cam groove **448** is curved away from an axis CC' connecting the first and second portions **450**, **452** of the second cam groove **448**. Additionally, the second cam groove **448** includes a third portion **456** extending from a distal end of the second portion **452**. The third portion **456** is arcuately disposed in relation to the second portion **452**. According to certain embodiments, the first, second, and mid-portions **442-446**, **450-454** of the first and second cam grooves **440**, **448** correspond with one another. However, it may be noted that other configurations of the first and second cam grooves **440**, **448** may be implemented by persons skilled in the art to realize the features of this invention.

(41) The actuating mechanism **424** further includes a rotary actuator **458** communicably coupled with the processor **208** of the infotainment device **108**. The actuating mechanism **424** further includes a cam member **460** having a central portion **462** coupled to the rotary actuator **458**. The rotary actuator **458** operatively rotates the cam member **460** about its central portion **462** in response to control signal output by the processor **208**. The cam member **460** also has a primary pin **464** and a secondary pin **466**. The primary pin **464** is disposed at a first end **468** of the cam member **460**. The secondary pin **466** is disposed at a second end **470** of the cam member **460**. The primary pin **464** is disposed in engagement with the first and second cam grooves **440**, **448** from respective ones of the first and second actuating members **426**, **434**.

(42) Additionally, as best shown in FIG. 6, the second link member **438** of the second actuating member **434** is slidably coupled to the first link member **430** of the first actuating member **426** with the help of a slot-pin arrangement in which each of the slots are denoted by numeral **414** while each of the sliding pins are denoted by numeral **416**. Moreover, as best shown in FIG. 6, the second link member **438** may be resiliently biased by a spring **472** coupled to the cover member **402**. The spring **472** facilitates a default position for each of the first and second actuating members **426**, **434** which in turn would cause the first and second sets of flow-guiding vanes **120a**, **120b** to be generally disposed in their respective default positions. The spring may assist secondary pin **466** in pulling the to pull the second link member **438** back to a centralized location. Further, when no user input is received at the user interface **206** for turning ON the HVAC system **110** or for effecting a particular flow-guiding position other than the vane closeout position, the default position of the first and second actuating members **426**, **434** may be effected by the spring **472** as the spring **472** generally biases the first and second actuating members **426**, **434** into their respective default positions, which according to a particular embodiment of this disclosure, is the vane closeout position. Alternatively, it has also been contemplated that when a user input is received vis-à-vis the high-level menu option **202d** for turning OFF the HVAC system **110**, the spring **472** offers a bias force to each of the first and second actuating members **426**, **434** such that the first and second sets of flow-guiding vanes **120a**, **120b** are disposed in their respective vane closeout positions. It

may be noted that the terms 'vane closeout position' disclosed herein may be regarded as a position in which the vanes **120** from the first and second sets of flow-guiding vanes **120a**, **120b** fully obstruct the flow of air from the air vent assembly **112** towards the interior **102** of the vehicle **100**.

(43) According to certain embodiments, a rotation of the cam member **460** about an axis DD' of the central portion **462** causes an engagement of the primary pin **464** with one of the first, second, and mid-portions **442-446**, **450-454** of respective ones of the first and second cam grooves **440**, **448** for positioning the first and second sets of flow-guiding vanes **120a**, **120b** in one of: the vane closeout position, the rightward flow-guiding position, the onward flow-guiding position, and the leftward flow-guiding position. Explanation to each of these functions is made in the appended disclosure.

(44) According to specific embodiments as shown in FIG. **8**, when the primary pin **464** of the cam member **460** is operatively moved into engagement with the first portions **442**, **450** of respective ones of the first and second cam grooves **440**, **448** (refer to FIG. **4**) and is located distally away from the mid-portions **446**, **454** of respective ones of the first and second cam grooves **440**, **448**, a corresponding movement of the first and second actuating members **426**, **434** causes respective ones of the first and second sets of flow-guiding vanes **120a**, **120b** to be positioned in their respective vane close-out positions.

(45) According to other embodiments as shown in FIG. **9**, when the primary pin **464** of the cam member **460** is operatively moved into engagement with the first portions **442**, **450** of respective ones of the first and second cam grooves **440**, **448** (refer to FIG. **4**) so as to be located partway along a length of the first portions **442**, **450** of respective ones of the first and second cam grooves **440**, **448**, a corresponding movement of the first and second actuating members **426**, **434** causes respective ones of the first and second sets of flow-guiding vanes **120a**, **120b** to be positioned in their respective rightward flow-guiding positions. It may be noted that the flow-guiding vanes **120a**, **120b** as shown in FIG. **9** are pointing in a leftward and downward direction as the view of FIG. **9** is the bottom view of the air vent assembly **112**.

(46) According to other embodiments as shown in FIG. **10**, when the primary pin **464** of the cam member **460** is operatively moved into engagement with the first portions **442**, **450** of respective ones of the first and second cam grooves **440**, **448** (refer to FIG. **4**) so as to be located proximal to the mid-portions **446**, **454** of respective ones of the first and second cam grooves **440**, **448**, a corresponding movement of the first and second actuating members **426**, **434** causes respective ones of the first and second sets of flow-guiding vanes **120a**, **120b** to be positioned in their respective onward flow-guiding positions.

(47) According to other embodiments as shown in FIG. **11**, when the primary pin **464** of the cam member **460** is operatively moved into engagement with the mid-portions **446**, **454** of respective ones of the first and second cam grooves **440**, **448** (refer to FIG. **4**) and is located at a center of the mid-portions **446**, **454** of respective ones of the first and second cam grooves **440**, **448**, a corresponding movement of the first and second actuating members **426**, **434** causes respective ones of the first and second sets of flow-guiding vanes **120a**, **120b** to be positioned in their respective leftward flow-guiding positions. The flow-guiding vanes **120a**, **120b** as shown in FIG. **11** are pointing in a rightward and downward direction as the view of FIG. **9** is the bottom view of the air vent assembly **112**.

(48) According to other embodiments as shown in FIG. **12**, when the primary pin **464** of the cam member **460** is operatively moved into engagement with the mid-portions **446**, **454** of respective ones of the first and second cam grooves **440**, **448** (refer to FIG. **4**) so as to be located proximal to the second portions **444**, **452** of respective ones of the first and second cam grooves **440**, **448**, a corresponding movement of the first and second actuating members **426**, **434** causes respective ones of the first and second sets of flow-guiding vanes **120a**, **120b** to be positioned in their respective onward flow-guiding positions.

(49) According to certain embodiments, as shown in FIG. **13**, a rotation of the cam member **460** about the axis DD' of the central portion **462** causes a partially-split flow-guiding position, and if

the rotation is continued further a fully-split flow-guiding position. When the primary pin **464** engages with the second portion **442** of the first cam groove **440** to be located distally away from the mid-portions **446**, **454** of the first and second cam grooves **440**, **448**. In this instance, upon further rotation of the cam member **460**, the first set of flow-guiding vanes **120b** rotate about their respective rotational axes AA' towards a leftward flow-guiding position. As the second cam groove **448** comprises a third portion **456**, the primary pin **464** of the rotating cam member **460** does not cause the second set of flow-guiding vanes **120a** to rotate. Rather, the secondary pin **466** of the cam member **460** engages with a retainer groove **474** defined on the second base portion **436**, causing the vanes **120** from the second set of flow-guiding vanes **120b** to rotate about their respective rotational axes AA' towards a rightward flow-guiding position.

(50) For the purposes of this disclosure, the rightward and leftward flow-guiding positions of respective ones of the first and second sets of flow-guiding vanes **120a**, **120b** from the foregoing embodiments may be regarded as a split flow-guiding position in which angular positions of respective ones of the first and second flow-guiding vanes **120** may be dissimilar from angular positions of the first and second flow-guiding vanes **120** when both of the first and second flow-guiding vanes **120** are disposed in either of the leftward flow-guiding position or the rightward flow-guiding position. The terms 'partially-split flow-guiding position' disclosed herein is used to refer to a type of the split flow-guiding position in which the first and second sets of flow-guiding vanes **120a**, **120b** would be disposed at a first pre-defined angle with respect to one another. The first pre-defined angle disclosed herein may be, in an example, 45 degrees between the first and second sets of flow-guiding vanes **120a**, **120b**. In another example, the first pre-defined angle disclosed herein may be 60 degrees. The terms 'fully-split flow-guiding position' is however, another type of the split flow-guiding position in which the first and second sets of flow-guiding vanes **120a**, **120b** would be disposed at a second pre-defined angle with respect to one another, the second pre-defined angle being greater than the first pre-defined angle. In an example, if the first pre-defined angle is 45 degrees, then the second pre-defined angle may be implemented by way of a 90-degree angle between the first and second sets of flow-guiding vanes **120a**, **120b**. In another example, if the first pre-defined angle is 60 degrees, then the second pre-defined angle may be implemented by way of a 120-degree angle.

(51) In another embodiment, the first and second pre-defined angles may result in the two sets of vanes being asymmetric with respect to one another. By selecting pre-determined lengths of the first and second cam grooves **440**, **448**, and in particular, a pre-determined length of the third portion **456** of the second cam groove **448** to achieve other values of the second pre-defined angle, such values however being greater in relation to the first pre-defined angle. For example, if the first pre-defined angle is 45 degrees, then the second pre-defined angle may be implemented by way of a 60-degree angle between the first and second sets of flow-guiding vanes **120a**, **120b**. In another example, the first pre-defined angle may be 45 degrees while the second pre-defined angle is 120 degrees.

(52) According to certain other embodiments of this invention, the first and second pre-defined angles corresponding to the partially and fully split-flow-guiding positions of the first and second flow-guiding vanes **120** can be pre-defined to the user interface **206** by the user. For example, the user interface **206** of the infotainment device **108** can present to the user via other menu options (not shown)—a range of values for selecting each of the first and second pre-defined angles for subsequent implementation by the processor **208** for rotating the cam member **460** via the rotary actuator **458**.

(53) FIG. **14A** illustrates cam-groove geometries for the pair of actuating members of the air vent assembly according to certain other embodiments of the invention. FIG. **14A** illustrates a cam-groove geometry for the first actuating member **426** that is linear and a cam groove geometry for the second actuating member **434** that is curved so as to define a "J" shaped portion **478** therein. FIG. **14B** illustrates a different set of cam-groove geometries for the pair of actuating members

426, 434 of the air vent assembly **112** according to certain embodiments of the invention. FIG. **14B** illustrates a cam-groove geometry for the first actuating member **426** that is predominantly linear but includes a bend **480** and a cam-groove geometry for the second actuating member **434** that is curved in a “J” portion **482** and also includes a bend **484** in the linear portion **486** of the cam groove. The specific geometries of the cam grooves **490, 492** defined on the first and second actuating members **426, 434** may be different according to certain embodiments of the invention. (54) In both of the cam-groove geometries illustrated in FIGS. **14a** and **14b**, a portion of the cam-groove geometries is the same, and a portion of the cam-groove geometries is different. This allows for the single cam member **460** to cause the vanes **120** from both the first and second sets of flow-guiding vanes **120a, 120b** to move in the same direction when the cam member **460** engages the portion of the cam grooves that are of the same geometry and also allows the cam member **460** to move the vanes **120** such that the vanes **120** associated with the first set of flow-guiding vanes **120a** are in a different direction than the vanes **120** associated with the second set of flow-guiding vanes **120b** when the primary pin **464** engages with the dissimilar portions from respective cam grooves of the first and second actuating members **426, 434**. This is particularly important to produce the partial and full split flow-guiding positions disclosed herein.

(55) The specific configurations of the first and second actuating members **426, 434** described above to close the vanes **120** or move the vanes **120** from respective ones of the first and second sets of flow-guiding vanes **120a, 120b** into the leftward, rightward, and split flow-guiding position is non-limiting of this disclosure. Rather, it will be acknowledged by persons skilled in the art that various other mechanisms may be used in place of the first and second actuating members **426, 434** disclosed herein without deviating from the spirit of the present disclosure.

(56) The foregoing disclosure is not intended to limit the present disclosure to the precise forms or particular fields of use disclosed. As such, it is contemplated that various alternative embodiments and/or modifications to the present disclosure, whether explicitly described or implied herein, are possible in light of the disclosure. Having thus described embodiments of the present disclosure, a person of ordinary skill in the art will recognize that changes may be made in form and detail without departing from the scope of the present disclosure. Thus, the present disclosure is limited only by the claims.

(57) In the foregoing specification, the disclosure has been described with reference to specific embodiments. However, as one skilled in the art will appreciate, various embodiments disclosed herein can be modified or otherwise implemented in various other ways without departing from the spirit and scope of the disclosure. Accordingly, this description is to be considered as illustrative and is for the purpose of teaching those skilled in the art the manner of making and using various embodiments of the disclosed air vent assembly. It is to be understood that the forms of disclosure herein shown and described are to be taken as representative embodiments. Equivalent elements, materials, processes or steps may be substituted for those representatively illustrated and described herein. Moreover, certain features of the disclosure may be utilized independently of the use of other features, all as would be apparent to one skilled in the art after having the benefit of this description of the disclosure. Expressions such as “including”, “comprising”, “incorporating”, “consisting of”, “have”, “is” used to describe and claim the present disclosure are intended to be construed in a non-exclusive manner, namely allowing for items, components or elements not explicitly described also to be present. Reference to the singular is also to be construed to relate to the plural.

(58) Further, various embodiments disclosed herein are to be taken in the illustrative and explanatory sense, and should in no way be construed as limiting of the present disclosure. All joinder references (e.g., attached, affixed, coupled, connected, and the like) are only used to aid the reader's understanding of the present disclosure, and may not create limitations, particularly as to the position, orientation, or use of the systems and/or methods disclosed herein. Therefore, joinder references, if any, are to be construed broadly. Moreover, such joinder references do not necessarily

infer that two elements are directly connected to each other.

(59) Additionally, all numerical terms, such as, but not limited to, “first”, “second”, “third”, “primary”, “secondary”, “main” or any other ordinary and/or numerical terms, should also be taken only as identifiers, to assist the reader's understanding of the various elements, embodiments, variations and/or modifications of the present disclosure, and may not create any limitations, particularly as to the order, or preference, of any element, embodiment, variation and/or modification relative to, or over, another element, embodiment, variation and/or modification.

(60) It will also be appreciated that one or more of the elements depicted in the drawings/figures can also be implemented in a more separated or integrated manner, or even removed or rendered as inoperable in certain cases, as is useful in accordance with a particular application. Additionally, any signal hatches in the drawings/figures should be considered only as exemplary, and not limiting, unless otherwise specifically specified.

Claims

1. A system for controlling an air vent assembly within an HVAC system of a vehicle, the system comprising: an actuating mechanism for independent control of a first set of flow guiding vanes and a second set of flow guiding vanes, the actuating mechanism that comprises a single rotary actuator mechanically coupled to both the first set of flow guiding vanes and the second set of flow guiding vanes via a pair of actuating members comprising a first actuating member that comprises a first link member to engage with each vane of the first set of flow guiding vanes, and a second actuating member that comprises a second link member to engage with each vane of the second set of flow guiding vanes; a display; a processor in communication with the display; a user interface in communication with the processor, the user interface configured to accept one or more inputs from a selection of menu control options; wherein the processor is configured to cause display of a menu of control options; and wherein at least one of the menu control options is an option to independently and simultaneously control, via the single rotary actuator, a positioning of the first set of flow guiding vanes and the second set of flow guiding vanes not directly connected to the first set of flow guiding vanes and arranged to be adjacent to each other in an elongated linear vent opening of the air vent assembly of the HVAC system.
2. The system of claim 1, wherein the menu control options include options for positioning respective ones of the first and second sets of flow guiding vanes in one of: a vane closeout position, a leftward flow-guiding position, an onward flow-guiding position, a rightward flow-guiding position, a partially-split flow-guiding position, and a fully-split flow-guiding position.
3. The system of claim 2, wherein in response to selection of one or more inputs via the user interface, the first set of flow guiding vanes and the second set of flow guiding vanes are independently moved to a position selected from the group consisting of: the vane closeout position, the leftward flow-guiding position, the onward flow-guiding position, the rightward flow-guiding position, the partially-split flow-guiding position, and the fully-split flow-guiding position.
4. The system of claim 3, wherein when the first set of flow guiding vanes and the second set of flow guiding vanes are independently moved to the partially-split flow-guiding position, the first and second sets of flow guiding vanes are disposed in a first pre-defined angular position relative to one another; and when the first set of flow guiding vanes and the second set of flow guiding vanes are independently moved to the fully-split flow-guiding position, the first and second sets of flow guiding vanes are disposed in a second pre-defined angular position relative to one another, wherein the second pre-defined angular position is greater than the first pre-defined angular position.
5. The system of claim 4, wherein each of the first pre-defined angular position and the second pre-defined angular position is settable by a menu control option.
6. The system of claim 1, wherein the air vent assembly comprises: a cover member having: a pair

of elongated walls disposed in a mutually opposing relation to one another; and an inlet disposed on an aft side of the pair of mutually opposing elongated walls, the inlet configured to allow an entry of air into the cover member.

7. The system of claim 6, further comprising a vent extending from the inlet toward a fore side of the cover member, the vent configured to allow air to exit the cover member, the vent comprising: a first vent portion having the first set of flow guiding vanes disposed therein, each vane from the first set of flow guiding vanes pivotally coupled to the pair of mutually opposing elongated walls of the cover member; and a second vent portion located adjacent to the first vent portion, the second vent portion having the second set of flow guiding vanes disposed therein, each vane from the second set of flow guiding vanes pivotally coupled to the pair of mutually opposing elongated walls of the cover member.

8. The system of claim 1, wherein the one or more inputs from the selection of menu control options includes a voice command.

9. The system of claim 1, wherein the user interface comprises a touch screen.

10. The system of claim 1, wherein the at least one of the menu control options includes the option to independently and simultaneously control the positioning of the first set of flow guiding vanes and the second set of flow guiding vanes in the air vent assembly.

11. The system of claim 1, wherein the processor controls the rotary actuator based on a selected option.

12. The system of claim 1, wherein the actuating mechanism further comprises: a first actuating member comprising a first link member configured to engage with each vane of the first set of flow guiding vanes; and a second actuating member comprising a second link member configured to engage with each of the vanes from the second set of flow guiding vanes.

13. The system of claim 1, wherein the user interface is disposed at a mid-portion of a vehicle dash console.

14. The system of claim 1, wherein the single rotary actuator is located adjacent to a first non-rotary actuating member, and the first non-rotary actuating member is further arranged to be adjacent to a second non-rotary actuating member.

15. The system of claim 1, additionally comprising a cam member having a central portion adjacently coupled to the single rotary actuator.

16. A vehicle comprising: a system for controlling an air vent assembly within an HVAC system of the vehicle, the system comprising: an actuating mechanism for independent control of a first set of flow guiding vanes and a second of flow guiding vanes, the actuating mechanism that comprises a single rotary actuator mechanically coupled to both the first set of flow guiding vanes and the second set of flow guiding vanes via a pair of actuating members comprising a first actuating member that comprises a first link member to engage with each vane of the first set of flow guiding vanes, and a second actuating member that comprises a second link member to engage with each vane of the second set of flow guiding vanes; a processor; a user interface in communication with the processor, the user interface configured to accept one or more inputs associated with selection of menu control options; wherein the processor is configured to output a menu of options; and wherein at least one of the menu control options is an option to independently and simultaneously control, via the single rotary actuator, a positioning of the first set of flow guiding vanes and the second set of flow guiding vanes not directly connected to the first set of flow guiding vanes and arranged to be adjacent to each other in an elongated linear vent opening of the air vent assembly of the HVAC system.

17. The vehicle of claim 16, wherein in response to selection of one or more inputs associated with the menu control options, the first set of flow guiding vanes and the second set of flow guiding vanes are independently moved to a position selected from the group consisting of: a vane closeout position, a leftward flow-guiding position, an onward flow-guiding position, a rightward flow-guiding position, a partially-split flow-guiding position, and a fully-split flow-guiding position.

18. The vehicle of claim 16, wherein the user interface comprises a touch screen.
 19. The vehicle of claim 16, wherein the processor is operatively coupled to the rotary actuator.
 20. The vehicle of claim 16, wherein the processor controls the rotary actuator based on a selected option.
 21. The vehicle of claim 16, wherein the air vent assembly comprises: a cover member comprising an inlet; a vent extending from the inlet, the vent comprising the first set of flow guiding vanes and the second set of flow guiding vanes; and an actuating mechanism, configured to receive a control signal from the processor, operably coupled to each of the first set of flow guiding vanes and the second set of flow guiding vanes.
 22. The vehicle of claim 21, wherein the actuating mechanism comprises: a first actuating member comprising a first link member configured to engage with each vane of the first set of flow guiding vanes, wherein the rotary actuator is located adjacent to the first actuating member; and a second actuating member comprising a second link member configured to engage with each of the vanes from the second set of flow guiding vanes, such that the first set of flow guiding vanes and the second set of flow guiding vanes are capable of moving independently of one another, wherein the first actuating member is further arranged to be adjacent to the second actuating member.
 23. A vehicle comprising: a system for controlling an air vent assembly within an HVAC system of the vehicle, the system comprising: a processor; a user interface in communication with the processor, the user interface configured to accept one or more inputs associated with selection of menu control options; wherein the processor is configured to output a menu of options; wherein at least one of the menu options is an option to independently and simultaneously control a positioning of a first set of flow guiding vanes and a separate second set of flow guiding vanes not directly connected to the first set of flow guiding vanes and arranged to be adjacent to each other in a horizontal direction in an elongated linear vent opening of the air vent assembly of the HVAC system; an actuating mechanism, configured to receive a control signal from the processor, for independent control of the first set of flow guiding vanes and the second set of flow guiding vanes; wherein the actuating mechanism comprises: a single rotary actuator configured to receive the control signal from the processor; a pair of actuating members coupled with the single rotary actuator, the pair of actuating members including a first actuating member and a second actuating member; the first actuating member coupled with the single rotary actuator and comprising a first link member configured to engage with each vane of the first set of flow guiding vanes, wherein the single rotary actuator is located adjacent to the first actuating member; and a second actuating member coupled with the single rotary actuator and comprising a second link member configured to engage with each of the vanes from the second set of flow guiding vanes, such that the first set of flow guiding vanes and the second set of flow guiding vanes are capable of moving independently of one another, wherein the first actuating member is further arranged to be adjacent to the second actuating member.
-