

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                        |
|----------------------|------------------------|
| United States Patent | 12417429               |
| Kind Code            | B2                     |
| Date of Patent       | September 16, 2025     |
| Inventor(s)          | Mimassi; Nagib Georges |

---

### En-route business selection, routing and order preparation timing system

---

#### Abstract

A system and method for en-route business selection, routing, and order preparation timing. The system is a cloud-based network containing an optimization server, portals for restaurants, customers, and drivers to enter their information, and an optimization engine which determines optimal pickup and delivery times for delivery drivers based on a multitude of variables associated with the business enterprises and delivery driver availability. The system may be accessed through web browsers or purpose-built computer and mobile phone applications.

---

|                   |                                               |
|-------------------|-----------------------------------------------|
| <b>Inventors:</b> | <b>Mimassi; Nagib Georges (Palo Alto, CA)</b> |
| <b>Applicant:</b> | <b>RockSpoon, Inc. (San Jose, CA)</b>         |
| <b>Family ID:</b> | <b>1000008819571</b>                          |
| <b>Assignee:</b>  | <b>ROCKSPOON, INC (San Jose, CA)</b>          |
| <b>Appl. No.:</b> | <b>17/472688</b>                              |
| <b>Filed:</b>     | <b>September 12, 2021</b>                     |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20220129849 A1          | Apr. 28, 2022           |

#### Related U.S. Application Data

continuation parent-doc US 16898839 20200611 US 10977606 20210413 child-doc US 17223192  
continuation-in-part parent-doc US 17223192 20210406 US 11379789 child-doc US 17472688  
continuation-in-part parent-doc US 16796505 20200220 ABANDONED child-doc US 16898839  
us-provisional-application US 62938835 20191121  
us-provisional-application US 62938822 20191121

---

## Publication Classification

**Int. Cl.:** G06Q30/00 (20230101); G06Q10/0631 (20230101); G06Q10/08 (20230101);  
G06Q10/0835 (20230101)

**U.S. Cl.:**

**CPC** G06Q10/08355 (20130101); G06Q10/063114 (20130101); G06Q10/08 (20130101);

## Field of Classification Search

**CPC:** G06Q (10/08355); G06Q (10/063114); G06Q (50/28)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name      | U.S. Cl.   | CPC           |
|--------------|-------------|--------------------|------------|---------------|
| 9082101      | 12/2014     | Kulasooriya et al. | N/A        | N/A           |
| 9519901      | 12/2015     | Dorogusker         | N/A        | G06Q 20/40145 |
| 9958272      | 12/2017     | Morris, IV et al.  | N/A        | N/A           |
| 10380536     | 12/2018     | Fornell et al.     | N/A        | N/A           |
| 2002/0188492 | 12/2001     | Borton             | 705/7.31   | G06Q 10/06316 |
| 2008/0275643 | 12/2007     | Yaquib             | 340/995.19 | G01C 21/343   |
| 2009/0048890 | 12/2008     | Burgh              | 705/7.26   | G06Q 10/06375 |
| 2016/0048821 | 12/2015     | Sprecher           | 705/16     | G06Q 20/4014  |
| 2016/0350837 | 12/2015     | Williams           | N/A        | G06Q 50/12    |

---

*Primary Examiner:* Masud; Rokib

*Attorney, Agent or Firm:* Galvin Patent Law LLC

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) Priority is claimed in the application data sheet to the following patents or patent applications, the entire written description of each of which is expressly incorporated herein by reference in its entirety: Ser. No. 17/223,192 Ser. No. 16/898,839 Ser. No. 16/796,505 Ser. No. 62/938,822 Ser. No. 62/938,835

### BACKGROUND

#### Field of the Art

(1) The disclosure relates to the field of computerized selection and routing systems, and more particularly to the field of computerized systems for business selection, ordering, customer routing, and delivery driver routing for retail business establishments.

#### Discussion of the State of the Art

(2) Travelers frequently wish to stop by a retail business establishment on the way to their destinations. As a very common example, drivers frequently wish to stop for food on the way to their destination, often preferring to order food for take-out that can be consumed at the destination. However, while mobile phones and navigation systems do allow for searching of nearby restaurants

the process requires substantial concentration, either requiring a passenger to do the work and coordinate with the driver or requiring the driver to park in order to conduct the searching. The process is cumbersome, and can take a considerable amount of time to complete, matching restaurant names or types to food preferences, or browsing through menus on the driver's mobile device. When performed by the driver while parked, the driver wastes driving time to the destination. Further, there is currently no available system that automatically optimizes the process to account for a variety of customer preferences, including minimizing the delay caused by the re-routing to pick up food, or that coordinates the customer's arrival time at the restaurant with the food preparation time, such that the customer's order is ready when the customer arrives.

(3) With respect to deliveries, there is currently no system that coordinates and optimizes order pickup times, delivery destinations, and driver routing to maximize efficiency, whether for a single business establishment or multiple business establishments that wish to share delivery drivers.

(4) What is needed is a system and method for automated en-route retail business establishment selection, ordering, and routing of both customers and delivery drivers.

## SUMMARY

(5) Accordingly, the inventor has conceived and reduced to practice, a system and method for en-route business selection, routing, and order preparation timing. The system is a cloud-based network containing an optimization server, portals for restaurants, customers, and drivers to enter their information, and an optimization engine which determines optimal pickup and delivery times for delivery drivers based on a multitude of variables associated with the business enterprises and delivery driver availability. The system may be accessed through web browsers or purpose-built computer and mobile phone applications.

(6) According to a preferred embodiment, a system for en-route business selection, routing, and order preparation timing, comprising: a business enterprise database comprising a plurality of business enterprise locations, and a good or service provided by at business enterprise location, and a time of order preparation for each good or service; and an optimization engine comprising a first plurality of programming instructions stored in a memory of, and operable on a processor of, a network-connected computing device, wherein the first plurality of programming instructions, when operating on the processor, cause the computing device to: receive an assistance request from a mobile device associated with a driver, the availability information comprising a good or service required, a current location, and a destination of the driver; retrieve business enterprise information for each of a plurality of business enterprises from the business enterprise database, each business enterprise being selected for retrieval based on the assistance request, and wherein the business enterprise information comprises at least a business enterprise location; create a data graph from the good or service required, the current location, the destination, and the business enterprise location, the data graph comprising vertices and edges, wherein the vertices represent data points and the edges represent relationships between the data points; analyze the data graph to identify potential delays en-route from the current location to each business enterprise location; analyze the data graph to create a predicted transit time to each business enterprise location, the predicted transit time being based on the current location and any identified potential delays; determine a best-fit route to one of the business enterprise locations, the best-fit route being based on the good or service required, the current location, the destination, and the predicted transit time; and send the business enterprise information and the best-fit route to the mobile device, is disclosed.

(7) According to another preferred embodiment, a method for en-route business selection, routing, and order preparation timing, comprising the steps of: receiving an assistance request from a mobile device associated with a driver, the availability information comprising a good or service required, a current location, and a destination of the driver; retrieving business enterprise information for each of a plurality of business enterprises from the business enterprise database, each business enterprise being selected for retrieval based on the assistance request, and wherein the business enterprise information comprises at least a business enterprise location; creating a data

graph from the good or service required, the current location, the destination, and the business enterprise location, the data graph comprising vertices and edges, wherein the vertices represent data points and the edges represent relationships between the data points; analyzing the data graph to identify potential delays en-route from the current location to each business enterprise location; analyzing the data graph to create a predicted transit time to each business enterprise location, the predicted transit time being based on the current location and any identified potential delays; determining a best-fit route to one of the business enterprise locations, the best-fit route being based on the good or service required, the current location, the destination, and the predicted transit time; and sending the business enterprise information and the best-fit route to the mobile device, is disclosed.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWING FIGURES

- (1) The accompanying drawings illustrate several aspects and, together with the description, serve to explain the principles of the invention according to the aspects. It will be appreciated by one skilled in the art that the particular arrangements illustrated in the drawings are merely exemplary, and are not to be considered as limiting of the scope of the invention or the claims herein in any way.
- (2) FIG. 1 is a block diagram illustrating an exemplary system architecture for an automated en-route business establishment selection, ordering, and routing system.
- (3) FIG. 2 is a block diagram illustrating an exemplary architecture for an aspect of an automated en-route business establishment selection, ordering, and routing system, the optimization engine.
- (4) FIG. 3 is a diagram illustrating an exemplary optimization variables and the decisions they may impact.
- (5) FIG. 4 is a diagram illustrating an exemplary weighted, directed graph of a type which may be used to optimize the multi-variate problem of optimizing en-route restaurant selection, ordering, and routing.
- (6) FIG. 5 is a flow diagram showing the steps of an exemplary method for en-route restaurant selection, food ordering, routing, and pickup by a customer.
- (7) FIG. 6 is a flow diagram showing the steps of an exemplary method for restaurant food preparation optimization based on a customer's order, expected arrival time, and the restaurant's current activity level.
- (8) FIG. 7 is a flow diagram showing the steps of an exemplary method for optimization of delivery driver routing for multiple restaurants sharing multiple drivers.
- (9) FIG. 8 is a diagram showing an exemplary screenshot of the display on a delivery driver mobile device for routing of pickups and deliveries.
- (10) FIG. 9 is a diagram showing an exemplary screenshot of a restaurant display screen showing kitchen preparation optimization for driver pickups.
- (11) FIG. 10 is a routing diagram showing an exemplary routing of two drivers for pickup and delivery of 6 orders from 3 restaurants.
- (12) FIG. 11 is a block diagram illustrating an exemplary hardware architecture of a computing device.
- (13) FIG. 12 is a block diagram illustrating an exemplary logical architecture for a client device.
- (14) FIG. 13 is a block diagram showing an exemplary architectural arrangement of clients, servers, and external services.
- (15) FIG. 14 is another block diagram illustrating an exemplary hardware architecture of a computing device.

### DETAILED DESCRIPTION

(16) The inventor has conceived, and reduced to practice, a system and method for en-route business selection, routing, and order preparation timing. The system is a cloud-based network containing an optimization server, portals for restaurants, customers, and drivers to enter their information, and an optimization engine which determines optimal pickup and delivery times for delivery drivers based on a multitude of variables associated with the business enterprises and delivery driver availability. The system may be accessed through web browsers or purpose-built computer and mobile phone applications.

(17) It is frequently the case that a driver wishes to stop to pick up food on the way to his or her destination. Very often, the driver wishes to minimize the impact on the trip by avoiding long time delays or long detours from the intended route. However, accomplishing this task using currently-available tools is difficult. The driver could select a restaurant by chance, usually by seeing a sign for a restaurant while driving. Alternately, the driver could try to find a restaurant by searching using a mobile device. Doing so while driving is dangerous because the driver must direct his or her attention away from the road for significant periods of time and perform tasks that require concentration. At a minimum, the driver first has to open a mapping application, search for nearby restaurants, and select a restaurant by clicking on it on the map. However, in doing so, the decision is, again, based largely on chance, as the driver is forced to make a restaurant selection from restaurants shown in the nearby area and based only on the restaurant name, which may or may not indicate a type of cuisine (e.g., Barbeque, Mexican food, Chinese food, etc.). If the driver wishes to get additional information, such as menu options, pricing, etc., the driver is forced to stop in order to be able to devote sufficient concentration to the task of clicking on restaurant websites, opening up menus, or calling the restaurant for more information. All of these methods involve substantial driver distraction, and all are inefficient. None of them takes into account a myriad of factors that may affect the customer's decision such as the customer's preferences in suggesting restaurants, delays associated with the detour to the restaurant, delays associated with food preparation times at the restaurant, or the time from pickup to arrival at the customer's destination (which may cause hot food to grow cold).

(18) The invention is particularly useful to commuters and those on business trips, where maintaining a planned arrival time is important. Efficiency in restaurant selection, ordering, food preparation time, pickup time, and minimization of delays due to re-routing become critical, especially where traffic can cause unexpected additional delays. As will be further disclosed herein, the invention makes a multi-variate analysis of a large variety of factors (customer preferences; restaurant location, menu options, and food preparation times; traffic data; etc.) to allow a driver or other user to quickly and easily make an en-route restaurant selection and order food items the customer prefers, all with a minimum of distraction and disruption to travel.

(19) While the use case of drivers searching for takeout food while en-route to a destination is a primary example used herein, it is important to note that the invention is not so limited, and may be used by any person (e.g., passengers in a vehicle, persons on public transportation, pedestrians, etc.) seeking to purchase goods or services at any retail business establishment (i.e., the invention is not limited to restaurants, and can be applied to any retail goods or services). In some embodiments, single or multiple delivery driver routing may be optimized for a single business establishment. In other embodiments, delivery driver routing may be optimized for one or more delivery drivers shared by multiple business establishments.

(20) One or more different aspects may be described in the present application. Further, for one or more of the aspects described herein, numerous alternative arrangements may be described; it should be appreciated that these are presented for illustrative purposes only and are not limiting of the aspects contained herein or the claims presented herein in any way. One or more of the arrangements may be widely applicable to numerous aspects, as may be readily apparent from the disclosure. In general, arrangements are described in sufficient detail to enable those skilled in the art to practice one or more of the aspects, and it should be appreciated that other arrangements may

be utilized and that structural, logical, software, electrical and other changes may be made without departing from the scope of the particular aspects. Particular features of one or more of the aspects described herein may be described with reference to one or more particular aspects or figures that form a part of the present disclosure, and in which are shown, by way of illustration, specific arrangements of one or more of the aspects. It should be appreciated, however, that such features are not limited to usage in the one or more particular aspects or figures with reference to which they are described. The present disclosure is neither a literal description of all arrangements of one or more of the aspects nor a listing of features of one or more of the aspects that must be present in all arrangements.

(21) Headings of sections provided in this patent application and the title of this patent application are for convenience only, and are not to be taken as limiting the disclosure in any way.

(22) Devices that are in communication with each other need not be in continuous communication with each other, unless expressly specified otherwise. In addition, devices that are in communication with each other may communicate directly or indirectly through one or more communication means or intermediaries, logical or physical.

(23) A description of an aspect with several components in communication with each other does not imply that all such components are required. To the contrary, a variety of optional components may be described to illustrate a wide variety of possible aspects and in order to more fully illustrate one or more aspects. Similarly, although process steps, method steps, algorithms or the like may be described in a sequential order, such processes, methods and algorithms may generally be configured to work in alternate orders, unless specifically stated to the contrary. In other words, any sequence or order of steps that may be described in this patent application does not, in and of itself, indicate a requirement that the steps be performed in that order. The steps of described processes may be performed in any order practical. Further, some steps may be performed simultaneously despite being described or implied as occurring non-simultaneously (e.g., because one step is described after the other step). Moreover, the illustration of a process by its depiction in a drawing does not imply that the illustrated process is exclusive of other variations and modifications thereto, does not imply that the illustrated process or any of its steps are necessary to one or more of the aspects, and does not imply that the illustrated process is preferred. Also, steps are generally described once per aspect, but this does not mean they must occur once, or that they may only occur once each time a process, method, or algorithm is carried out or executed. Some steps may be omitted in some aspects or some occurrences, or some steps may be executed more than once in a given aspect or occurrence.

(24) When a single device or article is described herein, it will be readily apparent that more than one device or article may be used in place of a single device or article. Similarly, where more than one device or article is described herein, it will be readily apparent that a single device or article may be used in place of the more than one device or article.

(25) The functionality or the features of a device may be alternatively embodied by one or more other devices that are not explicitly described as having such functionality or features. Thus, other aspects need not include the device itself.

(26) Techniques and mechanisms described or referenced herein will sometimes be described in singular form for clarity. However, it should be appreciated that particular aspects may include multiple iterations of a technique or multiple instantiations of a mechanism unless noted otherwise. Process descriptions or blocks in figures should be understood as representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of various aspects in which, for example, functions may be executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those having ordinary skill in the art.

Definitions

(27) “Business establishment” or “place of business” as used herein mean the location of any business entity with which customers may transact business. Typically, this will be a physical location where customers may enter the location and transact business directly with employees of the business, but may also be a delivery-based business. Many examples herein use a restaurant as the business establishment, but the invention is not limited to use in restaurants, and is applicable to any business establishment.

(28) Conceptual Architecture

(29) FIG. 1 is a block diagram illustrating an exemplary system architecture **100** for an automated en-route business establishment selection, ordering, and routing system. In this embodiment which uses a restaurant as the business establishment, the system comprises an optimization server **110**, a driver portal **120**, a customer portal, a restaurant portal, a database, and an optimization engine. Delivery driver mobile devices **121** may connect to the driver portal **120**, typically via a cellular phone network **160**, although connections may be made through other means, as well, such as through the Internet **170** (e.g., through a WiFi router). Customer mobile devices **131** may likewise connect to the customer portal **130** via a cellular phone network **160**, the Internet **170**, or other network connection. Restaurant computers **141** (which do not necessarily need to be mobile, as they are located as the restaurant location) may connect to the restaurant portal **140**, typically through an Internet **170** connection, although other network connections may be used.

(30) In the use case of a customer en-route to a destination, customers will connect to the customer portal **130** to pre-enter a variety of preferences and other information that will be stored in a database **150**, and used by the optimization engine **200** to suggest restaurants, menu items, and routing options that meet the customer's preferences. Examples of the types of preferences that a customer may enter include, but are not limited to: food preferences such as types of food, frequency with which preferred foods are eaten, ranking of particular foods relative to other foods, customer inconvenience preferences such as time delays and routing distances, time after pickup before eating (to ensure that food is still hot when arriving at the customer's destination), food attributes such as price, calories, ingredients, and side dishes. In some embodiments, certain of these preferences will be determined by the system. For example, the types of food preferred by the customer and the frequency with which preferred foods are eaten may be determined based on the customer's history of usage as stored in a database **150** in the system. Other such preferences and factors may also be determined by the system.

(31) Likewise, restaurants may connect to the restaurant portal **140** to enter information about the restaurant and its menu. Examples of the types of information that a restaurant may enter include, but are not limited to: restaurant name, location, types of food offered, hours of operation, phone number, specific menu offerings, food preparation times for certain dishes (including adjustments to food preparation times during busy periods for the restaurant), prices, calorie counts, ingredients, side dishes, drinks, and special pricing options like daily “happy hour” specials or seasonal offerings. In some embodiments, the system may be able to determine certain restaurant information by accessing external resources **180** such as mapping websites and applications. For example, the system may access a publicly-available mapping website such as Google maps, which may contain information about the restaurant's name, location, types of food offered, hours of operation, phone number, etc. Thus, in some embodiments, it is not necessary for the restaurant to enter certain information through the portal, as the information may be automatically obtained from external resources **180**.

(32) When a customer mobile device **131** connects to the optimization server **110** and the customer requests en-route restaurant selection assistance, the optimization engine **200** retrieves the customer's preferences from a database **150**. The customer may further enter a destination or select a pre-entered destination presented from the customer's preferences, which will allow the system to better customize its suggestions. The optimization engine **200** then determines the customer's location by querying the customer's mobile device for location information (e.g., provided by the

mobile device's GPS hardware, WiFi location applications, etc.) and gathers information from external resources **180** about restaurant options located nearby and along the route from the customer's currently location to the customer's destination, as well as traffic information related to the customer's location, intended route, and identified restaurant options. The optimization engine **200** retrieves additional information from a database about identified restaurant options, if such information is available. Based on the customer preferences, restaurant information, and traffic information, the optimization engine **200** identifies one or more restaurants and one or more food options available at those restaurants that are compatible with the customer's preferences, and presents the identified restaurants and their corresponding food options to the customer on the customer's mobile device **131** as suggestions along with indications of the additional delay that will be caused by choosing each suggestion. Thus, the driver is freed of the bulk of the distracting work of finding available restaurants, and can simply select an option presented by the optimization engine **200**, knowing that the option will be compatible with his or her preferences and that the delay time will be acceptable. In some embodiments, an application on the customer's mobile device **131** may dial the phone number of the chosen restaurant for the customer to place the order. In some embodiments, the optimization server **110** will contact the restaurant through the restaurant portal **140** to automatically enter an order into the restaurant's computer **141**, or to direct an employee of the restaurant to call the customer's mobile device **131**, or to establish a voice connection between the restaurant and the customer's mobile device **131** (e.g., dial a phone number corresponding to the business enterprise and dial a phone number of the mobile device) through another means (e.g., voice over internet protocol, or VOIP).

(33) In some embodiments, the optimization engine **200**, through the restaurant portal **140**, may also provide information to the restaurant to schedule the restaurant's food preparation activities to coordinate with the customer's arrival. If the restaurant has entered information such as food preparation times, the optimization engine **200** may use that information to instruct the restaurant's kitchen staff when to start preparation of the customer's order, such that the order will be ready just prior to arrival of the customer. Such food preparation times and scheduling may be adjusted for busy periods at the restaurant (typically around lunch and dinner) either automatically based on the restaurant's history as stored in a database **150**, or by retrieving information stored in a database **150** that has been manually entered by the restaurant through the restaurant portal **140**.

(34) In the use case of delivery driver routing, drivers will connect to the driver portal **120** to pre-enter a variety of preferences and other information that will be stored in a database **150**, and used by the optimization engine **200** to suggest pickup times, routes, and scheduling of deliveries. Delivery drivers may be employed by a single restaurant, employed on a shared basis among multiple restaurants, or may be freelance drivers who make themselves available through the system to any restaurant requiring delivery services. Examples of the types of preferences and information that a delivery driver may enter include, but are not limited to: hours of availability, geographical area served by the driver, type of vehicle, and vehicle capacity. The optimization engine **200** tracks driver location, number of orders in the vehicle currently in delivery, traffic information, order availability and location of participating restaurants, and the preferences and information entered by the driver to optimize pick ups, deliveries, and routing among one or more delivery drivers. As just one example of optimization, a driver on a scooter may only be able to carry a single order and may be further away from the restaurant than a driver in a car, but because of the scooter's small size and maneuverability the optimization engine may select the scooter over the car to make certain deliveries faster. In some embodiments, certain parameters will be determined by the system. For example, the optimization engine may recognize from historical information in a database of drivers that scooters, on average, save a certain number of minutes in delivery along certain routes, or that a particular driver is faster than others.

(35) FIG. 2 is a block diagram illustrating an exemplary architecture for an aspect of an automated en-route business establishment selection, ordering, and routing system, the optimization engine



**200**. In this embodiment, the optimization engine **200** comprises several subsystems, a restaurant selection subsystem **210**, a routing optimization subsystem **220**, a delivery optimization subsystem **230**, and a food preparation optimization subsystem **240**. The restaurant selection subsystem comprises a customer tracking engine **211** and a restaurant selection engine **214**. The customer tracking engine **211** keeps track of the customer's current location by querying the customer's mobile device **131** for location information. The customer preferences **212**, restaurant location data **215**, and restaurant menu data **216** may be retrieved from a database **150** or, in some embodiments, obtained from external resources **180**. The customer's destination **213** will typically be indicated by the customer using an application on his or her mobile device **131**.

(36) The routing optimization subsystem comprises a route optimizer **222**, a traffic data retriever **221**, and a map data retriever **223**. The traffic data retriever **221** obtains current traffic information from external sources **180**, while the map data retriever **223** may either obtain map data from a database **150** or from external resources **180**.

(37) The delivery optimization subsystem **230** comprises a driver tracking engine **231**, and a delivery scheduler **232**, and may receive as input delivery destinations **233**. The customer preferences database contains a variety of pre-entered or pre-determined information about the customer's preferences.

(38) The food preparation optimization subsystem **240** comprises a food preparation scheduler **242**, which receives as input food order information **241** comprising a customer's order. A food preparation scheduler **242** may allow for input provided manually or automatically through an Internet-Of-Things ("IOT") piece of cookware, such as a stove or microwave or other appliance, to track the progression of an order, such as cook time or status of the cooking or packaging of an order, or it may estimate based on a pre-determined time estimation for different food items to be prepared.

(39) A food preparation scheduler **242**, in concert with a route optimizer **222** and delivery scheduler **232**, may provide for automated or manual, or partially-manual, updates on a delivery's status, during the food preparation, the food pickup, and the food delivery, through any combination of IOT food preparation appliances and systems, manual input from cooks and chefs or other restaurant or kitchen staff, pre-stored time estimates for food preparation time, route optimization and scheduling based on traffic data and driver data, and delivery timing based on driver performance, route selection, traffic data, and any manually input data from a driver such as unexpected delays, as necessary.

(40) In operation, when a customer has requested restaurant selection assistance the restaurant selection engine **214** receives the customer's current location from the customer tracking engine **211** and the customer's destination **213**. The restaurant selection engine **214** obtains restaurant location data **215** and restaurant menu data **216** for one or more restaurants either from a database **150** or from external resources **180**. The restaurant selection engine **214** then uses optimization algorithms to determine which restaurants offer food items compatible with the customer's preferences, and which minimize the inconvenience to the customer of making a detour to the restaurant to pick up the food. The restaurant selection engine **214** presents recommendations to the customer about restaurants and food items meeting the customer's preferences and allows the customer to select an option on his or her mobile device **131** by simply selecting an option (on a touch-based mobile device interface, for example, the customer would simply touch on one of the presented options with his or her finger). The restaurant optimization engine **214** then sends the information about the selected restaurant to a route optimizer **222**, which obtains traffic data from the traffic data retriever **221** and map data from the map data retriever **223**, and calculates an optimal route. Simultaneously, the restaurant selection engine **214** sends food order information **241** to a food preparation scheduler **242** (which may be running on the optimization server **110** or on the restaurant's computer **141**), which calculates a food preparation start time determined by comparing the food's preparation time as retrieved from a database **150** with the customer's

expected arrival time as determined by the route optimizer **222**.

(41) In some embodiments, the optimization engine may have a delivery optimization subsystem **230**, in which a delivery scheduler **232** receives food pickup times from the food preparation scheduler **242**, restaurant locations and routing information from the route optimizer **222**, delivery destination information **233**, and the current location of the driver from the driver tracking engine **231**. Based on that information, the delivery scheduler may choose an available driver to deliver the order most efficiently (e.g., shortest time from order readiness to arrival at the delivery destination).

(42) Note that this example is simplified for clarity, and that the actual optimization engine **200** will address a much broader set of factors and variables, as described elsewhere herein. The optimization engine may use any number of optimization algorithms, including machine learning algorithms, to find optimal solutions to the large number of variables presented.

(43) Detailed Description of Exemplary Aspects

(44) FIG. **3** is a diagram illustrating an exemplary optimization variables and the decisions they may impact **300**. Customer preferences **301** (e.g., food preferences and routing/delay preferences) will impact both restaurant choice and routing decisions. Efficiency factors **302** (e.g., traffic, routing, food preparation times, and delivery deadlines) will impact all three decisions, restaurant choice **306**, routing **307**, and where applicable, driver selection **308**. Delivery driver information **303** (e.g., driver locations, vehicle types, vehicle capacities, hours of availability, area of operation) will impact routing decisions **307** and driver selection **308**. Restaurant menu information **304** (e.g., menu, customer feedback, price, calories, ingredients, side dishes) will impact primarily restaurant choice. Location information **305** (e.g., location of customer, customer destination, locations of restaurants, locations of drivers, and delivery destinations) will impact all three decisions, restaurant choice **306**, routing **307**, and where applicable, driver selection **308**. Adding complexity to the analysis, restaurant choice **306** can impact routing choices **307**, and vice-versa. Likewise, routing choices **307** may impact driver selection **308**, and vice-versa.

(45) FIG. **4** is a diagram illustrating an exemplary weighted, directed graph **400** of a type which may be used to optimize the multi-variate problem of optimizing en-route restaurant selection, ordering, and routing. One approach to solving multi-variate problems such as the coordination of customer preferences with locations and menu options is the use of data graphs to represent the totality of factors and their relationships, and apply one of a number of optimization algorithms to the graph to determine the shortest path or least-cost path. In a data graph, the nodes (also called vertices) of the graph represent data points, and the edges (lines between the nodes) represent relationships between the nodes. Data graphs may be directed or undirected, weighted or unweighted, and cyclical or acyclical. A directed graph contains edges that have a direction from one node to another, whereas undirected graphs contain edges that do not have a direction. A weighted graph has edges to which a value is assigned, whereas unweighted graphs do not have values assigned to their edges. Cyclical graphs contain at least one group of nodes through which a path may be repeated, whereas acyclical graphs do not contain any repeatable paths.

(46) In this example, which is simplified for clarity, a weighted, directional graph is shown which contains relationships between the customer's location, the customer's preferences, the location of two restaurants, the type of food the restaurants serve, and the delays from order to pickup and from pickup to consumption. The customer **401** lives in City B **403**, but is driving through City A **402**. City A has light traffic **411**, which would result in 5 minutes of additional drive time **412**, whereas City B has heavy traffic **413**, which would result in 15 minutes of additional drive time **414**. Restaurant A **405** is located in City A **402**, which is nearer to the customer's current location **401**, whereas Restaurant B **408** is located in City B **403**, which is further from the customer's **401** current location, but closer to the customer's **401** destination (assuming that the customer is driving home). Both restaurants serve a type of seafood **404** which is a preference of the customer **401**, but Restaurant A **405** serves lobster **406**, which is more preferred by the customer (preference value 4,

with lower numbers being more preferred) than the halibut **409** (preference value 6, with lower numbers being more preferred) offered by Restaurant B **408**.

(47) The choice of restaurants may be determined by performing one or more weighted path calculations to determine the least cost path between certain nodes. For example, the least cost path between the restaurants and the customer **401** is the path between Restaurant A and the customer (preference value 4), indicating that Restaurant A **405** would be a preferred food choice. The least cost path between the customer and pickup **416** through Restaurant A **405** is through City A **402** which has light traffic **411**, resulting in 5 additional minutes of drive time, but with a food prep time **407** of 15 minutes (meaning that the customer will have to wait at the restaurant for 10 minutes after arriving), resulting in a total time from order to pickup **416** of 15 minutes. The least cost path between the customer and pickup **416** through Restaurant B **405** is through City B **403** which has heavy traffic **413**, resulting in 15 additional minutes of drive time, and with a food prep time **410** of 15 minutes, also resulting in a total time from order to pickup **416** of 15 minutes. So, the total time from order to pickup **416** is the same for both restaurants, despite the additional time in heavy traffic for Restaurant B **408**. Lastly, the time from pickup **416** to consumption is analyzed. The least cost path from City A **402** to the destination **415** is 20 minutes, while the least cost path from City B **403** to the destination **415** is 5 minutes. Thus, Restaurant A **405** has a slightly preferred food, but will cause 15 minutes of delay to the travel time and the time from pickup **416** to consumption is much longer. Restaurant B **408** has an acceptable food, and will also cause 15 minutes of delay to the travel time, but the time from pickup **416** to consumption is much shorter, so the food will be hot on arrival at the destination. Based on this analysis Restaurant B **408** would likely be identified as preferable by the system, and would be presented to the customer over Restaurant A **405**. However, in a real-world scenario, there could be dozens of restaurants located in multiple cities along the customer's route, so this analysis would be greatly expanded. Certain choices would be eliminated entirely and other choices would be more obviously preferable.

(48) Various methods for determining shortest path in a data graph are known in the art, including the Bellman-Ford Algorithm for determining the single shortest distance in  $O(\text{\#vertices times \#of edges})$  time. For a graph with no negative weights, the single source shortest distance can be calculated using Dijkstra's algorithm in  $O(\text{\#of edges plus } (\text{\#vertices times } \log(\text{\#vertices})))$  time using Dijkstra's algorithm. Other shortest path and least cost algorithms are known in the art and may be applied.

(49) Alternatively, machine learning algorithms may be used to optimize the variables without creating a data graph in advance. Such algorithms may construct their own data graphs or other representations of the data, and continually optimize the outcomes either through multiple repetitions or through refinement of historical choices.

(50) FIG. 5 is a flow diagram showing the steps of an exemplary method for en-route restaurant selection, food ordering, routing, and pickup by a customer. A customer portal is provided for the customer to pre-enter preferences such as food types, food attributes, routing/delay, and other preferences **501**. During driving trip, the customer is presented with interface on mobile app for customer to request take-out restaurant options en-route to customer's destination **502**. One or more restaurant options are selected using customer's current location, customer's preferences, customer destination, restaurant locations, and menu options **503**. The restaurant options are displayed to the customer, along with a recommended menu item from each restaurant, with details such as type of food, food cost, additional commute time, and time from pickup to consumption **504**. A choice is received from the customer from the one or more restaurant options displayed with its recommend menu item **505**. The customer's navigation/routing is changed to include pickup at the chosen restaurant before proceeding to destination **506**. Finally, a call is placed to the restaurant for customer to order the recommended menu item for pickup **507**.

(51) FIG. 6 is a flow diagram showing the steps of an exemplary method for restaurant food preparation optimization based on a customer's order, expected arrival time, and the restaurant's

current activity level. The restaurant receives an order from a customer **601**. The customer's current location and expected time of arrival are determined **602**, which determination may take into account traffic and other factors. A food preparation time for the customer's order is retrieved from a database **603**. The restaurant's relative level of activity is determined (i.e., how busy is the restaurant?) **604**, and the food preparation time is adjusted to account for the level of activity **605**. Submission of the order to the kitchen is scheduled such that the order will be ready immediately prior to the customer's arrival **606**.

(52) FIG. 7 is a flow diagram showing the steps of an exemplary method for optimization of delivery driver routing for multiple restaurants sharing multiple drivers. Notification is received that an order is ready for pickup and delivery at a participating restaurant **701**. Drivers currently in or near the area are identified **702**. For each driver, a series of determinations is made **703**. First, the space available in the driver's vehicle is checked based on the number of orders the driver has picked up but not delivered and the capacity of the driver's vehicle **704**. If there is insufficient space, that driver is rejected **705**. Otherwise, a determination is made as to whether the driver is currently making a delivery **706**. If not, the driver is added to the list of potential drivers for step **709**. If the driver is currently making a delivery, a determination is made as to whether the restaurant and delivery are along (or near) the driver's current delivery route **707**. If not, the driver is rejected **705**. If they are, a final check is made to determine whether adding the pickup and delivery to the driver's current delivery route will cause the driver to miss any deadlines **708**. If yes, the driver is rejected **705**. Otherwise, the driver is added to the list of potential drivers for step **709**. At step **709**, a driver is selected from the list of potential drivers, the selection being based, in this example, on the shortest delivery time, although other options are possible. Finally, the selected driver is notified, and the pickup and delivery are added to the driver's route **710**. Note that the pickup and delivery do not have to be added to the end of the driver's route, and can be inserted between other deliveries, if that results in a more efficient overall route.

(53) FIG. 8 is a diagram showing an exemplary screenshot of the display on a delivery driver mobile device for routing of pickups and deliveries. The display of a delivery driver mobile device **800** is designed to facilitate pickups and deliveries that have been optimized by the optimization server **110**. A variety of information may be shown to on the delivery driver mobile device **800**, and multiple screens may be used to convey information to the driver. In this example, four screen areas provide information to the driver, a scheduled deliveries and pickups window **801**, a current delivery/pickup details window **802**, a route details and map window **803**, and a time and estimated time of arrival window **804**. The scheduled deliveries and pickups window **801** shows a time-ordered list of the pickups and deliveries to be made by the driver, including information such as the delivery number or identifier, the name of the person to whom the delivery is to be made, the delivery address, the scheduled delivery time, and the actual delivery time, as well as an indication of the delivery to which the driver is en route. The current delivery/pickup details window **802**, shows details regarding the current delivery or pickup to which the driver is en route, including information such as the delivery number or identifier, the item to be delivered, the item cost, the item quantity, the subtotal, tax, and the amount due. The amount due may be collected by the driver by cash, credit, or a pre-paid account, and entered into the system on another screen (not shown). The driver may be further assisted in pickups and deliveries by a navigation system similar to the route details and map window **803**. This window shows an aerial view of the geographical area in which the driver's pickups and deliveries are to be made, and the route to be taken by the driver. In this example, the driver has already made Delivery A at location A shown on the map, and delivery B at location B shown on the map. The driver is now en route to restaurant C for a pickup, and then will proceed directly to restaurant D for a pickup for the following reasons: restaurant D is closer to restaurant C than location C, the order at restaurant D will be ready immediately upon the driver's arrival, and location D is on the way to location C. Delivery D will be made at location D after the pickup from restaurant D, and on the way to delivering delivery C to location C. This example

represents one possible optimization of routing based on minimized driver travel distance, but many other optimizations are possible, including minimum time from pickup to delivery of each order, average time from pickup to delivery of a group of orders, shortest distance traveled by each driver, average distance traveled by a group of drivers, earliest pickup time of each order, average pickup time of a group of orders; earliest delivery time of each order, and average delivery time of a group of orders, and maximization of number of deliveries made without another pickup (depending on vehicle capacity). The availability and routes of other drivers may be taken into account, as well. For example, if two orders are available at a given restaurant at the same time, one driver may pick up one of the orders, and leave the second order for a different driver who may arrive later, but is going on a better route to deliver the second order more quickly. The time and estimated time of arrival window **804** shows other useful information to the driver such as the current time, confirmation of the driver's name (to ensure that the driver is not following another driver's route), and the estimated time of arrival at the next pickup or delivery location.

(54) FIG. **9** is a diagram showing an exemplary screenshot of a restaurant display screen showing kitchen preparation optimization for driver pickups. In this example, the information shown relates to the Lucky Chinese restaurant shown in pickup C and driver Jim of FIG. **8**. The restaurant display screen **900** is designed to coordinate food preparation times with pickup times that have been optimized by the optimization server **110**. Multiple such screens may be located in different locations around the restaurant, and different screens may show different information. For example, some screens may be optimized to show the kitchen staff order and prep times, while some screens (as in this example) may be optimized to show a take-out manager scheduled orders, the time of the next pickup, and the driver's current location. In this example, four screen areas provide information to the take-out manager, a scheduled orders and pickups window **901**, a next pickup details window **902**, a driver locations and map window **903**, and a time and estimated time of arrival window **904**. The scheduled orders and pickups window **901** shows a time-ordered listing of food orders to be prepared by the kitchen staff, including information such as the menu item to be prepared, whether the order is for in house consumption (dine-in) or delivery (take out), the start time that the kitchen needs to start preparation for the order to be ready when the delivery driver arrives, the estimated order completion time either, the driver scheduled to pickup and deliver the order, the estimated pickup time, and the time the order was delivered. The next pickup details window **902**, shows details regarding the next pickup to be made by a driver, including information such as the delivery number or identifier, the driver name, the item to be picked up, the item cost, the item quantity, the subtotal, tax, and the amount due. The amount due may be collected by the driver by cash, credit, or a pre-paid account, and entered into the system through a screen (not shown) on the delivery driver mobile device **800**. The take-out manager may monitor the location of drivers using a navigation system similar to the driver locations and map window **903**. This window shows an aerial view of the geographical area in which the restaurant's deliveries are to be made, the locations of the deliveries, and the locations and routes of available drivers. In this example, driver Sue has completed a delivery at 5:57 pm, but does not have another delivery scheduled for this restaurant. Driver Jim is just about to arrive at the restaurant to pick up Delivery C, which is an order for chicken. The order has just completed preparation by the kitchen at 6:12, and Jim is scheduled to arrive at the restaurant to pick up the order in one minute (at 6:15 pm). Jim will deliver the order to location C. As shown in the related example from FIG. **8**, Jim will stop at restaurant D and deliver order D first, but this is not shown in the screen of restaurant C. Driver A**1** is en route to restaurant C to pick up an order of noodles at 6:25 pm, and driver Jill is en route to the restaurant to pick up an order of wontons at 6:42 pm. Delivery driver scheduling and routing may be optimized based on any number of factors, including minimum time from pickup to delivery of each order, average time from pickup to delivery of a group of orders, shortest distance traveled by each driver, average distance traveled by a group of drivers, earliest pickup time of each order, average pickup time of a group of orders; earliest delivery time of each order, and

average delivery time of a group of orders, and maximization of number of deliveries made without another pickup (depending on vehicle capacity). Kitchen preparation start times would be coordinated automatically with the optimization, and the preparation finish times of other restaurants may be taken into account, as well. The availability and routes of other drivers may also be taken into account. For example, if two orders are available at a given restaurant at the same time, one driver may pick up one of the orders, and leave the second order for a different driver who may arrive later, but is going on a better route to deliver the second order more quickly. The time and estimated time of arrival window **904** shows other useful information to the take-out manager such as the current time, the name of the driver making the next pickup and the driver's phone number (to allow the take-out manager to easily contact the driver, if necessary), and the estimated time of arrival of the driver for the next pickup.

(55) FIG. **10** is a routing diagram showing an exemplary routing **1000** of two drivers for pickup and delivery of 6 orders from 3 restaurants. In this example, there is a driver **1 1001** (solid line), a driver **2 1002** (dashed line), a restaurant A **1010** with two orders **1011**, **1012**, a restaurant B **1020** with two orders **1021**, **1022**, and a restaurant C **1030** with two orders **1031**, **1032**. The orders are ready for pickup and delivery in the order shown in **1003**. As order B1 becomes ready, it is picked up by driver **2 1002**, who is nearby to restaurant B **1020**, and then delivered immediately to delivery location B1 **1021**. Order A1 becomes ready for pickup, and is picked up by Driver **1 1001**, who is nearby to restaurant A **1010**, and then delivered immediately to delivery location A1 **1011**. However, since driver **1** is far away from restaurants B **1020** and C **1030**, driver **1 1001** is instructed to wait and pick up order A2, which will be ready after orders B2 and C1. Driver **2** picks up order B2 from restaurant B **1020**, delivers it to delivery location B2 **1022**, then proceeds to restaurant C **1030** to pick up order C1 for delivery to location C1 **1031** which is located far away from restaurant C **1030**, so it's inefficient for driver **2 1002** to return to restaurant C **1030** to pick up order C2. As order A2 becomes available, driver **1 1001** picks up order A2 from restaurant A **1010**, and delivers it to delivery location A2, which is located nearby restaurant C **1030**, so driver **1 1001** then proceeds to restaurant C **1030** to pick up order C2 and deliver it to delivery location C2 **1032**. In this example, routing is optimized to minimize the time from pickup to delivery of each item. Delivery driver scheduling and routing may be optimized based on any number of factors, including minimum time from pickup to delivery of each order, average time from pickup to delivery of a group of orders, shortest distance traveled by each driver, average distance traveled by a group of drivers, earliest pickup time of each order, average pickup time of a group of orders; earliest delivery time of each order, and average delivery time of a group of orders, and maximization of number of deliveries made without another pickup (depending on vehicle capacity). Kitchen preparation start times would be coordinated automatically with the optimization and, as in this example, the preparation finish times of other restaurants may be taken into account, as well. As in this example, the availability and routes of other drivers may also be taken into account. For example, if two orders are available at a given restaurant at the same time, one driver may pick up one of the orders, and leave the second order for a different driver who may arrive later, but is going on a better route to deliver the second order more quickly.

(56) Hardware Architecture

(57) Generally, the techniques disclosed herein may be implemented on hardware or a combination of software and hardware. For example, they may be implemented in an operating system kernel, in a separate user process, in a library package bound into network applications, on a specially constructed machine, on an application-specific integrated circuit (ASIC), or on a network interface card.

(58) Software/hardware hybrid implementations of at least some of the aspects disclosed herein may be implemented on a programmable network-resident machine (which should be understood to include intermittently connected network-aware machines) selectively activated or reconfigured by a computer program stored in memory. Such network devices may have multiple network

interfaces that may be configured or designed to utilize different types of network communication protocols. A general architecture for some of these machines may be described herein in order to illustrate one or more exemplary means by which a given unit of functionality may be implemented. According to specific aspects, at least some of the features or functionalities of the various aspects disclosed herein may be implemented on one or more general-purpose computers associated with one or more networks, such as for example an end-user computer system, a client computer, a network server or other server system, a mobile computing device (e.g., tablet computing device, mobile phone, smartphone, laptop, or other appropriate computing device), a consumer electronic device, a music player, or any other suitable electronic device, router, switch, or other suitable device, or any combination thereof. In at least some aspects, at least some of the features or functionalities of the various aspects disclosed herein may be implemented in one or more virtualized computing environments (e.g., network computing clouds, virtual machines hosted on one or more physical computing machines, or other appropriate virtual environments).

(59) Referring now to FIG. **11**, there is shown a block diagram depicting an exemplary computing device **10** suitable for implementing at least a portion of the features or functionalities disclosed herein. Computing device **10** may be, for example, any one of the computing machines listed in the previous paragraph, or indeed any other electronic device capable of executing software- or hardware-based instructions according to one or more programs stored in memory. Computing device **10** may be configured to communicate with a plurality of other computing devices, such as clients or servers, over communications networks such as a wide area network a metropolitan area network, a local area network, a wireless network, the Internet, or any other network, using known protocols for such communication, whether wireless or wired.

(60) In one aspect, computing device **10** includes one or more central processing units (CPU) **12**, one or more interfaces **15**, and one or more busses **14** (such as a peripheral component interconnect (PCI) bus). When acting under the control of appropriate software or firmware, CPU **12** may be responsible for implementing specific functions associated with the functions of a specifically configured computing device or machine. For example, in at least one aspect, a computing device **10** may be configured or designed to function as a server system utilizing CPU **12**, local memory **11** and/or remote memory **16**, and interface(s) **15**. In at least one aspect, CPU **12** may be caused to perform one or more of the different types of functions and/or operations under the control of software modules or components, which for example, may include an operating system and any appropriate applications software, drivers, and the like.

(61) CPU **12** may include one or more processors **13** such as, for example, a processor from one of the Intel, ARM, Qualcomm, and AMD families of microprocessors. In some aspects, processors **13** may include specially designed hardware such as application-specific integrated circuits (ASICs), electrically erasable programmable read-only memories (EEPROMs), field-programmable gate arrays (FPGAs), and so forth, for controlling operations of computing device **10**. In a particular aspect, a local memory **11** (such as non-volatile random access memory (RAM) and/or read-only memory (ROM), including for example one or more levels of cached memory) may also form part of CPU **12**. However, there are many different ways in which memory may be coupled to system **10**. Memory **11** may be used for a variety of purposes such as, for example, caching and/or storing data, programming instructions, and the like. It should be further appreciated that CPU **12** may be one of a variety of system-on-a-chip (SOC) type hardware that may include additional hardware such as memory or graphics processing chips, such as a QUALCOMM SNAPDRAGON™ or SAMSUNG EXYNOS™ CPU as are becoming increasingly common in the art, such as for use in mobile devices or integrated devices.

(62) As used herein, the term “processor” is not limited merely to those integrated circuits referred to in the art as a processor, a mobile processor, or a microprocessor, but broadly refers to a microcontroller, a microcomputer, a programmable logic controller, an application-specific integrated circuit, and any other programmable circuit.

(63) In one aspect, interfaces **15** are provided as network interface cards (NICs). Generally, NICs control the sending and receiving of data packets over a computer network; other types of interfaces **15** may for example support other peripherals used with computing device **10**. Among the interfaces that may be provided are Ethernet interfaces, frame relay interfaces, cable interfaces, DSL interfaces, token ring interfaces, graphics interfaces, and the like. In addition, various types of interfaces may be provided such as, for example, universal serial bus (USB), Serial, Ethernet, FIREWIRE™, THUNDERBOLT™, PCI, parallel, radio frequency (RF), BLUETOOTH™, near-field communications (e.g., using near-field magnetics), 802.11 (WiFi), frame relay, TCP/IP, ISDN, fast Ethernet interfaces, Gigabit Ethernet interfaces, Serial ATA (SATA) or external SATA (ESATA) interfaces, high-definition multimedia interface (HDMI), digital visual interface (DVI), analog or digital audio interfaces, asynchronous transfer mode (ATM) interfaces, high-speed serial interface (HSSI) interfaces, Point of Sale (POS) interfaces, fiber data distributed interfaces (FDDIs), and the like. Generally, such interfaces **15** may include physical ports appropriate for communication with appropriate media. In some cases, they may also include an independent processor (such as a dedicated audio or video processor, as is common in the art for high-fidelity AN hardware interfaces) and, in some instances, volatile and/or non-volatile memory (e.g., RAM).

(64) Although the system shown in FIG. **11** illustrates one specific architecture for a computing device **10** for implementing one or more of the aspects described herein, it is by no means the only device architecture on which at least a portion of the features and techniques described herein may be implemented. For example, architectures having one or any number of processors **13** may be used, and such processors **13** may be present in a single device or distributed among any number of devices. In one aspect, a single processor **13** handles communications as well as routing computations, while in other aspects a separate dedicated communications processor may be provided. In various aspects, different types of features or functionalities may be implemented in a system according to the aspect that includes a client device (such as a tablet device or smartphone running client software) and server systems (such as a server system described in more detail below).

(65) Regardless of network device configuration, the system of an aspect may employ one or more memories or memory modules (such as, for example, remote memory block **16** and local memory **11**) configured to store data, program instructions for the general-purpose network operations, or other information relating to the functionality of the aspects described herein (or any combinations of the above). Program instructions may control execution of or comprise an operating system and/or one or more applications, for example. Memory **16** or memories **11**, **16** may also be configured to store data structures, configuration data, encryption data, historical system operations information, or any other specific or generic non-program information described herein.

(66) Because such information and program instructions may be employed to implement one or more systems or methods described herein, at least some network device aspects may include nontransitory machine-readable storage media, which, for example, may be configured or designed to store program instructions, state information, and the like for performing various operations described herein. Examples of such nontransitory machine-readable storage media include, but are not limited to, magnetic media such as hard disks, floppy disks, and magnetic tape; optical media such as CD-ROM disks; magneto-optical media such as optical disks, and hardware devices that are specially configured to store and perform program instructions, such as read-only memory devices (ROM), flash memory (as is common in mobile devices and integrated systems), solid state drives (SSD) and “hybrid SSD” storage drives that may combine physical components of solid state and hard disk drives in a single hardware device (as are becoming increasingly common in the art with regard to personal computers), memristor memory, random access memory (RAM), and the like. It should be appreciated that such storage means may be integral and non-removable (such as RAM hardware modules that may be soldered onto a motherboard or otherwise integrated into an electronic device), or they may be removable such as swappable flash memory modules (such as



“thumb drives” or other removable media designed for rapidly exchanging physical storage devices), “hot-swappable” hard disk drives or solid state drives, removable optical storage discs, or other such removable media, and that such integral and removable storage media may be utilized interchangeably. Examples of program instructions include both object code, such as may be produced by a compiler, machine code, such as may be produced by an assembler or a linker, byte code, such as may be generated by for example a JAVA™ compiler and may be executed using a Java virtual machine or equivalent, or files containing higher level code that may be executed by the computer using an interpreter (for example, scripts written in Python, Perl, Ruby, Groovy, or any other scripting language).

(67) In some aspects, systems may be implemented on a standalone computing system. Referring now to FIG. 12, there is shown a block diagram depicting a typical exemplary architecture of one or more aspects or components thereof on a standalone computing system. Computing device **20** includes processors **21** that may run software that carry out one or more functions or applications of aspects, such as for example a client application **24**. Processors **21** may carry out computing instructions under control of an operating system **22** such as, for example, a version of MICROSOFT WINDOWS™ operating system, APPLE macOS™ or iOS™ operating systems, some variety of the Linux operating system, ANDROID™ operating system, or the like. In many cases, one or more shared services **23** may be operable in system **20**, and may be useful for providing common services to client applications **24**. Services **23** may for example be WINDOWS™ services, user-space common services in a Linux environment, or any other type of common service architecture used with operating system **21**. Input devices **28** may be of any type suitable for receiving user input, including for example a keyboard, touchscreen, microphone (for example, for voice input), mouse, touchpad, trackball, or any combination thereof. Output devices **27** may be of any type suitable for providing output to one or more users, whether remote or local to system **20**, and may include for example one or more screens for visual output, speakers, printers, or any combination thereof. Memory **25** may be random-access memory having any structure and architecture known in the art, for use by processors **21**, for example to run software. Storage devices **26** may be any magnetic, optical, mechanical, memristor, or electrical storage device for storage of data in digital form (such as those described above, referring to FIG. 11). Examples of storage devices **26** include flash memory, magnetic hard drive, CD-ROM, and/or the like.

(68) In some aspects, systems may be implemented on a distributed computing network, such as one having any number of clients and/or servers. Referring now to FIG. 13, there is shown a block diagram depicting an exemplary architecture **30** for implementing at least a portion of a system according to one aspect on a distributed computing network. According to the aspect, any number of clients **33** may be provided. Each client **33** may run software for implementing client-side portions of a system; clients may comprise a system **20** such as that illustrated in FIG. 12. In addition, any number of servers **32** may be provided for handling requests received from one or more clients **33**. Clients **33** and servers **32** may communicate with one another via one or more electronic networks **31**, which may be in various aspects any of the Internet, a wide area network, a mobile telephony network (such as CDMA or GSM cellular networks), a wireless network (such as WiFi, WiMAX, LTE, and so forth), or a local area network (or indeed any network topology known in the art; the aspect does not prefer any one network topology over any other). Networks **31** may be implemented using any known network protocols, including for example wired and/or wireless protocols.

(69) In addition, in some aspects, servers **32** may call external services **37** when needed to obtain additional information, or to refer to additional data concerning a particular call. Communications with external services **37** may take place, for example, via one or more networks **31**. In various aspects, external services **37** may comprise web-enabled services or functionality related to or installed on the hardware device itself. For example, in one aspect where client applications **24** are

implemented on a smartphone or other electronic device, client applications **24** may obtain information stored in a server system **32** in the cloud or on an external service **37** deployed on one or more of a particular enterprise's or user's premises. In addition to local storage on servers **32**, remote storage **38** may be accessible through the network(s) **31**.

(70) In some aspects, clients **33** or servers **32** (or both) may make use of one or more specialized services or appliances that may be deployed locally or remotely across one or more networks **31**. For example, one or more databases **34** in either local or remote storage **38** may be used or referred to by one or more aspects. It should be understood by one having ordinary skill in the art that databases in storage **34** may be arranged in a wide variety of architectures and using a wide variety of data access and manipulation means. For example, in various aspects one or more databases in storage **34** may comprise a relational database system using a structured query language (SQL), while others may comprise an alternative data storage technology such as those referred to in the art as “NoSQL” (for example, HADOOP CASSANDRA™, GOOGLE BIGTABLE™, and so forth). In some aspects, variant database architectures such as column-oriented databases, in-memory databases, clustered databases, distributed databases, or even flat file data repositories may be used according to the aspect. It will be appreciated by one having ordinary skill in the art that any combination of known or future database technologies may be used as appropriate, unless a specific database technology or a specific arrangement of components is specified for a particular aspect described herein. Moreover, it should be appreciated that the term “database” as used herein may refer to a physical database machine, a cluster of machines acting as a single database system, or a logical database within an overall database management system. Unless a specific meaning is specified for a given use of the term “database”, it should be construed to mean any of these senses of the word, all of which are understood as a plain meaning of the term “database” by those having ordinary skill in the art.

(71) Similarly, some aspects may make use of one or more security systems **36** and configuration systems **35**. Security and configuration management are common information technology (IT) and web functions, and some amount of each are generally associated with any IT or web systems. It should be understood by one having ordinary skill in the art that any configuration or security subsystems known in the art now or in the future may be used in conjunction with aspects without limitation, unless a specific security **36** or configuration system **35** or approach is specifically required by the description of any specific aspect.

(72) FIG. **14** shows an exemplary overview of a computer system **40** as may be used in any of the various locations throughout the system. It is exemplary of any computer that may execute code to process data. Various modifications and changes may be made to computer system **40** without departing from the broader scope of the system and method disclosed herein. Central processor unit (CPU) **41** is connected to bus **42**, to which bus is also connected memory **43**, nonvolatile memory **44**, display **47**, input/output (I/O) unit **48**, and network interface card (NIC) **53**. I/O unit **48** may, typically, be connected to peripherals such as a keyboard **49**, pointing device **50**, hard disk **52**, real-time clock **51**, a camera **57**, and other peripheral devices. NIC **53** connects to network **54**, which may be the Internet or a local network, which local network may or may not have connections to the Internet. The system may be connected to other computing devices through the network via a router **55**, wireless local area network **56**, or any other network connection. Also shown as part of system **40** is power supply unit **45** connected, in this example, to a main alternating current (AC) supply **46**. Not shown are batteries that could be present, and many other devices and modifications that are well known but are not applicable to the specific novel functions of the current system and method disclosed herein. It should be appreciated that some or all components illustrated may be combined, such as in various integrated applications, for example Qualcomm or Samsung system-on-a-chip (SOC) devices, or whenever it may be appropriate to combine multiple capabilities or functions into a single hardware device (for instance, in mobile devices such as smartphones, video game consoles, in-vehicle computer systems such as navigation or multimedia systems in

automobiles, or other integrated hardware devices).

(73) In various aspects, functionality for implementing systems or methods of various aspects may be distributed among any number of client and/or server components. For example, various software modules may be implemented for performing various functions in connection with the system of any particular aspect, and such modules may be variously implemented to run on server and/or client components.

(74) The skilled person will be aware of a range of possible modifications of the various aspects described above. Accordingly, the present invention is defined by the claims and their equivalents.

## Claims

1. A system for en-route business selection, routing, and order preparation timing, comprising: a business enterprise database comprising a plurality of business enterprise locations, and a good or service provided by at business enterprise location, and a time of order preparation for each good or service; and an optimization engine comprising a first plurality of programming instructions stored in a memory of, and operable on a processor of, a network-connected computing device, wherein the first plurality of programming instructions, when operating on the processor, cause the computing device to: receive an assistance request from a mobile device associated with a driver, the availability information comprising a good or service required, a current location, and a destination of the driver; retrieve business enterprise information for each of a plurality of business enterprises from the business enterprise database, each business enterprise being selected for retrieval based on the assistance request, and wherein the business enterprise information comprises at least a business enterprise location; create a weighted, directed data graph structure from the good or service required, the current location, the destination, and the business enterprise location, the data graph comprising vertices and edges, wherein the vertices represent data points including the current location, the destination, and each business enterprise location, and the edges represent relationships between the data points including routing paths and estimated travel times; analyze the data graph structure using a shortest path algorithm to identify potential delays en-route from the current location to each business enterprise location based on real-time traffic data; analyze the data graph to create a predicted transit time to each business enterprise location, the predicted transit time being based on the current location and any identified potential delays; determine a best-fit route to one of the business enterprise locations, the best-fit route being based on the good or service required, the current location, the destination, and the predicted transit time, wherein the best-fit route minimizes diversion from an original route to the destination; coordinate food preparation time with driver arrival by calculating a start time for food preparation based on the predicted transit time; and send the business enterprise information, and the best-fit route, and navigation instructions to the mobile device, thereby reducing driver distraction during travel.
2. The system of claim 1, further comprising an automated dialer comprising a second plurality of programming instructions stored in a memory of, and operable on a processor of, a network-connected computing device, wherein the second plurality of programming instructions, when operating on the processor, cause the computing device to: receive a selection from the driver of one of the retrieved business enterprises; dial a phone number corresponding to the business enterprise; dial a phone number of the mobile device; and establish a voice connection between the business enterprise and the mobile device.
3. The system of claim 2, wherein the voice connection is a voice over internet protocol voice connection.
4. The system of claim 1, further comprising an ordering engine comprising a third plurality of programming instructions stored in a memory of, and operable on a processor of, a network-connected computing device, wherein the third plurality of programming instructions, when operating on the processor, cause the computing device to: receive a selection from the driver of

one of the retrieved business enterprises; connect with a network-connected computer at the selected business enterprise; and place an order on behalf of the driver through the network-connected computer at the business enterprise.

5. The system of claim 1, further comprising a traffic data retriever comprising a second plurality of programming instructions stored in a memory of, and operable on a processor of, a network-connected computing device, wherein the second plurality of programming instructions, when operating on the processor, cause the computing device to: retrieve traffic data from the Internet; and add the traffic data to the data graph.

6. The system of claim 1, further comprising a map data retriever comprising a third plurality of programming instructions stored in a memory of, and operable on a processor of, a network-connected computing device, wherein the third plurality of programming instructions, when operating on the processor, cause the computing device to: retrieve map data from the Internet or from a database; determine a route for pick up or delivery of an order; and send the route information to the mobile device.

7. The system of claim 1, wherein the data graph is a weighted graph.

8. The system of claim 1, wherein the data graph is a directed graph.

9. A method for en-route business selection, routing, and order preparation timing, comprising the steps of: receiving an assistance request from a mobile device associated with a driver, the availability information comprising a good or service required, a current location, and a destination of the driver; retrieving business enterprise information for each of a plurality of business enterprises from the business enterprise database, each business enterprise being selected for retrieval based on the assistance request, and wherein the business enterprise information comprises at least a business enterprise location; creating a weighted, directed data graph structure from the good or service required, the current location, the destination, and the business enterprise location, the data graph comprising vertices and edges, wherein the vertices represent data points including the current location, the destination, and each business enterprise location, and the edges represent relationships between the data points including routing paths and estimated travel times; analyze the data graph structure using a shortest path algorithm to identify potential delays en-route from the current location to each business enterprise location based on real-time traffic data; determining a best-fit route to one of the business enterprise locations, the best-fit route being based on the good or service required, the current location, the destination, and the predicted transit time, wherein the best-fit route minimizes diversion from an original route to the destination; coordinating food preparation time with driver arrival by calculating a start time for food preparation based on the predicted transit time; and sending the business enterprise information, and the best-fit route, and navigation instructions to the mobile device, thereby reducing driver distraction during travel.

10. The method of claim 9, further comprising the steps of: receiving a selection from the driver of one of the retrieved business enterprises; dialing a phone number corresponding to the business enterprise; dialing a phone number of the mobile device; and establishing a voice connection between the business enterprise and the mobile device.

11. The method of claim 10, wherein the voice connection is a voice over internet protocol voice connection.

12. The method of claim 9, further comprising the steps of: receiving a selection from the driver of one of the retrieved business enterprises; connecting with a network-connected computer at the selected business enterprise; and placing an order on behalf of the driver through the network-connected computer at the business enterprise.

13. The method of claim 9, further comprising the steps of: retrieving traffic data from the Internet; and adding the traffic data to the data graph.

14. The method of claim 9, further comprising the steps of: retrieving map data from the Internet or from a database; determining a route for pick up or delivery of an order; and sending the route

information to the mobile device.

15. The method of claim 9, wherein the data graph is a weighted graph.

16. The method of claim 9, wherein the data graph is a directed graph.

---