

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417640
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yamazaki; Daiki et al.

Surveillance system, surveillance apparatus, surveillance method, and non-transitory computer-readable storage medium

Abstract

A surveillance apparatus (**100**) includes a detection unit (**102**) processing an image in which an area around a road is captured and detecting that the relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value, and an output unit (**104**) selecting a type of information to be output, by using an attribute of the person detected to be in the state, and outputting information of the selected type.

Inventors:	Yamazaki; Daiki (Tokyo, JP), Wakakusa; Ryuji (Tokyo, JP)
Applicant:	NEC Corporation (Tokyo, JP)
Family ID:	1000008819584
Assignee:	NEC CORPORATION (Tokyo, JP)
Appl. No.:	17/790911
Filed (or PCT Filed):	April 13, 2020
PCT No.:	PCT/JP2020/016315
PCT Pub. No.:	WO2021/149274
PCT Pub. Date:	July 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230083156 A1	Mar. 16, 2023

Foreign Application Priority Data

WO	PCT/JP2020/001760	Jan. 20, 2020
----	-------------------	---------------

Publication Classification

Int. Cl.: G06V20/54 (20220101); G06T7/20 (20170101); G06T7/70 (20170101); G06V40/10 (20220101)

U.S. Cl.:

CPC G06V20/54 (20220101); G06T7/20 (20130101); G06T7/70 (20170101); G06V40/10 (20220101); G06T2207/30196 (20130101); G06T2207/30232 (20130101); G06T2207/30236 (20130101); G06T2207/30242 (20130101); G06V2201/08 (20220101)

Field of Classification Search

CPC: G06T (2207/30242); G06T (2207/30261); G06T (7/20); G06T (7/215); G06T (7/246); G06T (7/292); G06T (7/579); G06T (7/70); G06T (2207/10016); G06T (2207/30196); G06T (2207/30232); G06T (2207/30236); G06V (2201/08); G06V (40/103); G06V (40/00-20); G06V (20/44); G06V (2201/07); G06V (20/58); G06V (40/10); G06V (20/52-54); H04N (21/23418); H04N (7/188); H04N (7/18); H04N (7/181); G08B (13/00-19697)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10572737	12/2019	Leizerovich et al.	N/A	N/A
2014/0192194	12/2013	Bedell	348/148	H04N 7/183
2016/0096506	12/2015	Shreve	348/148	B60R 25/102
2016/0140872	12/2015	Palmer	434/65	G09B 19/167
2017/0313247	12/2016	Hsu	N/A	G08G 1/165
2017/0357855	12/2016	Kusumoto	N/A	N/A
2018/0090010	12/2017	Ikehara et al.	N/A	N/A
2018/0272992	12/2017	Gage	N/A	G06V 20/56
2019/0347914	12/2018	Kinoshita et al.	N/A	N/A
2019/0354773	12/2018	Leizerovich	N/A	G08B 25/016

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2007-195130	12/2006	JP	N/A
2007-251556	12/2006	JP	N/A
2012-059023	12/2011	JP	N/A
2017-220151	12/2016	JP	N/A
2018-054498	12/2017	JP	N/A
2018/110165	12/2017	WO	N/A

OTHER PUBLICATIONS

JP Office Action for JP Application No. 2023-175000, mailed on Oct. 1, 2024 with English Translation. cited by applicant
International Search Report for PCT Application No. PCT/JP2020/016315, mailed on Jun. 30, 2020. cited by applicant

Primary Examiner: Morse; Gregory A

Assistant Examiner: Dardano; Stefano Anthony

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

(1) This application is a National Stage Entry of PCT/JP2020/016315 filed on Apr. 13, 2020, which claims priority from International Application No. PCT/JP2020/001760, filed on Jan. 20, 2020, the contents of all of which are incorporated herein by reference, in their entirety.

TECHNICAL FIELD

(2) The present invention relates to a surveillance system, a surveillance apparatus, a surveillance method, and a program.

BACKGROUND ART

(3) Installation of surveillance cameras in towns has been under way in recent years and is utilized in crime prevention. Patent Document 1 describes a video surveillance system detecting an act of trespassing on a parking lot or the like by analyzing a video from a security camera and, at the same time, immediately transmitting a warning and the video being the basis of the determination to a display apparatus in a surveillance room where a surveillant stands by, or mobile phones or the like carried by a guard and a person concerned.

RELATED DOCUMENT

Patent Document

(4) Patent Document 1: Japanese Patent Application Publication No. 2007-195130

DISCLOSURE OF THE INVENTION

Technical Problem

(5) However, the aforementioned document does not disclose a technology for detecting criminal acts committed against a pedestrian and a vehicle, such as kidnapping and vehicle theft.

(6) The present invention has been made in view of the aforementioned circumstances, and an object of the present invention is to provide a technology for detecting situations in which criminal acts committed against a pedestrian and a vehicle may occur.

Solution to Problem

(7) In order to solve the aforementioned problem, aspects of the present invention employ the following configurations, respectively.

(8) A first aspect relates to a surveillance system.

(9) A surveillance system according to the first aspect includes: a plurality of cameras each capturing an image of an area around a road; and a surveillance apparatus surveilling images captured by a plurality of cameras, wherein the surveillance apparatus includes: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that outputs a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.

(10) A second aspect relates to a surveillance apparatus.

(11) A surveillance apparatus according to the second aspect includes: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that outputs a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.

- (12) A third aspect relates to a surveillance method executed by at least one computer.
- (13) A surveillance method according to the third aspect includes, by a surveillance apparatus: processing an image in which an area around a road is captured and detecting that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and outputting a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.
- (14) Note that another aspect of the present invention may be a program causing at least one computer to execute the method according to the aforementioned third aspect or a computer-readable storage medium on which such a program is recorded. The storage medium includes a non-transitory tangible medium.
- (15) The computer program includes a computer program code causing a computer to implement the surveillance method on the surveillance apparatus when being executed by the computer.
- (16) Note that any combination of the components described above and representation of the present invention converted among a method, an apparatus, a system, a storage medium, a computer program, and the like are also valid as embodiments of the present invention.
- (17) Further, various components of the present invention do not necessarily need to be individually independent, and, for example, a plurality of components may be formed as a single member, a plurality of members may form a single component, a certain component may be part of another component, and part of a certain component may overlap with part of another component.
- (18) Further, while a plurality of procedures are described in a sequential order in the method and the computer program according to the present invention, the order of description does not limit the order in which the plurality of procedures are executed. Therefore, when the method and the computer program according to the present invention are implemented, the order of the plurality of procedures may be changed without affecting the contents.
- (19) Furthermore, a plurality of procedures in the method and the computer program according to the present invention are not limited to being individually executed at different timings. Thus, another procedure may occur during execution of any procedure, and an execution timing of any procedure may partially or entirely overlap an execution timing of another procedure.
- Advantageous Effects of Invention
- (20) The aforementioned aspects can provide a technology for detecting a situation in which a criminal act committed against a pedestrian may occur.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram schematically illustrating an overview of a surveillance system according to an example embodiment.
- (2) FIG. 2 is a functional block diagram illustrating a logical configuration example of a surveillance apparatus in FIG. 1.
- (3) FIG. 3 is a block diagram illustrating a hardware configuration of a computer providing each of the surveillance apparatus and an image processing apparatus in the surveillance system illustrated in FIG. 1.
- (4) FIG. 4 is a flowchart illustrating an operation example of the surveillance apparatus according to the present example embodiment.
- (5) FIG. 5 is a functional block diagram illustrating a logical configuration example of a surveillance system.
- (6) FIG. 6 is a flowchart illustrating an example of operation of the surveillance system.
- (7) FIG. 7 is a flowchart illustrating an example of operation of the surveillance system.
- (8) FIG. 8 is a functional block diagram illustrating a logical configuration example of a

surveillance system.

(9) FIG. **9** is a flowchart illustrating an example of operation of the surveillance system.

(10) FIG. **10** is a flowchart illustrating an example of operation of the surveillance system.

(11) FIG. **11** is a functional block diagram illustrating a logical configuration example of a surveillance system.

(12) FIG. **12** is a flowchart illustrating an example of operation of the surveillance apparatus.

(13) FIG. **13** is a flowchart illustrating an example of operation of the surveillance system.

(14) FIG. **14** is a flowchart illustrating an example of operation of the surveillance system.

(15) FIG. **15** is a functional block diagram illustrating a logical configuration example of a surveillance system.

(16) FIG. **16** is a flowchart illustrating an example of operation of the surveillance system.

(17) FIG. **17** is a flowchart illustrating an example of operation of the surveillance system.

(18) FIGS. **18A** to **18C** are diagrams for each illustrating a positional relation between a vehicle and a person in a case of kidnapping.

(19) FIG. **19** is a flowchart illustrating an example of operation of a surveillance system.

(20) FIGS. **20A** to **20C** are diagrams for each illustrating a positional relation between a vehicle and a person in a case of vehicle theft.

(21) FIG. **21** is a flowchart illustrating an example of operation of the surveillance system.

DESCRIPTION OF EMBODIMENTS

(22) Example embodiments of the present invention are described below by using drawings. Note that, in every drawing, similar components are given similar signs, and description thereof is omitted as appropriate.

(23) In the example embodiments, “acquisition” includes at least either of an apparatus getting data or information stored in another apparatus or a storage medium (active acquisition), and an apparatus inputting data or information output from another apparatus to the apparatus (passive acquisition). Examples of the active acquisition include making a request or an inquiry to another apparatus and receiving a response and readout by accessing another apparatus or a storage medium. Further, examples of the passive acquisition include reception of distributed (or, for example, transmitted or push notified) information. Furthermore, “acquisition” may refer to acquisition by selection from received data or information, or selective reception of distributed data or information.

First Example Embodiment

(24) <System Overview>

(25) FIG. **1** is a diagram schematically illustrating an overview of a surveillance system **1** according to an example embodiment. The surveillance system **1** is a system in which an image processing apparatus **200** recognizes a vehicle **10** and a person **20** by processing an image captured by a surveillance camera **5** installed in a town, and a surveillance apparatus **100** detects criminal acts such as kidnapping and vehicle theft by using the processing result by the image processing apparatus **200**.

(26) The surveillance system **1** includes the surveillance apparatus **100**, the image processing apparatus **200**, and at least one surveillance camera **5**. As the surveillance camera **5**, a camera dedicated to the surveillance system **1** may be used, or, for example, a previously installed camera may be used.

(27) The surveillance camera **5** captures an image of a surveilled location and generates an image. The surveillance camera **5** includes imaging elements such as a lens and a charge coupled device (CCD) image sensor. The surveillance camera **5** may include a mechanism for performing direction control of the main body of the camera and the lens, zooming control, focusing, and the like following movement of a person entering the angle of view.

(28) The surveillance camera **5** captures an image of an area including at least a road passable by a vehicle **10**. For example, the surveillance camera **5** captures an image of an area including a road

with a width wider than that of a vehicle **10**. Further, the surveillance camera **5** may capture an image of an area including roads constituted of a sidewalk on which a person **20** passes and a roadway on which a vehicle **10** passes. However, without being limited to roads, the surveillance camera **5** may capture an image of a location where a vehicle **10** and a person **20** can enter, such as a parking lot. Note that the surveillance camera **5** may capture an image of a moving person **20** or a stationary person **20**. The surveillance camera **5** may capture an image of a moving vehicle **10** or a stationary vehicle **10**.

(29) The surveillance camera **5** may capture an image of an area including locations where crimes are likely to occur such as a location behind a structure such as shrubbery, a fence, or a building, an empty location, and a location where crimes have occurred repeatedly in the past.

(30) An image generated by the surveillance camera **5** is preferably transmitted to the surveillance apparatus **100** in real time. However, an image transmitted to the surveillance apparatus **100** may not be immediately transmitted from the surveillance camera **5** and may be an image delayed by a predetermined time. Images generated by the surveillance camera **5** may be temporarily stored in a separate storage apparatus and be read from the storage apparatus by the surveillance apparatus **100** sequentially or at predetermined intervals. Furthermore, images transmitted to the surveillance apparatus **100** are preferably dynamic images but may be frame images captured at a predetermined intervals or static images.

(31) A method of connecting the surveillance camera **5** to the surveillance apparatus **100** may be wireless or wired. In the case of a wireless connection, it is assumed that each of the surveillance camera **5** and the surveillance apparatus **100** has a wireless communication function. For example, the surveillance camera **5** may be a network camera such as an Internet Protocol (IP) camera.

(32) <Functional Configuration Example>

(33) FIG. 2 is a functional block diagram illustrating a logical configuration example of the surveillance apparatus **100** in FIG. 1. The surveillance apparatus **100** includes a detection unit **102** and an output unit **104**. The detection unit **102** detects that the relative distance between a person **20** and a vehicle **10** included in an image is in a state of being equal to or less than a reference value (hereinafter also referred to as an approaching state). The output unit **104** outputs a type of information to be output selected by using an attribute of a person **20** detected to be in the approaching state.

(34) The state of the relative distance between a person **20** and a vehicle **10** being equal to or less than the reference value refers to a state of the distance between the person **20** and the vehicle **10** being equal to or less than the reference value. The state of the relative distance between a person **20** and a vehicle **10** being equal to or less than the reference value may refer to a state of the relative distance gradually shortening and eventually becoming equal to or less than the reference value by at least either one of the person **20** and the vehicle **10** moving, that is, a state of the person **20** and the vehicle **10** approaching each other with time. The detection unit **102** may detect a state of the person **20** moving and approaching the vehicle **10** or may detect a state of the vehicle **10** moving and approaching the person **20**. The detection unit **102** may detect a state of both the person **20** and the vehicle **10** moving and the vehicle **10** approaching the moving person **20** from behind. The detection unit **102** may detect a state of the vehicle **10** approaching the moving person **20** from in front of the person **20**.

(35) For example, with regard to a change in the relative distance between a person **20** and a vehicle **10**, the image processing apparatus **200** can detect, in a plurality of time-series images, the positions of a feature part of each of the person **20** and the vehicle **10** determined in an image and estimate moving directions of the person **20** and the vehicle **10** and the relative distance between the person **20** and the vehicle **10** from changes in the positions of the person **20** and the vehicle **10** and a relative positional relation between the two. The detection unit **102** detects a state of the relative distance between the person **20** and the vehicle **10** included in the image being equal to or less than the reference value, based on the processing result by the image processing apparatus **200**.

- (36) An attribute of a person **20** is set based on at least one of attributes extracted from an image, such as gender, age, a feature of the face, height, belongings, clothing, and a situation.
- (37) Examples of a type of information to be output include information about a type of crime such as a possibility of occurrence of kidnapping and a possibility of occurrence of vehicle theft. An output destination and an output method may vary by the type of information to be output.
- (38) Examples of various output destinations that may be considered include a monitor screen for surveillance on a display apparatus at a surveillance center, a terminal (unillustrated) carried by a guard or the like, and a monitor screen for surveillance on a display apparatus (unillustrated) at a police station. Output methods include at least one method out of display on a monitor screen, transmission of an email, and output of a voice or a warning sound from a speaker (unillustrated). At least one of an email address, an IP address of a mobile terminal, and a mobile phone number may be preregistered as an output destination.
- (39) As for an output content, a video from a surveillance camera **5** for which notification is to be given may be output along with information indicating a selected type of information. In a case of a surveillance center, a video from a surveillance camera **5** for which notification is to be given may be highlighted in a state of videos of a plurality of surveillance cameras **5** being multi-displayed. For example, multi-display of videos may be switched to single-screen display of only a video from a surveillance camera **5** for which notification is to be given or display of an enlarged view of the video. Alternatively, a border of a relevant screen in multi-display may be highlighted, or an image to be highlighted may be displayed by superimposition.
- (40) In addition to a video from the surveillance camera **5**, a static image of an image captured by the surveillance camera **5**, an image (such as an icon or an animation) indicating the type of output information, text information indicating the type of output information, information notifying occurrence of a crime may be displayed. Alternatively, a warning sound based on the type of output information or a voice indicating the type of output information may be output from a speaker at the surveillance center.
- (41) Hardware Configuration Example
- (42) FIG. **3** is a block diagram illustrating a hardware configuration of a computer **1000** providing each of the surveillance apparatus **100** and the image processing apparatus **200** in the surveillance system **1** illustrated in FIG. **1**.
- (43) The computer **1000** includes a bus **1010**, a processor **1020**, a memory **1030**, a storage device **1040**, an input-output interface **1050**, and a network interface **1060**.
- (44) The bus **1010** is a data transmission channel for the processor **1020**, the memory **1030**, the storage device **1040**, the input-output interface **1050**, and the network interface **1060** to transmit and receive data to and from one another. Note that the method of interconnecting the processor **1020** and other components is not limited to a bus connection.
- (45) The processor **1020** is a processor provided by a central processing unit (CPU), a graphics processing unit (GPU), or the like.
- (46) The memory **1030** is a main storage provided by a random access memory (RAM) or the like.
- (47) The storage device **1040** is an auxiliary storage provided by a hard disk drive (HDD), a solid state drive (SSD), a memory card, a read only memory (ROM), or the like. The storage device **1040** stores program modules implementing the functions of the surveillance apparatus **100** in the surveillance system **1** (such as the detection unit **102** and the output unit **104**). By reading each program module into the memory **1030** and executing the program module by the processor **1020**, each function related to the program module is implemented. Further, the storage device **1040** also functions as a storage unit storing various types of information used by the surveillance apparatus **100**.
- (48) A program module may be recorded in a storage medium. Storage media recording program modules may include a non-transitory tangible medium usable by the computer **1000**, and a program code readable by the computer **1000** (processor **1020**) may be embedded in the medium.

(49) The input-output interface **1050** is an interface for connecting the computer **1000** to various types of input-output equipment.

(50) The network interface **1060** is an interface for connecting the computer **1000** to a communication network **3**. Examples of the communication network **3** include a local area network (LAN) and a wide area network (WAN). The method of connecting the network interface **1060** to the communication network **3** may be a wireless connection or a wired connection. Note that the network interface **1060** may not be used.

(51) Then, the computer **1000** is connected to required equipment [such as the surveillance camera **5**, a display (unillustrated), and a speaker (unillustrated)] through the input-output interface **1050** or the network interface **1060**.

(52) The surveillance system **1** is provided by a combination of the surveillance apparatus **100** and the image processing apparatus **200** and therefore is provided by a plurality of computers **1000** constituting the apparatuses, respectively. For example, the surveillance apparatus **100** is a server computer. The image processing apparatus **200** may be an apparatus separate from the surveillance apparatus **100**, an apparatus included in the surveillance apparatus **100**, or a combination of the two.

(53) Each component in the surveillance apparatus **100** according to the present example embodiment in FIG. **2** is implemented by any combination of hardware and software in the computer **1000** in FIG. **3**. Then, it should be understood by a person skilled in the art that various modifications to the implementation method and the apparatus can be made. A block diagram illustrating the surveillance apparatus **100** according to each example embodiment illustrates a logical function-based block rather than a hardware-based configuration.

(54) <Operation Example>

(55) FIG. **4** is a flowchart illustrating an operation example of the surveillance apparatus **100** according to the present example embodiment. Based on a processing result of a captured image of an area around a road, the detection unit **102** detects that the relative distance between a person **20** and a vehicle **10** included in the image is in a state of being equal to or less than the reference value (Step **S103**), and the output unit **104** outputs information of a type selected by using an attribute of the person (Step **S107**).

(56) According to the present example embodiment, the detection unit **102** detects a person **20** and a vehicle **10** in the approaching state, and the output unit **104** outputs information selected based on an attribute of the person **20**. Thus, a situation in which a criminal act committed against a pedestrian or a vehicle, such as kidnapping or vehicle theft, may occur can be detected by using an image from the surveillance camera **5** capturing an image of an area around a road.

Second Example Embodiment

(57) <Functional Configuration Example>

(58) FIG. **5** is a functional block diagram illustrating a logical configuration example of the surveillance system in FIG. **1**. Note that while the image processing apparatus **200** is provided separately from the surveillance apparatus **100**, according to the first example embodiment, the present example embodiment is described under the assumption that a surveillance apparatus **100** also has a function of an image processing apparatus **200**. Note that it goes without saying that the surveillance apparatus **100** and the image processing apparatus **200** may be hardware-wise separate or the same.

(59) A surveillance system **1** includes the surveillance apparatus **100**, a storage apparatus **300**, and a surveillance camera **5**.

(60) The surveillance apparatus **100** outputs information used for surveillance, based on an image generated by the surveillance camera **5**.

(61) The storage apparatus **300** stores data required for performing image processing. For example, the storage apparatus **300** stores information about a feature value for identifying a vehicle **10** or a person **20**, and information about a feature value used for determining an attribute of a person.

(62) The surveillance apparatus **100** includes an acquisition unit **120**, an object determination unit **122**, a position determination unit **124**, an attribute determination unit **126**, a detection unit **102**, a selection unit **128**, and an output unit **104**.

(63) The acquisition unit **120** acquires an image generated by the surveillance camera **5**.

(64) The object determination unit **122** determines an object by performing image processing on an image acquired by the acquisition unit **120**. The object determination unit **122** recognizes and determines a person **20** and a vehicle **10**.

(65) By image processing, the position determination unit **124** determines the positions of a person **20** and a vehicle **10** determined by the object determination unit **122**.

(66) By image processing, the attribute determination unit **126** determines an attribute of a person **20** determined by the object determination unit **122**. The attribute determination unit **126** determines whether the person **20** possesses a first attribute or a second attribute.

(67) The first attribute is an attribute being highly likely to lead to a victim of a crime. Examples of the first attribute include “female,” “male,” “child (for example, an estimated age being X years old or younger),” “aged person (for example, an estimated age being Y years old or older),” “girl (such as a female whose estimated age is X years old or younger),” “boy (such as a male whose estimated age is X years old or younger),” “tourist (such as a person carrying a suitcase),” and “independent action (for example, no other person existing within a predetermined distance).” The first attribute is set based on features extracted from an image, such as gender, age, a feature of the face, height, belongings, clothing, and a situation (where X and Y are integers).

(68) The second attribute is an attribute different from the first attribute. The second attribute includes an attribute having a feature leading to a perpetrator of a criminal act and an attribute of a person other than a person possessing the first attribute, that is, an attribute other than an attribute being highly likely to lead to a victim of a criminal act.

(69) For example, the second attribute may include a person carrying a dangerous object (for example, carrying a long metal bar) and a person covering the face (such as a person wearing a mask). The second attribute is also set based on features extracted from an image, such as gender, age, a feature of the face, height, belongings, clothing, and a situation, similarly to the first attribute.

(70) Note that a person satisfying the first attribute has only to possess an attribute being highly likely to lead to a victim of a crime, and therefore the first attribute is settable according to a criminal situation in a region. For example, “male” may be set to the first attribute in a region where “male” frequently becomes a victim of a crime, and “female” may be set to the first attribute in a region where “female” frequently becomes a victim of a crime.

(71) The detection unit **102** acquires an attribute related to a person **20** determined by the object determination unit **122** and the positions of the person **20** and a vehicle **10**.

(72) For each pair of a person **20** and a vehicle **10** included in an image, the detection unit **102** determines whether the relative distance is in a state of being equal to or less than a reference value, that is, an approaching state, based on the positions.

(73) When the detection unit **102** detects a person **20** and a vehicle **10** in the approaching state, the selection unit **128** acquires an attribute of the person **20** in the approaching state. The selection unit **128** selects a type of information to be output, by using the attribute of the detected person **20**.

(74) The output unit **104** outputs information of the type selected by the selection unit **128**.

(75) <Operation Example>

(76) FIG. **6** is a flowchart illustrating an operation example of the surveillance system **1** according to the present example embodiment.

(77) The surveillance apparatus **100** acquires an image captured by the surveillance camera **5** and performs image processing (Step **S101**). Specifically, the object determination unit **122** recognizes and determines a person **20** and a vehicle **10** from the acquired image. Then, the position determination unit **124** determines the positions of the person **20** and the vehicle **10** determined by

the object determination unit **122**.

(78) Next, the detection unit **102** detects that the relative distance between the person **20** and the vehicle **10** included in the image is in a state of being equal to or less than the reference value (Step **S103**).

(79) When the relative distance between the person **20** and the vehicle **10** included in the image is equal to or less than the reference value (YES in Step **S103**), the attribute determination unit **126** determines an attribute of the person **20** determined by the object determination unit **122** (Step **S104**). The attribute determination unit **126** performs image processing on the person **20** included in the image and determines whether the person **20** possesses the first attribute or the second attribute.

(80) Note that the timing for determining an attribute of the person **20** may be before detection of the approaching state of the person **20** and the vehicle **10** by the detection unit **102**.

(81) Then, the selection unit **128** selects a type of information to be output, based on the attribute of the person **20** (Step **S105**).

(82) Then, the output unit **104** outputs information of the selected type (Step **S107**).

(83) Note that the output unit **104** may also output an image or a voice at the detection of the approaching state by the detection unit **102** or a video captured before and after the detection of the approaching state by the detection unit **102**.

(84) During a period in which a person **20** and a vehicle **10** in the approaching state are not detected by the detection unit **102**, the processing returns to Step **S101** and the processing is repeated.

(85) FIG. 7 is a flowchart illustrating an example of a detailed procedure of Step **S105** in FIG. 6. The attribute determination unit **126** determines an attribute of the person **20** detected by the detection unit **102** (Step **S111**).

(86) When the attribute determination unit **126** determines that the person **20** is a person possessing the first attribute in Step **S111**, the selection unit **128** selects a type of information indicating that the person **20** may fall victim to a crime. For example, the selection unit **128** selects information indicating that kidnapping of the person **20** may occur (Step **S115**).

(87) On the other hand, when the attribute determination unit **126** determines that the detected person **20** is a person possessing the second attribute in Step **S111**, the selection unit **128** selects a type of information indicating that the person **20** may commit a crime against the vehicle **10**. For example, the selection unit **128** selects information indicating that the person **20** may commit vehicle theft (Step **S117**). In other words, the selection unit **128** may also be considered to select whether the person **20** may fall victim to a crime or the vehicle **10** may fall victim to a crime.

(88) The processing returns to Step **S107** in FIG. 6 after Step **S115** and Step **S117**.

(89) Returning to FIG. 6, the output unit **104** outputs the selected type of information to a predetermined output destination (Step **S107**). For example, the output unit **104** may output the selected type of information to a server **220** at a surveillance center, and the server **220** at the surveillance center may output information indicating possible occurrence of kidnapping to a monitor screen on a display apparatus equipped in the surveillance center. Furthermore, an image indicating detection of the approaching state may be displayed.

(90) While display on a monitor screen has been exemplified as information output above, any other technique allowing notification of possible occurrence of a crime may be employed.

(91) For example, selected information output by the output unit **104** may be output by various methods such as voice output, output of a warning sound, transmission of an email to a terminal, and a notification. Further, the output unit **104** may make a change to a voice or a warning sound, a change to a mail content, or a change to a notified content, based on the information selected.

(92) According to the present example embodiment, the detection unit **102** detects a person **20** and a vehicle **10** in the approaching state, the selection unit **128** selects a type of crime, based on the attribute of the person **20**, and the output unit **104** outputs the selected information. Thus, a

situation in which a criminal act committed against a pedestrian or a vehicle, such as kidnapping or vehicle theft, may occur can be detected by using an image from the surveillance camera 5 capturing an image of an area around a road, and therefore occurrence of a criminal act can be detected. Further, a crime deterrent effect can be expected as surveillance by the surveillance camera 5 becomes widely known.

(93) Further, when the detection unit 102 detects the approaching state of a vehicle 10 and a person 20, the output unit 104 can output information selected based on the attribute of the person 20. Thus, even when a vehicle 10 may fall victim to vehicle theft or the like, a possibility of vehicle theft can be notified before the person 20 gets into the vehicle 10. For example, the output unit 104 may also output a warning message or a warning sound from a speaker or the like in the neighborhood of the spot. Thus, a crime prevention effect can be improved.

Third Example Embodiment

(94) <Functional Configuration Example>

(95) FIG. 8 is a functional block diagram illustrating a logical configuration example of the surveillance system in FIG. 1. A surveillance system 1 according to the present example embodiment is similar to those according to the aforementioned example embodiments except for using moving velocity of a vehicle 10 for determination of a type of information to be output instead of using an attribute of a person 20. A surveillance apparatus 100 according to the present example embodiment includes a moving velocity estimation unit 130 in place of the attribute determination unit 126 in FIG. 5.

(96) Note that the configuration according to the present example embodiment may be combined with at least one of the configurations according to the other example embodiments without contradicting each other.

(97) The surveillance apparatus 100 includes an acquisition unit 120, an object determination unit 122, a position determination unit 124, the moving velocity estimation unit 130, a detection unit 102, a selection unit 128, and an output unit 104.

(98) The acquisition unit 120 acquires an image generated by a surveillance camera 5.

(99) The object determination unit 122 determines an object by performing image processing on an image acquired by the acquisition unit 120. The object determination unit 122 recognizes and determines a person 20 and a vehicle 10.

(100) By image processing, the position determination unit 124 determines the positions of a person 20 and a vehicle 10 determined by the object determination unit 122.

(101) The moving velocity estimation unit 130 detects, in a plurality of time-series images, the positions of a feature part of a vehicle 10 determined by the position determination unit 124 and estimates moving velocity from a change in the position of the vehicle 10. Further, the moving velocity estimation unit 130 may detect, in a plurality of time-series images, the positions of a feature part of each of a person 20 and a vehicle 10 determined in an image and estimate a change in velocity of the vehicle 10 relative to the person 20 from a change in a relative positional relation between the person 20 and the vehicle 10. Furthermore, the moving velocity estimation unit 130 can similarly estimate the moving direction of each of the person 20 and the vehicle 10.

(102) For example, the moving velocity estimation unit 130 can estimate at what velocity and from which direction a vehicle 10 approaches a person 20 or at what velocity and in which direction the vehicle 10 moves away from the person 20.

(103) For example, in a case of kidnapping, a vehicle 10 approaches a person 20 from behind at a low speed, puts the person 20 into the vehicle 10, and drives off from the spot. Therefore, when estimating that the moving velocity of a vehicle 10 is low and estimating that the vehicle 10 is moving in a direction approaching a person 20, the moving velocity estimation unit 130 can determine that kidnapping may occur. Further, in a case of vehicle theft, a person 20 approaches a stationary vehicle 10, and the person 20 subsequently goes away. Therefore, when estimating that a vehicle 10 is stationary, the moving velocity estimation unit 130 can determine that vehicle theft

may occur. Note that when the moving velocity of a vehicle **10** is normal travel velocity, the vehicle **10** may be determined to be traveling normally.

(104) For each pair of a person **20** and a vehicle **10** included in an image, the detection unit **102** determines whether the pair is in a state of the relative distance being equal to or less than a reference value, that is, an approaching state, based on the positions.

(105) By using the moving velocity of a vehicle **10** estimated by the moving velocity estimation unit **130**, the selection unit **128** selects a type of information to be output.

(106) The output unit **104** outputs information of the type selected by the selection unit **128**.

(107) <Operation Example>

(108) FIG. **9** is a flowchart illustrating an example of operation of the surveillance system **1**. The flowchart in FIG. **9** includes Step **S101**, Step **S103**, and Step **S107** in the flowchart in FIG. **6** and also includes Step **S204** and Step **S205** in place of Step **S104** and Step **S105** in FIG. **6**.

(109) The surveillance apparatus **100** acquires an image captured by the surveillance camera **5** and performs image processing (Step **S101**). Specifically, the object determination unit **122** recognizes and determines a person **20** and a vehicle **10** from the acquired image. Then, the position determination unit **124** determines the positions of the person **20** and the vehicle **10** determined by the object determination unit **122**.

(110) Next, the detection unit **102** detects that the relative distance between the person **20** and the vehicle **10** included in the image is in a state of being equal to or less than the reference value (Step **S103**).

(111) When the relative distance between the person **20** and the vehicle **10** included in the image is equal to or less than the reference value (YES in Step **S103**), the moving velocity estimation unit **130** estimates the moving velocity of the vehicle **10** (Step **S204**).

(112) Then, the selection unit **128** selects a type of information to be output, based on the moving velocity of the vehicle **10** (Step **S205**).

(113) Then, the output unit **104** outputs information of the selected type (Step **S107**).

(114) FIG. **10** is a flowchart illustrating an example of a detailed procedure of Step **S205** in FIG. **9**. The moving velocity estimation unit **130** determines the moving velocity of the vehicle **10** (Step **S211**). When the moving velocity estimation unit **130** determines that the vehicle **10** is approaching the person **20** at a low speed in Step **S211**, the selection unit **128** determines that the person **20** may fall victim to a crime and selects a type of information indicating that the person **20** may fall victim to a crime as a type of information to be output. For example, the selection unit **128** selects information indicating that kidnapping of the person **20** may occur (Step **S115**). On the other hand, when the moving velocity estimation unit **130** determines that the vehicle **10** is stationary in Step **S211**, the selection unit **128** determines that the person **20** may commit a crime and selects a type of information indicating that the person **20** may commit a crime as a type of information to be output. For example, the selection unit **128** selects information indicating that the person **20** may commit vehicle theft (Step **S117**). The processing returns to Step **S107** in FIG. **9** after Step **S115** and Step **S117**.

(115) Further, when the moving velocity estimation unit **130** determines that the moving velocity of the vehicle **10** indicates neither approaching at a low speed nor stationary in Step **S211**, the vehicle **10** may be determined to be merely passing, and therefore the processing returns to Step **S107** in FIG. **9**.

(116) Returning to FIG. **9**, the output unit **104** outputs information of the selected type (Step **S107**). When a person **20** and a vehicle **10** in the approaching state are not detected (NO in Step **S103**), the processing returns to Step **S101**, and the processing is repeated.

(117) According to the present example embodiment, the detection unit **102** detects a person **20** and a vehicle **10** in the approaching state, and the selection unit **128** determines, by using the moving velocity of the vehicle **10**, whether the person **20** may fall victim to a crime or the person **20** may commit a crime and selects information based on the determination result. Then, the output unit

104 outputs the selected information. Thus, by using an image from the surveillance camera **5** capturing an image of an area around a road, a type of criminal act such as kidnapping or vehicle theft can be detected. Further, a crime deterrent effect can be expected due to a wide spread of a fact that surveillance is being performed by the surveillance camera **5**.

Fourth Example Embodiment

(118) <Functional Configuration Example>

(119) FIG. **11** is a functional block diagram illustrating a logical configuration example of the surveillance system in FIG. **1**. A surveillance system **1** according to the present example embodiment is similar to that according to either of the second example embodiment and the third example embodiment except that a surveillance apparatus **100** has both the function according to the second example embodiment and the function according to the third example embodiment. The surveillance apparatus **100** according to the present example embodiment may be combined with at least one of the configurations according to the other example embodiments without contradicting each other.

(120) The surveillance apparatus **100** includes an acquisition unit **120**, an object determination unit **122**, a position determination unit **124**, an attribute determination unit **126**, a moving velocity estimation unit **130**, a detection unit **102**, a selection unit **128**, and an output unit **104**.

(121) The acquisition unit **120** acquires an image generated by the surveillance camera **5**.

(122) The object determination unit **122** determines an object by performing image processing on an image acquired by the acquisition unit **120**. The object determination unit **122** recognizes and determines a person **20** and a vehicle **10**.

(123) By image processing, the position determination unit **124** determines the positions of a person **20** and a vehicle **10** determined by the object determination unit **122**.

(124) The attribute determination unit **126** determines an attribute of a person **20** by image processing. The attribute determination unit **126** determines whether the person **20** possesses a first attribute or a second attribute.

(125) The moving velocity estimation unit **130** detects, in a plurality of time-series images, the positions of a feature part of a vehicle **10** determined by the position determination unit **124** and estimates moving velocity from a change in the position of the vehicle **10**.

(126) For each pair of a person **20** and a vehicle **10** included in an image, the detection unit **102** determines whether the relative distance is in a state of being equal to or less than a reference value, that is, an approaching state, based on the positions.

(127) The selection unit **128** selects a type of information to be output, by using the moving velocity of a vehicle **10** estimated by the moving velocity estimation unit **130** and an attribute determined by the attribute determination unit **126**.

(128) The output unit **104** outputs information of the type selected by the selection unit **128**.

(129) <Operation Example>

(130) FIG. **12** is a flowchart illustrating an example of operation of the surveillance system **1**. The flowchart in FIG. **12** includes Step **S101**, Step **S103**, Step **S104**, and Step **S107** in the flowchart in FIG. **6** and Step **S204** in FIG. **9** and also includes Step **S305** in place of Step **S105** in FIG. **6** or Step **S205** in FIG. **9**.

(131) The surveillance apparatus **100** acquires an image captured by the surveillance camera **5** and performs image processing (Step **S101**). Specifically, the object determination unit **122** recognizes and determines each of a person **20** and a vehicle **10** from the acquired image. Then, the position determination unit **124** determines the positions of the person **20** and the vehicle **10** determined by the object determination unit **122**.

(132) Next, the detection unit **102** detects that the relative distance between the person **20** and the vehicle **10** included in the image is in a state of being equal to or less than the reference value (Step **S103**).

(133) When the relative distance between the person **20** and the vehicle **10** included in the image is

equal to or less than the reference value (YES in Step S103), the attribute determination unit 126 determines an attribute of the person 20 determined by the object determination unit 122 (Step S104). Furthermore, the moving velocity estimation unit 130 detects, in a plurality of time-series images, the positions of a feature part of the vehicle 10 determined by the position determination unit 124 and estimates the moving velocity of the vehicle 10 from a change in the position of the vehicle 10 (Step S204).

(134) Then, the selection unit 128 selects a type of information to be output, based on the attribute of the person 20 and the moving velocity of the vehicle 10 (Step S305).

(135) Then, the output unit 104 outputs information of the selected type (Step S107).

(136) FIG. 13 is a flowchart illustrating an example of a detailed procedure of Step S305 in FIG. 12. The attribute determination unit 126 determines an attribute of the person 20 determined by the object determination unit 122 (Step S111). In Step S111, the attribute determination unit 126 determines whether the person 20 is a person possessing the first attribute and when determining that the person 20 is a person possessing the first attribute, advances to Step S121. On the other hand, when determining that the person 20 is a person possessing the second attribute in Step S111, the attribute determination unit 126 advances to Step S123.

(137) When the moving velocity estimation unit 130 determines that the vehicle 10 is approaching the person 20 at a low speed in Step S121 (YES in Step S121), the selection unit 128 determines that the person 20 may fall victim to a crime and selects a type of information indicating that the person 20 may fall victim to a crime as a type of information to be output. For example, the selection unit 128 selects information indicating that kidnapping of the person 20 may occur (Step S115). When the moving velocity estimation unit 130 determines that the vehicle 10 is not approaching the person 20 at a low speed (NO in Step S121), the vehicle 10 may be determined to be merely passing, and therefore the processing returns to Step S107 in FIG. 12.

(138) When the moving velocity estimation unit 130 determines that the vehicle 10 is stationary in Step S123 (YES in Step S123), the selection unit 128 determines that the vehicle 10 is stationary, determines that the person 20 may commit a crime, and selects a type of information indicating that the person 20 may commit a crime as a type of information to be output. For example, the selection unit 128 selects information indicating that the person 20 may commit vehicle theft (Step S117). When the moving velocity estimation unit 130 determines that the vehicle 10 is not stationary (NO in Step S123), the vehicle 10 is determined to be merely passing, and therefore the processing returns to Step S107 in FIG. 12.

(139) The processing returns to Step S107 in FIG. 12 after Step S115 and Step S117.

(140) FIG. 14 is a flowchart illustrating another example of a detailed procedure of Step S305 in FIG. 12. The procedure illustrated in FIG. 14 is the same as the procedure in FIG. 13 except that a determination using the moving velocity of the vehicle 10 is made earlier (Step S211) and subsequently a determination using the attribute of the person 20 is made (Step S131 and Step S133).

(141) The selection unit 128 makes a determination, based on the moving velocity of the vehicle 10 estimated by the moving velocity estimation unit 130 (Step S211). When the moving velocity estimation unit 130 determines that the vehicle 10 is approaching the person 20 at a low speed in Step S211, the processing advances to Step S131. When the moving velocity estimation unit 130 determines that the vehicle 10 is stationary in Step S211, the processing advances to Step S133. Further, when the moving velocity estimation unit 130 determines that the moving velocity of the vehicle 10 indicates neither approaching at a low speed nor stationary in Step S211, the vehicle 10 may be determined to be merely passing, and therefore the processing returns to Step S107 in FIG. 12.

(142) When the attribute determination unit 126 determines that the person 20 is a person possessing the first attribute in Step S131 (YES in Step S131), the selection unit 128 selects a type of information indicating that the person 20 may fall victim to a crime as a type of information to

be output. For example, the output unit **104** selects information indicating that kidnapping of the person **20** may occur (Step **S115**). When the attribute determination unit **126** determines that the person **20** is not a person possessing the first attribute (NO in Step **S131**), the processing returns to Step **S107** in FIG. **12**.

(143) When the attribute determination unit **126** determines that the person **20** is a person possessing the second attribute in Step **S133** (YES in Step **S133**), the selection unit **128** determines that the person **20** may commit a crime and selects a type of information indicating that the person **20** may commit a crime as a type of information to be output. For example, the selection unit **128** selects information indicating that the person **20** may commit vehicle theft (Step **S117**). When the attribute determination unit **126** determines that the person **20** is not a person possessing the second attribute (NO in Step **S133**), the processing returns to Step **S107** in FIG. **12**.

(144) The processing returns to Step **S107** in FIG. **12** after Step **S115** and Step **S117**.

(145) When the vehicle **10** is determined to be merely passing or stopping in Step **S121** or Step **S123**, or Step **S211**, Step **S131**, or Step **S133** in the flowchart in FIG. **13** or FIG. **14**, a type of information to be output is not selected, and therefore the output unit **104** performs processing without outputting information in Step **S107** in FIG. **12**. However, when the vehicle **10** is determined to be merely passing or stopping in Step **S121** or Step **S123**, or Step **S211**, Step **S131**, or Step **S133** in the flowchart in FIG. **13** or FIG. **14**, passage or stopping of the vehicle **10** may be respectively selected as a type of information to be output. In that case, the output unit **104** may select and output information indicating passage or stopping of the vehicle **10** in Step **S107** in FIG. **12**.

(146) The present example embodiment provides an effect similar to those of the aforementioned example embodiments and can further select a type of information to be output, by using both the moving velocity of a vehicle **10** and an attribute of a person **20**, and therefore increases the possibility to more precisely detect a criminal act.

Fifth Example Embodiment

(147) <Functional Configuration Example>

(148) FIG. **15** is a functional block diagram illustrating a logical configuration example of the surveillance system in FIG. **1**. A surveillance system **1** according to the present example embodiment is the same as that according to the second example embodiment except for selecting a type of information to be output, based on whether a person **20** is taking an independent action. In addition to the configuration according to the second example embodiment in FIG. **5**, a surveillance apparatus **100** according to the present example embodiment further includes a head count determination unit **132**. Note that the surveillance apparatus **100** according to the present example embodiment may be combined with at least one of the configurations according to the other example embodiments without contradicting each other.

(149) The surveillance apparatus **100** includes an acquisition unit **120**, an object determination unit **122**, a position determination unit **124**, an attribute determination unit **126**, the head count determination unit **132**, a detection unit **102**, a selection unit **128**, and an output unit **104**.

(150) The acquisition unit **120** acquires an image generated by a surveillance camera **5**.

(151) The object determination unit **122** determines an object by performing image processing on an image acquired by the acquisition unit **120**. The object determination unit **122** recognizes and determines a person **20** and a vehicle **10**.

(152) The position determination unit **124** determines the positions of a person **20** and a vehicle **10** determined by the object determination unit **122**.

(153) The attribute determination unit **126** determines an attribute of a person **20** by image processing. The attribute determination unit **126** determines whether the person **20** possesses a first attribute or a second attribute.

(154) The head count determination unit **132** determines the number of persons **20**. For example, the head count determination unit **132** determines whether a plurality of persons **20** are determined

by the object determination unit **122**. When the object determination unit **122** determines a plurality of persons **20**, the head count determination unit **132** determines whether persons the distance between whom is equal to or less than a reference value exist among the persons **20**. For example, the head count determination unit **132** determines whether persons the distance between whom is equal to or less than the reference value exist among a plurality of persons **20**, based on the positions of the persons **20** determined by the position determination unit **124**. Note that the reference value may be the same value as a reference value for determining the relative distance between a vehicle **10** and a person **20** or may be a different value.

(155) When persons the distance between whom is equal to or less than the reference value exist among the plurality of persons **20**, the head count determination unit **132** determines that the persons do not take independent actions. The head count determination unit **132** determines that an independent action is being taken when a plurality of persons **20** do not exist or persons the distance between whom is equal to or less than the reference value do not exist among a plurality of persons **20**.

(156) The reason is that kidnapping is likely to occur particularly when a person is alone. Note that an independent action may involve not only a single person but also a small number of persons such as two or three persons.

(157) For each pair of a person **20** and a vehicle **10** included in an image, the detection unit **102** determines whether the relative distance is in a state of being equal to or less than a reference value, that is, an approaching state, based on the positions.

(158) The selection unit **128** selects a type of information to be output depending on whether a determination result made by the head count determination unit **132** indicates that a person **20** is taking an independent action.

(159) The output unit **104** outputs information of the type selected by the selection unit **128**.

(160) <Operation Example>

(161) FIG. **16** is a flowchart illustrating an example of operation of the surveillance system **1**. The flowchart in FIG. **16** includes Step **S141** in place of Step **S121** in the flowchart in FIG. **13**.

However, the flowchart in FIG. **16** may include Step **S121** in FIG. **13**. The order of Step **S121** and Step **S141** is not particularly limited.

(162) The attribute determination unit **126** determines an attribute of the person **20** determined by the object determination unit **122** (Step **S111**). When determining that the person **20** possesses the first attribute in Step **S111**, the attribute determination unit **126** advances to Step **S141**. On the other hand, when determining that the person **20** possesses the second attribute in Step **S111**, the attribute determination unit **126** advances to Step **S123**.

(163) When the head count determination unit **132** determines that the person **20** is taking an independent action in Step **S141** (YES in Step **S141**), the selection unit **128** selects a type of information indicating that the person **20** may fall victim to a crime as a type of information to be output. For example, the output unit **104** selects information indicating that kidnapping of the person **20** may occur (Step **S115**). When the head count determination unit **132** determines that the person **20** is not taking an independent action (NO in Step **S141**), the vehicle **10** may be determined to be merely passing, and therefore the processing returns to Step **S107** in FIG. **12**.

(164) Processing in and after Step **S123** is the same as that in FIG. **13**, and therefore description thereof is not repeated.

(165) FIG. **17** is a flowchart illustrating another example of operation of the surveillance system **1**. The flowchart in FIG. **17** is the same as that in FIG. **16** except that the order of Step **S111** and Step **S141** is reversed in the flowchart in FIG. **16**. The flowchart in FIG. **17** may include Step **S121** in FIG. **13**. In that case, the order of Step **S121** and Step **S141** is not particularly limited.

(166) The head count determination unit **132** determines whether the person **20** is taking an independent action (Step **S141**). When the head count determination unit **132** determines that the person **20** is taking an independent action in Step **S141** (YES in Step **S141**), the processing

advances to Step S111. When the head count determination unit 132 determines that the person 20 is not taking an independent action in Step S141 (NO in Step S141), the vehicle 10 is determined to be merely passing, and therefore the processing returns to Step S107 in FIG. 12. (167) In Step S111, the attribute determination unit 126 determines an attribute of the person 20 determined by the object determination unit 122. When the attribute determination unit 126 determines that the person 20 possesses the first attribute in Step S111, the processing advances to Step S115. On the other hand, when the attribute determination unit 126 determines that the person 20 possesses the second attribute in Step S111, the processing advances to Step S123. Processing from here onward is the same as that in FIG. 16, and therefore description thereof is not repeated. (168) The present example embodiment enables determination of whether a person 20 is taking an independent action by the head count determination unit 132 and when the person 20 is taking an independent action, enables output that kidnapping is highly likely to occur. By combination with another condition, determination precision can be further improved and frequent notification can be prevented.

Sixth Example Embodiment

(169) <Functional Configuration Example>

(170) A surveillance system 1 according to the present example embodiment differs from that according to the aforementioned fourth example embodiment in being configured to detect that a vehicle 10 is in a stationary state and that entry and exit of a person 20 are performed after the vehicle becomes stationary and to select a type of information to be output by using the result. Specifically, operation of a detection unit 102 and operation of a selection unit 128 are different. The surveillance system 1 is described below by using the functional block diagram according to the fourth example embodiment in FIG. 11. Note that a surveillance apparatus 100 according to the present example embodiment may be combined with at least one of the configurations according to the other example embodiments without contradicting each other.

(171) For each pair of a person 20 and a vehicle 10 included in an image, the detection unit 102 determines whether the relative distance is in a state of being equal to or less than a reference value, that is, an approaching state, based on the positions. Further, when determining that a vehicle 10 determined to be in the approaching state by the detection unit 102 is in the stationary state from moving velocity estimated by the moving velocity estimation unit 130, the detection unit 102 further detects whether entry and exit of a person into and from the vehicle 10 are made.

(172) The selection unit 128 selects a type of information to be output, by further using a detection result of entry and exit of a person by the detection unit 102.

(173) For example, as illustrated in FIG. 18, in a case of kidnapping, a vehicle 10 may approach a person 20 (in FIG. 18A to in FIG. 18B), grab the person 20 by extending only an arm from the vehicle 10, drag the person 20 into the vehicle 10, and take the person 20 away (in FIG. 18C). In other words, a person does not come out of the stationary vehicle 10 in the case of kidnapping. In a case of vehicle theft, a driver is highly likely to come out of a stationary vehicle 10. By detecting the situations, kidnapping and vehicle theft are discriminated.

(174) <Operation Example>

(175) FIG. 19 is a flowchart illustrating an example of operation of the surveillance system 1. The flowchart in FIG. 19 includes Step S211, Step S131, Step S133, Step S115, and Step S117 in the flowchart in FIG. 14 and further includes Step S151.

(176) In Step S211, when the moving velocity estimation unit 130 estimates that the vehicle 10 is moving at a low speed and the detection unit 102 determines that the vehicle 10 is approaching the person 20, the process advances to Step S131, and the attribute determination unit 126 determines an attribute of the person 20.

(177) Next, when determining that the vehicle 10 is stationary in Step S211, the moving velocity estimation unit 130 advances to Step S151. In Step S151, the detection unit 102 determines whether a person, that is, a driver comes out of the stationary vehicle 10. For example, the

detection unit **102** may detect entry and exit of a person by determining whether a person comes out of the vehicle **10** within a predetermined time from the determination that the vehicle is in the stationary state by the moving velocity estimation unit **130**.

(178) When the detection unit **102** detects that a person does not come out of the vehicle **10** within the predetermined time (NO in Step **S151**), the possibility of kidnapping is high, and therefore the processing advances to Step **S131**. Further, when the moving velocity estimation unit **130** determines that the moving velocity of the vehicle **10** indicates neither approaching at a low speed nor stationary in Step **S211**, the vehicle **10** may be determined to be merely passing, and therefore the processing returns to Step **S107** in FIG. **12**. Processing in and after Step **S131** is the same as that according to the aforementioned example embodiments, and therefore description thereof is not repeated.

(179) On the other hand, when the detection unit **102** detects a person coming out of the vehicle **10** (YES in Step **S151**), the attribute determination unit **126** determines an attribute of the person **20** in the approaching state (Step **S133**). Then, when the attribute determination unit **126** determines that the person possesses the second attribute (YES in Step **S133**), the selection unit **128** selects information indicating that the person **20** may commit vehicle theft, similarly to FIG. **14** (Step **S117**).

(180) The present example embodiment enables selection of a type of information to be processed by detecting whether a person comes out of a stationary vehicle **10**. Accordingly, determination precision can be further improved.

(181) While the example embodiments of the present invention have been described above with reference to the drawings, the example embodiments are exemplifications of the present invention, and various configurations other than those described above may be employed.

(182) For example, since detection of a criminal act is performed by using an image from the surveillance camera **5**, an image at detection of the criminal act can be recorded, and the record can be used as evidence at occurrence of a crime. The above can lead to early resolution of a case, arrest of a culprit, and rescue of a victim.

(183) Furthermore, the detection unit **102** may perform processing by using an image from a specific surveillance camera **5** out of a plurality of surveillance cameras **5** each capturing an image of an area around a road. As described above, surveillance may be performed by using an image from a surveillance camera **5** installed at a particularly unsafe location, a location where criminal acts such as kidnapping and vehicle theft frequently occur, or the like. Further, priority may be given to a specific surveillance camera **5**, and the proportion of surveillance time of the high-priority surveillance camera **5** may be set longer than that of another surveillance camera **5**.

(184) Furthermore, the detection unit **102** may acquire and store a facial image of a person **20**, the relative distance between a vehicle **10** and the person **20** being detected to be in a state of being equal to or less than a reference value. The facial image may be stored in the memory **1030** or the storage device **1040** in FIG. **3**, or the like.

(185) As illustrated in FIG. **20**, in a case of vehicle theft, an owner **30** of a stationary vehicle **10** first comes out of the vehicle **10** (in FIG. **20A**). The detection unit **102** detects a person coming out of the vehicle **10** and acquires and temporarily stores a facial image of the person A (the owner of the vehicle **10**) coming out of the vehicle **10**.

(186) Further continuing the surveillance, the detection unit **102** detects a person **20** approaching the vehicle **10** (in FIG. **20B**). At this time, the detection unit **102** acquires a facial image of the person **20**. Then, the detection unit **102** may transmit the facial image of the person A acquired earlier and the facial image of the person **20** acquired later to the image processing apparatus **200** and cause the image processing apparatus **200** to check whether the two are the same person. The selection unit **128** selects a type of information to be output, by using the check result. When the two are not the same person, it is determined to be the vehicle theft (in FIG. **20C**). When the two are the same person, it is determined to be the owner.

(187) Further, in a case of a facial image not being able to be captured, the person **20** approaching the vehicle **10** in FIG. **20B** may be determined to commit vehicle theft when the person **20** comes out of the vehicle **10** immediately (after a predetermined time) after once getting into the vehicle **10**.

(188) Furthermore, a procedure other than the example of detecting entry and exit of a person into and from a stationary vehicle **10** and using the result thereof as described in FIG. **19** according to the fifth example embodiment may be considered. FIG. **21** is a flowchart illustrating an example of operation of the surveillance system **1**. The flowchart in FIG. **21** includes Step **S151** in place of Step **S131** in the flowchart in FIG. **14**. In this example, when the detection unit **102** determines that the vehicle **10** is approaching the person **20** at a low speed in Step **S211**, the processing advances to Step **S151**, and whether a person comes out of the vehicle **10** is determined. When the detection unit **102** does not detect a person coming out (NO in Step **S151**), the possibility of kidnapping is high, and therefore the processing advances to Step **S115**. When the detection unit **102** detects a person coming out (YES in Step **S151**), the vehicle **10** is determined to be merely stopping, and therefore the processing returns to Step **S107** in FIG. **12**. The remaining processing is the same as that in FIG. **14**, and therefore description thereof is not repeated.

(189) While the present invention has been described with reference to example embodiments (and examples) thereof, the present invention is not limited to the aforementioned example embodiments (and examples). Various changes and modifications that may be understood by a person skilled in the art may be made to the configurations and details of the present invention without departing from the scope of the present invention.

(190) Note that when information about a user is acquired and/or used in the present invention, the acquisition and/or use is assumed to be performed legally.

(191) Examples of reference embodiments are added as supplementary notes below.

(192) 1. A surveillance apparatus including: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that selects a type of information to be output, by using an attribute of the person detected to be in the state, and outputting the selected type of information.

(193) 2. The surveillance apparatus according to 1., wherein the output unit selects the type of information to be output, by further using moving velocity of the vehicle detected to be in the state.

(194) 3. A surveillance apparatus including: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that selects a type of information to be output, by using moving velocity of the vehicle detected to be in the state, and outputs the selected type of information.

(195) 4. The surveillance apparatus according to any one of 1. to 3., wherein the output unit selects the type of information to be output, further depending on whether the person detected to be in the state takes an independent action.

(196) 5. The surveillance apparatus according to any one of 1. to 4., wherein the detection unit detects that the vehicle detected to be in the state is determined to be in a stationary state, and that entry and exit of a person are performed after the vehicle becomes stationary, and the output unit selects the type of information to be output by further using a detection result made by the detection unit.

(197) 6. The surveillance apparatus according to any one of 1. to 5., wherein the detection unit performs the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(198) 7. A surveillance system including: a plurality of cameras each capturing an image of an area around a road; and a surveillance apparatus surveilling images captured by a plurality of cameras, wherein the surveillance apparatus includes: a detection unit that processes an image in which an

area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that selects a type of information to be output, by using an attribute of the person detected to be in the state, and outputs the selected type of information.

(199) 8. The surveillance system according to 7., wherein the output unit in the surveillance apparatus selects the type of information to be output, by further using moving velocity of the vehicle detected to be in the state.

(200) 9. A surveillance system including: a plurality of cameras each capturing an image of an area around a road; and a surveillance apparatus surveilling images captured by a plurality of cameras, wherein the surveillance apparatus includes: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that selects a type of information to be output, by using moving velocity of the vehicle detected to be in the state, and outputs the selected type of information.

(201) 10. The surveillance system according to any one of 7. to 9., wherein the output unit in the surveillance apparatus selects the type of information to be output, further depending on whether the person detected to be in the state takes an independent action.

(202) 11. The surveillance system according to any one of 7. to 10., wherein, the detection unit in the surveillance apparatus detects that the vehicle detected to be in the state is determined to be in a stationary state, and that entry and exit of a person are performed after the vehicle becomes stationary, and the output unit in the surveillance apparatus selects the type of information to be output, by further using a detection result made by the detection unit.

(203) 12. The surveillance system according to any one of 7. to 11., wherein the detection unit in the surveillance apparatus performs the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(204) 13. A surveillance method including, by a surveillance apparatus: processing an image in which an area around a road is captured and detecting that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and selecting a type of information to be output, by using an attribute of the person detected to be in the state, and outputting the selected type of information.

(205) 14. The surveillance method according to 13., further including, by the surveillance apparatus, selecting the type of information to be output, by further using moving velocity of the vehicle detected to be in the state.

(206) 15. A surveillance method including, by a surveillance apparatus: processing an image in which an area around a road is captured and detecting that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and selecting a type of information to be output, by using moving velocity of the vehicle detected to be in the state, and outputting the selected type of information.

(207) 16. The surveillance method according to any one of 13. to 15., further including, by the surveillance apparatus, selecting the type of information to be output, further depending on whether the person detected to be in the state takes an independent action.

(208) 17. The surveillance method according to any one of 13. to 16., further including, by the surveillance apparatus: detecting that the vehicle detected to be in the state is in a stationary state, and that entry and exit of a person are performed after the vehicle becomes stationary; and selecting the type of information to be output, by further using the detection result.

(209) 18. The surveillance method according to any one of 13. to 17., further including, by the surveillance apparatus, performing the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(210) 19. A program for causing a computer to execute: a procedure for processing an image in which an area around a road is captured and detecting that a relative distance between a person and

a vehicle included in the image is in a state of being equal to or less than a reference value; and a procedure for selecting a type of information to be output, by using an attribute of the person detected to be in the state, and outputting the selected type of information.

(211) 20. The program according to 19., further causing a computer to execute a procedure for selecting the type of information to be output, by further using moving velocity of the vehicle detected to be in the state.

(212) 21. A program for causing a computer to execute: a procedure for processing an image in which an area around a road is captured and detecting that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and a procedure for selecting a type of information to be output, by using moving velocity of the vehicle detected to be in the state, and outputting the selected type of information.

(213) 22. The program according to any one of 19. to 21., further causing a computer to execute a procedure for selecting the type of information to be output, further depending on whether the person detected to be in the state takes an independent action.

(214) 23. The program according to any one of 19. to 22., further causing a computer to execute: a procedure for detecting that the vehicle detected to be in the state is determined to be in a stationary state, and that entry and exit of a person are performed after the vehicle becomes stationary; and a procedure for selecting the type of information to be output, by further using a detection result made by the procedure for detection.

(215) 24. The program according to any one of 19. to 23., further causing a computer to execute a procedure for performing the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(216) More examples of reference embodiments are added as supplementary notes below.

(217) 25. A surveillance apparatus including: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that outputs a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.

(218) 26. The surveillance apparatus according to 25., further including: an acquisition unit that acquires the image in which the area around the road is captured, the image being generated by a camera; an object determination unit that recognizes and determining a person and a vehicle by performing image processing on the image acquired by the acquisition unit; a position determination unit that, by performing the image processing, determines positions of the person and the vehicle determined by the object determination unit; an attribute determination unit that, by performing the image processing, determines an attribute of the person determined by the position determination unit; and a selection unit that, when the detection unit detects a person and a vehicle in the state, selects the type of information to be output, by using the determined attribute of the detected person, wherein the output unit outputs information of the type selected by the selection unit.

(219) 27. The surveillance apparatus according to 25. or 26., further including: an acquisition unit that acquires the image in which the area around the road is captured, the image being generated by a camera; an object determination unit that recognizes and determines a person and a vehicle by performing image processing on the image acquired by the acquisition unit; a position determination unit that, by performing the image processing, determines positions of the person and the vehicle determined by the object determination unit; a moving velocity estimation unit that estimates moving velocity of the vehicle determined by the position determination unit, from a change in a position of the vehicle; and a selection unit that selects the type of information to be output, by using the moving velocity of the vehicle estimated by the moving velocity estimation unit, wherein the output unit outputs information of the type selected by the selection unit.

(220) 28. The surveillance apparatus according to any one of 25. to 27., further including: an

acquisition unit that acquires the image in which the area around the road is captured, the image being generated by a camera; an object determination unit that recognizes and determines a person and a vehicle by performing image processing on the image acquired by the acquisition unit; a position determination unit that, by performing the image processing, determines positions of the person and the vehicle determined by the object determination unit; a headcount determination unit that determines the number of the persons determined by the object determination unit and determines whether the determined person takes an independent action; and a selection unit that selects a type of the information to be output based on a determination result made by the headcount determination unit, wherein the output unit outputs information of the type selected by the selection unit.

(221) 29. The surveillance apparatus according to 27. or 28. citing 27., wherein, when determining that the vehicle detected to be in the state is in a stationary state from the moving velocity estimated by the moving velocity estimation unit, the detection unit further detects whether entry and exit of a person into and from the vehicle are performed, the selection unit selects a type of the information to be output, by further using a detection result of the entry and exit of the person made by the detection unit, and the output unit outputs information of the type selected by the selection unit.

(222) 30. The surveillance apparatus according to any one of 25. To 29., wherein the detection unit performs the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(223) 31. A surveillance system including: a plurality of cameras each capturing an image of an area around a road; and a surveillance apparatus surveilling images captured by a plurality of cameras, wherein the surveillance apparatus includes: a detection unit that processes an image in which an area around a road is captured and detects that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and an output unit that outputs a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.

(224) 32. The surveillance system according to 31., wherein the surveillance apparatus further includes: an acquisition unit that acquires the image in which the area around the road is captured, the image being generated by a camera; an object determination unit that recognizes and detects a person and a vehicle by performing image processing on the image acquired by the acquisition unit; a position determination unit that, by performing the image processing, determines positions of the person and the vehicle determined by the object determination unit; an attribute determination unit that, by performing the image processing, determines an attribute of the person determined by the position determination unit; and a selection unit that, when the detection unit detects a person and a vehicle in the state, selects the type of information to be output, by using the determined attribute of the detected person, wherein the output unit in the surveillance apparatus outputs information of the type selected by the selection unit.

(225) 33. The surveillance system according to 31. or 32., wherein the surveillance apparatus further includes: an acquisition unit that acquires the image in which the area around the road is captured, the image being generated by a camera; an object determination unit that recognizes and determines a person and a vehicle by performing image processing on the image acquired by the acquisition unit; a position determination unit that, by performing the image processing, determines positions of the person and the vehicle determined by the object determination unit; a moving velocity estimation unit that estimates moving velocity of the vehicle determined by the position determination unit, from a change in a position of the vehicle; and a selection unit that selects the type of information to be output, by using the moving velocity of the vehicle estimated by the moving velocity estimation unit, wherein the output unit in the surveillance apparatus outputs information of the type selected by the selection unit.

(226) 34. The surveillance system according to any one of 31. to 33., wherein the surveillance apparatus further including: an acquisition unit that acquires the image in which the area around the

road is captured, the image being generated by a camera; an object determination unit that recognizes and determines a person and a vehicle by performing image processing on the image acquired by the acquisition unit; a position determination unit that, by performing the image processing, determines positions of the person and the vehicle determined by the object determination unit; a headcount determination unit that determines the number of the persons determined by the object determination unit and determines whether the determined person takes an independent action; and a selection unit that selects a type of the information to be output based on a determination result made by the headcount determination unit, wherein the output unit in the surveillance apparatus outputs information of the type selected by the selection unit.

(227) 35. The surveillance system according to 33. or 34. citing 33., wherein, when determining that the vehicle detected to be in the state is in a stationary state from the moving velocity estimated by the moving velocity estimation unit, the detection unit in the surveillance apparatus further detects whether entry and exit of a person into and from the vehicle are performed, the selection unit in the surveillance apparatus selects a type of the information to be output, by further using a detection result of the entry and exit of the person by the detection unit, and the output unit in the surveillance apparatus outputs information of the type selected by the selection unit.

(228) 36. The surveillance system according to any one of 31. to 35., wherein the detection unit in the surveillance apparatus performs the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(229) 37. A surveillance method including, by a surveillance apparatus: processing an image in which an area around a road is captured and detecting that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and outputting a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.

(230) 38. The surveillance method according to 37., further including, by the surveillance apparatus: acquiring the image in which the area around the road is captured, the image being generated by a camera; recognizing and determining a person and a vehicle by performing image processing on the acquired image; determining positions of the determined person and the determined vehicle by performing the image processing; determining an attribute of the determined person by performing the image processing; when detecting a person and a vehicle in the state, selecting the type of information to be output, by using the determined attribute of the detected person; and outputting information of the selected type.

(231) 39. The surveillance method according to 37. or 38., further including, by the surveillance apparatus: acquiring the image in which the area around the road is captured, the image being generated by a camera; recognizing and determining a person and a vehicle by performing image processing on the acquired image; determining positions of the determined person and the determined vehicle by performing the image processing; estimating moving velocity of the determined vehicle from a change in a position of the vehicle; selecting the type of information to be output, by using the moving velocity of the estimated vehicle; and outputting information of the selected type.

(232) 40. The surveillance method according to any one of 37. to 39., further including, by the surveillance apparatus: acquiring the image in which the area around the road is captured, the image being generated by a camera; recognizing and determining a person and a vehicle by performing image processing on the acquired image; determining positions of the determined person and the determined vehicle by performing the image processing; determining the number of the determined persons and determining whether the determined person takes an independent action; selecting a type of the information to be output selected based on a result of the determination; and outputting information of the selected type.

(233) 41. The surveillance method according to 39. or 40. citing 39., further including, by the surveillance apparatus: when determining that the vehicle detected to be in the state is in a

stationary state from the estimated moving velocity, further detecting whether entry and exit of a person into and from the vehicle are performed; selecting a type of the information to be output, by further using a detection result of the entry and exit of the person; and outputting information of the selected type.

(234) 42. The surveillance method according to any one of 37. to 41., further including, by the surveillance apparatus: performing the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

(235) 43. A program for causing a computer to execute: a procedure for processing an image in which an area around a road is captured and detecting that a relative distance between a person and a vehicle included in the image is in a state of being equal to or less than a reference value; and a procedure for outputting a type of information to be output, the type of information being selected by using an attribute of the person detected to be in the state.

(236) 44. The program according to 43., further causing a computer to execute: a procedure for acquiring the image in which the area around the road is captured, the image being generated by a camera; a procedure for recognizing and determining a person and a vehicle by performing image processing on the image acquired in the procedure for acquisition; a procedure for, by performing the image processing, determining positions of the person and the vehicle determined in the procedure for determining a person and a vehicle; a procedure for, by performing the image processing, determining an attribute of the person determined in the procedure for determining positions; a procedure for, when a person and a vehicle in the state are detected in the procedure for detection, selecting the type of information to be output, by using the determined attribute of the detected person; and a procedure for outputting information of the type selected in the procedure for selection.

(237) 45. The program according to 43. or 44., further causing a computer to execute: a procedure for acquiring the image in which the area around the road is captured, the image being generated by a camera; a procedure for recognizing and determining a person and a vehicle by performing image processing on the image acquired in the procedure for acquisition; a procedure for, by performing the image processing, determining positions of the person and the vehicle determined in the procedure for determining a person and a vehicle; a procedure for estimating moving velocity of the vehicle determined in the procedure for determining positions, from a change in a position of the vehicle; a procedure for selecting the type of information to be output, by using the moving velocity of the vehicle estimated in the procedure for estimating moving velocity; and a procedure for outputting information of the type selected in the procedure for selection.

(238) 46. The program according to any one of 43. to 45., further causing a computer to execute: a procedure for acquiring the image in which the area around the road is captured, the image being generated by a camera; a procedure for recognizing and determining a person and a vehicle by performing image processing on the image acquired in the procedure for acquisition; a procedure for, by performing the image processing, determining positions of the person and the vehicle determined in the procedure for determining a person and a vehicle; a procedure for determining the number of the persons determined in the procedure for determining a person and a vehicle and determining whether the determined person takes an independent action; a procedure for selecting a type of the information to be output based on a result of the determination; and a procedure for outputting information of the type selected in the procedure for selection.

(239) 47. The program according to 45. or 46. citing 45., further causing a computer to execute a procedure for, when the vehicle detected to be in the state is determined to be in a stationary state from the moving velocity estimated in the procedure for estimating moving velocity, further detecting whether entry and exit of a person into and from the vehicle are performed, a procedure for selecting a type of the information to be output, by further using a detection result of the entry and exit of the person, and a procedure for outputting information of the selected type.

(240) 48. The program according to any one of 43. to 47., further causing a computer to execute a

procedure for performing the processing by using an image from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

REFERENCE SIGNS LIST

(241) **1** Surveillance system **3** Communication network **5** Surveillance camera **10** Vehicle **20** Person **30** Owner **100** Surveillance apparatus **102** Detection unit **104** Output unit **120** Acquisition unit **122** Object determination unit **124** Position determination unit **126** Attribute determination unit **128** Selection unit **130** Moving velocity estimation unit **132** Head count determination unit **200** Image processing apparatus **220** Server **300** Storage apparatus **1000** Computer **1010** Bus **1020** Processor **1030** Memory **1040** Storage device **1050** Input-output interface **1060** Network interface

Claims

1. A surveillance apparatus comprising: at least one memory storing instructions; and at least one processor configured to execute the instructions to: process a plurality of time-series images in which an area around a road is captured and detect positions of a feature part of each of person and vehicle in the plurality of time-series images, and by using the detected positions of the feature part of each of the person and the vehicle in the plurality of time-series images, determine that a relative distance between the person and the vehicle in the plurality of time-series images is equal to or less than a reference value; obtain an attribute of the person based on the relative distance between the person and the vehicle being equal to or less than the reference value; determine, using feature values stored in a storage, whether the attribute of the person is a first attribute or a second attribute, the first attribute related to information indicating whether the person is likely to be a victim of a crime, and a second attribute related to information indicating whether the person is likely to be a perpetrator of a criminal act; select one of a first type of warning information indicating a possibility of occurrence of kidnapping based on the attribute of the person being the first attribute, or a second type of warning information indicating a possibility of occurrence of vehicle theft based on the attribute of the person being the second attribute; and output the first type of warning information or the second type of warning information based on the selection.
2. The surveillance apparatus according to claim 1, wherein the at least one processor configured to execute the instructions to: acquire the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; recognize and determine the person and the vehicle by performing image processing on the plurality of time-series images.
3. The surveillance apparatus according to claim 1, wherein the at least one processor configured to execute the instructions to: acquire the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; recognize and determine the person and the vehicle by performing image processing on the plurality of time-series images; estimate moving velocity of the determined vehicle, from a change in a position of the vehicle; and select the first type of warning information or the second type of warning information, by using the estimated moving velocity of the determined vehicle.
4. The surveillance apparatus according to claim 1, wherein the at least one processor configured to execute the instructions to: acquire the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; recognize and determine the person and the vehicle by performing image processing on the plurality of time-series images, the determining the person comprising determining one or more persons; determine at least one of a number of the determined one or more persons or whether the determined one or more persons take an independent action; select the first type of warning information or the second type of warning information based on at least one of the number of the determined one or more persons or whether the determined one or more persons take the independent action.
5. The surveillance apparatus according to claim 3, wherein the at least one processor configured to

execute the instructions to: based on determining that the vehicle is in a stationary state using the estimated moving velocity, detecting whether entry and exit of a person into and from the vehicle occurs within a predetermined time from the determining that the vehicle is in the stationary state; select the first type of warning information based on no detection of the entry of the person into and from the vehicle and based on the attribute of the person being the first attribute; and select the second type of warning information based on detecting the entry of the person into and from the vehicle and based on the attribute of the person being the second attribute.

6. The surveillance apparatus according to claim 1, wherein the at least one processor configured to execute the instructions to perform the processing by using the plurality of time-series images from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

7. A surveillance method by a surveillance apparatus, the surveillance method comprising: processing a plurality of time-series images in which an area around a road is captured and detecting positions of a feature part of each of person and vehicle in the plurality of time-series images, and by using the detected positions of the feature part of each of the person and the vehicle in the plurality of time-series images, determining that a relative distance between the person and the vehicle in the plurality of time-series images is equal to or less than a reference value; obtaining an attribute of the person based on the relative distance between the person and the vehicle being equal to or less than the reference value; determining, using feature values stored in a storage, the attribute of the person selected from a set comprising a first attribute and a second attribute, the first attribute related to information indicating whether the person is likely to be a victim of a crime, and a second attribute related to information indicating whether the person is likely to be a perpetrator of a criminal act; selecting and outputting a type of warning information from a set comprising a first type of warning information corresponding to the first attribute and a second type of warning information corresponding to the second attribute, the first type of warning information indicating a possibility of occurrence of kidnapping and the second type of warning information indicating a possibility of occurrence of vehicle theft.

8. The surveillance method according to claim 7, further comprising: acquiring the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; recognizing and determining the person and the vehicle by performing image processing on the plurality of time-series images.

9. The surveillance method according to claim 7, further comprising, by the surveillance apparatus: acquiring the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; recognizing and determining the person and the vehicle by performing image processing on the plurality of time-series images; estimating moving velocity of the determined vehicle from a change in a position of the vehicle; and selecting the first type of warning information or the second type of warning information, by using the estimate moving velocity of the determined vehicle.

10. The surveillance method according to claim 7, further comprising, by the surveillance apparatus: acquiring the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; recognizing and determining the person and the vehicle by performing image processing on the plurality of time-series images, the determining the person comprising determining one or more persons; determining at least one of a number of the determined one or more persons or whether the determined one or more persons take an independent action; selecting the first type of warning information or the second type of warning information based on at least one of the number of the determined one or more persons or whether the determined one or more persons take the independent action.

11. The surveillance method according to claim 9, further comprising, by the surveillance apparatus: based on determining that the vehicle is in a stationary state using the estimated moving velocity, detecting whether entry and exit of a person into and from the vehicle occurs within a

predetermined time from the determining that the vehicle is in the stationary state; selecting the first type of warning information based on no detection of the entry of the person into and from the vehicle and based on the attribute of the person being the first attribute; and selecting the second type of warning information based on detecting the entry of the person into and from the vehicle and based on the attribute of the person being the second attribute.

12. The surveillance method according to claim 7, further comprising: performing the processing by using the plurality of time-series images from a specific camera out of a plurality of cameras each capturing an image of the area around the road.

13. A non-transitory computer-readable storage medium storing a program for causing a computer to execute: a procedure for processing a plurality of time-series images in which an area around a road is captured and detecting positions of a feature part of each of person and vehicle in the plurality of time-series images, and by using the detected positions of the feature part of each of the person and the vehicle in the plurality of time-series images, determining that a relative distance between the person and the vehicle in the plurality of time-series images is equal to or less than a reference value; a procedure for obtaining an attribute of the person based on the relative distance between the person and the vehicle being equal to or less than the reference value; a procedure for determining, using feature values stored in a storage, whether the attribute of the person is a first attribute or a second attribute, the first attribute related to information indicating whether the person is likely to be a victim of a crime, and a second attribute related to information indicating whether the person is likely to be a perpetrator of a criminal act; a procedure for selecting one of a first type of warning information indicating a possibility of occurrence of kidnapping based on the attribute of the person being the first attribute, or a second type of warning information indicating a possibility of occurrence of vehicle theft based on the attribute of the person being the second attribute; and a procedure for outputting the first type of warning information or the second type of warning information based on the selection.

14. The non-transitory computer-readable storage medium program according to claim 13, further the program causing the computer to execute: a procedure for acquiring the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; a procedure for recognizing and determining the person and the vehicle by performing image processing on the plurality of time-series images.

15. The non-transitory computer-readable storage medium according to claim 13, wherein the program further causing the computer to execute: a procedure for acquiring the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; a procedure for recognizing and determining the person and the vehicle by performing image processing on the plurality of time-series images; a procedure for estimating moving velocity of the determined vehicle from a change in a position of the vehicle; and a procedure for selecting the first type of warning information or the second type of warning information, by using the estimated moving velocity of determined the vehicle.

16. The non-transitory computer-readable storage medium according to claim 13, wherein the program further causing the computer to execute: a procedure for acquiring the plurality of time-series images in which the area around the road is captured, the plurality of time-series images being generated by a camera; a procedure for recognizing and determining the person and the vehicle by performing image processing on the plurality of time-series images, the determining the person comprising determining one or more persons; a procedure for determining at least one of a number of the determined one or more persons or whether the determined one or more persons take an independent action; a procedure for selecting the first type of warning information or the second type of warning information based on at least one of the number of the determined one or more persons or whether the determined one or more persons take the independent action.

17. The non-transitory computer-readable storage medium according to claim 15, wherein the program further causing the computer to execute a procedure for, based on the vehicle is

determined to be in a stationary state using the estimated moving velocity, detecting whether entry and exit of a person into and from the vehicle occurs within a predetermined time from the determining that the vehicle is in the stationary state, a procedure of selecting the first type of warning information based on no detection of the entry of the person into and from the vehicle and based on the attribute of the person being the first attribute; and a procedure of selecting the second type of warning information based on detecting the entry of the person into and from the vehicle and based on the attribute of the person being the second attribute.

18. The non-transitory computer-readable storage medium according to claim 13, wherein the program further causing the computer to execute a procedure for performing the processing by using the plurality of time-series images from a specific camera out of a plurality of cameras each capturing an image of the area around the road.
