

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418752
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kim; Daeho et al.

Sound apparatus

Abstract

A sound apparatus can include a vibration member; a housing at a rear surface of the vibration member; a connection member disposed between the vibration member and the housing; and a vibration apparatus configured to vibrate the vibration member. The vibration apparatus can include at least one piezoelectric element for producing sound. Also, the connection member can have a first stiffness that is less than a second stiffness of the housing, and the vibration member can be isolated from the housing by the connection member.

Inventors: Kim; Daeho (Paju-si, KR), Choi; YeongRak (Paju-si, KR), Choi; MinKyu (Paju-si, KR), Jeon; Seungo (Paju-si, KR), Kim; Kwangho (Paju-si, KR), Lee; Jeongbeom (Paju-si, KR), Kim; Taehyoung (Paju-si, KR), Park; KwanHo (Paju-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 1000008819444

Assignee: LG DISPLAY CO., LTD. (Seoul, KR)

Appl. No.: 18/090661

Filed: December 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230217189 A1	Jul. 06, 2023

Foreign Application Priority Data

KR	10-2021-0194781	Dec. 31, 2021
----	-----------------	---------------

Publication Classification

Int. Cl.: H04R17/00 (20060101); **H04R1/02** (20060101); **H10N30/20** (20230101)

U.S. Cl.:

CPC H04R17/00 (20130101); **H04R1/028** (20130101); **H10N30/204** (20230201);
H04R2499/15 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8259930	12/2011	Kawasaki	455/566	H04M 1/02
11218798	12/2021	Yang	N/A	G06F 1/1684
11571712	12/2022	Ishii	N/A	H10N 30/708
2015/0023530	12/2014	Takahashi	381/190	G10K 9/121
2016/0088399	12/2015	Watanabe	N/A	N/A
2016/0241689	12/2015	Watanabe	N/A	H10N 30/2047
2017/0105294	12/2016	Shimoda	N/A	G06F 3/016
2020/0280796	12/2019	Lee	N/A	H04R 9/025
2020/0314551	12/2019	Kim	N/A	H04R 7/045
2021/0168540	12/2020	Liao	N/A	H04R 9/06

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108337618	12/2017	CN	N/A
108881523	12/2017	CN	N/A
211720577	12/2019	CN	N/A
2005-236352	12/2004	JP	N/A
2007-27923	12/2006	JP	N/A
2013-229908	12/2012	JP	N/A
2014-82572	12/2013	JP	N/A
2015-115629	12/2014	JP	N/A
2015-149368	12/2014	JP	N/A
2021-141584	12/2020	JP	N/A
2021-180486	12/2020	JP	N/A
10-2012-0136582	12/2011	KR	N/A
WO 2012/157691	12/2011	WO	N/A
WO2015/064112	12/2014	WO	N/A

Primary Examiner: Huber; Paul W

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of and priority to Korean Patent Application No. 10-2021-0194781 filed on Dec. 31, 2021 in the Republic of Korea, the entirety of which is hereby incorporated by reference into the present application.

BACKGROUND

Technical Field

(2) The present disclosure relates to a sound apparatus.

Discussion of the Related Art

(3) An apparatus includes a separate speaker or a sound apparatus providing a sound. When a speaker is disposed in an apparatus, the speaker occupies a space, due to this, the design and spatial disposition of the apparatus are limited due to space constraints, particularly when the speaker is rather large.

(4) A speaker applied to the apparatus can be, for example, an actuator including a magnet and a coil. However, when an actuator is applied to the apparatus, a thickness thereof is thickened. Therefore, piezoelectric elements for realizing a thin thickness are attracting much attention.

(5) Because piezoelectric elements have a fragile characteristic, the piezoelectric elements are easily damaged due to an external impact, and due to this, have a problem where reliability is low in sound reproduction. And, when a speaker such as a piezoelectric element or the like is applied to a flexible apparatus, there is a problem where damage occurs due to a fragile characteristic. For example, if a piezoelectric element for providing sound is applied to a mobile device, the piezoelectric element may be damaged if the mobile device is dropped, which can severely impair sound quality. Also, if a piezoelectric element for providing sound is applied to a vehicle, the piezoelectric element may be damaged vehicle is involved in a minor accident or even when going over rough terrain, which can severely impair sound quality. Also, when the actuator is applied to an apparatus, there may be sound quality issues, such as an impaired bass response, impaired reproduction of midrange frequencies, or harsh high frequency sounds that are too loud related to the lower frequency sounds.

SUMMARY OF THE DISCLOSURE

(6) The inventors of the present disclosure have recognized the problems described above and have performed various experiments for implementing a sound apparatus (or a vibration apparatus) which can enhance the quality of a sound and a sound pressure level characteristic. Through the various experiments, the inventors have invented a new sound apparatus (or vibration apparatus) and an apparatus including the same, which can enhance the quality of a sound.

(7) Accordingly, the present disclosure is directed to providing an apparatus and a vehicular apparatus including the same that substantially obviate one or more problems due to limitations and disadvantages of the related art.

(8) An aspect of the present disclosure is directed to providing an apparatus which can vibrate a vibration member to generate a vibration or a sound and can enhance a sound characteristic and/or a sound pressure level characteristic.

(9) Additional features and aspects of the disclosure will be set forth in the description that follows, and in part will become apparent from the description or can be learned by practice of the inventive concepts provided herein. Other features and aspects of the inventive concepts can be realized and attained by the structure particularly pointed out in the written description, or derivable therefrom, and claims hereof as well as the appended drawings.

(10) To achieve these and other aspects of the inventive concepts, as embodied and broadly described, a sound apparatus comprises a vibration member, a housing at a rear surface of the vibration member, a connection member between the vibration member and the housing, and a vibration apparatus vibrating the vibration member.

(11) In addition to the above-mentioned advantageous effects of the present disclosure, other

features and advantages of the present disclosure will be described below or can be clearly understood by those skilled in the art from such description or explanation.

(12) A sound apparatus according to an embodiment of the present disclosure can include an apparatus (or a sound apparatus) which vibrates a display panel or a vibration member and can generate a sound so that a sound of the apparatus travels toward a front surface of the display panel or the vibration member.

(13) Other systems, methods, features and advantages will be, or will become, apparent to one with skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description, be within the scope of the present disclosure, and be protected by the following claims. Nothing in this section should be taken as a limitation on those claims. Further aspects and advantages are discussed below in conjunction with embodiments of the disclosure.

(14) It is to be understood that both the foregoing general description and the following detailed description of the present disclosure are exemplary and explanatory, and are intended to provide further explanation of the disclosures as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are included to provide a further understanding of the disclosure and are incorporated in and constitute a part of this application, illustrate aspects and embodiments of the disclosure and together with the description serve to explain principles of the disclosure

(2) FIG. 1 is a perspective view illustrating a sound apparatus according to an embodiment of the present disclosure.

(3) FIG. 2 is a cross-sectional view taken along line A-A' illustrated in FIG. 1 according to an embodiment of the present disclosure.

(4) FIG. 3 is another cross-sectional view taken along line A-A' illustrated in FIG. 1 according to an embodiment of the present disclosure.

(5) FIG. 4 illustrates a vibration device according to an embodiment of the present disclosure.

(6) FIG. 5 is a cross-sectional view taken along line B-B' illustrated in FIG. 4 according to an embodiment of the present disclosure.

(7) FIG. 6 is a perspective view illustrating a piezoelectric vibration portion illustrated in FIG. 5 according to an embodiment of the present disclosure.

(8) FIGS. 7A to 7D are perspective views illustrating a piezoelectric vibration portion in the vibration device according to embodiments of the present disclosure.

(9) FIG. 8 illustrates a vibration device according to another embodiment of the present disclosure.

(10) FIG. 9 is a cross-sectional view taken along line C-C' illustrated in FIG. 8.

(11) FIG. 10 illustrates a vibration device according to another embodiment of the present disclosure.

(12) FIGS. 11 to 14 are cross-sectional views taken along line A-A' illustrated in FIG. 1 according to embodiments of the present disclosure.

(13) FIGS. 15 to 17 are cross-sectional views taken along line A-A' illustrated in FIG. 1 according to other embodiments of the present disclosure.

(14) FIGS. 18A and 18B are perspective views illustrating an inner housing according to embodiments of the present disclosure.

(15) FIGS. 19A, 19B, and 19C are plan views illustrating an inner housing according to embodiments of the present disclosure.

(16) FIG. 20 is a perspective view illustrating a sound apparatus according to another embodiment

of the present disclosure.

(17) FIG. 21 is a cross-sectional view taken along line D-D' illustrated in FIG. 20 according to an embodiment of the present disclosure.

(18) FIG. 22 illustrates an arrangement structure of a vibration apparatus on a rear surface of a vibration member according to an embodiment of the present disclosure.

(19) FIG. 23 illustrates a sound output characteristic of a sound apparatus where a vibration member protrusion portion is not provided in the sound apparatus of FIG. 2 according to an embodiment of the present disclosure.

(20) FIG. 24 illustrates a sound pressure level with respect to a frequency of a sound apparatus where a first groove portion is provided in the sound apparatus of FIG. 11 and is not provided in the sound apparatus of FIG. 12 according to embodiments of the present disclosure.

(21) FIGS. 25a to 25f illustrate a sound pressure level with respect to a frequency of the sound apparatus of FIG. 12 where a first groove portion is prepared through modification under various conditions according to embodiments of the present disclosure.

(22) FIGS. 26a to 26e illustrate a sound pressure level with respect to a frequency of the sound apparatus of FIG. 12 which is provided by changing a thickness of a vibration member corresponding to a first groove portion under various conditions according to embodiments of the present disclosure.

(23) FIG. 27 illustrates a sound pressure level with respect to a frequency of a sound apparatus to which a structure of the inner housing of FIGS. 18A, 18B, 19A, 19B, and 19C is applied, according to embodiments of the present disclosure.

(24) FIG. 28 illustrates a sound pressure level with respect to a frequency of a structure where a first groove portion is not provided in the sound apparatus of FIGS. 15 and 16 and the sound apparatus of FIG. 12, according to embodiments of the present disclosure.

(25) FIG. 29 illustrates a sound pressure level with respect to a frequency of the sound apparatus of FIG. 22 according to an embodiment of the present disclosure.

(26) Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference numerals should be understood to refer to the same elements, features, and structures. The relative size and depiction of these elements can be exaggerated for clarity, illustration, and convenience.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(27) Reference will now be made in detail to embodiments of the present disclosure, examples of which can be illustrated in the accompanying drawings. In the following description, when a detailed description of well-known functions or configurations related to this document is determined to unnecessarily cloud a gist of the inventive concept, the detailed description thereof will be omitted. The progression of processing steps and/or operations described is an example; however, the sequence of steps and/or operations is not limited to that set forth herein and can be changed as is known in the art, with the exception of steps and/or operations necessarily occurring in a particular order. Same reference numerals designate same elements throughout. Names of the respective elements used in the following explanations are selected only for convenience of writing the specification and can be thus different from those used in actual products.

(28) Advantages and features of the present disclosure, and implementation methods thereof will be clarified through following embodiments described with reference to the accompanying drawings. The present disclosure can, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present disclosure to those skilled in the art.

(29) A shape, a size, a ratio, an angle, and a number disclosed in the drawings for describing embodiments of the present disclosure are merely an example, and thus, the present disclosure is not limited to the illustrated details. Like reference numerals refer to like elements throughout. In

the following description, when the detailed description of the relevant known function or configuration is determined to unnecessarily obscure the important point of the present disclosure, the detailed description will be omitted. When “comprise,” “have,” and “include” described in the present specification are used, another part can be added unless “only” is used. The terms of a singular form can include plural forms unless referred to the contrary.

(30) In construing an element, the element is construed as including an error or tolerance range although there is no explicit description of such an error or tolerance range.

(31) In describing a position relationship, for example, when a position relation between two parts is described as, for example, “on,” “over,” “under,” and “next,” one or more other parts can be disposed between the two parts unless a more limiting term, such as “just” or “direct(ly)” is used. In the description of embodiments, when a structure is described as being positioned “on or above” or “under or below” another structure, this description should be construed as including a case in which the structures contact each other as well as a case in which a third structure is disposed therebetween.

(32) In describing a time relationship, for example, when the temporal order is described as, for example, “after,” “subsequent,” “next,” and “before,” or the like a case that is not continuous can be included unless a more limiting term, such as “just,” “immediate(ly),” or “direct(ly)” is used.

(33) It will be understood that, although the terms “first,” “second,” etc. can be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of the present disclosure.

(34) In describing elements of the present disclosure, the terms “first,” “second,” “A,” “B,” “(a),” “(b),” etc. can be used. These terms are intended to identify the corresponding elements from the other elements, and basis, order, or number of the corresponding elements should not be limited by these terms. The expression that an element or layer is “connected,” “coupled,” or “adhered” to another element or layer the element or layer can not only be directly connected or adhered to another element or layer, but also be indirectly connected or adhered to another element or layer with one or more intervening elements or layers “disposed,” or “interposed” between the elements or layers, unless otherwise specified.

(35) The term “at least one” should be understood as including any and all combinations of one or more of the associated listed items. For example, the meaning of “at least one of a first item, a second item, and a third item” denotes the combination of all items proposed from two or more of the first item, the second item, and the third item as well as the first item, the second item, or the third item.

(36) The expression of a first element, a second elements “and/or” a third element should be understood as one of the first, second and third elements or as any or all combinations of the first, second and third elements. By way of example, A, B and/or C can refer to only A; only B; only C; any or some combination of A, B, and C; or all of A, B, and C.

(37) Features of various embodiments of the present disclosure can be partially or overall coupled to or combined with each other, and can be variously inter-operated with each other and driven technically as those skilled in the art can sufficiently understand. The embodiments of the present disclosure can be carried out independently from each other, or can be carried out together in co-dependent relationship.

(38) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. Also, for convenience of description, a scale, size and thickness of each of elements illustrated in the accompanying drawings differs from a real scale, and thus, embodiments of the present disclosure are not limited to a scale illustrated in the drawings.

(39) FIG. 1 is a perspective view illustrating a sound apparatus **10** according to an embodiment of the present disclosure. FIG. 2 is a cross-sectional view taken along line A-A' illustrated in FIG. 1.

(40) With reference to FIGS. 1 to 3, the sound apparatus **10** according to an embodiment of the present disclosure can include a vibration member **110** and a vibration apparatus **130**.

(41) The vibration member **110** can output a sound according to a vibration of the vibration apparatus **130**. Accordingly, the vibration member **110** can be referred to as a vibration object, a vibration plate, a vibration panel, a sound plate, or a sound output member, or the like, but embodiments of the present disclosure are not limited thereto.

(42) The vibration member **110** can be configured to be transparent, translucent, or opaque. The vibration member **110** according to an embodiment of the present disclosure can include a metal material or a nonmetal material (or a composite nonmetal material) having a material characteristic suitable for outputting a sound based on a vibration. The metal material of the vibration member **110** according to an embodiment of the present disclosure can include any one or more materials of stainless steel, aluminum (Al), an Al alloy, magnesium (Mg), a Mg alloy, and a magnesium-lithium (Mg—Li) alloy, but embodiments of the present disclosure are not limited thereto. The nonmetal material (or the composite nonmetal material) of the vibration member **110** can include one or more of glass, plastic, fiber, leather, wood, cloth, rubber, carbon, mirror, and paper, but embodiments of the present disclosure are not limited thereto.

(43) The vibration member **110** according to an embodiment of the present disclosure can implement a signage panel such as an analog signage or the like, e.g., an advertising signboard, a poster, or a noticeboard, or the like. For example, in a situation where the vibration member **110** implements the signage panel, the analog signage can include signage content, such as a sentence, a picture, and a sign, or the like. The signage content can be disposed at the vibration member **110** to be visible. For example, the signage content can be directly attached on one or more of a first surface (or a front surface) of the vibration member **110** and a second surface (or a rear surface) different from (or opposite to) the first surface. For example, the signage content can be printed on a medium such as paper or the like, and the medium with the signage content printed thereon can be directly attached on one or more of the first surface and the second surface of the vibration member **110**. For example, when the signage content is attached on the second surface of the vibration member **110**, the vibration member **110** can be configured to be a transparent material.

(44) The vibration member **110** according to another embodiment of the present disclosure can include one or more of a display panel including a pixel configured to display an image, a light emitting diode lighting panel, an organic light emitting lighting panel, and an inorganic light emitting lighting panel.

(45) The vibration member **110** according to another embodiment of the present disclosure can include one or more of a display panel including a pixel configured to display an image, a screen panel on which an image is to be projected from a display apparatus, a lighting panel, a signage panel, a vehicular interior material, a vehicular glass window, a vehicular exterior material, a building ceiling material, a building interior material, a building glass window, an aircraft interior material, an aircraft glass window, metal, wood, rubber, plastic, glass, fiber, cloth, paper, leather, carbon, and a mirror.

(46) The vibration member **110** according to an embodiment of the present disclosure can include a plate structure having a tetragonal shape. The vibration member **110** can have a horizontal length (or a widthwise length) parallel to a first direction X and a vertical length (or a lengthwise length) parallel to a second direction Y intersecting with the first direction X. For example, the vibration member **110** can have a rectangular shape where a horizontal length is relatively longer than a vertical length. However, the present disclosure is not limited thereto, and the vibration member **110** can have a square shape where a horizontal length is the same as a vertical length, a triangular shape, a circular shape or an oval shape, etc. For example, due to the compact size of the vibration member **110**, the vibration member **110** can fit in places where a coil speaker cannot fit.

(47) The vibration member **110** according to an embodiment of the present disclosure can include a protrusion portion (or a vibration member protrusion portion) **111** which is formed to surround an

edge of the vibration member **110** at a second surface of the vibration member **110**. In FIG. 2, the protrusion portion **111** can denote an element which protrudes from the rear surface of the vibration member **110**. For example, the protrusion portion **111** and the vibration member **110** can be provided as one body, but embodiments of the present disclosure are not limited thereto. For example, the protrusion portion **111** can be referred to as a protrusion portion **111**.

(48) The protrusion portion **111** can include the same material as that of the vibration member **110** and can be formed to protrude from the second surface of the vibration member **110**.

(49) The vibration member **110** according to an embodiment of the present disclosure can be configured to have a plurality of natural vibration frequencies (or a natural frequency). The vibration member **110** can include a non-planar structure, and thus, can have a plurality of natural vibration frequencies. The vibration member **110** can have a plurality of natural vibration frequencies which differ for each region (or area) of the vibration member **110**. For example, the vibration member **110** can have a plurality of natural vibration frequencies which differ based on a thickness of each region (or area).

(50) The vibration apparatus **130** can be configured to autonomously vibrate (or displace or drive) based on an electrical signal (or a voice signal) applied thereto, or can be configured to vibrate (or displace or drive) a vibration member (or a vibration plate or a vibration object) **110**. For example, the vibration apparatus **130** can be referred to as a vibration structure, a vibrator, a vibration generating apparatus, a vibration generating device, a vibration generator, a sounder, a sound device, a sound generating device, or a sound generator, or the like, but embodiments of the present disclosure are not limited thereto.

(51) The vibration apparatus **130** according to an embodiment of the present disclosure can include a piezoelectric material (or an electroactive material) having a piezoelectric characteristic. The vibration apparatus **130** can vibrate (or displace or drive) the vibration member **110** based on a vibration (or a displacement or driving) of a piezoelectric material generated by an electrical signal (or a voice signal) applied thereto. For example, the vibration apparatus **130** can vibrate (or displace or drive) as contraction and expansion are alternately repeated by a piezoelectric effect (or a piezoelectric characteristic). For example, the vibration apparatus **130** can vibrate (or displace or drive) in a vertical direction (or a thickness direction) Z as contraction and expansion are alternately repeated by an inverse piezoelectric effect.

(52) The vibration apparatus **130** according to an embodiment of the present disclosure can include one or more vibration devices **131** having a piezoelectric type.

(53) The one or more vibration devices **131** according to an embodiment of the present disclosure can be configured to have flexibility. For example, the one or more vibration devices **131** can be configured to be bent in a non-planar shape including a curved surface. For example, the one or more vibration devices **131** according to an embodiment of the present disclosure can be referred to as a flexible vibration structure, a flexible vibrator, a flexible vibration generating device, a flexible vibration generator, a flexible sounder, a flexible sound device, a flexible sound generating device, a flexible sound generator, a flexible actuator, a flexible exciter, or a flexible transducer, or the like, but embodiments of the present disclosure are not limited thereto.

(54) The one or more vibration devices **131** according to an embodiment of the present disclosure can include a tetragonal shape which has a first length parallel to a first direction X and a second length parallel to a second direction Y intersecting with the first direction X. For example, the one or more vibration devices **131** can include a square shape where the first length is the same as the second length. However, embodiments of the present disclosure are not limited thereto, and the one or more vibration devices **131** can include a rectangular shape where one of the first length and the second length is greater than the other length, a non-tetragonal shape, a triangular shape, a circular shape, or an oval shape.

(55) The vibration apparatus **130** according to an embodiment of the present disclosure can be connected or coupled to a second surface of the vibration member **110** by an adhesive member **120**.

(56) The adhesive member **120** can be disposed between the vibration member **110** and the vibration apparatus **130**. For example, the adhesive member **120** can be disposed between the vibration member **110** and one or more vibration devices **131**. For example, the adhesive member **120** can connect or couple the one or more vibration devices **131** to the second surface of the vibration member **110**.

(57) The adhesive member **120** according to an embodiment of the present disclosure can include an adhesive layer (or a tacky layer or an adhesive film) which is good in adhesive force or attaching force. For example, the adhesive member **120** can include a double-sided adhesive tape, a double-sided foam pad, an adhesive film, or a tacky sheet. For example, when the adhesive member **120** includes a tacky sheet or adhesive film (or a tacky layer), the adhesive member **120** can include only an adhesive layer or a tacky layer without a base member such as a plastic material or the like.

(58) The adhesive layer (or a tacky layer) of the adhesive member **120** according to an embodiment of the present disclosure can include epoxy, acrylic, silicone, or urethane, but embodiments of the present disclosure are not limited thereto.

(59) The adhesive layer (or a tacky layer) of the adhesive member **120** according to another embodiment of the present disclosure can include a pressure sensitive adhesive (PSA), an optically clear adhesive (OCA), or an optically clear resin (OCR), but embodiments of the present disclosure are not limited thereto.

(60) The sound apparatus **10** according to an embodiment of the present disclosure can further include a housing **150** and a connection member **140**.

(61) The housing **150** can be disposed at a rear surface of the vibration member **110** to cover the second surface of the vibration member **110** and the one or more vibration devices **131**. The housing **150** can include an accommodation space **150s** for accommodating the vibration apparatus **130** and can have a box shape where one side is opened. In addition, an opening of one side of the accommodation space **150s** is covered by the vibration member **110**, and a predetermined air gap can be formed between the accommodation space **150s** and the vibration member **110**. For example, the accommodation space **150s** can act as a type of sound space or resonance chamber.

(62) The housing **150** according to an embodiment of the present disclosure can include one or more of a metal material and a nonmetal material (or a composite nonmetal material), but embodiments of the present disclosure are not limited thereto. For example, the housing **150** can include one or more materials of a metal material, plastic, and wood, but embodiments of the present disclosure are not limited thereto. For example, the housing **150** can be referred to as various terms, such as a case, an outer case, a case member, a housing member, a cabinet, an enclosure, a sealing member, a sealing cap, a sealing box, or a sound box, or the like, but embodiments of the present disclosure are not limited thereto. For example, the accommodation space **150s** of the housing **150** can be referred to as various terms, such as a gap space, an air gap, a vibration space, a sound space, a sound box, a resonance chamber, or a sealing space, but embodiments of the present disclosure are not limited thereto.

(63) The housing **150** according to an embodiment of the present disclosure can maintain an impedance component based on air, which acts on the vibration member **110** when the vibration member **110** vibrates. For example, air near the vibration member **110** can resist a vibration of the vibration member **110** and can act as an impedance component having a reactance component and a different resistance based on a frequency. Therefore, the housing **150** can configure the closed space, which surrounds the vibration apparatus **130**, and thus, can maintain an impedance component (or an air impedance or an acoustic impedance) which acts on the vibration member **110** due to air, thereby enhancing a sound characteristic and/or a sound pressure level characteristic of a low-pitched sound band generated based on the vibration of the vibration member **110** and enhancing the quality of a sound of a high-pitched sound band generated based on the vibration of the vibration member **110**.

(64) The housing **150** according to an embodiment of the present disclosure can include a bottom

portion **151** and a lateral portion **152**.

(65) The bottom portion **151** can be disposed at the rear surface of the vibration member **110** to cover the second surface of the vibration member **110** and the vibration apparatus **130**. For example, the bottom portion **151** can be disposed to be spaced apart from the second surface of the vibration member **110** and the vibration apparatus **130**. For example, the bottom portion **151** can be referred to as various terms, such as a floor portion, a housing plate, a housing floor portion, or a housing bottom portion, or the like, but embodiments of the present disclosure are not limited thereto.

(66) The lateral portion **152** can be connected to a periphery portion of the bottom portion **151**. For example, the lateral portion **152** can be bent from the periphery portion of the bottom portion **151** along a third direction Z parallel to a thickness direction of the vibration member **110**. For example, the lateral portion **152** can include first to fourth lateral portions. For example, the lateral portion **152** can be referred to as a housing lateral surface or a housing sidewall, or the like, but embodiments of the present disclosure are not limited thereto.

(67) The lateral portion **152** can be integrated into the bottom portion **151**. For example, the bottom portion **151** and the lateral portion **152** can be integrated as one body, and thus, the accommodation space **150s** surrounded by the lateral portion **152** can be provided on the bottom portion **151**. Accordingly, the bottom portion **151** and the lateral portion **152** can have a box shape where one side is opened or a tray shape.

(68) The lateral portion **152** can be connected or coupled to the second surface of the vibration member **110** by the connection member **140**. For example, the lateral portion **152** can be connected or coupled to a periphery portion of the second surface of the vibration member **110** by the connection member **140**.

(69) According to an embodiment of the present disclosure, when the housing **150** includes the lateral portion **152**, the connection member **140** can be disposed between the lateral portion **152** of the housing **150** and the protrusion portion **111** of the vibration member **110**. For example, the connection member **140** can connect or couple one end of the lateral portion **152** of the housing **150** and one end of the protrusion portion **111**.

(70) According to an embodiment of the present disclosure, the connection member **140** which is disposed between the housing **150** and the vibration member **110** can be configured to minimize or prevent the transfer of a vibration of the vibration member **110** to the housing **150** (e.g., made of a shock absorbing material). The connection member **140** can include a material characteristic suitable for blocking a vibration. For example, the connection member **140** can include a material having elasticity. For example, the connection member **140** can include a material having elasticity for vibration absorption (or impact absorption). The connection member **140** according to an embodiment of the present disclosure can be configured as polyurethane materials or polyolefin materials, but embodiments of the present disclosure are not limited thereto. For example, the connection member **140** according to an embodiment of the present disclosure can include one or more of a double-sided polyurethane tape, a double-sided polyurethane foam tape, or a double-sided sponge tape.

(71) The connection member **140** according to an embodiment of the present disclosure can have a thickness for minimizing or preventing the transfer of a vibration of the vibration member **110** to the housing **150**. The connection member **140** can absorb a vibration of the vibration member **110** based on a thickness and elasticity, thereby minimizing or preventing the transfer of a vibration of the vibration member **110** to the housing **150**. In addition, the connection member **140** can prevent a physical contact (or friction) between the vibration member **110** and the housing **150**, and thus, can prevent the occurrence of noise (or a noise sound) caused by the physical contact (or friction) between the vibration member **110** and the housing **150**. For example, the connection member **140** can be referred to as a buffer member, an elastic member, a damping member, a vibration absorption member, or a vibration blocking member, or the like, but embodiments of the present

disclosure are not limited thereto.

(72) The one or more vibration devices **131** according to an embodiment of the present disclosure can vibrate based on a vibration driving signal (or a sound signal or a voice signal) provided from a sound processing circuit to vibrate the vibration member **110**, thereby generating or outputting a sound. In a sound generated based on a vibration of the vibration member **110**, a sound pressure level characteristic can increase based on a vibration, having various natural vibration frequencies, of the vibration member **110**, and a reproduction-pitched sound band can be extended.

(73) Because the vibration member **110** of the sound apparatus **10** according to an embodiment of the present disclosure further includes the protrusion portion **111**, a sound output characteristic of the sound apparatus **10** can be improved, and in detail, a dip phenomenon can be reduced and a sound characteristic can be enhanced. Dip can be a phenomenon where the occurrence of a specific frequency is prevented or attenuated and a low sound pressure level is generated. A sound output characteristic of the sound apparatus **10** can be reduced by the dip phenomenon.

(74) FIG. **3** is another cross-sectional view taken along line A-A' illustrated in FIG. **1**. FIG. **3** illustrates a sound apparatus according to another embodiment of the present disclosure and illustrates an embodiment implemented by modifying a structure of the housing of FIG. **2**.

Therefore, in the following description, their repetitive descriptions of the other elements except the vibration member and the housing and relevant elements may be omitted.

(75) With reference to FIG. **3**, a housing **150** can further include a second groove portion **153** which is formed inward from a lateral portion **152**, and the second groove portion **153** of the housing **150** can accommodate and fix a protrusion portion **111** of a vibration member **110**. In addition, according to an embodiment of the present disclosure, a connection member **140** can include a first connection member **141** between a first surface of the vibration member **110** and the groove portion **153** of the housing **150**, and a second connection member **143** between the protrusion portion **111** and the second groove portion **153** of the housing **150**. According to an embodiment of the present disclosure, the first and second connection members **141** and **143** can include the same material as that of the connection member **140**. For example, a second groove portion **153** can be a groove portion or a first groove portion, but embodiments of the present disclosure are not limited thereto. For example, the vibration member **110** can float or be isolated within second groove portion **153** by attaching first and second connection members **141** and **143** above and below the protrusion portion **111**, which can securely fix the vibration member **110** while also reducing vibrations and absorbing shocks or impacts (e.g., the protrusion portion **111** of vibration member **110** can be cushioned within the second groove portion **153** by the first and second connection members **141** and **143**).

(76) According to an embodiment of the present disclosure, the vibration member **110** can be fixed by the second groove portion **153** or can be inserted into the second groove portion **153**. For example, because both ends of the vibration member **110** are fixed by the second groove portion **153**, a reflected wave can be offset at the both ends of the vibration member **110**, and thus, the peak or dip phenomenon of a sound characteristic caused by a standing wave can be reduced and a sound characteristic of a low-pitched sound band can be enhanced. The peak can be a phenomenon where a sound pressure level bounces in a specific frequency, and the dip can be phenomenon where a low pressure level occurs because the occurrence of a specific frequency is prevented. A sound output characteristic of the sound apparatus can be reduced by the peak or dip phenomenon. In detail, in the sound apparatus according to another embodiment of the present disclosure, a sound characteristic of the low-pitched sound band can be enhanced, and a dip phenomenon of a middle-pitched sound band and a dip phenomenon of a high-pitched sound band can be reduced. For example, the low pitched sound can be a frequency range of 500 Hz or less, the middle-pitched sound band can be a frequency range of 500 Hz to 2,000 Hz, and the high-pitched sound band can be a frequency range of 2,000 Hz to 20,000 Hz. However, the frequency ranges of the middle-pitched sound band and a middle-high-pitched sound band according an embodiment of the present

disclosure are not limited thereto.

(77) FIG. 4 illustrates a vibration device according to an embodiment of the present disclosure, FIG. 5 is a cross-sectional view taken along line B-B' illustrated in FIG. 4, and FIG. 6 is a perspective view illustrating a piezoelectric vibration portion illustrated in FIG. 5. FIGS. 4 to 6 illustrate another embodiment of the vibration device illustrated in one or more of FIGS. 1 to 3.

(78) With reference to FIGS. 4 to 6, a vibration device **131** according to an embodiment of the present disclosure can be referred to as a flexible vibration structure, a flexible vibrator, a flexible vibration generating device, a flexible vibration generator, a flexible sounder, a flexible sound device, a flexible sound generating device, a flexible sound generator, a flexible actuator, a flexible speaker, a flexible piezoelectric speaker, a film actuator, a film-type piezoelectric composite actuator, a film speaker, a film-type piezoelectric speaker, or a film-type piezoelectric composite speaker, or the like, but embodiments of the present disclosure are not limited thereto.

(79) The vibration device **131** according to an embodiment of the present disclosure can include a vibration generating portion which has a piezoelectric vibration portion **131a**, a first electrode portion **131b**, and a second electrode portion **131c**.

(80) The piezoelectric vibration portion **131a** can include a piezoelectric material (or an electroactive material) which includes a piezoelectric effect. For example, the piezoelectric material can have a characteristic in which, when pressure or twisting (or bending) is applied to a crystalline structure by an external force, a potential difference occurs due to dielectric polarization caused by a relative position change of a positive (+) ion and a negative (−) ion, and a vibration is generated by an electric field based on a reverse voltage applied thereto. The piezoelectric vibration portion **131a** can be referred to as a vibration layer, a piezoelectric layer, a piezoelectric material layer, an electroactive layer, a vibration portion, a piezoelectric material portion, an electroactive portion, a piezoelectric structure, a piezoelectric composite layer, a piezoelectric composite, or a piezoelectric ceramic composite, or the like, but embodiments of the present disclosure are not limited thereto. The piezoelectric vibration portion **131a** can be formed of a transparent, semitransparent, or opaque piezoelectric material (or an electroactive material) and can be transparent, semitransparent, or opaque.

(81) The piezoelectric vibration portion **131a** according to an embodiment of the present disclosure can include a plurality of first portions **131a1** and a plurality of second portions **131a2**. For example, the plurality of first portions **131a1** and the plurality of second portions **131a2** can be alternately and repeatedly arranged along a first direction X (or a second direction Y). For example, the first direction X can be a widthwise direction of the piezoelectric vibration portion **131a**, the second direction Y can be a lengthwise direction of the piezoelectric vibration portion **131a**, but embodiments of the present disclosure are not limited thereto. For example, the first direction X can be the lengthwise direction of the piezoelectric vibration portion **131a**, and the second direction Y can be the widthwise direction of the piezoelectric vibration portion **131a**.

(82) Each of the plurality of first portions **131a1** can be configured as an inorganic material portion. The inorganic material portion can include a piezoelectric material, a composite piezoelectric material, or an electroactive material which includes a piezoelectric effect.

(83) Each of the plurality of first portions **131a1** can be configured as a ceramic-based material for generating a relatively high vibration, or can be configured as a piezoelectric ceramic having a perovskite-based crystalline structure. The perovskite crystalline structure can have a piezoelectric effect and an inverse piezoelectric effect, and can be a plate-shaped structure having orientation. The perovskite crystalline structure can be represented by a chemical formula “ABO.sub.3”. In the chemical formula, “A” can include a divalent metal element, and “B” can include a tetravalent metal element. For example, in the chemical formula “ABO.sub.3”, “A”, and “B” can be cations, and “O” can be anions. For example, each of the plurality of first portions **131a1** can include at least one or more among lead (II) titanate (PbTiO.sub.3), lead zirconate (PbZrO.sub.3), lead zirconate titanate (PbZrTiO.sub.3), barium titanate (BaTiO.sub.3), and strontium titanate (SrTiO.sub.3), but

embodiments of the present disclosure are not limited thereto.

(84) The first portions **131a1** of the piezoelectric vibration portion **131a** according to an embodiment of the present disclosure can include a lead zirconate titanate (PZT)-based material, including lead (Pb), zirconium (Zr), and titanium (Ti); or can include a lead zirconate nickel niobate (PZNN)-based material, including lead (Pb), zirconium (Zr), nickel (Ni), and niobium (Nb), but embodiments of the present disclosure are not limited thereto. In addition, the first portions **131a1** of the piezoelectric vibration portion **131a** can include at least one or more of calcium titanate (CaTiO₃), BaTiO₃, and SrTiO₃, each without lead (Pb), but embodiments of the present disclosure are not limited thereto.

(85) Each of the plurality of first portions **131a1** according to an embodiment of the present disclosure can be disposed between the plurality of second portions **131a2** and can have a first width W1 parallel to the first direction X (or the second direction Y) and a length parallel to the second direction Y (or the first direction X). Each of the plurality of second portions **131a2** can have a second width W2 parallel to the first direction X (or the second direction Y) and can have a length parallel to the second direction Y (or the first direction X). The first width W1 can be the same as or different from the second width W2. For example, the first width W1 can be greater than the second width W2. For example, the first portion **131a1** and the second portion **131a2** can include a line shape or a stripe shape which has the same size or different sizes. Therefore, the piezoelectric vibration portion **131a** can include a 2-2 composite structure having a piezoelectric characteristic of a 2-2 vibration mode, and thus, can have a resonance frequency of 20 kHz or less, but embodiments of the present disclosure are not limited thereto. For example, a resonance frequency of the piezoelectric vibration portion **131a** can vary based on at least one or more of a shape, a length, and a thickness, or the like.

(86) In the piezoelectric vibration portion **131a**, each of the plurality of first portions **131a1** and the plurality of second portions **131a2** can be disposed (or arranged) at the same plane (or the same layer) in parallel. Each of the plurality of second portions **131a2** can be configured to fill a gap between two adjacent first portions of the plurality of first portions **131a1** and can be connected or adhered to a second portion **131a2** adjacent thereto. Therefore, the piezoelectric vibration portion **131a** can extend by a desired size or length based on the side coupling (or connection) of the first portion **131a1** and the second portion **131a2**.

(87) In the piezoelectric vibration portion **131a**, a width (or a size) W2 of each of the plurality of second portions **131a2** can progressively decrease in a direction from a center portion to both peripheries (or both ends) of the piezoelectric vibration portion **131a** or the vibration device **131**. For example, the widths of the plurality of second portions **131a2** can be larger in the center area and smaller at the outer edges.

(88) According to an embodiment of the present disclosure, a second portion **131a2**, having a largest width W2 among the plurality of second portions **131a2**, can be located at a portion at which a highest stress can concentrate when the piezoelectric vibration portion **131a** or the vibration device **131** is vibrating in a vertical direction Z (or a thickness direction). A second portion **131a2**, having a smallest width W2 among the plurality of second portions **131a2**, can be located at a portion where a relatively low stress can occur when the piezoelectric vibration portion **131a** or the vibration device **131** is vibrating in the vertical direction Z. For example, the second portion **131a2**, having the largest width W2 among the plurality of second portions **131a2**, can be disposed at the center portion of the piezoelectric vibration portion **131a**, and the second portion **131a2**, having the smallest width W2 among the plurality of second portions **131a2** can be disposed at each of the both peripheries of the piezoelectric vibration portion **131a**. Therefore, when the piezoelectric vibration portion **131a** or the vibration device **131** is vibrating in the vertical direction Z, interference of a sound wave or overlapping of a resonance frequency, each occurring in the portion on which the highest stress concentrates, can be reduced or minimized. Thus, the dipping phenomenon or the attenuation of a sound pressure level occurring in the low-pitched

sound band can be reduced, thereby improving flatness of a sound characteristic in the low-pitched sound band.

(89) In the piezoelectric vibration portion **131a**, each of the plurality of first portions **131a1** can have different sizes (or widths). For example, a size (or a width) of each of the plurality of first portions **131a1** can progressively decrease or increase in a direction from the center portion to the both peripheries (or both ends) of the piezoelectric vibration portion **131a** or the vibration device **131**. Accordingly, in the piezoelectric vibration portion **131a**, a sound pressure level characteristic of a sound can be enhanced and a sound reproduction band can increase, based on various natural vibration frequencies according to a vibration of each of the plurality of first portions **131a1** having different sizes.

(90) The plurality of second portions **131a2** can be disposed between the plurality of first portions **131a1**. Therefore, in the piezoelectric vibration portion **131a** or the vibration device **131**, vibration energy by a link in a unit lattice of each first portion **131a1** can increase by a corresponding second portion **131a2**, and thus, a vibration characteristic can increase, and a piezoelectric characteristic and flexibility can be secured. For example, the second portion **131a2** can include one or more of an epoxy-based polymer, an acrylic-based polymer, and a silicone-based polymer, but embodiments of the present disclosure are not limited thereto.

(91) The plurality of second portions **131a2** according to an embodiment of the present disclosure can be configured as an organic material portion. For example, the organic material portion can be disposed between the inorganic material portions, and thus, can absorb an impact applied to the inorganic material portion (or the first portion), can release a stress concentrating on the inorganic material portion to enhance the total durability of the piezoelectric vibration portion **131a** or the vibration device **131**, and can provide flexibility to the piezoelectric vibration portion **131a** or the vibration device **131**.

(92) The plurality of second portions **131a2** according to an embodiment of the present disclosure can have a modulus (or Young's modulus) and viscoelasticity that are lower than those of each first portion **131a1**, and thus, the second portion **131a2** can enhance the reliability of each first portion **131a1** vulnerable to an impact due to a fragile characteristic. For example, the second portion **131a2** can be configured as a material having a loss coefficient of about 0.01 to about 1 (e.g., 0.5) and modulus of about 0.1 GPa (Giga pascal) to about 10 GPa (Giga pascal) (e.g., 5 GPa).

(93) The organic material portion configured at the second portion **131a2** can include one or more of an organic material, an organic polymer, an organic piezoelectric material, or an organic non-piezoelectric material that has a flexible characteristic in comparison with the inorganic material portion of the first portions **131a1**. For example, the second portion **131a2** can be referred to as an adhesive portion, an elastic portion, a bending portion, a damping portion, or a flexible portion each having flexibility, but embodiments of the present disclosure are not limited thereto.

(94) The plurality of first portions **131a1** and the second portion **131a2** can be disposed on (or connected to) the same plane, and thus, the piezoelectric vibration portion **131a** according to an embodiment of the present disclosure can have a single thin film-type. For example, the piezoelectric vibration portion **131a** can have a structure in which a plurality of first portions **131a1** are connected to one side. For example, the plurality of first portions **131a1** can have a structure connected to a whole the piezoelectric vibration portion **131a**. For example, the piezoelectric vibration portion **131a** can be vibrated in a vertical direction by the first portion **131a1** having a vibration characteristic and can be bent in a curved shape by the second portion **131a2** having flexibility. In addition, in the piezoelectric vibration portion **131a** according to an embodiment of the present disclosure, a size of the first portion **131a1** and a size of the second portion **131a2** can be adjusted based on a piezoelectric characteristic and flexibility needed for the piezoelectric vibration portion **131a** or the vibration device **131**. As an embodiment of the present disclosure, when the piezoelectric vibration portion **131a** needs a piezoelectric characteristic rather than flexibility, a size of the first portion **131a1** can be adjusted to be greater than that of the second

portion **131a2**. As another embodiment of the present disclosure, when the piezoelectric vibration portion **131a** needs flexibility rather than a piezoelectric characteristic, a size of the second portion **131a2** can be adjusted to be greater than a size of the first portion **131a1**. Accordingly, a size of the piezoelectric vibration portion **131a** can be adjusted based on a characteristic needed therefor, and thus, the piezoelectric vibration portion **131a** can be easy to design or modifiable.

(95) The first electrode portion **131b** can be disposed at a first surface (or an upper surface) of the piezoelectric vibration portion **131a**. The first electrode portion **131b** can be disposed at or coupled to a first surface of each of a plurality of first portions **131a1** and a first surface of each of a plurality of second portions **131a2** in common and can be electrically connected to the first surface of each of the plurality of first portions **131a1**. For example, the first electrode portion **131b** can be a single-body electrode (or a common electrode) shape which is disposed at a whole first surface of the piezoelectric vibration portion **131a**. For example, the first electrode portion **131b** can have substantially the same shape as that of the piezoelectric vibration portion **131a**, but embodiments of the present disclosure are not limited thereto.

(96) The first electrode portion **131b** according to an embodiment of the present disclosure can be formed of a transparent conductive material, a semitransparent conductive material, or an opaque conductive material. For example, the transparent conductive material or the semitransparent conductive material can include indium tin oxide (ITO) or indium zinc oxide (IZO), but embodiments of the present disclosure are not limited thereto. The opaque conductive material can include aluminum (Al), copper (Cu), gold (Au), silver (Ag), molybdenum (Mo), Mg, or the like, or an alloy thereof, but embodiments of the present disclosure are not limited thereto.

(97) The second electrode portion **131c** can be disposed at a second surface (or a rear surface) different from (or opposite to) the first surface of the piezoelectric vibration portion **131a**. The second electrode portion **131c** can be disposed at or coupled to a second surface of each of a plurality of first portions **131a1** and the second surface of each of a plurality of second portions **131a2** in common and can be electrically connected to a second surface of each of the plurality of first portions **131a1**. For example, the second electrode portion **131c** can be a single-body electrode (or a common electrode) shape which is disposed at a whole second surface of the piezoelectric vibration portion **131a**. The second electrode portion **131c** can have the same shape as the piezoelectric vibration portion **131a**, but embodiments of the present disclosure are not limited thereto. The second electrode portion **131c** according to an embodiment of the present disclosure can be formed of a transparent conductive material, a semitransparent conductive material, or an opaque conductive material. For example, the second electrode portion **131c** can be formed of the same material as the first electrode portion **131b**, but embodiments of the present disclosure are not limited thereto. As another embodiment of the present disclosure, the second electrode portion **131c** can be formed of a different material than the first electrode portion **131b**.

(98) The piezoelectric vibration portion **131a** can be polarized by a certain voltage applied to the first electrode portion **131b** and the second electrode portion **131c** in a certain temperature atmosphere, or a temperature atmosphere that can be changed from a high temperature to a room temperature, but embodiments of the present disclosure are not limited thereto. For example, the piezoelectric vibration portion **131a** can alternately and repeatedly contract and expand based on an inverse piezoelectric effect according to a sound signal (or a voice signal) applied to the first electrode portion **131b** and the second electrode portion **131c** from the outside to vibrate. For example, the piezoelectric vibration portion **131a** can vibrate based on a vertical-direction vibration and a planar direction vibration by the first electrode portion **131b** and the second electrode portion **131c**. The piezoelectric vibration portion **131a** can increase the displacement of a vibration member (or a vibration plate or a vibration object) by contraction and expansion of the planar direction, thereby further improving the vibration.

(99) The vibration device **131** according to an embodiment of the present disclosure can further include a first cover member **131d** and a second cover member **131e**.

(100) The first cover member **131d** can be disposed at the first surface of the vibration device **131**. For example, the first cover member **131d** can be configured to cover the first electrode portion **131b**. Accordingly, the first cover member **131d** can protect the first electrode portion **131b**.

(101) The second cover member **131e** can be disposed at the second surface of the vibration device **131**. For example, the second cover member **131e** can be configured to cover the second electrode portion **131c**. Accordingly, the second cover member **131e** can protect the second electrode portion **131c**.

(102) The first cover member **131d** and the second cover member **131e** according to an embodiment of the present disclosure can each include one or more material of a plastic, a fiber, and wood, but embodiments of the present disclosure are not limited thereto. For example, each of the first cover member **131d** and the second cover member **131e** can include the same or different material. For example, each of the first cover member **131d** and the second cover member **131e** can be a polyimide (PI) film or a polyethylene terephthalate (PET) film, but embodiments of the present disclosure are not limited thereto.

(103) The first cover member **131d** according to an embodiment of the present disclosure can be connected or coupled to the first electrode portion **131b** by a first adhesive layer **131f**. For example, the first cover member **131d** can be connected or coupled to the first electrode portion **131b** by a film laminating process using the first adhesive layer **131f**.

(104) The second cover member **131e** according to an embodiment of the present disclosure can be connected or coupled to the second electrode portion **131c** by a second adhesive layer **131g**. For example, the second cover member **131e** can be connected or coupled to the second electrode portion **131c** by a film laminating process using the second adhesive layer **131g**.

(105) The first adhesive layer **131f** can be disposed between the first electrode portion **131b** and the first cover member **131d**. The second adhesive layer **131g** can be disposed between the second electrode portion **131c** and the second cover member **131e**. For example, the first adhesive layer **131f** and second adhesive layer **131g** can be configured between the first cover member **131d** and the second cover member **131e** to completely surround the piezoelectric vibration portion **131a**, the first electrode portion **131b**, and the second electrode portion **131c**. For example, the piezoelectric vibration portion **131a**, the first electrode portion **131b**, and the second electrode portion **131c** can be embedded or built-in between the first adhesive layer **131f** and the second adhesive layer **131g**.

(106) Each of the first adhesive layer **131f** and second adhesive layer **131g** according to an embodiment of the present disclosure can include an electric insulating material which has adhesiveness and is capable of compression and decompression. For example, each of the first adhesive layer **131f** and the second adhesive layer **131g** can include an epoxy resin, an acrylic resin, a silicone resin, or a urethane resin, but embodiments of the present disclosure are not limited thereto.

(107) According to an embodiment of the present disclosure, any one of the first cover member **131d** and the second cover member **131e** can be attached to or coupled to the vibration member (or the vibration plate or the vibration object) by an adhesive member. For example, any one of the first cover member **131d** and the second cover member **131e** can be attached on or coupled to the vibration member **110** by the adhesive member **120** as described above with reference to FIGS. 1 to 3.

(108) The vibration device **131** according to an embodiment of the present disclosure can further include a first power supply line PL1 disposed at the first cover member **131d**, a second power supply line PL2 disposed at the second cover member **131e**, and a pad part **131p** electrically connected to the first power supply line PL1 and the second power supply line PL2.

(109) The first power supply line PL1 can be disposed between the first electrode portion **131b** and the first cover member **131d** and can be electrically connected to the first electrode portion **131b**. The first power supply line PL1 can be extended long along the second direction Y and can be electrically connected to a central portion of the first electrode portion **131b**. As an embodiment of

the present disclosure, the first power supply line PL1 can be electrically connected to the first electrode portion **131b** by an anisotropic conductive film. As another embodiment of the present disclosure, the first power supply line PL1 can be electrically connected to the first electrode portion **131b** through a conductive material (or conductive particles) included in the first adhesive layer **131f**.

(110) The second power supply line PL2 can be disposed between the second electrode portion **131c** and the second cover member **131e** and can be electrically connected to the second electrode portion **131c**. The second power supply line PL2 can be extended long along the second direction Y and can be electrically connected to a central portion of the second electrode portion **131c**. As an embodiment of the present disclosure, the second power supply line PL2 can be electrically connected to the second electrode portion **131c** by an anisotropic conductive film. As another embodiment of the present disclosure, the second power supply line PL2 can be electrically connected to the second electrode portion **131c** through a conductive material (or particle) included in the second adhesive layer **131g**.

(111) The pad part **131p** can be configured at one periphery portion of any one of the first cover member **131d** and the second cover member **131e** to be electrically connected to one portion (or one end) of each of the first power supply line PL1 and the second power supply line PL2.

(112) The pad part **131p** according to an embodiment of the present disclosure can include a first pad electrode electrically connected to one end of the first power supply line PL1, and a second pad electrode electrically connected to one end of the second power supply line PL2.

(113) The first pad electrode can be disposed at one periphery portion of any one of the first cover member **131d** and the second cover member **131e** to be electrically connected to one portion of the first power supply line PL1. For example, the first pad electrode can pass through any one of the first cover member **131d** and the second cover member **131e** to be electrically connected to one portion of the first power supply line PL1.

(114) The second pad electrode can be disposed in parallel with the first pad electrode to be electrically connected to one portion of the second power supply line PL2. For example, the second pad electrode can pass through any one of the first cover member **131d** and the second cover member **131e** to be electrically connected to one portion of the second power supply line PL2.

(115) According to an embodiment of the present disclosure, each of the first power supply line PL1, the second power supply line PL2, and the pad part **131p** can be configured to be transparent, translucent, or opaque.

(116) The pad part **131p** according to another embodiment of the present disclosure can be electrically connected to a signal cable **132**.

(117) The signal cable **132** can be electrically connected to the pad part **131p** disposed at the vibration device **131** and can supply the vibration device **131** with vibration driving signals (or a sound signal or a voice signal) provided from a sound processing circuit. The signal cable **132** according to an embodiment of the present disclosure can include a first terminal electrically connected to the first pad electrode of the pad part **131p** and a second terminal electrically connected to the second pad electrode of the pad part **131p**. For example, the signal cable **132** can be configured as a flexible printed circuit cable, a flexible flat cable, a single-sided flexible printed circuit, a single-sided flexible printed circuit board, a flexible multilayer printed circuit, or a flexible multilayer printed circuit board, but embodiments of the present disclosure are not limited thereto.

(118) The sound processing circuit can generate an alternating current (AC) vibration driving signal including a first vibration driving signal and a second vibration driving signal based on a sound data provided from an external sound data generating circuit part. The first vibration driving signal can be any one of a positive (+) vibration driving signal and a negative (−) vibration driving signal, and the second vibration driving signal can be any one of a positive (+) vibration driving signal and a negative (−) vibration driving signal. For example, the first vibration driving signal can be

supplied to the first electrode portion **131b** through a first terminal of the signal cable **132**, the first pad electrode of the pad part **131p**, and the first power supply line **PL1**. The second vibration driving signal can be supplied to the second electrode portion **131c** through a second terminal of the signal cable **132**, the second pad electrode of the pad part **131p**, and the second power supply line **PL2**.

(119) According to an embodiment of the present disclosure, the signal cable **132** can be configured to be transparent, semitransparent, or opaque.

(120) As described above, the vibration device **131** according to an embodiment of the present disclosure can be implemented as a thin film type where the first portion **131a1** having a piezoelectric characteristic and a second portion **131a2** having flexibility are alternately repeated and connected, and thus, can be bent in a shape corresponding to a shape of the vibration member or the vibration object. For example, when the vibration device **131** is connected or coupled to the vibration member including various curved portions by an adhesive member **120**, the vibration device **131** can be bent in a curved shape along a shape of a curved portion of the vibration member and reliability against damage or breakdown may not be reduced despite being bent in a curved shape.

(121) FIGS. 7A to 7D are perspective views illustrating different types of piezoelectric vibration portions, in the vibration device according to other embodiments of the present disclosure.

(122) With reference to FIG. 7A, the piezoelectric vibration portion **131a** according to another embodiment of the present disclosure can include a plurality of first portions **131a1**, which are spaced apart from one another along a first direction X and a second direction Y, and a second portion **131a2** (or one or more second portions) disposed between the plurality of first portions **131a1**.

(123) Each of the plurality of first portions **131a1** can be disposed to be spaced apart from one another along the first direction X and the second direction Y. For example, each of the plurality of first portions **131a1** can have a hexahedral shape (or a six-sided object shape) having the same size and can be disposed in a lattice shape or a grid shape. Each of the plurality of first portions **131a1** can include a piezoelectric material which is substantially the same as the first portion **131a1** described above with reference to FIGS. 4 to 6, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(124) The second portion **131a2** can be disposed between the plurality of first portions **131a1** along each of the first direction X and the second direction Y. The second portion **131a2** can be configured to fill a gap or a space between two adjacent first portions **131a1** or to surround each of the plurality of first portions **131a1**, and thus, can be connected or adhered to an adjacent first portion **131a1**. According to an embodiment of the present disclosure, a width of a second portion **131a2** disposed between two first portions **131a1** adjacent to each other along the first direction X can be the same as or different from that of a width of the first portion **131a1**, and the width of a second portion **131a2** disposed between two first portions **131a1** adjacent to each other along the second direction Y can be the same as or different from that of the width of the first portion **131a1**. The second portion **131a2** can include an organic material which is substantially the same as the second portion **131a2** described above with reference to FIGS. 4 to 6, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(125) As described above, the piezoelectric vibration portion **131a** according to another embodiment of the present disclosure can include a 1-3 composite structure having a piezoelectric characteristic of a 1-3 vibration mode, and thus, can have a resonance frequency of 30 MHz or less, but embodiments of the present disclosure are not limited thereto. For example, a resonance frequency of the piezoelectric vibration portion **131a** can vary based on at least one or more of a shape, a length, and a thickness, or the like.

(126) With reference to FIG. 7B, the piezoelectric vibration portion **131a** according to another embodiment of the present disclosure can include a plurality of first portions **131a1**, which are

spaced apart from one another along a first direction X and a second direction Y, and a second portion (or one or more second portions) **131a2** disposed between the plurality of first portions **131a1**.

(127) Each of the plurality of first portions **131a1** can have a flat structure of a circular shape. For example, each of the plurality of first portions **131a1** can have a circular plate shape, but embodiments of the present disclosure are not limited thereto. For example, each of the plurality of first portions **131a1** can have a dot shape including an oval shape, a polygonal shape, or a donut shape. Each of the plurality of first portions **131a1** can include a piezoelectric material which is be substantially the same as the first portion **131a1** described above with reference to FIGS. 4 to 6, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(128) The second portion **131a2** can be disposed between the plurality of first portions **131a1** along each of the first direction X and the second direction Y. The second portion **131a2** can be configured to surround each of the plurality of first portions **131a1**, and thus, can be connected or adhered to a side surface of each of the plurality of first portions **131a1**. Each of the plurality of first portions **131a1** and the second portion **131a2** can be disposed (or arranged) in parallel on the same plane (or the same layer). The second portion **131a2** can include an organic material which is be substantially the same as the second portion **131a2** described above with reference to FIGS. 4 to 6, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(129) With reference to FIG. 7C, in the vibration device **131** according to another embodiment of the present disclosure, the piezoelectric vibration portion **131a** can include a plurality of first portions **131a1**, which are spaced apart from one another along a first direction X and a second direction Y, and a second portion (or one or more second portions) **131a2** disposed between the plurality of first portions **131a1**.

(130) Each of the plurality of first portions **131a1** can have a flat structure of a triangular shape. For example, each of the plurality of first portions **131a1** can have a triangular plate shape. Each of the plurality of first portions **131a1** can include a piezoelectric material which is be substantially the same as the first portion **131a1** described above with reference to FIGS. 4 to 6, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(131) According to an embodiment of the present disclosure, four adjacent first portions **131a1** among the plurality of first portions **131a1** can be adjacent to one another to form a tetragonal shape (or a square shape or quadrilateral shape). Vertices of the four adjacent first portions **131a1** forming a tetragonal shape can be adjacent to one another in a center portion (or a central portion) of the tetragonal shape.

(132) The second portion **131a2** can be disposed between the plurality of first portions **131a1** along each of the first direction X and the second direction Y. The second portion **131a2** can be configured to surround each of the plurality of first portions **131a1**, and thus, can be connected or adhered to a side surface of each of the plurality of first portions **131a1**. Each of the plurality of first portions **131a1** and the second portion **131a2** can be disposed (or arranged) in parallel on the same plane (or the same layer). The second portion **131a2** can include an organic material which is be substantially the same as the second portion **131a2** described above with reference to FIGS. 4 to 6, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(133) With reference to FIG. 7D, in the vibration device **131** according to another embodiment of the present disclosure, the piezoelectric vibration portion **131a** can include a plurality of first portions **131a1**, which are spaced apart from one another along a first direction X and a second direction Y, and a second portion (or one or more second portions) **131a2** disposed between the plurality of first portions **131a1**.

(134) Each of the plurality of first portions **131a1** can have a flat structure of a triangular shape.

For example, each of the plurality of first portions **131a1** can have a triangular plate shape. Each of the plurality of first portions **131a1** can include a piezoelectric material which is substantially the same as the first portion **131a1** described above with reference to FIGS. **4** to **6**, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(135) According to another embodiment of the present disclosure, six adjacent first portions **131a1** of the plurality of first portions **131a1** can be adjacent to one another to form a hexagonal shape (or a regularly hexagonal shape). Vertices of the six adjacent first portions **131a1** forming a hexagonal shape can be adjacent to one another in a center portion (or a central portion) of the hexagonal shape.

(136) The second portion **131a2** can be disposed between the plurality of first portions **131a1** along each of the first direction X and the second direction Y. The second portion **131a2** can be configured to surround each of the plurality of first portions **131a1**, and thus, can be connected or adhered to a side surface of each of the plurality of first portions **131a1**. Each of the plurality of first portions **131a1** and the second portion **131a2** can be disposed (or arranged) in parallel on the same plane (or the same layer). The second portion **131a2** can include an organic material which is substantially the same as the second portion **131a2** described above with reference to FIGS. **4** to **6**, and thus, like reference numerals can refer to like elements, and their repetitive descriptions may be omitted.

(137) FIG. **8** illustrates a vibration device according to another embodiment of the present disclosure. FIG. **9** is a cross-sectional view taken along line C-C' illustrated in FIG. **8**. FIGS. **8** and **9** illustrate another embodiment of the vibration device illustrated in one or more of FIGS. **1** to **3**.

(138) With reference to FIGS. **8** and **9**, the vibration device **131** according to another embodiment of the present disclosure can include first and second vibration generating portions **131-1** and **131-2**.

(139) Each of the first and second vibration generating portions **131-1** and **131-2** can be electrically separated and disposed while being spaced apart from each other along a first direction X. Each of the first and second vibration generating portions **131-1** and **131-2** can alternately and repeatedly contract and expand based on a piezoelectric effect to vibrate. For example, the first and second vibration generating portions **131-1** and **131-2** can be disposed or tiled at a certain interval (or distance) SD1 along the first direction X. Thus, the vibration device **131** in which the first and second vibration generating portions **131-1** and **131-2** are tiled can be a vibration array, a vibration array portion, a vibration module array portion, a vibration array structure, a tiling vibration array, a tiling vibration array module, or a tiling vibration film.

(140) Each of the first and second vibration generating portions **131-1** and **131-2** according to an embodiment of the present disclosure can have a tetragonal shape. For example, each of the first and second vibration generating portions **131-1** and **131-2** can have a tetragonal shape having a width of about 5 cm or more. For example, each of the first and second vibration generating portions **131-1** and **131-2** can have a square shape having a size of 5 cm×5 cm or more, but embodiments of the present disclosure are not limited thereto.

(141) Each of the first and second vibration generating portions **131-1** and **131-2** can be arranged or tiled on the same plane, and thus, the vibration device **131** can have an enlarged area based on tiling of the first and second vibration generating portions **131-1** and **131-2** having a relatively small size.

(142) Each of the first and second vibration generating portions **131-1** and **131-2** can be arranged or tiled at a certain interval SD1, and thus, can be implemented as one vibration apparatus (or a single vibration apparatus) which is driven as one complete single-body without being independently driven. According to an embodiment of the present disclosure, with respect to the first direction X, a first separation distance (or a first interval) SD1 between the first and second vibration generating portions **131-1** and **131-2** can be 0.1 mm or more and less than 3 cm, but embodiments of the present disclosure are not limited thereto.

(143) According to an embodiment of the present disclosure, each of the first and second vibration generating portions **131-1** and **131-2** can be disposed or tiled to have the first separation distance (or an interval) **SD1** of 0.1 mm or more and less than 3 cm, and thus, can be driven as one vibration apparatus, thereby increasing a reproduction band of a sound and a sound pressure level characteristic of a sound which is generated based on a single-body vibration of the first and second vibration generating portions **131-1** and **131-2**. For example, the first and second vibration generating portions **131-1** and **131-2** can be disposed in the first separation distance (or the interval) **SD1** of 0.1 mm or more and less than 5 mm, in order to increase a reproduction band of a sound generated based on a single-body vibration of the first and second vibration generating portions **131-1** and **131-2** and to increase a sound of a low-pitched sound band (for example, a sound pressure level characteristic in 500 Hz or less).

(144) According to an embodiment of the present disclosure, when the first and second vibration generating portions **131-1** and **131-2** are disposed in the interval **SD1** of less than 0.1 mm or without the interval **SD1**, the reliability of the first and second vibration generating portions **131-1** and **131-2** or the vibration device **131** may be reduced due to damage or a crack caused by a physical contact therebetween which occurs when each of the first and second vibration generating portions **131-1** and **131-2** vibrates.

(145) According to an embodiment of the present disclosure, when the first and second vibration generating portions **131-1** and **131-2** are disposed in the interval **SD1** of 3 cm or more, the first and second vibration generating portions **131-1** and **131-2** may not be driven as one vibration apparatus due to an independent vibration of each of the first and second vibration generating portions **131-1** and **131-2** (e.g., may become unsynchronized). Therefore, a reproduction band of a sound and a sound pressure level characteristic of a sound which is generated based on vibrations of the first and second vibration generating portions **131-1** and **131-2** can be reduced. For example, when the first and second vibration generating portions **131-1** and **131-2** are disposed in the interval **SD1** of 3 cm or more, a sound characteristic and a sound pressure level characteristic of the low-pitched sound band (for example, in 500 Hz or less) may each be reduced.

(146) According to an embodiment of the present disclosure, when the first and second vibration generating portions **131-1** and **131-2** are disposed in an interval **SD1** of 5 mm, each of the first and second vibration generating portions **131-1** and **131-2** may not be perfectly driven as one vibration apparatus, and thus, a sound characteristic and a sound pressure level characteristic of the low-pitched sound band (for example, in 200 Hz or less) may each be reduced.

(147) According to another embodiment of the present disclosure, when the first and second vibration generating portions **131-1** and **131-2** are disposed in an interval **SD1** of 1 mm, each of the first and second vibration generating portions **131-1** and **131-2** can be driven as one vibration apparatus, and thus, a reproduction band of a sound can increase and a sound of the low-pitched sound band (for example, a sound pressure level characteristic in 500 Hz or less) can increase. For example, when the first and second vibration generating portions **131-1** and **131-2** are disposed in the interval **SD1** of 1 mm, the vibration device **131** can be implemented as a large-area vibrator which is enlarged based on optimization of a separation distance between the first and second vibration generating portions **131-1** and **131-2**. Therefore, the vibration device **131** can be driven as a large-area vibrator based on a single-body vibration of the first and second vibration generating portions **131-1** and **131-2**, and thus, a sound characteristic and a sound pressure level characteristic can each increase a reproduction band of a sound and in the low-pitched sound band generated based on a large-area vibration of the vibration device **131**.

(148) Therefore, to implement a single-body vibration (or one vibration apparatus) of the first and second vibration generating portions **131-1** and **131-2**, the separation distance (or the interval) **SD1** between the first and second vibration generating portions **131-1** and **131-2** can be adjusted to 0.1 mm or more and less than 3 cm. In addition, to implement a single-body vibration (or one vibration apparatus) of the first and second vibration generating portions **131-1** and **131-2** and to increase a

sound pressure level characteristic of a sound of the low-pitched sound band, the separation distance (or the interval) **SD1** between the first and second vibration generating portions **131-1** and **131-2** can be adjusted to 0.1 mm or more and less than 5 mm.

(149) Each of the first and second vibration generating portions **131-1** and **131-2** according to an embodiment of the present disclosure can include a piezoelectric vibration portion **131a**, a first electrode portion **131b**, and a second electrode portion **131c**.

(150) The piezoelectric vibration portion **131a** of each of the first and second vibration generating portions **131-1** and **131-2** can include a piezoelectric material (or an electroactive material) including a piezoelectric effect. For example, the piezoelectric vibration portion **131a** of each of the first and second vibration generating portions **131-1** and **131-2** can be configured substantially the same as any one of the piezoelectric vibration portion **131a** described above with reference to FIGS. 6 and 7A to 7D, and thus, like reference numeral can refer to like element, and the repetitive description thereof may be omitted.

(151) According to an embodiment of the present disclosure, each of the first and second vibration generating portions **131-1** and **131-2** can include any one piezoelectric vibration portion **131a** of the piezoelectric vibration portion **131a** described above with reference to FIGS. 6 and 7A to 7D, or can include different piezoelectric vibration portion **131a**.

(152) The first electrode portion **131b** can be disposed at a first surface of the piezoelectric vibration portion **131a** and can be electrically connected to the first surface of the piezoelectric vibration portion **131a**. For example, the first electrode portion **131b** can be substantially the same as the first electrode portion **131b** described above with reference to FIG. 5, and thus, like reference numeral can refer to like element, and the repetitive description thereof may be omitted.

(153) The second electrode portion **131c** can be disposed at a second surface of the piezoelectric vibration portion **131a** and electrically connected to the second surface of the piezoelectric vibration portion **131a**. The second electrode portion **131c** can be substantially the same as the second electrode portion **131c** described above with reference to FIG. 5, and thus, like reference numerals can refer to like elements, and the repetitive description thereof may be omitted.

(154) The vibration device **131** according to another embodiment of the present disclosure can further include a first cover member **131d** and a second cover member **131e**.

(155) The first cover member **131d** can be disposed at the first surface of the vibration device **131**. For example, the first cover member **131d** can cover the first electrode portion **131b** which is disposed at a first surface of each of the first and second vibration generating portions **131-1** and **131-2**, and thus, the first cover member **131d** can be connected to the first surface of each of the first and second vibration generating portions **131-1** and **131-2** in common or can support the first surface of each of the first and second vibration generating portions **131-1** and **131-2** in common. Accordingly, the first cover member **131d** can protect the first surface or the first electrode portion **131b** of each of the first and second vibration generating portions **131-1** and **131-2**.

(156) The second cover member **131e** can be disposed at the second surface of the vibration device **131**. For example, the second cover member **131e** can cover the second electrode portion **131c** which is disposed at a second surface of each of the first and second vibration generating portions **131-1** and **131-2**, and thus, the second cover member **131e** can be connected to the second surface of each of the first and second vibration generating portions **131-1** and **131-2** in common or can support the second surface of each of the first and second vibration generating portions **131-1** and **131-2** in common. Accordingly, the second cover member **131e** can protect the second surface or the second electrode portion **131c** of each of the first and second vibration generating portions **131-1** and **131-2**.

(157) The first cover member **131d** and the second cover member **131e** according to an embodiment of the present disclosure can each include one or more materials of plastic, fiber, and wood, but embodiments of the present disclosure are not limited thereto. For example, each of the first cover member **131d** and the second cover member **131e** can include the same material or

different material. For example, each of the first cover member **131d** and the second cover member **131e** can be a polyimide (PI) film or a polyethylene terephthalate (PET) film, but embodiments of the present disclosure are not limited thereto.

(158) The first cover member **131d** according to an embodiment of the present disclosure can be disposed at the first surface of each of the first and second vibration generating portions **131-1** and **131-2** by a first adhesive layer **131f**. For example, the first cover member **131d** can be directly disposed at the first surface of each of the first and second vibration generating portions **131-1** and **131-2** by a film laminating process using the first adhesive layer **131f**. Accordingly, each of the first and second vibration generating portions **131-1** and **131-2** can be integrated (or disposed) or tiled with the first cover member **131d** to have the certain interval SD1.

(159) The second cover member **131e** according to an embodiment of the present disclosure can be disposed at the second surface of each of the first and second vibration generating portions **131-1** and **131-2** by a second adhesive layer **131g**. For example, the second cover member **131e** can be directly disposed at the second surface of each of the first and second vibration generating portions **131-1** and **131-2** by a film laminating process using the second adhesive layer **131g**. Accordingly, each of the first and second vibration generating portions **131-1** and **131-2** can be integrated (or disposed) or tiled with the second cover member **131e** to have the certain interval SD 1.

(160) The first adhesive layer **131f** can be disposed between the first and second vibration generating portions **131-1** and **131-2** and disposed at the first surface of each of the first and second vibration generating portions **131-1** and **131-2**. For example, the first adhesive layer **131f** can be formed at a rear surface (or an inner surface) of the first cover member **131d** facing the first surface of each of the first and second vibration generating portions **131-1** and **131-2**, filled between the first and second vibration generating portions **131-1** and **131-2**, and disposed between at the first cover member **131d** and the first surface of each of the first and second vibration generating portions **131-1** and **131-2**.

(161) The second adhesive layer **131g** can be disposed between the first and second vibration generating portions **131-1** and **131-2** and disposed at the second surface of each of the first and second vibration generating portions **131-1** and **131-2**. For example, the second adhesive layer **131g** can be formed at a front surface (or an inner surface) of the second cover member **131e** facing the second surface of each of the first and second vibration generating portions **131-1** and **131-2**, filled between the first and second vibration generating portions **131-1** and **131-2**, and disposed between at the second cover member **131e** and the second surface of each of the first and second vibration generating portions **131-1** and **131-2**.

(162) The first and second adhesive layers **131f** and **131g** can be connected or coupled to each other between the first and second vibration generating portions **131-1** and **131-2**. Therefore, each of the first and second vibration generating portions **131-1** and **131-2** can be surrounded by the first and second adhesive layers **131f** and **131g**. For example, the first and second adhesive layers **131f** and **131g** can be configured between the first cover member **131d** and the second cover member **131e** to completely surround the first and second vibration generating portions **131-1** and **131-2**. For example, each of the first and second vibration generating portions **131-1** and **131-2** can be embedded or built-in between the first adhesive layer **131f** and the second adhesive layer **131g**. Thus, the first and second vibration generating portions **131-1** and **131-2** can be effectively sealed and protected between the first adhesive layer **131f** and the second adhesive layer **131g**.

(163) Each of the first and second adhesive layers **131f** and **131g** according to an embodiment of the present disclosure can include an electric insulating material which has adhesiveness and is capable of compression and decompression. For example, each of the first and second adhesive layers **131f** and **131g** can include an epoxy resin, an acrylic resin, a silicone resin, or a urethane resin, but embodiments of the present disclosure are not limited thereto. Each of the first and second adhesive layers **131f** and **131g** can be configured to be transparent, translucent, or opaque.

(164) The vibration device **131** according to another embodiment of the present disclosure can

further include a first power supply line PL1 disposed at the first cover member **131d**, a second power supply line PL2 disposed at the second cover member **131e**, and a pad part **131p** electrically connected to the first power supply line PL1 and the second power supply line PL2.

(165) The first power supply line PL1 can be disposed at the rear surface of the first cover member **131d** facing the first surface of each of the first and second vibration generating portions **131-1** and **131-2**. The first power supply line PL1 can be electrically connected to the first electrode portion **131b** of each of the first and second vibration generating portions **131-1** and **131-2**. For example, the first power supply line PL1 can be electrically and directly connected to the first electrode portion **131b** of each of the first and second vibration generating portions **131-1** and **131-2**. As an embodiment of the present disclosure, the first power supply line PL1 can be electrically connected to the first electrode portion **131b** of each of the first and second vibration generating portions **131-1** and **131-2** by an anisotropic conductive film. As another embodiment of the present disclosure, the first power supply line PL1 can be electrically connected to the first electrode portion **131b** of each of the first and second vibration generating portions **131-1** and **131-2** through a conductive material (or conductive particles) included in the first adhesive layer **131f**.

(166) The first power supply line PL1 according to an embodiment of the present disclosure can include first and second upper power lines PL11 and PL12 disposed along a second direction Y. For example, the first upper power line PL11 can be electrically connected to the first electrode portion **131b** of the first vibration generating portion **131-1**. The second upper power line PL12 can be electrically connected to the first electrode portion **131b** of the second vibration generating portion **131-2**.

(167) The second power supply line PL2 can be disposed at the front surface of the second cover member **131e** facing the second surface of each of the first and second vibration generating portions **131-1** and **131-2**. The second power supply line PL2 can be electrically connected to the second electrode portion **131c** of each of the first and second vibration generating portions **131-1** and **131-2**. For example, the second power supply line PL2 can be electrically and directly connected to the second electrode portion **131c** of each of the first and second vibration generating portions **131-1** and **131-2**. As an embodiment of the present disclosure, the second power supply line PL2 can be electrically connected to the second electrode portion **131c** of each of the first and second vibration generating portions **131-1** and **131-2** by an anisotropic conductive film. As another embodiment of the present disclosure, the second power supply line PL2 can be electrically connected to the second electrode portion **131c** of each of the first and second vibration generating portions **131-1** and **131-2** through a conductive material (or conductive particles) included in the second adhesive layer **131g**.

(168) The second power supply line PL2 according to an embodiment of the present disclosure can include first and second lower power lines PL21 and PL22 disposed along a second direction Y. For example, the first lower power line PL21 can be electrically connected to the second electrode portion **131c** of the first vibration generating portion **131-1**. For example, the first lower power line PL21 can be overlapped the first upper power line PL11. For example, the first lower power line PL21 can be disposed not to overlap the first upper power line PL11. The second lower power line PL22 can be electrically connected to the second electrode portion **131c** of the second vibration generating portion **131-2**. For example, the second lower power line PL22 can be overlapped the second upper power line PL12. For example, the second lower power line PL22 can be disposed not to overlap the second upper power line PL12.

(169) The pad part **131p** can be configured at one periphery portion of any one of the first cover member **131d** and the second cover member **131e** to be electrically connected to one portion (or one end) of each of the first power supply line PL1 and the second power supply line PL2.

(170) The pad part **131p** according to an embodiment of the present disclosure can include a first pad electrode electrically connected to one end of the first power supply line PL1, and a second pad electrode electrically connected to one end of the second power supply line PL2.

(171) The first pad electrode can be connected to one portion of each of the first and second upper power lines PL11 and PL12 of the first power supply line PL1 in common. For example, the one portion of each of the first and second upper power lines PL11 and PL12 can branch out from the first pad electrode. The second pad electrode can be connected to one portion of each of the first and second lower power lines PL21 and PL22 of the second power supply line PL2 in common. For example, the one portion of each of the first and second lower power lines PL21 and PL22 can branch out from the second pad electrode.

(172) The vibration device 131 according to another embodiment of the present disclosure can further include a signal cable 132.

(173) The signal cable 132 can be electrically connected to the pad part 131p disposed at the vibration device 131 and can supply the vibration device 131 with a vibration driving signal (or a sound signal or a voice signal) provided from a sound processing circuit. The signal cable 132 according to an embodiment of the present disclosure can include a first terminal electrically coupled to the first pad electrode of the pad part 131p and a second terminal electrically coupled to the second pad electrode of the pad part 131p. For example, the signal cable 132 can be configured as a flexible printed circuit cable, a flexible flat cable, a single-sided flexible printed circuit, a single-sided flexible printed circuit board, a flexible multilayer printed circuit, or a flexible multilayer printed circuit board, but embodiments of the present disclosure are not limited thereto.

(174) The sound processing circuit can generate an alternating current (AC) vibration driving signal including a first vibration driving signal and a second vibration driving signal based on a sound data. The first vibration driving signal can be any one of a positive (+) vibration driving signal and a negative (-) vibration driving signal, and the second vibration driving signal can be any one of a positive (+) vibration driving signal and a negative (-) vibration driving signal. For example, the first vibration driving signal can be supplied to the first electrode portion 131b of each of the first and second vibration generating portions 131-1 and 131-2 through a first terminal of the signal cable 132, the first pad electrode of the pad part 131p, and the first power supply line PL1. The second vibration driving signal can be supplied to the second electrode portion 131c of each of the first and second vibration generating portions 131-1 and 131-2 through a second terminal of the signal cable 132, the second pad electrode of the pad part 131p, and the second power supply line PL2.

(175) FIG. 10 illustrates a vibration device according to another embodiment of the present disclosure. FIG. 10 illustrates an embodiment where four vibration generating portions are provided in the vibration device illustrated in FIGS. 8 and 9. Hereinafter, therefore, the other elements except for the four vibration generating portions and relevant elements can be referred to by like reference numerals, and their repetitive descriptions may be omitted or will be briefly given. A cross-sectional surface taken along line C-C' illustrated in FIG. 10 is illustrated in FIG. 9.

(176) With reference to FIG. 10 in conjunction with FIG. 9, the vibration device 131 according to another embodiment of the present disclosure can include a plurality of vibration generating portions 131-1 to 131-4.

(177) The plurality of vibration generating portions 131-1 to 131-4 can be electrically disconnected and disposed spaced apart from one another along a first direction X and a second direction Y. For example, the plurality of vibration generating portions 131-1 to 131-4 can be arranged or tiled in an $i \times j$ form on the same plane, and thus, the vibration device 131 can be implemented to have a large area based on tiling of the plurality of vibration generating portions 131-1 to 131-4 having a relatively small size, where i and j are positive integers greater than zero. For example, i can be the number of vibration generating portions disposed along the first direction X and can be a natural number of 2 or more, and j can be the number of vibration generating portions disposed along the second direction Y and can be a natural number of 2 or more which is the same as or different from i . For example, the plurality of vibration generating portions 131-1 to 131-4 can be arranged or tiled in a 2×2 form, but embodiments of the present disclosure are not limited thereto. Hereinafter,

an example where the vibration device **131** includes first to fourth vibration generating portions **131-1** to **131-4** will be described.

(178) According to an embodiment of the present disclosure, the first and second vibration generating portions **131-1** and **131-2** can be spaced apart from each other along the first direction X. The third and fourth vibration generating portions **131-3** and **131-4** can be spaced apart from each other along the first direction X and can be spaced apart from each of the first and second vibration generating portions **131-1** and **131-2** along the second direction Y. The first and third vibration generating portions **131-1** and **131-3** can be spaced apart from each other along the second direction Y to face each other. The second and fourth vibration generating portions **131-2** and **131-4** can be spaced apart from each other along the second direction Y to face each other.

(179) The first to fourth vibration generating portions **131-1** to **131-4** can be disposed between the first cover member **131d** and the second cover member **131e**. For example, each of the first cover member **131d** and the second cover member **131e** can be connected to the first to fourth vibration generating portions **131-1** to **131-4** or can support the first to fourth vibration generating portions **131-1** to **131-4** in common, and thus, can drive the first to fourth vibration generating portions **131-1** to **131-4** as one vibration apparatus (or a single vibration apparatus). For example, the first to fourth vibration generating portions **131-1** to **131-4** can be tiled in a certain interval by the cover members **131d** and **131e**, and thus, can be driven as one vibration apparatus (or a single vibration apparatus).

(180) According to an embodiment of the present disclosure, as described above with reference to FIGS. **8** and **9**, in order to provide a complete single body vibration or a large-area vibration, the first to fourth vibration generating portions **131-1** to **131-4** can be disposed (or tiled) in the intervals SD1 and SD2 of 0.1 mm or more and less than 3 cm, more preferably, can be disposed (or tiled) in the intervals SD1 and SD2 0.1 mm or more and less than 5 mm (e.g., 2.5 mm), along each of the first direction X and the second direction Y.

(181) Each of the first to fourth vibration generating portions **131-1** to **131-4** can include a piezoelectric vibration portion **131a**, a first electrode portion **131b**, and a second electrode portion **131c**.

(182) The piezoelectric vibration portion **131a** of each of the first to fourth vibration generating portions **131-1** to **131-4** can include a piezoelectric material (or an electroactive material) including a piezoelectric effect. The piezoelectric vibration portion **131a** of each of the first to fourth vibration generating portions **131-1** to **131-4** can be configured substantially the same as any one of the piezoelectric vibration portion **131a** described above with reference to FIGS. **6** and **7A** to **7D**, and thus, like reference numerals can refer to like elements, and the repetitive description thereof may be omitted.

(183) According to an embodiment of the present disclosure, each of the first to fourth vibration generating portions **131-1** to **131-4** can include any one piezoelectric vibration portion **131a** of the piezoelectric vibration portion **131a** described above with reference to FIGS. **6** and **7A** to **7D**, or can include different piezoelectric vibration portion **131a**.

(184) According to another embodiment of the present disclosure, one or more of the first to fourth vibration generating portions **131-1** to **131-4** can include different piezoelectric vibration portion **131a** of the piezoelectric vibration portion **131a** described above with reference to FIGS. **6** and **7A** to **7D**.

(185) The first electrode portion **131b** can be disposed at a first surface of the corresponding piezoelectric vibration portion **131a** and electrically connected to the first surface of the piezoelectric vibration portion **131a**. The first electrode portion **131b** can be substantially the same as the first electrode portion **131b** described above with reference to FIG. **5**, and thus, like reference numeral can refer to like element, and the repetitive description thereof may be omitted.

(186) The second electrode portion **131c** can be disposed at a second surface of the corresponding piezoelectric vibration portion **131a** and electrically connected to the second surface of the

piezoelectric vibration portion **131a**. The second electrode portion **131c** can be substantially the same as the second electrode portion **131c** described above with reference to FIG. 5, and thus, like reference numeral can refer to like element, and the repetitive description thereof may be omitted. (187) According to an embodiment of the present disclosure, first and second adhesive layers **131f** and **131g** can be connected or coupled to each other between first to fourth vibration generating portions **131-1** to **131-4**. Therefore, each of the first to fourth vibration generating portions **131-1** to **131-4** can be surrounded by the first and second adhesive layers **131f** and **131g**. For example, the first and second adhesive layers **131f** and **131g** can be configured between a first cover member **131d** and a second cover member **131e** to completely surround each of the first to fourth vibration generating portions **131-1** to **131-4**. For example, each of the first to fourth vibration generating portions **131-1** to **131-4** can be embedded or built-in between the first adhesive layer **131f** and the second adhesive layer **131g**.

(188) The vibration device **131** according to another embodiment of the present disclosure can further include a first power supply line PL1, a second power supply line PL2, and a pad part **131p**.

(189) Except for an electrical connection structure between the first and second power supply lines PL1 and PL2 and the first to fourth vibration generating portions **131-1** to **131-4**, the first and second power supply lines PL1 and PL2 can be substantially the same as the first and second power supply lines PL1 and PL2 described above with reference to FIGS. 8 and 9, and thus, only the electrical connection structure between the first and second power supply lines PL1 and PL2 and the first to fourth vibration generating portions **131-1** to **131-4** will be briefly described below.

(190) The first power supply line PL1 according to an embodiment of the present disclosure can include first and second upper power lines PL11 and PL12 disposed along a second direction Y. For example, the first upper power line PL11 can be electrically connected to the first electrode portion **131b** of each of the first and third vibration generating portions **131-1** and **131-3** (or a first group or a first vibration generating group) disposed at a first row parallel to a second direction Y of the first to fourth vibration generating portions **131-1** to **131-4**. The second upper power line PL12 can be electrically connected to the first electrode portion **131b** of each of the second and fourth vibration generating portions **131-2** and **131-4** (or a second group or a second vibration generating group) disposed at a second row parallel to the second direction Y of the first to fourth vibration generating portions **131-1** to **131-4**.

(191) The second power supply line PL2 according to an embodiment of the present disclosure can include first and second lower power lines PL21 and PL22 disposed along a second direction Y. For example, the first lower power line PL21 can be electrically connected to the second electrode portion **131c** of each of the first and third vibration generating portions **131-1** and **131-3** (or the first group or the first vibration generating group) disposed at the first row parallel to the second direction Y of the first to fourth vibration generating portions **131-1** to **131-4**. The second lower power line PL22 can be electrically connected to the second electrode portion **131c** of each of the second and fourth vibration generating portions **131-2** and **131-4** (or the second group or the second vibration generating group) disposed at the second row parallel to the second direction Y of the first to fourth vibration generating portions **131-1** to **131-4**.

(192) The pad part **131p** can be configured at one periphery portion of any one among the first cover member **131d** and the second cover member **131e** to be electrically connected to one side (or one end) of each of the first and second power supply lines PL1 and PL2. The pad part **131p** can be substantially the same as the pad part **131p** illustrated in FIGS. 8 and 9, and thus, like reference numeral can refer to like element, and the repetitive description thereof may be omitted.

(193) As described above, the vibration device **131** according to another embodiment of the present disclosure can have the same effect as that of the vibration device **131** described above with reference to FIGS. 4 to 9, and thus, the repetitive description thereof may be omitted.

(194) FIGS. 11 to 14 are a cross-sectional view taken along line A-A' illustrated in FIG. 1. FIG. 11 illustrates a sound apparatus according to another embodiment of the present disclosure and

illustrates an embodiment implemented by modifying a structure of the vibration member of in FIG. 3. FIG. 12 illustrates a sound apparatus according to another embodiment of the present disclosure and illustrates an embodiment implemented by modifying a structure of the vibration member of in FIG. 2. FIG. 13 illustrates a sound apparatus according to another embodiment of the present disclosure and illustrates an embodiment implemented by modifying a structure of the vibration member and the housing of in FIG. 11. FIG. 14 illustrates a sound apparatus according to another embodiment of the present disclosure and illustrates an embodiment implemented by modifying a structure of the vibration member and the housing of in FIG. 2. Therefore, in the following description, repetitive descriptions of the other elements except a vibration member and the housing, and relevant elements may be omitted.

(195) With reference to FIGS. 1 and 11, a vibration member 110 can be configured in a form where the vibration member 110 is inserted or accommodated into a second groove portion 153 of a housing 150. The vibration member 110 of a sound apparatus 10 according to another embodiment of the present disclosure can be configured in a form where both ends of a first surface and a second surface of the vibration member 110 are fixed in the second groove portion 153. In detail, the first surface of the vibration member 110 can be connected to the second groove portion 153 of the housing 150 through a first connection member 141, and the second surface of the vibration member 110 can be connected to the second groove portion 153 of the housing 150 through a second connection member 143. According to another embodiment of the present disclosure, because both ends of the vibration member 110 are fixed by the second groove portion 153, a reflected wave can be offset at the both ends of the vibration member 110, and thus, the peak or dip phenomenon of a sound characteristic caused by a standing wave can be reduced. The peak can be a phenomenon where a sound pressure level bounces in a specific frequency, and the dip can be a phenomenon where a low pressure level occurs because the occurrence of a specific frequency is prevented. A sound output characteristic of a sound apparatus can be reduced by the peak or the dip phenomenon.

(196) In the sound apparatus 10 according to another embodiment of the present disclosure, because both ends of the vibration member 110 are fixed by the second groove portion 153, a reflected wave can be offset at the both ends of the vibration member 110, and thus, the peak or dip phenomenon of a sound characteristic caused by a standing wave can be reduced, a sound characteristic of the low-pitched sound band can be enhanced, and when the peak or dip phenomenon occurs, a sound output characteristic of the sound apparatus can be reduced. In detail, in the sound apparatus according to another embodiment of the present disclosure, a sound characteristic of the low-pitched sound band can be enhanced, and a dip phenomenon of a middle-pitched sound band and a dip phenomenon of a high-pitched sound band can be reduced. For example, the low pitched sound can be a frequency range of 500 Hz or less, the middle-pitched sound band can be a frequency range of 500 Hz to 2,000 Hz, and the high-pitched sound band can be a frequency range of 2,000 Hz to 20,000 Hz. However, the frequency ranges of the middle-pitched sound band and a middle-high-pitched sound band according an embodiment of the present disclosure are not limited thereto.

(197) With reference to FIGS. 1 and 12, the vibration member 110 can further include a first groove portion 110a (e.g., in an area overlapping with the vibration apparatus 130). In FIG. 12, for convenience of description, a first groove portion 110a can denote an empty space where a vibration member 110 is not provided, but the first groove portion 110a can denote a portion which is thinner in thickness t1 of at least a portion of the vibration member 110 than another portion. At least a portion of the first groove portion 110a can overlap a vibration apparatus 130. According an embodiment of the present disclosure, a thickness of the vibration member 110 overlapping the first groove portion 110a can be a thickness which is thinner than a portion, which does not overlap the first member groove portion 110a, of the vibration member 110. For example, a thickness of the vibration member 110 overlapping the first groove portion 110a can be adjusted to 10% to 90%

(e.g., 50%) of a thickness of a portion, where the first groove portion **110a** is not provided, of the vibration member **110**. For example, a first groove portion **110a** can be a groove portion, a second groove portion, or a groove portion of a vibration member, or a vibration member groove portion, but embodiments of the present disclosure are not limited thereto.

(198) The vibration apparatus **130** can be adjusted to have a first length **D1** in a first direction **X** and can be adjusted to have a second length in a second direction **Y**. The first groove portion **110a** can be set to have a first length **L1** in the first direction **X** and can be adjusted to have a second length in the second direction **Y**.

(199) According an embodiment of the present disclosure, the first length **D1** of the vibration apparatus **130** can be equal to or different from the first length **L1** of the first groove portion **110a**, and the second length of the vibration apparatus **130** can be equal to or different from the second length of the first groove portion **110a**. According an embodiment of the present disclosure, the first length **D1** of the vibration apparatus **130** can be greater than or equal to the first length **L1** of the first groove portion **110a**, and the second length of the vibration apparatus **130** can be greater than or equal to the second length of the first groove portion **110a**.

(200) According an embodiment of the present disclosure, a dimension of the first groove portion **110a** adjusted in the first direction **X** and the second direction **Y** can have a value which is adjusted to be two times each dimension adjusted in the first direction **X** and the second direction **Y**. When adjusted in this manner, the flatness of a sound pressure level output characteristic can increase.

(201) The first groove portion **110a** can have a thickness which is thinner than another portion of the vibration member **110**, and thus, bending stiffness of the vibration apparatus **130** disposed on a rear surface of the vibration member **110** at a position corresponding to the first groove portion **110a** can be reduced, a sound reproduction characteristic of the low-pitched sound band can be enhanced because a vibration displacement based on the application of a driving force or a voltage of the vibration apparatus **130** increases, and the dip phenomenon of the middle-pitched sound band and the peak phenomenon of the high-pitched sound band can be reduced. For example, the first groove portion **110a** can allow the vibration member **110** to flex more in an area overlapping with the vibration apparatus **130**, which can improve sound production.

(202) According an embodiment of the present disclosure, bending stiffness of the vibration apparatus **130** can be calculated as expressed in the following Equation 1.

Bending Stiffness= $Eh^3/12$ [Equation 1]

(203) In Equation 1, **E** can denote a young's modulus, and **h** can denote a thickness of a vibration member at a position at which the first groove portion **110a** is provided. Accordingly, With reference to Equation 1, it can be seen that the bending stiffness is proportional to cube (or 3 raised to the power) of a thickness of the vibration member **110**.

(204) According an embodiment of the present disclosure, the bending stiffness should be 0.20 Nm or more. For example, when the vibration member **110** configures as a material including acrylonitrile-butadiene-styrene (ABS) and has a thickness of 1 mm, the vibration member **110** can be calculated to have a bending stiffness value of about 0.19 Nm. When the bending stiffness is less than 0.20 Nm, a sound pressure level of 75 dB or more may not be secured near 100 Hz.

Accordingly, when the vibration member **110** includes a material including ABS and is set to have a thickness of less than 1 mm, it may be unable to realize a desired low sound characteristic (e.g., bass sounds may be impaired).

(205) With reference to FIGS. **1** and **13**, a vibration member **110** can be configured in a form where the vibration member **110** is inserted or accommodated into a second groove portion **153** of a housing **150**. The vibration member **110** of a sound apparatus **10** according to another embodiment of the present disclosure can be configured in a form where both ends of a first surface and a second surface of the vibration member **110** are fixed in the second groove portion **153**. In detail, the first surface of the vibration member **110** can be connected to the second groove portion **153** of the housing **150** through a first connection member **141**, and the second surface of the vibration

member **110** can be connected to the second groove portion **153** of the housing **150** through a second connection member **143**. According to another embodiment of the present disclosure, because both ends of the vibration member **110** are fixed by the second groove portion **153**, a reflected wave can be offset at the both ends of the vibration member **110**, and thus, the peak or dip phenomenon of a sound characteristic caused by a standing wave can be reduced. In addition, the vibration member **110** can be configured to further include a first groove portion **110a**.

(206) With reference to FIGS. **1** and **14**, the vibration member **110** according to another embodiment of the present disclosure can be configured to further include a protrusion portion **111**. The protrusion portion **111** can be connected to a periphery portion of the vibration member **110**. For example, the protrusion portion **111** can be bent from the periphery portion of the vibration member **110** along a third direction Z parallel to a thickness direction of the vibration member **110**. For example, the protrusion portion **111** can include first to fourth lateral portions. The protrusion portion **111** can be connected or coupled to a lateral portion **152** of the housing **150** by the connection member **140**. The protrusion portion **111** can be configured to increase stiffness (or bending stiffness) of the vibration member **110**. The vibration member **110** including a protrusion portion **111** can be configured to further include a first groove portion **110a**.

(207) FIGS. **15** to **17** are another cross-sectional views taken along line A-A' illustrated in FIG. **1**. FIGS. **15** to **17** are diagrams illustrating a sound apparatus according to another embodiment of the present disclosure and illustrate an embodiment where a structure of an inner housing is added to an inner portion of a housing and a structure of a sound apparatus is modified so that the inner housing is coupled to an auxiliary vibration member (or a secondary vibration member). Therefore, in the following description, repetitive descriptions of the other elements except an inner housing, and relevant elements is omitted.

(208) With reference to FIGS. **1** and **15**, a sound apparatus **10** according to another embodiment of the present disclosure can further include an inner housing **170** which is disposed inside (or an inward) a housing **150**. The housing **150** can be disposed to surround the inner housing **170**, can include an accommodation space **170s** for accommodating the vibration apparatus **130**, and can have a box shape where one side is opened. In addition, an opening of one side of the accommodation space **170s** is covered by the vibration member **110**, and a predetermined air gap can be formed between the accommodation space **170s** and the vibration member **110**.

(209) The inner housing **170** according to an embodiment of the present disclosure can include one or more of a metal material and a nonmetal material (or a composite nonmetal material), but embodiments of the present disclosure are not limited thereto. For example, the inner housing **170** can include one or more materials of a metal material, plastic, and wood, but embodiments of the present disclosure are not limited thereto. For example, the inner housing **170** can be referred to as the term such as an inner case, an inner case member, a housing member, an inner cabinet, an inner enclosure, an inner sealing member, an inner sealing cap, an inner sealing box, or an inner sound box, or the like, but embodiments of the present disclosure are not limited thereto. For example, the accommodation space **170s** of the inner housing **170** can be referred to as various terms, such as a gap space, an air gap, a vibration space, a sound space, a sound box, or a sealing space, but embodiments of the present disclosure are not limited thereto.

(210) The inner housing **170** according to an embodiment of the present disclosure can include a bottom portion **171** and a lateral portion **172**. The bottom portion **171** can be disposed at a rear surface of the vibration member **110** to cover a second surface of the vibration member **110** and the vibration apparatus **130**. For example, the bottom portion **171** can be disposed to be spaced apart from the second surface of the vibration member **110** and the vibration apparatus **130**.

(211) The lateral portion **172** can be connected to a periphery portion of the bottom portion **171**. For example, the lateral portion **172** can be bent from the periphery portion of the bottom portion **171** in a third direction Z parallel to a thickness direction of the vibration member **110**. For example, the lateral portion **172** can include first to fourth lateral portions. The lateral portion **172**

can be integrated into the bottom portion **171**. For example, the bottom portion **171** and the lateral portion **172** can be integrated as one body, and thus, the accommodation space **170s** surrounded by the lateral portion **172** can be provided on the bottom portion **171**. Accordingly, the bottom portion **171** and the lateral portion **172** can have a box shape where one side is opened.

(212) The inner housing **170** can further include a first reinforcement member **173** which is formed to protrude toward the vibration apparatus **130** from the bottom portion **171** thereof. The first reinforcement member **173** can also define different chambers within the inner housing **170**.

(213) The first reinforcement member **173** can be formed to protrude toward the vibration apparatus **130** from a center portion of the bottom portion **171** and can be configured to contact the vibration apparatus **130**. The first reinforcement member **173** can have a certain width at a portion contacting the vibration apparatus **130** or can be implemented in a stumpy shape and can have a height capable of contacting the vibration apparatus **130**.

(214) When an impact is applied from the outside (for example, a rear surface of the bottom portion **171**), the first reinforcement member **173** can disperse a dotted-contact impact into a line-contact impact (e.g., spreading out the force across a larger area), thereby preventing a specific portion of the vibration apparatus **130** from being damaged.

(215) The inner housing **170** can be coupled to the vibration member **110** through a connection member **117** (or a third connection member). The connection member **117** (or the third connection member) can couple inner housing **170** to the vibration member **110**.

(216) The connection member **117** according to an embodiment of the present disclosure can include an adhesive layer (or a tacky layer) which is good in adhesive force or attaching force. For example, the connection member **117** can include a double-sided adhesive tape, a double-sided foam pad, or a tacky sheet. For example, when the connection member **117** includes a tacky sheet or adhesive film (or a tacky layer), the connection member **117** can include only an adhesive layer or a tacky layer without a base member such as a plastic material or the like.

(217) The adhesive layer (or a tacky layer) of the connection member **117** according to an embodiment of the present disclosure can include epoxy, acrylic, silicone, or urethane, but embodiments of the present disclosure are limited thereto.

(218) The adhesive layer (or a tacky layer) of the connection member **117** according to another embodiment of the present disclosure can include a pressure sensitive adhesive (PSA), an optically clear adhesive (OCA), or an optically clear resin (OCR), but embodiments of the present disclosure are limited thereto.

(219) With reference to FIGS. **1** and **16**, the sound apparatus **10** according to another embodiment of the present disclosure can further include a secondary vibration member **115** between the vibration apparatus **130** and the vibration member **110** and can further include a connection member **119** (or a fourth connection member) between the secondary vibration member **115** and the vibration member **110**.

(220) The secondary vibration member **115** can include a metal material or a nonmetal material (or a composite nonmetal material) having a material characteristic suitable for outputting a sound based on a vibration. The metal material of the secondary vibration member **115** according to an embodiment of the present disclosure can include any one or more materials of stainless steel, aluminum (Al), an Al alloy, magnesium (Mg), a Mg alloy, and a magnesium-lithium (Mg—Li) alloy, but embodiments of the present disclosure are not limited thereto. The nonmetal material (or the composite nonmetal material) of the secondary vibration member **115** can include one or more of glass, plastic, fiber, leather, wood, cloth, rubber, carbon, and paper, but embodiments of the present disclosure are not limited thereto.

(221) The connection member **119** according to an embodiment of the present disclosure can include an adhesive layer (or a tacky layer) which is good in adhesive force or attaching force. For example, the connection member **119** can include a double-sided adhesive tape, a double-sided foam pad, or a tacky sheet. For example, when the connection member **119** includes a tacky sheet

(or a tacky layer), the connection member **119** can include only an adhesive layer or a tacky layer without a base member such as a plastic material or the like.

(222) The adhesive layer (or a tacky layer) of the connection member **119** according to an embodiment of the present disclosure can include epoxy, acrylic, silicone, or urethane, but embodiments of the present disclosure are limited thereto.

(223) The adhesive layer (or a tacky layer) of the connection member **119** according to another embodiment of the present disclosure can include a pressure sensitive adhesive (PSA), an optically clear adhesive (OCA), or an optically clear resin (OCR), but embodiments of the present disclosure are limited thereto.

(224) Moreover, according to an embodiment of the present disclosure, the secondary vibration member **115**, the vibration apparatus **130** at the rear surface of the secondary vibration member **115**, and the inner housing **170** coupled to the secondary vibration member **115** can be provided as a module type. Accordingly, a vibration apparatus module including the secondary vibration member **115**, the vibration apparatus **130**, and the inner housing **170** can be assembled as a predetermined configuration, and then, can be connected or coupled to a rear surface of the vibration member **110** by the connection member **119** as needed.

(225) With reference to FIGS. **1** and **17**, a sound apparatus **10** according to another embodiment of the present disclosure can further include a sound processing circuit **190** mounted at a bottom portion of the inner housing **170**, and the sound processing circuit **190** can be connected to a vibration apparatus **130** through a signal cable **132**.

(226) The sound processing circuit **190** can be connected to the signal cable **132**, or can be mounted at the signal cable **132**. The sound processing circuit **190** can be protected from impacts and outside elements by being housed within a chamber inside the inner housing **170**.

(227) The sound processing circuit **190** according to an embodiment of the present disclosure can include a decoding part which receives sound data supplied from an external sound data generating circuit part, an audio amplifier circuit which outputs first and second vibration driving signals based on the sound data supplied from the decoding part, a memory circuit which stores a setting value of the audio amplifier circuit, a control circuit which controls an operation of each of the decoding part, the audio amplifier circuit, and the memory circuit, and a passive element such as a resistor.

(228) The sound processing circuit **190** can generate first and second vibration driving signals based on the sound data and can output each of the generated first and second vibration driving signals to a corresponding terminal of first and second terminals through each of a corresponding contact pad and a corresponding driving signal supply line. Therefore, a vibration apparatus **130** can vibrate based on the first and second vibration driving signals which are supplied from the sound processing circuit **190** through each of a signal line of the signal cable **132**, the first and second terminals, a pad portion, and first and second power supply lines.

(229) FIGS. **18A** and **18B** are a perspective view illustrating an inner housing according to an embodiment of the present disclosure. FIGS. **19A**, **19B**, and **19C** are a plan view illustrating an inner housing according to an embodiment of the present disclosure.

(230) With reference to FIG. **18A**, the inner housing **170** can further include a first reinforcement member **173** which is formed to protrude toward a vibration apparatus **130** from a bottom portion **171** thereof.

(231) The first reinforcement member **173** can be formed to protrude toward the vibration apparatus **130** from a center portion of the bottom portion **171** and can be configured to contact the vibration apparatus **130**. The first reinforcement member **173** can have a certain width at a portion contacting the vibration apparatus **130** or can be implemented in a stumpy shape and can have a height capable of contacting the vibration apparatus **130**.

(232) When an impact is applied from the outside (for example, a rear surface of the bottom portion **171**), the first reinforcement member **173** can disperse a dotted-contact impact into a line-contact

impact, thereby preventing a specific portion of the vibration apparatus **130** from being damaged by spreading the force out across a larger area.

(233) With reference to FIG. **18B**, the inner housing **170** can further include a second reinforcement member **175** which is formed to protrude toward a vibration apparatus **130** from the bottom portion **171** thereof.

(234) The second reinforcement member **175** can be formed to protrude toward the vibration apparatus **130** in a mesh form or a net network form at all regions of the bottom portion **171** except a region where the first reinforcement member **173** is provided and can be configured not to contact the vibration apparatus **130**. An upper end of the second reinforcement member **175** can have a certain width or can be configured in a stumpy shape and can have a height which is lower than the first reinforcement member **173**. For example, the first reinforcement member **173** and the second reinforcement member **175** can have the same width. For example, the second reinforcement member **175** can have an egg crate type of structure or a honeycomb type of structure.

(235) When an impact is applied from the outside (for example, a rear surface of the bottom portion **171**), the first reinforcement member **173** can disperse a dotted-contact impact into a line-contact impact, thereby preventing a specific portion of the vibration apparatus **130** from being damaged.

(236) When an impact is applied from the outside (for example, a rear surface of the bottom portion **171**), the second reinforcement member **175** can disperse a dotted-contact impact to be similar to a surface contact in a mesh structure, thereby preventing a specific portion of the vibration apparatus **130** from being damaged by spreading out the force across a larger area.

(237) With reference to FIGS. **19A** to **19C**, the inner housing **170** can further include an opening portion **177** which communicates a first surface (or an upper surface) of the bottom portion **191** with a second surface (or a lower surface) of the bottom portion **191**. The opening portion **177** can be formed in a slit shape formed in parallel with a second direction Y, or can be formed like a cylindrical hole having a certain standard. However, in the present disclosure, when the opening portion **177** is configured in a slit shape, a long side of the opening portion **177** having a slit shape is not limited to be parallel with the second direction Y. In addition, the opening portion **177** having a cylindrical hole shape in FIG. **19B** is not limited in shape and can be prepared in various shapes as well as an opening portion having a cylindrical hole shape.

(238) In FIGS. **19A** to **19C**, with respect to a plane, a cross-sectional area of a plurality of opening portions can be variously adjusted. For example, a sum of cross-sectional areas of opening portions **177** having a plurality of slit shapes can be adjusted to an area of 700 mm.² to 1,000 mm.² in FIG. **19A**, a sum of cross-sectional areas of opening portions **177** having a plurality of cylindrical hole shapes can be adjusted to an area of 50 mm.² to 200 mm.² in FIG. **19B**, and a sum of cross-sectional areas of opening portions **177** having a plurality of slit shapes can be adjusted to an area of 500 mm.² to 700 mm.² in FIG. **19C**.

(239) According to an embodiment of the present disclosure, when a plurality of opening portions **177** capable of communication of air are formed in a rear surface of the vibration apparatus **130**, a close space surrounding the vibration apparatus **130** can be configured to communicate with a rear surface of the inner housing **170**, and in this situation, an impedance component (or an air impedance or an elastic impedance) acting on the vibration member **110** can vary. The holes can all allow air to pass in and out of one or more sound chambers within the inner housing **170**. For example, when a plurality of opening portions are formed in the inner housing **170**, a sound characteristic of the high-pitched sound band can be enhanced.

(240) FIG. **20** is a perspective view of a sound apparatus according to another embodiment of the present disclosure. FIG. **21** is a cross-sectional view taken along line D-D' of FIG. **20**. FIG. **22** illustrates an arrangement structure of a vibration apparatus on a rear surface of a vibration member. A sound apparatus **20** of FIG. **20** is implemented by modifying a structure so that a dimension of the sound apparatus **10** of FIG. **1** in a first direction X is the same as a dimension of the sound apparatus **10** of FIG. **1** in a second direction Y. In the following description, therefore,

repetitive descriptions of the other elements except an arrangement structure of each of a vibration member **110** and a vibration apparatus **130** may be omitted.

(241) With reference to FIGS. **20** and **21**, the sound apparatus according to another embodiment of the present disclosure can be configured so that a dimension thereof in a first direction X is the same as a dimension thereof in a second direction Y. In addition, a structure of each of a vibration member **110** and a housing **150** in the sound apparatus **20** of FIG. **21** can be applied to be identical to a structure of each of the vibration member **110** and the housing **150** of the sound apparatus **10** described above with reference to FIGS. **2**, **3**, and **11** to **17**.

(242) With reference to FIG. **22**, the vibration member **110** can have a length corresponding to X_t in a first direction X and can have a length corresponding to Y_t in a second direction Y. According to another embodiment of the present disclosure, in the vibration member **110**, X_t in the first direction X can be adjusted to the same length as Y_t in the second direction Y, and thus, the vibration member **110** can be prepared in a square shape. The vibration apparatus **130** can be disposed at a second surface (or a rear surface) of the vibration member **110**.

(243) With respect to a direction parallel with the first direction X, a length from one side of the vibration member **110** to a center portion of the vibration apparatus **130** can be a first length X_1 , and a length from the center portion of the vibration apparatus **130** to the other side of the vibration member **110** can be a second length X_2 . A sum of the first length X_1 and the second length X_2 can be the same length as the length X_t of the vibration member **110** in the first direction X.

(244) With respect to a direction parallel with the second direction Y, a length from one side of the vibration member **110** to a center portion of the vibration apparatus **130** can be a first length Y_1 , and a length from the center portion of the vibration apparatus **130** to the other side of the vibration member **110** can be a second length Y_2 . A sum of the first length Y_1 and the second length Y_2 can be the same length as the length Y_t of the vibration member **110** in the first direction Y.

(245) According to another embodiment of the present disclosure, a sound characteristic of the sound apparatus **20** can be enhanced based on the optimal arrangement of a rear surface of the vibration member **110** of the vibration apparatus **130**. For example, the vibration apparatus **130** may not be disposed at a center of the vibration member **110**, and a sound characteristic can be enhanced in a direction biased toward the first direction X or the second direction Y from the center of the vibration member **110**.

(246) FIG. **23** illustrates a sound output characteristic of a sound apparatus where a protrusion portion is not provided in the sound apparatus of FIG. **2**.

(247) A sound output characteristic can be measured by a sound analysis equipment. The sound output characteristic has been measured by a B&K audio measurement apparatus. The sound analysis equipment can include a sound card which transmits or receives a sound to or from a control personal computer (PC), an amplifier which amplifies a signal generated from the sound card and transfers the amplified signal to a vibration apparatus, and a microphone which collects a sound generated by the vibration apparatus in a display panel. For example, the microphone can be disposed at a center of the vibration apparatus, and a distance between the display panel and the microphone can be 50 cm. A sound can be measured under a condition where the microphone is vertical to the vibration apparatus. The sound collected through the microphone can be input to the control PC through the sound card, and a control program can check the input sound to analyze a sound of the vibration apparatus. For example, a frequency response characteristic corresponding to a frequency range of 100 Hz to 20 kHz can be measured by using a pulse program.

(248) In FIG. **23**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB). A solid line of FIG. **23** represents a sound output characteristic of the sound apparatus of FIG. **2**, and a dotted line represents a sound output characteristic of a sound apparatus structure where the protrusion portion **111** is not provided in the sound apparatus structure of FIG. **2**.

(249) With reference to FIG. **23**, comparing with a dotted line, in a solid line, it can be seen that a

sound output characteristic is enhanced in a frequency range of 2,000 Hz to 4,000 Hz and 6 kHz to 10 kHz. For example, comparing with the dotted line, in the solid line, it can be seen that a sound pressure level is enhanced in the middle-pitched sound band and the high-pitched sound band. For example, comparing with the dotted line, in the solid line, it can be seen that a sound pressure level is averagely enhanced by about 10 dB or more in a frequency range of 2,000 Hz to 4,000 Hz and is enhanced by about 5 dB or more in a frequency range of 6 kHz to 10 kHz. In other words, the protrusion portion **111** can help improve the midrange sound frequencies produced by the vibration apparatus **130**.

(250) FIG. **24** illustrates a sound pressure level with respect to a frequency of a sound apparatus where a first groove portion **110a** is provided in the sound apparatus of FIG. **11** and is not provided in the sound apparatus of FIG. **12**.

(251) A method of measuring a sound output characteristic can be the same as the descriptions of FIG. **23**, and thus, repetitive descriptions thereof may be omitted.

(252) In FIG. **24**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB). A solid line of FIG. **24** represents a sound output characteristic of the sound apparatus of FIG. **11**, and a dotted line represents a sound output characteristic of a sound apparatus structure where the first groove portion **110a** is not provided in the sound apparatus structure of FIG. **12**.

(253) With reference to FIG. **24**, comparing with a dotted line, in a solid line, it can be seen that a sound output characteristic is enhanced in a frequency range of 100 Hz or less, 500 Hz to 1,000 Hz, and 2000 Hz or more. For example, comparing with the dotted line, in the solid line, it can be seen that a sound pressure level is enhanced in the low-pitched sound band, the middle-pitched sound band, and the high-pitched sound band. For example, comparing with a dotted line, in a solid line, it can be seen that a sound output characteristic is averagely enhanced by about 5 dB in 100 Hz or less, it can be seen that the dip phenomenon is reduced in a frequency range of 500 Hz to 1,000 Hz, and it can be seen that the peak phenomenon of the high-pitched sound band is reduced in 2,000 Hz or more. In other words, the first groove portion **110a** can help the vibration apparatus **130** improve bass response, improve midrange response, and dampen harsh high pitched sound levels.

(254) FIGS. **25a** to **25f** illustrate a sound pressure level with respect to a frequency of the sound apparatus of FIG. **12** where a first groove portion is prepared through modification under various conditions.

(255) A method of measuring a sound output characteristic can be the same as the descriptions of FIG. **23**, and thus, repetitive descriptions thereof may be omitted.

(256) In FIGS. **25a** to **25e**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB). In FIGS. **25a** to **25e**, a solid line represents a sound output characteristic of the sound apparatus of FIG. **12** where a thickness of a vibration member is set to 1 mm, and a dotted line represents a sound output characteristic of a sound apparatus structure where the first groove portion **110a** is not provided in the sound apparatus structure of FIG. **12** and a thickness of the vibration member is set to 1 mm. In FIG. **25f**, a solid line represents a sound output characteristic of a sound apparatus structure where the first groove portion **110a** is not provided in the sound apparatus structure of FIG. **12** and a thickness of the vibration member is set to 3 mm.

(257) In FIGS. **25a** to **25f**, the vibration member **110** can configure a material including acrylonitrile-butadiene-styrene (ABS).

(258) In FIGS. **25a** to **25e**, an experiment has been performed under a condition where a thickness of the vibration member corresponding to the first groove portion **110a** is adjusted to 1 mm, a length of the first groove portion **110a** in the first direction X and the second direction Y is formed in the same square shape, and a length of one corner thereof is changed to 60 mm, 120 mm, 140 mm, 180 mm, and 240 mm, and a length of the vibration apparatus **130** in the first direction X and the second direction Y has been formed to 120 mm in the same square shape.

(259) With reference to FIG. 25a, when a length of the first groove portion **110a** illustrated by a solid line in the first direction X and the second direction Y is adjusted to 60 mm, it can be seen that a low sound peak observed in a lowest frequency is measured to be a value of about 90 dB in about 190 Hz.

(260) Comparing with a dotted line, in a solid line, it can be seen that a dip phenomenon of a middle-pitched sound band is improved and a sound pressure level of a high-pitched sound band is enhanced. For example, the middle-pitched sound band is a frequency range of 500 Hz to 1,000 Hz, and the high-pitched sound band can be a frequency range of more than 10 kHz.

(261) With reference to FIG. 25b, when a length of the first groove portion **110a** illustrated by a solid line in the first direction X and the second direction Y is adjusted to 120 mm, it can be seen that a low sound peak observed in a lowest frequency is measured to be a value of about 85 dB in about 180 Hz.

(262) Comparing with a dotted line, in a solid line, it can be seen that a sound pressure level of a high-pitched sound band is enhanced. For example, the high-pitched sound band can be a frequency range of more than 10 kHz.

(263) With reference to FIG. 25c, when a length of the first groove portion **110a** illustrated by a solid line in the first direction X and the second direction Y is adjusted to 140 mm, it can be seen that a low sound peak observed in a lowest frequency is measured to be a value of about 85 dB in about 170 Hz.

(264) Comparing with a dotted line, in a solid line, it can be seen that a sound pressure level of a high-pitched sound band is enhanced. For example, the high-pitched sound band can be a frequency range of more than 10 kHz.

(265) With reference to FIG. 25d, when a length of the first groove portion **110a** illustrated by a solid line in the first direction X and the second direction Y is adjusted to 180 mm, it can be seen that a low sound peak observed in a lowest frequency is measured to be a value of about 82 dB in about 150 Hz.

(266) Comparing with a dotted line, in a solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band is enhanced and a sound pressure level of a high-pitched sound band is enhanced. For example, the low-pitched sound band can be a frequency range of less than 200 Hz, and the high-pitched sound band can be a frequency range of more than 10 kHz.

(267) With reference to FIG. 25e, when a length of the first groove portion **110a** illustrated by a solid line in the first direction X and the second direction Y is adjusted to 240 mm, it can be seen that a low sound peak observed in a lowest frequency is measured to be a value of about 80 dB in about 130 Hz.

(268) Comparing with a dotted line, in a solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band is enhanced, a sound pressure level characteristic of the middle-pitched sound band is enhanced, and a sound pressure level characteristic of the high-pitched sound band is enhanced. Also, comparing with a dotted line, in a solid line, it can be seen that the flatness of a total sound pressure level is improved in a frequency range of 200 Hz or more. For example, the low-pitched sound band can be a frequency range of less than 200 Hz, the middle-pitched sound band can be a frequency range of 500 Hz to 2,000 kHz, and the high-pitched sound band can be a frequency range of more than 10 kHz.

(269) With reference to FIG. 25f, when a thickness of the vibration member **110** is adjusted to 3 mm, it can be seen that a low sound peak observed in the lowest frequency is measured to be a value of about 72 dB in about 100 Hz. Comparing with a dotted line, in a solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band is enhanced.

(270) With reference to results of FIGS. 25a to 25e, it has been confirmed that a low sound peak observed in a low frequency moves in a lowering direction as a relative length of the first groove portion **110a** in the first direction X and the second direction Y with respect to the vibration

apparatus **130** increases progressively. In other words, as the length of the first groove portion **110a** is made longer, a sound peak for the bass response moves to lower and lower sound frequencies, thus improving the lower range response. Accordingly, it can be seen that a sound characteristic of the low-pitched sound band increases as a size of the first groove portion **110a** increases compared to the vibration apparatus **130**.

(271) FIGS. **26a** to **26e** illustrate a sound pressure level with respect to a frequency of the sound apparatus of FIG. **12** which is provided by changing a thickness of a vibration member corresponding to a first groove portion under various conditions.

(272) A method of measuring a sound output characteristic can be the same as the descriptions of FIG. **23**, and thus, repetitive descriptions thereof may be omitted.

(273) In FIGS. **26a** to **26e**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB). In FIGS. **26a** to **26e**, a solid line represents a sound output characteristic of the sound apparatus of FIG. **12** where a thickness of the vibration member **110** corresponding to the first groove portion **110a** is adjusted to 0.5 mm to 2.5 mm, and a dotted line represents a sound output characteristic of a sound apparatus structure where the first groove portion **110a** is not provided in the sound apparatus structure of FIG. **12** and a thickness of the vibration member is adjusted to 3 mm. In addition, a length of the first groove portion **110a** in the first direction X and the second direction Y is adjusted to 240 mm in FIGS. **26a** to **26e**, and the vibration member **110** in FIGS. **26A** to **26E** includes a material including acrylonitrile-butadiene-styrene (ABS).

(274) With reference to FIG. **26a**, in the dotted line, it can be seen that a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 180 Hz. In the solid line, when a thickness of the vibration member **110** corresponding to the first groove portion **110a** is adjusted to 0.5 mm, a low sound peak observed in the lowest frequency is measured to be a value of about 62 dB in about 70 Hz. Therefore, when a thickness of the vibration member **110** is adjusted to 1.0 mm or less, because the bending stiffness of the vibration member **110** for appropriate driving of the vibration apparatus **130** is not satisfied, the sound characteristic efficiency of a low-pitched sound band may be reduced. For example, the low-pitched sound band may be a frequency range of less than 200 Hz.

(275) With reference to FIG. **26b**, in the dotted line, it can be seen that a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 180 Hz. In the solid line, when a thickness of the vibration member **110** corresponding to the first groove portion **110a** is adjusted to 1.0 mm, a low sound peak observed in the lowest frequency is measured to be a value of about 80 dB in about 130 Hz.

(276) Comparing with the dotted line, in the solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band and a sound pressure level characteristic of the high-pitched sound band are enhanced, and a peak phenomenon of a middle-high-pitched sound band is reduced. For example, the low-pitched sound band can be a frequency range of less than 200 Hz, and the middle-high-pitched sound band can be a frequency range of 2,000 Hz to 5,000 kHz. The high-pitched sound band can be a frequency range of more than 10 kHz.

(277) With reference to FIG. **26c**, in the dotted line, it can be seen that a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 180 Hz. In the solid line, when a thickness of the vibration member **110** corresponding to the first groove portion **110a** is adjusted to 1.5 mm, a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 150 Hz.

(278) Comparing with the dotted line, in the solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band is enhanced, a peak phenomenon of the middle-high-pitched sound band is reduced, and the flatness of a sound pressure level is improved in a full frequency range of 200 Hz or more. For example, the low-pitched sound band can be a frequency range of less than 200 Hz, and the middle-high-pitched sound band can be a frequency range of

2,000 Hz to 5,000 kHz.

(279) With reference to FIG. **26d**, in the dotted line, it can be seen that a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 180 Hz. In the solid line, when a thickness of the vibration member **110** corresponding to the first groove portion **110a** is adjusted to 2.0 mm, a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 170 Hz. Comparing with the dotted line, in the solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band is enhanced, the flatness of a sound pressure level is improved in a full frequency range of 200 Hz or more, and a peak phenomenon of the middle-pitched sound band is reduced. For example, the low-pitched sound band can be a frequency range of less than 200 Hz, and the middle-pitched sound band can be a frequency range of 500 Hz to 2,000 kHz.

(280) With reference to FIG. **26e**, in the dotted line, it can be seen that a low sound peak observed in the lowest frequency is measured to be a value of about 90 dB in about 180 Hz. In the solid line, when a thickness of the vibration member **110** corresponding to the first groove portion **110a** is adjusted to 2.5 mm, a low sound peak observed in the lowest frequency is measured to be a value of about 92 dB in about 180 Hz. Comparing with the dotted line, in the solid line, it can be seen that a sound pressure level characteristic of the low-pitched sound band is enhanced, the flatness of a sound pressure level is improved in a full frequency range of 200 Hz or more. For example, the low-pitched sound band can be a frequency range of less than 200 Hz.

(281) With reference to results of FIGS. **26a** to **26e**, a thickness of the vibration member **110** corresponding to the first groove portion **110a** can be adjusted to have a thickness which is greater than or equal to a least thickness, to secure bending stiffness based on the vibration apparatus **130**. For example, when the vibration member **110** includes a material including ABS, a lowest thickness can be adjusted to 1 mm, and for example, the bending stiffness of the vibration member **110** can be 0.20 Nm or more. Also, when the first groove portion **110a** is provided and the vibration member **110** satisfies a desired thickness, a sound characteristic of the low-pitched sound band can be enhanced, the flatness of a sound pressure level can be improved across a full frequency range, and a dip phenomenon of the middle-pitched sound band and a peak of the high-pitched sound band can be reduced. In other words, a sound frequency response having improved flatness can be provided by appropriately adjusting a thickness of the first groove portion **110a**.

(282) FIG. **27** illustrates a sound pressure level with respect to a frequency of a sound apparatus to which a structure of the inner housing of FIGS. **18A**, **18B**, **19A**, **19B**, and **19C** is applied.

(283) A method of measuring a sound output characteristic can be the same as the descriptions of FIG. **23**, and thus, repetitive descriptions thereof may be omitted.

(284) In FIG. **27**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB).

(285) In FIG. **27**, a thick solid line represents a sound output characteristic of a sound apparatus to which a structure of the inner housing **150** of FIG. **18A** is applied, a thin solid line represents a sound output characteristic of a sound apparatus to which a structure of the inner housing **150** of FIG. **18B** is applied, a thick dotted line represents a sound output characteristic of a sound apparatus to which a structure of the inner housing **150** of FIG. **19A** is applied, a thin dotted line represents a sound output characteristic of a sound apparatus to which a structure of the inner housing **150** of FIG. **19B** is applied, and a dash-single dotted line represents a sound output characteristic of a sound apparatus to which a structure of the inner housing **150** of FIG. **19C** is applied.

(286) With reference to FIG. **27**, in the sound apparatuses **10** illustrated by the thick solid line, the thin solid line, the thick dotted line, the thin dotted line, and the dash-single dotted line, it can be seen that a difference between sound output characteristics hardly occur in a frequency range of a middle-high-pitched sound band or less. Comparing with the thick solid line, the thin solid line, the thin dotted line, and the dash-single dotted line, in the thick dotted line, it can be seen that a sound

pressure level is enhanced in a frequency range of a high-pitched sound band. For example, the high-pitched sound band can be in a frequency range of 8,000 Hz to 10,000 Hz.

(287) FIG. **28** illustrates a sound pressure level with respect to a frequency of a structure where a first groove portion is not provided in the sound apparatus of FIGS. **15** and **16**, and the sound apparatus of FIG. **12**.

(288) A method of measuring a sound output characteristic can be the same as the descriptions of FIG. **23**, and thus, repetitive descriptions thereof may be omitted.

(289) In FIG. **28**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB).

(290) In FIG. **28**, a dotted line represents a sound output characteristic of a sound apparatus to which the inner housing of FIG. **15** is applied, a solid line represents a sound output characteristic of a sound apparatus to which the inner housing of FIG. **16** is applied, and a dash-single dotted line represents a sound output characteristic of a structure where a first groove portion is not provided in the sound apparatus **10** of FIG. **12**.

(291) With reference to FIG. **28**, comparing with the dash-single dotted line, in the dotted line and the solid line, it can be seen that a sound pressure level characteristic is enhanced in a frequency range of a middle-low-pitched sound band. For example, the middle-low-pitched sound band can be a frequency range of 300 Hz to 500 Hz. Also, comparing with the dash-single dotted line, in the dotted line and the solid line, it can be seen that there is no difference between sound output characteristics in a full-pitched sound band, except for the middle-low-pitched sound band.

(292) FIG. **29** shows a sound pressure level with respect to a frequency of the sound apparatus of FIG. **22**.

(293) A method of measuring a sound output characteristic can be the same as the descriptions of FIG. **23**, and thus, repetitive descriptions thereof may be omitted.

(294) In FIG. **28**, the abscissa axis represents a frequency in hertz (Hz), and the ordinate axis represents a sound pressure level SPL in decibels (dB).

(295) In FIG. **29**, a length of the vibration member **110** in the first direction X and a length of the vibration member **110** in the second direction Y is each adjusted to 150 mm, and a length of a valid vibration plate of the vibration member **110** can be reduced by the connection member **140** at one side and the other side of the vibration member **110** (e.g., see FIG. **22**). In FIG. **29**, a first-direction length of the connection member **140** is adjusted to 10 mm. Accordingly, a length of a valid vibration plate of the vibration member **110** is 130 mm. The vibration apparatus **130** is disposed at a center of the vibration member **110**, and then, a sound pressure level output characteristic has been measured while moving by 5 mm each toward one side of the vibration member in the first direction X. For example, FIG. **29** plots various sound responses as certain dimensions shown in FIG. **22** are adjusted.

(296) In FIG. **29**, a dotted line represents a value which has been measured under a condition where each of a first length X1 and a second length X2 of the vibration member **110** in the first direction X is 65 mm identically and each of a first length Y1 and a second length Y2 of the vibration member **110** in the second direction Y is 65 mm identically (e.g., also see FIG. **22**).

(297) In FIG. **29**, a solid line represents a value which has been measured under a condition where each of a first length X1 and a second length X2 of the vibration member **110** in the first direction X is 65 mm identically, a first length Y1 of the vibration member **110** in the second direction Y is 60 mm, and a second length Y2 of the vibration member **110** in the second direction Y is 70 mm (e.g., also see FIG. **22**).

(298) In FIG. **29**, a dash-single dotted line represents a value which has been measured under a condition where each of a first length X1 and a second length X2 of the vibration member **110** in the first direction X is 65 mm identically, a first length Y1 of the vibration member **110** in the second direction Y is 55 mm, and a second length Y2 of the vibration member **110** in the second direction Y is 75 mm (e.g., also see FIG. **22**).

(299) In FIG. 29, a thick dotted line represents a value which has been measured under a condition where each of a first length X1 and a second length X2 of the vibration member **110** in the first direction X is 65 mm identically, a first length Y1 of the vibration member **110** in the second direction Y is 50 mm, and a second length Y2 of the vibration member **110** in the second direction Y is 80 mm (e.g., also see FIG. 22).

(300) In FIG. 29, a thick solid line represents a value which has been measured under a condition where each of a first length X1 and a second length X2 of the vibration member **110** in the first direction X is 65 mm identically, a first length Y1 of the vibration member **110** in the second direction Y is 45 mm, and a second length Y2 of the vibration member **110** in the second direction Y is 85 mm (e.g., also see FIG. 22).

(301) Comparing with the dotted line, in the solid line, the dash-single dotted line, and the thick solid line, a sound pressure level of a low-pitched sound band or a primarily resonance point band of the vibration apparatus **130** can increase. For example, a sound pressure level of about 400 Hz can increase in the low-pitched sound band or the primarily resonance point band, and thus, comparing with the dotted line, in the solid line, the dash-single dotted line, and the thick solid line, there can be an advantage in sound pressure level of the low-pitched sound band.

(302) In a certain frequency range including 2 kHz which is a quaternary resonance point, a sound pressure level can decrease in a direction distancing from a center portion of the vibration member **110**. For example, comparing with the dotted line, in the thick dotted line, a sound pressure level can decrease by about 6 dB.

(303) Therefore, when a position of one corner of the vibration member **110** in the first direction X is defined as a value of 0% and a position of the other corner of the vibration member **110** in the first direction X is defined as a value of 100%, for example, the vibration apparatus **130** can be disposed within a range of 35% to 65% in the first direction X of the vibration member **110**, or can be disposed within a range of 38.5% to 61.5%.

(304) Therefore, when a position of one corner of the vibration member **110** in the second direction Y is defined as a value of 0% and a position of the other corner of the vibration member **110** in the second direction Y is defined as a value of 100%, for example, the vibration apparatus **130** can be disposed within a range of 35% to 65% in the second direction Y of the vibration member **110**, or can be disposed within a range of 38.5% to 61.5%.

(305) The sound apparatus according to an embodiment of the present disclosure will be described below.

(306) An apparatus according to an embodiment of the present disclosure can comprise a vibration member, a housing at a rear surface of the vibration member, a connection member between the vibration member and the housing, and a vibration apparatus vibrating the vibration member.

(307) According to some embodiments of the present disclosure, the vibration member can have a non-flat structure.

(308) According to some embodiments of the present disclosure, the vibration member can comprise a protrusion portion, the protrusion portion protrudes from the rear surface of the vibration member, and the protrusion portion and the vibration member can be configured as one body.

(309) According to some embodiments of the present disclosure, the vibration member can further comprise a first groove portion, the first groove portion can be provided at a first surface of the vibration member to have a thickness which is thinner than another portion of the vibration member that does not overlap with the vibration apparatus, and the vibration apparatus can overlap at least a portion of the first groove portion.

(310) According to some embodiments of the present disclosure, the housing can comprise a bottom portion, a lateral portion connected to a periphery of the bottom portion to protrude toward the vibration member, and a second groove portion provided at an inner surface of the lateral portion.

(311) According to some embodiments of the present disclosure, a periphery portion of the vibration member can be inserted or accommodated into the second groove portion of the housing.

(312) According to some embodiments of the present disclosure, the vibration member can comprise a protrusion portion, and the protrusion portion can protrude from a second surface of the vibration member and is inserted or accommodated into the second groove portion.

(313) According to some embodiments of the present disclosure, the vibration member can further comprise a first groove portion, the first groove portion can be provided at a first surface of the vibration member to have a thickness which is thinner than another portion of the vibration member, the vibration apparatus can overlap at least a portion of the first groove portion, and a periphery portion of the vibration member can be inserted or accommodated into the second groove portion of the housing.

(314) According to some embodiments of the present disclosure, the connection member can comprise a first connection member disposed at an upper end of the second groove portion of the housing, and a second connection member disposed at a lower end of the second groove portion of the housing.

(315) According to some embodiments of the present disclosure, the sound apparatus can further comprise an inner housing disposed inside the housing to surround the vibration apparatus, the inner housing can comprise a bottom portion, a lateral portion connected to a periphery of the bottom portion to protrude toward the vibration member, and a first reinforcement member provided at a center portion of the bottom portion, the first reinforcement member protruding to contact the vibration apparatus.

(316) According to some embodiments of the present disclosure, the inner housing can further comprise a second reinforcement member provided at a periphery portion of the first reinforcement member to protrude toward the vibration apparatus from the bottom portion, and the second reinforcement member can have a height which is lower than the first reinforcement member.

(317) According to some embodiments of the present disclosure, the inner housing can further comprise an opening portion formed to pass through a first surface of the bottom portion and a second surface, which is opposite to the first surface, of the bottom portion, and the opening portion can comprise at least one of a hole shape and a slit shape. For example, the opening portion can allow air to pass in and out of the inner housing.

(318) According to some embodiments of the present disclosure, the sound apparatus can further comprise a secondary vibration member between the inner housing and the vibration member, a third connection member between the inner housing and the secondary vibration member, and a fourth connection member between the secondary vibration member and the vibration member.

(319) According to some embodiments of the present disclosure, the sound apparatus can further comprise a sound processing circuit mounted at the bottom portion of the inner housing, and the sound processing circuit can be connected to the vibration apparatus through a signal cable.

(320) According to some embodiments of the present disclosure, the vibration apparatus can be disposed to overlap the vibration member, between one corner and the other corner of the vibration member in a first direction or a second direction, and a center portion of a horizontal surface of the vibration apparatus can overlap a center portion of a horizontal surface of the vibration member, or can be disposed close thereto in the first direction or the second direction.

(321) According to some embodiments of the present disclosure, the center portion of the horizontal surface of the vibration apparatus can be disposed within a range of 0% to 15% in the first direction or the second direction from the center portion of the horizontal surface of the vibration member, with respect to a size of a valid vibration plate of the vibration member.

(322) According to some embodiments of the present disclosure, the vibration apparatus can comprise a vibration device, the vibration device can comprise a vibration portion, a first electrode portion at a first surface of the vibration portion, and a second electrode portion at a second surface different from the first surface of the vibration portion.

(323) According to some embodiments of the present disclosure, the vibration apparatus can further comprise a first cover member at the first electrode portion, and a second cover member at the second electrode portion.

(324) According to some embodiments of the present disclosure, the vibration apparatus can further comprise a first adhesive layer between the first cover member and the first electrode portion, and a second adhesive layer between the second cover member and the second electrode portion.

(325) According to some embodiments of the present disclosure, the vibration portion can comprise an inorganic material portion having a piezoelectric characteristic.

(326) According to some embodiments of the present disclosure, the vibration portion can comprise a plurality of inorganic material portions having a piezoelectric characteristic, and a plurality of organic material portion between the plurality of inorganic material portions.

(327) According to some embodiments of the present disclosure, the vibration member can comprise a metal material, or comprises single nonmetal materials or composite nonmetal materials of one or more of wood, rubber, plastic, glass, fiber, cloth, paper, a mirror, carbon, and leather.

(328) According to some embodiments of the present disclosure, the vibration member can comprise one or more of a display panel including a pixel configured to display an image, a light emitting diode lighting panel, an organic light emitting lighting panel, and an inorganic light emitting lighting panel.

(329) According to some embodiments of the present disclosure, the vibration member can comprise one or more of a display panel including a pixel configured to display an image, a screen panel on which an image is to be projected from a display apparatus, a lighting panel, a signage panel, a vehicular dash board, a vehicular roof panel, side panel or column, a vehicular interior material, a vehicular glass window, a vehicular exterior material, a building ceiling material, a building interior material, a building glass window, an aircraft interior material, an aircraft glass window, metal, wood, rubber, plastic, glass, fiber, cloth, paper, leather, carbon, and a mirror.

(330) The sound apparatus according to an embodiment of the present disclosure can be connected to all electronic devices by wire or wirelessly and can be used as a sound apparatus of a corresponding electronic device. For example, an apparatus connectable to the sound apparatus according to some embodiments of the present disclosure can be applied to mobile apparatuses, video phones, smart watches, watch phones, wearable apparatuses, foldable apparatuses, rollable apparatuses, bendable apparatuses, flexible apparatuses, curved apparatuses, sliding apparatuses, variable apparatuses, electronic organizers, electronic books, portable multimedia players (PMPs), personal digital assistants (PDAs), MP3 players, mobile medical devices, desktop personal computers (PCs), laptop PCs, netbook computers, workstations, navigation apparatuses, automotive navigation apparatuses, automotive display apparatuses, automotive apparatuses, theater apparatuses, theater display apparatuses, TVs, wall paper display apparatuses, signage apparatuses, game machines, notebook computers, monitors, cameras, camcorders, and home appliances, or the like. Also, the sound apparatus according to some embodiments of the present disclosure can be applied to organic light-emitting lighting apparatuses or inorganic light-emitting lighting apparatuses. When the sound apparatus according to some embodiments of the present disclosure is applied to lighting apparatuses, the lighting apparatuses can act as lighting and a speaker. Also, when the sound apparatus according to some embodiments of the present disclosure is applied to a mobile device, or the like, the sound apparatus can be one or more of a speaker, a receiver, and a haptic device, but embodiments of the present disclosure are not limited thereto.

(331) It will be apparent to those skilled in the art that various modifications and variations can be made in the present disclosure without departing from the spirit or scope of the disclosures. Thus, it is intended that the present disclosure covers the modifications and variations of this disclosure provided they come within the scope of the appended claims and their equivalents.

Claims

1. A sound apparatus, comprising: a vibration member; a housing at a rear surface of the vibration member; a connection member disposed between the vibration member and the housing; and a vibration apparatus configured to vibrate the vibration member, wherein the vibration member comprises a first groove portion at a front surface of the vibration member, and wherein the vibration apparatus overlaps at least a portion of the first groove portion.
2. The sound apparatus of claim 1, wherein the vibration member has a non-flat structure.
3. The sound apparatus of claim 2, wherein: the vibration member comprises a protrusion portion; the protrusion portion protrudes from the rear surface of the vibration member; and the protrusion portion and the vibration member are configured as one body.
4. The sound apparatus of claim 2, wherein the first groove portion of the vibration member is thinner than another portion of the vibration member that does not overlap with the vibration apparatus.
5. The sound apparatus of claim 1, wherein the housing comprises: a bottom portion; a lateral portion connected to a periphery of the bottom portion and protruding toward the vibration member; and a second groove portion at an inner surface of the lateral portion of the housing.
6. The sound apparatus of claim 5, wherein a periphery portion of the vibration member is fitted into the second groove portion of the housing.
7. The sound apparatus of claim 6, wherein the connection member comprises: a first connection member disposed at an upper side of the second groove portion of the housing; and a second connection member disposed at a lower side of the second groove portion of the housing, wherein at least a portion of the vibration member is disposed between the first connection member and the second connection member.
8. The sound apparatus of claim 5, wherein the vibration member comprises a protrusion portion, and wherein the protrusion portion protrudes from a second surface of the vibration member and is fitted into the second groove portion of the housing.
9. The sound apparatus of claim 5, wherein: the first groove portion of the vibration member is being-thinner than another portion of the vibration member that does not overlap with the vibration apparatus; and a periphery portion of the vibration member is fitted into the second groove portion of the housing.
10. The sound apparatus of claim 1, further comprising an inner housing disposed inside the housing, the inner housing at least partially surrounding the vibration apparatus, wherein the inner housing comprises: a bottom portion; a lateral portion connected to a periphery of the bottom portion and protruding toward the vibration member; and a first reinforcement member at a center portion of the bottom portion, the first reinforcement member protruding toward the vibration apparatus for supporting the vibration apparatus.
11. The sound apparatus of claim 10, wherein: the inner housing further comprises a second reinforcement member provided at a periphery portion of the first reinforcement member and protruding toward the vibration apparatus from the bottom portion of the inner housing, and the second reinforcement member has a height lower than a height of the first reinforcement member.
12. The sound apparatus of claim 10, wherein: the inner housing further comprises an opening portion passing through a first surface of the bottom portion of the inner housing and a second surface of the inner housing; and the opening portion in the inner housing comprises at least one of a hole shape and a slit shape.
13. The sound apparatus of claim 10, further comprising: an auxiliary vibration member disposed between the inner housing and the vibration member; a third connection member disposed between the inner housing and the auxiliary vibration member; and a fourth connection member disposed between the auxiliary vibration member and the vibration member.

14. The sound apparatus of claim 10, further comprising a sound processing circuit mounted at the bottom portion of the inner housing, wherein the sound processing circuit is connected to the vibration apparatus through a signal cable.

15. The sound apparatus of claim 1, wherein: the vibration apparatus overlaps with the vibration member, between one corner and another corner of the vibration member in a first direction or a second direction; and a center portion of a horizontal surface of the vibration apparatus overlaps a center portion of a horizontal surface of the vibration member in the first direction or the second direction, or the center portion of the horizontal surface of the vibration apparatus corresponds to the center portion of the horizontal surface of the vibration member in the first direction or the second direction.

16. The sound apparatus of claim 1, wherein the vibration apparatus comprises a vibration device, wherein the vibration device comprises: a vibration portion; a first electrode portion at a first surface of the vibration portion; and a second electrode portion at a second surface different from the first surface of the vibration portion.

17. The sound apparatus of claim 16, wherein the vibration apparatus further comprises: a first cover member at the first electrode portion; and a second cover member at the second electrode portion.

18. The sound apparatus of claim 17, wherein the vibration apparatus further comprises: a first adhesive layer disposed between the first cover member and the first electrode portion; and a second adhesive layer disposed between the second cover member and the second electrode portion.

19. The sound apparatus of claim 16, wherein the vibration portion comprises an inorganic material portion having a piezoelectric characteristic.

20. The sound apparatus of claim 16, wherein the vibration portion comprises: a plurality of inorganic material portions having a piezoelectric characteristic; and an organic material portion disposed between the plurality of inorganic material portions.

21. The sound apparatus of claim 1, wherein the vibration member comprises a metal material, a single nonmetal material, or a composite including one or more of wood, rubber, plastic, glass, fiber, cloth, paper, a mirror, carbon, and leather.

22. The sound apparatus of claim 1, wherein the vibration member is mounted on or in at least one of a display panel including a pixel configured to display an image, a light emitting diode lighting panel, an organic light emitting lighting panel, an inorganic light emitting lighting panel, a screen panel on which an image is to be projected from a display apparatus, a lighting panel, a signage panel, a vehicular interior material, a vehicular glass window, a vehicular exterior material, a building ceiling material, a building interior material, a building glass window, an aircraft interior material, an aircraft glass window, metal, wood, rubber, plastic, glass, fiber, cloth, paper, leather, carbon, and a mirror.

23. A sound apparatus, comprising: a vibration member; a vibration apparatus configured to vibrate the vibration member, the vibration apparatus including at least one piezoelectric element for producing sound; a housing disposed at a rear surface of the vibration member; and a connection member disposed between the vibration member and the housing, wherein the connection member has a first stiffness that is less than a second stiffness of the housing, wherein the vibration member is isolated from the housing by the connection member, wherein the vibration member comprises a first groove portion at a front surface of the vibration member, and wherein the vibration apparatus overlaps at least a portion of the first groove portion.

24. The sound apparatus of claim 23, wherein the first groove portion is being-configured to reduce a stiffness of the vibration member for adjusting a sound frequency response of the sound apparatus, and wherein a thickness of the first groove portion of the vibration member is thinner than a thickness of another portion of vibration member that does not overlap with the vibration apparatus.

25. The sound apparatus of claim 23, further comprising: a first reinforcement member disposed at a rear surface of the vibration apparatus for supporting the vibration apparatus and for adjusting a sound frequency response of the sound apparatus.

26. The sound apparatus of claim 23, wherein the first reinforcement member directly contacts the rear surface of the vibration apparatus.
