

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396566
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Petzold Sotomayor; Heidi Pamela

Protective, collapsible, lightweight bed finishing frame

Abstract

A protective, highly padded/cushioned, lightweight, collapsible, portable, affordable, and aesthetically pleasing bed finishing frame. The apparatus slips over a box spring without any assembly necessary, tangentially supporting generous padding/cushion around the perimeter of the box spring, thereby protecting individuals from injury by contacting any hard edges or surfaces associated with the box spring or bed frame and providing a stylistic and finished appearance.

Inventors:	Petzold Sotomayor; Heidi Pamela (Los Angeles, CA)
Applicant:	Petzold Sotomayor; Heidi Pamela (Los Angeles, CA)
Family ID:	1000008778628
Appl. No.:	17/713990
Filed:	April 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220225783 A1	Jul. 21, 2022

Related U.S. Application Data

continuation parent-doc US 15173857 20160606 US 11317726 child-doc US 17713990
us-provisional-application US 62230437 20150606

Publication Classification

Int. Cl.: A47C19/02 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: A47C (21/06); A47C (21/08); A47C (19/02); A47C (19/021); A47C (31/00); A47C (31/10); A47C (31/105); A47C (31/11); A47C (27/002); A47G (9/0284); A47G (9/0292); A47D (15/008)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
113605	12/1870	Willmot	N/A	N/A
1699498	12/1928	Hanauer	N/A	N/A
1710591	12/1928	Pingry	N/A	N/A
1885558	12/1931	Smith	2/69.5	A47D 15/008
3144666	12/1963	Ragsdale Mazera	5/493	A47G 9/0284
4092752	12/1977	Dougan	N/A	N/A
4117782	12/1977	Cahill	N/A	N/A
4141097	12/1978	Levinsohn	5/493	A47G 9/0292
4153230	12/1978	Giacin	N/A	N/A
4514871	12/1984	Fisher et al.	N/A	N/A
4873734	12/1988	Pollard	N/A	N/A
5021279	12/1990	Whitener	N/A	N/A
5027454	12/1990	Peng	N/A	N/A
5247897	12/1992	Pepp	N/A	N/A
5473785	12/1994	Lager et al.	N/A	N/A
5496609	12/1995	Michelstein	N/A	N/A
5508078	12/1995	Stalnaker	N/A	N/A
5639072	12/1996	McCall	N/A	N/A
5802637	12/1997	Bordo	5/663	A47G 9/0292
6076212	12/1999	Feld	N/A	N/A
6708941	12/2003	Bowen et al.	N/A	N/A
6848130	12/2004	Wilson	N/A	N/A
7086101	12/2005	Welch et al.	N/A	N/A
7904977	12/2010	Singh	N/A	N/A
2004/0049847	12/2003	Leoutsakos	N/A	N/A
2005/0278858	12/2004	Polevoy et al.	N/A	N/A
2006/0037146	12/2005	Heng	N/A	N/A
2007/0017034	12/2006	Creekmuir	N/A	N/A
2007/0090259	12/2006	Chen et al.	N/A	N/A
2007/0234479	12/2006	Warshaver	5/690	A47C 31/105
2007/0283668	12/2006	Oh	N/A	N/A
2008/0111043	12/2007	Chen et al.	N/A	N/A
2008/0172799	12/2007	Constantinescu et al.	N/A	N/A
2009/0200445	12/2008	Benn	N/A	N/A
2009/0239005	12/2008	Hawkins et al.	N/A	N/A
2010/0192299	12/2009	Schermel et al.	N/A	N/A
2010/0287707	12/2009	Beard et al.	N/A	N/A

2011/0127892	12/2010	Joachim Meyer	248/345.1	A47B 95/043
2011/0219540	12/2010	Polevoy et al.	N/A	N/A
2012/0066835	12/2011	Kelly	5/493	A47G 9/0292
2013/0025051	12/2012	Syrowitz et al.	N/A	N/A
2013/0117932	12/2012	Stewart	5/400	A47C 19/025
2015/0305495	12/2014	Tsai	N/A	N/A
2016/0174709	12/2015	Ustach et al.	N/A	N/A
2016/0235192	12/2015	Kramer et al.	N/A	N/A
2018/0014660	12/2017	Iwata et al.	N/A	N/A
2018/0035821	12/2017	Bass-Conn	N/A	N/A
2018/0049558	12/2017	Jurcenko	N/A	N/A
2018/0125253	12/2017	Choi	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2976467	12/2011	FR	A47C 27/086

OTHER PUBLICATIONS

FR-2976467-A1 Eng translation (Year: 2012). cited by examiner

Primary Examiner: Mikowski; Justin C

Assistant Examiner: Bailey; Amanda L

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of application Ser. No. 15/173,857, filed Jun. 6, 2016, which claims the benefit of Provisional Application No. 62/230,437, filed Jun. 6, 2015, the disclosures of which are hereby incorporated by reference in their entirety.

FIELD OF THE PRESENT DISCLOSURE

(1) This disclosure relates generally to bedroom furniture and bedding, and more particularly to a protective, highly padded/cushioned, lightweight, portable, collapsible, affordable, and aesthetically pleasing bed finishing frame apparatus.

BACKGROUND OF THE RELATED ART

(2) The most classic style bed frames include a headboard and a footboard connected by rail boards and various cross members forming a structure to support a box spring, sometime called a foundation, a mattress. (For the purposes of this document “box spring” and “foundation” have the same definition meaning and the term “box spring” will be used for the remainder of this document.) While this style of bed frame is often desired, many individuals choose other options for a variety reasons. One of the most common reasons is safety. Classic style bed frames are often made of hard wood, metal, or some other structurally rigid material and often feature many unforgiving exposed edges, corners, and connective hardware upon which one could accidentally injure themselves.

(3) Whether it be by accidentally kicking the leg of the footboard in the middle of the night while sleepily walking past the bed or banging or scraping one's shin against the rail board or exposed connective hardware when attempting to enter bed too quickly, almost everybody who has ever owned a classic style bed frame has accidentally injured themselves at one point or another and understands the unpleasantness of that experience. This is a particular concern for individuals that

are accident prone, bruise easily, or have limited coordination.

(4) The risk of injury from a classic style bed frame is also significant for children, both young and old. Children typically play on their bed and risk losing their balance or falling off and hitting or bumping themselves against a traditional rigid hard wood or metal bed frame. This is also true for the parents' own bed when children are in the house. Small children tend to be less coordinated and have a knack for injuring themselves in numerous and unpredictable ways, and older children tend to be more coordinated but are also more energetic and play more aggressively.

(5) Some classic style bed frame designs have attempted to mitigate the risk of injury by including light padding along the head, foot and/or rail boards, however, beneath the thin padding there is always a very hard, rigid structural material that can prove to be painful if unintentionally impacted with enough force because the classic style bed frame is a load bearing structure and must be constructed from rigid materials.

(6) There are other reasons individuals avoid the classic style bed frame as well. Such reasons include their typical weight and the assembly labor often required. Classic style bed frames are frequently made from substantial materials and require a fair amount of assembly effort, often times requiring tools, screws, bolts, and anchors. This also means that they must be disassembled to be moved. This process can be particularly burdensome for individuals who find themselves moving frequently, which is increasingly common in today's modern urban lifestyle. What's more, apart from the hassle of the assembly and disassembly process, classic style beds often do not break down into very small component parts making transportation during moves particularly awkward and burdensome, whether it be to another room in the same house or building or across town.

(7) One common alternative is to use a box spring and mattress supported only by a simple collapsible metal frame with legs or casters. In some cases, a decorative headboard is attached to the metal frame to create the partial impression of a classic style bed, but it is not required as the metal frame typically provides all the structural support necessary for the box spring and mattress. A simple metal frame is often less expensive than a classic style bed frame and often requires considerably less effort to assemble and disassemble and may not even require tools. It also weighs much less than a classic style bed which makes portability more convenient.

(8) One major drawback of using only a simple metal frame is that they are not particularly attractive, and without rail boards there is nothing to obscure the box springs, which leaves the bed looking very unfinished and not aesthetically pleasing. Further, collapsible metal frames are very exposed, hard, and very uncomfortable if kicked or accidentally contacted otherwise. Likewise, the sides, corners, and edges of the box springs are not particularly soft may not be pleasant to contact unintentionally. Some individuals try to aesthetically obscure the bed's box spring and metal frame with a bed skirt, however, a bed skirt only obscures injury hazards, it does nothing to minimize them, and by obscuring injury hazards from view, bed skirts may even make injuries more likely. There exists a need for an aesthetically pleasing bed frame finishing option that also provides protective benefits.

(9) Other individuals choose to forego using a bed frame all together and either place a box spring and mattress on a platform or directly on the ground. This option is usually chosen for its low cost and simplicity, however, this option lacks an aesthetically finished appearance. There exists a need for an aesthetically finished option that does not add significant cost or undue complexity.

(10) The present disclosure distinguishes over the related art providing heretofore unknown advantages as described in the following summary.

BRIEF SUMMARY OF THE INVENTION

(11) The present disclosure describes a highly padded and protective bed finishing frame apparatus designed to fit snugly over a box spring as a contour sheet that supports strategically placed padding situated in pocket chambers located along at least three of the four vertical sides of the box spring thereby creating an aesthetically pleasing and highly protective barrier around the external perimeter of the bed.

(12) The padding provides the primary function of reducing or eliminating bumps, scrapes and/or stubbed toes that commonly result from getting in and out and moving around classic style bed frames that constructed from hard wood or metal. By providing a large, generous, soft protective layer around the box spring, the present disclosure generously covers any unforgiving edges and/or corners of the box spring and creates a cushioned/padded barrier far enough out from the perimeter of the box spring that any metal frame, platform, or other structure used to support the box spring that would otherwise present a toe stubbing hazard is sufficiently recessed and out of reach.

(13) As a secondary benefit the present disclosure creates a very stylish and finished looking frame around the bed whether the mattress is situated on a box spring that is elevated by a simple metal frame, platform, or other structure, or is situated directly on the floor.

(14) Further benefits include the fact that the presently described apparatus is collapsible and requires no assembly and can be easily folded into a relatively lightweight, reasonably sized box and shipped or transported, either by a purveyor after purchase or by its owner when moving, and then removed from the box and installed simply by skipping the device over the box spring without any tools or hassle.

(15) For example of portability, one embodiment can be collapsed and placed into a box of Dimensions 35" L.times.20" W.times.12" H for all standard sized beds including but not limited to the following mattress and box spring sets: Twin: 39" W.times.75" L; Full: 54" W.times.75" L; Queen: 60" W.times.80" L; California King: 72" W.times.84" L; Eastern King: 76" W.times.80" L. A single apparatus in a box weighs between twelve and thirty pounds and fits inside a standard car for transportation. These sizes are offered for example and are not intended to be limiting or restrictive. Other embodiments may require varying box sizes, however, generally, the presently disclosed apparatus can be folded into a reasonable sized and lightweight box making its portability a life-friendly advantage.

(16) Regarding construction, most embodiments include a contour sheet that is sized Specifically to snugly slip over a particular sized box spring including the top and all four sides, at least three of which further include a pocket chamber sized to hold between one (1) and six (6) inches of padding along the entire length of the pocket chamber. A thickness of two and half (2.5) inches is often preferred in many style designs.

(17) The pocket chambers are substantially similar in size to the sides of the industry standard box springs that the particular apparatus is design to fit. The phrase "substantially similar" in reference to size makes allowance for the moderate variance necessary for style preferences and because the padding creates a large perimeter than the box spring and extends marginally further, and therefore, the pocket chamber must extend marginally further in length than the box spring. In many embodiments, the chamber pocket also extends marginally higher than the box spring as well to create the preferred stylistic appearance and ensure functional protection against injury by the hard upper edge of the box spring. These marginal differences all fall within the definition of substantially similar in size.

(18) In most embodiments, the padding can be added or removed through an internally accessible resealable aperture. Some embodiments may be manufactured with the padding permanently encapsulated, however, a resealable aperture is preferred because when a resealable aperture is included in the embodiment design the padding can be removed and the remaining portion of the apparatus may be washed, providing yet another life-friendly benefit.

(19) Different varieties of padding can be used, however, high density foam is an advantageous choice because of its protective nature and ability to take and hold a shape. Through the use of high density foam inserts, the padding can be shaped to add extra styling appeal to the apparatus. Two different preferred style shapes that have been discussed and illustrated in this specification are the "squared-style" and the "rounded-style." These terms refer to shape of the padding created by the shape of the high-density foam inserts.

(20) The squared-style is created by using rectangular cuboid shaped high-density foam inserts and

the rounded-style is created by using semicylinder shaped high-density foam inserts with the flat side facing inward toward the box spring when installed and the rounded edge facing outward away from the box spring when installed. For both of these two depicted styles, each terminal end of the high-density foam inserts may be shaped differently depending whether or not it will join the terminal end of another foam insert from another side of the box spring to form a corner. Each terminal end that is perpendicularly adjacent another is beveled at a forty-five (45) degree angle thereby forming a stylistically pleasing miter joint, whereas each terminal end that is not perpendicularly adjacent to another is cut straight forming a square terminal end. This is a style choice and can be adjusted accordingly as with the shape of the high density foam inserts. The presently disclosed apparatus can take on a wide variety of different stylistic embodiments. The styles illustrated are intended to be examples and are not intended to be limiting.

(21) This disclosure teaches certain benefits in construction and use which give rise to the objectives described below.

(22) A primary objective inherent in the above described method and apparatus is to provide advantages not taught by the prior art.

(23) Another objective is to provide a highly protective and aesthetically pleasing bed finishing frame that is relatively affordable.

(24) A further objective is to provide a highly protective and aesthetically pleasing bed finishing frame that requires no assembly.

(25) A still further objective is to provide as highly protective and aesthetically pleasing bed finishing frame that is lightweight, collapsible, and convenient to transport.

(26) A yet still further objective is to provide a highly protective and aesthetically pleasing bed finishing frame that is washable.

(27) Other features and advantages of the present invention will become apparent from the following more detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles and features of the presently described apparatus.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

(1) The accompanying drawings illustrate various exemplary implementations and are part of the specification. The illustrated implementations are proffered for purposes of example not for purposes of limitation. Illustrated elements will be designated by numbers. Once designated, an element will be identified by the identical number throughout. Illustrated in the accompanying drawing(s) is at least one of the best embodiments of the present disclosure. In such drawing(s):

(2) FIG. 1 is a perspective view of an exemplary rounded-style embodiment of the presently described apparatus;

(3) FIG. 2A is a perspective view of an exemplary embodiment of the presently described apparatus shown collapsed neatly in a relatively small box for shipping or transportation;

(4) FIG. 2B is a blown up view of an exemplary embodiment of the presently described apparatus depicting the apparatus being removed from a collapsed state in a relatively small box and unfolding it to a ready to install state without any assembly required;

(5) FIG. 3 is a perspective view of an exemplary rounded-style embodiment of the presently described apparatus shown installed over a box spring located directly on the floor and beneath a mattress and pillow;

(6) FIG. 4 is a perspective view of an exemplary rounded-style embodiment of the presently described apparatus shown installed over a box spring supported by a metal frame on casters and beneath a mattress and pillow, it also shows that the apparatus can be used with a decorative headboard;

- (7) FIG. 5 is a perspective view of an exemplary squared-style embodiment of the presently described apparatus shown installed over a box spring located directly on the floor and beneath a mattress and pillow;
- (8) FIG. 6 is a perspective view of an exemplary squared-style embodiment of the presently described apparatus shown installed over a box spring supported by a metal frame on castors and beneath a mattress and pillow with a decorative headboard;
- (9) FIG. 7 is an exploded bottom perspective view of an exemplary rounded-style embodiment illustrating the semicylinder shaped high density foam insert and the resealable insertion aperture;
- (10) FIG. 8 is an exploded bottom perspective view of an exemplary squared-style embodiment illustrating the rectangular cuboid shaped high density foam insert and the resealable insertion aperture;
- (11) FIG. 9 is an exploded perspective view of an exemplary round-style embodiment of the presently described apparatus shown installed over a box spring supported by a metal frame on casters and beneath a mattress;
- (12) FIG. 10 is an exploded perspective view of an exemplary rounded-style embodiment of the presently described apparatus shown installed over a box spring located directly on the floor beneath a mattress with a decorative headboard;
- (13) FIG. 11 is an exploded perspective view of an exemplary squared style embodiment of the presently described apparatus shown installed over a box spring located directly on the floor beneath a mattress;
- (14) FIG. 12 is a side-by-side comparison view of an exemplary round-style embodiment of the presently described apparatus shown installed over a box spring supported by a metal frame on casters and beneath a mattress with a decorative headboard and the most comparable prior art which is a mattress resting on a box spring, looking very unfinished;
- (15) FIG. 13 is a side-by-side comparison view of an exemplary squared-style embodiment of the presently described apparatus shown installed over a box spring located directly on the ground and the most comparable prior art which is a mattress resting on a box spring located directly on the ground looking very unfinished;
- (16) FIG. 14 is a breakout top view of a corner junction on an exemplary rounded-style embodiment of the presently described apparatus;
- (17) FIG. 15 is a breakout top view of a corner junction on an exemplary squared-style embodiment of the presently described apparatus;
- (18) FIG. 16 is a breakout perspective view of the straight cut end of the foam insert of an exemplary rounded-style embodiment of the presently described apparatus;
- (19) FIG. 17 is a breakout perspective view the straight cut end of the foam insert of an exemplary squared-style embodiment of the presently described apparatus;

DETAILED DESCRIPTION THE EXEMPLARY EMBODIMENT

(20) The above described drawing figures illustrate an exemplary embodiment of presently disclosed apparatus and its many features in at least one of its preferred, best mode embodiments, which is further defined in detail in the following description. Those having ordinary skill in the art may be able to make alterations and modifications to what is described herein without departing from its spirit and scope of the disclosure. Therefore, it must be understood that what is illustrated is set forth only for the purposes of example and that it should not be taken as a limitation in the scope of the present apparatus or its many features.

(21) Described now in detail is a protective, highly padded/cushioned, lightweight, collapsible, portable, affordable, and aesthetically pleasing bed finishing frame.

(22) FIG. 1 illustrates an exemplary rounded-style embodiment of the presently disclosed apparatus **100** fully expanded and ready to slip over a box spring to provide both physical protection in the form of the generous padding **110** along three sides and aesthetic finishing due to its unique and stylish design. The apparatus comprises a horizontal top **120** and four vertical sides forming a

contour sheet that fits snugly over a box spring.

(23) In the embodiment illustrated in FIG. 1, three of the four vertical sides contain pocket chambers capable of supporting padding. The aesthetically round shape of the rounded-style embodiment is created by both the shape of the pocket chamber as well as the shape of the internal padding itself. The illustration also shows a small vertical rise **180** between the beginning of the curvature of the horizontal top **120** and the curvature of the side **112**. The purpose of this rise **180** is both a functional one ensuring that padding protects individuals from the hard upper edge of the box spring and stylistic providing the appropriate finishing appearance.

(24) Through similar shading, FIG. 1 also illustrates that the trim **130** along the outside of the horizontal top **120** is of the same fabric variety and color of the vertical sides for aesthetic continuity. Whereas the center of the horizontal top **120** can be another color or quality of fabric.

(25) FIG. 2A is an illustration of the compact manner in which the presently disclosed apparatus can be neatly collapsed **140** into a reasonably sized box. This allows both purveyors the ability to ship the product via standard parcel carriers and for owners to pack and move the apparatus without excessive stress or strain.

(26) FIG. 2B illustrates an exploded view of the presently disclosed apparatus being removed from a reasonable sized box neatly collapsed **140** and expanded into a fully assembled apparatus ready for installation **100**. There are no tools or assembly steps required between opening the box in which the apparatus is shipped, removal, expansion and installation.

(27) FIG. 3 illustrates the rounded-style embodiment of the presently disclosed apparatus **100** installed on a box spring that is resting on the floor and supporting a mattress. This illustration depicts the aesthetically finished look that the presently disclosed apparatus created even with a simple box spring and mattress resting on the floor without a bedframe. FIG. 3 also depicts the visually seamless transition that is assisted by the small riser **180** identified in FIG. 1.

(28) FIG. 4 is an illustration of the same rounded-style embodiment of the presently disclosed apparatus **100** installed on a box spring that is resting on a simple metal frame on casters with a stylistic headboard. The metal frame raises the apparatus off the floor compared to the illustration in FIG. 3 creating a gap between the curved vertical side **114** and the floor, however, because the curved, vertical side **114** protrudes outward from the assembled bed, the risk of accidentally kicking a caster while walking by the bed is greatly reduced.

(29) FIG. 5 is an illustration of the squared-style embodiment of the presently disclosed apparatus **100** installed over a box spring that is resting directly on the floor. Very similar to the rounded-style embodiment, the squared-style embodiment both creates an aesthetically pleasing finish on the box spring-mattress assembly and provides a generously cushioned protective barrier **150** between the unpleasantly hard edges of the box spring and the individual.

(30) Likewise, FIG. 6 depicts the squared-style version of the presently disclosed apparatus **100** installed on a box spring that is supported by a simple metal frame on casters. Again, as with the rounded-style embodiment **100**, FIG. 6 illustrates how the riser depicted **180** assists in the seamless integration between the box spring and mattress.

(31) FIG. 7 is a bottom view a rounded-style embodiment illustrating that the rounded shape **116** is created in part by the semicylinder shaped high density foam inserts **160**. High density foam inserts **160** are a preferred form of padding because it is very protective and is shapeable. It also holds its shape well over time. In other embodiments, shapeless padding such as cotton may be used. In such embodiments, the external shape of the apparatus may be determined more by the shape of the pocket chamber than by the shape of the padding.

(32) FIG. 7 also illustrates that the padding **160** can be removed through a zipper **170** along the internal side. This is an important feature because it allows an individual to remove the padding **160** and wash the apparatus. While not all embodiments feature zippers **170**, most embodiments feature a resealable aperture **170** of some variety. Embodiment with such a feature must be washed more carefully by hand without removing the padding.

(33) FIG. 7 also depicts the vertical side **170** that does not include a pocket chamber. Vertical sides **170** that do not include a pocket chamber are important because they assist the apparatus fit snugly on the box spring. The preferred embodiment of the presently disclosed apparatus **100** include three chamber pockets, however, some embodiments include chamber pockets in all four vertical sides or in less than three vertical sides.

(34) FIG. 8 illustrates a bottom view of a squared-style embodiment and the rectangular cuboidal high-density foam inserts **160** that assist in creating the squared appearance **150**. FIG. 8 and FIG. 7 also illustrate the forty-five degree beveled terminal ends of the foam inserts that join to form a ninety degree miter joint. In embodiments in which the padding **160** is shapeless soft padding such defined ninety degree corners are more difficult to achieve.

(35) FIG. 9 illustrates an exploded view of a rounded-style embodiment of the presently disclosed apparatus **100** and a box spring supported by a simple metal frame on casters with a decorative headboard. It is very apparent from the exploded view that the metal frame on casters is a significant toe stubbing risk and is not aesthetically attractive at all.

(36) Similarly, FIG. 10 and FIG. 11 illustrate exploded views of a rounded-style and a squared style embodiment of the presently disclosed apparatus, respectively, being placed over a box spring that are located directly on the floor showing both the ease of installment and the relative protection and aesthetic style the presently disclosed apparatus **100** provides.

(37) FIG. 12 and FIG. 13 provides a side-by-side comparisons of a round-style embodiment **100** on a box spring supported by a metal frame and a squared-style embodiment **100** on a box spring situated on the floor, each next to the comparable prior art. Such a side-by-side comparison demonstrate the vast difference in aesthetic finish the presently disclosed apparatus provides of the prior art.

(38) FIGS. 14 and 15 illustrate breakaway close up views of the rounded-style and squared-style corners, respectively. The clean lines and well defined corners are made possible by the beveled terminal ends of the foam inserts.

(39) FIGS. 16 and 17 illustrate breakaway close up views of the straight cut ends of the foam inserts **160** when the padded side is perpendicularly adjacent as non-padded side. These breakaway view also depict the small riser **180** between the vertical side and the pocket chamber that exist for both stylistic and protective functional reasons.

(40) The enablements described in detail above are considered novel over the prior art of record and are considered critical to the operation of at least one aspect of the apparatus and its method of use, and to the achievement of the above-described objectives. The words used in this specification to describe the instant embodiments are to be understood not only in the sense of their commonly defined meanings, but to include by special definition in this specification: structure, material, or acts beyond the scope of the commonly defined meanings. Thus, if an element can be understood in the context of this specification as including more than one meaning, then its use must be understood as being generic to all possible meanings supported by the specification and by the word(s) describing the element.

(41) The definitions of the words or drawing elements described herein are meant to include not only the combination of elements, which are literally set forth, but all equivalent structures, materials or arts for performing substantially the same function in substantially the same way to obtain substantially the same result. In this sense it is therefore contemplated that an equivalent substitution of two or more elements may be made for any one of the elements described and its various embodiments or that a single element may be substituted for two or more elements in a claim.

(42) Changes from the claimed subject matter as viewed by a person with ordinary skill in the art, now known or later devised, are expressly contemplated as being equivalents within the scope intended and its various embodiments. Therefore, substitutions, now or later known to one with ordinary skill in the art, are defined to be within the scope of the defined elements. This disclosure

is thus meant to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, what can be obviously substituted, and also what incorporates the essential ideas.

(43) The scope of this description is to be interpreted only in conjunction with the appended claims and it is made clear, here, that each named inventor believes that the claimed subject matter is what is intended to be patented.

Claims

1. A contour sheet that fits over a top side of a box spring comprising: a top sheet portion configured to extend across a top portion of the box spring; and a plurality of vertical side sheet portions configured to extend, from a perimeter of the top sheet portion, in a perpendicular direction to surround the box spring, wherein the plurality of vertical side sheet portions includes three vertical side sheet portions extending in the perpendicular directions from different sides of the top sheet portion, the three vertical side sheet portions including respective pocket chambers for retaining respective volumes of padding, each pocket chamber extending a respective distance of a respective one of the three vertical side sheet portions, wherein the plurality of vertical side sheet portions includes a fourth vertical side sheet portion that does not include a pocket chamber, wherein each pocket chamber is accessible via an opening on a side of the pocket chamber proximate to the box spring to enable removal of the respective volume of padding through the opening, and at least one vertical exterior edge of the box spring is entirely covered by at least one of the respective volumes of padding where two sides of the box spring meet when the top sheet portion is positioned on the top portion of the box spring.
2. The contour sheet of claim 1, wherein: each of the respective volumes of padding has a first side adjacent to a side of the top sheet portion, one of the respective volumes of padding has terminal ends that are beveled at forty-five degrees from the first side, and two of the respective volumes of padding have a first terminal end that is beveled at forty-five degrees from the first side and second terminal ends that are perpendicular to the first side.
3. The contour sheet of claim 1, further comprising a trim around outer edges of the top sheet portion.
4. The contour sheet of claim 3, wherein the trim extends from the outer edges of the top sheet portion from the three vertical side sheet portions.
5. The contour sheet of claim 3, wherein the trim is a different material or a different color from the top sheet portion.
6. The contour sheet of claim 3, wherein a color of the trim matches a color of the plurality of vertical side sheet portions.
7. The contour sheet of claim 3, wherein a material of the trim matches a material of the plurality of vertical side sheet portions.
8. The contour sheet of claim 1, wherein each of the three vertical side sheet portions having the pocket chambers includes a rise that extends in a direction opposite to the perpendicular direction in which plurality of vertical side sheet portions extend.
9. A contour sheet that fits over a top side of a box spring comprising: a first portion configured to extend across a top portion of the box spring; and vertical side sheet portions configured to extend, from a perimeter of the first portion, in a perpendicular direction, to surround the box spring, wherein each of three vertical side sheet portions of the vertical side sheet portions includes a pocket chamber extending a respective distance of a respective vertical side sheet portion of the three vertical side sheet portions, and a fourth vertical side sheet portion of the vertical side sheet portions does not include a pocket chamber, wherein the pocket chambers retaining respective volumes of padding, wherein each pocket chamber is accessible via an opening on a side of the pocket chamber proximate to the box spring to enable removal of the respective volume of padding

through the opening, and wherein at least one of the volumes of padding fully covers at least one vertical exterior edge of the box spring where two sides of the box spring meet when the first portion is positioned on the top portion of the box spring.

10. The contour sheet of claim 9, wherein the pocket chamber for each of the three vertical side sheet portions extends through each of the three vertical side sheet portions.

11. The contour sheet of claim 10, wherein each volume of padding corresponds to a respective one of the three vertical side sheet portions.

12. The contour sheet of claim 11, wherein: each volume has a first side adjacent to a side of the first portion, one of the respective volumes of padding has terminal ends that are beveled at forty-five degrees from the first side, and two of the respective volumes of padding have a first terminal end that is beveled at forty-five degrees from the first side and second terminal ends that are perpendicular to the first side.

13. The contour sheet of claim 9, further comprising a trim around outer edges of the first portion.

14. The contour sheet of claim 13, wherein the trim extends from the outer edges of the first portion from the three vertical side sheet portions.

15. The contour sheet of claim 13, wherein the trim is a different material or a different color from the first portion.

16. The contour sheet of claim 13, wherein a color and a material of the trim matches a color and a material of the vertical side sheet portions.

17. The contour sheet of claim 9, wherein the three vertical side sheet portions having the pocket chambers includes a rise that extends in a direction opposite to the perpendicular direction in which the vertical side sheet portions extend.
