

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12398676
B2
August 26, 2025
Anderson; Corey D. et al.

Tongue joint including mating channel for cooling

Abstract

A gas turbine engine including a core having a compressor section fluidly connected to a combustor via a primary flowpath and a turbine section connected to the combustor via the core flow path. An assembly is disposed within the gas turbine engine and includes a first part connected to a second part via a radial stack joint. The first part includes a radially inward facing surface contacting a corresponding radially outward facing surface of the second part. A fastener protrudes through the first part and the second part and is configured to maintain the relative positions of the first part and the second part. A channel is disposed on at least one of the radially inward facing surfaces and is positioned between the fastener and a circumferential edge of the first part. The channel is connected to at least one cooling air source.

Inventors: Anderson; Corey D. (East Hartford, CT), Boucher; Edward (New Haven, CT), Dunnigan; Rebecca R. (Sturbridge, MA), Broulidakis; Nicholas (Vernon, CT), Murakami; Matthew (West Hartford, CT), Brandt; Daniel R. (Somerville, MA), Kuc; Konrad (West Hartford, CT), Imlach; Victoria M. (Marlborough, CT), Kamath; Sushruth G. (Manchester, CT), Casares Rivas; Manuel A. (Hartford, CT), Leamon; Eric G. (Manchester, CT), Castles; Adam (West Hartford, CT), Cheung; Edmond (East Hampton, CT), Thole-Wilson; Kyra A. (West Hartford, CT), Johnson; Javier Nebero (South Glastonbury, CT)

Applicant: RTX Corporation (Farmington, CT)

Family ID: 1000008778564

Assignee: RTX Corporation (Farmington, CT)

Appl. No.: 18/428025

Filed: January 31, 2024

Prior Publication Data

Document Identifier
US 20240218830 A1

Publication Date
Jul. 04, 2024

Related U.S. Application Data

division parent-doc US 17967315 20221017 US 11933221 child-doc US 18428025
us-provisional-application US 63270099 20211021

Publication Classification

Int. Cl.: F02C7/18 (20060101); F23R3/60 (20060101)

U.S. Cl.:

CPC F02C7/18 (20130101); F23R3/60 (20130101); F05D2220/32 (20130101); F05D2230/60 (20130101); F05D2260/232 (20130101)

Field of Classification Search

CPC: F02C (7/18); F23R (3/60)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5350278	12/1993	Burge	N/A	N/A
5435139	12/1994	Pidcock et al.	N/A	N/A
6238712	12/2000	Nakashima	N/A	N/A
10815784	12/2019	Capolungo et al.	N/A	N/A
11041461	12/2020	Beach et al.	N/A	N/A
2002/0187046	12/2001	Beutin et al.	N/A	N/A
2004/0159107	12/2003	Sullivan et al.	N/A	N/A
2014/0360196	12/2013	Graves	60/753	F23R 3/002

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1099826	12/2004	EP	N/A
3523507	12/2019	EP	N/A
2973433	12/2011	FR	N/A

OTHER PUBLICATIONS

European Search Report for EP Application No. 22203152.8 dated Mar. 15, 2023. cited by applicant

Primary Examiner: Malatek; Katheryn A

Attorney, Agent or Firm: Carlson, Gaskey & Olds, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a divisional of U.S. application Ser. No. 17/967,315 filed Oct. 17, 2022, which claims priority to U.S. Provisional Patent Application No. 63/270,099 filed on Oct. 21, 2021.

TECHNICAL FIELD

(1) The present disclosure relates generally to tongue joints for gas turbine engine systems, and more specifically to tongue joints including a cooling channel positioned between matefaces.

BACKGROUND

(2) Gas turbine engines are used for commercial transportation, commercial shipping, military applications, as well as any number of additional aircraft uses. Common across the uses of gas turbine engines is the need to incorporate part to part interfaces where two parts abut each other and are joined to form the overall structure. Designs for part to part interfaces must ensure that the parts interface correctly, are able to be assembled using a practical assembly process, and are structurally sound. In addition, when part to part interfaces are used in or near the primary flowpath of the gas turbine engine or other heat source it can be important to ensure that the part to part interface provides or is provided sufficient cooling.

(3) Certain types of joints for part to part interfaces add complexity, requiring interfacing elements to have adequate stiffness to maintain the joint and to maintain part to part contact, while at the same time requiring the joint to provide sufficient strength to withstand vibrations and other stresses common within a gas turbine engine.

SUMMARY OF THE INVENTION

(4) In one exemplary embodiment a gas turbine engine includes a core including a compressor section fluidly connected to a combustor via a primary flowpath and a turbine section connected to the combustor via the core flow path, an assembly disposed within the gas turbine engine, the assembly including a first part connected to a second part via a radial stack joint, the first part including a radially inward facing surface contacting a corresponding radially outward facing surface of the second part, a fastener protruding through the first part and the second part and configured to maintain the relative positions of the first part and the second part, and a channel disposed on at least one of the radially inward facing surfaces and positioned between the fastener and a circumferential edge of the first part, the channel being connected to at least one cooling air source.

(5) In another example of the above described gas turbine engine the channel includes a radially outward intrusion into the radially inward facing surface of the first part.

(6) In another example of any of the above described gas turbine engines the channel includes a radially inward intrusion into the radially outward facing surface of the second part.

(7) In another example of any of the above described gas turbine engines the channel includes a radially outward intrusion into the radially inward facing surface of the first part and wherein the radially outward intrusion into the radially inward facing surface is at least partially overlapping the radially inward intrusion into the radially outward facing surface thereby creating a single channel.

(8) In another example of any of the above described gas turbine engines the channel includes at least one cooling hole extending from the channel.

(9) In another example of any of the above described gas turbine engines the least one cooling hole extends at least partially radially outward from the channel.

(10) Another example of any of the above described gas turbine engines further includes a leakage path between the first part and the second part, the leakage path connecting the channel to a portion of the first part connecting the leakage path to a radially outward facing surface of the first part.

(11) In another example of any of the above described gas turbine engines the channel includes at least a portion aligned with the circumferential edge of the first part.

(12) In another example of any of the above described gas turbine engines the channel includes at least a portion unaligned with the circumferential edge of the first part.

- (13) In one exemplary embodiment a radial stack joint connecting two parts including a flange extending outward from a first part and having a mating surface, a second part including a second mating surface, the second mating surface contacting the first mating surface, a fastener extending through the first part and the second part at the first and second mating surfaces, and a channel defined in at least one of the first mating surface and the second mating surface.
- (14) In another example of the above described radial stack joint connecting two parts the channel is connected to a surface of the second part via a plurality of cooling holes.
- (15) In another example of any of the above described radial stack joints connecting two parts the channel includes at least one groove intruding into one of the first mating surface and the second mating surface.
- (16) In another example of any of the above described radial stack joints connecting two parts the at least one groove includes a first groove intruding into the first surface and a second groove intruding into the second surface.
- (17) In another example of any of the above described radial stack joints connecting two parts the channel includes at least one corner.
- (18) In another example of any of the above described radial stack joints connecting two parts the channel is connected to at least a first cooling gas source.
- (19) In another example of any of the above described radial stack joints connecting two parts the channel is connected to at least two cooling gas sources.
- (20) An exemplary method for cooling a radial stack joint includes providing cooling air from at least a first cooling air source to a channel within a radial stack joint, the channel being defined on at least one mating surface of the radial stack joint.
- (21) In another example of the above described method for cooling a radial stack joint the radial stack joint joins at least two components, and wherein a non-mating surface of at least one of the at least two components is cooled via a plurality of cooling holes connected to the channel.
- (22) In another example of any of the above described methods for cooling a radial stack joint the channel vents cooling air through an interface gap of the radial stack joint.
- (23) In another example of any of the above described methods for cooling a radial stack joint the channel includes at least one corner.
- (24) These and other features of the present invention can be best understood from the following specification and drawings, the following of which is a brief description.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates a gas turbine engine including multiple components joined using the part to part interfaces illustrated in FIGS. 2A-7.
- (2) FIG. 2A illustrates a cross section of a first example tongue joint along line A-A in FIG. 2B.
- (3) FIG. 2B illustrates an outer diameter looking in view of the first example tongue joint.
- (4) FIG. 3 schematically illustrates a tongue joint including a cooling channel integral to a radially inner tongue.
- (5) FIG. 4 schematically illustrates a tongue joint including a cooling channel defined by two overlapping channels.
- (6) FIG. 5 schematically illustrates a tongue joint including an axially aligned channel (relative to an axis of the engine).
- (7) FIG. 6 schematically illustrates a tongue joint including a channel traversing multiple directions and including a corner.
- (8) FIG. 7 schematically illustrates a tongue joint including a channel providing air to corresponding cooling holes.

DETAILED DESCRIPTION

(9) FIG. 1 schematically illustrates a gas turbine engine **20**. The gas turbine engine **20** is disclosed herein as a two-spool turbopfan that generally incorporates a fan section **22**, a compressor section **24**, a combustor section **26** and a turbine section **28**. The fan section **22** drives air along a bypass flow path B in a bypass duct defined within a housing **15** such as a fan case or nacelle, and also drives air along a core flow path C for compression and communication into the combustor section **26** then expansion through the turbine section **28**. Although depicted as a two-spool turbopfan gas turbine engine in the disclosed non-limiting embodiment, it should be understood that the concepts described herein are not limited to use with two-spool turbopfans as the teachings may be applied to other types of turbine engines including three-spool architectures.

(10) The exemplary engine **20** generally includes a low speed spool **30** and a high speed spool **32** mounted for rotation about an engine central longitudinal axis A relative to an engine static structure **36** via several bearing systems **38**. It should be understood that various bearing systems **38** at various locations may alternatively or additionally be provided, and the location of bearing systems **38** may be varied as appropriate to the application.

(11) The low speed spool **30** generally includes an inner shaft **40** that interconnects, a first (or low) pressure compressor **44** and a first (or low) pressure turbine **46**. The inner shaft **40** is connected to the fan **42** through a speed change mechanism, which in exemplary gas turbine engine **20** is illustrated as a geared architecture **48** to drive a fan **42** at a lower speed than the low speed spool **30**. The high speed spool **32** includes an outer shaft **50** that interconnects a second (or high) pressure compressor **52** and a second (or high) pressure turbine **54**. A combustor **56** is arranged in exemplary gas turbine **20** between the high pressure compressor **52** and the high pressure turbine **54**. A mid-turbine frame **57** of the engine static structure **36** may be arranged generally between the high pressure turbine **54** and the low pressure turbine **46**. The mid-turbine frame **57** further supports bearing systems **38** in the turbine section **28**. The inner shaft **40** and the outer shaft **50** are concentric and rotate via bearing systems **38** about the engine central longitudinal axis A which is collinear with their longitudinal axes.

(12) The core airflow is compressed by the low pressure compressor **44** then the high pressure compressor **52**, mixed and burned with fuel in the combustor **56**, then expanded over the high pressure turbine **54** and low pressure turbine **46**. The mid-turbine frame **57** includes airfoils **59** which are in the core airflow path C. The turbines **46**, **54** rotationally drive the respective low speed spool **30** and high speed spool **32** in response to the expansion. It will be appreciated that each of the positions of the fan section **22**, compressor section **24**, combustor section **26**, turbine section **28**, and fan drive gear system **48** may be varied. For example, gear system **48** may be located aft of the low pressure compressor, or aft of the combustor section **26** or even aft of turbine section **28**, and fan **42** may be positioned forward or aft of the location of gear system **48**.

(13) The engine **20** in one example is a high-bypass geared aircraft engine. In a further example, the engine **20** bypass ratio is greater than about six (6), with an example embodiment being greater than about ten (10), the geared architecture **48** is an epicyclic gear train, such as a planetary gear system or other gear system, with a gear reduction ratio of greater than about 2.3 and the low pressure turbine **46** has a pressure ratio that is greater than about five. In one disclosed embodiment, the engine **20** bypass ratio is greater than about ten (10:1), the fan diameter is significantly larger than that of the low pressure compressor **44**, and the low pressure turbine **46** has a pressure ratio that is greater than about five 5:1. Low pressure turbine **46** pressure ratio is pressure measured prior to inlet of low pressure turbine **46** as related to the pressure at the outlet of the low pressure turbine **46** prior to an exhaust nozzle. The geared architecture **48** may be an epicycle gear train, such as a planetary gear system or other gear system, with a gear reduction ratio of greater than about 2.3:1 and less than about 5:1. It should be understood, however, that the above parameters are only exemplary of one embodiment of a geared architecture engine and that the present invention is applicable to other gas turbine engines including direct drive turbopfans.

(14) A significant amount of thrust is provided by the bypass flow B due to the high bypass ratio. The fan section **22** of the engine **20** is designed for a particular flight condition—typically cruise at about 0.8 Mach and about 35,000 feet (10,668 meters). The flight condition of 0.8 Mach and 35,000 ft (10,668 meters), with the engine at its best fuel consumption—also known as “bucket cruise Thrust Specific Fuel Consumption (‘TSFC’)”—is the industry standard parameter of lbf of fuel being burned divided by lbf of thrust the engine produces at that minimum point. “Low fan pressure ratio” is the pressure ratio across the fan blade alone, without a Fan Exit Guide Vane (“FEGV”) system. The low fan pressure ratio as disclosed herein according to one non-limiting embodiment is less than about 1.45. “Low corrected fan tip speed” is the actual fan tip speed in ft/sec divided by an industry standard temperature correction of $[(T_{\text{am}} / 518.7^\circ \text{R})]^{0.5}$. The “Low corrected fan tip speed” as disclosed herein according to one non-limiting embodiment is less than about 1150 ft/second (350.5 meters/second).

(15) The combustor **56** in one example includes a wall constructed of multiple combustor panels, each of the panels being connected to at least one of the other combustor panels or an underlying combustor structure via a part to part interface including a tongue groove joint. The tongue joint mates the two parts, allowing them to form a complete structure. One problem that can arise from a tongue joint, and particularly a tongue joint in a combustor area or other high heat areas of the engine, is the thermal behavior of the parts. The thickness of the tongue joint can insulate the outer portion of the joint. In addition, the joint can include a leakage path that allows part to part leakage flow to leak out in the localized area of the joint resulting in a local hotspot.

(16) Further, while described within the context of combustor panels for a commercial gas turbine engine, it is appreciated that the tongue joints described below can be suitable for use in any gas turbine engine, and for multiple parts within gas turbine engines including turbine exhaust case components, turbine vanes, blade outer air seals, combustor components and the like.

(17) FIG. 2A illustrates a cross section of a first example tongue joint **100** along line A-A in FIG. 2B. FIG. 2B illustrates an outer diameter looking in view of the first example tongue joint **100**. The tongue joint **100** joins two parts **110**, **120**. A tongue **122** protruding from an edge **124** of the second part **120** radially inward of the first part **110**. As is clear, the edge **124** extends for a first distance that is greater than a distance through which the tongue **122** extends. A bolt **130**, or other similar fastener, extends through a corresponding hole in the tongue **122** and the first part **110** and fastens the tongue joint **100**. While illustrated and described herein as a tongue extending radially underneath a second part, it should be understood that the cooling features and arrangements described herein can be applied to any radially stacked joint configuration (referred to as a radial stack), and is not limited to the specific tongue shape illustrated herein.

(18) The exemplary bolt **130** is fastened using a nut **132** and washer **134**, however another fixing technique able to withstand the heat, vibration, and other engine conditions could be used to similar effect. Similarly, other mechanical fastener styles aside from a bolt **130** could be used to join the parts depending on the needs of a particular system. While illustrated as a single fastener, it is appreciated that additional fasteners, such as adjacent bolts, or more distributed bolts could be used within a single tongue joint **100**.

(19) A channel **140** is defined between a radially outer surface **126** of the tongue **122** and a radially inner surface **112** of the first part **110**. The channel **140** provides a passageway through which air, or another cooling gas, can flow. The air then provides cooling to the first part **110**, the second part **120**, or both parts **110**, **120**. The cooling minimizes or eliminates local hotspots and improves the durability of the joint **100**, and thus the durability of the parts **110**, **120**.

(20) Air is fed to the channel **140** from at least one coolant source **150** that is connected to the channel **140** via a feed line **152**. In alternative examples, the air can be fed to the channel using ambient air radially inward of the second part **120**, with a pressure differential causing the air to flow into and through the channel **140**. In yet other examples, multiple air sources can be used to feed the channel **140**. In the example of FIGS. 2A and 2B, the cooling air enters one end of the

channel **140**, and exits the opposite end of the channel **140** radially inward of the first part **110**.

(21) In the example of FIGS. 2A and 2B the channel **140** is integral to the first part **110**. With continued reference to FIGS. 2A and 2B, and with like numerals indicating like elements, FIGS. 3 and 4 illustrate cross sections of similar joints, with the channel **140** being integral to the second part **120** (FIG. 3) and with the channel **140** being defined by two overlapping channels **140**, **140'** (FIG. 4). In the example of FIG. 4, the channels **140**, **140'** partially overlap, however alternatives can utilize channels **140**, **140'** that are fully aligned depending on the needs and tolerances of the parts **110**, **120**. As used herein, a channel **140**, **140'** being "integral to" a given part **110**, **120** refers to the channel being defined at least partially by a groove protruding radially into the part **110**, **120**. The specific depth and dimension of the channel can be customized, or tailored, to each given application to allow for sufficient airflow through the channel, while still maintaining a proper stiffness at the joint.

(22) Any given tongue joint can include multiple channels **140**, **140'** defined on the single joint **100**, and the channels **140** can be aligned or oriented to direct cooling air to particular hotspots of the tongue joint **100**. By way of example, FIG. 5 schematically illustrates a channel **440** that extends entirely axially along the tongue joint relative to an axis defined by the engine, thereby allowing the cooling air from cooling air source **450** to reach a region **402** of the joint that is particularly susceptible to thermal fatigue (i.e. a hot spot). In the example of FIG. 5, cooling air is provided to the channel **440** through an end **442** that is open to the ambient region radially inward of the first and second parts **410**, **420**. The cooling air travels through the channel **440** and exits through a leakage path **460** between the first and second parts **410**, **420**.

(23) In another example, illustrated in FIG. 6, the channel **540** includes a corner **546** that allows the channel to pass under or through multiple regions **502** that are susceptible to thermal damage. In the example of FIG. 6, each end **542**, **544** of the channel **540** receives cooling air from a source **550**, **550'**, and the air escapes the channel through the leakage pathway **560**. The corner **546** is illustrated as a 90 degree turn, however, alternate angles and/or arcs can be used to similar effect. In yet another variation of the example of FIG. 6, the channel **540** can be split into two straight channels **540** with each of the straight channels **540** passing through one of the regions **502**, and providing airflow through the leakage path **560**, but not requiring a connection at the corner **546**. In yet another example, the single channel **540** can receive cooling air from only a single end **542**, **544** and the cooling air can pass through to the opposite end **542**, **544** without exiting through the leakage path **560**.

(24) With continued reference to each of FIGS. 2A-6, and with like numerals indicating like elements, FIG. 7 schematically illustrates an example tongue joint **600** in which additional cooling holes **670** are positioned radially outward of the channel **640**. The additional cooling holes **640** can be used as the only outlet for the cooling air from cooling air source **650** in the channel **640** in examples where the channel **640** includes no overlap with the interface between the two parts **610**, **620**. Alternatively, the cooling holes **640** can provide additional cooling flow outlets when the leakage flow through the interface gap **660** is not large enough to provide sufficient airflow.

(25) While illustrated above as single tongue joints, it is appreciated that a joint between two parts can include multiple tongue joints, with each tongue joint utilizing or combining different characteristics of the configurations described above and illustrated in FIGS. 2A-7. Further, the configurations are illustrated individually to minimize the require illustration purely for ease of explanation and are not mutually exclusive examples. Furthermore it should be appreciated that the tongue joints illustrated and described above can be used with any tongue joint interface within the gas turbine engine and are not limited to the combustor panel example.

(26) It is further understood that any of the above described concepts can be used alone or in combination with any or all of the other above described concepts. Although an embodiment of this invention has been disclosed, a worker of ordinary skill in this art would recognize that certain

modifications would come within the scope of this invention. For that reason, the following claims should be studied to determine the true scope and content of this invention.

Claims

1. A method for cooling a radial stack joint comprising: providing a first part and a second part as a radially stacked joint, the first part including a radially inward facing surface contacting a corresponding radially outward facing surface of the second part over an extent, and one of the contacting radially inward facing surface and the radially outward facing surface being a tongue extending from an associated one of the first and second parts, with a fastener extending through the radially inward facing surface of the first part and the radially outward facing surface of the second part in the extent and configured to maintain the relative positions of the first and second part; and providing cooling air from at least a first cooling air source to a channel within the radial stack joint, the channel being defined on at least one mating surface of the radial stack joint; providing the channel between the tongue and another of the first and second parts; and wherein the channel is formed into the tongue.
 2. The method of claim 1, wherein a non-mating surface of at least one of the first and second parts is cooled via a plurality of cooling holes connected to the channel.
 3. The method of claim 1, wherein the channel vents the cooling air through an interface gap of the radial stack joint.
 4. The method of claim 1, wherein the channel includes at least one corner.
 5. The method of claim 1, wherein the first and second parts are panels in a gas turbine engine combustor.
 6. The method of claim 1, wherein the tongue protruding from an edge of the associated one of the first and second parts, with the edge extending for a first distance that is greater than a second distance through which the tongue extends.
 7. The method of claim 6, wherein the channel is between the fastener and the edge.
 8. A method for cooling a radial stack joint comprising: providing a first part and a second part as a radially stacked joint, the first part including a radially inward facing surface contacting a corresponding radially outward facing surface of the second part over an extent, and one of the contacting radially inward facing surface and the radially outward facing surface being a tongue extending from an associated one of the first and second parts, with a fastener extending through the radially inward facing surface of the first part and the radially outward facing surface of the second part in the extent and configured to maintain the relative positions of the first and second part; providing cooling air from at least a first cooling air source to a channel within the radial stack joint, the channel being defined on at least one mating surface of the radial stack joint; wherein the tongue protruding from an edge of the associated one of the first and second parts, with the edge extending for a first distance that is greater than a second distance through which the tongue extends; and wherein the channel is formed into the tongue.
 9. The method of claim 8, wherein the channel is between the fastener and the edge.
-