

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399329
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Gniadek; Jeffrey

Adapter system for multi-fiber mechanical transfer type ferrule

Abstract

Devices and methods for connecting optical fibers are provided. In some embodiments, connectors and adaptors for two-fiber mechanical transfer type ferrules are disclosed. In some embodiments, MT connectors, such as simplex, duplex, and quad micro-MT adaptors are disclosed. In some embodiments, MT adaptors, such as simplex, duplex, and quad adaptors are disclosed. In some embodiments, optical fiber cables that modularly coupled with at least one optical fiber connector, adaptor, and other optical fiber cable the cable is configured to provide a remote release from an adaptor receptacle.

Inventors:	Gniadek; Jeffrey (Oxford, ME)
Applicant:	SENKO Advanced Components, Inc. (Hudson, MA)
Family ID:	1000008778532
Assignee:	SENKO Advanced Components, Inc. (Hudson, MA)
Appl. No.:	18/054955
Filed:	November 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230071065 A1	Mar. 09, 2023

Related U.S. Application Data

continuation parent-doc US 17115975 20201209 US 11531169 child-doc US 18054955
continuation parent-doc US 16123381 20180906 US 10866371 20201215 child-doc US 17115975
continuation parent-doc US 16016577 20180623 US 10107972 20181023 child-doc US 16123381
continuation parent-doc US 15670161 20170807 US 10078187 20180918 child-doc US 16016577
continuation parent-doc US 15195405 20160628 US 9726830 20170808 child-doc US 15670161

Publication Classification

Int. Cl.: G02B6/38 (20060101)

U.S. Cl.:

CPC G02B6/3879 (20130101); G02B6/3821 (20130101); G02B6/3825 (20130101);
G02B6/3885 (20130101); G02B6/3893 (20130101);

Field of Classification Search

CPC: G02B (6/3879); G02B (6/3821); G02B (6/3825); G02B (6/3885); G02B (6/3893)

USPC: 385/59

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3733576	12/1972	Cooper	N/A	N/A
4645295	12/1986	Pronovost	N/A	N/A
5181267	12/1992	Gerace et al.	N/A	N/A
5222168	12/1992	Saito et al.	N/A	N/A
5390272	12/1994	Repta et al.	N/A	N/A
5528712	12/1995	Belenkiy et al.	N/A	N/A
5615293	12/1996	Sayegh	N/A	N/A
5673346	12/1996	Iwano et al.	N/A	N/A
5719977	12/1997	Lampert et al.	N/A	N/A
5915058	12/1998	Clairardin et al.	N/A	N/A
6146023	12/1999	Weigel	N/A	N/A
6149313	12/1999	Giebel et al.	N/A	N/A
6206581	12/2000	Driscoll et al.	N/A	N/A
6220762	12/2000	Kanai et al.	N/A	N/A
6224268	12/2000	Manning et al.	N/A	N/A
6305961	12/2000	Szilagyi et al.	N/A	N/A
6331079	12/2000	Grois et al.	N/A	N/A
6357931	12/2001	Shirakawa et al.	N/A	N/A
6371659	12/2001	Weigel	N/A	N/A
6386768	12/2001	Yoon et al.	N/A	N/A
6419399	12/2001	Loder et al.	N/A	N/A
6450695	12/2001	Matsumoto	N/A	N/A
6511230	12/2002	Connelly et al.	N/A	N/A
6568861	12/2002	Benner et al.	N/A	N/A
6575640	12/2002	Connelly et al.	N/A	N/A
6715928	12/2003	Matasek et al.	N/A	N/A
6764222	12/2003	Szilagyi et al.	N/A	N/A
6796715	12/2003	Chiu et al.	N/A	N/A
6918704	12/2004	Marrs et al.	N/A	N/A
6929406	12/2004	Amorim	N/A	N/A

7001081	12/2005	Cox et al.	N/A	N/A
7150567	12/2005	Luther et al.	N/A	N/A
7204644	12/2006	Barnes et al.	N/A	N/A
7284912	12/2006	Suzuki et al.	N/A	N/A
7347634	12/2007	Güenther et al.	N/A	N/A
7500790	12/2008	Erdman et al.	N/A	N/A
7628545	12/2008	Cody et al.	N/A	N/A
7677812	12/2009	Castagna et al.	N/A	N/A
8061906	12/2010	Nehler et al.	N/A	N/A
8406597	12/2012	Case	N/A	N/A
8465317	12/2012	Gniadek et al.	N/A	N/A
8556646	12/2012	Kappla et al.	N/A	N/A
8636424	12/2013	Kuffel et al.	N/A	N/A
8641293	12/2013	Lin et al.	N/A	N/A
8662760	12/2013	Cline et al.	N/A	N/A
8764308	12/2013	Irwin et al.	N/A	N/A
8834038	12/2013	Limbert et al.	N/A	N/A
8858089	12/2013	Bradley	N/A	N/A
9366829	12/2015	Czosnowski et al.	N/A	N/A
9411111	12/2015	Banal, Jr. et al.	N/A	N/A
9557495	12/2016	Raven et al.	N/A	N/A
9568689	12/2016	Nguyen et al.	N/A	N/A
9599778	12/2016	Wong et al.	N/A	N/A
9625658	12/2016	Lin	N/A	N/A
9684130	12/2016	Veatch et al.	N/A	N/A
10156683	12/2017	Manes et al.	N/A	N/A
10156684	12/2017	Nguyen et al.	N/A	N/A
10191230	12/2018	Wong et al.	N/A	N/A
10495823	12/2018	Good et al.	N/A	N/A
10890723	12/2020	Nguyen et al.	N/A	N/A
11061190	12/2020	Takano et al.	N/A	N/A
11181701	12/2020	Wong et al.	N/A	N/A
11307369	12/2021	Takano et al.	N/A	N/A
11333836	12/2021	Wong et al.	N/A	N/A
11340405	12/2021	Hendrick	N/A	N/A
11385415	12/2021	Nguyen et al.	N/A	N/A
11415760	12/2021	Takano et al.	N/A	N/A
11428875	12/2021	Nguyen et al.	N/A	N/A
11525965	12/2021	Childers et al.	N/A	N/A
11719893	12/2022	Higley et al.	N/A	N/A
11733466	12/2022	Higley et al.	N/A	N/A
11808994	12/2022	Higley et al.	N/A	N/A
11846813	12/2022	Childers et al.	N/A	N/A
11880075	12/2023	Nguyen et al.	N/A	N/A
11906794	12/2023	Higley et al.	N/A	N/A
2003/0118293	12/2002	Canace et al.	N/A	N/A
2003/0147230	12/2002	Hutermans et al.	N/A	N/A
2004/0043654	12/2003	Lee et al.	N/A	N/A
2004/0078961	12/2003	Chen et al.	N/A	N/A
2004/0109646	12/2003	Anderson et al.	N/A	N/A

2004/0247252	12/2003	Ehrenreich et al.	N/A	N/A
2005/0111796	12/2004	Matasek et al.	N/A	N/A
2005/0135752	12/2004	Kiani et al.	N/A	N/A
2005/0135753	12/2004	Eigenmann et al.	N/A	N/A
2005/0136722	12/2004	Cairns	N/A	N/A
2005/0281509	12/2004	Cox et al.	N/A	N/A
2008/0037938	12/2007	Kiani et al.	N/A	N/A
2008/0144303	12/2007	Ice	N/A	N/A
2008/0260333	12/2007	Roth	N/A	N/A
2009/0176401	12/2008	Gu	N/A	N/A
2010/0284656	12/2009	Morra et al.	N/A	N/A
2011/0019962	12/2010	Childers et al.	N/A	N/A
2011/0091159	12/2010	de Jong et al.	N/A	N/A
2011/0299814	12/2010	Nakagawa	N/A	N/A
2012/0057824	12/2011	Katoh	N/A	N/A
2012/0057826	12/2011	Katoh	N/A	N/A
2012/0082416	12/2011	Katoh	N/A	N/A
2012/0099822	12/2011	Kuffel	N/A	N/A
2012/0141072	12/2011	Katagiyama et al.	N/A	N/A
2012/0177326	12/2011	Peng et al.	N/A	N/A
2012/0213484	12/2011	Childers et al.	N/A	N/A
2013/0019423	12/2012	Srutkowski	N/A	N/A
2013/0094816	12/2012	Lin et al.	N/A	N/A
2013/0122745	12/2012	Soubh et al.	N/A	N/A
2013/0308916	12/2012	Buff	N/A	N/A
2013/0322825	12/2012	Cooke et al.	N/A	N/A
2013/0322826	12/2012	Henke et al.	N/A	N/A
2014/0064690	12/2013	Nhep	29/446	G02B 6/3825
2014/0241689	12/2013	Bradley et al.	N/A	N/A
2016/0041347	12/2015	Hodge	385/84	G02B 6/3885
2016/0094432	12/2015	Tingle	370/249	H04L 43/50
2016/0161680	12/2015	Nguyen et al.	N/A	N/A
2016/0178850	12/2015	Nhep	N/A	N/A
2016/0202431	12/2015	Hill et al.	N/A	N/A
2016/0238796	12/2015	Nguyen et al.	N/A	N/A
2016/0327756	12/2015	Raven et al.	N/A	N/A
2017/0153879	12/2016	George et al.	N/A	N/A
2017/0205587	12/2016	Chang et al.	N/A	N/A
2017/0205588	12/2016	Lee	N/A	N/A
2017/0227720	12/2016	Lin	N/A	N/A
2017/0343740	12/2016	Nguyen	N/A	N/A
2017/0351037	12/2016	Watanabe et al.	N/A	N/A
2017/0363818	12/2016	Suzic	N/A	N/A
2018/0106972	12/2017	Liu et al.	N/A	N/A
2018/0217340	12/2017	Wong et al.	N/A	N/A
2018/0224608	12/2017	Liu et al.	N/A	N/A
2018/0252872	12/2017	Chen	N/A	N/A
2019/0018201	12/2018	Takano et al.	N/A	N/A

2019/0018209	12/2018	Takano et al.	N/A	N/A
2019/0204513	12/2018	Davidson et al.	N/A	N/A
2019/0243072	12/2018	Takano et al.	N/A	N/A
2020/0285005	12/2019	Watanabe et al.	N/A	N/A
2021/0099229	12/2020	Cox et al.	N/A	N/A
2023/0213709	12/2022	Higley et al.	N/A	N/A
2023/0393351	12/2022	Childers et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201740886	12/2010	CN	N/A
2573482	12/1997	JP	N/A
2001305391	12/2000	JP	N/A
2004-354693	12/2003	JP	N/A
3886610	12/2006	JP	N/A
2012-53375	12/2011	JP	N/A
WO2012/174227	12/2011	WO	N/A
WO2013/100892	12/2012	WO	N/A
WO2014/057264	12/2013	WO	N/A
WO2015/027033	12/2014	WO	N/A
WO2017/127208	12/2016	WO	N/A
WO2018/042775	12/2017	WO	N/A
WO2019126337	12/2018	WO	N/A
WO2002/042818	12/2021	WO	N/A

OTHER PUBLICATIONS

International Searching Authority, International Search Report and Written Opinion, dated Mar. 24, 2017, Application No. PCT/US17/19901, 12 pages. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 11,340,413, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00118, U.S. Pat. No. 11,340,413, dated Dec. 21, 2023, 131pgs. cited by applicant
Fibermart, “Fiber Optic Connector Tutorial,” accessed on the internet at <https://www.fibermart.com/news/fiber-optic-connector-tutorial-a-848.html>, retrieved Dec. 21, 2023, 5pgs. cited by applicant

“Fiber Optic Rack Mount Enclosure, 3-Panel 1 RMS,” accessed on the internet at <https://www.computercablestore.com/fiber-optic-rack-mount-enclosure-3-panel-1-rms>, retrieved Dec. 21, 2023, 4pgs. cited by applicant

Liteon, “19-Inch Rack,” accessed on the internet at <https://liteon-cips.com/products/racks/19-inch-rack/>, retrieved Dec. 21, 2023, 5pgs. cited by applicant

Wagner et al., “SC-DC/SC-QC fiber optic connector,” *Opt. Eng.*, 37(12) 3129-3133, Dec. 1998. cited by applicant

Wenke, “Report On Fiber Optic Cables,” Optical Communication ONT, Hochschule Bremen, City University of Applied Sciences, pp. 1-30, Dec. 18, 2015. cited by applicant

Kant, “Data center evolution A tutorial on state of the art, issues, and challenges,” *Computer Networks*, 53:2939-2965, 2009. cited by applicant

Curran et al. “Basics of Fiber Optics,” Amphenol Fiber Systems International, pp. 1-13, dated no later than Jan. 11, 2024. cited by applicant

Nishimura et al., “High-Density Multi-Fiber Connectors for Optical Interconnection,” *Furukawa Review*, 34:13-16, Aug. 29, 2008. cited by applicant

Gurreri et al., “Multi-Fiber, MT Ferrule Endface Fiber Tip Displacement Model for Physical

Contact Interconnects,” 2006, pp. 1-12. cited by applicant

Declaration of James F. Brennan III, Ph.D. in Support of Petition for Inter Partes Review of U.S. Pat. No. 11,340,413, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00118, U.S. Pat. No. 11,340,413, dated Dec. 21, 2023, 294pgs. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 10,191,230, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00120, U.S. Pat. No. 10,191,230 B2, dated Dec. 22, 2023, 177pgs. cited by applicant

“HDI-45 connector,” accessed on the internet at https://en.wikipedia.org/wiki/HDI-45_connector, retrieved Dec. 22, 2023, 4pgs. cited by applicant

Google Data Centers gallery, accessed on the internet at <https://www.google.com/about/datacenters/gallery/>, retrieved Dec. 24, 2023, 83pgs. cited by applicant

Order Staying Case, *Senko Advanced Components, Inc. vs. US Conec Ltd.*, In the United States District Court for the District of Delaware, C.A. No. 23-083 (JPM), Jul. 6, 2023, 2pgs. cited by applicant

Kordz, “RJ45 CAT6 Field Termination Connector & Strain Relief,” Technical Data Sheet, kordz.com, 2019, 2pgs. cited by applicant

“Machine Design—An Integrated Approach,” 3rd Edition, Pearson College Div, Jan. 1, 2005, 93pgs. cited by applicant

Declaration of William Singhose, PH.D. in Support of Petition for Inter Partes Review of U.S. Pat. No. 10,191,230, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00120, U.S. Pat. No. 10,191,230 B2, dated Dec. 19, 2023, 342pgs. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 11,385,415, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00805, U.S. Pat. No. 11,385,415, dated Apr. 12, 2024, 207pgs. cited by applicant

Scheduling Order, *Senko Advanced Components, Inc. vs. US Conec Ltd.*, In the United States District Court for the District of Delaware, Case No. 1:23-cv-00083-JPM, Mar. 12, 2024, 9pgs. cited by applicant

Declaration of Edward Lurie, *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00805, U.S. Pat. No. 11,385,415, dated Apr. 11, 2024, 386pgs. cited by applicant

U.S. Appl. No. 61/789,499, filed Mar. 15, 2013, 32pgs. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 11,181,701, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00121, U.S. Pat. No. 11,181,701, dated Dec. 28, 2023, 112pgs. cited by applicant

“Maelstrom (ride),” Wikipedia, accessed on the internet at [https://en.wikipedia.org/wiki/Maelstrom_\(ride\)](https://en.wikipedia.org/wiki/Maelstrom_(ride)), retrieved Dec. 27, 2023, 3pgs. cited by applicant

Declaration of William Singhose, PH.D. in Support of Petition for Inter Partes Review of U.S. Pat. No. 11,181,701, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00121, U.S. Pat. No. 11,181,701, dated Dec. 27, 2023, 330pgs. cited by applicant

“Fiber Optic adapter/Coupler Tutorial,” accessed on the internet at <https://community.fs.com/article/fiber-optic-adaptercoupler-tutorial.html>, retrieved Dec. 21, 2023, 4pgs. cited by applicant

“What Is Optical Fiber Technology, and How Does It Work?,” accessed on the internet at <https://www.nai-group.com/optical-fiber-technology-how-it-works/>, retrieved Dec. 21, 2023, 8pgs. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 11,333,836, *US Conec Ltd.*, Petitioner v. *Senko*

Advanced Components, Inc., Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00117, U.S. Pat. No. 11,333,836, dated Dec. 30, 2023, 131pgs. cited by applicant
U.S. Appl. No. 62/546,920, filed Aug. 17, 2017, 76pgs. cited by applicant
U.S. Appl. No. 62/458,042, filed Feb. 13, 2017, 22pgs. cited by applicant
U.S. Appl. No. 62/463,898, filed Feb. 27, 2017, 87pgs. cited by applicant
U.S. Appl. No. 62/457,150, filed Feb. 9, 2017, 76pgs. cited by applicant
U.S. Appl. No. 62/463,901, filed Feb. 27, 2017, 87pgs. cited by applicant
Moxel Adaptor, dated no later than Apr. 22, 2024, 1pg. cited by applicant
Hendrick, "Interface Specification for MDC Receptacle," Feb. 6, 2020, 7pgs. cited by applicant
Declaration of William Singhose, PH.D. in Support of Petition for Inter Partes Review, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00117, U.S. Pat. No. 11,333,836, 225pgs. cited by applicant
Fiberroad, "QSFP-DD releases Interface Specification," accessed on the internet at <https://fiberroad.com/400g-qsfpdd-dco-standards/>, retrieved Dec. 30, 2023, 3pgs. cited by applicant
Cabling, "QSFP-DD MSA Group intros new specs, plus white paper," accessed on the internet at <https://www.cablinginstall.com/standards/article/14203903/qsfp-dd-msa-group-intros-new-specs-plus-white-paper>, retrieved Dec. 30, 2023, 3pgs. cited by applicant
Lightwave, "QSFP-DD MSA Group offers rev 6.0 specifications for QSFPDDS00, QSFP112," accessed on the internet at <https://www.lightwaveonline.com/optical-tech/transmission/article/14204021/qsfp-dd-msa-group-offers-rev-60-specifications-for-qsfp-dd800-qsfp112>, retrieved Dec. 30, 2023, 4pgs. cited by applicant
Jenkins et al., "Controlling Human Perception of Haptic Profiles Using Contextual Cues," 2023 IEEE World Haptics Conference (WHC), WHC 2023, Delft, Netherlands, Jul. 10-13, 2023, pp. 1-7. cited by applicant
Petition for Inter Partes Review of U.S. Pat. No. 11,415,760, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00119, U.S. Pat. No. 11,415,760, dated Jan. 3, 2024, 126pgs. cited by applicant
Patent Owner's Preliminary Response to the Petition for Inter Partes Review, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00119, U.S. Pat. No. 11,415,760, dated Apr. 18, 2024, 42pgs. cited by applicant
Assignment of U.S. Appl. No. 14/996,865, Takano, Gniadek to Senko Advanced Components, Inc., dated Jan. 15, 2016, 3pgs. cited by applicant
Assignment of U.S. Appl. No. 14/521,414, Wong, Ruffner to Senko Advanced Components, Inc., dated Apr. 23, 2015, 8pgs. cited by applicant
Declaration of Eric Pearson, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00119, U.S. Pat. No. 11,415,760, dated Apr. 17, 2024, 35pgs. cited by applicant
The New. Oxford American Dictionary, 2.SUP.nd .ed., Cover and Bibliographic pages, p. 1596
"Slickenslide—Slip," 2005, 4pgs. cited by applicant
Meriam Webster's Collegiate Dictionary, 11.SUP.th .ed., Cover and Bibliographic pages, p. 1172
"sleep-slider," 2012, 4pgs. cited by applicant
Webster's New International Dictionary of the English Language, 2.SUP.nd .ed., p. 2364, "Slick-Slight," 1947, 4pgs. cited by applicant
Satake, "The History of the MT and its Variations," accessed on the internet at IEEE Xplore, retrieved Oct. 30, 2023, 2pgs. cited by applicant
Nissin Kasei USA Corp., "MPO Connector Kit, Product Specifications," dated no later than Apr. 22, 2024, 9pgs. cited by applicant
Furukawa Electric, "MT Ferrules," accessed on the internet at <https://www.furukawa.co.jp/telecom/en/product/connector/product/mt.html#:~:text=MT ferrules>

are key components, wealth of technology and experience., retrieved Nov. 1, 2023, 4pgs. cited by applicant

OCC, “18 Port Rack Mount Fiber Enclosure,” accessed on the internet at <https://www.computercablestore.com/18-port-rack-mount-fiber-enclosure>, retrieved Dec. 18, 2023, 4pgs. cited by applicant

“Rack unit,” accessed on the internet https://en.wikipedia.org/wiki/Rack_unit, retrieved Oct. 24, 2023, 5pgs. cited by applicant

Declaration of James F. Brennan III, Ph.D. in Support of Petition for Inter Partes Review, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00119, U.S. Pat. No. 11,415,760, dated Jan. 3, 2024, 281pgs. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 11,061,190, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00122, U.S. Pat. No. 11,061,190, dated Jan. 4, 2024, 147pgs. cited by applicant

Patent Owner's Preliminary Response to the Petition for Inter Partes Review, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00122, U.S. Pat. No. 11,061,190, dated Mar. 27, 2024, 93pgs. cited by applicant

International Standard, “Fibre optic interconnecting devices and passive components—Fibre optic connector interfaces—Part 20: Type LC connector family,” Ed. 2.0, Apr. 2012, 30pgs. cited by applicant

Senko, “The Importance of Proper Crimping in Fiber Optic Assemblies,” Application Note, Rev. 01, pp. 1-9, Feb. 2021. cited by applicant

Buijs, Marcel, Fiber Optic Center, “Proper Crimping Techniques are Critical When Terminating Fiber Optic Connectors,” FOC Blogs, accessed on the internet <https://focenter.com/blog/proper-crimping-techniques-are-critical-when-terminating-fiber-optic-connectors>, retrieved Feb. 20, 2024, 7pgs. cited by applicant

Bulgin, “Terminating and crimping for fiber optics: methods and tips,” Nov. 25, 2019, accessed on the internet <https://community.element14.com/products/manufacturers/bulgin/b/blog/posts/terminating-and-crimping-for-fiber-optics-methods-and-tips>, retrieved Feb. 20, 2024, 4pgs. cited by applicant

Cambridge English Dictionary, “Meaning of elongate in English,” accessed on the internet <https://dictionary.cambridge.org/us/dictionary/english/elongate>, retrieved Feb. 20, 2024, 8pgs. cited by applicant

Declaration of Eric Pearson, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00122, U.S. Pat. No. 11,061,190, dated Mar. 26, 2024, 115pgs. cited by applicant

Leviton, “Application Note: Understanding Duplex Polarity,” 2020, 3pgs. cited by applicant

L-com Fiber Coupler, LC Duplex Bronze Sleeve, Low Profile (SKU_ FOA-802), dated no later than Apr. 22, 2024, 1pg. cited by applicant

Huber+Suhner LC-XD Connector, dated no later than Apr. 22, 2024, 2pgs. cited by applicant

PolyPhaser Fiber Optic Patch Cord Duplex Uniboot LC to LC Single Mode Fiber, OFNR, Yellow 3.0mm Jacket, 5m (SKU_ FPC2LCLC-USMRY30-05), dated no later than Apr. 22, 2024, 2pgs. cited by applicant

Universal LC Fiber Cable—Singlemode 9_125—Plenum 4M with Uniboot LC Connectors (SKU_ FODULC-SNG-4m), dated no later than Apr. 22, 2024, 10pgs. cited by applicant

Declaration of James F. Brennan III, Ph.D. in Support of Petition for Inter Partes Review of U.S. Pat. No. 11,061,190, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, U.S. Pat. No. 11,061,190, IPR2024-00122, dated Jan. 4, 2024, 271pgs. cited by applicant

Petition [1 of 2] for Inter Partes Review of U.S. Pat. No. 11,307,369 [Claims 1-22], *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00115, U.S. Pat. No. 11,307,369, dated Jan. 6, 2024, 121pgs. cited by applicant

Petition [2 of 2] for Inter Partes Review of U.S. Pat. No. 11,307,369 [Claims 23-40], *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00116, U.S. Pat. No. 11,307,369, dated Jan. 6, 2024, 126pgs. cited by applicant

Declaration of James F. Brennan III, Ph.D. in Support of Petition for Inter Partes Review of Claims 23-40 of U.S. Pat. No. 11,307,369, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00116, U.S. Pat. No. 11,307,369, dated Jan. 5, 2024, 257pgs. cited by applicant

Declaration of James F. Brennan III, Ph.D. in Support of Petition for Inter Partes Review of Claims 1-22 of U.S. Pat. No. 11,307,369, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00115, U.S. Pat. No. 11,307,369, dated Jan. 5, 2024, 256pgs. cited by applicant

Decision Denying Institution of Inter Partes Review, *US Conec Ltd. V. Senko Advanced Components Inc*, Before the Patent Trial and Appeal Board, Case IPR2024-00122, U.S. Pat. No. 11,061,190, Jun. 5, 2024, 23 pages. cited by applicant

White Paper: SC-RJ—Reliability for Every Category, 2008, 14 pages. cited by applicant

Petition for Post-Grant Review of U.S. Pat. No. 11,733,466, *Senko Advanced Components v. US Conec LTD*, Case PGR2024-00032, May 21, 2024, 242 pages. cited by applicant

Declaration of Edward Lurie, *Senko Advanced Components v. US Conec LTD*, Case PGR2024-00032, U.S. Pat. No. 11,733,466, May 19, 2024, 310 pages. cited by applicant

U.S. Appl. No. 62/532,710, filed Jul. 14, 2017, 79 pages. cited by applicant

QSFP-DD Hardware Specification, Sep. 19, 2017, 69 pages. cited by applicant

TIA/EI Standard, FOCIS 10 Fiber Optic Connector Intermateability Standard—Type LC, 2002, 38 pages. cited by applicant

CS Connector, May 20, 2024, 8 pages. cited by applicant

Exhibit I, *US Conec EX1007*, IPR2024-00116, U.S. Pat. No. 11,307,369, dated no later than Apr. 22, 2024; 4pgs. cited by applicant

BSI Standards Publication, Fibre Optic Interconnecting Devices and Components, Part 24, Jan. 2010, 32pgs. cited by applicant

INTL Standard 61754-4 ed1.2b Connector interfaces SC connector, Mar. 2002, 92pgs. cited by applicant

Declaration of Edward M. Cady, Jr., *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-01074, U.S. Pat. No. 11,880,075, dated Jun. 19, 2024, 258pgs. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 11,880,075, *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-01074, U.S. Pat. No. 11,880,075, dated Jun. 20, 2024, 159pgs. cited by applicant

Representative Claim Chart Showing Infringement of U.S. Pat. No. 11,880,075, Mar. 22, 2024, 67pgs. cited by applicant

Declaration of Edward Lurie, *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case PGR2024-00037, U.S. Pat. No. 11,906,794, dated Jun. 14, 2024, 311pgs. cited by applicant

Petition for Post-Grant Review of U.S. Pat. No. 11,906,794, *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case PGR2024-00037, U.S. Pat. No. 11,906,794, dated Jun. 20, 2024, 270pgs. cited by applicant

U.S. Appl. No. 62/649,539, filed Mar. 28, 2018, 209pgs. cited by applicant

U.S. Appl. No. 62/640,914, filed Mar. 9, 2018, 41pgs. cited by applicant

Senko Advanced Components, "The Importance of Proper Cleaving for Fiber Optic Connectors," Application Engineering Note, Feb. 2022, 10pgs. cited by applicant

Thorlabs, Guide to Connectorization and Polishing Optical Fibers, FN96A, Apr. 17, 2013, 36pgs. cited by applicant

Designerdata Polypropylene, accessed on the internet at [https://designerdata.nl/materials/plastics/thermo-plastics/polypropylene-\(cop.\)?cookie=YES](https://designerdata.nl/materials/plastics/thermo-plastics/polypropylene-(cop.)?cookie=YES), retrieved Apr. 28, 2024, 2pgs. cited by applicant

Typical Engineering Properties of Polypropylene, INEOS Olefins & Polymers USA, accessed on the internet at www.ineos-op.com, Apr. 2014, 2pgs. cited by applicant

The Engineering ToolBox: Polymers, accessed on the internet at https://www.engineeringtoolbox.com/polymer-properties-d_1222.html, retrieved Apr. 28, 2024, 9pgs. cited by applicant

Omnexus Plastics & Elastomers, accessed on the internet at <https://omnexus.specialchem.com/polymer-property/young-modulus>, retrieved Apr. 28, 2024, 14pgs. cited by applicant

U.S. Appl. No. 62/793,198, filed Jan. 16, 2019, 55pgs. cited by applicant

U.S. Appl. No. 62/653,706, filed Apr. 6, 2018, 19pgs. cited by applicant

Exhibit A-1—U.S. Pat. No. 11,733,466 Invalidity Claim Chart, Jun. 21, 2024, 55pgs. cited by applicant

Exhibit A-2—U.S. Pat. No. 11,733,466 Invalidity Claim Chart, Jun. 21, 2024, 43pgs. cited by applicant

Exhibit A-3—U.S. Pat. No. 11,733,466 Invalidity Claim Chart, Jun. 21, 2024, 49pgs. cited by applicant

Exhibit A-4—U.S. Pat. No. 11,733,466 Invalidity Claim Chart, Jun. 21, 2024, 37pgs. cited by applicant

Exhibit B-1—U.S. Pat. No. 11,808,994 Invalidity Claim Chart, Jun. 21, 2024, 38pgs. cited by applicant

Exhibit B-2—U.S. Pat. No. 11,808,994 Invalidity Claim Chart, Jun. 21, 2024, 64pgs. cited by applicant

Exhibit B-3—U.S. Pat. No. 11,808,994 Invalidity Claim Chart, Jun. 21, 2024, 68pgs. cited by applicant

Exhibit B-4—U.S. Pat. No. 11,808,994 Invalidity Claim Chart, Jun. 21, 2024, 53pgs. cited by applicant

Exhibit C-1—U.S. Pat. No. 11,906,794 Invalidity Claim Chart, Jun. 21, 2024, 105pgs. cited by applicant

Exhibit C-2—U.S. Pat. No. 11,906,794 Invalidity Claim Chart, Jun. 21, 2024, 98pgs. cited by applicant

Exhibit C-3—U.S. Pat. No. 11,906,794 Invalidity Claim Chart, Jun. 21, 2024, 105pgs. cited by applicant

Exhibit C-4—U.S. Pat. No. 11,906,794 Invalidity Claim Chart, Jun. 21, 2024, 33pgs. cited by applicant

Exhibit C-5—U.S. Pat. No. 11,906,794 Invalidity Claim Chart, Jun. 21, 2024, 39pgs. cited by applicant

Exhibit C-6—U.S. Pat. No. 11,906,794 Invalidity Claim Chart, Jun. 21, 2024, 22pgs. cited by applicant

Exhibit D-1—U.S. Pat. No. 11,880,075 Invalidity Claim Chart, Jun. 21, 2024, 90pgs. cited by applicant

Exhibit D-2—U.S. Pat. No. 11,880,075 Invalidity Claim Chart, Jun. 21, 2024, 91pgs. cited by applicant

Exhibit D-3—U.S. Pat. No. 11,880,075 Invalidity Claim Chart, Jun. 21, 2024, 86pgs. cited by applicant

Exhibit E-1—U.S. Pat. No. 11,385,415 Invalidity Claim Chart, Jun. 21, 2024, 50pgs. cited by applicant

Exhibit E-2—U.S. Pat. No. 11,385,415 Invalidity Claim Chart, Jun. 21, 2024, 25pgs. cited by applicant

Exhibit E-3—U.S. Pat. No. 11,385,415 Invalidity Claim Chart, Jun. 21, 2024, 57pgs. cited by applicant

Exhibit E-4—U.S. Pat. No. 11,385,415 Invalidity Claim Chart, Jun. 21, 2024, 57pgs. cited by applicant

Exhibit E-5—U.S. Pat. No. 11,385,415 Invalidity Claim Chart, Jun. 21, 2024, 8pgs. cited by applicant

Exhibit F-1—U.S. Pat. No. 10,495,823 Invalidity Claim Chart, Jun. 21, 2024, 29pgs. cited by applicant

Exhibit F-2—U.S. Pat. No. 10,495,823 Invalidity Claim Chart, Jun. 21, 2024, 26pgs. cited by applicant

Exhibit G—Other Validity Grounds (Non-Prior Art), Jun. 21, 2024, 54pgs. cited by applicant

Molex Incorporated, HBMt Motherboard Adapter, Doc. No. SD-106105-100MX, Oct. 31, 2005, 2pgs. cited by applicant

EX1027—Meriam Webster's Collegiate Dictionary, 11.SUP.th .ed., Cover and Bibliographic pages, p.551 “groove,” 2003, 4pgs. cited by applicant

EX1028—The Deposition of Witness, William Singhose, Ph.D, The United States International Trade Commission, Investigation No. 337-TA, Sep. 9, 2024', 82pgs. cited by applicant

EX1028—QSFP-DD, “Thermal Whitepaper: Enabling QSFP-001600 Ecosystem With Performance-Driven Thermal Innovations,” accessed on the internet at www.qsfp-dd.com/wp-content/uploads/, retrieved Aug. 6, 2024, 12pgs. cited by applicant

EX1029—Representative Domestic Industry Claim Chart for U.S. Pat. No. 11,385,415 by MMC Adapters, Aug. 19, 2024, 5pgs. cited by applicant

EX2002—Molex Adaptor, Jul. 24, 2024, 1pg. cited by applicant

EX2003—Encyclopedia.com, Definition of Frame, accessed on the internet at <https://www.encyclopedia.com/science-and-technology/computers-and-electrical-engineering/computers-and-computing/frame>, retrieved Jul. 23, 2024, 12pgs. cited by applicant

Exhibit 1002—Declaration of Edward Lurie, *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case PGR2024-00046, U.S. Pat. No. 11,808,994, dated Jul. 10, 2024, 362pgs. cited by applicant

Exhibit 1016—MOLEX—SFP-DD Hardware Specification for SFP Double Density 2x Pluggable Transceiver, Rev 1.0, Sep. 14, 2017, 50pgs. cited by applicant

Exhibit 1028—Tutorials Of Fiber Optic Products, “Fiber Optic Connector Polishing,” accessed on the internet at <https://www.fiber-optic-tutorial.com/category/network-solutions/fiber-optic-polishing>, retrieved Jun. 4, 2024, 6pgs. cited by applicant

Exhibit 1029—Fiber Cabling Solution, “UPC or APC—Which One to Choose?,” accessed on the internet at <https://www.fiber-optic-cable-sale.com/upc-or-apc-which-one-to-choose.html>, retrieved Jun. 4, 2024, 3pgs. cited by applicant

Exhibit 1030—Belden, “APC vs. UPC: What's the Difference?,” accessed on the internet at <https://www.belden.com/blogs/upc-or-apc#:~:text=The main difference between APC,curvature for better core alignment 1>, retrieved Jun. 4, 2024, 3pgs. cited by applicant

Exhibit 1035—QSFP-DD, “QSFP-DD MSA Group Announces New Hardware Specification,” accessed on the internet at www.qsfp-dd.com/qsfp-dd-msa-group-announces-new-hardware-specification/, retrieved Jul. 10, 2024, 2pgs. cited by applicant

Exhibit 1036—QSFP-DD, “QSFP-DD MSA Group Announces New Hardware Specification,”

Internet Archive WayBack Machine, accessed on the internet at www.qsfp-dd.com/qsfp-dd-msa-group-announces-new-hardware-specification/, retrieved Oct. 29, 2017, 2pgs. cited by applicant
Exhibit 1037—SFP-DD, SFP-DD MSA Releases Specification for High-Speed, High-Density Interface, accessed on the internet at sfp-dd.com/2017/09/sfp-dd-msa-releases-specification-for-high-speed-high-density-interface/, retrieved Jul. 10, 2024, 4pgs. cited by applicant
Exhibit 1038—SFP-DD, SFP-DD MSA Releases Specification for High-Speed, High-Density Interface, Internet Archive WayBack Machine, accessed on the internet at sfp-dd.com/2017/09/sfp-dd-msa-releases-specification-for-high-speed-high-density-interface/, retrieved Oct. 15, 2017, 3pgs. cited by applicant

Patent Owner's Preliminary Response Under 37 C.F.R. § 42.107(a), *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00805, U.S. Pat. No. 11,385,415, dated Jul. 24, 2024, 44pgs. cited by applicant
Petition For Post-Grant Review of U.S. Pat. No. 11,808,994, *Senko Advanced Components, Inc.*, Petitioner v. *US Conec Ltd.*, Patent Owner, Before the Patent Trial and Appeal Board, Case PGR2024-00046, U.S. Pat. No. 11,808,994, dated Jul. 23, 2024, 266pgs. cited by applicant
Paper 6, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00117, U.S. Pat. No. 11,333,836 B2, dated Jul. 9, 2024, 25pgs. cited by applicant

Paper 6, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00118, U.S. Pat. No. 11,340,413 B2, dated Jul. 9, 2024, 28pgs. cited by applicant

Paper 6, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00120, U.S. Pat. No. 10,191,230 C1, dated Jul. 9, 2024, 44pgs. cited by applicant

Paper 6, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00121, U.S. Pat. No. 11,181,701 B2, dated Jul. 9, 2024, 26pgs. cited by applicant

Paper 7, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00115, U.S. Pat. No. 11,307,369 B2, dated Jul. 9, 2024, 20pgs. cited by applicant

Paper 7, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00116, U.S. Pat. No. 11,307,369 B2, dated Jul. 9, 2024, 16pgs. cited by applicant

Petitioner's Reply to Preliminary Response to the Petition for Inter Partes Review, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00805, U.S. Pat. No. 11,385,415, dated Aug. 19, 2024, 10pgs. cited by applicant

Petitioner's Request for Rehearing of the Institution Decision, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00122, U.S. Pat. No. 11,061,190, dated Jul. 5, 2024, 19pgs. cited by applicant

Paper 9, Decision Granting Institution of Inter Partes Review 35 U.S.C. § 314, *US Conec Ltd.*, Petitioner v. *Senko Advanced Components, Inc.*, Patent Owner, Before the Patent Trial and Appeal Board, Case IPR2024-00119, U.S. Pat. No. 11,415,760 B2, dated Jul. 9, 2024, 41pgs. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/115,975 filed Dec. 9, 2020, which is a continuation of U.S. application Ser. No. 16/123,381, filed Sep. 6, 2018, now U.S. Pat. No. 10,866,371 issued on Dec. 15, 2020, which is a continuation of U.S. application Ser. No. 16/016,577 filed Jun. 23, 2018, now U.S. Pat. No. 10,107,972 issued on Oct. 23, 2018, a continuation of U.S. application Ser. No. 15/670,161 filed Aug. 7, 2017, now U.S. Pat. No. 10,078,187, issued on Sep. 18, 2018, which is a continuation of U.S. application Ser. No. 15/195,405 filed Jun. 28, 2016, now U.S. Pat. No. 9,726,830, issued on Aug. 8, 2017 and all are incorporated in their entireties.

FIELD OF THE INVENTION

(1) The present teaching relates generally to connectors and adaptors for two-fiber mechanical transfer type ferrules, and more specifically to micro connectors and adaptors, such as simplex, duplex and quad micro connectors and adaptors with remote release and two-fiber ferrules.

BACKGROUND

(2) The prevalence of the Internet has led to unprecedented growth in communication networks. Consumer demand for service and increased competition has caused network providers to continuously find ways to improve quality of service while reducing cost.

(3) Certain solutions have included the deployment of high-density network panels. These panels are designed to consolidate the increasing volume of interconnections necessary to support the fast-growing networks into a compacted space, thereby increasing quality of service and decreasing costs such as floor space and support overhead. High-density network panels may contain a large number of ports to accommodate the large number of connections often necessary to connect the network panels with the network switches or other network end terminals. The panels' ports are generally designed to mate with connectors that contain two fibers (herein referred to as a 2-fiber connector) where one fiber transmits data (Tx) and the other fiber receives data (Rx). It is common to have a number of 2-fiber connectors, such as six 2-fiber connectors, from the network panel combined together into a fan-out jumper. In this design, the 2-fiber connectors and their fibers couple through a fan-out block and into a single cable, such as a 12-fiber cable. A multi-fiber push-on (MPO) connector, such as a 12-fiber MPO connector, is usually mounted at the end of the single cable to connect to a transceiver located at the network switch or other network end terminal. The transceiver can then manage a large number of fibers and 2-fiber connectors using the fan-out jumper and connect to a large number of pores from the network panels. However, the design, the connector dimensions and the connector accessibility of the presently available fan-out jumpers have not been fully optimized for high-density network panels.

(4) Fan-out jumpers with 2-fiber Tx-Rx connectors may require individual ports for each Tx-Rx network connection; however, due to their design, they may create fiber management and maintenance issues for the operator that are challenging and undesirable. For instance, in a fan-out jumper with one 12-fiber MPO connector and six 2-fiber connectors, the MPO connector activates all 12 fibers as soon as it is plugged into the transceiver. However, this is convenient if there are six Tx-Rx ports that need service simultaneously on the network panel. This can cause some or all of the six Tx-Rx ports to become interrupted due to a malfunction with the MPO connector at the transceiver. Moreover, repairing the MPO connector will interrupt all 6 Tx-Rx ports as soon as the MPO connector is unplugged for troubleshooting, which may lead to an unnecessary interruption of services. Furthermore, if the network switch has 12-fiber MPO type transceivers and only one

network panel Tx-Rx port coupled to a 2-fiber jumper connector needs service, this results in five additional 2-fiber connectors that are “active” but not utilized from the cable jumper. The unused but active 2-fiber connectors then need to be stored along with some lengths of 2-fiber cables until a future need is realized, adding to the fiber management problems. Additionally, 2-fiber connectors from one 12-fiber MPO fan-out jumper may not be able to reach Tx-Rx ports on the network panel needing service, in which case another transceiver would need to be powered up and another 12-fiber MPO fan-out jumper would need to be added to the equipment racks. If the length of the 12-fiber MPO fan-out jumper was determined based on the Tx-Rx port farthest from the transceiver, then there would be excessively long 2-fiber connector cables to manage when nearby Tx-Rx ports are serviced, again adding to the problem of fiber management. It is most desired to manage or “dress” the cables in horizontal and vertical cable troughs and not crossover the equipment in diagonal “short-cuts”, as this causes equipment access and cable identification problems.

(5) Certain available ferrules and connectors may be designed to couple with fan-out jumper and high-density network panels but their dimensions are not optimized for 2-fiber applications. For instance, MPO connectors are commonly configured for 2 to 36 fiber ribbon cables and are therefore much bigger than what is needed for two fiber applications with the same fiber-to-fiber center distance of about 0.25 mm. MPO connectors are about 7.6 mm high, 12.4 mm wide, 25.7 mm long (without including the strain relief boot), and MPO ferrules have a frontal contact surface of about 2.5 mm high and 6.4 mm wide. In contrast, MT-RJ connectors are configured for cable with a smaller number of fiber ribbons, such as 1 to 4 fibers, but they are larger than what is needed for two-fiber applications. MT-RJ connectors are about 10 mm high, 9.2 mm wide, 20 mm long (without including the strain relief boot), and MT-RJ ferrules have a frontal contact surface of about 2.5 mm high and 4.4 mm wide. Also, LC and SC duplex connectors may be designed for 2-fiber applications but their overall dimensions are not optimized to address the high-density requirement of high-density network panels. LC duplex connectors are about 12.7 mm high, 12.8 mm wide, 27.3 mm long (without including the strain relief boot), and SC duplex connectors are about 9.3 mm high, 24.2 mm wide, 25.2 mm long (without including the strain relief boot).

(6) For 2-fiber jumper connectors coupled to fan-out jumpers and high-density network panels, adjacent connectors and cable assemblies may obstruct access to the individual release mechanisms at the Tx-Rx network panel port. Such physical obstructions may impede the ability of an operator to minimize the stresses applied to the cables and the connectors. For example, these stresses may be applied when the user reaches into a dense group of jumper connectors and pushes aside surrounding cables to access an individual connector release mechanism with his/her thumb and forefinger. Overstressing the cables and connectors may produce latent defects, compromise the integrity and/or reliability of the terminations, and potentially cause serious disruptions to network performance.

(7) While an operator may attempt to use a tool, such as a screwdriver, to reach into the dense group of 2-fiber jumper connectors and activate the release mechanism, the adjacent cables and connectors may obstruct the operator's line of sight, making it difficult to guide the tool to the release mechanism without pushing aside the surrounding cables. Moreover, even when the operator has a clear line of sight, guiding the tool to the release mechanism may be a time-consuming process. Thus, using a tool may not be effective at reducing support time and increasing the quality of service.

(8) Accordingly, there remains a critical need for a better designed fan-out jumper that meets the requirements of high-density network panels.

SUMMARY

(9) In one aspect, a connector is disclosed for two-fiber mechanical transfer type ferrule. The connector may comprise, for example and without limitation, at least one housing, a latch body, at least one latch spring, at least one ferrule, at least one ferrule spring, and a pull-tab. The connector

can be, for example and without limitation, a micro-mechanical transfer (micro-MT) type connector, and more specifically a simplex micro-MT connector, a duplex micro-MT connector, or a quad micro-MT connector.

(10) In some embodiments, the micro-MT connector contains at least one ferrule. The ferrule can be a micro-MT ferrule, and more specifically a male micro-MT ferrule or a female micro-MT ferrule. The male micro-MT ferrule and the female micro-MT ferrule have a contact surface with a height in a range of about 1.0 mm to about 2.4 mm, such as a height of about 2.0 mm, or a height of about 1.6 mm. The male micro-MT ferrule and the female micro-MT ferrule have a contact surface with a width in a range of about 2.4 mm to about 4.3 mm, such a width of about 4.0 mm or a width of about 3.6 mm.

(11) In some embodiments, the micro-MT connector is a simplex micro-MT connector comprising a housing defining a longitudinal passage therethrough. The simplex micro-MT connector comprises a latch body defining a longitudinal passage therethrough and being movably coupled to the housing. The simplex micro-MT connector comprises a latch spring defining a longitudinal passage therethrough and being movably coupled with the housing. The simplex micro-MT connector comprises one ferrule extending longitudinally from a first end to a second end, the ferrule disposed at least partially within the longitudinal passage of the housing with the first end protruding external to the longitudinal passage. The simplex micro-MT connector comprises a ferrule spring dispersed in the longitudinal passage of the housing and coupled to the ferrule.

(12) In some embodiments, the micro-MT connector is a simplex micro-MT connector having a height in a range of about 3.8 mm to about 7.5 mm, such a height of about 6.5 mm or a height of about 5.5 mm. The simplex micro-MT connector has a width in a range of about 6.4 mm to about 9.1 mm, such a width of about 8.8 mm or a width of about 8.5 mm. The simplex micro-MT connector has a length in a range of about 17.0 mm to about 25.1 mm, such a length of about 23.2 mm or a length of about 21.3 mm.

(13) In some embodiments, the micro-MT connector is a simplex micro-MT connector comprising a pull-tab. The pull-tab comprises a proximal end and a distal end spaced from the proximal end. The proximal end may include a latch hook uniquely shaped so as to engage with the unique profile of the latch body that is integral to the simplex micro-MT connector.

(14) In some embodiments, the micro-MT connector is a simplex micro-MT connector comprising a latch body and a latch spring. When the simplex micro-MT connector is coupled to an adaptor, the latch spring is not compressed and therefore not actuated. A latch hole from the housing and a latch hole from the latch body are disposed vertically, one above each other, to generate a large cavity where a latch from the adaptor can couple to fasten the connector to the adaptor. In contrast, when the simplex micro-MT connector is decoupled from an adaptor, the latch spring is compressed and therefore actuated. The latch hole from the housing and the latch hole from the latch body are not disposed vertically, one above each other, and do not generate a large enough cavity where the latch from the adaptor can couple to fasten the connector to the adaptor.

(15) In some embodiments, the micro-MT connector is a duplex micro-MT connector comprising a first housing and a second housing each defining a longitudinal passage therethrough from a proximal end to a distal end and including a latch hole designed to couple with a latch arm from an adaptor. The duplex micro-MT connector comprises a latch body defining a first longitudinal passage therethrough from a proximal end to a distal end spaced from the first end, a second longitudinal passage therethrough from a middle to the distal end spaced from the middle. The latch body is movably coupled with the housings wherein at least part of the housing is movably within at least the first longitudinal passage of the latch body. The duplex micro-MT connector comprises a latch spring defining a longitudinal passage therethrough and being movably coupled with the housing. The duplex micro-MT connector comprises a first ferrule and a second ferrule each extending longitudinally from a first end to a second end, the ferrule disposed at least partially within the longitudinal passage of the housing with the first end protruding external to the

longitudinal passage. The duplex micro-MT connector comprises a first ferrule spring and a second ferrule spring each dispersed in the longitudinal passage of the housing and coupled to the ferrule.

(16) In some embodiments, the micro-MT connector is a duplex micro-MT connector having a height in a range of about 7.8 mm to about 13.8 mm, such as a height of about 12.8 mm or a height of about 11.8 mm. The duplex micro-MT connector has a width in a range of about 6.4 mm to about 9.1 mm, such as a width of about 8.8 mm or a width of about 8.5 mm. The duplex micro-MT connector has a length in a range of about 19.4 mm to about 29.0 mm, such as a length of about 27.0 mm or a length of about 25.0 mm.

(17) In some embodiments, the micro-MT connector is a duplex micro-MT connector comprising a pull-tab. The pull-tab comprises a proximal end and a distal end spaced from the proximal end. The proximal end may include a first latch hook and a second latch hook uniquely shaped so as to engage with the unique profile of the latch body that is integral to the duplex micro-MT connector.

(18) In some embodiments, the micro-MT connector is a quad micro-MT connector comprising a first housing and a second housing and a third housing and a fourth housing each defining a longitudinal passage therethrough from a proximal end to a distal end and including a latch hole designed to couple with a latch arm from an adaptor. The quad micro-MT connector comprises a latch body defining a first longitudinal passage therethrough from a proximal end to a distal end, a second longitudinal passage therethrough from a middle to the distal end. The latch body is movably coupled with the housings wherein at least part of the housing is movably within at least the first longitudinal passage of the latch body. The quad micro-MT connector comprises a first latch spring and a second latch spring each defining a longitudinal passage therethrough and being movably coupled with the housing. The quad micro-MT connector comprises a first ferrule and a second ferrule and a third ferrule and a fourth ferrule each extending longitudinally from a first end to a second end, the ferrule disposed at least partially within the longitudinal passage of the housing with the first end protruding external to the longitudinal passage. The quad micro-MT connector comprises a first ferrule spring and second ferrule spring and a third ferrule spring and a fourth ferrule spring each dispersed in the longitudinal passage of the housing and coupled to the ferrule.

(19) In some embodiments, the micro-MT connector is a quad micro-MT connector having a height in a range of about 7.8 mm to about 13.8 mm, such as a height of about 12.8 mm or a height of about 11.8 mm. The quad micro-MT connector has a width in a range of about 12.8 mm to about 21.2 mm, such as a width of about 20.2 mm or a width of about 19.2 mm. The quad micro-MT connector has a length in a range of about 19.4 mm to about 29.0 mm, such as a length of about 27.0 mm or a length of about 25.0 mm.

(20) In some embodiments, the micro-MT connector is a quad micro-MT connector comprising a pull-tab. The pull tab comprises a proximal end and a distal end spaced from the proximal end. The proximal end may include a first latch hook and a second latch hook uniquely shaped so as to engage with the unique profile of the latch body that is integral to the quad micro-MT connector.

(21) In another aspect, an adaptor is disclosed for two-fiber mechanical transfer type ferrule. The adaptor may comprise, for example and without limitation, a housing and at least one latch hook arm. The adaptor can be, for example and without limitation, a micro-mechanical transfer (micro-MT) type adaptor, and more specifically a simplex micro-MT adaptor, a duplex micro-MT adaptor, or a quad micro-MT adaptor.

(22) In some embodiments, the micro-MT adaptor is a simplex micro-MT adaptor comprising a housing defining a longitudinal passage therethrough, the housing comprising at least one mounting tab, wherein a first wall, a second wall, a third wall, and a fourth wall, wherein the first wall and the third wall are opposite to each other, wherein the second wall and the fourth wall are opposite to each other, and wherein the second wall comprises at least one adaptor housing hole. The simplex micro-MT adaptor comprises a latch-hook arm defined by a first side, a second side, a first end, and a second end spaced from the first end, wherein the first end and the second end each comprise a first hook configured to couple with the connector, wherein one of the sides comprises a

second hook to couple with an adaptor housing hole.

(23) In some embodiments, the micro-MT adaptor is a simplex micro-MT adaptor, which may have a length in a range of about 22 mm to about 28 mm, such as a length of about 27 mm or a length of about 26 mm. The simplex micro-MT adaptor may have a height in a range of about 4 mm to about 10 mm, such as a height of about 9 mm or a height of about 8 mm. The simplex micro-MT adaptor may have a width in a range of about 7.2 mm to about 13.2 mm, such as a width of about 12.2 mm or a width of about 11.2 mm. The simplex micro-MT adaptor may have mounting handles and a height in a range of about 7 mm to about 13 mm, such as a height of about 12 mm or a height of about 11 mm.

(24) In some embodiments, the micro-MT adaptor is a duplex micro-MT adaptor comprising a housing defining a longitudinal passage therethrough, the housing comprising at least one mounting tab, wherein a first wall, a second wall, a third wall, and a fourth wall, wherein the first wall and the third wall are opposite to each other, wherein the second wall and the fourth wall are opposite to each other, and wherein the second wall comprises at least one adaptor housing hole. The duplex micro-MT adaptor comprises two latch-hook arms each defined by a first side, a second side, a first end, and a second end spaced from the first end, wherein the first end and the second end each comprise a first hook configured to couple with the connector, wherein one of the sides comprises a second hook to couple with an adaptor housing hole.

(25) In some embodiments, the micro-MT adaptor is a duplex micro-MT adaptor, which may have a length in a range of about 22 mm to about 28 mm, such as a length of about 27 mm or a length of about 26 mm. The duplex micro-MT adaptor may have a height in a range of about 9 mm to about 15 mm, such as a height of about 14 mm or a height of about 13 mm. The duplex micro-MT adaptor may have a width in a range of about 7.2 mm to about 13.2 mm, such as a width of about 12.2 mm or a width of about 11.2 mm. The duplex micro-MT adaptor may have mounting handles and a height in a range of about 12 mm to about 18 mm, such as a height of about 17 mm or a height of about 16 mm. The duplex micro-MT adaptor may have flanges and a height in a range of about 18 mm to about 24 mm, such as a height of about 23 mm or a height of about 22 mm.

(26) In some embodiments, the micro-MT adaptor is a quad micro-MT adaptor comprising a housing defining a longitudinal passage therethrough, the housing comprising at least one mounting tab, wherein a first wall, a second wall, a third wall, and a fourth wall, wherein the first wall and the third wall are opposite to each other, wherein the second wall and the fourth wall are opposite to each other, and wherein the second wall comprises at least one adaptor housing hole. The quad micro-MT adaptor comprises four latch-hook arms each defined by a first side, a second side, a first end, and a second end spaced from the first end, wherein the first end and the second end each comprise a first hook configured to couple with the connector, wherein one of the sides comprises a second hook to couple with an adaptor housing hole.

(27) In some embodiments, the micro-MT adaptor is a quad micro-MT adaptor, which may have a length in a range of about 22 mm to about 28 mm, such as a length of about 27 mm or a length of about 26 mm. The quad micro-MT adaptor may have a height in a range of about 15.3 mm to about 21.3 mm, such as a height of about 20.3 mm or a height of about 19.3 mm. The duplex micro-MT adaptor may have a width in a range of about 9 mm to about 15 mm, such as a width of about 14 mm or a width of about 13 mm. The duplex micro-MT adaptor may have mounting handles and a height in a range of about 18.3 mm to about 24.3 mm, such as a height of about 23.3 mm or a height of about 22.3 mm. The duplex micro-MT adaptor may have flanges and a height in a range of about 24.5 mm to about 30.5 mm, such as a height of about 29.5 mm or a height of about 28.5 mm.

(28) In another aspect, a micro-MT adaptor is used to couple at least one micro-MT connector. The connector can be, for example and without limitation, a micro-MT type connector, and more specifically a simplex micro-MT connector, a duplex micro-MT connector, or a quad micro-MT connector. The adaptor can be, for example and without limitation, a micro-MT type adaptor, and

more specifically a simplex micro-MT adaptor, a duplex micro-MT adaptor, or a quad micro-MT adaptor.

(29) In some embodiments, the micro-MT adaptor is a duplex micro-MT adaptor coupling with a duplex micro-MT connector, a first simplex micro-MT connector, and a second simplex micro-MT connector.

(30) In some embodiments, the micro-MT adaptor is a quad micro-MT adaptor coupling with a first simplex micro-MT connector, a second simplex micro-MT connector, a duplex micro-MT connector, and a quad micro-MT connector.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a perspective view of a prior art standard MPO connector;
- (2) FIG. 1B is a perspective view of a prior art standard MPO male ferrule;
- (3) FIG. 1C is a perspective view of a prior art standard MPO female ferrule;
- (4) FIG. 1D is a front view of a prior art standard MPO connector;
- (5) FIG. 1E is a top view of a prior art standard MPO connector;
- (6) FIG. 2A is a perspective view of a prior art standard MT-RJ connector;
- (7) FIG. 2B is a perspective view of a prior art standard MT-RJ male ferrule;
- (8) FIG. 2C is a perspective view of a prior art standard MT-RJ female ferrule;
- (9) FIG. 2D is a front view of a prior art standard MT-RJ connector;
- (10) FIG. 2E is a top view of a prior art standard MT-RJ connector;
- (11) FIG. 3A is a front view of a prior art standard LC duplex connector;
- (12) FIG. 3B is a top view of a prior art standard LC duplex connector;
- (13) FIG. 4A is a front view of a prior art standard SC duplex connector;
- (14) FIG. 4B is a top view of a prior art standard SC duplex connector;
- (15) FIG. 5A is a front view of a prior art standard 12-fiber MPO connector;
- (16) FIG. 5B is a schematic representation of a prior art standard LC duplex fan-out jumper, showing six 2-fiber connectors;
- (17) FIG. 6 is a schematic representation of network switch and distribution equipment racks, showing the MPO connector end of a jumper at a transceiver;
- (18) FIG. 7A is a perspective view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure;
- (19) FIG. 7B is a perspective view of one embodiment of a micro-MT male ferrule according to aspects of the present disclosure;
- (20) FIG. 7C is a perspective view of one embodiment of a micro-MT female ferrule according to aspects of the present disclosure;
- (21) FIG. 7D is a front view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure;
- (22) FIG. 7E is a top view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure;
- (23) FIG. 7F is an exploded view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure;
- (24) FIG. 8A is a perspective view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure, showing a pull-tab;
- (25) FIG. 8B is a perspective view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure, showing the pull-tab of FIG. 8A engaged in a hook hole;
- (26) FIG. 9A is a perspective view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure, showing a relaxed latch spring;

(27) FIG. 9B is a perspective view of one embodiment of a simplex micro-MT connector according to aspects of the present disclosure, showing a compressed latch spring;

(28) FIG. 10A is a front view of one embodiment of a duplex micro-MT connector according to aspects of the present disclosure;

(29) FIG. 10B is a top view of one embodiment of a duplex micro-MT connector according to aspects of the present disclosure;

(30) FIG. 10C is an exploded view of one embodiment of a duplex micro-MT connector according to aspects of the present disclosure;

(31) FIG. 11A is a perspective view of one embodiment of a duplex micro-MT connector according to aspects of the present disclosure, showing a pull-tab;

(32) FIG. 11B is a perspective view of one embodiment of a duplex micro-MT connector according to aspects of the present disclosure, showing the pull-tab of FIG. 11A engaged in a hook hole;

(33) FIG. 12A is a front view of one embodiment of a quad micro-MT connector according to aspects of the present disclosure;

(34) FIG. 12B is a top view of one embodiment of a quad micro-MT connector according to aspects of the present disclosure;

(35) FIG. 12C is an exploded view of one embodiment of a quad micro-MT connector according to aspects of the present disclosure;

(36) FIG. 13A is a perspective view of one embodiment of a quad micro-MT connector according to aspects of the present disclosure, showing a pull-tab;

(37) FIG. 13B is a perspective view of one embodiment of a quad micro-MT connector according to aspects of the present disclosure, showing the pull-tab of FIG. 13A engaged in a latch hook;

(38) FIG. 14A is a top view of one embodiment of a simplex micro-MT adapter according to aspects of the present disclosure;

(39) FIG. 14B is an end view of one embodiment of a simplex micro-MT adapter without flanges according to aspects of the present disclosure;

(40) FIG. 15A is a top view of one embodiment of a duplex micro-MT adapter according to aspects of the present disclosure;

(41) FIG. 15B is an end view of one embodiment of a duplex micro-MT adapter without flanges according to aspects of the present disclosure;

(42) FIG. 15C is an end view of one embodiment of a duplex micro-MT adapter with flanges according to aspects of the present disclosure;

(43) FIG. 16A is a top view of one embodiment of a quad micro-MT adapter according to aspects of the present disclosure;

(44) FIG. 16B is an end view of one embodiment of a quad micro-MT adapter without flanges according to aspects of the present disclosure;

(45) FIG. 16C is an end view of one embodiment of a quad micro-MT adapter with flanges according to aspects of the present disclosure;

(46) FIG. 17A is an exploded view of one embodiment of a simplex micro-MT adapter according to aspects of the present disclosure;

(47) FIG. 17B is a perspective view of one embodiment of a simplex micro-MT adapter according to aspects of the present disclosure;

(48) FIG. 18A is an exploded view of one embodiment of a duplex micro-MT adapter according to aspects of the present disclosure;

(49) FIG. 18B is a perspective view of one embodiment of a duplex micro-MT adapter according to aspects of the present disclosure;

(50) FIG. 19A is an exploded view of one embodiment of a quad micro-MT according to aspects of the present disclosure;

(51) FIG. 19B is a perspective view of one embodiment of a quad micro-MT adapter according to aspects of the present disclosure;

(52) FIG. 20A is an exploded view of one embodiment of a duplex micro-MT connector coupled to a first simplex micro-MT connector and a second simplex micro-MT connector through a duplex micro-MT adapter according to aspects of the present disclosure;

(53) FIG. 20B is a perspective view of the duplex micro-MT connector coupled to a first simplex micro-MT connector and a second simplex micro-MT connector through the duplex micro-MT adapter of FIG. 20A;

(54) FIG. 21A is an exploded view of one embodiment of a duplex micro-MT connector, a first simplex micro-MT connector, and a second simplex micro-MT connector coupled to a quad micro-MT connector through a quad micro-MT adapter according to aspects of the present disclosure; and

(55) FIG. 21B a perspective view of the duplex micro-MT connector, the first simplex micro-MT connector, and the second simplex micro-MT connector coupled to a quad micro-MT connector through the quad micro-MT adapter of FIG. 21A.

DETAILED DESCRIPTION

(56) Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in accompanying drawings. Those skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such embodiments and variations are intended to be included within the scope of the present invention.

(57) So that the present invention may more readily be understood, certain terms are first defined.

(58) As used herein, the terms “about” or “approximately” or “substantially” for any numerical values or ranges indicate a suitable dimensional tolerance that allows the part or collection of elements to function for its intended purpose as described herein. These terms indicate a $\pm 10\%$ variation about a central value.

(59) The term “ferrule” is used herein consistent with its customary meaning in the art to refer to a device and/or components thereof that connect optical fibers.

(60) The term “connector” is used herein consistent with its customary meaning in the art to refer to a device and/or components thereof that connects a first module or cable to a second module or cable. The connectors may be configured for fiber optic transmission or electrical signal transmission. The connector may be any suitable type now known or later developed such as, for example and without any limitation, a ferrule connector (FC), a fiber distributed data interface (FDDI) connector, a LC connector, a mechanical transfer (MT) connector, a mechanical transfer registered jack (MT-RJ) connector, a SC connector, a SC duplex connector, a straight tip (ST) connector, a multiple-fiber push-on (MPO) connector, or a media interface connector (MIC).

(61) The term “adaptor” is used herein consistent with its customary meaning in the art to refer to a device and/or components thereof that couples a first module or cable or set of cables with a second module or cable or set of cables.

(62) The term “cable” is used herein consistent with its customary meaning in the art to refer to an insulated wire or wires comprising a protective casing (e.g., a jacket, a sheathing material) and used for transmitting electricity or telecommunication signals. A “fiber optic cable” or an “optical cable” referred herein to a cable containing one or more optical fibers for conducting optical signals in beams of light. The optical fibers can be constructed from any suitable transparent material, including glass, fiberglass, and plastic. In addition, the cable can be connected to a connector on one end or on both ends of the cable, the cable can be coupled to an adaptor on one end or on both ends of the cable, and the cable can be connected to another cable on one end or on both ends of the cable.

(63) The term “jumper” is used herein consistent with its customary meaning in the art to refer to a device and/or components thereof that connect multicore cables.

(64) The term “panel” is used herein consistent with its customary meaning in the art to refer to a device and/or components thereof that connect incoming and outgoing lines of communication cables.

(65) The present application relates generally to devices and methods for connecting optical fibers. For example and without any limitation, the various devices and methods of the invention can be utilized to optimize the connections between ports in high-density network panels by increasing the accessibility to the connectors by the operator and by reducing the number of connector cables, the length of the connector cables, the number of connector cables that are dressed crossover to the equipment, and the dimension of the connectors. As discussed in more detail below, in some embodiments, optical fiber cables can be modularly coupled with one or more optical fiber connectors, adaptors, and other optical fiber cables using a remote release. Various aspects of the prior art and invention are described below.

(66) Those in the art will understand that the devices and methods described herein are more suitable at least for 2-fiber cable and high-density network panel applications than the devices and methods described in the prior art.

(67) For instance, as shown in FIG. 1A, a conventional MPO connector **100** is commonly configured for 2 to 36 fiber ribbon cables and is therefore much bigger than what is needed for 2-fiber applications with the same fiber-to-fiber center distance of about 0.25 mm. The conventional MPO Connector **100** is mounted with a male MPO ferrule **102** as shown in FIG. 1B or a female MPO ferrule **104** as shown in FIG. 1C, and the MPO ferrules have a frontal contact surface height **106** of about 2.5 mm and a frontal contact surface width **108** of about 6.4 mm. FIG. 1D shows a front view of the conventional MPO connector **100** with a height **110** of about 7.6 mm, and FIG. 1E shows a side view of the conventional MPO connector **100** with a width **112** of about 12.4 mm and a length **114** of about 25.7 mm.

(68) In another instance, as shown in FIG. 2A, a conventional MT-RJ connector **200** is configured for cable with a smaller number of fiber ribbons, such as 1 to 4 fibers, but it is larger than what is needed for 2-fiber applications. The MT-RJ connector **200** is mounted with a male MT-RJ ferrule **202** as shown in FIG. 2B or a female MT-RJ ferrule **204** as shown in FIG. 2C, and the MT-RJ ferrules have a frontal contact surface height **206** of about 2.5 mm and a frontal contact surface width **208** of about 4.4 mm. FIG. 2D shows a front view of the conventional MT-RJ connector **200** with a height **210** of about 10 mm and a width **212** of about 9.2 mm, and FIG. 2E shows a side view of the conventional MT-RJ connector **200** with a length **214** of about 20 mm.

(69) In another instance, as shown in FIG. 3A, a conventional LC duplex connector **300** is designed for 2-fiber applications but its overall dimension is not optimized to address the requirements of high-density network panels. The LC duplex connector **300** has a height **302** of about 12.7 mm and a width **304** of about 12.8 mm. FIG. 3B shows a side view of the conventional LC duplex connector **300** with a length **306** of about 27.3 mm.

(70) In another instance, as shown in FIG. 4A, a conventional SC duplex connector **400** is designed for 2-fiber applications, similar to the LC duplex connector **300**, but its overall dimension is not optimized to address the requirements of high-density network panels. The SC duplex connector **400** has a height **402** of about 9.3 mm. FIG. 4B shows a side view of the conventional SC duplex connector **400** with a width **404** of about 24.2 mm and a length **406** of about 25.2 mm.

(71) In another example, FIG. 5B shows a plan view of a conventional 12-fiber MPO—6 LC duplex fan-out jumper **502** that is often used to couple with a high-density network panel, and FIG. 5A shows a front view of a 12-fiber MPO connector **506** that is attached at one end of the 12-fiber MPO-6 LC duplex fan-out jumper **502**. The 12-fiber MPO connector **506** comprises six fiber pairs **520**, **522**, **524**, **526**, **528**, and **530**, wherein each pair has one data-transmitting Tx fiber and one data-receiving Rx fiber. The twelve fibers go through a cable **508** and are separated into 2-fiber cables **514** at a fan-out block **512**. The 2-fiber cables **514** have a length **516** and are terminated by an LC connector **518** comprising one of the fiber pairs **520**, **522**, **524**, **526**, **528**, and **530**.

(72) FIG. 6 shows a perspective view of the 12-fiber MPO—6 LC duplex fan-out jumper **500** and conventional network equipment racks **600** that can be found, for example, in a central office and data center. The network equipment racks **600** comprise a plurality of network switches **602** comprising a transceiver **604** and a plurality of network panels **606** comprising a plurality of network panel ports **608**. The network switches **602** and the network panels **604** are connected through the 12-fiber MPO—6 LC duplex jumper **500**. The 12-fiber MPO connector **506** (not shown) located at one end of the 12-fiber MPO—6 LC duplex fan-out jumper **500** connects to the transceiver **604**, and only four of the six 2-fiber LC cables **514** located at the other end of the 12-fiber MPO—6 LC duplex fan-out jumper **500** connect to the network panel ports **608**. The remaining two 2-fiber LC cables **514** do not connect to the network panel ports since the desired panel ports **608a** are not accessible due to the too short length **516** of the 2-fiber cables **514**. Therefore, the 12-fiber MPO—6 LC duplex fan-out jumper **500** is not optimized for a high-density network panel having network panel ports located at different distances from the 12-fiber MPO—6 LC duplex fan-out jumper **500**.

(73) Various embodiments disclosed herein are configured for use as a mechanical transfer (MT) connector, such as a micro-MT (MMT) connector **700** as shown in FIG. 7A, comprising a male micro-MT ferrule **702** as shown in FIG. 7B or a female micro-MT ferrule **704** as shown in FIG. 7C. The male micro-MT ferrule **702** and the female micro-MT ferrule **704** have a frontal contact surface smaller than that of conventional 2.5 mm high and 7.6 mm wide MPO ferrules and conventional 2.5 mm high and 4.4 mm wide MT-RJ ferrules. In some embodiments, the MT ferrule is a micro-MT ferrule having a contact surface with a height **706** in a range of about 1.0 mm to about 2.4 mm, such as a height of about 2.0 mm or a height of about 1.6 mm. In some embodiments, the MT ferrule is a micro-MT ferrule having a contact surface with a width **708** in a range of about 2.4 mm to about 4.3 mm, such as a width of about 4.0 mm or a width of about 3.6 mm.

(74) FIG. 7D shows a front view of a simplex micro-MT connector **700** having a height **710** smaller than that of a conventional 7.6 mm high MPO connector, a conventional 10 mm high MT-RJ connector, a conventional 12.7 mm high LC duplex connector, or a conventional 9.3 mm high SC duplex connector. In some embodiments, the simplex MT connector is a simplex micro-MT connector having a height **710** in a range of about 3.8 mm to about 7.5 mm, such as a height of about 6.5 mm or a height of about 5.5 mm.

(75) The simplex micro-MT connector **700** shown in FIG. 70 has a width **712** smaller than that of a conventional 12.4 mm wide MPO connector, a conventional 9.2 mm wide MT-RJ connector, a conventional 12.8 mm wide LC duplex connector, or a conventional 24.2 mm wide SC duplex connector. In some embodiments, the MT simplex connector is a simplex micro-MT connector having a width **712** in a range of about 6.4 mm to about 9.1 mm, such as a width of about 8.8 mm or a width of about 8.5 mm.

(76) FIG. 7E shows a side view of the simplex micro-MT connector **700** having a length **714** smaller than that of a conventional 25.7 mm long MPO connector, a conventional 27.3 mm long LC duplex connector, or a conventional 25.2 mm long SC duplex connector. In some embodiments, the simplex MT connector is a simplex micro-MT connector having a length **714** in a range of about 17.0 mm to about 25.1 mm, such as a length of about 23.2 mm or a length of about 21.3 mm.

(77) FIG. 7F shows one embodiment of the simplex micro-MT connector **700** according to aspects disclosed herein. The simplex micro-MT connector **700** may include a housing **736** defining a longitudinal passage therethrough from a proximal end **736a** to a distal end **736b** and including a latch hole **736c** designed to couple with a latch arm (not shown) from an adaptor (not shown).

(78) The simplex micro-MT connector **700** may include a latch body **730** defining a first longitudinal passage therethrough from a proximal end **730a** to a distal end **730b**, a second longitudinal passage therethrough from a middle **730c** to the distal end **730b**. The latch body **730** comprises a bottom **730d**, a hook hole **732** to couple with a pull-tab (not shown), and a latch hole

730e to couple with a latch arm (not shown) from an adaptor (not shown). The latch body is movably coupled with the housing **736** wherein at least part of the housing is movably within at least the first longitudinal passage of the latch body **730**.

(79) The simplex micro-MT connector **700** may comprise a latch spring **734** defining a longitudinal passage therethrough and comprising arms **734a**, lower parts **734b**, and upper parts **734c**, and a top part **734d**. The latch spring is coupled with the distant end **730b** and the bottom **730d** of the latch body **730**. The latch spring is movably coupled with the housing **736** wherein at least part of the housing is movably within the longitudinal passage of the latch spring **734**.

(80) The simplex micro-MT connector **700** may comprise a ferrule **738** extending longitudinally from a proximal end **746** to a distal end **748** and disposed at least partially within the longitudinal passage of the housing **736** with the proximal end protruding externally through the passage defined by the latch body **730** and the housing.

(81) The simplex micro-MT connector **700** may comprise a ferrule spring **740** defining a longitudinal and movable passage therethrough from a proximal end **740a** to a distal end **740b**. The ferrule spring **740** is at least partially within the longitudinal passage of the housing **736**.

(82) The simplex micro-MT connector **700** may comprise a spring push **742** defining a longitudinal passage therethrough from a proximal end **750** to a distal end **752** and comprising a flange **742a**. The spring push **742** is at least partially within the housing **736**.

(83) The simplex micro-MT connector **700** may comprise a cable boot **754** defining a longitudinal passage therethrough from a proximal end **754a** to a distal end **754b**. The proximal end **754a** of the cable boot **754** is coupled with the distal end **752** of the spring push **742**.

(84) As shown in FIG. **8A**, the simplex micro-MT connector **700** may comprise a pull-tab **800** having a distal end **802** and a proximal end **804**. The proximal end **804** may include a latch hook **806** uniquely shaped so as to engage with the unique profile of the latch body **730** that is integral to the simplex micro-MT connector **700**. As shown in FIG. **8B**, the proximal end **804** is disposed within the second longitudinal passage of the latch body **730**. The pull-tab hook **806** snaps with the hook hole **732** so that the pull-tab **800** is coupled to the simplex micro-MT connector **700**. The pull-tab **800** can be removably coupled to the simplex micro-MT connector **700**. The pull-tab **800** may be coupled to the simplex micro-MT connector **700** by means other than by snapping into position, such as sliding or hooking into position. The pull-tab **800** may alternatively be an integral component of the simplex micro-MT connector **700**.

(85) FIG. **9A** shows the configuration of the simplex micro-MT connector **700** when it is coupled with an adaptor (not shown). In this configuration, the latch spring **734** is not compressed and therefore not actuated. The lower part **734b** of the latch spring **734** is in contact with the latch body **730** distal end **730b**, and the top part **734d** of the latch spring **734** is in contact with the flange **742a** from the spring push **742**. Most importantly, in this configuration, the latch hole **736c** from the housing **736** and the latch hole **730e** from the latch body **730** are disposed vertically, one above each other, to generate a large cavity where a latch from an adaptor can couple to fasten the connector to the adaptor.

(86) FIG. **9B** shows the configuration of the simplex micro-MT connector **700** when it is not coupled with an adaptor (not shown). In this configuration, the latch spring **734** is compressed and therefore actuated. The latch body **730** is pulled back manually or by the pull-tab **800** (not shown) toward the distal end of the housing **736** and compresses the latch spring **734** so its lower part **734b**, middle part **734c** and top **734d** are in contact with both the distal end **730b** of the latch body **730** and the flange **742a** of the push spring **742**. In this configuration, the latch hole **736c** from the housing **736** and the latch hole **730e** from the latch body **730** are not disposed vertically, one above each other, and do not generate a large enough cavity where a latch from the adaptor can couple to fasten the connector to the adaptor micro-MT duplex connector.

(87) Various embodiments disclosed herein are configured for use as a mechanical transfer (MT) connector, such as a duplex micro-MT (MMT) connector **1000** as shown in FIG. **10A**. In some

embodiments, the duplex micro-MT connector **1000** has a height **1010** in a range of about 7.8 mm to about 13.8 mm, such as a height of about 12.8 mm or a height of about 11.8 mm. In some embodiments, the duplex micro-MT connector **1000** has a width **1012** in a range of about 6.4 mm to about 9.1 mm, such as a width of about 8.8 mm or a width of about 8.5 mm.

(88) FIG. **10B** shows a side view of the duplex micro-MT connector **1000**. In some embodiments, the duplex micro-MT connector **1000** has a length **1014** in a range of about 19.4 mm to about 29.0 mm, such as a length of about 27.0 mm or a length of about 25.0 mm.

(89) FIG. **10C** shows one embodiment of the duplex micro-MT connector **1000** according to aspects disclosed herein. The duplex micro-MT connector **1000** may include a first housing and a second housing **1036** each defining a longitudinal passage therethrough from a proximal end **1036a** to a distal end **1036b** and including a latch hole **1036c** designed to couple with a latch arm (not shown) from an adaptor (not shown).

(90) The duplex micro-MT connector **1000** may include a latch body **1030** defining a first longitudinal passage therethrough from a proximal end **1030a** to a distal end **1030b**, a second longitudinal passage therethrough from a middle **1030c** to the distal end **1030b**. The latch body **1030** comprises a bottom **1030d**, two hook holes **1032** to couple with a pull-tab (not shown), and two latch holes **1030e** to couple with a latch arm (not shown) from an adaptor (not shown). The latch body **1030** is movably coupled with the housings **1036** wherein at least part of the housing is movably within at least the first longitudinal passage of the latch body **1030**.

(91) The duplex era-MT connector **1000** may comprise a latch spring **1034** defining a longitudinal passage therethrough and comprising arms lower parts **1034b**, upper parts **1034c**, and a top part **1034d**. The latch spring **1034** is coupled with the distal end **1030b** and the bottom **1030d** of the latch body **1030**. The latch is movably coupled with the housings **1036** wherein at least part of the housings is movably within the longitudinal passage of the latch spring **1034**.

(92) The duplex micro-MT connector **1000** may comprise two ferrules **1038** each extending longitudinally from a proximal end **1046** to a distal end **1048** and disposed at least partially within the longitudinal passage of one of the housings **1036** with the proximal end **1046** protruding externally to the passage.

(93) The duplex micro-MT connector **1000** may comprise two ferrule springs **1040** defining a longitudinal and movable passage therethrough from a proximal end **1040a** to a distal end **1040b**. The ferrule springs **1040** are at least partially within a longitudinal passage of the housing **1036**.

(94) The duplex micro-MT connector **1000** may comprise a spring separator **1056** defining two longitudinal passages therethrough and comprising an elongated part extending from a proximal end **1056a** to a distal end **1056b**.

(95) The duplex micro-MT connector **1000** may comprise a spring push **1042** defining a longitudinal passage therethrough from a proximal end **1050** to a distal end **1052** and comprising a flange **1042a**. The spring push **1042** is at least partially within the housing **1036**.

(96) The duplex micro-MT connector **1000** may comprise a cable boot **1054** defining a longitudinal passage therethrough from a proximal end **1054a** to a distal end **1054b**. The proximal end **1054a** of the cable boot **1054** is coupled with the distal end **1052** of the spring push **1042**.

(97) As shown in FIG. **11A**, the duplex micro-MT connector **1000** may comprise a pull-tab **1100** having a distal end **1102** and a proximal end **1104**. The proximal end **1104** may include two latch hooks **1106a** and **1106b** uniquely shaped so as to engage with the unique profile of latch body **1030** from the duplex micro-MT connector **1000**. As shown in FIG. **11B**, proximal end **1104** is disposed within the second longitudinal passage of the latch body **1030**. The pull-tab hooks **1106a** and **1106b** then snaps with the hook holes **1032** so that the pull-tab **1100** is coupled to the duplex micro-MT connector **1000**.

(98) Various embodiments disclosed herein are configured for use as a mechanical transfer (MT) connector, such as a quad micro-MT (MMT) connector **1200** as shown in FIG. **12A**. In some embodiments, the quad micro-MT connector **1200** has a height **1210** in a range of about 7.8 mm to

about 13.8 mm, or such as a height of about 7.8 mm to about 12.8 mm or a height of about 7.8 mm to about 11.8 mm. In some embodiments, the quad micro-MT connector **1200** has a width **1212** in a range of about 12.8 mm to about 21.2 mm, such as a width of about 20.2 mm or a width of about 19.2 mm.

(99) FIG. **12B** shows a side view of the quad micro-MT connector **1200**. In some embodiments, the quad micro-MT connector **1200** has a length **1214** in a range of about 20.2 mm to about 32.0 mm, such as a length of about 31.0 mm or a length of about 30.0 mm.

(100) FIG. **12C** shows one embodiment of quad micro-MT connector **1200** according to aspects disclosed herein. The quad micro-MT connector **1200** may include four housings **1236** each defining a longitudinal passage therethrough from a proximal end **1236a** to a distal end **1236b** and including a latch hole **1236c** designed to couple with a latch arm (not shown) from an adaptor (not shown).

(101) The quad micro-MT connector **1200** may include a latch body **1230** defining a first longitudinal passage therethrough from a proximal end **1230a** to a distal end **1230b**, a second longitudinal passage therethrough from a middle **1230c** to the distal end **1230b**. The latch body **1230** comprises a bottom **1230d**, two hook holes **1232** to couple with a pull-tab (not shown), and four latch holes **1230e** to couple with a latch arm (not shown) from an adaptor (not shown). The latch body is movably coupled with the housings **1236** wherein at least part of the housings is movably within at least the first longitudinal passage of the latch body.

(102) The quad micro-MT connector **1200** may comprise two latch springs **1234** each defining a longitudinal passage therethrough and comprising arms **1234a**, lower parts **1234b**, upper parts **1234c**, and a top part **1234d**. The latch springs are coupled with the distal end **1230b** of the latch body **1230**. The latch springs are movably coupled with the housings **1236** wherein at least part of the housings is movably within the longitudinal passage of the latch springs **1234**.

(103) The quad micro-MT connector **1200** may comprise four ferrules **1238** each extending longitudinally from a proximal end **1246** to a distal end **1248** and disposed at least partially within the longitudinal passage of one housing **1236** with the proximal end **1246** protruding externally to the passage.

(104) The quad micro-MT connector **1200** may comprise four ferrule springs **1240** defining a longitudinal and movable passage therethrough from a proximal end **1240a** to a distal end **1240b**. The ferrule springs **1240** are at least partially within the longitudinal passage of housings **1236**.

(105) The quad micro-MT connector **1200** may comprise a spring separator **1256** defining four longitudinal passages therethrough and comprising two elongated parts extending from a proximal end **1256a** to a distal end **1256b**.

(106) The quad micro-MT connector **1200** may comprise a spring push **1242** defining a longitudinal passage therethrough from a proximal end **1250** to a distal end **1252** and comprising a flange **1242a**. The spring push **1242** is at least partially within the housing **1236**.

(107) The quad micro-MT connector **1200** may comprise a cable boot **1254** defining a longitudinal passage therethrough from a proximal end **1254a** to a distal end **1254b**. The proximal end **1254a** of the cable boot **1254** is coupled with the distal end **1252** of the spring push **1242**.

(108) As shown in FIG. **13A**, the quad micro-MT connector **1200** may comprise a pull-tab **1300** having a distal end **1302** and a proximal end **1304**. The proximal end **1304** may include two latch hooks **1306a** and **1306b** uniquely shaped so as to engage with the unique profile of latch body **1230** from the quad micro-MT connector **1200**. As shown in FIG. **13B**, proximal end is disposed within the second longitudinal passage of the latch body **1230**. The pull-tab hooks **1306a** and **1306b** then snap with the hook holes **1232** so that the pull-tab **1300** is coupled to the quad micro-MT connector **1200**.

(109) Various embodiments disclosed herein are configured for use as an adaptor, such as a simplex micro-MT adaptor **1400** as shown in FIGS. **14A** and **14B**. FIG. **14A** shows a top view of the simplex micro-MT adaptor **1400**, and FIG. **14B** shows an end view of the simplex micro-MT

adaptor **1400** without a flange. In some embodiments, the simplex micro-MT adaptor **1400** has a length **1402** in a range of about 22 mm to about 28 mm, such as a length of about 27 mm or a length of about 26 mm. In some embodiments, the simplex micro-MT adaptor **1400** has a height **1404** in a range of about 4 mm to about 10 mm, such as a height of about 9 mm or a height of about 8 mm. In some embodiments, the simplex micro-MT adaptor **1400** has a width **1406** in a range of about 7.2 mm to about 13.2 mm, such as a width of about 12.2 mm or a width of about 11.2 mm. In some embodiments, the simplex micro-MT adaptor **1400** has mounting handles **1407** and a height **1408** in a range of about 7 mm to about 13 mm, such as a height of about 12 mm or a height of about 11 mm.

(110) Various embodiments disclosed herein are configured for use as an adaptor, such as a duplex micro-MT adaptor **1500** as shown in FIGS. **15A**, **15B**, and **15C**. FIG. **15A** shows a top view of the duplex micro-MT adaptor **1500**, FIG. **15B** shows an end view of the duplex micro-MT adaptor **1500** without a flange, and FIG. **15C** shows an end view of the duplex micro-MT adaptor **1500** with a flange. In some embodiments, the duplex micro-MT adaptor **1500** has a length **1502** in a range of about 22 mm to about 28 mm, such as a length of about 27 mm or a length of about 26 mm. In some embodiments, the duplex micro-MT adaptor **1500** has a height **1504** in a range of about 9 mm to about 15 mm, such as a height of about 14 mm or a height of about 13 mm. In some embodiments, the duplex micro-MT adaptor **1500** has a width **1506** in a range of about 7.2 mm to about 13.2 mm, such as a width of about 12.2 mm or a width of about 11.2 mm. In some embodiments, the duplex micro-MT adaptor **1500** has mounting handles **1507** and a height **1508** in a range of about 12 mm to about 18 mm, such as a height of about 17 mm or a height of about 16 mm. In some embodiments, the duplex micro-MT adaptor **1500** has flanges **1509** and a height **1510** in a range of about 18 mm to about 24 mm, such as a height of about 23 mm or a height of about 22 mm.

(111) Various embodiments disclosed herein are configured for use as an adaptor, such as a quad micro-MT adaptor **1600** as shown in FIGS. **16A**, **16B**, and **16C**. FIG. **16A** shows a top view of the quad micro-MT adaptor **1600**, FIG. **16B** shows an end view of the quad micro-MT adaptor **1600** without a flange, and FIG. **16C** shows an end view of the quad micro-MT adaptor **1600** with a flange. In some embodiments, the quad micro-MT adaptor **1600** has a length **1602** in a range of about 22 mm to about 28 mm, such as a length of about 27 mm or a length of about 26 mm. In some embodiments, the quad micro-MT adaptor **1600** has a height **1604** in a range of about 15.3 mm to about 21.3 mm, such as a height of about 20.3 mm or a height of about 19.3 mm. In some embodiments, the quad micro-MT adaptor **1600** has mounting handles **1607** and a width **1608** in a range of about 9 mm to about 15 mm, such as a height of about 14 mm or a height of about 13 mm. In some embodiments, the quad micro-MT adaptor **1600** has a height **1606** in a range of about 18.3 mm to about 24.3 mm, such as a height of about 23.3 mm or a width of about 22.3 mm. In some embodiments, the quad micro-MT adaptor **1600** has flanges **1609** and a height **1610** in a range of about 24.5 mm to about 30.5 mm, such as a height of about 29.5 mm or a height of about 28.5 mm.

(112) FIG. **17A** shows an exploded of the simplex micro-MT adaptor **1400**, and FIG. **17B** shows a perspective view of the simplex micro-MT adaptor **1400**. The simplex micro-MT adaptor **1400** comprises a housing **1402** defining a longitudinal passage therethrough, a proximal end **1404** and a distal end **1406**, wherein the proximal end **1404** is spaced from the distal end **1406**. The housing **1402** comprises at least one mounting tab **1408**, a first wall **1410**, a second wall **1412**, a third wall (not shown), and a fourth wall (not shown), wherein the first wall and the third wall are opposite to each other, the second wall and the fourth wall are opposite to each other, and the second wall **1412** comprises at least one adaptor housing hole **1414**. The adaptor **1400** includes at least one latch arm **1416** defined by a proximal end **1418** and a distal end **1420**, wherein the proximal end is spaced from the distal end. The proximal end **1418** and the distal end **1420** may each comprise a hook to couple with the adaptor **1400**, and the top side of the latch arm **1416** comprises a hook **1422** to couple with the adaptor housing hole **1414**.

(113) FIG. 18A shows an exploded view of the duplex micro-MT adaptor **1500**, and FIG. 18B shows a perspective view of the duplex micro-MT adaptor **1500**. The duplex micro-MT adaptor **1500** comprises a housing **1502** defining a longitudinal passage therethrough, a proximal end **1504** and a distal end **1506**, wherein the proximal end **1504** is spaced from the distal end **1506**. The housing **1502** comprise at least one mounting tab **1508**, a first wall **1510**, a second wall **1512**, a third wall (not shown), and a fourth wall (not shown), wherein the first wall and the third wall are opposite to each other, the second and fourth walls are opposite to each other, and the second wall **1512** comprises two adaptor housing holes **1514**. The duplex micro-MT adaptor **1500** includes at least one latch arm **1516** defined by a proximal end **1518** and a distal end **1520**, wherein the proximal end is spaced from the distal end. The proximal end **1518** and the distal end **1520** may each comprise a hook to couple with the adaptor **1500**, and a top side of each latch arm **1516** comprises a hook **1522** to couple with an adaptor housing hole **1514**.

(114) FIG. 19A shows an exploded view of the quad micro-MT adaptor **1600**, and FIG. 19B shows a perspective view of the quad micro-MT adaptor **1600**. The quad micro-MT adaptor **1600** comprises a housing **1602** defining a longitudinal passage therethrough, a proximal end **1604** and a distal end **1606**, wherein the proximal end **1604** is spaced from the distal end **1606**. The housing **1602** comprises at least one mounting tab **1608** that attaches to the housing, a first wall **1610**, a second wall **1612**, a third wall (not shown), and a fourth wall (not shown), wherein the first wall and the third wall are opposite to each other, the second and fourth walls are opposite to each other, the second wall **1612** comprises two adaptor housing holes **1614**, and the third wall (not shown) comprises two holes. The quad micro-MT adaptor **1600** includes four latch arms **1616** defined by a proximal end **1618** and a distal end **1620**, wherein the proximal end is spaced from the distal end. The proximal end **1618** and the distal end **1620** may each comprise a hook to couple with the adaptor **1600**, and each latch arm **1616** comprises a hook **1622** to couple with an adaptor housing hole **1614**.

(115) FIG. 20A shows an exploded view of a duplex micro-MT adaptor **1500** coupled with a duplex micro-MT connector **1000**, a first simplex micro-MT connector **700**, and a second simplex micro-MT connector **700**. FIG. 20B shows a perspective view of the duplex micro-MT adaptor **1500** coupled with a duplex micro-MT connector **1000**, a first simplex micro-MT connector **700**, and a second simplex micro-MT connector **700**.

(116) FIG. 21A shows an exploded view of a quad micro-MT adaptor **1600** coupled with a first simplex micro-MT connector **700**, a second simplex micro-MT connector **700**, a duplex micro-MT connector **1000**, and a quad micro-MT **1200** connector. FIG. 21B shows a perspective view of the quad micro-MT adaptor **1600** coupled with a first simplex micro-MT connector **700**, a second simplex micro—MT connector **700**, a duplex micro-MT connector **1000**, and a quad micro-MT **1200** connector.

Claims

1. A breakout method in a high density network panel application, the breakout method comprising: plugging an optical fiber connector terminating a single optical fiber cable into a first end portion of an optical fiber adapter such that a respective group of optical fibers of the optical fiber connector are received in each of four channels of the optical fiber adapter; plugging a plurality of individual optical fiber connectors into a second end portion of the optical fiber adapter such that one of the individual optical fiber connectors is received in each of the four channels of the optical fiber adapter, each of the plurality of individual optical fiber connectors terminating an individual optical fiber cable; wherein said plugging the optical fiber connector and said plugging the individual optical fiber connectors makes optical connections between the individual optical fiber connectors and the groups of optical fibers in each of the four channels and thereby breaks out the single optical fiber cable into the plurality of individual cables; wherein said plugging a plurality of

individual optical fiber connectors into a second end portion of the optical fiber adapter latches the plurality of individual optical fiber connectors with the optical fiber adapter and such that each of the plurality of individual optical fiber connectors is configured to be individually unlatched from the optical fiber adapter for individual removal by pulling an externally accessible latch release backward away from the optical fiber adapter to displace the latch release in relation to a remainder of the respective individual optical fiber connector such that the individual optical fiber connector can be individually removed without removing any other individual optical fiber connector.

2. The breakout method of claim 1, wherein the optical fiber adapter comprises an adapter housing having first and second cross-sectional outer dimensions, the first and second cross-sectional outer dimensions being perpendicular, the first cross-sectional outer dimension being greater than the second cross-sectional outer dimension, the first cross-sectional outer dimension being in a range of from about 18.3 mm to about 24.3 mm.

3. The breakout method of claim 2, wherein the second cross-sectional outer dimension is in a range of from about 9 mm to about 15 mm.

4. The breakout method of claim 1, wherein the optical fiber connector comprises four MT ferrules and each individual optical fiber connector comprises at least one MT ferrule.

5. The breakout method of claim 1, wherein said plugging the optical fiber connector and said plugging the individual optical fiber connectors makes four Tx-Rx connections between the optical fiber connector and the plurality of individual connectors.

6. The breakout method of claim 1, further comprising pulling an externally accessible latch release of one of the individual optical fiber connectors backward away from the optical fiber adapter to displace the latch release in relation to a remainder of said one of the individual optical fiber connectors to remove said one of the individual optical fiber connectors from the optical fiber adapter without removing any other individual optical fiber connector.
