

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399771
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Gardner; Douglas J.

Power supply with system monitoring

Abstract

Various examples described herein are directed to power supplies and methods of operating power supplies. A power supply may comprise a regulator circuit configured to generate an output electrical signal and a sensor configured to generate a sensor signal describing the output electrical signal. The power supply may also comprise at least one processor that is programmed to determine that the sensor signal fails to match expected system profile data describing an operation of at least one component electrically coupled to the power supply. Responsive to determining that the sensor signal fails to match the expected system profile data, the at the least one processor may be programmed to execute a remedial action.

Inventors:	Gardner; Douglas J. (Palm Harbor, FL)
Applicant:	Analog Devices, Inc. (Wilmington, MA)
Family ID:	1000008778659
Assignee:	Analog Devices, Inc. (Wilmington, MA)
Appl. No.:	18/465771
Filed:	September 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250086049 A1	Mar. 13, 2025

Publication Classification

Int. Cl.: G06F11/00 (20060101); G06F1/28 (20060101); G06F11/07 (20060101); G06N20/00 (20190101)

U.S. Cl.:

Field of Classification Search

CPC: G06F (1/28); G06F (11/0793); G06F (11/079); G06N (20/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10871818	12/2019	De La Cropte De Chanterac	N/A	G06F 1/325
11316851	12/2021	Sohail	N/A	G06N 20/00
11372465	12/2021	Srinivasan	N/A	G06F 1/30
11681831	12/2022	Ngo	726/22	G06F 1/28
2017/0010652	12/2016	Huang	N/A	G06F 1/3234
2017/0185495	12/2016	Jau	N/A	G06F 1/28
2018/0330091	12/2017	Prowell	N/A	G06F 21/552
2020/0033923	12/2019	Koeninger	N/A	H04L 43/0811
2020/0133752	12/2019	Ganesan	N/A	G06F 1/28
2020/0327255	12/2019	Ngo	N/A	G06F 21/577
2020/0403991	12/2019	Sohail	N/A	H04L 63/1433
2025/0086049	12/2024	Gardner	N/A	G06F 11/0793

Primary Examiner: Gibson; Jonathan D

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

BACKGROUND

(1) A power supply can generate one or more output electrical signals that can be utilized by various components of a powered system. For example, a power supply may provide power to for various sensors, motors, actuators, and/or other components. The output electrical signal may be an alternating current (AC) signal or a direct current (DC) signal.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.
- (2) FIG. 1 is a diagram showing one example of an environment including a powered system and a process control system.
- (3) FIG. 2 is a diagram showing another example of an environment comprising a powered system and a process control system.
- (4) FIG. 3 is a diagram showing one example of an environment comprising a powered system

having multiple power busses and a process control system.

(5) FIG. 4 is a diagram showing one example of an environment comprising a powered system comprising two power supplies and a process control system.

(6) FIG. 5 is a flowchart showing one example of a process flow that may be executed, for example, in any of the environments of FIGS. 1-4 to monitor a powered system.

(7) FIG. 6 is a flowchart showing one example of a process flow that may be executed, for example, in any of the environments of FIGS. 1-4 to detect a deviation between observed system profile data and expected system profile data utilizing power profile data.

(8) FIG. 7 is a flowchart showing one example of a process flow that may be executed, for example, in any of the environments to detect a deviation between observed system profile data and expected system profile data utilizing spectrum data.

(9) FIG. 8 is a flowchart describing one example or a process flow that may be executed, for example, in any of the environments of FIGS. 1-4 to detect a deviation between observed system profile data and expected system profile data using a trained computerized model.

(10) FIG. 9 is a flowchart showing one example of a process flow showing how the processor may, in some examples, train the trained computerized model for detecting a mismatch between expected system profile data and observed system profile data.

(11) FIG. 10 is a flowchart showing one example of a process flow that may be executed, for example, in any of the environments of FIGS. 1-4 to monitor a powered system according to more than one expected system profile data set.

(12) FIG. 11 is a flowchart showing one example of a process flow that may be executed, for example, in any of the environments of FIGS. 1-4 to monitor a powered system considering an aging profile or the powered system.

(13) FIG. 12 is a diagram showing one example of an environment comprising a management system and a number of power supplies.

(14) FIG. 13 is a flowchart showing one example of a process flow that may be executed in the environment of FIG. 12 to enable a power supply for powered system monitoring.

(15) FIG. 14 is a flowchart showing one example of a process flow that may be executed, for example, in any of the environments of FIGS. 1-4 to detect a monitored activity at a powered system.

(16) FIG. 15 is a block diagram illustrating a computing device hardware architecture, within which a set or sequence of instructions can be executed to cause a machine to perform examples of any one of the methodologies discussed herein.

DESCRIPTION

(17) Systems utilizing a power supply, referred to herein as powered systems, may be vulnerable to various attacks. Consider an example powered system comprising a number of security cameras and a power supply. The security cameras may be programmed to execute a control loop that involves capturing images of a secure location or set of secured locations. According to an example attack, an attacker may modify software for controlling the security cameras. The modified software may, for example, falsify image data captured by the various security cameras, modify the field-of-view of the cameras, and/or otherwise change the output of security cameras. This may compromise the effectiveness with which the security cameras can monitor the secure location or locations, allowing the security system to be defeated.

(18) Consider another example powered system comprising a number of motors, sensors, actuators, and/or other components in an industrial system. The powered system may be arranged to perform all or part of an industrial process such as, for example, a manufacturing process, a chemical process, and/or the like. An attacker may modify the system, for example, by disabling or modifying one or more of the components and/or by modifying software operating the components so as to compromise the effectiveness of the industrial system. For example, the attacker may modify software accessing the sensors so as to provide false data to a process control system

monitoring the components. In other examples, the attacker may modify the software so as to sabotage the industrial process being performed by the powered system.

(19) Security for powered systems can be provided, for example, by securing any networks that might provide a malicious actor with access to the powered system and its components. In other examples, security for a powered system may include software-implemented security tools at the components themselves and/or at a process control system or other computing device associated with the powered system.

(20) Security techniques that involve securing networks and/or powered system components may be effective, but also suffer from certain disadvantages. For example, an attack against a powered system may involve modifying software executing at one or more of the system components. When security measures are implemented in software, those security measures themselves may be vulnerable to an attack that involves modifying the system software.

(21) Various examples address these and other challenges with a power supply that is programmed to monitor a powered system and detect anomalies in the powered system that may indicate a security breach, malfunction, or other abnormality in the operation of the powered system. For example, a power supply may comprise a regulator circuit that is configured to generate an output electrical signal, a sensor configured to generate at least one sensor signal describing the output electrical signal, and at least one processor. The processor may be programmed to compare the at least one sensor signal to expected system profile data. The expected system profile data describes the operation of the at least one component electrically coupled to the power supply such as, for example, a security camera, motor, sensor, actuator, and/or other component of a powered system. If the at least one sensor signal fails to match the expected system profile data, the power supply may execute a remedial action. Example remedial actions may include sending an alert message describing a deviation of the sensor signal from the expected system profile data, initiating a shutdown of the power supply, initiating a shutdown the powered system, and/or the like.

(22) The expected system profile data may describe the operation of the powered system according to its intended control routine. For example, the expected system profile data for a powered system may describe changes to the output electrical signal of the power supply over time as the powered system operates. For example, as the powered system operates over time, the power consumed by the various components changes, causing a corresponding change in the output electrical signal provided by power supply. For example, consider a powered system comprising a motor. If the motor is running, it may consume power and, thereby, cause an increase in voltage, current, power, or other measurable of the output electrical signal of the power supply. If the motor is not running, it may consume less power or no power, resulting in a corresponding decrease in the measurable of the output electrical signal.

(23) A powered system may operate according to a repeatable control routine. The expected system profile data may describe changes to the output electrical signal of the power supply over time as the repeated control routine executes. Deviations between the sensor signal(s) and the expected system profile data may occur, for example, when the current operation of the powered system does not match the expected operation of the control routine, as indicated by the expected system profile data.

(24) Consider the example powered system introduced above that comprises a number of security cameras. The system may execute a control routine that includes capturing a predetermined set and/or sequence of images using the various security cameras. This may result in expected system profile data indicating increases to the output electrical signal of the power supply at the points in time when the various security cameras are capturing respective images. If a malicious actor modifies the powered system, for example, to disable one or more of the security cameras, falsify images captured by one or more of security cameras, change the order of image capture, or otherwise modify the powered system, the power supply may detect the modification by detecting a deviation between the sensor signal and the expected system profile data.

(25) Also, consider again the example powered system comprising motors, sensors, actuators, and/or other components in an industrial system. As the powered system performs an industrial process, the various components may be operated according to a control routine that implements a repeating pattern. As various components are activated or deactivated, they may draw more or less power from the power supply. The expected system profile data for the powered system may indicate changes to the output electrical signal of the power supply during the industrial process. If a malicious actor modifies the powered system to disable, sabotage, or otherwise modify the industrial process, the power supply may detect the modification by detecting a deviation between the sensor signal and the expected system profile data.

(26) In various examples, the systems and methods described herein may also be used for detecting malfunctions in a powered system. For example, just as an attack from a malicious actor may cause the one or more sensor signals to deviate from the expected system profile data, a malfunction in the powered system may also cause such a deviation. Various examples described herein may detect deviations from the expected system profile of a powered system that are due to malfunctions, only where, and/or other reasons.

(27) FIG. 1 is a diagram showing one example of an environment **100** including a powered system **101** and a process control system **104**. The powered system **101** comprises a power supply **102** and a load **106**. The load **106** may comprise a set of one or more components of the powered system **101**. The one or more components may include various sensors, motors, pumps, actuators, and/or the like. Additional details and examples describing the load **106** are provided herein with respect to FIG. 2.

(28) The power supply **102** receives an input electrical signal **116** relative to a ground **118**. The input electrical signal **116** may be described by a voltage, a current, a power, and/or other suitable metric or metrics. The input electrical signal **116** may be an AC or DC signal. A regulator circuit **105** receives the input electrical signal **116** and generates an output electrical signal **120** that may be measured relative to an output common **122**. The output electrical signal **120** is provided to the load **106**.

(29) The input electrical signal **116** and output electrical signal **120** may be of different types such as different voltage levels, different current levels, different polarities, and/or the like. In some examples, the regulator circuit **105** is an AC/AC regulator that receives an AC input electrical signal **116** and generates an AC output electrical signal **120**, for example, at a different voltage level than the input electrical signal **116**, a different current level than the input electrical signal **116**, a different frequency than the input electrical signal **116**, a different polarity than the input electrical signal **116**, and/or the like. In some examples, the regulator circuit **105** is a DC/DC regulator that receives an DC input electrical signal **116** and generates a DC electrical output signal **120**, for example, at a different voltage level than the input electrical signal **116**, a different current level than the input electrical signal **116**, and/or the like. In some examples, the regulator circuit **105** is an AC/DC regulator that receives an AC input electrical signal **116** and generates a DC output electrical signal **120**. Example types of AC/DC regulators include linear regulators, switch-mode regulators, capacitive regulators, and/or the like.

(30) The power supply **102** also includes sensors **108**, **110**, **111** and at least one processor **114**. An input sensor **108** may sense the input electrical signal **116**. For example, the input sensor **108** may sense a voltage level of the input electrical signal **116**, a current level of the input electrical signal **116**, or other suitable property of the input electrical signal **116**. An output sensor **110** may sense the output electrical signal **120**. The output sensor **110** may sense a voltage level of the output electrical signal **120**, a current level of the output electrical signal **120**, or other suitable property of the output electrical signal **120**. An output common sensor **111** may sense a return signal from the load **106** received at the output common **122**. For example, the output electrical signal may be a difference between the signal generated by the output sensor **110** and the signal generated by the output common sensor **111**.

(31) The input sensor **108**, output sensor **110**, and common output sensor **111** may be of any suitable type. In the example of FIG. **1**, the input sensor **108**, output sensor **110**, and common output sensor **111** are analog sensors generating analog sensor signals. The analog sensor signals are provided to an analog-to-digital (A/D) converter **112** that converts the respective sensor signals to digital signals that are provided to the processor **114**. In some examples, one or more of the sensors **108**, **110**, **111** are digital sensors that provide a digital signal directly to the processor **114**.

(32) The processor **114** may be programmed to manage the operation of the power supply **102**. For example, the processor **114** may be configured to provide a control signal to the regulator circuit **105** to cause the regulator circuit **105** to modify the output electrical signal **120**. In this way, the power supply **102** may maintain a desirable output electrical signal **120** despite, for example, changes in behavior and/or properties of the load **106**, changes in the input electrical signal **116**, and/or the like. In some examples, components of the power supply **102** may be fully or partially contained within an enclosure. The enclosure may be made from any suitable material such as, for example, a metal, a plastic, a composite, and/or the like.

(33) In the example of FIG. **1**, the processor **114** is also programmed to perform monitoring of the power supply system, including the load **106**. The processor **114** may receive and/or generate expected system profile data describing the operation of the load **106**. The expected system profile data may describe an expected output electrical signal **120** of the power supply **102** over time, such as over one or more control routine cycles of the powered system **101**. As described herein, changes to the output electrical signal **120** of the power supply over time may be caused by changes in the operation of components making up the load **106**. The expected system profile data may describe an expected behavior of the load **106**, as expressed by the output electrical signal **120**. The expected system profile data, in some examples, is determined by the processor **114** based on observations of the behavior of the load **106**. In other examples, the expected system profile data is received by the processor **114** from another component such as, for example, the process control system **104**.

(34) Expected system profile data may be expressed in any suitable manner. In some examples, the expected system profile data comprises power profile data of the load **106** describing one or more metrics of the output electrical signal **120** over one or more time periods. For example, the expected system profile data may describe a current of the output electrical signal **120** over time, a voltage of the output electrical signal **120** over time, a power provided by the output electrical signal **120** over time, and/or the like. In some examples, the expected system profile data comprises a spectrum or power signature of the load **106**. The spectrum of the load **106** indicates a frequency content of the output electrical signal **120**.

(35) The expected system profile data may describe power profile data of the output electrical signal **120**, spectrum data of the output electrical signal **120**, or both over one or more time periods. The time period may correspond to one or more control routine cycles of the components of the load **106**. Consider again the powered system example including security cameras. One control routine cycle of the powered system may include, for example, capturing an image from each of the security cameras. Also consider the powered system example including components for executing an industrial process. One control routine cycle of the powered system may include, for example, one instance or unit of the industrial process.

(36) The processor **114** may receive sensor signals from one or more of the sensors **108**, **110**, **111** and generate observed system profile data. The observed system profile data may describe one or more properties of the output electrical signal **120** provided to the load **106** as sensed by one or more of the sensors **108**, **110**, **111** in a present time period. In some examples, the processor **114** may express the observed system profile data as a power profile of the output electrical signal **120** over a measured time period, a spectrum of the output electrical signal **120** over a measured time period, and/or both. For example, the processor **114** may receive data from one or more of the sensors **108**, **110**, **111** over a time period corresponding to one or more control routine cycles of the

powered system **101**. The processor **114** may derive power profile data describing the powered system **101** over the time period and/or a spectrum of the output electrical signal **120** over the time period. In some examples, the processor **114** may derive an observed spectrum by applying a transform to the one or more sensor signals such as, for example, a Fast Fourier Transform (FFT), a Short Time Fourier Transform (STFT), or other suitable algorithm.

(37) An example representation of an STFT transform that may be used to derive an observed spectrum from one or more sensor signals is provided by Equation [1] below:

$$(38) \text{ STFT} = \{x[n]\}(m, w) = \text{Math.} \sum_{n=-\infty}^{+\infty} x[n]w[n-m]e^{jn} \quad [1]$$

In Equation [1], the STFT transform is taken over a time window indicated by window function $w[n-m]$. Accordingly, the expected spectrum and observed spectrum may be measured over a series of multiple time windows, which may provide a comparison of frequency content and time.

(39) The processor **114** may compare the sensor signals, as represented by the observed system profile data, to the expected system profile data. This may include time-aligning the observed system profile data and the expected system profile data. FIG. **1** includes a breakout window **126** depicting plots **128**, **130**, **132**, **134** illustrating an example comparison between observed system profile data and expected system profile data. The plots **128**, **130** describe power profile data, with the plot **128** describing an observed metric of the output electrical signal **120** over time and the plot **130** representing expected values for the metric of the output electrical signal **120** over time. In the plots **128**, **130**, the horizontal axis corresponds to time and the vertical axis corresponds to power consumption, current, voltage, and/or the like. Plots **132**, **134** describe spectrums, with the plot **132** describing a spectrum from an observed system profile data (an observed spectrum) and the plot **134** describing a spectrum from expected system profile data (an expected spectrum). In the plots **132**, **134**, the horizontal axis represents frequency and the vertical axis represents time.

(40) The processor **114** may be configured to compare observed system profile data and expected system data, for example, by comparing power profile data of the expected and observed system profile data, spectrums of the expected and observed system profile data, and/or other properties of the observed system profile data and the expected system profile data. If the observed system profile data matches the expected system profile data, it may indicate that the powered system **101**, including the components of the load **106**, are operating as expected. If the observed system profile data does not match the expected system profile data, it may indicate that the components of the load **106** are not operating as expected. This may occur, for example, if the powered system is misconfigured, malfunctioning, or compromised by an attack from a malicious actor.

(41) When the processor **114** determines that the observed system profile data does not match the expected system profile data, it may perform a remedial action. In some examples, the remedial action comprises sending an alert message **124** to a process control system **104**. The alert message **124** may describe a deviation between the observed system profile data and the expected system profile data. The process control system **104** may, in some examples, use the alert message **124** to perform an additional remedial action such as, for example, providing an alert to appropriate personnel, shutting down the power supply **102**, shutting down one or more components of the load **106**, and/or the like. In some examples, the remedial action performed by the processor **114** may include shutting down the power supply **102**, shutting down one or more components of the load **106**, and/or the like.

(42) FIG. **2** is a diagram showing one example of an environment **200** comprising a powered system **201** and a process control system **204**. The powered system comprises a power supply **202** providing an output electrical signal to a load comprising various components **250**, **252**, **254**, **256**, **258**. A power supply **202** comprises a processor **214** and may be programmed to perform powered system monitoring, as described herein. For example, the processor **214** may receive one or more sensor signals describing an output electrical signal or other indicator of an output electrical signal of the power supply **202**. The processor **214** may compare the at least one sensor signal (e.g.,

observed system profile data derived from the at least one sensor signal) to expected system profile data for the powered system **201**, as described herein. If there is no match to the expected system profile data, the processor **214** may execute a remedial action, as described herein. For example, the remedial action may include sending an alert message to **224** to a process control system **204**, shutting down the power supply **202**, shutting down one or more of the **250, 252, 254, 256, 258**, and/or the like.

(43) The components **250, 252, 254, 256, 258** provide examples of components that may be part of the load of a powered system. For example, component **250** may include one or more cameras or other image sensors. Component **252** may include one or more motors, actuators, and/or the like. Component **254** may include one or more pumps, compressors, and/or the like. Component **256** may comprise one or more sensors. Component **258** may comprise one or more heaters, heating elements, and/or the like. The example components **250, 252, 254, 256, 258** provide examples of components that may make up a load of a powered system. It will be appreciated that, in various examples, a powered system may comprise various different combinations of example components **250, 252, 254, 256, 258** and/or other components in various numbers.

(44) FIG. 3 is a diagram showing one example of an environment **300** comprising a powered system **301** and a process control system **304**. The powered system **301** comprises a power supply **302** provides an output electrical signal to a load comprising various components **360, 362, 364, 366, 368, 370**. The power supply **302** comprises a processor **314** and may be programmed to perform powered system monitoring, as described herein. For example, the processor **314** may receive one or more sensor signals describing an output electrical signal or other indicator of an output electrical signal of the power supply **302**. The processor **314** may compare the at least one sensor signal (e.g., observed system profile data derived from the at least one sensor signal) to expected system profile data for the powered system **301**, as described herein. If there is no match to the expected system profile data, the processor **314** may execute a remedial action, as described herein. For example, the remedial action may include sending an alert message to **324** to a process control system **304**, as described herein.

(45) In the example environment **300**, the power supply **302** comprises two power buses **303, 305**. The power bus **303** may provide power to components **360, 362, 364** and the power bus **305** may provide power to components **366, 368, 370**. The power buses **303, 305** may provide different output electrical signals to the respective components. For example, the power bus **303** may provide an output electrical signal at a first voltage and the power bus **305** may provide an output electrical signal at a second voltage different than the first voltage. Also, in some examples, the power bus **303** may provide an output electrical signal that can support a first maximum current and the power bus **305** may provide an electrical signal that can support a second maximum current different than the first maximum current. The power supply **302** may comprise sensors for monitoring both power buses **303, 305**. Also, although two power buses **303, 305** are shown, it will be appreciated that power supplies **302** may have and may more than two power buses.

(46) The processor **314** may be programmed to analyze system profile data describing both the power bus **303** and the power bus **305**. In some examples, the expected system profile data may comprise expected system profile data describing the power bus **303** and distinct expected system profile data describing the power bus **305**. Processor **314** may collect respective observed system profile data describing each of the power buses **303, 305** individually. The processor **314** may be programmed to detect a deviation between the expected system profile data and the observed system profile data if a deviation is detected with respect to the power bus **303** or with respect to the power bus **305**. In some examples, the processor **314** may be programmed to detect a deviation between the expected system profile data and the observed system profile data for the power supply only if a deviation is detected with respect to both the power bus **303** and the power bus **305**. Also, in some examples, behavior of the power buses **303, 305** may be described by common expected system profile data and observed system profile data. The processor **314** may be programmed to

compare the common expected system profile data and the observed system profile data, for example, as described herein.

(47) FIG. 4 is a diagram showing one example of an environment **400** comprising a powered system **401** comprising two power supplies **402A**, **402B** and a process control system **404**. The power supply **402A** provides power to components **480**, **482**, **484**. The power supply **402B** provides power to components **486**, **488**, **490**. The power supplies **402A**, **402B** comprise respective processors **414A**, **414B** that may be programmed to perform power system monitoring, for example, as described herein. For example, the processor **414A** may receive one or more sensor signals describing an output electrical signal or other indicator of an output electrical signal of the power supply **402A**. The processor **414A** may compare the at least one sensor signal (e.g., observed system profile data derived from the at least one sensor signal) to expected system profile data for the components **480**, **482**, **484**. If there is no match to the expected system profile data, the processor **414A** may execute a remedial action, such as, for example, sending an alert message **424A** to a process control system **404**. The processor **414B** may compare the at least one sensor signal (e.g., observed system profile data derived from the at least one sensor signal) to expected system profile data for the components **486**, **488**, **490**. If there is no match to the expected system profile data, the processor **414B** may execute a remedial action, such as, for example, sending an alert message **424B** to a process control system **404**.

(48) In some examples, the respective processors **414A**, **414B** may access separate expected system profile data. For example, the processor **414A** may access expected system profile data describing the components **480**, **482**, **484**. The processor **414A** may generate observed system profile data for the components **480**, **482**, **484** and compare the observed system profile data to the corresponding expected system profile data to determine a deviation, if any. In parallel, the processor **414B** may access expected system profile data describing the components **486**, **488**, **490** and may generate observed system profile data for the components **486**, **488**, **490**. The processor **414B** may compare the observed system profile data to the corresponding expected system profile data to determine a deviation if any. In some examples, one of the processors **414A**, **414B** compares expected system profile data and observed system profile data describing the powered system **401** as a whole. For example, one processor **414A**, **414B** may provide the other processor **414A**, **414B** with observed sensor data and/or observed system profile data captured at the respective power supply **402A**, **402B**.

(49) In another example embodiment, the processors **414A**, **414B** may be programmed to gather observed system profile data describing the respective components **480**, **482**, **484**, **486**, **488**, **490** and provide the observed system profile data to the process control system **404**. The process control system **404** may access expected system profile data describing all of the components **480**, **482**, **484**, **486**, **488**, **490**. The process control system **404** may compare the observed system profile data received from the respective processors **414A**, **414B** to detect a deviation, if any.

(50) FIG. 5 is a flowchart showing one example of a process flow **500** that may be executed, for example, in any of the environments **100**, **200**, **300**, **400** to monitor a powered system. For example, the process flow **500** may be performed by a processor of a power supply, such as by one or more of the processors **114**, **214**, **314**, **414A**, **414B**. At operation **502**, the processor accesses expected system profile data. The expected system profile data describes the output electrical signal (or signals) provided to components of a powered system over time. The expected system profile data may be generated in any suitable manner. In some examples, the expected system profile data is generated deterministically based on expected operation of the powered system. In other examples, the expected system profile data is determined by observation of the operation of the powered system and/or of one or more other equivalent powered systems. As described herein, the expected system profile data may indicate, for example, one or more peak patterns, one or more spectrums, and/or the like.

(51) At operation **504**, the processor observes the operation of the powered system. This may

include, for example, receiving sensor signals from one or more sensors such as, for example, the input sensor **108**, the output sensor **110**, and/or the output common sensor **111**. The processor may perform various preprocessing on the sensor signals. For example, the processor may apply an FFT, STFT, or other suitable algorithm for finding a spectrum of the powered system using the one or more sensor signals. In some examples, the processor may compile the received sensor signal or signals to generate a power profile of the powered system. The observation at operation **504** may result in observed system profile data describing the operation of the powered system.

(52) At operation **506**, the processor may compare the observed system profile data and the expected system profile data. This may include various different comparisons including, for example, as described with respect to FIGS. **6-8**. At operation **508**, the processor may determine if a difference between the observed system profile data and the expected system profile data is greater than a threshold difference. The threshold may be determined in any suitable manner, for example, as described herein with respect to FIGS. **6-8**. If the difference between the observed system profile data and the expected system profile data is greater than the threshold distance, then the processor may execute a remedial action at operation **510**. If the difference between the observed system profile data and the expected system profile data is not greater than the threshold difference, then the processor may continue to observe the powered system at operation **504**.

(53) FIG. **6** is a flowchart showing one example of a process flow **600** that may be executed, for example, in any of the environments **100, 200, 300, 400** to detect a deviation between observed system profile data and expected system profile data. For example, FIG. **6** shows one example way of executing the operations **506, 508** from the process flow **500**. In the example of FIG. **6**, the expected system profile data comprises an expected peak pattern. The expected peak pattern describes magnitudes and positions for peaks in the output electrical signal generated by the power supply according to expected operation of the powered system (e.g., according to one or more cycles of the control routine. Individual peaks of the peak pattern may indicate a peak in current drawn from the power supply, a peak in voltage provided by the power supply, a peak in power provided by the power supply, and/or the like.

(54) At operation **602**, a processor associated with the power supply may detect an observed peak pattern from one or more sensor signals at the power supply. The observed peak pattern may indicate magnitudes and positions for peaks in the output electrical signal generated by the power supply. At operation **604**, the processor may compare the observed peak pattern to the expected peak pattern. Various different comparison techniques may be used. In some examples, the processor may attempt to match individual peaks. For example, the processor may match individual peaks from the expected peak pattern to corresponding peaks in the observed peak pattern. An individual peak from the observed peak pattern may match an individual peak from the expected peak pattern if its position in time is within a time threshold of the individual peak from the expected peak pattern and its magnitude is within a magnitude threshold of the individual peak from the expected peak pattern.

(55) At operation **606**, the processor may determine if a difference between the expected peak pattern and the observed peak pattern is greater than a threshold. The difference may be expressed in various different ways. In some examples, the difference is expressed as a number of peaks from the observed peak pattern that match corresponding peaks in the expected peak pattern. In other examples, the differences expressed are based on differences between corresponding peaks in the observed peak pattern and the expected peak pattern. For example, each attempted match between a peak in the observed peak pattern and a corresponding peak in the expected peak pattern may be described by a time difference and a magnitude difference. This may be converted to a cumulative difference over the observed peak pattern.

(56) If the difference between the expected peak pattern and the observed peak pattern is greater than the threshold, then the processor may return an indicator that the observed peak pattern does not match the expected peak pattern at operation **608**. If the difference between the expected peak

pattern and the observed peak pattern is not greater than the threshold at operation **606**, the processor may, at operation **610**, return an indication that there was no detected deviation between the expected peak pattern and the observed peak pattern.

(57) FIG. 7 is a flowchart showing one example of a process flow **700** that may be executed, for example, in any of the environments **100**, **200**, **300**, **400** to detect a deviation between observed system profile data and expected system profile data. For example, FIG. 7 shows another example way of executing the operations **506**, **508** from the process flow **500**. In the example of FIG. 7, the expected system profile data comprises spectrum data describing an expected spectrum of the electrical output signal generated by the power supply. The expected spectrum may indicate a frequency content of the electrical output signal. The expected spectrum may be based on any suitable metric describing the electrical output signal generated by the power supply such as, for example, current drawn from the power supply, voltage provided by the power supply, power provided by the power supply, and/or the like.

(58) At operation **702**, the processor may detect an observed spectrum of the power supply. The observed spectrum may be generated from sensor signals provided by one or more sensors such as, for example, one or more of the sensors **108**, **110**, **111**. Detecting the observed spectrum may involve converting one or more received sensor signals from the time to the frequency domain. This may include applying a transformed algorithm such as, for example, an FFT or STFT algorithm.

(59) At operation **704**, the processor may compare the observed spectrum to an expected spectrum indicated by the expected system profile data. In some examples, comparing an observed spectrum to an expected spectrum may include determining a distance metric describing a distance between the observed spectrum and the expected spectrum. If, at operation **706**, the distance metric is greater than a threshold, then, at operation **708**, the processor may return an indication of a mismatch between the observed spectrum and the expected spectrum. If, at operation **706**, the distance metric is not greater than the threshold, then, at operation **710**, the processor may return an indicator of no mismatch between the observed spectrum in the expected spectrum.

(60) One example way of determining a distance metric between an expected spectrum and an observed spectrum includes binning the expected spectrum and the observed spectrum and comparing corresponding frequency bins. The frequency bins may be selected in any suitable manner. In some examples, the spectrum may be divided into a series of equal frequency bins. Corresponding frequency bins between the expected spectrum and the observed spectrum may be frequency bins over an equivalent range of frequencies. The distance metric may consider each set of corresponding frequency bins and determine whether the bins are paired or isolated. Initially, the processor may determine whether a considered set of corresponding frequency bins are paired. In some examples, two corresponding bins may be considered paired if the condition of Expression [2] is met and isolated if the condition of Expression [2] is not met.

$$(61) \quad b_e \cdot \text{freq} - b_o \cdot \text{freq} < \text{threshold} \quad [2]$$

In Expression [2], b_e indicates a frequency bin from the expected spectrum and b_o indicates a corresponding frequency bin from the observed spectrum. If the two considered frequency bins are paired, a distance metric for the bins may be determined based on the frequency and amplitude of the paired frequency bins, for example, according to Equation [3] below:

$$(62) \quad \text{Dist}_{\text{paired}} += \text{Math. } b_e \cdot \text{freq} - b_o \cdot \text{freq} \cdot \text{Math. } * \cdot \text{Math. } b_e \cdot \text{amp} - b_o \cdot \text{amp} \cdot \text{Math.} \quad [3]$$

If the considered frequency bins are not paired, and therefore considered isolated, a distance metric for the frequency bins may be determined, for example, according to Equation [4] below:

$$(63) \quad \text{Dist}_{\text{isolated}} += \text{thresh} + \text{Math. } \frac{b_e}{b_o} \cdot \text{amp} - \text{Avg}(\frac{ES}{OS}) \cdot \text{Math.} \quad [4]$$

In Equation [4], $b_o/b_e \cdot \text{Math. amp}$ describes a ratio of the amplitude of the corresponding frequency bins. $\text{Avg}(\frac{OS}{ES})$ describes an average ratio of amplitudes over all frequency

bins. In this way, the processor may determine a distance metric for each set of corresponding frequency bins.

(64) In addition to determining distance metrics for each corresponding set of frequency bins, the processor may determine a distance between the average amplitude of the expected spectrum and the average amplitude of the observed spectrum, for example, as provided by Equation [5] below:

$$(65) \text{ } Dist_{avg} = .\text{Math. Avg}(ES) = \text{Avg(OS) } .\text{Math.} \quad [5]$$

In this example, the total distance metric between the expected spectrum and the observed spectrum may be found by summing the distance metrics for paired frequency bins, the distance metrics for isolated frequency bins, and the average distance between the two spectrums, for example, as shown by Equation [6] below:

$$(66) \text{ } Dist_{oe} = Dist_{paired} + Dist_{isolated} + Dist_{avg} \quad [6]$$

(67) In some examples, such as those utilizing the STFT transform, an expected spectrum and observed spectrum may be taken over a plurality of time windows. When this occurs, the processor may determine a difference between the expected spectrum and the observed spectrum, for example, by determining a distance metric as described herein with respect to Equations/Expressions [2]-[6]. Distance metrics over all considered time windows may be summed to provide a total distance metric describing a distance between the observed spectrum and the expected spectrum over all time windows.

(68) FIG. 8 is a flowchart describing one example or a process flow **800** that may be executed, for example, in any of the environments **100, 200, 300, 400** to detect a deviation between observed system profile data and expected system profile data using a trained computerized model. For example, FIG. 8 shows one example way of executing the operations **506, 508** from the process flow **500**.

(69) At operation **802**, the processor may gather observed system profile data. The observed system profile data may include any data describing the powered system such as, for example, one or more sensor signals from one or more sensors **108, 110, 111**. At operation **804**, processor may access a trained computerized model. The trained computerized model may be any suitable type of model such as, for example, a supervised learning model or an unsupervised learning model. In some examples, the trained computerized model is a classification model that is trained to receive observed system profile data as an input or inputs and return an indication of whether the observed system profile data matches expected system profile data for the powered system. Example classification model algorithms that may be used include, for example, logistic regression models, k-nearest neighbor models, decision tree models, support Vector machine models, naïve Bayes models, and/or the like.

(70) The computerized model, in some examples, is trained by the processor. For example, the processor may access training data. The training data may be or include the expected system profile data describing expected and/or typical operation range of the powered system. The processor may utilize the expected system profile data to train the computerized model to return an output indicating whether observed system profile data matches or does not match the expected system profile data range.

(71) At operation **806**, the processor may execute the trained computerized model using the observed system profile data as input. The executed computerized model may provide an output classifying the observed system profile data as matching or not matching the expected system profile data. If, at operation **808**, the output of the trained computerized model indicates that the observed system profile data matches the expected system profile data, then the processor may, at operation **810**, return an indication of no mismatch. If, at operation **808**, the output of the trained computerized model indicates that the observed system profile data does not match the expected system profile data, then the processor may, at operation **812**, return an indication of a mismatch. Returning an indication of a mismatch may indicate that the monitoring system has detected that

the powered system is operating outside of the expected normal operation profile range.

(72) FIG. **9** is a flowchart showing one example of a process flow **900** showing how the processor may, in some examples, train the trained computerized model for detecting a mismatch between expected system profile data and observed system profile data. At operation **902**, the processor may gather observed system profile data. The observed system profile data may be gathered utilizing sensor signals from one or more sensors, such as sensors **108**, **110**, **111**. At operation **904**, the processor may receive an indicator that the powered system was operating within accepted parameters during the gathering of the observed system profile data at operation **902**. For example, a human user may verify the correct operation of the powered system and provide an indication of the correct operation to the processor.

(73) Based on the indicator of acceptable system operation, the processor may utilize the observed system profile data as training data indicating expected system profile data. The processor, at operation **906**, may utilize the observed system profile data to train the computerized model. In some examples, the process flow **900** may be re-executed on a periodic basis. For example, the processor **114** may, at operation **906**, retrain an existing model utilizing the additional observed system profile data that has been verified as acceptable at operation **904**.

(74) In some examples, a power supply (e.g., a processor thereof) may be programmed to compare observed system profile data against more than one set of expected system profile data. For example, a powered system may operate according to one or more known modifications. Consider the example powered system including security cameras. In some examples, the powered system may modify its sequence of operations, for example, based on received image data. For example, if an image from one or more of the security cameras depicts an anomaly, the powered system may be programmed to capture an additional image from the same security camera before continuing with its normal control routine. Consider also the example powered system for implementing an industrial process. The industrial process may comprise one or more contingencies during which the powered system will operate differently, for example, depending upon the results of an earlier stage of the routine.

(75) FIG. **10** is a flowchart showing one example of a process flow **1000** that may be executed, for example, in any of the environments **100**, **200**, **300**, **400** to monitor a powered system according to more than one expected system profile data set. The process flow **1000** may be performed by a processor of a power supply, such as by one or more of the processors **114**, **214**, **314**, **414A**, **414B**.

(76) At operation **1002**, the processor accesses first expected system profile data. The first expected system profile data describes the output electrical signal (or signals) provided to components of a powered system over time. At operation **1004**, the processor observes the operation of the powered system. This may include, for example, receiving sensor signals from one or more sensors such as, for example, the input sensor **108**, the output sensor **110**, and/or the output common sensor **111**.

The processor may perform various preprocessing on the sensor signals. For example, the processor may apply an FFT, STFT, or other suitable algorithm for finding a spectrum of the powered system using the one or more sensor signals. In some examples, the processor may compile the received sensor signal or signals to generate a power profile of the powered system. The observation at operation **1004** may result in observed system profile data describing the operation of the powered system.

(77) At operation **1006**, the processor may compare the observed system profile data and the first expected system profile data. This may include various different comparisons including, for example, as described with respect to FIGS. **6-8**. At operation **1008**, the processor may determine if a difference between the observed system profile data and the first expected system profile data is greater than a threshold difference. The threshold may be determined in any suitable manner, for example, as described herein with respect to FIGS. **6-8**. If the difference between the observed system profile data and the first expected system profile data is greater than the threshold distance, then the processor may execute a remedial action at operation **1010**. If the difference between the

observed system profile data and the first expected system profile data is not greater than the threshold difference, then the processor may continue to observe the powered system at operation **1004**.

(78) If the difference between the observed system profile data and the first expected system profile data is greater than the threshold distance, then the processor may, at operation **1010**, compare the observed system profile data to a modified expected system profile data describing a first known modification to the operation of the powered system. If, at operation **1012**, the deviation between the observed system profile data and the modified expected system profile data is not greater than a threshold, the processor may continue to observe the powered system at operation **1004**. If, at operation **1012**, the deviation between the observed system profile data and the modified expected system profile data is greater than the threshold, then the processor may execute a remedial action at operation **1014**.

(79) Although the process flow **1000** shows two sets of expected system profile data (the first expected system profile data and the modified expected system profile data), it will be appreciated that a power supply may compare observed system profile data to more than two sets of expected system profile data (for example, if there are more than two known modifications to the behavior of the powered system).

(80) In some examples, the operation of a powered system changes over time as the components age. For example, a new electric motor may draw power differently than an equivalent electric motor in which the various electrical and/or mechanical components of the electric motor have aged. As components of the powered system age, the observed system profile data may begin to deviate from the expected system profile data by virtue of the aging. In various examples, a power supply may be programmed to compensate for aging of components and powered system.

(81) FIG. **11** is a flowchart showing one example of a process flow **1100** that may be executed, for example, in any of the environments **100**, **200**, **300**, **400** to monitor a powered system considering an aging profile of the powered system. For example, the process flow **1100** may be performed by a processor of a power supply, such as by one or more of the processors **114**, **214**, **314**, **414A**, **414B**.

(82) At operation **1102**, the processor accesses expected system profile data. The expected system profile data describes the output electrical signal (or signals) provided to components of a powered system over time. At operation **1104**, the processor applies an aging profile to the expected system profile data. This may include, for example, applying a modification to the expected system profile data based on an age of the powered system. The age may be expressed in any suitable manner such as, for example, a chronological age, a number of control routine cycles executed, and/or the like. In some examples utilizing a trained computerized model, such as described herein with respect to FIG. **7**, the age of the powered system may be provided as an input to the trained computerized model in addition to or instead of applying the aging profile to the expected system profile data. Also, in some examples, processor **114** may receive, store, or otherwise access different sets of expected system profile data based on the age of the powered system. In this way, the processor may not affirmatively apply an aging profile to expected system profile data, but may instead access expected system profile data corresponding to the current age of the powered system.

(83) At operation **1106**, the processor observes the operation of the powered system. This may include, for example, receiving sensor signals from one or more sensors such as, for example, the input sensor **108**, the output sensor **110**, and/or the output common sensor **111**. The processor may perform various preprocessing on the sensor signals. For example, the processor may apply an FFT, STFT, or other suitable algorithm for finding a spectrum of the powered system using the one or more sensor signals. In some examples, the processor may compile the received sensor signal or signals to generate a power profile of the powered system. The observation at operation **1106** may result in observed system profile data describing the operation of the powered system.

(84) At operation **1108**, the processor may compare the observed system profile data and the

expected system profile data, as corrected for the age of the powered system. This may include various different comparisons including, for example, as described with respect to FIGS. **6-8**. At operation **1110**, the processor may determine if a difference between the observed system profile data and the expected system profile data is greater than a threshold difference. The threshold may be determined in any suitable manner, for example, as described herein with respect to FIGS. **6-8**. If the difference between the observed system profile data and the expected system profile data is greater than the threshold distance, then the processor may execute a remedial action at operation **1112**. If the difference between the observed system profile data and the expected system profile data is not greater than the threshold difference, then the processor may continue to observe the powered system at operation **1106**. In some examples, as the age of the powered system changes, the processor may periodically re-execute operations **1102** and **1104**.

(85) In some examples, a power supply comprising a processor may be pre-programmed to perform powered system monitoring, as described herein. However, not every user of the power supply may desire to perform powered system monitoring. In various examples, a management system may be utilized to selectively enable and/or disable powered system monitoring in power supplies, for example, power supplies that have been installed to operate with powered systems.

(86) FIG. **12** is a diagram showing one example of an environment **1200** comprising a management system **1202** and a number of power supplies **1204**, **1206**, **1208**. Power supplies **1204**, **1206**, **1208** may comprise respective processors **1210**, **1212**, **1214** that are programmed to perform powered system monitoring as described herein. The management system **1202** and power supplies **1204**, **1206**, **1208** are in communication via a communications network **1222**. The communications network **1222** may be any suitable wired or wireless communication network, for example, similar to the communications network **1526** described herein. The management system **1202** may be a programmed computing device that is programmed to manage the power supplies **1204**, **1206**, **1208**. In some examples, the management system **1202** may be implemented by a manufacturer of the power supplies **1204**, **1206**, **1208**. The management system **1202** may be programmed to provide respective enablement messages **1216**, **1218**, **1220** to power supplies **1204**, **1206**, **1208** to enable the power supplies for powered system monitoring.

(87) FIG. **13** is a flowchart showing one example of a process flow **1300** that may be executed in the environment **1200** to enable a power supply **1204**, **1206**, **1208** for powered system monitoring. The process flow **1300** comprises two columns **1301**, **1303**. The column **1301** includes operations that are executed by a management system, such as the management system **1202**. The column **1303** includes operations that are executed by a power supply, such as one of the power supplies **1204**, **1206**, **1208**.

(88) At operation **1302**, the management system may receive a request to enable powered system monitoring at a power supply. The request may be received, for example, from a proprietor of the power supply who desires to utilize the powered system monitoring capabilities. The request may include an indicator of the power supply to be enabled for system monitoring. For example, the request message may include a serial number, Universal Resource Locator (URL), or other suitable indicator of each power supply to be enabled. In some examples, a single request may indicate multiple power supplies.

(89) At operation **1304**, the management system may send an enable message **1305** to the power supply. The enable message **1305** may include an enablement instruction that instructs the power supply to begin performing powered system monitoring, for example, as described herein. In some examples, the enable message **1305** also includes cryptographic data that may be utilized by the power supply to authenticate the enablement message **1305**.

(90) The power supply may receive the enable message **1305** at operation **1306** and may, at operation **1308**, activate power anomaly monitoring at operation **1308**. In examples in which the enable message **1305** comprises cryptographic data, the power supply may verify the cryptographic data prior to activating power anomaly monitoring. For example, the cryptographic data may

comprise a digital signature cryptographically generated (e.g., by the management system) using a private key associated with the management system. The power supply (e.g. the processor thereof) may access a public key associated with the management system and utilize the public key to decrypt the digital signature and thereby authenticate the enable message **1305**.

(91) In some examples, a processor of a power supply may be programmed to detect one or more particular activities in a powered system. Consider an example in which one or more components of the powered system are provided with access to a communications network. Particular actions to access the component via the communications network may be an indicator of potentially nefarious activity. For example, access to a particular communications port at a component during operation of the powered system may be an indicator of improper or mistaken activity.

(92) In various examples, the processor may be programmed to detect monitored activities, for example, by comparing observed system profile data to monitored activities signature data describing one or more monitored activities. If a monitored activity is detected, the processor may implemented a remedial action, for example, as described herein.

(93) FIG. **14** is a flowchart showing one example of a process flow **1400** that may be executed, for example, in any of the environments **100**, **200**, **300**, **400** to detect a monitored activity at a powered system. For example, the process flow **1400** may be performed by a processor of a power supply, such as by one or more of the processors **114**, **214**, **314**, **414A**, **414B**. At operation **1402**, the processor may access monitored activity signature data. The monitored activity signature data may describe the operation of the powered system when one or more monitored activities are occurring. In some examples, the monitored activity signature data may be similar to the expected system profile data albeit indicating a particular activity or activities.

(94) At operation **1404**, the processor observes the operation of the powered system. This may include, for example, receiving sensor signals from one or more sensors such as, for example, the input sensor **108**, the output sensor **110**, and/or the output common sensor **111**. The processor may perform various preprocessing on the sensor signals. For example, the processor may apply an FFT, STFT, or other suitable algorithm for finding a spectrum of the powered system using the one or more sensor signals. In some examples, the processor may compile the received sensor signal or signals to generate a power profile of the powered system. The observation at operation **1404** may result in observed system profile data describing the operation of the powered system.

(95) At operation **1406**, the processor may compare the observed system profile data and the monitored activity signature data. This may include various different comparisons. For example, if the monitored activity signature data comprises spectrum data, the processor may compare the spectrum data to a spectrum indicated by the observed system profile data. Also, if the monitored activity signature data comprises power profile data, the processor may compare the power profile data to a power profile indicated by the observed system profile data. Also, in some examples, monitored activity signature data may include a trained computerized model. Comparing the observed system profile data to the monitored activity signature data may comprise executing the model while providing some or all of the observed system profile data as inputs to the model. An output of the model may classify the observed system profile data as indicating a monitored activity or not indicating a monitored activity.

(96) In some examples, the monitored activity signature data may indicate a single monitored activity or may indicate multiple monitored activities. Comparison of the observed system profile data to the monitored activity signature data may provide a binary result (e.g., monitored activity detected or not detected). In some examples, when a monitored activity is detected, the processor may provide an indication of a particular monitored activity that is detected.

(97) At operation **1408**, the processor may determine whether there is a match between the observed system profile data and the monitored activity signature data. If there is a match, then the processor may execute a remedial action at operation **1410**. If there is no match, the processor may continue to observed the powered system at operation **1404**. It will be appreciated that the process

flow **1400** may be executed in addition to or instead of monitoring that includes comparing expected system profile data to the observed system profile data, for example, as described with respect to FIG. 5. In some examples, the processor may concurrently compare the observed system profile data to both expected system profile data and to monitored activity signature data.

(98) FIG. 15 is a block diagram illustrating a computing device hardware architecture **1500**, within which a set or sequence of instructions can be executed to cause a machine to perform examples of any one of the methodologies discussed herein. For example, the architecture **1500** may describe one example arrangement of a power supply including a processor, as described herein. The architecture **1500** may operate as a standalone device or may be connected (e.g., networked) to other machines. In a networked deployment, the architecture **1500** may operate in the capacity of either a server or a client machine in server-client network environments, or it may act as a peer machine in peer-to-peer (or distributed) network environments. The architecture **1500** can be implemented in an embedded system, a personal computer (PC), a tablet PC, a hybrid tablet, a set-top box (STB), a personal digital assistant (PDA), a mobile telephone, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing instructions (sequential or otherwise) that specify operations to be taken by that machine.

(99) The example architecture **1500** includes a processor unit **1502** comprising at least one processor (e.g., a central processing unit (CPU), a graphics processing unit (GPU), or both, processor cores, compute nodes). The architecture **1500** may further comprise a main memory **1504** and a static memory **1506**, which communicate with each other via a link **1508** (e.g., a bus). The architecture **1500** can further include a video display unit **1510**, an input device **1512** (e.g., a keyboard), and a user interface (UI) navigation device **1514** (e.g., a mouse). In some examples, the video display unit **1510**, input device **1512**, and UI navigation device **1514** are incorporated into a touchscreen display. The architecture **1500** may additionally include a storage device **1516** (e.g., a drive unit), a signal generation device **1518** (e.g., a speaker), a network interface device **1520**, and one or more sensors (not shown), such as a Global Positioning System (GPS) sensor, compass, accelerometer, or other sensor.

(100) In some examples, the processor unit **1502** or another suitable hardware component may support a hardware interrupt. In response to a hardware interrupt, the processor unit **1502** may pause its processing and execute an ISR, for example, as described herein.

(101) The storage device **1516** includes a machine-readable medium **1522** on which is stored one or more sets of data structures and instructions **1524** (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. The instructions **1524** can also reside, completely or at least partially, within the main memory **1504**, within the static memory **1506**, and/or within the processor unit **1502** during execution thereof by the architecture **1500**, with the main memory **1504**, the static memory **1506**, and the processor unit **1502** also constituting machine-readable media.

(102) Executable Instructions and Machine-Storage Medium

(103) The various memories (**1504**, **1506**, and/or memory of the processor unit(s) **1502**) and/or the storage device **1516** may store one or more sets of instructions and data structures (e.g., the instructions **1524**) embodying or used by any one or more of the methodologies or functions described herein. These instructions, when executed by the processor unit(s) **1502**, cause various operations to implement the disclosed examples.

(104) As used herein, the terms “machine-storage medium,” “device-storage medium,” and “computer-storage medium” (referred to collectively as “machine-storage medium”) mean the same thing and may be used interchangeably. The terms refer to a single or multiple storage devices and/or media (e.g., a centralized or distributed database, and/or associated caches and servers) that store executable instructions and/or data, as well as cloud-based storage systems or storage networks that include multiple storage apparatus or devices. The terms shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including

memory internal or external to processors. Specific examples of machine-storage media, computer-storage media, and/or device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), field-programmable gate array (FPGA), and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium” discussed below.

(105) Signal Medium

(106) The term “signal medium” or “transmission medium” shall be taken to include any form of modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal.

(107) Computer-Readable Medium

(108) The terms “machine-readable medium,” “computer-readable medium,” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure. The terms are defined to include both machine-storage media and signal media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals.

(109) The instructions **1524** can further be transmitted or received over a communications network **1526** using a transmission medium via the network interface device **1520** using any one of a number of well-known transfer protocols (e.g., Hypertext Transfer Protocol (HTTP)). Examples of communication networks include a local area network (LAN), a wide area network (WAN), the Internet, mobile telephone networks, plain old telephone service (POTS) networks, and wireless data networks (e.g., Wi-Fi, 3G, 4G Long-Term Evolution (LTE)/LTE-A, 5G, or WiMAX networks).

Various Notes & Examples

(110) Example 1 is a power supply comprising: a regulator circuit configured to generate an output electrical signal; a sensor configured to generate a sensor signal describing the output electrical signal; and at least one processor, the at least one processor programmed to perform operations comprising: determining that the sensor signal fails to match expected system profile data describing an operation of at least one component electrically coupled to the power supply; and responsive to determining that the sensor signal fails to match the expected system profile data, executing a remedial action.

(111) In Example 2, the subject matter of Example 1 optionally includes an enclosure, the regulator circuit, the sensor, and the at least one processor being positioned within the enclosure.

(112) In Example 3, the subject matter of any one or more of Examples 1-2 optionally include the remedial action comprising sending an alert message to a process control system, the alert message describing a deviation of the sensor signal from the expected system profile data.

(113) In Example 4, the subject matter of any one or more of Examples 1-3 optionally include the remedial action comprising initiating a shutdown of the at least one component electrically coupled to the power supply.

(114) In Example 5, the subject matter of any one or more of Examples 1~4 optionally include the operations further comprising: executing a trained computerized model; and accessing an output of the trained computerized model, the output of the trained computerized model being generated from at least one input that is based at least in part on the sensor signal, the output of the trained computerized model indicating that the sensor signal fails to match the expected system profile data.

(115) In Example 6, the subject matter of Example 5 optionally includes the operations further comprising: accessing training data generated using the sensor; and periodically retraining the trained computerized model using the training data. In Example 7, the subject matter of any one or

more of Examples 1-6 optionally include the determining that the sensor signal fails to match the expected system profile data comprising determining that the sensor signal indicates at least one monitored activity at a first component of the at least one component.

(116) In Example 8, the subject matter of any one or more of Examples 1-7 optionally include the determining that the sensor signal fails to match the expected system profile data comprising determining that the sensor signal fails to match modified system profile data describing an operation of the at least one component according to a first known modification.

(117) In Example 9, the subject matter of any one or more of Examples 1-8 optionally include the determining that the sensor signal fails to match the expected system profile data being based at least in part on an aging profile data driving a change in the operation of the at least one component over time.

(118) In Example 10, the subject matter of any one or more of Examples 1-9 optionally include the determining that the sensor signal fails to match the expected system profile data comprising: determining that the sensor signal indicates a first plurality of power peaks over a first instance of a time period; and comparing the first plurality of power peaks to a second plurality of power peaks over the time period indicated by the expected system profile data.

(119) In Example 11, the subject matter of Example 10 optionally includes the comparing comprising comparing a magnitude of a first power peak of the first plurality of power peaks to a magnitude of a first power peak of the second plurality of power peaks.

(120) In Example 12, the subject matter of any one or more of Examples 10-11 optionally include the comparing comprising comparing a time of a first power peak of the first plurality of power peaks within the time period to a time of a first power peak of the second plurality of power peaks within the time period.

(121) In Example 13, the subject matter of any one or more of Examples 1-12 optionally include the determining that the sensor signal fails to match the expected system profile data comprising comparing a frequency spectrum of the sensor signal to a frequency spectrum of the expected system profile data.

(122) In Example 14, the subject matter of any one or more of Examples 1-13 optionally include the operations further comprising receiving an enablement message, the enablement message indicating that the power supply is to be enabled to compare the sensor signal to the expected system profile data.

(123) Example 15 is a method of operating a power supply, the power supply comprising at least one processor, the method comprising: accessing, by the at least one processor, a sensor signal generated by a sensor of the power supply, the sensor signal describing an output electrical signal of the power supply; determining, by the at least one processor, that the sensor signal fails to match expected system profile data describing an operation of at least one component electrically coupled to the power supply; and responsive to determining that the sensor signal fails to match the expected system profile data, executing, by the at least one processor, a remedial action.

(124) In Example 16, the subject matter of Example 15 optionally includes the remedial action comprising sending an alert message to a process control system, the alert message describing a deviation of the sensor signal from the expected system profile data.

(125) In Example 17, the subject matter of any one or more of Examples 15-16 optionally include the remedial action comprising initiating a shutdown of the at least one component electrically coupled to the power supply.

(126) In Example 18, the subject matter of any one or more of Examples 15-17 optionally include executing, by the at least one processor, a trained computerized model; and accessing, by the at least one processor, an output of the trained computerized model, the output of the trained computerized model being generated from at least one input that is based at least in part on the sensor signal, the output of the trained computerized model indicating that the sensor signal fails to match the expected system profile data.

(127) In Example 19, the subject matter of any one or more of Examples 15-18 optionally include the determining that the sensor signal fails to match the expected system profile data comprising determining that the sensor signal indicates at least one monitored activity at a first component of the at least one component.

(128) Example 20 is a non-transitory machine-readable medium comprising instructions that, when executed by at least one processor of a power supply, cause the at least one processor of the power supply to perform operations comprising: accessing a sensor signal generated by a sensor of the power supply, the sensor signal describing an output electrical signal of the power supply; determining that the sensor signal fails to match expected system profile data describing an operation of at least one component electrically coupled to the power supply; and responsive to determining that the sensor signal fails to match the expected system profile data, executing a remedial action.

(129) The above detailed description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the disclosed examples can be practiced. These embodiments are also referred to herein as “examples.” Such examples can include elements in addition to those shown or described. However, the present inventors also contemplate examples in which only those elements shown or described are provided. Moreover, the present inventors also contemplate examples using any combination or permutation of those elements shown or described (or one or more aspects thereof), either with respect to a particular example (or one or more aspects thereof), or with respect to other examples (or one or more aspects thereof) shown or described herein.

(130) In the event of inconsistent usages between this document and any documents so incorporated by reference, the usage in this document controls.

(131) In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended, that is, a system, device, article, composition, formulation, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

(132) The term “circuit” can include a dedicated hardware circuit, a general-purpose microprocessor, digital signal processor, or other processor circuit, and may be structurally configured from a general purpose circuit to a specialized circuit such as using firmware or software.

(133) Any one or more of the techniques (e.g., methodologies) discussed herein may be performed on a machine. In various embodiments, the machine may operate as a standalone device or may be connected (e.g., networked) to other machines. In a networked deployment, the machine may operate in the capacity of a server machine, a client machine, or both in server-client network environments. In an example, the machine may act as a peer machine in peer-to-peer (P2P) (or other distributed) network environment. The machine may be a PC, a tablet PC, a STB, a PDA, a mobile telephone, a web appliance, a network router, switch or bridge, or any machine capable of executing instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein, such as cloud computing, software as a service (SaaS), other computer cluster configurations.

(134) Examples, as described herein, may include, or may operate by, logic or a number of components, or mechanisms. Circuit sets are a collection of circuits implemented in tangible entities that include hardware (e.g., simple circuits, gates, logic, etc.). Circuit set membership may be flexible over time and underlying hardware variability. Circuit sets include members that may, alone or in combination, perform specified operations when operating. In an example, hardware of the circuit set may be immutably designed to carry out a specific operation (e.g., hardwired). In an example, the hardware of the circuit set may include variably connected physical components (e.g., execution units, transistors, simple circuits, etc.) including a computer readable medium physically modified (e.g., magnetically, electrically, moveable placement of invariant massed particles, etc.) to encode instructions of the specific operation. In connecting the physical components, the underlying electrical properties of a hardware constituent are changed, for example, from an insulator to a conductor or vice versa. The instructions can enable embedded hardware (e.g., the execution units or a loading mechanism) to create members of the circuit set in hardware via the variable connections to carry out portions of the specific operation when in operation. Accordingly, the computer readable medium is communicatively coupled to the other components of the circuit set member when the device is operating. In an example, any of the physical components may be used in more than one member of more than one circuit set. For example, under operation, execution units may be used in a first circuit of a first circuit set at one point in time and reused by a second circuit in the first circuit set, or by a third circuit in a second circuit set at a different time.

(135) Particular implementations of the systems and methods described herein may involve use of a machine (e.g., computer system) that may include a hardware processor (e.g., a CPU, a GPU, a hardware processor core, or any combination thereof), a main memory and a static memory, some or all of which may communicate with each other via an interlink (e.g., bus). The machine may further include a display unit, an alphanumeric input device (e.g., a keyboard), and a UI navigation device (e.g., a mouse). In an example, the display unit, input device and UI navigation device may be a touch screen display. The machine may additionally include a storage device (e.g., drive unit), a signal generation device (e.g., a speaker), a network interface device, and one or more sensors, such as a GPS sensor, compass, accelerometer, or other sensor. The machine may include an output controller, such as a serial (e.g., universal serial bus (USB), parallel, or other wired or wireless (e.g., infrared (IR), near field communication (NFC), etc.) connection to communicate or control one or more peripheral devices (e.g., a printer, card reader, etc.).

(136) The storage device may include a machine readable medium on which is stored one or more sets of data structures or instructions (e.g., software) embodying or utilized by any one or more of the techniques or functions described herein. The instructions may also reside, completely or at least partially, within the main memory, within static memory, or within the hardware processor during execution thereof by the machine. In an example, one or any combination of the hardware processor, the main memory, the static memory, or the storage device may constitute machine readable media.

(137) While the machine readable medium can include a single medium, the term “machine readable medium” may include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) configured to store the one or more instructions.

(138) The term “machine readable medium” may include any medium that is capable of storing, encoding, or carrying instructions for execution by the machine and that cause the machine to perform any one or more of the techniques of the present disclosure, or that is capable of storing, encoding or carrying data structures used by or associated with such instructions. Non-limiting machine readable medium examples may include solid-state memories, and optical and magnetic media. In an example, a massed machine readable medium comprises a machine readable medium with a plurality of particles having invariant (e.g., rest) mass. Accordingly, massed machine-readable media are not transitory propagating signals. Specific examples of massed machine

readable media may include: non-volatile memory, such as semiconductor memory devices (e.g., EPROM, EEPROM) and flash memory devices; magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks.

(139) The instructions may further be transmitted or received over a communications network using a transmission medium via the network interface device utilizing any one of a number of transfer protocols (e.g., frame relay, internet protocol (IP), transmission control protocol (TCP), user datagram protocol (UDP), (HTTP, etc.). Example communication networks may include a LAN, a WAN, a packet data network (e.g., the Internet), mobile telephone networks (e.g., cellular networks), POTS networks, and wireless data networks (e.g., Institute of Electrical and Electronics Engineers (IEEE) 802.11 family of standards known as Wi-Fi®, IEEE 802.16 family of standards known as WiMax®, IEEE 802.15.4 family of standards, P2P networks, among others. In an example, the network interface device may include one or more physical jacks (e.g., Ethernet, coaxial, or phone jacks) or one or more antennas to connect to the communications network. In an example, the network interface device may include a plurality of antennas to wirelessly communicate using at least one of single-input multiple-output (SIMO), multiple-input multiple-output (MIMO), or multiple-input single-output (MISO) techniques. The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such software.

(140) Method examples described herein can be machine or computer-implemented at least in part. Some examples can include a computer-readable medium or machine-readable medium encoded with instructions operable to configure an electronic device to perform methods as described in the above examples. An implementation of such methods can include code, such as microcode, assembly language code, a higher-level language code, or the like. Such code can include computer readable instructions for performing various methods. The code may form portions of computer program products. Further, in an example, the code can be tangibly stored on one or more volatile, non-transitory, or non-volatile tangible computer-readable media, such as during execution or at other times. Examples of these tangible computer-readable media can include, but are not limited to, hard disks, removable magnetic disks, removable optical disks (e.g., compact disks and digital video disks), magnetic cassettes, memory cards or sticks, RAMs, ROMs, and the like.

(141) The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more aspects thereof) may be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. The Abstract is provided to comply with 37 C.F.R. § 1.72 (b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. Also, in the above Detailed Description, various features may be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter may lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description as examples or embodiments, with each claim standing on its own as a separate embodiment, and it is contemplated that such embodiments can be combined with each other in various combinations or permutations. The scope of the disclosure should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

Claims

1. A power supply comprising: a regulator circuit configured to generate an output electrical signal; a sensor configured to generate a sensor signal describing the output electrical signal; and at least

one processor, the at least one processor programmed to perform operations comprising: determining that the sensor signal fails to match expected system profile data describing an operation of at least one component electrically coupled to the power supply, the determining that the sensor signal fails to match the expected system profile data comprising: executing a trained computerized model; and accessing an output of the trained computerized model, the output of the trained computerized model being generated from at least one input that is based at least in part on the sensor signal, the output of the trained computerized model indicating that the sensor signal fails to match the expected system profile data; and responsive to determining that the sensor signal fails to match the expected system profile data, executing a remedial action, the remedial action comprising initiating a shutdown of the at least one component electrically coupled to the power supply.

2. The power supply of claim 1, further comprising an enclosure, the regulator circuit, the sensor, and the at least one processor being positioned within the enclosure.

3. The power supply of claim 1, the remedial action further comprising sending an alert message to a process control system, the alert message describing a deviation of the sensor signal from the expected system profile data.

4. The power supply of claim 1, the operations further comprising: accessing training data generated using the sensor; and periodically retraining the trained computerized model using the training data.

5. The power supply of claim 1, the determining that the sensor signal fails to match the expected system profile data comprising determining that the sensor signal indicates at least one monitored activity at a first component of the at least one component.

6. The power supply of claim 1, the determining that the sensor signal fails to match the expected system profile data comprising determining that the sensor signal fails to match modified system profile data describing an operation of the at least one component according to a first known modification.

7. The power supply of claim 1, the determining that the sensor signal fails to match the expected system profile data being based at least in part on an aging profile data driving a change in the operation of the at least one component over time.

8. The power supply of claim 1, the determining that the sensor signal fails to match the expected system profile data comprising: determining that the sensor signal indicates a first plurality of power peaks over a first instance of a time period; and comparing the first plurality of power peaks to a second plurality of power peaks over the time period indicated by the expected system profile data.

9. The power supply of claim 8, the comparing comprising comparing a magnitude of a first power peak of the first plurality of power peaks to a magnitude of a first power peak of the second plurality of power peaks.

10. The power supply of claim 8, the comparing comprising comparing a time of a first power peak of the first plurality of power peaks within the time period to a time of a first power peak of the second plurality of power peaks within the time period.

11. The power supply of claim 1, the determining that the sensor signal fails to match the expected system profile data comprising comparing a frequency spectrum of the sensor signal to a frequency spectrum of the expected system profile data.

12. The power supply of claim 1, the operations further comprising receiving an enablement message, the enablement message indicating that the power supply is to be enabled to compare the sensor signal to the expected system profile data.

13. A method of operating a power supply, the power supply comprising at least one processor, the method comprising: accessing, by the at least one processor, a sensor signal generated by a sensor of the power supply, the sensor signal describing an output electrical signal of the power supply; determining, by the at least one processor, that the sensor signal fails to match expected system

profile data describing an operation of at least one component electrically coupled to the power supply, the determining that the sensor signal fails to match the expected system profile data comprising: executing a trained computerized model; and accessing an output of the trained computerized model, the output of the trained computerized model being generated from at least one input that is based at least in part on the sensor signal, the output of the trained computerized model indicating that the sensor signal fails to match the expected system profile data; and responsive to determining that the sensor signal fails to match the expected system profile data, executing, by the at least one processor, a remedial action, the remedial action comprising initiating a shutdown of the at least one component electrically coupled to the power supply.

14. The method of claim 13, the remedial action further comprising sending an alert message to a process control system, the alert message describing a deviation of the sensor signal from the expected system profile data.

15. The method of claim 13, the determining that the sensor signal fails to match the expected system profile data comprising determining that the sensor signal indicates at least one monitored activity at a first component of the at least one component.

16. A non-transitory machine-readable medium comprising instructions that, when executed by at least one processor of a power supply, cause the at least one processor of the power supply to perform operations comprising: accessing a sensor signal generated by a sensor of the power supply, the sensor signal describing an output electrical signal of the power supply; determining that the sensor signal fails to match expected system profile data describing an operation of at least one component electrically coupled to the power supply, the determining that the sensor signal fails to match the expected system profile data comprising: executing a trained computerized model; and accessing an output of the trained computerized model, the output of the trained computerized model being generated from at least one input that is based at least in part on the sensor signal, the output of the trained computerized model indicating that the sensor signal fails to match the expected system profile data; and responsive to determining that the sensor signal fails to match the expected system profile data, executing a remedial action, the remedial action comprising initiating a shutdown of the at least one component electrically coupled to the power supply.

17. The non-transitory machine-readable medium of claim 16, the operations further comprising receiving an enablement message, the enablement message indicating that the power supply is to be enabled to compare the sensor signal to the expected system profile data.

18. The non-transitory machine-readable medium of claim 16, the remedial action further comprising sending an alert message to a process control system, the alert message describing a deviation of the sensor signal from the expected system profile data.

19. The non-transitory machine-readable medium of claim 16, the operations further comprising: accessing training data generated using the sensor; and periodically retraining the trained computerized model using the training data.

20. The non-transitory machine-readable medium of claim 16, the operations further comprising receiving an enablement message, the enablement message indicating that the power supply is to be enabled to compare the sensor signal to the expected system profile data.
