

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401965
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Hegstad; Kjell et al.

Systems and methods for providing mobile proving ground

Abstract

The disclosed embodiments include methods, systems, and articles of manufacture for enabling beta testing of new features within a native application. In one embodiment, a native application executed by a client device may include executable instructions that are activated and executed only upon indication of a user belonging to a beta test group. The client device may receive a signal from a service or content provider that includes test group information indicating whether a user is a member of a test group. The client device may process the received signal to determine whether the user is a member of a test group and, if so, activates and executes certain instructions received as part of the native application that define a user interface enabling access to additional functionality unavailable to a user determined not to be a member of a test group.

Inventors:	Hegstad; Kjell (McLean, VA), Brandt; Dennis R. (Wilmington, DE)
Applicant:	Capital One Services, LLC (McLean, VA)
Family ID:	1000008778580
Assignee:	Capital One Services, LLC (McLean, VA)
Appl. No.:	18/605130
Filed:	March 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240223992 A1	Jul. 04, 2024

Related U.S. Application Data

continuation parent-doc US 18172177 20230221 US 11968589 child-doc US 18605130
continuation parent-doc US 17713172 20220404 US 11622225 20230404 child-doc US 18172177
continuation parent-doc US 17146062 20210111 US 11330392 20220510 child-doc US 17713172
continuation parent-doc US 16377106 20190405 US 10917738 20210209 child-doc US 17146062

Publication Classification

Int. Cl.: **H04W4/00** (20180101); **G06F11/3668** (20250101); H04W4/21 (20180101); H04W4/60 (20180101)

U.S. Cl.:

CPC **H04W4/00** (20130101); **G06F11/3688** (20130101); H04W4/21 (20180201); H04W4/60 (20180201)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8997246	12/2014	Grinstein	726/4	G06F 21/629
2013/0080467	12/2012	Carson	707/769	G06F 16/9536
2013/0151374	12/2012	Sims	705/26.35	G06Q 30/0605
2014/0282016	12/2013	Hosier, Jr.	715/733	G06F 3/017
2015/0334117	12/2014	Terleski	726/27	G06Q 10/10
2017/0064551	12/2016	Block	N/A	G06Q 20/341

Primary Examiner: Vu; Toan H

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of Ser. No. 18/172,177, filed Feb. 21, 2023, which is a continuation of U.S. patent application Ser. No. 17/713,172, filed Apr. 4, 2022, which is a continuation of U.S. patent application Ser. No. 17/146,062, filed Jan. 11, 2021, which is a continuation of U.S. patent application Ser. No. 16/377,106, filed Apr. 5, 2019, which is a continuation of U.S. patent application Ser. No. 14/324,639, filed Jul. 7, 2014, which claims priority under 35 U.S.C. § 119 to U.S. Provisional Application No. 61/843,715, filed on Jul. 8, 2013, which is expressly incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates generally to systems and methods for mobile proving grounds. More particularly, and without limitation, the present disclosure relates to systems and methods for providing a user interface in a mobile application that allows a set of users to test, in real-time, new or modified features and functionality of the mobile application within the native mobile

application.

BACKGROUND

(2) The prevalence of mobile technologies such as smart phones, tablets, and other electronic mobile wireless devices has driven the proliferation of mobile applications (or “apps”) that enable diverse functionality of these devices. As the use of smart phones, tablets, and other electronic mobile devices becomes even more widespread, it becomes increasingly important to provide a convenient and enriching experience to clients and consumers of businesses, institutions, and other content or service providers (“providers”) through a well-designed app. For example, users may opt to transact with one provider over another based on the convenience and functionality of that provider's app. With respect to a financial services provider, the particular functionality of a mobile app can eliminate the need for some users to visit a brick-and-mortar location for routine transactions.

(3) As users continue to increasingly rely on the functionality of mobile applications for their service and content needs, providers are challenged with identifying the usefulness and desirability of particular features to incorporate into their mobile app. Additionally, providers strive to identify how users interact with the mobile app and to what extent additional or modified functionality can lead to increased revenues from existing clients and/or attract new clients. In particular, providers desire a way to efficiently and effectively test the use and desirability of new features in a mobile app by evaluating real-time interactions of a large number of users according to their actual typical use of the mobile app.

(4) Conventional testing methods include traditional surveying actual or potential users of a mobile app regarding the desirability of particular functionality and how that functionality might be used. Traditional surveys, however, may not be very accurate in predicting how users will utilize that feature within the actual working (or “native”) mobile app that is available for all users. Thus, real-time beta testing of a native app with the new features and functionality is more desirable.

Conventional beta testing methods, however, are incapable of effectively testing the new features and functionality among a large group of actual users. A provider typically must provide a beta version of its mobile app (a “beta app”) to a mobile app distributor, such as the Apple App Store® or Google Play®, where select users may be instructed to download the beta app. But mobile app distributors often limit the number of versions of a particular app that are available for download. Accordingly, a provider typically must include all new features or functionality it is testing within the beta app. Mobile app distributors also limit the number of users that can download the beta app. Thus, conventional beta testing of new mobile app functionality typically suffers from being unable to release multiple versions of a beta app to test specific new features and functionality or to reach large numbers of users that may have diverse demographics and varying levels of interaction with the mobile app.

(5) Typical beta testing methods also fail because they require select users to download a beta version of the mobile app for each newly planned feature, which many of these select users may neglect or be reluctant to do. Additionally, some users may find that the beta app includes new functionality that is undesirable or results in a negative experience, requiring that user to once again download another version of the mobile app, such as the native app. Thus, it is desirable to enable beta testing of new features for select users within the native app. Additionally, it is desirable to implement a method and system to dynamically control the availability of new discreet features (beta features) of the mobile app to select users, without requiring separate downloading of new versions of the mobile app for each beta feature.

SUMMARY

(6) Disclosed embodiments include methods, systems, and computer-readable media configured to, for example, provide a user interface in a native mobile application to a set of users for testing new features and functionality of the mobile application. For example, a mobile device is disclosed for providing a user interface on a mobile application, comprising at least one processor and at least

one memory device that stores a set of instructions corresponding to the mobile application. When executed by the processor, the stored instructions may cause the processor to receive a signal from a service provider, the signal including information indicating test group membership data. The mobile device may also be configured to determine, based on at least the received signal, whether the user is a member of a test group and enable access to a first set of functions in the mobile application after the user is determined to be one of the members of the test group. The first set of functions may be unavailable to non-members of the test group. The mobile device may also be configured to display a user interface including at least one feature from the first set of functions on the mobile application.

(7) In one aspect, the disclosed embodiments include a method for providing a user interface on a device. The method may include receiving a communication signal including at least test group identification information for a user associated with the device. The method may also include identifying whether the test group identification information indicates the user is a member of at least one test group, and executing a first set of instructions after the user is identified as a member of a test group associated with the first set of functions, and a second set of instructions when the user is identified as not a member of the test group. The method may also include displaying a user interface according to the execution of the first or second set of instructions, wherein the first set of instructions enable access to at least one or more test functions that are un-available to a user that is not a member of a test group.

(8) Aspects of the disclosed embodiments may include tangible computer-readable media that stores software instructions that, when executed by one or more processors, are configured to and capable of performing and executing one or more of the methods, operations, and the like consistent with the disclosed embodiments. Also, aspects of the disclosed embodiments may be performed by one or more processors, that are configured as special-purpose processor(s) based on software instructions that are programmed with logic and instructions that perform, when executed, one or more operations consistent with the disclosed embodiments.

(9) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the disclosed embodiments, as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate disclosed embodiments and, together with the description, serve to explain the disclosed embodiments. In the drawings:

(2) FIG. 1 is a block diagram of an exemplary system, consistent with disclosed embodiments.

(3) FIG. 2 is a block diagram of an exemplary client device system, consistent with disclosed embodiments.

(4) FIG. 3 is a block diagram of an exemplary application system, consistent with disclosed embodiments.

(5) FIG. 4 is a flowchart of an exemplary application download process, consistent with disclosed embodiments.

(6) FIG. 5 is a flowchart of an exemplary beta user registration process, consistent with disclosed embodiments.

(7) FIG. 6 is a flowchart of an exemplary client device application process, consistent with disclosed embodiments.

(8) FIG. 7 is a flowchart of an exemplary beta user identification process, consistent with disclosed embodiments.

(9) FIGS. **8A-8D** are illustrations of exemplary user interfaces, consistent with disclosed embodiments.

(10) FIGS. **9A** and **9B** are illustrations of an exemplary rating interface, consistent with disclosed embodiments.

DETAILED DESCRIPTION

(11) Reference will now be made in detail to the disclosed embodiments, examples of which are illustrated in the accompanying drawings. Wherever convenient, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

(12) FIG. **1** is a block diagram of an exemplary system **100** for performing one or more operations consistent with the disclosed embodiments. As further disclosed herein, system **100** may be used for providing a user interface in a native mobile application to a set of users for testing new features and functionality of the mobile application. In one embodiment, system **100** may include one or more service or content application system(s) **112** (“application system”) interconnected via a network **120** to one or more client devices **130**. Application system **112** may be one of many systems controlled, operated, or utilized by a service or content provider **110** (“provider”). In other embodiments, application system **112** is a separate and distinct system from service or content provider **110**. System **100** may include other components or subsystems that perform or assist in the performance of one or more processes consistent with the disclosed embodiments as would be understood by one of ordinary skill in the art.

(13) As will be described in more detail below, in certain embodiments, one or more components of system **100** may be configured to select one or more, or a subset of, users **132** to join a beta test group for testing new features and functionality of a mobile application. Such select users may be designated as beta users **134**. System **100** may notify the beta users **134** of the availability to join the beta test group. In some embodiments, system **100** may notify the beta users **134** via, for example, client device **130**, personal computer, telephone, traditional mail, or other communication medium. System **100** may receive enrollment information from at least one beta user **134** for enrolling in the beta test group and may store that information or otherwise update information in a database related to the beta testing of new or updated mobile application features. System **100** may enable users **132** and **134** to download and execute a native mobile application on client devices **130**. Upon execution of the application, system **100** may receive user information from a user (via, e.g., client device **130**) and determine whether the user is one of beta users **134**. System **100** may then transmit information to client device **130** indicating whether the user is one of beta users **134** via an application signal, e.g., a signal including a software command, program variable setting, etc. Client device **130** may determine whether the signal information indicates that the user is one of beta users **134**. If the user executing the application is one of beta users **134**, client device **130** may display one or more beta features for testing on a user interface of the native application. If the user executing the application is not one of beta users **134**, i.e., user **132**, client device **130** may display the normal or current features of the native mobile application.

(14) In an exemplary embodiment, provider **110** corresponds to a business, merchant, or entity that provides goods, services, and/or information content, such as a retailer, grocery store, service provider (e.g., utility company, etc.), non-profit organization, content provider (whether offline or online), or any other type of entity that provides goods, services, and/or information that consumers (i.e., end-users or other business entities) may purchase, consume, use, etc. Provider **110** is not limited to entities that conduct business in any particular industry or field.

(15) Provider **110** may be associated with a merchant brick-and-mortar location(s) that a consumer (e.g., users **132**, **134**) may visit in person and purchase and/or receive goods and services. Such physical locations may include computing devices that perform financial service transactions with consumers (e.g., Point-of-Sale (POS) terminal(s), kiosks, etc.). According to some embodiments, provider **110** may perform financial transactions, e.g., purchase transactions, with users **132**, **134** (via, e.g., client device **130** operate by users **132**, **134**). Provider **110** may also include back and/or

front-end computing components that store data and execute software instructions to perform operations consistent with disclosed embodiments, independent of or in conjunction with application system **112**.

(16) Provider **110** may also be associated with a merchant that provides goods or services via online or e-commerce solutions. For example, provider **110** may be a merchant selling goods via a website using known online or e-commerce systems and solutions to market, sell and process online transactions. Provider **110** may also provide such services through a mobile application, such as a native mobile app operating on client device **130**, which may communicate with application system **112** via network **120**.

(17) In an exemplary embodiment, provider **110** may correspond to a financial services provider. For example, the financial services provider may be associated with a bank, stock broker, fund manager, credit card issuer, or other type of financial services entity or institution that generates, provides, manages, and/or maintains financial service accounts for one or more users. Financial service accounts may include, for example, credit card accounts, loan accounts, checking accounts, savings accounts, stock accounts, reward or loyalty program accounts, and/or any other type of financial service account known to those skilled in the art. The financial services provider is capable of providing such services through a mobile application, such as a native mobile app operating on client device **130** that communicates with application system **112** via network **120**. In this embodiment, financial service provider **110** may also include one or more physical locations and the infrastructure and systems configured to generate and/or provide the desired financial services.

(18) In another embodiment, provider **110** may be a system associated with an entity providing content, which is viewed, listened to, or otherwise consumed by users. For example, provider **110** may be associated with a broadcasting network, radio network, website, news service, social network, digital media source, or other type of entity that generates, provides, manages, distributes, and/or delivers content (whether offline or online) to others. For instance, as non-limiting examples, provider **110** may be associated with a television network, cable company, radio service, news service, or digital media source. Provider **110** may deliver to client device **130**, via network **120**, dynamic media content (i.e., video, audio, interactive content, etc.) and/or static content (digital print media, images, etc.). The content delivered to client device **130** may be provided to a user **132**, **134** through an application operating on the client device, such as a native application or a web browser operating on client device **130**, which communicates with application system **112** via network **120**. Provider **110** may further include additional infrastructure and systems configured to generate, provide, manage, distribute, and/or deliver content. As noted above, however, provider **110** is not limited to entities that conduct business in any particular industry or field.

(19) Application system **112** may include a number of computing systems configured to provide services or content to users **132**, **134** via network **120** and client device **130** according to the disclosed embodiments. As further described herein, components of application system **112** may include one or more computing devices (e.g., computer(s), server(s), processor(s) etc.), memory systems for storing data and content, and/or software instructions (e.g., database(s), memory devices, etc.), and other known computing components. In some embodiments, the one or more computing devices are configured to execute software instructions stored on one or more memory devices to perform one or more operations consistent with the disclosed embodiments. Although computing devices operating according to disclosed embodiments may be implemented as computer processing instructions, all or a portion of the functionality of the computing devices may be implemented instead in electronics hardware. The components of application system **112** may be provided in a single location or distributed across a number of locations interconnected via one or more networks. Additionally, application system **112** may be directly or indirectly controlled or operated by provider **110**, or may be part of a third party system on behalf of provider **110**. In some embodiments, one or more aspects or components of application system **112** may be operated or

controlled by provider **110**, whereas other aspects and components are operated or controlled by a third party.

(20) Network **120** may be any type of network configured to provide communications between components of system **100**. For example, network **120** may be any type of network or combination of networks that provides communications, exchanges information, and/or facilitates the exchange of information, such as the Internet, a Local Area Network, a Wide Area Network, a wired or wireless network, a cellular network, or other suitable connection(s) and infrastructure that enables the sending and receiving of information between the components of system **100**. The disclosed embodiments are not limited to any particular configuration of network **120**.

(21) Client device(s) **130** may be one or more computing devices configured to perform one or more operations consistent with the disclosed embodiments. In an exemplary embodiment, client device **130** may be a mobile device (e.g., tablet, smartphone, personal digital assistant (PDA), a-reader, iPad®, iPod®, etc.). Disclosed embodiments, however, are not limited to any particular configuration of client device **130**. As such, client device **130** may be a desktop computer, a laptop, smart television or any other type of computing device or any other device capable of presenting content or displaying a user interface to user **132** for receiving a service or content via network **120**. According to some embodiments, client device **130** may comprise a network-enabled computing device operably connected to one or more other presentation devices, which may themselves constitute client devices **130**.

(22) As shown in FIG. 2, client device **130** may include one or more controllers or processors **220**, which may include one or more microprocessors configured to control the operation of client device **130** according to the disclosed embodiments. Processor **220** may be configured to interact with a number of device subsystems, such as display **210**, input device **212**, communication unit **214**, and memory unit **230**. Client device **130** is not limited to the particular components or subsystems illustrated in FIG. 2, and may include any number of additional subsystems or arrangements of subsystems for performing the operations of client device **130** consistent with the disclosed embodiments.

(23) In an exemplary embodiment, display **210** may comprise a screen for displaying content or providing a user interface. Display **210** may include a visible screen realized by underlying LED-backlit LCD technology, organic LED technology, electronic ink, or any other suitable display technology according to the disclosed embodiments. In some embodiments, display **210** may be an external component in communication with client device **130** for displaying content or a user interface consistent with the disclosed embodiments. Input device **212** may incorporate a keyboard realized using hardware or software, one or more buttons, a stylus, a trackball or any other input device for enabling input or control by user **132**. In some embodiments, input device **212** may be provided as part of display **210**, such as through a touch-sensitive input surface or touch-screen or any other method of recognizing user input via display **210**.

(24) Communication unit **214** may include one or more communication systems suitable for communicating via network **120**. The particular design of communication unit **214** depends on the configuration of network **120**, through which client device **130** is capable of communicating with application system **112**, in the disclosed embodiments, client device **130** is capable of sending and receiving communication signals over a plurality and/or combination of network configurations, such as wired, wireless, cellular, radio, etc.

(25) Memory unit **230** may store software instructions which may include one or more operating systems (“OS”) **232**, one or more applications (“apps”) **234**, and data **236**. Processor **220** is configured to execute software instructions stored in memory unit **230** to communicate via network **120** and to carry out a number of operation processes and applications to realize functionality of client device **130**. For example, client device **130** may execute software instructions that may be provided as a native application or app **234** to generate and display a user interface and/or content via display **210**, which may be internal to or operably connected to client device **130**. Applications

234 may enable not only the display of content and/or a user interface but may also enable client device **130** to communicate with application system **112** (FIG. **1**) in order to receive additional content from and/or the provision of services with provider **110** (FIG. **1**), such as mobile or online banking. Applications **234** may include software instructions for a wide range and number of applications or apps configured to run on operating system **232**, including a native application associated with provider **110**, an internet browser application, and/or a content player application. Operating system **232** includes one or more software instructions according to any platform suitable for controlling operation of client device **130** according to the disclosed embodiments.

(26) In the disclosed embodiments, one or more of applications **234** may be realized as a native application, a web application, or a combination thereof. With respect to a native application, the software code may be developed for use on a particular client device **130** or according to a particular platform or operating system **232** controlling the functionality of client device **130**. In an exemplary embodiment, a native application may be installed directly onto client device **130** and stored in memory unit **230**. The native application may be retrieved or downloaded from an application distributor or directly from application system **112**. In an exemplary embodiment, data and content associated with the native application may be stored in memory unit **230** as data **236**. A web application, on the other hand, may be generalized for a number of platforms and may enable receipt of content that is stored at application system **112** via network **120** as opposed to being stored locally on client device **130**. Web applications may be accessed using a separate web browser application and/or other native application stored on client device **130**, which includes instructions for retrieving content from application system **112** via network **120**. Applications **234** according to exemplary embodiments are not restricted to any particular configuration or label applied to the application, and are described herein according to their functionality.

(27) FIG. **3** shows an exemplary application system **112**, a subsystem of provider **110**, for implementing embodiments consistent with the present disclosure. Variations of application system **112** may be realized according to a particular provider **110**. As shown in FIG. **3**, in one embodiment, application system **112** may include a content server **320**, an authentication server **330**, and a database **340**. According to some embodiments, content server **320** may comprise one or more web servers or similar computing devices that generate, maintain, and provide websites or web content consistent with disclosed embodiments. Content server **320** and authentication server **330** may further include one or more processors, one or more memories, and one or more interfaces for communicating with database **340** and network **120** (FIG. **1**) and/or each other. Content server **320** and authentication server **330** may be any computing device capable of performing the desired functionality, such as a general purpose computer, a mainframe computer, or any combination of these components. Alternatively, content server **320** and authentication server **330** may be configured as a particular apparatus, embedded system, dedicated circuit, and the like based on the storage, execution, and/or implementation of the software instructions that perform one or more operations consistent with the disclosed embodiments.

(28) Content server **320** and authentication server **330** may be standalone server units, or they may be part of a subsystem, which may be part of an even larger system. Each of the shown components need not be provided within a single location and may be widely distributed among various other systems or subsystems. For example, application system **112** may include distributed servers that are remotely located and communicate over a network (e.g., network **120**), which may include a dedicated network such as a LAN. In some embodiments, the functionality of content server **320** and authentication server **330** may be encompassed in a single server or server system.

(29) Content server **320** and authentication server **330** may also be communicatively connected to one or more database(s) **340**. Database **340** may include one or more memory device(s) that store information, which may be accessed and/or managed through content server **320**, authentication server **330**, and/or other systems provided by provider **110**. By way of example, database **340** may include Oracle™ databases, Sybase™ databases, or other relational databases or non-relational

databases, such as Hadoop sequence files, HBase, or Cassandra. Databases **340** may include, for example, data and information related to the source and destination of a network request, multimedia content, web page content, user information etc. according to the disclosed embodiments. In some embodiments, database **340** may be located remotely from application system **112**. Database **340** may include computing components (e.g., database management system, database server, etc.) configured to receive and process requests for data stored in memory devices of database **340** and to provide data from database **340**.

(30) As shown in FIG. 4, according to an exemplary embodiment, a native mobile application associated with provider **110** (FIG. 1) may be installed onto a client device **130** via application download process **400**. In an exemplary embodiment, application system **112** may receive a request from client device **130** to download a native application to client device **130** (step **410**). In one embodiment, application system **112** may receive the request from an application distributor navigated by user **132**, **134** using a web browser application installed on client device **130** or any particular application installed on client device **130**. In another embodiment, application system **112** may receive the request to download a native application associated with provider **110** onto client device **130** from a webpage or some other portal associated with a provider **110** accessed by user **132**, **134** via, e.g., client device **130**. In this embodiment, application system **112** may store software instructions corresponding to a native application in content server **320** and/or database **340**. In one embodiment, application system **112** may receive additional information from client device **130** regarding the particular device specifications of client device **130** to enable client device **130** to download software instructions corresponding to its particular specifications. In yet another embodiment, application system **112** may push a download request link to client device **130** or transmit the software code corresponding to a native application directly to client device **130** in, for example, an e-mail, a text or short message service (“SMS”) message, a prompt through an app, or other suitable method. In step **420**, client device **130** may receive the native application software code, preferably via network **120**, and downloads and installs the software code to be stored in memory unit **230** as one of applications **234** (step **430**).

(31) In an exemplary embodiment, provider **110** includes a financial services provider, and the native application, once executed by processor **220** in client device **130**, provides a user interface (such as shown in FIG. 8A-D) for receiving various financial services information and for performing various transactions with financial services provider **110**. In one embodiment, a native application may include software code defining the content and placement of particular fields (e.g., text fields, input fields, graphic fields, icons, colors, etc.) and directing client device **130** to display a user interface of the native application according to the software code. For example, the native application software code includes instructions for generating a “standard” (i.e., non-beta) menu screen **810** and each of the displayed menu features and options as shown in FIG. 8A. In one embodiment, the native application software code also includes instructions to display additional information or graphics or to execute a process in response to a selection received from user **132** of any one of the menu features displayed. For example, one such process may include accessing, via network **120**, additional information stored or generated by application system **112**. Such process performed in response to receiving user **132**'s, **134**'s selection may include receiving personal financial information, such as the user's account balance from application system **112**, and displaying such information within the native application interface. Therefore, according to the disclosed embodiments, the native application software code enables client device **130** to access to personal financial information stored on client device **130** and information retrieved remotely, such as from application system **112**.

(32) As shown in FIGS. 8A and 8B, an exemplary native application for a financial services provider **110**, such as one of applications **234** executed on client device **130**, may provide a user interface displaying a number of convenient features for improving a user's access to financial services. For example, as shown in menu **810**, a user **132**, **134** may access information concerning

a particular account, such as a savings account offered by Capital One 360®, by selecting the “My Accounts” field **812**. Additionally, a user **132**, **134** may access another account, such as a credit card account or a checking account by selecting the “Credit Cards” field **816** or the “Capital One Bank” field **818**, respectively. A number of other features or functionality may be realized as suggested by the remaining menu items. For example, the native application may enable user **132**, **134** to transfer money by selecting field **813**, deposit checks by selecting field **814**, pay a bill by selecting field **815**, etc. The particular features shown are provided only as an example, and are not limiting of any of the disclosed embodiments. Additionally, the disclosed embodiments are not limited to a particular design of a native application user interface. As such, the functionality of a native application may be realized by a user interface displaying one or more icons relating to particular features, or any other method desired by provider **110**.

(33) According to an exemplary embodiment, each user **132**, **134** operating client device **130** may receive native application software code associated with a particular provider **110**. Application system **112** may provide a single version of a native application available for download by any user **132**, **134**. While the visual appearance of the native application user interface may vary for some users **132**, **134** depending on the specifications of client device **130**, in one embodiment, a particular native application may contain substantially the same functionality for each client device **130**, to the extent such functionality is not limited by the specifications of client device **130**. In some embodiments, application system **112** may provide multiple versions of a native application, one for each of varying specifications for client devices **130**. For example, one version of a native application may be provided for similarly functional smartphones, and another version of the native application may be provided for a smart television, and yet another version for a tablet.

(34) The present disclosure provides systems, methods, and computer readable media for improving the delivery of content or the provisions of services to users **132**, **134** when accessing and using a native application on client device **130**. The functionality of a provider's **110** native application or app may be a significant factor toward increasing the total client base, thereby increasing revenue. As such, the present disclosure describes methods and systems to develop and test new functionality and new features (“beta features”) for the native application to keep a user engaged with the app, as well as to increase the usability and convenience of the app. According to the present disclosure, provider **110** is enabled to test the real-time functionality, use, and desirability of beta features for a future version of the native app within an enrolled or current version of the native application before making the beta features available to all users **132** of the native application.

(35) In FIG. 5, a method **500** is provided for identifying and enrolling a beta user **134** as a user of a beta test group according to some embodiments. In step **505**, application system **112** identifies a select group of beta users **134** to test beta features of the native application. In one embodiment, the select group of beta users **134** is a subset of all users **132**. The beta users **134** may be selected from a current group of customers of provider **110**, or current users **132** of the native application provided by application system **112**.

(36) In one embodiment, application system **112** may select the beta users **134** according to any number of criteria. For example, the beta users **134** may be chosen from the most frequent users of a current version of the native application, or may be chosen based on particular demographics such as age, geographic location, net value of accounts, duration of being a customer, etc. In another embodiment, the beta users **134** may be determined from a random sample, or may be selected as a diverse group with little or no identifying characteristics. In yet another embodiment, application system **112** may seek interest from the general pool of users **132** to become one of beta users **134** without identifying any particular group of users. In the disclosed embodiments, a beta test group may include several hundred beta users **134** to several thousand beta users **134**. A beta test group may, alternatively, contain more or less beta users **134**. There is no artificial minimum or maximum on the number of beta users **134** that may be chosen to participate in a beta test group.

(37) Application system **112** may notify the selected users of their ability to join a beta test group (step **510**) according to any effective method for providing notices or communications to select users. For example, application system **112** may communicate with prospective beta users **134** via e-mail or text message, or upon the selected user accessing their account associated with the provider **110**, either online or through a native application of application system **112** via client device **130**. In another embodiment, a link may be provided to the prospective beta users **134**, directing them to a webpage or portal or the like, which enables the beta user **134** to participate in an enrollment or pre-registration process to join a beta test group. In another embodiment, the prospective beta users **134** may be requested to reply to any particular method of communication to enroll in a beta test group. Once application system **112** receives a user agreement to enroll in a beta test group (step **520**), via, e.g., client device **130**, application system **112** may receive user information from the enrolling beta user **134** (step **530**). User information may include a username, login identifier, account number, or any other credential or identifier used by application system **112** to identify a user **132**, **134**. In another embodiment, application system **112** may gather user information regarding the enrolling beta user **134** from information stored, for example, in database **340**. After obtaining information concerning the enrolling beta user **134**, application system **112** may update beta test group data stored, for example, in database **340** to include the enrolling beta user's **134** information (step **540**). Application system **112** may store a record or log, such as in database **340** or in authentication server **330** (FIG. 3), including identifying information for each beta user **134** enrolled in a beta test group. In another embodiment, application system **112** may update user identification records stored in database **340** with, for example, a flag or other indicator identifying the beta user **134** as enrolled in one or more beta test groups.

(38) In another embodiment, steps **510** and **520** of beta user registration process **500** may be omitted. For example, application system **112** may automatically enroll one or more of select users identified in step **505** in a beta test group. In this embodiment, application system **112** may enroll select beta users **134** without notifying the user. Application system **112** may gather user information (step **530**) regarding the select beta users **134** from information previously received or stored by application system **112**.

(39) According to one embodiment, a single beta test group may be chosen to test all available beta "features of a native application. As such, every beta user **134** may be enabled to test all beta features planned for the native application. In another embodiment, there may be more than one beta test group. For example, there may be a first beta test group for testing a first beta feature of the native application, and a second beta test group for testing a second and different beta feature of the native application. Additionally, there may be one or more combinations of beta test groups associated with one or more beta features or groups of beta features. In the exemplary embodiments, application system **112** may store identifying information for each beta user **134**, including an indication of one or more beta test groups in which the beta user **134** is selected to participate. In some embodiments, identification information for each beta user **134** may correspond to information associated with client device **130**, such as a device serial number, a network identifier, or any other indicia for identifying client device **130**.

(40) Once provider **110** or application system **112** enrolls a beta user **134** in a beta test group according to registration process **500**, for example, that beta user **134** may be enabled to access new beta features of an exemplary native application according to application process **600** (FIG. 6) executed by client device **130**. Prior to beginning application process **600**, a beta user **134** may have completed the application download process **400**. The latest, most recent, or most current version of the native application software may have been installed onto client device **130**.

According to an exemplary embodiment, the version of the native application software that has been installed onto client device **130** of a beta user **134** may be the same version installed on client devices of other users **132** that are not part of a beta test group. According to this embodiment, beta features may be made available to beta users **134** within the native application. As such, a beta user

134 may not be required to download and install a different version or a separate, beta version of the exemplary native application specifically to test the beta features. As discussed in detail below, the native application software provided to all users **132** may include “hidden” code defining the beta features or functionality and defining an interface to access the beta features. The “hidden” code may be “activated” or executed by client device **130** upon receipt of a signal from application system **112**, indicating that the particular user associated with client device **130** is a member of a beta test group (i.e., a beta user **134**).

(41) FIG. 6 shows an exemplary application process **600** according to the disclosed embodiments. According to process **600**, a user **132** or **134** may execute a native application via client device **130** (step **610**). A user **132** or **134** may execute the native application by selecting an icon corresponding to the native application by any input means available for client device **130** or by any other method. As discussed in detail above, an exemplary native application may be one of several applications **234** installed in memory unit **230** of client device **130**. Upon execution of the native application, processor **220** (FIG. 2) may execute native application software to display a user interface via display **210**. In an exemplary embodiment, the native application may display a user login screen requesting login credentials or other identifying information from user **132** or **134** for authenticating the user to receive specific content or services. In such an embodiment, user **132** or **134** may enter or otherwise provide the requested login information (step **620**), such as via input device **212**. In another embodiment, a native application may retrieve user identification information, such as information stored as data **236** in memory unit **230**, without requiring user input. In yet another embodiment, user identification information may correspond to identification information associated with client device **130** as opposed to user **132** or **134**. In such an embodiment, the native application may not require any user authentication procedure.

(42) Upon receiving or retrieving user identification information (step **620**), client device **130** executing the native application may transmit the user information to application system **112** (step **630**) via network **120** utilizing communication unit **214**.

(43) Referring now to FIG. 7, illustrating an exemplary beta user identification process **700**, application system **112** may receive the transmitted user identification information (step **710**) from client device **130** via network **120**. Application system **112**, via authentication server **330**, for example, may determine whether the user **132**, **134** is authorized to access content or receive a service (step **720**). In one embodiment, the native application enables access, e.g., by client device **130**, to user-specific financial information stored at or accessible by application system **112**. In such an embodiment, application system **112** may determine whether the received user identification information corresponds to an authorized user. For example, authentication server **330** may receive user identification information and compare such information to other data stored by authentication server **330** or database **340**, if authentication server **330** determines that user identification information does not correspond to an authorized user (step **720**; NO), then application system **112** may transmit an un-authentication signal to client device **130** (step **722**) indicating that the particular user **132**, **134** is unable to be authenticated by application system **112**. According to some embodiments, the native application does not require or desire user authentication, and step **720** may be omitted.

(44) If user authentication is required and user **132**, **134** is authenticated (step **720**; YES), application system **112** may determine whether the user is a beta user **134** (step **730**), as discussed above. The determination in step **730** may be performed by authentication server **330**, content server **320**, or any other appropriate means. In an exemplary embodiment, application system **112** may compare user identification information received from client device **130** with a beta test group record identifying enrolled beta users **134**. Additionally or alternatively, application system **112** may inspect a record corresponding to the identified user and determine whether that user is “flagged” as a beta user **134** or whether the user record includes any indicia indicating that user is a beta user **134**. As discussed above, in an alternative embodiment where user identification

information corresponds to identification information of client device **130**, determination as to whether the client device **130** is part of a beta test group may be performed in a similar manner. In the exemplary embodiments, if application system **112** has established more than one beta test group, application system **112** may determine each beta test group in which the beta user **134** or client device **130** is indicated as being a member.

(45) Application system **112** may also transmit a signal to client device **130**, including information indicating whether the client device **130** or user belongs to a beta test group. In an exemplary embodiment, the signal transmitted by application system **112** may be according to the specification of any network **120** or combinations of networks. If the user or client device **130** is a member of a beta test group (step **730**; YES), application system **112** transmits a beta test group signal to client device including information indicating the one or more beta test groups to which the beta user **134** or client device **130** belongs (step **740**). If a user **132** or client device **130** has not been previously enrolled as a beta test group member (step **730**; NO), then application system **112** transmits a non-test group signal to client device (step **750**). In one embodiment, application system **112** may also include authentication information as part of the signal transmitted in step **740** or **750**, if authentication is required.

(46) Returning back to FIG. **6**, client device **130** may receive the signal transmitted in step **740** or **750** via network **120** and communication unit **214** (step **640**). Processor **220** may be configured to process the received signal and to perform a next process under the instructions of the native application software and according to the received signal or signals. In step **640**, client device **130** may determine whether the received signal includes any beta test group information. If the received signal includes beta test group information (step **645**; YES), the native application may display a user interface that enables beta user **134** to access one or more new beta features (step **650**). For example, as shown in FIG. **8B**, a beta test menu **811a** may be made visible only for beta users **134**, in one embodiment, beta test menu **811a** may include an additional menu item or field such as the “Feature Center” field **822** displayed under “Tools” heading **820**. As compared to a menu **810** in FIG. **8A** that is displayed to non-beta users **132**, beta test menu **811a** shown in FIG. **8B** enables a beta user **134** to access beta features of the native application by selecting the “Feature Center” field **822**. If client device **130** determines that the received signal from application system **112** does not include beta test group information (step **645**; NO), client device **130** may execute the native application software instructions for displaying a “standard” non-beta test menu **810** (step **660**) that does not include access to “Feature Center” field **822**, for example.

(47) In another embodiment, beta test group information may be stored at client device **130** once received from application system **112** according to the above embodiments. Thus, after receiving a signal from application system **112** for the first time in step **640**, client device **130** may store the received beta test group information in memory **230**, for example, to be accessed each subsequent time a user **132** or **134** executes the native application. In another embodiment, a native application may also include software instructions to modify itself upon receipt of a first signal from application system **112** in step **640** to automatically display a beta test group interface, such as beta test menu **811a**, upon each subsequent execution of the native application at client device **130**. Thus, beta features may be made available to beta user **134** without receiving beta test group information from application system **112** or without retrieving such information from memory unit **230**, for example.

(48) In yet another embodiment, steps **620**, **630**, and **640** may be omitted or performed at another time, such as during the native application download process **400**. For example, prior to or as part of requesting download of a native application (step **410**), a user **132**, **134**, via, e.g., client device **130**, may provide identification information to application system **112**. During that process, application system **112** may determine whether the user and/or client device **130** is enrolled in a beta test group in a manner that may be similar to step **730** (FIG. **7**). If it is determined that the user or client device **130** is enrolled in a beta test group, application system **112** may provide additional

beta test group information along with the native application software for installation at client device **130**. As such, the installed native application may include instructions for executing code for displaying a beta test menu **811a**, such as shown in FIG. **8B**, upon execution of the native application. Accordingly, in one embodiment, a beta user **134** may be able to access beta features in the native application without specifically receiving a signal from application system **112** upon execution of the native application.

(49) In an alternative embodiment, upon application system **112** identifying a user as a beta user **134** (step **730**; YES), application system **112** may transmit or push to client device **130** additional code corresponding to beta functionality instead of or together with beta test group information (step **740**). For example, application system **112** may transmit executable code or instructions that when processed by processor **220** may enable beta functionality within the native application for a beta user **134**. The additional code may include instructions for displaying “Feature Center” field **822** or other beta features, as discussed below.

(50) In some embodiments, as shown in FIGS. **8B** and **8C**, a beta user **134** may be enabled to access and test new beta features by selecting “Feature Center” field **822**. Upon selecting “Feature Center” field **822**, the native application may instruct processor **220** to display a subsequent menu screen **830** corresponding to the Feature Center, as shown in FIG. **8C**. The code for displaying the subsequent menu screen **830** may be provided or received as part of the native application. As shown in FIG. **8C**, a number of beta features such as features **836**, **837**, and **838** may be made available to a beta user **134** for beta testing. Beta user **134** may then select a download/install icon **839** corresponding to each beta feature displayed to install that particular feature to client device **130**. In one embodiment, software code corresponding to a particular beta feature, such as feature **836**, may be received by client device **130** together with the native application during the download process, such as during step **420** (FIG. **4**). As such, each beta feature may already be stored at client device **130** prior to selecting download/install icon **839**. In an alternative embodiment, upon selecting download/install icon **839** corresponding to a particular beta feature, beta user **134** may be directed to subsequently receive and download software code for the beta feature from application system **112** in a manner similar to application download process **400**.

(51) According to the exemplary embodiments, the beta features may include any particular functionality that provider **110** desires to provide users **132**, **134** of its native application. For example, as shown in FIG. **8C**, one such beta feature may correspond to a “Refer a Friend” feature **836**. In one embodiment, “Refer a Friend” feature **836** enables a user **132**, **134** of the native application to recommend the native application to another friend. Beta features **836**, **837**, and **838** may enable new transactions or operations, and in the disclosed embodiments, such beta features are fully workable within the native application.

(52) In one embodiment, application system **112** can dynamically control which beta features within the Feature Center menu **830** are made available, if at all, to select groups of beta users **134**. For example, application system **112** may form a number of beta test groups for testing particular beta features of the native application. In this embodiment, application system **112** in step **740** (FIG. **7**) may include such group information indicating the one or more beta test subgroups to which the beta user **134** or client device **130** belongs. As such, the native application executed at client device **130** may execute specific software code directed only to the one or more beta features designated for a particular beta test group according to the received beta test group information. For example, a particular beta user may not be able to access or view every beta feature contemplated by application system **112**. As such, upon accessing the Feature Center shown in screen **830** (FIG. **8C**), only select beta features may be made available for a particular beta user **134** to install on client device **130** according to received beta test group information.

(53) In another embodiment, application system **112** may dynamically update or add new beta features accessible via a Feature Center menu **830** for any particular beta test group. According to this embodiment, Feature Center menu **830** may provide access to beta features stored at

application system **112**, for example, via one or more links to the beta features. In one embodiment, the one or more links may correspond to a storage location enabling a beta user **134** to receive and download software code for the beta feature from application system **112**. In another embodiment, the one or more links may direct a beta user **134** to a mobile web page providing access to one or more beta features, as discussed below.

(54) In yet another embodiment, Feature Center menu **830** may be provided as a mobile web page that is accessible within the native application. As such, a beta user **134** may be redirected within the native application to an internet web page, such as a mobile web page, upon selecting the “Feature Center” field **822**. In this embodiment, the mobile web page may be provided by content server **320** of application system **112**. Application system **112** may then dynamically add or update any number of beta features which are made accessible to beta user **134** through such a mobile web page. Beta user **134** may then be able to select (via, e.g., client device **130**) which of the new beta features it desires to install onto client device **130** according to the above embodiments. For example, upon selecting a download/install icon **839**, client device **130** may receive software corresponding to the selected feature for download similar to application download process **400** (FIG. 4).

(55) In another embodiment, all users **132**, **134** of a native application may have access to the Feature Center menu **830** within the native application, however, only beta users **134** may be able to see and/or select one or more beta features. For example, a Feature Center according to the alternative embodiment may include a number of features, some of which are beta features made available only to beta users **134**. In such an embodiment, the native application may direct non-beta users **132** to a first Feature Center displaying features available for all users, whereas beta users **134** may be directed to a second Feature Center displaying additional beta features. The separate first and second Feature Centers may be individual mobile web pages accessible within the native application, similar to the above embodiment. In this embodiment, the native application may direct a beta user **134** to the second Feature Center web page according to beta test group information received from application center **112**, such as according to steps **640** and **740** (FIGS. 6 and 7, respectively).

(56) In yet another embodiment, application system **112** may transmit or push additional software code or instructions corresponding to new beta features to client device **130**. Application system **112** may push the additional code to a select group of beta users **134** or all beta users **134**. The additional beta feature code may be transmitted to client device **130** of a beta user **134** upon executing the native application at client device **130**. Alternatively, application system **112** may transmit new beta feature code to beta users **134** on a scheduled release or at any desired time for releasing new beta functionality to beta users **134**. For example, application system **112** may transmit executable code or instructions that when processed by processor **220** enable a beta user **134** to execute the beta features and functionality. The additional code may include instructions for displaying the beta feature in beta feature screen **830**, as shown in FIG. 8C, corresponding to the Feature Center. The additional code may also include instructions enabling functionality of the new beta feature upon installation of the beta feature in the manner discussed above.

(57) Upon installing a beta feature, such as **836**, **837**, or **838**, at client device **130**, according to any of the above embodiments, a native application may be configured to display the installed beta feature within a user interface such as shown in menu **811b** in FIG. 8D. Interface menu **811b** may be substantially the same as the beta test menu **811a** (FIG. 8B), except it may provide one or more new fields within the native application interface corresponding to the installed one or more beta features, such as field **824** corresponding to an installed “Refer a Friend” beta feature **836**, by way of example. The exemplary embodiments are advantageous at least because a beta feature can be tested in real-time, or substantially real-time, as part of an interface as would be implemented in a full rollout of the feature within a native application made available for all users **132**, **134**. For example, a beta user **134** can now access and test “Refer a Friend” beta feature **836** as it would any

other feature available in the standard version of the native application available for all other users **132**. Furthermore, beta user **134** is not required to download a new beta version of the native application in order to test a beta feature. Additionally, beta user **134** is enabled to choose to install only those beta features that it may find desirable and uninstall any beta feature it does not desire, such as by selecting an uninstall icon **904** shown in FIG. **9A**. Accordingly, the overall beta test experience for a beta user **134** is more closely simulated to a regular user experience and is more convenient for the beta user **134**, thus resulting in improved beta testing metrics.

(58) According to the exemplary embodiments, beta testing results may be received (by, for example, application system **112**) as feedback from beta users **134** and/or from analytics or metrics captured in the background regarding how the particular beta user **134** uses a beta feature. In one embodiment, as shown in FIGS. **9A** and **9B**, once a new beta feature is installed to client device **130**, the native application enables beta user **134** to rate the beta feature and provide specific comments concerning the beta feature and its interaction with the native application. For example, a beta user **134** may be able to rate an installed beta feature by selecting a rate icon **902** within the Feature Center, as shown in FIG. **9A**. Alternatively, a rating icon or interface may be displayed upon accessing the beta feature itself. Upon selecting rate icon **902**, beta user **134** may be directed to a second screen **906**, as shown in FIG. **9B**, providing an interface for rating the beta feature. For example, a beta user **134** may be able to rate the “Refer a Friend” beta feature **836** on a particular number or other scale such as a star scale shown in field **908**. Additionally, beta user **134** may be prompted to enter more detailed rating or review information such as via field **909**. Upon completion of its review, beta user **134** may transmit the rating and review information to application system **112** such as by selecting a send icon **910**. In one embodiment, beta user **134** may be prompted to rate or review a particular beta feature immediately after utilizing the beta feature or a particular aspect of the beta feature. Additionally, in another embodiment, the native application may provide a rating section or rating icon for each particular aspect of a beta feature, such as regarding visual aesthetics, ease of use, ways to improve, desirability of the feature, etc. The rating section may be displayed on each screen or interface viewed within the beta feature or native application as desired. In one embodiment, a beta user **134** may be encouraged to rate a particular beta feature by incentivizing them with the prospect of being granted access to additional beta features, more favorable account terms (such as a higher interest rate on savings account, lower interest rates on credit cards, etc.), or other incentives.

(59) In one embodiment, analytics and metrics may also be captured in real-time (or substantially real-time) based on a beta user's **134** use of a particular beta feature or standard feature, and automatically uploaded or sent to application system **112**. For example, any number of analytics or metrics may be captured in real-time, such as the length of time it takes a beta user **134** to execute a process, the number and frequency of interactions with the beta feature, how often a beta user **134** may request additional assistance from provider **110**, when a beta user **134** exits the feature or the native application, and whether inclusion of the beta feature results in increased interaction with other features of the native application, etc. The particular analytics that may be analyzed are limitless and are not limiting of the exemplary embodiments. According to the exemplary embodiments, the gathered analytics may be compared to other non-beta users **132** and other beta users **134**. The comparisons may then be analyzed in a number of ways as desired. For example, the compared analytics may enable provider **110** or application system **112** to determine and report statistics indicating whether the beta features and functionality improve or increase user engagement with the native application based on, for example, the number of interactions with a feature of a particular user pre- and post-installation of the beta features, the number of user interactions with one or more features between distinct beta and non-beta users, etc.

(60) Additionally, application system **112** may prompt a beta user **134** to provide additional information concerning its use of the particular beta feature or the native application if it identifies a particular pattern of behavior. For example, if a beta user **134** frequently exits the native

application without completing a process within the application or a beta feature, application system **112** may prompt beta user **134** to explain those actions. Such prompt may be displayed to beta user **134** within the native application itself, by e-mail, or any other suitable method.

(61) Application system **112** may be capable of sorting the received ratings and reviews and all other gathered analytics and metrics concerning a beta user's **134** use of a particular beta feature or the native application. Application system **112** may then use this information to improve a beta feature before making it available to all other users **132**, if desirable. In some embodiments, a beta feature may be updated and then provided to a new group of beta users **134** to test the updated functionality of such beta feature. Each new beta feature may be frequently updated and provided to new beta users **134**, if desired, until the beta feature is ready to implement to all other users **132** of the native application. Such beta testing processes may enable application system **112** to rapidly implement compelling new features and improve current features to maintain a positive customer experience with the native application.

(62) The above embodiments are not limited to any particular operating system or platform. Each of the above embodiments may be realized by implementing any software development kit available for any particular operating system or platform. Although embodiments may be implemented as computer processing instructions, all or a portion of the functionality of disclosed embodiments may be implemented instead in electronics hardware. Other embodiments will be apparent to those skilled in the art from consideration of the specification and practice of the disclosed embodiments. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the disclosed embodiments being indicated by the following claims. Furthermore, although aspects of the disclosed embodiments are described as being associated with data stored in memory and other tangible computer-readable storage mediums, one skilled in the art will appreciate that these aspects can also be stored on and executed from many types of tangible computer-readable media, such as secondary storage devices, like hard disks, floppy disks, or CD-ROM, or other forms of RAM or ROM. Accordingly, the disclosed embodiments are not limited to the above described examples, but instead is defined by the appended claims in light of their full scope of equivalents.

Claims

1. A system for determining feature sets for a user, the system comprising: one or more processors and non-transitory computer-readable media comprising instructions that, when executed by the one or more processors, cause operations comprising: receive a first user request, from a first user, to access a native application stored at a client device comprising a first feature set and a second feature set; in response to receiving the first user request, determining whether to provide the first user access to (i) first features of the second feature set or (ii) second features of the second feature set that are different from the first features of the second feature set; in response to determining that the first user is to be provided access to the first features of the second feature set: enabling the first user to access the first features of the second feature set and the first feature set via the native application; and generating for display, in the native application on the client device, a first set of icons, wherein the first set of icons are related to the first features of the second feature set and the first feature set; and in response to determining that the first user is to be provided access to the second features of the second feature set: enabling the first user to access the second features of the second feature set and the first feature set via the native application; and generating for display, in the native application on the client device, a second set of icons, wherein the second set of icons are related to the second features of the second feature set and the first feature set.

2. One or more non-transitory computer-readable media comprising instructions that, when executed by one or more processors, cause operations comprising: receiving a first user request, from a first user, to access a native application, wherein the native application comprises a first

feature set and a second feature set; in response to receiving the first user request, determining whether to provide the first user access to (i) first features of the second feature set or (ii) second features of the second feature set that are different from the first features of the second feature set; in response to determining that the first user is to be provided access to the first features of the second feature set, enabling the first user to access the first features of the second feature set and the first feature set via the native application; and generating for display, in the native application, a first set of icons, wherein the first set of icons are related to the first features of the second feature set and the first feature set.

3. The one or more non-transitory computer-readable media of claim 2, the operations further comprising: in response to determining that the first user is to be provided access to the second features of the second feature set, enabling the first user to access the second features of the second feature set and the first feature set via the native application; and generating for display, in the native application, a second set of icons, wherein the second set of icons are related to the second features of the second feature set and the first feature set.

4. The one or more non-transitory computer-readable media of claim 2, the operations further comprising: storing test group identification information for the first user; and accessing the test group identification information to determine whether to enroll the first user in a first test group or a second test group, wherein the first test group is associated with testing the first features of the second feature set, and wherein the second test group is associated with testing the second features of the second feature set.

5. The one or more non-transitory computer-readable media of claim 4, further comprising: determining a subgroup of the first user based on the test group identification information for the first user; and selecting the first user in the first test group based on the subgroup.

6. The one or more non-transitory computer-readable media of claim 2, further comprising: monitoring a length of time that the first user accesses the first set of icons; and transmitting the length of time to a remote device.

7. The one or more non-transitory computer-readable media of claim 2, further comprising: monitoring a frequency of interactions of the first user with the first set of icons; and transmitting the frequency of interactions to a remote device.

8. The one or more non-transitory computer-readable media of claim 2, further comprising: monitoring a number of requests from the first user for additional assistance; and transmitting the number of requests to a remote device.

9. The one or more non-transitory computer-readable media of claim 2, further comprising: monitoring a time when the first user exits the native application; and transmitting the time to a remote device.

10. The one or more non-transitory computer-readable media of claim 2, further comprising: receiving an initial request from a client device to download the native application to the client device; and in response to the initial request, accessing test group identification information to determine whether to provide the first user access to (i) the first features of the second feature set or (ii) the second features of the second feature set.

11. The one or more non-transitory computer-readable media of claim 2, further comprising: selecting a current feature in the first features of the second feature set; and dynamically updating the current feature.

12. A method for determining feature sets for a user, the method comprising: receiving a first user request, from a first user, to access a native application, wherein the native application comprises a first feature set and a second feature set; in response to receiving the first user request, determining whether to provide the first user access to (i) first features of the second feature set or (ii) second features of the second feature set that are different from the first features of the second feature set; in response to determining that the first user is to be provided access to the first features of the second feature set, enabling the first user to access the first features of the second feature set and

the first feature set via the native application, wherein it is determined that the first user is to be provided access to the first features of the second feature set; and generating for display, in the native application, a first set of icons, wherein the first set of icons are related to the first features of the second feature set and the first feature set.

13. The method of claim 12, further comprising: in response to determining that the first user is to be provided access to the second features of the second feature set, enabling the first user to access the second features of the second feature set and the first feature set via the native application; and generating for display, in the native application, a second set of icons, wherein the second set of icons are related to the second features of the second feature set and the first feature set.

14. The method of claim 12, further comprising: storing test group identification information for the first user; and accessing the test group identification information to determine whether to enroll the first user in a first test group or a second test group, wherein the first test group is associated with testing the first features of the second feature set, and wherein the second test group is associated with testing the second features of the second feature set.

15. The method of claim 14, further comprising: determining a subgroup of the first user based on the test group identification information for the first user; and selecting the first user in the first test group based on the subgroup.

16. The method of claim 12, further comprising: monitoring a length of time that the first user accesses the first set of icons; and transmitting the length of time to a remote device.

17. The method of claim 12, further comprising: monitoring a frequency of interactions of the first user with the first set of icons; and transmitting the frequency of interactions to a remote device.

18. The method of claim 12, further comprising: monitoring a number of requests from the first user for additional assistance; and transmitting the number of requests to a remote device.

19. The method of claim 12, further comprising: monitoring a time when the first user exits the native application; and transmitting the time to a remote device.

20. The method of claim 12, further comprising: receiving an initial request from a client device to download the native application to the client device; and in response to the initial request, accessing test group identification information to determine whether to provide the first user access to (i) the first features of the second feature set or (ii) the second features of the second feature set.
