

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415069
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Liu; Lili et al.

Activation fixation lead for cardiac conductive system pacing

Abstract

Various aspects of the present disclosure are directed toward apparatuses, systems, and methods that include an implantable lead. The lead may include a taper or tapered portion and a fixation helix both configured to embed within tissue. In addition, the apparatuses, systems, and methods may include a guide wire configured to obtain and record signals from the heart tissue and facilitate placement of the fixation helix.

Inventors: Liu; Lili (St Paul, MN), Foster; Arthur J. (Blaine, MN), Miller; Matthew J. (Stillwater, MN)

Applicant: Cardiac Pacemakers, Inc. (St Paul, MN)

Family ID: 1000008821383

Assignee: Cardiac Pacemakers, Inc. (St. Paul, MN)

Appl. No.: 17/839633

Filed: June 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220305255 A1	Sep. 29, 2022

Related U.S. Application Data

continuation parent-doc US 16722470 20191220 US 11383079 child-doc US 17839633
us-provisional-application US 62783916 20181221

Publication Classification

Int. Cl.: A61N1/05 (20060101); A61N1/362 (20060101)

U.S. Cl.:

CPC **A61N1/0573** (20130101); **A61N1/362** (20130101); A61N2001/058 (20130101)

Field of Classification Search

CPC: A61N (1/0573); A61N (1/362); A61N (2001/058)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5658327	12/1996	Altman et al.	N/A	N/A
7212870	12/2006	Helland	607/122	A61N 1/0573
7379776	12/2007	Chitre	604/528	A61N 1/056
8160721	12/2011	Cooke et al.	N/A	N/A
9149632	12/2014	Vase	N/A	N/A
11383079	12/2021	Liu et al.	N/A	N/A
2003/0109914	12/2002	Westlund et al.	N/A	N/A
2004/0024425	12/2003	Worley	607/27	A61N 1/056
2004/0064172	12/2003	McVenes	607/122	A61N 1/056
2005/0070988	12/2004	Kawula	607/126	A61N 1/0575
2006/0036307	12/2005	Zarembo et al.	N/A	N/A
2008/0294229	12/2007	Friedman et al.	N/A	N/A
2009/0259272	12/2008	Reddy	607/9	A61N 1/0573
2010/0324636	12/2009	Hill et al.	N/A	N/A
2012/0035590	12/2011	Whiting	604/528	A61M 25/09
2012/0130220	12/2011	Maskara	600/374	A61B 5/287
2012/0232373	12/2011	Hallander	607/116	A61B 5/6882
2013/0053851	12/2012	Schmitz	606/79	A61B 17/3421
2015/0366581	12/2014	Hincapie Ordonez	606/129	A61B 90/37
2020/0197693	12/2019	Liu et al.	N/A	N/A

Primary Examiner: Fairchild; Mallika D

Attorney, Agent or Firm: Nelson Mullins Riley & Scarborough LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a Continuation application that claims priority to U.S. application Ser. No. 16/722,470, filed Dec. 20, 2019, which claims priority to Provisional Application No. 62/783,916, filed Dec. 21, 2018, which are herein incorporated by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates to leads and stimulation systems. In particular, the present disclosure relates to leads and stimulation of the bundle of His or left or right bundle branch.

BACKGROUND

(2) Cardiac rhythm management systems are useful for electrically stimulating a patient's heart to treat various cardiac arrhythmias. Placement of a lead for stimulation of the patient's heart may be difficult based on the location of a stimulation target, size of the stimulation target, and/or the depth of the stimulation target. The bundle of HIS, for example, is subsurface. The left and right bundle branches, for example, may be difficult to locate. There is a continuing need for improved targeting difficult stimulation targets such as the bundle of His and the left and right bundle branches.

SUMMARY

(3) In Example 1, an implantable lead includes: an elongate body extending between a proximal end and a distal end and including at least one lumen extending between the proximal end and the distal end, the distal end of the elongate body configured to embed within heart tissue and reducing in diameter with a taper ending at the distal end and with a maximum diameter of the taper being substantially equal to a maximum outer diameter of the elongate body; and a fixation helix extending from distally from the at least one lumen and configured to rotate and therefore translate relative to the elongate body.

(4) In Example 2, the implantable lead of Example 1, the lead is configured to embed at the heart tissue and the fixation helix is electrically active and configured to pace a left bundle branch or a right bundle branch of a patient.

(5) In Example 3, the implantable lead of any one of Examples 1-2, the distal end of the lead body includes a tapered portion reducing the elongate body in diameter with the reduction in diameter having a minimum at the distal end.

(6) In Example 4, the implantable lead of Example 3, wherein the tapered portion facilitates penetration into the heart tissue.

(7) In Example 5, the implantable lead of any one of Examples 2-4, the tapered portion includes an outer diameter that is substantially equal to an outer diameter of the fixation helix.

(8) In Example 6, the implantable lead of any one of Examples 1-5, the fixation helix is configured to extend beyond the distal end of the elongate body by between approximately 2 mm and approximately 4 mm.

(9) In Example 7, the implantable lead of any one of Examples 1-6, the lead also includes a wire having a length to pass from the proximal end of the elongate body and extend outwardly from the distal end of the elongate body and configured to obtain and record signals from the heart tissue.

(10) In Example 8, the implantable lead of Example 7, a distal end of the wire being configured to penetrate the heart tissue and facilitate placement of the fixation helix in the heart tissue.

(11) In Example 9, the implantable lead of Example 8, the lead also includes an electrode arranged near the distal end of the elongate body, and wherein the fixation helix and the electrode are configured to pace the heart tissue and the wire is configured to simultaneously obtain and record signals from the heart tissue.

(12) In Example 10, the implantable lead of Example 9, the electrode is arranged between approximately 3 mm and approximately 10 mm from the distal end of the elongate body.

(13) In Example 11, the implantable lead of any one of Examples 7-10, the wire includes a proximal end, a distal end, and an insulated intermediate portion with the distal end of the wire being between approximately 2 mm and approximately 4 mm in length.

(14) In Example 12, the implantable lead of Example 11, the proximal end of the wire is uninsulated and configured to interface with a mapping processor.

(15) In Example 13, the implantable lead of any one of Examples 7-12, the wire includes markers arranged near a proximal end of the wire configured to control a penetration depth of the wire.

(16) In Example 14, the implantable lead of Example 13, wherein a portion of the distal end of the wire is radiopaque.

(17) In Example 15, the implantable lead of any one of Examples 1-14, at least a proximal portion of the fixation helix is insulated and at least one turn of a distal end of the fixation helix is uninsulated.

- (18) In Example 16, an implantable lead for pacing a left or right bundle branch of a patient's heart includes an elongate body extending between a proximal end and a distal end and including at least one lumen extending between the proximal end and the distal end, the distal end of the elongate body configured to embed within heart tissue and including a tapered portion reducing the elongate body in diameter with a minimum of the tapered portion at the distal end and a maximum diameter of the tapered portion being substantially equal to a maximum outer diameter of the elongate body; and a fixation helix extending from distally from the at least one lumen and configured to rotate and therefore translate relative to the elongate body.
- (19) In Example 17, the implantable lead of Example 16, the tapered portion facilitates penetration into the heart tissue.
- (20) In Example 18, the implantable lead of Example 16, the tapered portion includes an outer diameter that is substantially equal to an outer diameter of the fixation helix.
- (21) In Example 19, the implantable lead of Example 16, the fixation helix is configured to extend beyond the distal end of the elongate body by between approximately 2 mm and approximately 4 mm.
- (22) In Example 20, the implantable lead of Example 16, the lead also includes a wire having a length to pass from the proximal end of the elongate body and extend outwardly from the distal end of the elongate body and configured to obtain and record signals from the heart tissue.
- (23) In Example 21, the implantable lead of Example 20, a distal end of the wire being configured to penetrate the heart tissue and facilitate placement of the fixation helix in the heart tissue.
- (24) In Example 22, the implantable lead of Example 16, the lead also includes an electrode arranged near the distal end of the elongate body, and wherein the fixation helix and the electrode are configured to pace the heart tissue and the wire is configured as a unipolar electrode to simultaneously obtain and record signals from the heart tissue.
- (25) In Example 23, the implantable lead of Example 23, the fixation helix and the wire configured as bipolar electrodes to obtain and record signals from the heart tissue.
- (26) In Example 24, a system for pacing a patient's heart includes an implantable lead including: an elongate body extending between a proximal end and a distal end and including at least one lumen extending between the proximal end and the distal end, and a fixation helix extending from distally from the at least one lumen and configured to rotate and therefore translate relative to the elongate body; and a guide wire having a proximal end, a distal end, and an insulated intermediate portion and configured to obtain and record signals from the heart tissue and facilitate placement of the fixation helix.
- (27) In Example 25, the system of Example 24, the lead is configured to embed at the heart tissue and the fixation helix is electrically active and configured to pace a left bundle branch or a right bundle branch of the patient.
- (28) In Example 26, the system of Example 24, the fixation helix is electrically active and configured to pace a His bundle the patient.
- (29) In Example 27, the system of Example 24, the guide wire is configured as a unipolar electrode to obtain and record signals from the heart tissue.
- (30) In Example 28, the system of Example 24, the fixation helix and the guide wire are configured as bipolar unipolar electrodes to obtain and record signals from the heart tissue.
- (31) In Example 29, the system of Example 24, the distal end of the guide wire is between approximately 2 mm and approximately 4 mm in length and is configured to control a penetration depth of the guide wire.
- (32) In Example 30, the system of Example 27, the guide wire includes markers arranged near a proximal end of the wire configured to control a penetration depth of the wire.
- (33) In Example 31, a method of pacing a patient's heart includes delivering an implantable lead to a target location within a patient using a guide wire, the implantable lead including an elongate body extending between a proximal end and a distal end and including at least one lumen extending

between the proximal end and the distal end, and a fixation helix extending from distally from the at least one lumen and configured to rotate and therefore translate relative to the elongate body; penetrating heart tissue at a His bundle or bundle branch with a distal end of the guide wire; obtaining signals from the heart tissue at the His bundle or the bundle branch with the guide wire; and penetrating the heart tissue with the fixation helix.

(34) In Example 32, the method of Example 31, obtaining signals from the heart tissue with the guide wire includes operating the guide wire as a unipolar electrode.

(35) In Example 33, the method of Example 31, obtaining signals from the heart tissue with the guide wire includes operating the guide wire and the fixation helix as bipolar electrodes.

(36) In Example 34, the method of Example 31, penetrating the heart tissue with the fixation helix occurs while the guide wire is imbedded in the heart tissue.

(37) In Example 35, the method of Example 31, penetrating heart tissue occurs at the bundle branch and the implantable lead includes a tapered portion reducing the elongate body in diameter with a minimum of the tapered portion at the distal end.

(38) While multiple instances are disclosed, still other instances of the present invention will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative instances of the invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 a schematic diagram of a stimulation system including a pulse generator and a lead implanted in a patient's heart, in accordance with certain instances of the present disclosure.

(2) FIG. 2 is an illustration of an example implantable lead, in accordance with certain instances of the present disclosure.

(3) FIG. 3 is an illustration of an example implantable lead and wire, in accordance with certain instances of the present disclosure.

(4) FIG. 4 is an illustration of another stimulation system including an implantable lead, in accordance with certain instances of the present disclosure.

(5) FIG. 5 is an illustration of an example wire, in accordance with certain instances of the present disclosure.

(6) While the invention is amenable to various modifications and alternative forms, specific instances have been shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the invention to the particular instances described. On the contrary, the invention is intended to cover all modifications, equivalents, and alternatives falling within the scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

(7) Various aspects of the present disclosure are directed toward lead fixation and lead location. Certain leads, such as those discussed herein, may include a fixation helix that is embedded into tissue of the heart to fixate the lead. In certain instances, a lead tip or a distal end of the lead may shift or move while the lead or helix is rotated to fixate the lead. Various aspects of the present disclosure are directed toward a lead and guide wire that facilitates placement of the lead. The guide wire, for example, can be used to penetrate the heart tissue and map the targeted pacing location. The guide wire may penetrate the tissue in order to locate the targeted stimulation area along the heart tissue surface and also a penetration depth for the fixation helix. In addition, the guide wire may help stabilize and facilitate embedding of the fixation helix in the heart tissue.

(8) Various aspects of the present disclosure are also directed toward a lead that may be embedded in the heart tissue. The left and right bundle branches, for example, are located within a septum of

the heart. It may be beneficial for the fixation helix to be embedded in the septum in order to effectively pace the left bundle branch and/or right bundle branch. As compared to leads used in other areas of the heart that target areas of the heart having thin or fragile tissue, the lead itself may include a tapered distal end that embedded in the tissue wall when targeting the subsurface left bundle branch and/or right bundle for stimulation. In addition, the guide wire, as discussed above, may facilitate location of the left bundle branch and/or right bundle and penetration of the fixation helix.

(9) The output of the heart is dependent on the synchrony of contraction within, and between, the chambers of the heart. Normally, each cardiac cycle is initiated by the depolarization of cells in the sinoatrial node which starts contraction of the cardiac muscle cells of the atria. The electrical impulse continues to the atrioventricular node, which delays propagation of the signal to allow the atria to contract before the ventricles. The distal portion of the atrioventricular node comprises the bundle of His. The bundle of His propagates the depolarization signal to left and right branches in the interventricular septum. The left and right branches propagate the depolarization signal to the left and right ventricles, respectively.

(10) Various conditions can interfere with the normal electrical conduction system of the heart, which can result in arrhythmia and can compromise the output of the heart. For example, conduction block along the atrioventricular node can cause the atria and ventricles to contract out of rhythm. Conventional pacing therapies attempt to bypass the conduction system between the atria and ventricles by implanting a lead in the apex of the right ventricle where, ideally, each pulse delivered to cardiac muscle tissue propagates in a depolarization wave. However, direct stimulation of working myocardium (e.g., at the apex of the right ventricle) can result in slower propagation than direct stimulation of specialized conduction system fibers. For these and other reasons, it can be difficult to replicate the synchronous contractions of a natural conduction system by pacing at the apex of the right ventricle or other working myocardial site alone.

(11) FIG. 1 illustrates a schematic diagram of a stimulation system 2 for direct stimulation of a patient's heart. In certain instances, the system 2 may be provided for direct stimulation of the bundle of His 30 or the left bundle branch and/or right bundle branch 32 within the septum 38 (between the left ventricle 22 and the right ventricle 24) as described in further detail. The stimulation system 2 includes an implantable pulse generator 6. The implantable pulse generator 6 can include circuitry for sensing bioelectrical signals and/or delivering electrical stimulation via one or more leads. The implantable pulse generator 6 can include a header 8 for connecting one or more leads to the implantable pulse generator 6. The header 8 can individually connect to respective contacts on the proximal end of the one or more leads, the contacts in respective electrical connection with electrical elements on the distal ends of the one or more leads (e.g., ring electrode, conductive helix) via conductors within the one or more leads.

(12) As shown in FIG. 1, a lead 10 implanted is connected with the implantable pulse generator 6 through the header 8. The lead 10 operates to convey electrical signals between the bundle of His 30 or left/right bundle branches 32 and the implantable pulse generator 6. In various instances, the lead 10 enters the vascular system through a vascular entry site formed in the wall of the left subclavian vein, extends through the left brachiocephalic vein and the superior vena cava 34, traverses the right atrium 26, and is implanted in the right ventricle 24 proximate the bundle of His 30 or left/right bundle branches 32. In other instances, the lead 10 may enter the vascular system through the right subclavian vein, the left axillary vein, the left external jugular, the left internal jugular, or the left brachiocephalic vein, for example. Other suitable vascular access sites may be utilized in various other instances.

(13) In certain instances, the lead 10 is a multi-polar medical electrical lead that includes a lead body formed from one or more materials, at least one lumen formed within the lead body, a proximal connector for interfacing with the implantable pulse generator 6, one or more electrical elements (e.g., ring electrodes, conductive helix) on the distal end of the lead 10, and one or more

conductors for conducting electrical energy (e.g., bioelectrical signals, stimulation pulses) between the one or more electrical elements and the proximal connector. The lead **10** can have a flexible tubular body having an outer surface. The tubular body can be made from various materials such as silicone rubber and/or polymer material (e.g., polyurethane). In some cases, a distal portion of the lead is more flexible than a proximal portion of the lead. For example, the tubular body and external surface of the distal end of the lead **10**, corresponding to a distal portion of the lead within the right ventricle **24** proximate the target stimulation location, can be less stiff relative to a proximal portion that traverses the tricuspid valve **28** and continues to the lead interface **8**. For example, the lead body and external surface of the distal portion can be made from silicone while the lead body and the external surface of the proximal portion can be made from polyurethane to configure the lead to have the distal portion be more flexible than the proximal portion.

(14) The lead **10** can include a fixation element (e.g., a helix) **18** which can fix the lead **10** to cardiac tissue. The fixation element **18** can be electrically coupled to an electrical conductor (e.g., one or more coils or one or more cable conductors) extending to the proximal end of the lead **10** for interfacing with a channel of the implantable pulse generator **6**. As such, a fixation element **18** can mechanically and electrically couple the lead **10** to the tissue and facilitate the transmission of electrical energy from the bundle of His **30** or left/right bundle branches **32** in a sensing mode and to the bundle of His **30** or left/right bundle branches **32** in a stimulation mode. As discussed in further detail below, the lead **10** may be used with a guide wire that can be configured to function as an electrode and penetrating structure to facilitate locating of a desired or effective stimulation location for the bundle of His **30** or left/right bundle branches **32**. In instances where the lead **10** is used for pacing the left/right bundle branches **32**, the lead **10** may include a portion that is embedded in the heart tissue.

(15) FIG. **2** is an illustration of an example implantable lead **200**, in accordance with certain instances of the present disclosure. The lead **200** shown in FIG. **2** is particularly used for stimulation of the left and/or right bundle branches. The lead **200**, for example, includes an elongate body **202** that extends between a proximal end (not shown) that is configured to interface with an implantable pulse generator and a distal end **204**.

(16) The elongate body **204** may also include a lumen (e.g., as shown in FIG. **3**) that extends between the proximal end and the distal end **204**. In addition and as shown, the distal end **204** may be configured to embed within heart tissue and reduce in diameter with a taper ending at the distal end **204**. As shown in FIG. **2**, the distal end **204** includes a tapered portion **206** that reduces the elongate body **204** in diameter. The tapered portion **206** facilitates embedding of the lead **200** into tissue. As shown, the tapered portion **206** includes a maximum diameter that is substantially equal to a maximum outer diameter of the elongate body **204**.

(17) In addition and as shown in FIG. **2**, the elongate body **204** may also include a fixation helix **208** extending from distally from the at least one lumen of the elongate body **202** and configured to rotate and therefore translate relative to the elongate body **202**. In certain instances, the fixation helix **208** may be configured to function as an electrode.

(18) The tapered portion **206** may facilitate pacing for use with left bundle branch and/or right bundle branch stimulation (or other subsurface stimulation locations). As shown in FIG. **2**, the tapered portion **206** reduces the elongate body **202** in diameter with the reduction in diameter having a minimum (or terminating) at the distal end **204**. The lead **200** is to embed at the heart tissue and the fixation helix **208** is electrically active and configured to pace a left bundle branch or a right bundle branch of a patient. Leads configured to pace other portions of the heart may not include a taper or other similar structure that facilitates embedding of the lead within heart tissue due to tissue being thin or otherwise fragile. The left bundle branch and right bundle branch are within the heart septum, which is thicker or stronger than other portions of the heart. In addition, the left bundle branch and right bundle branch are subsurface, therefore, it is beneficial for the fixation helix **208** to penetrate into the tissue deeper than other leads configured to penetrate other

portions of the heart. The tapered portion **206** facilitates embedding (and penetration) of the fixation helix **208** to stimulate or pace the left bundle branch and/or right bundle branch.

(19) As shown in FIG. 2, the tapered portion **206** may include an outer diameter that is substantially equal to an outer diameter of the fixation helix **208**. In certain instances, the diameters being substantially equal may facilitate a transition between the fixation helix **208** and the tapered portion **206** and thereby facilitate embedding of the lead **200** within the heart tissue.

(20) In certain instances, the fixation helix **208** is configured to extend beyond the distal end **204** of the elongate body **202** by between approximately 2 mm and approximately 4 mm (as compared to 1.8 mm, for example, in certain bradycardia leads). The length **210** of the fixation helix **208** may facilitate embedding of the electrically active embedding to target and stimulate the subsurface left or right bundle branches. In certain instances, the lead **200** may also include an electrode **212** arranged near the distal end **204** of the elongate body. The electrode **212** and the fixation helix **208** may be configured to stimulate the tissue in a bipolar manner. The electrode **212** may be spaced apart from the distal end **204** of the elongate body **202** by a length **214** where the length **214** is between approximately 3 mm and approximately 10 mm. In certain instances, the electrode **212** may be configured as anode and the fixation helix **208** may be configured as a cathode. In certain instances, the electrode **212** may be configured as cathode and the fixation helix **208** may be configured as an anode. The maximum diameter of the elongate body **206** includes the electrode **212**. The maximum diameter of the elongate body **206** and the tapered portion **206** being substantially equal facilitates embedding (and penetration) of the tapered portion **206** into the tissue.

(21) In certain instances, at least a proximal portion of the fixation helix **208** may be insulated and at least one turn of a distal end of the fixation helix **208** is uninsulated. One or more turns of the fixation helix **208** (e.g., internal to the lumen of the elongate body **202**) may be covered by a dielectric or other insulative material as shown in FIG. 3. The proximal portion or turn of the fixation helix **208** being eliminated may minimize impedance interference that can result from the spacing of the electrode **212** and the fixation helix **208**.

(22) FIG. 3 is an illustration of an example implantable lead **300** and wire **320**, in accordance with certain instances of the present disclosure. The lead **300** includes an elongate body **302** extending between a proximal end **316** and a distal end **304** and including a lumen **318**. In certain instances, the lead **300** may include a tapered portion **306** reducing an outer diameter of the lead **300** in diameter with the taper ending at the distal end **304** (e.g., a minimum of the outer diameter of the elongate body **302** is at the distal end **304**). As shown, the tapered portion **306** includes a maximum diameter that is substantially equal to a maximum outer diameter of the elongate body **302**. In these instances, the lead **300** may be for pacing a left or right bundle branch of a patient's heart. In instances where the lead **300** does not include the tapered portion **306**, the lead **300** may be configured to pace a bundle of HIS of the patient.

(23) The tapered portion **306** may facilitate penetration of the lead **300** into the heart tissue. The lead **300** may also include a fixation helix **308** extending from distally from the at least one lumen **318** and configured to rotate and therefore translate relative to the elongate body **302**. In certain instances, the tapered portion **306** may facilitate the fixation helix **308** more deeply penetrating the heart tissue of a patient's septum to pace the stimulate the left and/or right bundle branches.

(24) As shown in FIG. 3, the lead **300** may cooperate and be usable with the wire **320**. The wire **320** may have a length to pass from the proximal end **316** of the elongate body **302** and extend outwardly from the distal end **304** of the elongate body **304** and configured to obtain and record signals from the heart tissue. The wire **320** may function as a conductor when connected to a programmer or recording system (e.g., as shown in FIG. 4) to facilitate mapping or pacing of a target location. The wire **320** may allow a physician to measure electrical signals prior to embedding of the fixation helix **308** in the tissue. The wire **320** may also facilitate an amount of depth of penetration of the fixation helix **308** into the tissue as discussed in further detail below

with reference to FIG. 4. In addition, a distal end 322 of the wire 320 may be configured penetrate the heart tissue and facilitate placement of the fixation helix in the heart tissue. In certain instances, the distal end 322 may be uninsulated, as compared to the remaining length 326 of the wire 320, to serve as an electrode. In certain instances, a length 328 of between approximately 0.5 cm and 3 cm of the distal end 322 of the wire 320 is uninsulated.

(25) The lead 300 may also include an electrode 312 arranged near the distal end 304 of the elongate body 302. In certain instances, the fixation helix 308 and the electrode 312 are configured to pace the heart tissue and the wire 320 is configured as a unipolar electrode to simultaneously obtain and record signals from the heart tissue. Pacing with the electrode 312 and the fixation helix 308 may facilitate mapping with the wire 320 by showing real-time reaction of the heart to stimulation from the electrode 312 and the fixation helix 308. In other instances, the fixation helix 308 and the wire 320 are configured as bipolar electrodes to obtain and record signals from the heart tissue.

(26) As shown in FIG. 3, the fixation helix 308 may include a proximal portion 324 that is insulated. The proximal portion 324 of the fixation helix 308 may be covered with an insulative material. In certain instances as noted above with reference to FIG. 2, the lead 300 may decrease impedance interference and maintain an appropriate pacing impedance between the fixation helix 308 and the electrode 312. In certain instances, the fixation helix 308 is extendable and retractable relative to the elongate body 302, and in other instances, the fixation helix 308 is fixed in relative to the elongate body 302. In instances where the fixation helix 308 is extendable and retractable, a terminal pin (not shown) may be rotated to extend and retract the fixation helix 308 into tissue. In instances where the fixation helix 308 is fixed in relative to the elongate body 302, the elongate body 302 may be rotated to arrange the fixation helix 308 into tissue.

(27) FIG. 4 is an illustration of another stimulation system including an implantable lead 400, in accordance with certain instances of the present disclosure. The system may also include a guide wire 420. The lead 400 includes an elongate body 402 extending between a proximal end 416 and a distal end 404 and including a lumen 418. The lead 400 may include an electrode 424 having a diameter substantially equal to an outer diameter of the elongate body 402. In certain instances, the lead 400 may include a tapered portion 406 reducing an outer diameter of the lead 300 in diameter with the taper ending at the distal end 404 (e.g., a minimum of the outer diameter of the elongate body 402 is at the distal end 404). The tapered portion 406 may have a maximum outer diameter that is substantially equal to an outer diameter of the lead body 402 (which includes the electrode 424). In these instances, the lead 400 may be for pacing a left or right bundle branch of a patient's heart. In instances where the lead 400 does not include the tapered portion 406, the lead 400 may be configured to pace a bundle of HIS of the patient.

(28) The guide wire 420 may have a length to pass from the proximal end 416 of the elongate body 402 and extend outwardly from the distal end 404 of the elongate body 402 and configured to obtain and record signals from the heart tissue. The guide wire 420 may function as a conductor when connected to a programmer 422 or recording system to facilitate mapping or pacing of a target location. The guide wire 420 may allow a physician to measure electrical signals prior to embedding of the fixation helix 408 in the tissue. The programmer 422 may monitor the electrical signal and measure pacing impedance and confirm the stimulation site (e.g., His bundle or left and/or right bundle branches). In certain instances, the fixation helix 408 and an electrode (as shown in FIG. 3) on the elongate body 402 are configured to pace the heart tissue and the guide wire 420 is configured as a unipolar electrode to simultaneously obtain and record signals from the heart tissue. The programmer 422 may include circuitry configured to execute a mapping function. Based on detected electrical signals, the mapping signal programmer 422 outputs electrocardiograms (ECGs) to a display (not shown), which may be analyzed by the physician. The programmer 422 may facilitate depth of placement of the fixation helix 408 by showing a QRS wave morphology to a physician. The physician may alter a depth of penetration of the guide wire

420 to find the strongest signal for pacing by the fixation helix **408** and the lead **400**.

(29) In certain instances, pacing the patient's heart may include delivery the lead **400** to a target location (e.g., His bundle or left and/or right bundle branches) and penetrating heart tissue at a His bundle or bundle branch with the guide wire **420**. Signals from the heart tissue are obtained at the His bundle or bundle branch with the guide wire **420** and the heart tissue may be penetrated with the fixation helix **408**. Obtaining the signals from the heart tissue with the guide wire **420** may include operating the guide wire **420** as a unipolar electrode with bipolar pacing occurring between the electrode **454** and the fixation helix **408**. In certain instances, obtaining signals from the heart tissue with the guide wire **420** includes operating the guide wire **420** and the fixation helix **408** as bipolar electrodes. A proximal end (e.g., shown in FIG. 5) of the guide wire **420** may be coupled to the programmer **422** during lead **400** placement.

(30) In certain instances, selection between conductor structures (e.g., electrode **424** and helix **408**) can facilitate accurate and localized pacing. For example and as discussed in detail, the tapered portion **406** may be embedded into tissue when pacing a patient's left bundle branch or right bundle branch. The left bundle branch is further embedded, relative to the positioning of the lead **400** as shown in FIG. 1, than the right bundle branch. In certain instances, the depth of pacing may be altered by changing which of the electrode **424** and helix **408** is selected as the cathode and which of the electrode **424** and helix **408** is selected as the anode. In certain instances, the helix **408** may be selected as the cathode when pacing the left bundle branch and the electrode **424** may be selected as the cathode when pacing the right bundle branch. The tapered portion **406** may facilitate arrangement of the electrode **424** near the target left bundle branch or right bundle branch by embedding a portion of the lead **400** into tissue and brining the electrode **424** closer to the target pacing location than if the lead **400** was not embedded. The helix **408** being partially insulated, as noted above, maintains the appropriate pacing impedance. The pacing depth may be determined or verified with the guide wire **420** as note above.

(31) FIG. 5 is an illustration of an example wire **500**, in accordance with certain instances of the present disclosure. As detailed above, the guide wire **500** may facilitate an amount of depth of penetration of a fixation helix or lead into the tissue as discussed in further detail below with reference to FIG. 4. In addition, a distal end **502** of the guide wire **500** may be configured to penetrate the heart tissue and facilitate placement of the fixation helix in the heart tissue. In certain instances, the distal end (as shown in FIG. 3) may be uninsulated, as compared to a remaining length of the wire **500**, to serve as an electrode.

(32) As shown in FIG. 5, the guide wire **500** includes an insulated intermediate portion **504**. In addition, the proximal end **502** may not be insulated to enable connection to a controller. In certain instances, the proximal end **502** of the guide wire **500** may include a series of markers **506**. The markers **506** may be arranged near the proximal end **502** of the guide wire **500** to control a penetration depth of the wire **500**.

(33) The markers **506** may be a visual indicator to an operating physician as to a depth of penetration of the distal end of the guide wire **500**. The guide wire **500** may be removably arranged through a lead body (not shown) and used as a guide wire **500** for arranging the lead body at a target location. The amount of length of the guide wire **500** arranged within the lead body may correspond to an amount of extension of the guide wire **500** from the distal end of the lead body. The markers **506** on the proximal end **502** of the guide wire **500** may correspond to an amount of extension of the guide wire **500** beyond the distal end or beyond a fixation helix and show the operating physician ad depth of guide wire **500** penetration.

(34) Various modifications and additions can be made to the exemplary instances discussed without departing from the scope of the present invention. For example, while the instances described above refer to particular features, the scope of this invention also includes instances having different combinations of features and instances that do not include all of the described features. Accordingly, the scope of the present invention is intended to embrace all such alternatives,

modifications, and variations as fall within the scope of the claims, together with all equivalents thereof.

Claims

1. A system for pacing a patient's heart at a stimulation site, the system comprising: an implantable lead including: an elongate body extending between a proximal end and a distal end and including at least one lumen extending between the proximal end and the distal end, the distal end of the elongate body configured to embed within heart tissue and including a tapered portion reducing the elongate body in diameter with a minimum diameter of the tapered portion at the distal end and a maximum diameter of the tapered portion being substantially equal to a maximum outer diameter of the elongate body, and a fixation helix having an outer diameter, the fixation helix extending from distally from the at least one lumen and configured to rotate and therefore translate relative to the elongate body, the fixation helix further including a proximal portion and a distal portion, wherein the proximal portion of the fixation helix is covered by an electrically insulative material and the distal portion is uninsulated, and wherein the minimum diameter of the tapered portion of the elongate body is equal to the outer diameter of the fixation helix; and a guide wire having a proximal end, an insulated intermediate portion distal to the proximal end, and an uninsulated distal end located distally of the intermediate portion, wherein the guide wire is removably disposed within the lead body and is selectively extendable beyond the fixation helix, wherein the distal portion of the fixation helix and the uninsulated distal end of the guide wire are configured as a bipolar electrode pair; a programmer coupled to the guide wire and adapted to receive electrical signals from the uninsulated distal end prior to embedding the fixation helix and adapted to receive electrical signals from the uninsulated distal end to confirm contact with the stimulation site, wherein the programmer is configured to facilitate placement of the fixation helix by analyzing the electrical signals prior to embedding the fixation helix.
2. The system of claim 1, wherein the lead is configured to embed at the heart tissue and the fixation helix is electrically active and configured to pace a left bundle branch or a right bundle branch of the patient.
3. The system of claim 1, wherein the fixation helix is electrically active and configured to pace a His bundle the patient.
4. The system of claim 1, wherein the uninsulated distal end of the guide wire is configured as a unipolar electrode to obtain and record signals from the heart tissue.
5. The system of claim 1, wherein the bipolar electrode pair is configured to obtain and record signals from the heart tissue.
6. The system of claim 1, wherein the uninsulated distal end of the guide wire is between 2 mm and 4 mm in length.
7. The system of claim 1, wherein the guide wire includes markers arranged near a proximal end of the wire configured to provide a visual indication of a penetration depth of the guide wire into tissue.
8. The system of claim 1, wherein the lead further comprises a proximal electrode arranged on the elongate body proximal to the distal end of the elongate body.
9. A system for pacing a bundle branch of a patient's heart, the system comprising: an implantable lead including: an elongate body extending between a proximal end and a distal end and including at least one lumen extending between the proximal end and the distal end, the distal end of the elongate body configured to embed within heart tissue and including a tapered portion reducing the elongate body in diameter with a minimum diameter of the tapered portion at the distal end and a maximum diameter of the tapered portion being substantially equal to a maximum outer diameter of the elongate body, and a fixation helix having an outer diameter, the fixation helix extending from distally from the at least one lumen and configured to rotate and therefore translate relative to

the elongate body, the fixation helix further including a proximal portion and a distal portion, wherein the proximal portion of the fixation helix is covered by an electrically insulative material and the distal portion is uninsulated, and wherein the minimum diameter of the tapered portion of the elongate body is equal to the outer diameter of the fixation helix; and a guide wire having an uninsulated distal end configured as a guide wire electrode and being removably disposed within the lead body and selectively extendable beyond the fixation helix, wherein the distal portion of the fixation helix and the uninsulated distal end of the guide wire are configured as a bipolar electrode pair; a programmer coupled to the guide wire and adapted to receive electrical signals from the uninsulated distal end prior to embedding the fixation helix and adapted to receive electrical signals from the uninsulated distal end to confirm contact with the bundle branch, wherein the programmer is configured to facilitate placement of the fixation helix by analyzing the electrical signals prior to embedding the fixation helix.

10. The system of claim 9, wherein the fixation helix is electrically active and configured to pace a His bundle the patient.

11. The system of claim 9, wherein the uninsulated distal end of the guide wire is configured as a unipolar electrode to obtain and record signals from the heart tissue.

12. The system of claim 9, wherein the bipolar electrode pair is configured to obtain and record signals from the heart tissue.

13. The system of claim 12, wherein the guide wire includes markers arranged near a proximal end of the wire configured to provide a visual indication of a penetration depth of the guide wire into tissue.
