

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415235
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Oh; Taekil et al.

Deposition mask manufacturing apparatus

Abstract

An apparatus for manufacturing a deposition mask including a stage on which a mask substrate is mounted, a light source configured to irradiate a laser beam, a beam splitter configured to split the irradiated laser beam into a plurality of laser beams, a scanner configured to simultaneously scan the plurality of laser beams onto the mask substrate, and a tuner configured to finely change irradiation states of the plurality of laser beams to correspond to shapes of a plurality of pattern holes, while the plurality of laser beams are scanned.

Inventors: Oh; Taekil (Yongin-si, KR), Han; Gyoowan (Yongin-si, KR), Kim; Wonyong (Yongin-si, KR), Myoung; Seungho (Yongin-si, KR), Park; Jaeseok (Yongin-si, KR), Voronov; Alexander (Yongin-si, KR), Jeun; Jinhong (Yongin-si, KR)

Applicant: Samsung Display Co., Ltd. (Yongin-si, KR)

Family ID: 1000008821380

Assignee: SAMSUNG DISPLAY CO., LTD. (Gyeonggi-Do, KR)

Appl. No.: 17/838243

Filed: June 12, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220297236 A1	Sep. 22, 2022

Foreign Application Priority Data

KR	10-2017-0131642	Oct. 11, 2017
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **B23K26/362** (20140101); **B23K26/06** (20140101); **B23K26/067** (20060101); **B23K26/082** (20140101); **B23K26/382** (20140101); **C22C38/08** (20060101); **H01L21/027** (20060101); **H01L21/033** (20060101); **H10K71/00** (20230101); **H10K71/16** (20230101); B23K103/02 (20060101); G03F1/00 (20120101)

U.S. Cl.:

CPC **B23K26/362** (20130101); **B23K26/0626** (20130101); **B23K26/0673** (20130101); **B23K26/0676** (20130101); **B23K26/082** (20151001); **B23K26/382** (20151001); **C22C38/08** (20130101); **H01L21/0275** (20130101); **H01L21/0337** (20130101); **H10K71/00** (20230201); **H10K71/166** (20230201); B23K2103/02 (20180801); G03F1/00 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8455790	12/2012	Tanaka et al.	N/A	N/A
8680430	12/2013	Unrath	N/A	N/A
9259805	12/2015	Kim et al.	N/A	N/A
9377681	12/2015	Lee et al.	N/A	N/A
9457426	12/2015	Lee et al.	N/A	N/A
9592570	12/2016	Lee et al.	N/A	N/A
9643280	12/2016	Lee et al.	N/A	N/A
10160000	12/2017	Hirobe et al.	N/A	N/A
10377096	12/2018	Wildsmith et al.	N/A	N/A
10507544	12/2018	Zhang et al.	N/A	N/A
2006/0203214	12/2005	Shiraishi	N/A	N/A
2007/0138151	12/2006	Tanaka et al.	N/A	N/A
2011/0183271	12/2010	Lee et al.	N/A	N/A
2014/0076869	12/2013	Lee et al.	N/A	N/A
2014/0177055	12/2013	Lee et al.	N/A	N/A
2014/0238963	12/2013	Jo et al.	N/A	N/A
2014/0291306	12/2013	Lee et al.	N/A	N/A
2015/0001194	12/2014	Unrath et al.	N/A	N/A
2015/0104608	12/2014	Lee et al.	N/A	N/A
2016/0145762	12/2015	Im et al.	N/A	N/A
2016/0151114	12/2015	Gu et al.	N/A	N/A
2016/0250714	12/2015	Zhang et al.	N/A	N/A
2019/0259950	12/2018	Jung et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102094167	12/2010	CN	N/A
103658978	12/2013	CN	N/A
103962719	12/2013	CN	N/A
104002041	12/2013	CN	N/A
104053813	12/2013	CN	N/A
2017-144465	12/2016	JP	N/A
10-2008-0085873	12/2007	KR	N/A
10-2011-0102319	12/2010	KR	N/A
10-2013-0127981	12/2012	KR	N/A
10-2014-0036593	12/2013	KR	N/A
10-2014-0043524	12/2013	KR	N/A
10-2014-0064475	12/2013	KR	N/A
10-2014-0118537	12/2013	KR	N/A
10-2015-0035131	12/2014	KR	N/A
201637764	12/2015	TW	N/A
201639651	12/2015	TW	N/A
2015093304	12/2014	WO	N/A

OTHER PUBLICATIONS

KR 2015-0035131 (Lee, Do-hyung) Apr. 6, 2015 [retrieved on Jun. 15, 2024]. Retrieved from Foreign Image and Text database, translation by Clarivate Analytics. (Year: 2015). cited by examiner

Non-Final Office Action dated Apr. 29, 2020, issued to U.S. Appl. No. 15/973,462. cited by applicant

Final Office Action dated Aug. 27, 2020, issued to U.S. Appl. No. 15/973,462. cited by applicant

Non-Final Office Action dated Dec. 28, 2020, issued to U.S. Appl. No. 15/973,462. cited by applicant

Final Office Action dated May 19, 2021, issued to U.S. Appl. No. 15/973,462. cited by applicant

Notice of Allowance dated Feb. 16, 2022, issued to U.S. Appl. No. 15/973,462. cited by applicant

Office Action dated Dec. 2, 2022, issued to Chinese Patent Application No. 201811175880.0 (with English Concise Explanation). cited by applicant

Primary Examiner: Norton; John J

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 15/973,462, filed on May 7, 2018, which issued as U.S. Pat. No. 11,358,240 on Jun. 22, 2022, which claims priority from and the benefit of Korean Patent Application No. 10-2017-0131642, filed on Oct. 11, 2017, each of which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND

Field

(1) Exemplary embodiments of the invention relate generally to a method of manufacturing a

deposition mask that includes an improved process of forming a pattern hole of a mask used for deposition, and, more specifically, to an apparatus for manufacturing a deposition mask.

Discussion of the Background

(2) In general, an organic light-emitting display device implements colors based on the principle in which holes and electrons injected from an anode and a cathode recombine in an emission layer, and pixels have a structure in which the emission layer is between a pixel electrode that is an anode and an opposite electrode that is a cathode.

(3) Each pixel may be a sub-pixel of any one of, for example, a red pixel, a green pixel, and a blue pixel, and due to a color combination of the above three pixels, a desired color may be produced. That is, each sub-pixel has a structure in which an emission layer is between two electrodes, the emission layer emitting light of any one of a red color, a green color, and a blue color. Due to a combination of light of three colors, a color of one unit pixel is produced.

(4) The electrodes, the emission layer, and the like of the above organic light-emitting device may be formed by deposition. That is, a mask, which has pattern holes having the same pattern as a thin film to be formed, is located on a substrate, and a raw material of the thin film is deposited on the substrate through the pattern holes in the mask, thereby forming a thin film having a desired pattern. The mask is often used as a mask frame assembly together with a frame that supports end portions of the mask, and the pattern holes are usually formed during an etching process using photoresist.

(5) However, when pattern holes of the mask are formed during an etching process, it is difficult to form pattern holes having highly precise dimensions. In addition, since etching generally starts from both side surfaces of a mask towards an inner portion thereof such that etched portions meet around a middle thickness to thereby form pattern holes, working speed is greatly low, and non-continuous protruding surfaces appear around the middle thickness at which the etching portions meet, which may result in disturbance of accurate patterning that is so-called 'shadow' during deposition.

(6) The above information disclosed in this Background section is only for understanding of the background of the inventive concepts, and, therefore, it may contain information that does not constitute prior art.

SUMMARY

(7) One or more exemplary embodiments include a method of manufacturing a deposition mask which is improved to accurately and quickly form pattern holes in a mask without performing an etching process, and an apparatus for manufacturing a deposition mask.

(8) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(9) According to one or more exemplary embodiments, a method of manufacturing a deposition mask includes: a preparing process in which a mask substrate is located on a stage; and a hole processing process in which laser beams are irradiated onto the mask substrate to form a plurality of pattern holes. The hole processing process includes: an irradiation process in which a light source irradiates a laser beam; a splitting process in which the irradiated laser beam is split into a plurality of laser beams; a scanning process in which the plurality of laser beams are simultaneously scanned onto the mask substrate; and a tuning process in which irradiation states of the plurality of laser beams are finely changed to correspond to shapes of the plurality of pattern holes while the plurality of laser beams are scanned.

(10) According to one or more exemplary embodiments, an apparatus for manufacturing a deposition mask, includes: a stage on which a mask substrate is mounted; a light source configured to irradiate a laser beam; a beam splitter configured to split the irradiated laser beam into a plurality of laser beams; a scanner configured to simultaneously scan the plurality of laser beams onto the mask substrate; and a tuner configured to finely change irradiation states of the plurality of laser beams to correspond to shapes of a plurality of pattern holes, while the plurality of laser beams are

scanned.

(11) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the invention, and together with the description serve to explain the inventive concepts.
- (2) FIG. 1 illustrates a deposition process using a deposition mask manufactured according to an exemplary embodiment.
- (3) FIG. 2 is an exploded perspective view of a mask frame assembly including the deposition mask of FIG. 1.
- (4) FIG. 3 is a perspective view of an apparatus for manufacturing a deposition mask, according to an exemplary embodiment.
- (5) FIG. 4 is a block diagram of a schematic structure of an optical system of FIG. 3.
- (6) FIG. 5 is a plan view of a process of scanning laser beams in the apparatus of FIG. 3.
- (7) FIG. 6 is a plan view illustrating a movement path of a laser beam in each pattern hole during a scanning process of FIG. 5.
- (8) FIGS. 7A, 7B, 7C, and 7D are plan views illustrating processes of manufacturing a deposition mask, according to an exemplary embodiment.
- (9) FIG. 8 is a cross-sectional view of a detailed structure of a target substrate of FIG.

DETAILED DESCRIPTION

(10) In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of various exemplary embodiments or implementations of implementations of the invention. As used herein “embodiments” and “implementations” are interchangeable words that are non-limiting examples of devices or methods employing one or more of the inventive concepts disclosed herein. It is apparent, however, that various exemplary embodiments may be practiced without these specific details or with one or more equivalent arrangements. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring various exemplary embodiments. Further, various exemplary embodiments may be different, but do not have to be exclusive. For example, specific shapes, configurations, and characteristics of an exemplary embodiment may be used or implemented in another exemplary embodiment without departing from the inventive concepts.

(11) Unless otherwise specified, the illustrated exemplary embodiments are to be understood as providing exemplary features of varying detail of some ways in which the inventive concepts may be implemented in practice. Therefore, unless otherwise specified, the features, components, modules, layers, films, panels, regions, and/or aspects, etc. (hereinafter individually or collectively referred to as “elements”), of the various embodiments may be otherwise combined, separated, interchanged, and/or rearranged without departing from the inventive concepts.

(12) The use of cross-hatching and/or shading in the accompanying drawings is generally provided to clarify boundaries between adjacent elements. As such, neither the presence nor the absence of cross-hatching or shading conveys or indicates any preference or requirement for particular materials, material properties, dimensions, proportions, commonalities between illustrated elements, and/or any other characteristic, attribute, property, etc., of the elements, unless specified.

Further, in the accompanying drawings, the size and relative sizes of elements may be exaggerated for clarity and/or descriptive purposes. When an exemplary embodiment may be implemented differently, a specific process order may be performed differently from the described order. For example, two consecutively described processes may be performed substantially at the same time or performed in an order opposite to the described order. Also, like reference numerals denote like elements.

(13) When an element, such as a layer, is referred to as being “on,” “connected to,” or “coupled to” another element or layer, it may be directly on, connected to, or coupled to the other element or layer or intervening elements or layers may be present. When, however, an element or layer is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. To this end, the term “connected” may refer to physical, electrical, and/or fluid connection, with or without intervening elements. Further, the D1-axis, the D2-axis, and the D3-axis are not limited to three axes of a rectangular coordinate system, such as the x, y, and z-axes, and may be interpreted in a broader sense. For example, the D1-axis, the D2-axis, and the D3-axis may be perpendicular to one another, or may represent different directions that are not perpendicular to one another. For the purposes of this disclosure, “at least one of X, Y, and Z” and “at least one selected from the group consisting of X, Y, and Z” may be construed as X only, Y only, Z only, or any combination of two or more of X, Y, and Z, such as, for instance, XYZ, XYY, YZ, and ZZ. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(14) Although the terms “first,” “second,” etc. may be used herein to describe various types of elements, these elements should not be limited by these terms. These terms are used to distinguish one element from another element. Thus, a first element discussed below could be termed a second element without departing from the teachings of the disclosure.

(15) Spatially relative terms, such as “beneath,” “below,” “under,” “lower,” “above,” “upper,” “over,” “higher,” “side” (e.g., as in “sidewall”), and the like, may be used herein for descriptive purposes, and, thereby, to describe one elements relationship to another element(s) as illustrated in the drawings. Spatially relative terms are intended to encompass different orientations of an apparatus in use, operation, and/or manufacture in addition to the orientation depicted in the drawings. For example, if the apparatus in the drawings is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. Furthermore, the apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations), and, as such, the spatially relative descriptors used herein interpreted accordingly.

(16) The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting. As used herein, the singular forms, “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Moreover, the terms “comprises,” “comprising,” “includes,” and/or “including,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components, and/or groups thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. It is also noted that, as used herein, the terms “substantially,” “about,” and other similar terms, are used as terms of approximation and not as terms of degree, and, as such, are utilized to account for inherent deviations in measured, calculated, and/or provided values that would be recognized by one of ordinary skill in the art.

(17) Various exemplary embodiments are described herein with reference to sectional and/or exploded illustrations that are schematic illustrations of idealized exemplary embodiments and/or intermediate structures. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, exemplary embodiments disclosed herein should not necessarily be construed as limited to the particular illustrated shapes of regions, but are to include deviations in shapes that result from, for instance,

manufacturing. In this manner, regions illustrated in the drawings may be schematic in nature and the shapes of these regions may not reflect actual shapes of regions of a device and, as such, are not necessarily intended to be limiting.

(18) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure is a part. Terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and should not be interpreted in an idealized or overly formal sense, unless expressly so defined herein.

(19) FIG. 1 schematically illustrates a structure of a thin film deposition apparatus including a deposition mask **120**, according to an exemplary embodiment.

(20) As illustrated, the thin film deposition apparatus may include the deposition mask **120** forming a desired pattern on a target substrate **300** and a deposition source **200** discharging a deposition gas towards the target substrate **300** within a chamber **400**.

(21) Thus, when the deposition source **200** discharges the deposition gas within the chamber **400**, the discharged deposition gas may pass through pattern holes **121** (refer to FIG. 2) in the deposition mask **120** and adhere to the target substrate **300**, thereby forming a thin film having a certain pattern.

(22) As illustrated in FIG. 2, the deposition mask **120** may be used as a mask frame assembly **100**, including a frame **130** supporting both end portions of the deposition mask **120** and long-side sticks **110** crossing the deposition masks **120** and supported on the frame **130**.

(23) That is, the mask frame assembly **100** may include the frame **130**, the long-side sticks **110** each having both end portions fixed to the frame **130**, and the deposition masks **120** perpendicularly crossing the long-side sticks **110** and each having both end portions fixed to the frame **130**.

(24) The frame **130** may form an outer peripheral shape of the mask frame assembly **100** and have a rectangular shape having an opening **132** at the center thereof. The end portions of the long-side sticks **110** may be welded and fixed to a pair of sides of the frame **130** which face each other, and both end portions of the deposition mask **120** may be welded and fixed to another pair of sides of the frame **130** which are perpendicular to the above pair of sides.

(25) The deposition masks **120** may be members having long stick shapes and have the pattern holes **121** disposed in the opening **132**, and the end portions of the deposition mask **120** may be welded to the frame **130**. The reference numeral **122** may denote clamping portions, and the clamping portions **122** may be stretched in a lengthwise direction of the deposition mask **120** when the deposition mask **120** is welded to the frame **130**, and after the welding is completed, the clamping portions **122** may be cut and removed. The deposition mask **120** may be formed as one large deposition mask, but in that case, the large deposition mask may be sagged due to its own load. Thus, as illustrated in the drawings, the deposition mask **120** may be divided into multiple sticks. The deposition mask **120** may include an iron (Fe)-nickel (Ni) alloy that has about 36% nickel and about 64% iron. Put another way, the deposition mask **120** may include 64FeNi or Invar.

(26) The pattern holes **121** may be holes through which a deposition gas passes during a deposition process, and the deposition gas having passed through the pattern holes **121** may adhere to the target substrate **300** (see FIG. 1) to thereby form a thin film.

(27) Areas of the pattern holes **121** may not be divided in units of cells having certain sizes, but connected into one pattern hole **121**. The long-side sticks **110** may divide the areas of the pattern holes **121** in units of cells. That is, as illustrated in the drawings, the deposition mask **120** and the long-side stick **110** may perpendicularly cross and adhere to each other on the frame **130**, and accordingly, the long-side sticks **110** cross the areas of the pattern holes **121** in the deposition mask **120** and divide the same in units of cells. In other words, the long-side sticks **110** may draw boundary lines between unit cells.

(28) The pattern holes **121** in the deposition mask **120** may be formed by an apparatus illustrated in FIGS. **3** and **4**. Although a structure of the apparatus is schematically illustrated, the structure is not limited thereto. That is, in addition to the components illustrated in FIGS. **3** and **4**, the apparatus may further include components such as various mirrors, lenses, or a correction optical system, and when the components perform functions to be described below, an arrangement order of the components may vary.

(29) A mask substrate **120** (has the same reference numeral as the deposition mask **120** because, as soon as the pattern holes **121** are formed, the mask substrate **120** becomes the deposition mask **120**), in which the pattern holes **121** are to be formed, may be mounted on a stage **30**, and the stage **30** may support the mask substrate **120** during the formation of the pattern holes **121** and allow the mask substrate **120** to move at certain pitches in a Y-axis direction.

(30) A light source **20** may emit pulse laser beams used to form the pattern holes **121**, and an optical system **10** may adjust the emitted laser beams to satisfy optimum conditions for forming the pattern holes **121**.

(31) With regard to components included in the optical system **10**, as illustrated in FIG. **4**, there may be a tuner **11** that finely adjusts a location, power, and the number of irradiations of a laser beam, a beam splitter **12** that splits the laser beam emitted from the light source **20** into multiple laser beams, a beam clipper **13** that selectively hides some of the split laser beams and adjusts the number of laser beams, a scanner **14** that scans the laser beams onto the mask substrate **120** in an X-axis direction of FIG. **3**, a telecentric F- θ lens **15** that adjusts incidence angles of the laser beams to allow the laser beams to be perpendicularly incident to the mask substrate **120**, and the like.

(32) Functions of the beam splitter **12** will be described first. As described above, the beam splitter **12** may split the light emitted from the light source **20** into laser beams. That is, the beam splitter **12** may increase the number of laser beams in such a manner that multiple laser beams, instead of a single laser beam, may be simultaneously irradiated onto the mask substrate **120**.

(33) When the increased number of laser beams is scanned by the scanner **14**, laser beams L1 to Ln illustrated in FIG. **5** may simultaneously pass a surface of the mask substrate **120** in an X-axis direction. Thus, multiple columns of pattern holes **121** may be formed.

(34) The beam clipper **13** may decrease the increased number of laser beams, according to necessity. For example, when it is assumed that the beam splitter **12** splits a laser beam into ten laser beams and there are, on the mask substrate **120**, seventeen columns in which the pattern holes **121** are to be formed, all the ten laser beams are scanned onto first to tenth columns to form the pattern holes **121**, but when the pattern holes **121** are to be formed in eleventh to seventeenth columns as the stage **30** is moved at a certain pitch, only seven laser beams have to be used. In this case, the beam clipper **13** hides and blocks the rest of the three laser beams.

(35) The scanner **14** may include a Galvano mirror or a polygon mirror, and may scan the laser beams on the mask substrate **120** in the X-axis direction, and when the laser beams are irradiated, the telecentric F- θ lens **15** may adjust the incidence angles in such a manner that the laser beams from a central portion as well as the laser beams from edge portions may be perpendicularly incident onto the mask substrate **120**.

(36) The tuner **11** may use an Acousto-Optic Deflector (AOD) and quickly change fine states of the laser beams, for example, locations, power, the number of irradiations thereof, and the like. Since the tuner **11** may be placed before the beam splitter **12**, the laser beam emitted from the light source **20** may be finely adjusted, and the laser beams split by the beam splitter **12** may move according to the finely adjusted laser beam.

(37) A first fine adjustment target may be a movement path of the laser beams within the areas of the pattern holes **121**. Referring to FIGS. **5** and **6**, the laser beams L1 to Ln may be uniformly moved by the scanner **14** in the X-axis direction without stopping. While moved, the laser beams L1 to Ln may pass the areas of the pattern holes **121**, and as illustrated in FIG. **6**, the laser beam L1 may spirally circle once from a point **1** to a point **9** in the area of each pattern hole **121**, and then

pass. This quick and fine adjustment may be performed by the tuner **11**. That is, a relatively slow movement of the laser beam **L1** in a scanning direction may be conducted by the scanner **14**, and a movement, which is faster by several tens of times within the area of each pattern hole **121**, may be adjusted by the tuner **11**. Here, the pattern hole **121** may have a rhomboid shape, and the tuner **11** may finely adjust the path to allow the laser beam **L1** to be irradiated onto the entire area of the pattern hole **121** having a rhomboid shape.

(38) A second fine adjustment target may be the number of irradiations. While being scanned as illustrated in FIG. 5, the laser beams **L1** to **Ln** may not always be “on,” but may only be “on” only in areas of the pattern holes **121** to be processed. Also, the laser beam **L1** may not continuously be “on” in the areas of the pattern hole **121**, but may only be “on” only in nine points from the point **1** to the point **9**, as illustrated in FIG. 6. Nine irradiations are not absolute, but when irradiating the laser beams, nine times may be enough to cover the entire area of the pattern hole **121** to form the pattern holes **121** having a rhomboid shape. The tuner **11** may adjust the path and a timing when the laser beam is “on” and control the laser beam **L1** such that the laser beam **L1** circles and passes the pattern holes **121** having a rhomboid shape while being turned “on.” The irradiation numbers of the laser beam **L1** may decrease as the pattern holes **121** decreases in size, which will be described again together with a process of forming a taper of the pattern holes **121**.

(39) A third fine adjustment target may be the power of the laser beams, and in the present embodiment, power of the laser beams may be maintained to a certain degree. That is, when the pattern holes **121** decrease in size, power of laser beams may decrease instead of decreasing the number of irradiations, but in the present disclosure, the power is maintained to a certain level, and the number of irradiations may decrease.

(40) The tuner **11** may adjust the fine movement path, the number of irradiations, and the power of the laser beams.

(41) Processes of manufacturing the deposition mask **120** by using a deposition mask manufacturing apparatus will be described below, and examples of the target substrate **300** that may be deposited by using the deposition mask **120** will be briefly provided.

(42) The deposition mask **120** may be used to deposit various thin films, for example, patterns of an emission layer of an organic light-emitting display apparatus.

(43) FIG. 8 illustrates a structure of the organic light-emitting display apparatus as an example of the target substrate **300** on which a thin film may be deposited by using the deposition mask **120**.

(44) Referring to FIG. 8, a buffer layer **330** is formed on a base plate **320**, and a thin film transistor TFT is above the buffer layer **330**.

(45) The thin film transistor TFT may include an active layer **331**, a gate insulating layer **332** covering the active layer **331**, and a gate electrode **333** on the gate insulating layer **332**.

(46) An interlayer insulating layer **334** may cover the gate electrode **333**, and a source electrode **335a** and a drain electrode **335b** may be formed on the interlayer insulating layer **334**.

(47) The source electrode **335a** and the drain electrode **335b** may respectively contact a source area and a drain area of the active layer **331** through contact holes in the gate insulating layer **332** and the interlayer insulating layer **334**.

(48) A pixel electrode **321** of an organic light-emitting diode OLED may be connected to the drain electrode **335b**. The pixel electrode **321** may be formed on a planarization layer **337**, and on the pixel electrode **321**, a pixel-defining layer **338** that divides sub-pixel areas may be formed. The reference numeral **339** indicates spacers that maintain a gap between the target substrate **300** and the deposition mask **120** during deposition and prevent damage to members of the target substrate **300** due to contact of the deposition mask **120**. The spacers **339** may protrude from portions of the pixel-defining layer **338**. An emission layer **326** of the organic light-emitting diode OLED may be formed in the opening of the pixel-defining layer **338**, and an opposite layer **327** may be deposited on the emission layer **326**. That is, the opening surrounded by the pixel-defining layer **338** may become an area of a sub-pixel such as a red pixel R, a green pixel G, or a blue pixel B, and the

emission layer **326** emitting a corresponding color may be formed in the opening.

(49) Therefore, for example, when the deposition mask **120** is prepared to make the pattern hole **121** correspond to the emission layer **326**; the emission layer **326** having a desired pattern may be formed during the deposition process described above with reference to FIG. **1**. The above-described unit cell may correspond to a display area of the organic light-emitting display apparatus.

(50) A process of forming the pattern holes **121** of the deposition mask **120** that may form the organic light-emitting display apparatus will be described with reference to FIGS. **3**, **4**, and **7A** to **7D**. As illustrated in FIG. **7D**, the pattern holes **121** are formed in tapered shapes, that is, shapes in which the areas of the pattern holes **121** continuously decrease from surfaces to which laser beams are irradiated to opposite surfaces.

(51) As illustrated in FIG. **3**, when the mask substrate **120** is prepared after being mounted on the stage **30**, a hole processing process is performed as the light source **20** emits the laser beam and the optical system **10** adjusts the laser beam, as described above.

(52) FIGS. **7A**, **7B**, and **7C** illustrate a process in which one laser beam **L1** among the laser beams **L1** to **Ln** passes, and the other laser beams **L2** to **Ln** also pass in the same path.

(53) FIG. **7A** illustrates a first scanning process. The laser beam **L1** may be moved along a scan path in an X-axis direction, and as the laser beam **L1** spirally circles according to the control of the tuner **11** in the areas of each pattern hole **121** and is irradiated nine times, holes **121a** having a rhombus shape may be formed. The holes **121a** may not immediately become the pattern holes **121** that are thoroughly penetrated, and may have a certain depth in a surface layer. When power of a laser beam increases, the pattern holes **121** may be formed at once, but in the present disclosure, the pattern holes **121** need to have tapered shapes and thus are gradually processed from the surface layer.

(54) As illustrated in FIG. **7B**, second scanning is performed, and at this time, sizes of holes **121b** to be formed decrease compared to the holes **121a** formed during the first scanning. As described above, the holes **121b** that decrease in size for the tapered shapes may be formed. The tuner **11** may decrease the number of irradiations of the laser beam **L1** to seven, in relation to the decreased size of the holes **121b**. That is, the number of irradiations decreases to prevent energy from being excessively input to small areas.

(55) During third scanning of FIG. **7C**, the laser beam **L1** may be irradiated to form holes **121c** that are smaller than the holes **121b**, and thus, the number of irradiations may be reduced to five.

(56) As described, when scanning is repeatedly performed by gradually decreasing sizes of target holes as well as the number of irradiations, the pattern holes **121** having tapered shapes may be formed as illustrated in FIG. **7D**.

(57) Then, for example, when the pattern holes **121** are formed in the first to tenth columns on the mask substrate **120** by using ten laser beams, the stage **30** is moved at certain pitches, and pattern holes **121** are formed in eleventh to twentieth columns. However, when the pattern holes **121** need to be formed from the first column to the seventeenth column, the beam clipper **13** may block the rest of the three laser beams, and the pattern holes **121** may be formed in the eleventh to seventeenth columns.

(58) By using the above-described processes, the mask substrate **120** may be gradually etched from one surface, compared to a case where the mask substrate **120** is etched from both side surfaces thereof and the etched portions meet in the middle of the mask substrate **120**. Thus, no protruding surfaces may be formed at a middle thickness portion of the pattern holes **121**, and multiple laser beams may be controlled and directly irradiated onto the mask substrate **120** to form the pattern holes **121** in multiple columns such that accurate and quick processing of the pattern holes **121** may be enabled.

(59) Consequently, when the pattern holes **121** of the deposition mask **120** are formed by using the above method, a problem such as formation of protruding portions causing a shadow during an etching process may be solved, and the fine paths of the laser beams may be adjusted regardless of

shapes of the pattern holes **121**. Therefore, productivity and quality of a final product may be improved.

(60) In the present embodiment, the pattern holes **121** are formed in the deposition mask **120** that is divided into multiple sticks, but the present embodiment may be applied to an integrated mask, in which one member covers the opening **132** of the frame **130**, or a mask in which the pattern holes **121** are divided in units of cells in the deposition mask **120** without the long-side sticks **110**. In other words, when the pattern holes **121** are formed by directly irradiating laser beams, the apparatus and method of manufacturing a deposition mask of the present embodiment may be applied regardless of types of masks.

(61) Therefore, according to the above-described apparatus and method of manufacturing a deposition mask, since pattern holes are formed by irradiating laser beams without performing an etching process, the pattern holes may be highly accurately formed. Also, even when multiple laser beams, which are split from one laser beam, are scanned without stopping, locations of the laser beams may be finely and quickly adjusted according to shapes of the pattern holes, and thus pattern holes having various shapes may be quickly and stably formed. As a result, productivity may be improved, and uniform quality of products may be secured.

(62) Although certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the inventive concepts are not limited to such embodiments, but rather to the broader scope of the appended claims and various obvious modifications and equivalent arrangements as would be apparent to a person of ordinary skill in the art.

Claims

1. An apparatus for manufacturing a deposition mask, the apparatus comprising: a stage on which a mask substrate is mounted; a light source configured to irradiate a laser beam; a beam splitter configured to split the irradiated laser beam into a plurality of laser beams; a scanner configured to simultaneously scan the plurality of laser beams onto the mask substrate; and a tuner configured to finely change irradiation states of the plurality of laser beams to correspond to shapes of a plurality of pattern holes while the plurality of laser beams are scanned, wherein the scanner is further configured to gradually form each of the plurality of pattern holes by allowing a corresponding one of the laser beams to pass an area of each of the plurality of pattern holes a plurality of times, the tuner is further configured to vary a number of irradiations of each laser beam in the area of each pattern hole each time the laser beam passes the area of the pattern hole, and the tuner is further configured to vary a location of each of the number of irradiations of the laser beam for any given one of the laser beam passes.
2. The apparatus of claim 1, wherein the tuner comprises an Acousto-Optic Deflector (AOD).
3. The apparatus of claim 2, the tuner is further configured to gradually decrease an area where the laser beam is irradiated within the area of the one pattern hole with each subsequent time the laser beam passes the area of the pattern hole.
4. The apparatus of claim 3, wherein each of the plurality of pattern holes has a tapered shape in which an open area gradually decreases from a side where the laser beam is irradiated to an opposite side.
5. The apparatus of claim 3, wherein the tuner gradually decreases the area covered by the number of irradiations of the laser beam for each subsequent pass by decreasing the number of irradiations of the laser beam for each pass.
6. The apparatus of claim 1, wherein the tuner further adjusts power of the laser beam within areas of the plurality of pattern holes.
7. The apparatus of claim 1, further comprising a beam clipper configured to block some of the plurality of laser beams to decrease a number of laser beams that are irradiated onto the mask

substrate.

8. The apparatus of claim 1, further comprising a telecentric F- θ lens configured to adjust incidence angles of the plurality of laser beams to allow all of the plurality of laser beams to be perpendicularly incident to the mask substrate.
 9. The apparatus of claim 1, wherein the stage is configured to move the mask substrate at a certain pitch in a direction perpendicular to a direction in which the plurality of laser beams are scanned.
 10. The apparatus of claim 1, wherein the scanner comprises any one of a Galvano mirror and a polygon mirror.
 11. The apparatus of claim 1, wherein the tuner is further configured to control each of the plurality of laser beams to spirally circle in an area corresponding to ones of the plurality of pattern holes to produce ones of the plurality of pattern holes.
 12. The apparatus of claim 11, wherein the each of the plurality of pattern holes has a quadrangular shape in a plan view.
 13. The apparatus of claim 1, wherein the scanner translates the laser beam linearly in a single direction.
 14. The apparatus of claim 1, wherein a movement of the laser beam within an area of each of the plurality of pattern holes by the tuner is faster than a movement of the laser beam from one column to another column by the scanner.
 15. The apparatus of claim 14, wherein the tuner moves the laser beam more than about 10 times faster than the scanner.
 16. The apparatus of claim 1, wherein the tuner is further configured to: irradiate a center of one of the plurality of pattern holes and then around a first circumference of the pattern hole during a first pass, and irradiate the center of the pattern hole and then around a second circumference less than the first circumference during a second and subsequent pass of a same one of the plurality of pattern holes.
 17. An apparatus for manufacturing a deposition mask, the apparatus comprising: a stage on which a mask substrate is mounted; a light source configured to irradiate a laser beam; a beam splitter configured to split the irradiated laser beam into a plurality of laser beams; a scanner configured to simultaneously scan the plurality of laser beams onto the mask substrate; and a tuner configured to finely change irradiation states of the plurality of laser beams to correspond to shapes of a plurality of pattern holes while the plurality of laser beams are scanned by adjusting a number of irradiations of the plurality of laser beams within the areas of the plurality of pattern holes, wherein the tuner is further configured to: irradiate a center of one of the plurality of pattern holes and then around a first circumference of the pattern hole during a first scanning, irradiate the center of the pattern hole and then around a second circumference less than the first circumference during a second and subsequent scanning of a same one of the plurality of pattern holes, and irradiate the center and then around a third circumference less than the second circumference during a third and subsequent scanning of the one of the plurality of pattern holes.
 18. The apparatus of claim 17, wherein a number of irradiations of the first scanning is 9, a number of irradiations of the second scanning is 7, and a number of irradiations of the third scanning is 5.
-