

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415575
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Inami; Takuma et al.

Vehicle-body structure with controller

Abstract

A vehicle-body structure may include a floor panel constituting a floor of an occupant space, a center frame disposed to be higher than and away from the floor panel at a vehicle-width-direction central portion of the occupant space and extending in a vehicle front-rear direction, and a control device configured to control a control target unit mounted on an automobile. The control device may be arranged at a lower position than a vehicle front portion of the center frame.

Inventors: Inami; Takuma (Hiroshima, JP), Nakayama; Nobuyuki (Hiroshima, JP), Baba; Hiroyuki (Hiroshima, JP), Tanaka; Hiroshi (Hiroshima, JP)

Applicant: Mazda Motor Corporation (Hiroshima, JP)

Family ID: 1000008821430

Assignee: MAZDA MOTOR CORPORATION (Hiroshima, JP)

Appl. No.: 17/938942

Filed: September 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230094047 A1	Mar. 30, 2023

Foreign Application Priority Data

JP	2021-161834	Sep. 30, 2021
JP	2021-183253	Nov. 10, 2021
JP	2021-183255	Nov. 10, 2021
JP	2021-183319	Nov. 10, 2021
JP	2021-183336	Nov. 10, 2021

Related U.S. Application Data

us-provisional-application US 63403800 20220905

Publication Classification

Int. Cl.: **B62D25/20** (20060101); **B60H1/00** (20060101); **B60H1/24** (20060101); **B60K1/00** (20060101); **B60K1/04** (20190101); **B60L50/60** (20190101); **B62D21/11** (20060101)

U.S. Cl.:

CPC **B62D25/2045** (20130101); **B60H1/00392** (20130101); **B60H1/00564** (20130101); **B60H1/00571** (20130101); **B60H1/246** (20130101); **B60K1/04** (20130101); **B60L50/60** (20190201); **B60L50/66** (20190201); **B62D21/11** (20130101); **B62D25/20** (20130101); **B62D25/2018** (20130101); B60K2001/006 (20130101); B60K2001/0438 (20130101)

Field of Classification Search

CPC: B60H (1/00564); B62D (25/20); B62D (21/04); B62D (25/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0065442	12/2017	Maier	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102018112098	12/2018	DE	B62D 25/145
102020108534	12/2020	DE	N/A
2005-41395	12/2004	JP	N/A
2009-101815	12/2008	JP	N/A
2019-123461	12/2018	JP	N/A
2019-177831	12/2018	JP	N/A
2021-35789	12/2020	JP	N/A

Primary Examiner: Bosques; Edelmira

Assistant Examiner: Giordano; Michael James

Attorney, Agent or Firm: XSENSUS LLP

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) The present application claims priority to Provisional Ser. No. 63/403,800 filed on Sep. 5, 2022, which claims benefit of Japanese Patent Application 2021-161834, filed Sep. 30, 2021, Japanese Patent Application 2021-183253, filed Nov. 10, 2021, Japanese Patent Application 2021-183319, filed Nov. 10, 2021, Japanese

Patent Application 2021-183255, filed Nov. 10, 2021, and Japanese Patent Application 2021-183336, filed Nov. 10, 2021, the entire contents of each of which are incorporated herein by reference.

BACKGROUND

Field

(1) The present disclosure relates to a vehicle-body structure of an automobile.

Description of the Related Art

(2) Recently, computerized control of each portion of an automobile has been developing, and the size of a control device including a microcomputer or the like that executes control of a plurality of control target units has been increasing. The size increase of the control device is also accelerated by, for example, automation of driving, implementation of an external communication function, and implementation of an entertainment function.

(3) For example, in an automobile disclosed in Patent Literature 1, a control device is arranged inside an instrument panel at a position lower than the upper surface of the instrument panel and higher than an accelerator pedal.

CITATION LIST

Patent Literature

(4) [Patent Literature 1] Japanese Patent Laid-open No. 2021-35789

SUMMARY

Problems to be Solved by the Disclosure

(5) The control device or controller of a vehicle includes a microcomputer and the like as described above, and thus is vulnerable to high heat and impact and it is a problem where the control device is arranged in the vehicle body. However, in Patent Literature 1, since the control device is arranged at a lower position than the upper surface of the instrument panel, it is thought to be advantageous that the control device is unlikely to receive direct sunlight.

(6) However, when it is assumed that, for example, an impact load is applied on the vehicle front side, it is assumed that protection of the control device is insufficient since the instrument panel of Patent Literature 1 has no structure with which a load in the front-rear direction can be received.

(7) The present disclosure has been made in view of the above-described problems and has an objective to improve protection performance of a control device of a vehicle.

Means for Solving the Problems

(8) To achieve the above-described objective, a vehicle-body structure provided in an automobile may be premised in a first aspect of the present disclosure. The vehicle-body structure may include a floor panel constituting a floor of an occupant space including a seat on which a passenger sits, a center frame disposed to be higher than and away from the floor panel at a vehicle-width-direction central portion of the occupant space and extending in a vehicle front-rear direction, and a control device that controls a control target unit mounted on the automobile. The control device may be arranged at a lower position than a vehicle front portion of the center frame.

(9) With this configuration, since the control device is arranged at a lower position than the center frame in the occupant space, for example, direct sunlight from the outside is interrupted by the center frame and unlikely to reach the control device. Thus, the control device can be arranged at a thermally advantageous place.

(10) For example, when a case in which an impact load is applied from the vehicle front side is assumed, at least part of the impact load is absorbed by the center frame and deformation of the vehicle body in the vicinity of the center frame is suppressed since the center frame extends in the vehicle front-rear direction. Accordingly, the control device arranged at a lower position than the center frame is protected against the impact load from the front side. This is same for an impact load from the vehicle rear side.

(11) When a case in which an impact load is applied from a side of the vehicle is assumed, the

impact load from a side is unlikely to be directly conveyed to the control device since the control device is arranged corresponding to the vehicle width direction central portion, and thus the control device is protected against the impact load from a side as well.

(12) In a second aspect of the present disclosure, an air-conditioning device or air-conditioner provided on a vehicle front side of the center frame, and an air introducing duct that provides communication between a vent portion provided to the air-conditioning device and inside of the center frame formed in a hollow shape and through which air-conditioned air vented out of the vent portion is introduced into the center frame may be further included. The air introducing duct may be arranged at a higher position than the control device.

(13) With this configuration, air-conditioned air generated by the air-conditioning device is introduced into the center frame through the air introducing duct. Since the center frame extends in the front-rear direction, the air-conditioned air can be guided to a desired place in the front-rear direction in the occupant space. In this case, since the air introducing duct is arranged at a position higher than the control device, direct sunlight is interrupted by the air introducing duct as well and further unlikely to reach the control device.

(14) In a third aspect of the present disclosure, an instrument panel may be arranged at a higher position than a front portion of the center frame.

(15) With this configuration, since the instrument panel is arranged at a higher position than the control device, direct sunlight is interrupted by the instrument panel as well and further unlikely to reach the control device.

(16) In a fourth aspect of the present disclosure, a connecting member or structure extending upward from the floor panel, having an upper portion fixed to the center frame, and connecting the center frame to the floor panel may be further included. The connecting member may include a first connecting member or structure and a second connecting member or structure, the first connecting member being provided on a vehicle front side of the control device, the second connecting member being provided on a vehicle rear side of the control device.

(17) With this configuration, at least two places of the center frame can be solidly connected to the floor panel through the first connecting member and the second connecting member. Since the control device is arranged between the first connecting member and the second connecting member, an impact load in the vehicle front-rear direction is unlikely to be applied to the control device and the protection performance further improves.

(18) In a fifth aspect of the present disclosure, a dash panel extending upward from a front portion of the floor panel and partitioning a vehicle front portion of the occupant space may be further included. In this case, a front portion of the center frame may be connected to the dash panel.

(19) With this configuration, since an impact load from the vehicle front side is absorbed by the dash panel as well, an impact load from the vehicle front side is unlikely to be applied to the control device, and the protection performance further improves.

(20) The floor panel according to a sixth aspect of the present disclosure may include a cross member or structure extending in a vehicle width direction such that the cross member intersects with the center frame in a plan view in the occupant space. The connecting member may extend upward from the cross member, have an upper portion fixed to the center frame, and connect the center frame to the cross member.

(21) With this configuration, since the cross member is provided in the occupant space, a vehicle-body reinforcement effect by the cross member is obtained. In addition, since the center frame higher than and away from the floor panel is connected to the cross member through the connecting member, the strength of the vehicle body around the control device increases and the protection performance further improves.

Advantageous Effects of Disclosure

(22) As described above, since a control device of a vehicle is arranged at a lower position than a

center frame disposed to be higher than and away from a floor panel, the control device can be protected from heat and impact.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) The scope of the present disclosure is best understood from the following detailed description of exemplary embodiments when read in conjunction with the accompanying drawings.
- (2) FIG. 1 is a side view of an automobile having a vehicle-body structure according to an embodiment of the present disclosure.
- (3) FIG. 2 is a perspective view illustrating a state in which the automobile is divided into an upper-portion structural body and a lower-portion structural body according to an embodiment of the present disclosure.
- (4) FIG. 3 is a perspective view in which part of the vehicle-body structure is viewed from an upper side according to an embodiment of the present disclosure.
- (5) FIG. 4 is a plan view of part of the vehicle-body structure according to an embodiment of the present disclosure.
- (6) FIG. 5 is a cross-sectional diagram along line V-V in FIG. 4 according to an embodiment of the present disclosure.
- (7) FIG. 6 is a cross-sectional diagram along line VI-VI in FIG. 4 according to an embodiment of the present disclosure.
- (8) FIG. 7 is a cross-sectional diagram along line VII-VII in FIG. 4 according to an embodiment of the present disclosure.
- (9) FIG. 8 is a perspective view illustrating an occupant-space-side floor panel and the vicinity thereof in an enlarged manner according to an embodiment of the present disclosure.
- (10) FIG. 9 is a cross-sectional diagram illustrating a seat rail and the vicinity thereof in an enlarged manner according to an embodiment of the present disclosure.
- (11) FIG. 10 is a plan view illustrating part of the seat rail and the vicinity thereof in an enlarged manner according to an embodiment of the present disclosure.
- (12) FIG. 11 is a perspective view illustrating a mounting part of the seat rail and the vicinity thereof in an enlarged manner according to an embodiment of the present disclosure.
- (13) FIG. 12 is a cross-sectional diagram of a bend portion of a center frame and the vicinity thereof according to an embodiment of the present disclosure.
- (14) FIG. 13 is a cross-sectional diagram of the vicinity of a front portion of a rear-side frame member constituting the center frame according to an embodiment of the present disclosure.
- (15) FIG. 14 is a perspective view of a connection member according to an embodiment of the present disclosure.
- (16) FIG. 15 is a perspective view of the connection member when viewed in another direction according to an embodiment of the present disclosure.
- (17) FIG. 16 is a side view of the connection member according to an embodiment of the present disclosure.
- (18) FIG. 17 is a cross-sectional diagram of an air-conditioning device and the vicinity thereof according to an embodiment of the present disclosure.
- (19) FIG. 18 is a perspective view illustrating a rear-portion vehicle-body structure in a case in which the tilt angle of the center frame is increased according to an embodiment of the present disclosure.
- (20) FIG. 19 is a cross-sectional diagram illustrating the case in which the tilt angle of the center frame is increased according to an embodiment of the present disclosure.
- (21) FIG. 20 is a perspective view of a dash panel and the vicinity thereof when viewed from a

vehicle rear side according to an embodiment of the present disclosure.

(22) FIG. 21 is a schematic diagram of a cooling path according to an embodiment of the present disclosure.

(23) FIG. 22 is a diagram of a layout of a supply pipe and a discharge pipe for cooling water when viewed from the rear side according to an embodiment of the present disclosure.

(24) FIG. 23 is a diagram of the layout of the supply pipe and the discharge pipe for the cooling water when viewed from a left side according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

(25) Some embodiments of the present disclosure will be described below in detail with reference to the accompanying drawings. The following description of the preferable embodiment is merely exemplary in essence and not intended to limit the present disclosure, its application, nor its usage.

(26) FIG. 1 is a side view of an automobile 1 including a vehicle-body structure A according to one embodiment of the present disclosure when viewed from left. In description of the embodiment, a vehicle front-rear direction is simply referred to as a “front-rear direction”, a vehicle front side is simply referred to as a “front side”, and a vehicle “rear side” is simply referred to as a “rear side”. In addition, a vehicle width direction is the right-left direction of the vehicle, a vehicle left side is simply referred to as a “left side”, and a vehicle right side is simply referred to as a “right side”.

(27) (Entire Structure of Automobile)

(28) The automobile 1 is a passenger automobile, and an occupant space R1 in which a passenger boards is provided at a front-rear direction intermediate portion of the automobile 1. The occupant space R1 includes front seats (front-row seats) FS included in a front row, and rear seats (rear-row seats) RS included in a rear row. The front seats FS include a driver seat arranged on the right side (or the left side) in the occupant space R1, and a front passenger seat arranged on the left side (or the right side) in the occupant space R1. The rear seats RS are arranged on the right and left sides, respectively, in the occupant space R1. Third-row seats may be arranged on the rear side of the rear seats RS. The rear seats RS are not essential and may be omitted.

(29) A front door FD and a rear door RD are disposed on each of the left and right sides of the occupant space R1. The rear door RD may be omitted in a case of the automobile 1 including no rear seats RS.

(30) A front-side space R2 is provided on the front side of the occupant space R1 in the automobile 1. A powertrain PT can be mounted in the front-side space R2 as necessary. When the powertrain PT is mounted in the front-side space R2, the front-side space R2 may be called, for example, a powertrain storage room, a motor room, or an engine room. A bonnet hood BF is provided at an upper portion of the front-side space R2.

(31) A trunk space R3 in which a package or the like can be housed is provided on the rear side of the occupant space R1 in the automobile 1. The trunk space R3 can be opened and closed by a trunk lid TR. A rear-side space R4 is provided on the rear side of the occupant space R1 and at a position lower than the trunk space R3 in the automobile 1. The powertrain PT that generates power for the automobile 1 can be mounted in the rear-side space R4 as necessary. When the powertrain PT is mounted in the rear-side space R4, the rear-side space R4 may be called, for example, a powertrain storage room, a motor room, or an engine room.

(32) The powertrain PT may be mounted in each of the front-side space R2 and the rear-side space R4 or the powertrain PT may be mounted in one of them. A front-wheel-drive vehicle in which only front wheels FT are driven by the powertrain PT is achieved when the powertrain PT is mounted only in the front-side space R2, or a rear-wheel-drive vehicle in which only rear wheels RT are driven by the powertrain PT is achieved when the powertrain PT is mounted only in the rear-side space R4. Alternatively, a four-wheel-drive vehicle is achieved when the front wheels FT and the rear wheels RT are driven by the powertrains PT mounted in both the front-side space R2 and the rear-side space R4.

(33) Each powertrain PT includes at least a traveling motor M (illustrated in FIG. 2) for driving a

drive wheel and also includes a speed reducer, a transmission, or the like as necessary. Thus, the automobile **1** is an electric vehicle. The traveling motor M is disposed such that the rotation center thereof extends in the right-left direction. The powertrain PT may include, for example, a controller in addition to the traveling motor M. The powertrain PT may include an internal combustion engine. A battery unit Y (also illustrated in FIG. **1**) for supplying electric power to the traveling motor M is mounted at a lower portion of the automobile **1**. For example, the battery unit Y may be charged by using power generated by the internal combustion engine, and either the front wheels FT or the rear wheels RT or both may be driven by power generated by the internal combustion engine.

(34) The type of the automobile **1** does not necessarily need to be a four-door vehicle as exemplarily illustrated in FIG. **1** and may be, for example, an automobile including no rear doors RD. The present disclosure is also applicable to an automobile, such as a hatchback vehicle, in which the rear-side space R4 can be opened and closed by a tail gate.

(35) As illustrated in FIG. **2**, the automobile **1** includes a lower-portion structural body **2** and an upper-portion structural body **3**, and the vehicle-body structure A is constituted by the lower-portion structural body **2** and the upper-portion structural body **3**. FIG. **2** illustrates a state in which the doors FD and RD, the bonnet hood BF, a fender, window glasses, a roof, a center pillar, a rear pillar, a bumper, front and rear lighting devices, an instrument panel, the front and rear seats, and the like, which are included in the upper-portion structural body **3** in reality, are removed. FIG. **2** also illustrates a state in which the front wheels FT, the rear wheels RT, a suspension device, and the like, which are included in the lower-portion structural body **2** in reality, are removed.

(36) The lower-portion structural body **2** includes the battery unit Y. The battery unit Y includes a front-side battery FB, a rear-side battery RB, and a rack frame **10** surrounding the front-side battery FB and the rear-side battery RB. The lower-portion structural body **2** also includes a front support frame **20** extending from a front portion of the rack frame **10** toward the front side, and a rear support frame **30** extending from a rear portion of the rack frame **10** toward the rear side.

(37) In a typical electric automobile, a battery unit is often detachably attached as a separated body from a vehicle body under a floor, but in the present embodiment, not only the batteries FB and RB but also the front support frame **20** and the rear support frame **30** are integrated with the rack frame **10** surrounding the batteries FB and RB, and the front support frame **20** and the rear support frame **30** are detachably attached to the upper-portion structural body **3** together with the batteries FB and RB.

(38) Specifically, the automobile **1** of the present embodiment is configured to be able to be divided in the up-down direction into the lower-portion structural body **2** including the batteries FB and RB, and the upper-portion structural body **3** in which the occupant space R1 and the trunk space R3 are formed. Being able to be divided in the up-down direction means integration of the lower-portion structural body **2** with the upper-portion structural body **3** by using fastening members such as bolts and nuts, screws, and the like without using welding, bonding, and the like. Accordingly, the lower-portion structural body **2** can be separated from the upper-portion structural body **3** as necessary when maintenance and repair are performed after the automobile **1** is handed over to a user, and thus maintainability is excellent.

(39) A vehicle-body structure of a ladder frame type is known as the vehicle-body structure of an automobile. In a case of the vehicle-body structure of the ladder frame type, division into a ladder frame and a cabin in the up-down direction is possible, but the ladder frame continuously extends in the front-rear direction and thus mainly receives a collision load at front collision and rear collision. At side collision, the ladder frame only supplementarily receives a collision load, and the collision load is mainly received by the cabin. In this manner, in the vehicle-body structure of the ladder frame type, it is normal that a member that receives a collision load is different between front or rear collision and side collision.

(40) However, in a case of the automobile **1** of the present embodiment, the lower-portion

structural body **2**, which includes the front support frame **20** and the rear support frame **30**, and the upper-portion structural body **3** can be divided from each other, but its technical idea is largely different from that of the conventional vehicle-body structure of the ladder frame type in that a collision load is received by the lower-portion structural body **2** and the upper-portion structural body **3** in both cases of front or rear collision and side collision and thus the collision load can be dispersed to and absorbed by the structural bodies **2** and **3**. Hereinafter, the structures of the lower-portion structural body **2** and the upper-portion structural body **3** will be sequentially described.

(41) (Lower-Portion Structural Body)

(42) First, the lower-portion structural body **2** will be described below. The lower-portion structural body **2** includes the powertrain PT, the front wheels FT, the rear wheels RT, and front-side suspension devices SP1 and SP2 and rear-side suspension devices SP3 and SP4, which are illustrated with virtual lines in FIG. 4, in addition to the batteries FB and RB, the rack frame **10**, the front support frame **20**, and the rear support frame **30**. The formats of the front-side suspension devices SP1 and SP2 and the rear-side suspension devices SP3 and SP4 are not particularly limited, and the vehicle-body structure may be changed in accordance with the formats of the front-side suspension devices SP1 and SP2 and the rear-side suspension devices SP3 and SP4.

(43) As illustrated in FIG. 2, the rack frame **10** as a framework of the battery unit Y is a member for surrounding and protecting the front-side battery FB, the rear-side battery RB, harnesses, and the like. The rack frame **10** is formed in such a large size that, on the lower side of an occupant-space-side floor panel **41** to be described later, the rack frame **10** extends from the vicinity of a left end portion of the occupant-space-side floor panel **41** to the vicinity of a right end portion thereof and extends from the vicinity of a front end portion of the occupant-space-side floor panel **41** to the vicinity of a rear end portion thereof. In this manner, since the rack frame **10** is provided in a large part of a region on the lower side of the occupant-space-side floor panel **41**, the batteries FB and RB having large capacities can be mounted on the automobile **1**. The batteries FB and RB may be, for example, lithium-ion batteries or all-solid-state batteries or may be any other secondary batteries. Alternatively, the batteries FB and RB may be what is called battery cells or may be battery packs in which a plurality of battery cells are housed.

(44) The rack frame **10** includes a left side member **11**, a right side member **12**, a front-side member **13**, and a rear-side member **14**. The left side member **11**, the right side member **12**, the front-side member **13**, and the rear-side member **14** are formed of, for example, an extruded material made of an aluminum alloy, but may be formed of a press-formed material such as an aluminum alloy plate material or a steel plate. In description below, an “extruded material” is an extruded material made of an aluminum alloy, and a “press-formed material” is a press-formed material such as an aluminum alloy plate material or a steel plate. Alternatively, each member may be formed of, for example, cast metal or die cast.

(45) A cross-sectional shape of each of the left side member **11**, the right side member **12**, the front-side member **13**, and the rear-side member **14** in a direction orthogonal to its longitudinal direction is a rectangular shape. The left side member **11**, the right side member **12**, the front-side member **13**, and the rear-side member **14** are all arranged at the same height and substantially horizontally extend. When the lower-portion structural body **2** is to be connected to the upper-portion structural body **3**, the front-side member **13** is fastened and fixed to a lower portion of a dash panel **50** by a fastening member, and the left side member **11** and the right side member **12** are fastened and fixed to right and left side sills **60**, respectively, by fastening members. The rear-side member **14** is fastened and fixed to a connection panel **43**, which will be described later, by a fastening member.

(46) The left side member **11** is provided at a left end portion of the lower-portion structural body **2** and extends in the front-rear direction. The right side member **12** is provided at a right end portion of the lower-portion structural body **2** and extends in the front-rear direction. The left side member **11** and the right side member **12** are arranged on a vehicle-width-direction inner side of the right and left side sills **60**, respectively, to be described later. The front-side member **13** is provided at a

front portion of the battery unit Y and extends in the right-left direction from a front end portion of the left side member **11** to a front end portion of the right side member **12**. A left end portion of the front-side member **13** and the front end portion of the left side member **11** are connected to each other, and a right end portion of the front-side member **13** and the front end portion of the right side member **12** are connected to each other. The rear-side member **14** is provided at a rear portion of the battery unit Y and extends in the right-left direction from a rear end portion of the left side member **11** to a rear end portion of the right side member **12**. A left end portion of the rear-side member **14** and the rear end portion of the left side member **11** are connected to each other, and a right end portion of the rear-side member **14** and the rear end portion of the right side member **12** are connected to each other.

(47) A cover member **15** as a bottom plate is attached to a lower portion of the rack frame **10**. The rack frame **10** is blocked from the lower side by the cover member **15**. The cover member **15** substantially horizontally extends and is fixed to lower surfaces of the left side member **11**, the right side member **12**, the front-side member **13**, and the rear-side member **14** and also fixed to the side sills **60** as described later. Note that an upper portion of the rack frame **10** may be blocked by a non-illustrated lid or may be blocked by the occupant-space-side floor panel **41** to be described later. Note that electric power of the batteries FB and RB housed in the rack frame **10** is supplied to the traveling motor M through a non-illustrated traveling control circuit. The batteries FB and RB can be charged through a non-illustrated charging socket.

(48) FIG. 5 illustrates a cross-section of a right-left direction central portion of the vehicle-body structure A. As illustrated in FIG. 5, first to third battery-side cross members **10A**, **10B**, and **10C** as reinforcement members extending in the right-left direction are provided inside the rack frame **10**. The heights of the first to third battery-side cross members **10A**, **10B**, and **10C** are all the same and are the same as the heights of the front-side member **13** and the rear-side member **14**. The first to third battery-side cross members **10A**, **10B**, and **10C** may be formed of extruded materials or may be formed of press-formed materials. In the present embodiment, the three battery-side cross members **10A**, **10B**, and **10C** are provided, but the number of the battery-side cross members **10A**, **10B**, and **10C** may be increased or decreased in accordance with dimensions of the rack frame **10** in the front-rear direction.

(49) The first to third battery-side cross members battery-side cross members **10A**, **10B**, and **10C** are arranged at an interval from each other in the front-rear direction, the first battery-side cross member **10A** is positioned farthest on the front side, and the third battery-side cross member **10C** is positioned farthest on the rear side. Lower portions of the battery-side cross members **10A**, **10B**, and **10C** are fixed to an upper surface of the cover member **15**. Left end portions of the battery-side cross members **10A**, **10B**, and **10C** are fixed to an inner surface (right-side surface) of the left side member **11**, and right end portions of the battery-side cross members **10A**, **10B**, and **10C** are fixed to an inner surface (left-side surface) of the right side member **12**. In other words, the battery-side cross members **10A**, **10B**, and **10C** are members connecting the left side member **11** and the right side member **12**.

(50) A front-portion central member **16** and first to third rear-portion central members **17** to **19** as reinforcement members extending in the front-rear direction are provided inside the rack frame **10**. The front-portion central member **16** and the first to third rear-portion central members **17** to **19** may be referred to as a battery frame extending in the front-rear direction, and the battery unit Y has a structure including the battery frame constituted by the front-portion central member **16**, the first to third rear-portion central members **17** to **19**, and the like. The left side member **11**, the right side member **12**, the front-side member **13**, and the rear-side member **14** may be included in the battery frame.

(51) The front-portion central member **16** and the first to third rear-portion central members **17** to **19** are arranged at substantially same heights and provided at a right-left direction center of the rack frame **10**. Lower end portions of the front-portion central member **16** and the first to third rear-

portion central members **17** to **19** are attached to the upper surface of the cover member **15**. The front-portion central member **16** and the first to third rear-portion central members **17** to **19** extend from the front-side member **13** to the rear-side member **14**.

(52) The front-portion central member **16** is arranged between the front-side member **13** and the first battery-side cross member **10A**, a front end portion of the front-portion central member **16** is fixed to a right-left direction central portion of the front-side member **13**, and a rear end portion of the front-portion central member **16** is fixed to a right-left direction central portion of the first battery-side cross member **10A**. Accordingly, the front-side member **13** is a member extending to connect the front end portions of the left side member **11** and the right side member **12** to the front end portion of the front-portion central member **16**.

(53) The first rear-portion central member **17** is arranged between the first battery-side cross member **10A** and the second battery-side cross member **10B**, a front end portion of the first rear-portion central member **17** is fixed to the right-left direction central portion of the first battery-side cross member **10A**, and a rear end portion of the first rear-portion central member **17** is fixed to a right-left direction central portion of the second battery-side cross member **10B**. The second rear-portion central member **18** is arranged between the second battery-side cross member **10B** and the third battery-side cross member **10C**, a front end portion of the second rear-portion central member **18** is fixed to the right-left direction central portion of the second battery-side cross member **10B**, and a rear end portion of the second rear-portion central member **18** is fixed to a right-left direction central portion of the third battery-side cross member **10C**. The third rear-portion central member **19** is arranged between the third battery-side cross member **10C** and the rear-side member **14**, a front end portion of the third rear-portion central member **19** is fixed to the right-left direction central portion of the third battery-side cross member **10C**, and a rear end portion of the third rear-portion central member **19** is fixed to a right-left direction central portion of the rear-side member **14**. Accordingly, the first to third battery-side cross members **10A**, **10B**, and **10C** and the front-portion central member **16** and the first to third rear-portion central members **17** to **19** are disposed in a lattice shape and connected to each other inside the rack frame **10**, which further increases the effect of reinforcing the rack frame **10** and thus the effect of reinforcing the lower-portion structural body **2**.

(54) When a virtual straight line extending in the front-rear direction in a plan view is assumed, the positions of the front-portion central member **16** and the first to third rear-portion central members **17** to **19** in the right-left direction are set such that the members are arranged on the virtual line. In other words, the members are provided such that the first to third rear-portion central members **17** to **19** are positioned on a virtual extended line from the front-portion central member **16** on the rear side. Note that the front-portion central member **16** and the first to third rear-portion central members **17** to **19** may be formed as one member that is continuous in the front-rear direction. In this case, the one member extends from the front-side member **13** to the rear-side member **14**.

(55) As illustrated in FIG. 2, a pair of right and left front support frames **20** are provided and substantially horizontally extend in straight lines on the lower side of the upper-portion structural body **3**. Each front support frame **20** may be formed of, for example, an extruded material or a press-formed material. In the present embodiment, each front support frame **20** is formed of an extruded material, and thus a cross-sectional shape thereof in a direction orthogonal to the front-rear direction is substantially constant from a front end portion to a rear end portion.

(56) The left-side front support frame **20** is connected to a site on the left side of a right-left direction center of the front-side member **13** constituting the front portion of the rack frame **10**, and this connection site is positioned on the right side of the left side member **11** of the rack frame **10**. The right-side front support frame **20** is connected to a site on the right side of the right-left direction center of the front-side member **13**, and this connection site is positioned on the left side of the right side member **12** of the rack frame **10**. The heights of the right and left front support frames **20** are substantially same.

(57) The front-side powertrain PT is attached to each front support frame **20** through a non-illustrated mounting member. In this case, the front support frame **20** serves as a front-side motor support frame that supports the traveling motor M on the front side of the battery unit Y. In the lower-portion structural body **2**, drive shafts S1 through which output from the powertrain PT (rotational force of the traveling motor M) is transferred to the right and left front wheels FT, respectively, are provided on the right and left sides.

(58) Right and left suspension arms constituting parts of the front-side suspension devices SP1 and SP2 illustrated with virtual lines in FIG. 4 are freely swingably supported to the right and left front support frames **20**, respectively, in the up-down direction. The front support frames **20** may be members for supporting the suspension arms without supporting the powertrain PT.

(59) As illustrated in FIG. 2, similarly to the front support frames **20**, a pair of right and left rear support frames **30** are provided and substantially horizontally extend in straight lines toward the rear side. Each rear support frame **30** may be formed of, for example, an extruded material or a press-formed material. In the present embodiment each rear support frame **30** is formed of an extruded material.

(60) The left-side rear support frame **30** is connected to a site on the left side of a right-left direction center of the rear-side member **14** constituting the rear portion of the rack frame **10**, and this connection site is positioned on the right side of the left side member **11** of the rack frame **10**. The right-side rear support frame **30** is connected to a site on the right side of the right-left direction center of the rear-side member **14**, and this connection site is positioned on the left side of the right side member **12** of the rack frame **10**.

(61) The rear-side powertrain PT is attached to each rear support frame **30** through a non-illustrated mounting member. In this case, the rear support frame **30** serves as a rear-side motor support frame that supports the rear-side traveling motor M of the battery unit Y. In the lower-portion structural body **2**, drive shafts S2 through which output from the powertrain PT (rotational force of the traveling motor M) is transferred to the right and left rear wheels, respectively, are provided on the right and left sides.

(62) Right and left suspension arms constituting parts of the rear-side suspension devices SP3 and SP4 illustrated with virtual lines in FIG. 4 are freely swingably supported to the right and left rear support frames **30**, respectively, in the up-down direction. The rear support frames **30** may be members for supporting the suspension arms without supporting the powertrain PT.

(63) (Upper-Portion Structural Body)

(64) Subsequently, the upper-portion structural body **3** will be described below. The upper-portion structural body **3** includes a floor member **40**, the dash panel **50**, and the pair of right and left side sills **60**. The floor member **40** is a member arranged at a higher position than the rack frame **10** and the rear support frames **30** of the lower-portion structural body **2**. The floor member **40** includes the occupant-space-side floor panel (first floor panel) **41** constituting a floor of the occupant space R1 including the front seats FS and the rear seats RS (illustrated in FIG. 1) on which passengers sits, a trunk-space-side floor panel (second floor panel) **42** constituting a floor of the trunk space R3, and the connection panel **43** connecting a rear portion of the occupant-space-side floor panel **41** and a front portion of the trunk-space-side floor panel **42**. A kick-up portion is constituted by the connection panel **43**.

(65) The floor member **40** may be formed of, for example, a member shaped by pressing a steel plate or the like. The occupant-space-side floor panel **41**, the trunk-space-side floor panel **42**, and the connection panel **43** may be integrally formed or may be formed by separately forming components and then connecting them. In the present embodiment, description is made with the three divided portions of the occupant-space-side floor panel **41**, the trunk-space-side floor panel **42**, and the connection panel **43**, but the floor member **40** including the panels **41** to **43** may be referred to as a floor panel. Alternatively, only the occupant-space-side floor panel **41** may be referred to as a floor panel.

(66) The occupant-space-side floor panel **41** extends from a front portion of the occupant space **R1** to a rear portion thereof and from a left-side portion of the occupant space **R1** to a right-side portion thereof. The occupant-space-side floor panel **41** according to the present embodiment has a floor tunnel-less structure including no tunnel portion. Specifically, a vehicle-width-direction central portion of a floor panel of a conventional automobile is typically provided with a tunnel portion largely bulging upward and extending in the front-rear direction. The tunnel portion is a part for allowing, for example, insertion of an exhaust pipe extending toward the rear side from an engine mounted in an engine room at a vehicle front portion and insertion of a propeller shaft through which output from the engine mounted in the engine room at the vehicle front portion is transferred to rear wheels. The diameters of the exhaust pipe and the propeller shaft are often, for example, equal to or larger than 10 cm, and furthermore, a gap of at least several centimeters or larger needs to be provided between each of the exhaust pipe and the propeller shaft and the floor panel to prevent interference of the exhaust pipe or the propeller shaft with the floor panel. In addition, for example, an insulator is disposed on an inner surface of the tunnel portion in some cases. With these factors, the height of bulging of the tunnel portion from the floor panel is, for example, equal to or larger than 15 cm or equal to or larger than 20 cm in some cases, and as for a positional relation with a seat, an upper end of the tunnel portion is higher than a lower end of a seat cushion on a seat rail or an up-down direction central portion of the seat cushion. A structure without such a tunnel portion largely bulging upward is a tunnel-less structure.

(67) The occupant-space-side floor panel **41** includes no tunnel portion having a height equal to or larger than 15 cm or equal to or larger than 20 cm from an upper surface of the occupant-space-side floor panel **41** as described above, but may include, for example, a bulging portion having a low height equal to or smaller than 5 cm or equal to or smaller than 10 cm from the upper surface of the occupant-space-side floor panel **41**. In a case of such a bulging portion having a low height, neither exhaust pipe nor a propeller shaft can be inserted inside the bulging portion, and thus the bulging portion does not function as a tunnel portion. Thus, the occupant-space-side floor panel **41**, which includes a bulging portion having a low height equal to or smaller than 5 cm or equal to or smaller than 10 cm from the upper surface of the occupant-space-side floor panel **41**, is a floor panel of a tunnel-less structure. In addition, the occupant-space-side floor panel **41** may be provided with, for example, a rib protruding upward and extending in the front-rear direction. The height of such a rib is several centimeters approximately, and thus the floor panel is of a tunnel-less structure even when provided with the rib.

(68) In the present embodiment, since each powertrain **PT** includes the traveling motor **M**, no internal combustion engine needs to be mounted in the front-side space **R2** and thus no exhaust pipe needs to be guided to the vehicle rear side. When a powertrain **PT** is mounted in the rear-side space **R4**, the rear wheels **RT** can be driven by the powertrain **PT** and a propeller shaft can be omitted. Accordingly, the occupant-space-side floor panel **41** can have a tunnel-less structure.

(69) As illustrated in FIG. 3 as well, a recessed portion **41a** formed bulging downward is formed at a front-rear direction intermediate portion of the occupant-space-side floor panel **41**. The recessed portion **41a** has a bottom surface **41b** on which the feet of a rear-seat passenger sitting on a rear seat **RS** can be placed. The bottom surface **41b** is substantially horizontally formed. A front-side part of the recessed portion **41a** is formed to be gradually deeper toward the rear side. The recessed portion **41a** may be continuously formed from a left side portion of the occupant-space-side floor panel **41** to a right side portion thereof.

(70) The bottom surface **41b** of the recessed portion **41a** has a height substantially same as that of a lower portion of the corresponding side sill **60** to be described later, and accordingly, the height of the bottom surface **41b** is sufficiently low. The positional relation between the recessed portion **41a** and a seat cushion of each rear seat **RS** in the front-rear direction is set such that the feet of a rear-seat passenger sitting on the rear seat **RS** are naturally placed on the bottom surface **41b** when the feet are held directly downward. The position of a front portion of the recessed portion **41a** is set

such that the feet of a rear-seat passenger sitting on the rear seat RS are placed on the bottom surface **41b** even when the feet are moved obliquely forward. In other words, the position of the recessed portion **41a** and the dimension thereof in the front-rear direction are set such that the feet of a rear-seat passenger can be placed on the bottom surface **41b** when the feet are moved somehow in the front-rear direction. Accordingly, a foot space for a rear-seat passenger can be expanded, which improves comfortability. The depth of the recessed portion **41a** may be, for example, 5 cm or larger, or 10 cm or larger.

(71) A floor frame **41c** extending in the front-rear direction is provided at a right-left direction central portion of the recessed portion **41a**. A lower portion of the floor frame **41c** is fixed to the bottom surface **41b** of the recessed portion **41a**. A part at which the recessed portion **41a** is formed at the occupant-space-side floor panel **41** can be reinforced since the floor frame **41c** is provided.

(72) A rear reinforcement member **47** extending in the front-rear direction is provided on the rear side of the recessed portion **41a** of the occupant-space-side floor panel **41**. The rear reinforcement member **47** is joined to the upper surface of the occupant-space-side floor panel **41**. The rear reinforcement member **47** may be provided as necessary and may be omitted.

(73) The trunk-space-side floor panel **42** is positioned higher than the occupant-space-side floor panel **41**. The rear-side space R4 is positioned lower than the trunk-space-side floor panel **42**. In other words, the trunk-space-side floor panel **42** is arranged to separate the trunk space R3 from the rear-side space R4. The dimension of the trunk-space-side floor panel **42** in the front-rear direction is set to be shorter than the dimension of the occupant-space-side floor panel **41** in the front-rear direction.

(74) Since the trunk-space-side floor panel **42** is arranged at a higher position than the occupant-space-side floor panel **41**, the connection panel **43** extends in the up-down direction. The connection panel **43** may be vertical or may be tilted such that the connection panel **43** is positioned farther on the rear side at a position farther on the upper side.

(75) As illustrated in FIG. 7 as well, the dash panel **50** is a member as a partition wall between the front-side space R2 and the occupant space R1 and extends upward from a front portion of the occupant-space-side floor panel **41** and in the right-left direction as well, thereby partitioning the front portion of the occupant space R1.

(76) As illustrated in FIG. 4, the right and left side sills **60** are disposed extending in the front-rear direction at right and left end portions, respectively, of the occupant-space-side floor panel **41**. The left end portion of the occupant-space-side floor panel **41** is connected to an up-down direction intermediate portion of the left side sill **60**, an upper part of the side sill **60** protrudes upward from a connection site of the occupant-space-side floor panel **41**, and a lower part of the side sill **60** protrudes downward from the connection site of the occupant-space-side floor panel **41**. Since the battery unit Y including the batteries FB and RB is disposed at a lower position than the occupant-space-side floor panel **41**, such arrangement is made that the lower part of the side sill **60** overlaps with the batteries FB and RB in a vehicle side view. Similarly, the right side sill **60** is connected to the right end portion of the occupant-space-side floor panel **41**.

(77) As illustrated in FIG. 3, the upper-portion structural body **3** includes a pair of right and left hinge pillars **70**. The right hinge pillar **70** extends upward from a front end portion of the right side sill **60**. The left hinge pillar **70** extends upward from a front end portion of the left side sill **60**. The right and left front doors FD (illustrated in FIG. 1) are rotatably attached to the right and left hinge pillars **70**, respectively. A left edge portion of the dash panel **50** is connected to a right-side surface of the left hinge pillar **70**. A right edge portion of the dash panel **50** is connected to a left-side surface of the right hinge pillar **70**. Note that, The upper-portion structural body **3** is also provided with a center pillar, a rear pillar, and the like.

(78) A left-side front-wheel suspension support member **51A** that supports the suspension device (front suspension device) SP1 (illustrated with virtual lines in FIG. 4) for the left front wheel FT is provided on the left side on the front side of the dash panel **50** in the upper-portion structural body

3. A right-side front-wheel suspension support member **51B** that supports the suspension device (front suspension device) **SP2** (illustrated with virtual lines in FIG. **4**) for the right front wheel **FT** is provided on the right side on the front side of the dash panel **50** in the upper-portion structural body **3**. The suspension devices **SP1** and **SP2** are not limited to a particular format but include suspension arms that freely swingably support the front wheels **FT** in the up-down direction, shock absorbers, springs, or the like. End portions of the suspension arms on the vehicle body side, upper end portions of the shock absorbers, or the like are attached to the front-wheel suspension support members **51A** and **51B**. The front-wheel suspension support members **51A** and **51B** can be made of, for example, aluminum die cast, but are not limited thereto and may be made of a combination of steel plates or the like.

(79) As illustrated in, for example, FIG. **6**, three left-side fixation frames **52A** for fixing the left-side front-wheel suspension support member **51A** are provided on the left side on the front side of the dash panel **50**. The three left-side fixation frames **52A** are arranged at an interval from each other in the up-down direction, and front portions of the three left-side fixation frames **52A** are fixed to the front-wheel suspension support member **51A**. Rear portions of the left-side fixation frames **52A** arranged uppermost and at an up-down direction intermediate position are fixed to the left-side hinge pillar **70** and the left side of the dash panel **50**. A rear portion of the left-side fixation frame **52A** arranged lowermost is fixed to the left side sill **60**.

(80) As partially illustrated in FIG. **3**, three right-side fixation frames **52B** for fixing the right-side front-wheel suspension support member **51B** are provided on the right side on the front side of the dash panel **50**. The three right-side fixation frames **52B** are arranged at an interval from each other in the up-down direction, and front portions of the three right-side fixation frames **52B** are fixed to the front-wheel suspension support member **51B**. Rear portions of the right-side fixation frames **52B** arranged uppermost and at an up-down direction intermediate position are fixed to the right-side hinge pillar **70** and the right side of the dash panel **50**. A rear portion of the right-side fixation frame **52B** arranged lowermost is fixed to the right side sill **60**.

(81) As illustrated in FIG. **2**, a left-side crush can **53A** extending toward the front side is fixed to a front portion of the left-side front-wheel suspension support member **51A**. A right-side crush can **53B** extending toward the front side is fixed to a front portion of the right-side front-wheel suspension support member **51B**. A bumper reinforcement **140** extending in the right-left direction is attached to a front portion of the left-side crush can **53A** and a front portion of the right-side crush can **53B**.

(82) As illustrated in FIG. **4**, the upper-portion structural body **3** includes a left-side front frame **54A** and a right-side front frame **54B**. Specifically, the left-side front frame **54A** connecting a front portion of a center frame **80** to be described later and the left-side front-wheel suspension support member **51A**, and the right-side front frame **54B** connecting the front portion of the center frame **80** and the right-side front-wheel suspension support member **51B** are provided on the front side of the dash panel **50**. The left-side front frame **54A** is tilted such that the left-side front frame **54A** is positioned farther on the left side at a position farther on the front side. The right-side front frame **54B** is tilted such that the right-side front frame **54B** is positioned farther on the right side at a position farther on the front side. Since the right and left front-wheel suspension support members **51A** and **51B** are each connected to the front portion of the center frame **80**, the stiffness of the front-wheel suspension support members **51A** and **51B** is increased, which improves maneuvering stability of the vehicle. In addition, the stiffness of the vehicle front side including the vicinity of the dash panel **50** is increased as well.

(83) The upper-portion structural body **3** includes a left-side rear-side frame **112A** extending in the front-rear direction on the left side on the rear side of the rear portion of the occupant-space-side floor panel **41**, and a right-side rear-side frame **112B** extending in the front-rear direction on the right side on the rear side of the rear portion of the occupant-space-side floor panel **41**. A front portion of the left-side rear-side frame **112A** is connected to a rear portion of the left-side side sill

60. A front portion of the right-side rear-side frame **112B** is connected to a rear portion of the right-side side sill **60**. A front-rear direction intermediate portion of the left-side rear-side frame **112A** and a front-rear direction intermediate portion of the right-side rear-side frame **112B** are connected to each other through a trunk-side cross member (connecting member) **105** extending in the right-left direction.

(84) A left-side rear-wheel suspension support member **110A** that supports the suspension device (rear suspension device) **SP3** (illustrated with virtual lines in FIG. **4**) for the left rear wheel **RT** is provided on the left side on the rear side of the connection panel **43** in the upper-portion structural body **3**. The rear-wheel suspension support member **110A** is fixed to the left-side rear-side frame **112A**. A right-side rear-wheel suspension support member **110B** that supports the suspension device (rear suspension device) **SP4** (illustrated with virtual lines in FIG. **4**) for the right rear wheel **RT** is provided on the right side on the rear side of the connection panel **43** in the upper-portion structural body **3**. The rear-wheel suspension support member **110B** is fixed to the right-side rear-side frame **112B**. The suspension devices **SP3** and **SP4** are not limited to a particular format but include suspension arms that freely swingably support the rear wheels **RT** in the up-down direction, shock absorbers, springs, or the like.

(85) An upper portion of the spring or shock absorber included in the left-side suspension device **SP3** is connected to an upper portion of the rear-wheel suspension support member **110A**. As illustrated in FIG. **3**, the upper portion of the rear-wheel suspension support member **110A** is a left-side load input portion **110a** to which loads from the springs or the shock absorbers are input. An upper portion of the spring or shock absorber included in the right-side suspension device **SP4** is connected to an upper portion of the rear-wheel suspension support member **110B**. The upper portion of the rear-wheel suspension support member **110B** is a right-side load input portion **110b** to which a load from the spring or the shock absorber is input. The left-side load input portion **110a** and the right-side load input portion **110b** are also fixed to the right and left sides of the trunk-space-side floor panel **42**. In addition, the left-side load input portion **110a** and the right-side load input portion **110b** are connected to each other through the trunk-side cross member **105**. The trunk-side cross member **105** is joined to an upper surface of the trunk-space-side floor panel **42**, and a closed cross-section structure extending in the vehicle width direction is constituted by the trunk-space-side floor panel **42** and the trunk-side cross member **105**.

(86) As illustrated in FIG. **2**, a rear-portion cross member **44E** is provided at a position lower than the left-side load input portion **110a** and the right-side load input portion **110b**. The rear-portion cross member **44E** is joined to the rear portion of the occupant-space-side floor panel **41**.

(87) The upper-portion structural body **3** can be partitioned into, for example, a front-portion vehicle-body structure and a rear-portion vehicle-body structure. As illustrated in FIG. **4**, the rear-portion vehicle-body structure may be the rear side of the occupant-space-side floor panel **41** in the upper-portion structural body **3**. A left-side rear frame **111A** connecting a rear portion of the center frame **80** and the left-side rear-wheel suspension support member **110A**, and a right-side rear frame **111B** connecting the rear portion of the center frame **80** and the right-side rear-wheel suspension support member **110B** are provided on the rear side of the connection panel **43** of the upper-portion structural body **3**. Since the right and left rear-wheel suspension support members **110A** and **110B** are each connected to the rear portion of the center frame **80**, the stiffness of the rear-wheel suspension support members **110A** and **110B** is increased, which improves maneuvering stability of the vehicle. In addition, the stiffness of the vehicle rear side including the vicinity of the connection panel **43** is increased as well.

(88) The left-side rear frame **111A** and the right-side rear frame **111B** are arranged at a lower position than the trunk-space-side floor panel **42**. As illustrated in FIG. **6**, a rear portion of the left-side rear frame **111A** is fixed to the upper portion of the rear-wheel suspension support member **110A**, in other words, the left-side load input portion **110a**. The left-side rear frame **111A** is tilted in a side view such that the left-side rear frame **111A** is positioned farther on the lower side at a

position farther on the front side from the upper portion of the rear-wheel suspension support member **110A** toward the front side, and is also tilted in a plan view such that the left-side rear frame **111A** is positioned closer to a vehicle width direction central portion at a position farther on the front side as illustrated in FIG. 4. A rear portion of the right-side rear frame **111B** is fixed to the upper portion of the rear-wheel suspension support member **110B**, in other words, the right-side load input portion **110b**. The right-side rear frame **111B** is tilted in a side view such that the right-side rear frame **111B** is positioned farther on the lower side at a position farther on the front side from the upper portion of the rear-wheel suspension support member **110B** toward the front side, and is also tilted in a plan view such that the right-side rear frame **111B** is positioned closer to the vehicle width direction central portion at a position farther on the front side as illustrated in FIG. 4. Accordingly, the left-side rear frame **111A** and the right-side rear frame **111B** are each arranged such that the rear frame is positioned on a vehicle-width-direction outer side at a position farther on the rear side, and the interval between the left-side rear frame **111A** and the right-side rear frame **111B** is smaller at a position farther on the front side.

(89) The rear portion of the left-side rear frame **111A** is also connected to the front-rear direction intermediate portion of the left-side rear-side frame **112A**. Accordingly, the left-side rear frame **111A** serves as a left-side connection frame extending from the rear portion of the center frame **80** to the left-side rear-side frame **112A** and connecting the rear portion of the center frame **80** and the left-side rear-side frame **112A**. The left-side rear frame **111A** also serves as a left-side rear connection frame connecting the left-side load input portion **110a** and the rear-portion cross member **44E**. Specifically, a front portion of the left-side rear frame **111A** is fixed to the left-side load input portion **110a**, and the rear portion of the left-side rear frame **111A** is also fixed to the rear-portion cross member **44E**.

(90) The rear portion of the right-side rear frame **111B** is also connected to the front-rear direction intermediate portion of the right-side rear-side frame **112B**. Accordingly, the right-side rear frame **111B** serves as a right-side connection frame extending from the rear portion of the center frame **80** to the right-side rear-side frame **112B** and connecting the rear portion of the center frame **80** and the right-side rear-side frame **112B**. The right-side rear frame **111B** also serves as a right-side rear connection frame connecting the right-side load input portion **110b** and the rear-portion cross member **44E**. Specifically, a front portion of the right-side rear frame **111B** is fixed to the right-side load input portion **110b**, and the rear portion of the right-side rear frame **111B** is also fixed to the rear-portion cross member **44E**.

(91) The left-side rear frame **111A** is arranged at an upward tilt toward the left-side load input portion **110a**. Accordingly, an upward load from the rear suspension device **SP3** is input to the left-side rear frame **111A** in a pulling direction, and thus deflection deformation of the left-side rear frame **111A** is unlikely to occur as compared to a case in which a load in a compression direction is input, which leads to suppression of vibration and noise due to load input from the rear suspension device **SP3**. This is same for the right-side rear frame **111B**.

(92) The left-side rear frame **111A** is arranged on the front side of the left rear drive shaft **S2**. The left rear drive shaft **S2** is arranged such that the left rear drive shaft **S2** overlaps with part of the left-side rear frame **111A** when viewed in the front-rear direction. Specifically, the height of a right-left direction intermediate portion of the left rear drive shaft **S2** is substantially equal to the height of a part between the front and rear portions of the left-side rear frame **111A**.

(93) The right-side rear frame **111B** is arranged on the front side of the right rear drive shaft **S2**. The right rear drive shaft **S2** is arranged such that the right rear drive shaft **S2** overlaps with part of the right-side rear frame **111B** when viewed in the front-rear direction. Specifically, the height of a right-left direction intermediate portion of the right rear drive shaft **S2** is substantially equal to the height of a part between the front and rear portions of the right-side rear frame **111B**.

(94) As illustrated in FIGS. 3 and 6, the occupant-space-side floor panel **41** includes a front-portion cross member **44A**, an intermediate cross member **44B**, a recessed-portion front-side cross member

44C, a recessed-portion rear-side cross member **44D**, and the rear-portion cross member **44E**. The front-portion cross member **44A**, the intermediate cross member **44B**, the recessed-portion front-side cross member **44C**, the recessed-portion rear-side cross member **44D**, and the rear-portion cross member **44E** extend in the right-left direction and are fixed to the upper surface of the occupant-space-side floor panel **41**. Thus, the front-portion cross member **44A**, the intermediate cross member **44B**, the recessed-portion front-side cross member **44C**, the recessed-portion rear-side cross member **44D**, and the rear-portion cross member **44E** are disposed such that the members intersect with the center frame **80**, which will be described later, in a plan view in the occupant space **R1**.

(95) The front-portion cross member **44A** is disposed at the front portion of the occupant-space-side floor panel **41**. A front portion of the front-portion cross member **44A** is also joined to the lower portion of the dash panel **50**. The intermediate cross member **44B** is disposed on the rear side of the front-portion cross member **44A** and on the front side of the recessed portion **41a**, and a closed cross-section is constituted by the intermediate cross member **44B** and the occupant-space-side floor panel **41**. The rear-portion cross member **44E** is disposed at the rear portion of the occupant-space-side floor panel **41**. The rear-portion cross member **44E** is also fixed to the connection panel **43**.

(96) The recessed-portion front-side cross member **44C** is disposed extending in the right-left direction along the front portion of the recessed portion **41a** on the rear side of the intermediate cross member **44B**. The recessed-portion rear-side cross member **44D** is disposed extending in the right-left direction along a rear portion of the recessed portion **41a** on the rear side of the recessed-portion front-side cross member **44C**. A closed cross-section is constituted by the recessed-portion front-side cross member **44C** and the occupant-space-side floor panel **41**, and a closed cross-section is constituted by the recessed-portion rear-side cross member **44D** and the occupant-space-side floor panel **41**. Since the recessed-portion front-side cross member **44C** and the recessed-portion rear-side cross member **44D** are provided, the part at which the recessed portion **41a** is formed can be reinforced. A front portion of the floor frame **41c** provided inside the recessed portion **41a** is connected to a right-left direction central portion of the recessed-portion front-side cross member **44C**, and a rear portion of the floor frame **41c** is connected to a right-left direction central portion of the recessed-portion rear-side cross member **44D**.

(97) As illustrated in FIG. **8**, the upper-portion structural body **3** includes a pair of right and left left-side seat rails **90** supporting the left-side front seat **FS**, and a pair of right and left right-side seat rails **91** supporting the right-side front seat **FS**. The left-side seat rails **90** are used to adjust the position of the left-side front seat **FS** in the front-rear direction, are disposed on the left side on the occupant-space-side floor panel **41**, and extend in the front-rear direction. The right-side seat rails **91** are used to adjust the position of the right-side front seat **FS** in the front-rear direction, are disposed on the right side of the occupant-space-side floor panel **41**, and extend in the front-rear direction.

(98) The left-side seat rails **90** are positioned higher than the intermediate cross member **44B** and the recessed-portion front-side cross member **44C** and attached to the intermediate cross member **44B** and the recessed-portion front-side cross member **44C**. Specifically, as illustrated in FIG. **9** as well, the left-side seat rails **90** extend from the intermediate cross member **44B** to the recessed-portion front-side cross member **44C**, front portions of the left-side seat rails **90** are attached to the intermediate cross member **44B**, and rear portions of the left-side seat rails **90** are attached to the recessed-portion front-side cross member **44C**.

(99) Similarly, the right-side seat rails **91** extend from the intermediate cross member **44B** to the recessed-portion front-side cross member **44C**, front portions of the right-side seat rails **91** are attached to the intermediate cross member **44B**, and rear portions of the right-side seat rails **91** are attached to the recessed-portion front-side cross member **44C**.

(100) As illustrated in FIG. **10**, the intermediate cross member **44B** includes a front-portion

common bracket **45** to which the front portions of the left-side seat rails **90** and the front portions of the right-side seat rails **91** are attached in a state in which the seat rails are separated from each other in the right-left direction. Note that the center frame **80** is omitted in FIG. **10**. As illustrated in FIG. **11**, the front-portion common bracket **45** has a shape that is long in the right-left direction and is fixed to an upper surface of the intermediate cross member **44B**. A right-left direction central portion of the front-portion common bracket **45** is positioned at a right-left direction central portion of the intermediate cross member **44B**. A central fixation portion **45a** (illustrated only in FIGS. **10** and **11**) into which a lower portion of a second connecting member **102** to be described later is inserted is provided at the right-left direction central portion of the front-portion common bracket **45**. A left-side fixation portion **45b** (illustrated only in FIGS. **4** and **11**) to which the front portions of the left-side seat rails **90** are fixed by fastening members such as bolts or screws is provided on the left side of the central fixation portion **45a** of the front-portion common bracket **45**. A right-side fixation portion **45c** (illustrated only in FIGS. **4** and **11**) to which the front portions of the right-side seat rails **91** are fixed by fastening members is provided on the right side of the central fixation portion **45a** of the front-portion common bracket **45**. Note that the seat rails are omitted in FIGS. **3** to **5** and **11**.

(101) The recessed-portion front-side cross member **44C** includes a rear-portion common bracket **46** to which the rear portions of the left-side seat rails **90** and the rear portions of the right-side seat rails **91** are attached in a state in which the seat rails are separated from each other in the right-left direction. As illustrated in FIG. **11**, the rear-portion common bracket **46** has a shape that is long in the right-left direction and is fixed to an upper surface of the recessed-portion front-side cross member **44C**. A right-left direction central portion of the rear-portion common bracket **46** is positioned at the right-left direction central portion of the recessed-portion front-side cross member **44C**. A central fixation portion **46a** (illustrated only in FIGS. **10** and **11**) in which a lower portion of a connecting member to be described later is inserted and fixed is provided at the right-left direction central portion of the rear-portion common bracket **46**. A left-side fixation portion **46b** (illustrated only in FIGS. **4** and **11**) to which the rear portions of the left-side seat rails **90** are fixed by fastening members is provided on the left side of the central fixation portion **46a** of the rear-portion common bracket **46**. A right-side fixation portion **46c** (illustrated only in FIGS. **4** and **11**) to which the rear portions of the right-side seat rails **91** are fixed by fastening members is provided on the right side of the central fixation portion **46a** of the rear-portion common bracket **46**.

(102) As illustrated in, for example, FIG. **8**, the upper-portion structural body **3** includes the center frame **80** that is continuous from the dash panel **50** to the connection panel **43**. The center frame **80** is positioned at a right-left direction central portion, and also the front-portion central member **16** and the first to third rear-portion central members **17** to **19** of the battery unit **Y** are positioned at the right-left direction central portion. Specifically, the disposition positions of the front-portion central member **16** and the first to third rear-portion central members **17** to **19** and the center frame **80** are set to have a positional relation in which the front-portion central member **16** and the first to third rear-portion central members **17** to **19** each overlaps with the center frame **80** in a plan view.

(103) The center frame **80** is disposed to be higher than and away from the occupant-space-side floor panel **41** at a right-left direction central portion of the occupant space **R1** and extends in the front-rear direction. The distance between a lower surface of the center frame **80** and the upper surface of the occupant-space-side floor panel **41** may be set to be, for example, equal to or larger than 10 cm or equal to or larger than 20 cm at a part separated most. The left-side front seat **FS** and a rear seat **RS** are disposed on the left side of the center frame **80**, and the right-side front seat **FS** and a rear seat **RS** are disposed on the right side of the center frame **80**.

(104) Since the center frame **80** is arranged to be higher than and away from the occupant-space-side floor panel **41**, components and the like can be disposed in a space between a lower surface of the center frame **80** and the upper surface of the occupant-space-side floor panel **41**. Alternatively, the space between the lower surface of the center frame **80** and the upper surface of the occupant-

space-frame floor panel **41** can be used as an object housing unit. As illustrated in FIGS. **5** and **6**, the center frame **80** according to the present embodiment includes a bend portion **80A** that bends in the up-down direction at a front-rear direction intermediate portion. Since the bend portion **80A** is provided in the center frame **80**, for example, a rear-side part of the center frame **80** can be positioned lower than a front-side part of the center frame **80**, and thus comfortability of rear-seat passengers can be improved. Since the front-side part of the center frame **80** can be positioned higher than the rear-side part of the center frame **80**, a large-sized component or object, a plurality of components, or the like can be arranged on the lower side of the front-side part of the center frame **80**. The bend portion **80A** is formed at a site on the front side of a front-rear direction central portion of the center frame **80**. The formation position of the bend portion **80A** is not limited to the illustrated position but may be, for example, the front-rear direction central portion of the center frame **80** or a site on the rear side of the front-rear direction central portion of the center frame **80**.

(105) Specifically, the center frame **80** includes a front-side frame member **81** extending in the front-rear direction, a rear-side frame member **82** disposed on the vehicle rear side of the front-side frame member **81** and extending toward the rear side, and a connection member **83** connecting a rear portion of the front-side frame member **81** and a front portion of the rear-side frame member **82**. The front-side frame member **81** and the rear-side frame member **82** have hollow shapes, in other words, tubular shapes extending in the front-rear direction and may be formed of, for example, an extruded material. The front-side frame member **81** and the rear-side frame member **82** having hollow shapes are lightweight and high-stiffness members. When the center frame **80** is used as an air sending means of air-conditioned air to be described later, a rear portion of the rear-side frame member **82** may be blocked to prevent leakage of air-conditioned air.

(106) Vertical cross-sections of the front-side frame member **81** and the rear-side frame member **82** in the vehicle width direction have rectangular shapes, and thus the front-side frame member **81** and the rear-side frame member **82** each include an upper wall portion and a lower wall portion extending in the right-left direction and right and left sidewall portions extending in the up-down direction. Note that the cross-sectional shapes of the front-side frame member **81** and the rear-side frame member **82** are not limited to rectangular shapes but may be pentagonal shapes or higher polygonal shapes or may be circular shapes or elliptical shapes.

(107) The dimension of the rear-side frame member **82** in the longitudinal direction is set to be longer than the dimension of the front-side frame member **81** in the longitudinal direction. Accordingly, a connection part between the front-side frame member **81** and the rear-side frame member **82** is positioned on the front side of a front-rear direction central portion of the occupant space **R1**. Note that the center frame **80** is not limited to the two-division structure of the front-side frame member **81** and the rear-side frame member **82** but may be formed as one member a front portion to a rear portion or may have a three-division structure.

(108) The front-side frame member **81** is tilted at a first tilt angle relative to a horizontal plane and extends straight. The rear-side frame member **82** is tilted at a second tilt angle smaller than the first tilt angle relative to the horizontal plane and extends straight. Since the rear-side frame member **82** is tilted at a tilt angle different from that of the front-side frame member **81**, the bend portion **80A** that bends downward is formed at the connection part between the front-side frame member **81** and the rear-side frame member **82**. In the present embodiment, the rear-side frame member **82** is arranged at a downward tilt toward the rear side. Note that the front-side frame member **81** and the rear-side frame member **82** may have the same tilt angle. In this case, no bend portion **80A** is formed.

(109) As illustrated in FIGS. **12** and **13**, inside the rear-side frame member **82**, a first partition wall portion **82a** for partitioning the inner space into an upper path and a lower path is provided extending in the vehicle width direction and the front-rear direction. In addition, inside the rear-side frame member **82**, a second partition wall portion **82b** for separating a left path on the vehicle-width-direction left side from a right path on the vehicle-width-direction right side is provided

extending in the up-down direction and the front-rear direction. The first partition wall portion **82a** and the second partition wall portion **82b** are integrally formed. Four paths, namely, an upper-left path **T11**, an upper-right path **T12**, a lower-left path **T13**, and a lower-right path **T14** are formed inside the rear-side frame member **82** by the first partition wall portion **82a** and the second partition wall portion **82b**. The first partition wall portion **82a** and the second partition wall portion **82b** function as ribs provided inside the center frame **80**. Note that the first partition wall portion **82a** and the second partition wall portion **82b** may be provided as necessary, and one or both thereof may be omitted. Three partition wall portions or more may be provided.

(110) Inside the front-side frame member **81**, similarly to the inside of the rear-side frame member **82**, a first partition wall portion **81a** is provided extending in the vehicle width direction and the front-rear direction, and an inner space of the front-side frame member **81** is divided into an upper path and a lower path by the first partition wall portion **81a**. In addition, a second partition wall portion **81b** separates a left path on the vehicle-width-direction left side from a right path on the vehicle-width-direction right side is provided inside the front-side frame member **81**. Similarly to the rear-side frame member **82**, an upper-left path **T11**, an upper-right path **T12**, a lower-left path **T13**, and a lower-right path **T14** are formed inside the front-side frame member **81** by the first partition wall portion **81a** and the second partition wall portion **81b**.

(111) As illustrated in FIGS. **14** to **16**, the connection member **83** has a tubular shape connecting the rear portion of the front-side frame member **81** and the front portion of the rear-side frame member **82** to allow communication therebetween, and the rear portion of the front-side frame member **81** and the front portion of the rear-side frame member **82** are connected in a state of being inserted in the connection member **83**. Specifically, the connection member **83** includes an upper wall portion **83a** and a lower wall portion **83b** extending in the right-left direction and a left wall portion **83c** and a right wall portion **83d** extending in the up-down direction. The upper wall portion **83a** extends from an upper portion of the left wall portion **83c** to an upper portion of the right wall portion **83d**, and the lower wall portion **83b** extends from a lower portion of the left wall portion **83c** to a lower portion of the right wall portion **83d**. The dimension of the lower wall portion **83b** of the connection member **83** in the front-rear direction is set to be longer than the dimension of the upper wall portion **83a** in the front-rear direction. The dimensions of the left wall portion **83c** and the right wall portion **83d** in the front-rear direction are longer at a lower position in accordance with the difference between the dimensions of the upper wall portion **83a** and the lower wall portion **83b** in the front-rear direction.

(112) A first connection wall portion **83e** extending in the right-left direction from an up-down direction intermediate portion of the left wall portion **83c** to an up-down direction intermediate portion of the right wall portion **83d** and a second connection wall portion **83f** extending from a right-left direction intermediate portion of the upper wall portion **83a** to a right-left direction intermediate portion of the lower wall portion **83b** are provided inside the connection member **83**. The first connection wall portion **83e** and the second connection wall portion **83f** are integrally formed with the upper wall portion **83a**, the lower wall portion **83b**, the left wall portion **83c**, and the right wall portion **83d**.

(113) A front-side cutout portion **83g** into which the rear portion of the front-side frame member **81** is inserted is formed on the front side of the second connection wall portion **83f**. A rear-side cutout portion **83h** into which the front portion of the rear-side frame member **82** is inserted is formed on the rear side of the second connection wall portion **83f**. When the front-side frame member **81** and the rear-side frame member **82** are connected to each other through the connection member **83**, the upper-left path **T11**, the upper-right path **T12**, the lower-left path **T13**, and the lower-right path **T14** of the front-side frame member **81** communicate with the upper-left path **T11**, the upper-right path **T12**, the lower-left path **T13**, and the lower-right path **T14**, respectively, of the rear-side frame member **82**.

(114) The bend portion **80A** may be provided without the connection member **83**. In this case, the

bend portion **80A** of the center frame **80** can be formed through bending fabrication of the center frame **80**. For example, the bending fabrication may be simultaneously provided when the center frame **80** is fabricated by extrusion, or the bending fabrication may be provided after the extrusion fabrication.

(115) As illustrated in FIG. **17**, the upper-portion structural body **3** includes an air-conditioning device **120** that generates air-conditioned air to be sent to the occupant space **R1**. The air-conditioning device **120** is disposed on the front side of a front portion of the front-side frame member **81** and positioned on the front side of the center frame **80**. The air-conditioning device **120** will be described later in detail.

(116) As illustrated in FIG. **20**, the center frame **80** includes a left-side frame member **84A** and a right-side frame member **84B** constituting the front portion of the center frame **80**, and accordingly, the front portion of the center frame **80** has a shape bifurcated in the right-left direction. The left-side frame member **84A** and the right-side frame member **84B** are provided at an interval from each other in the right-left direction. A rear portion of the left-side frame member **84A** is fixed to a left-side surface of a front-rear direction intermediate portion of the front-side frame member **81**. The left-side frame member **84A** is tilted from a fixation part to the front-side frame member **81** toward the front side in a plan view such that the left-side frame member **84A** is positioned farther on the left side at a position farther on the front side. A front portion of the left-side frame member **84A** is connected to a part of the dash panel **50** higher than and away from the occupant-space-side floor panel **41**. A rear portion of the left-side front frame **54A** is connected to the front portion of the left-side frame member **84A**. Specifically, as illustrated in FIG. **20**, the rear portion of the left-side front frame **54A** includes a left-side connection portion **54a**. The left-side connection portion **54a** is a member for connecting the left-side front frame **54A** to the front portion of the left-side frame member **84A** and is fixed to the dash panel **50**. A front portion of the left-side front frame **54A** extends to the left-side front-wheel suspension support member **51A** and is fixed to the left-side front-wheel suspension support member **51A**.

(117) A rear portion of the right-side frame member **84B** is fixed to a right-side surface of the front-rear direction intermediate portion of the front-side frame member **81**. The right-side frame member **84B** is tilted from a fixation part to the front-side frame member **81** toward the front side in a plan view such that the right-side frame member **84B** is positioned farther on the right side at a position farther on the front side. A front portion of the right-side frame member **84B** is connected to the part of the dash panel **50** higher than and away from the occupant-space-side floor panel **41**. A rear portion of the right-side front frame **54B** (illustrated in FIG. **4**) is connected to the front portion of the right-side frame member **84B**. Specifically, the rear portion of the right-side front frame **54B** includes a right-side connection portion **54b** as illustrated in FIG. **20**. The right-side connection portion **54b** is a member for connecting the right-side front frame **54B** to the front portion of the right-side frame member **84B** and is fixed to the dash panel **50**. A front portion of the right-side front frame **54B** extends to the right-side front-wheel suspension support member **51B** and is fixed to the right-side front-wheel suspension support member **51B**.

(118) The upper-portion structural body **3** includes a plurality of connecting members **101** to **103**. The connecting members **101** to **103** are members for connecting the center frame **80** to the occupant-space-side floor panel **41**, each member extending upward from the occupant-space-side floor panel **41** and having an upper portion fixed to the center frame **80**. The connecting members **101** to **103** include the first connecting member **101**, the second connecting member **102**, and the third connecting member **103** and are each formed of, for example, an extruded material. The number of connecting members **101** to **103** is not limited to plurality but may be one.

(119) Among the first to third connecting members **101** to **103**, the first connecting member **101** is disposed farthest on the front side in the occupant space **R1**, and the first connecting member **101** is separated on the rear side from the dash panel **50**. A lower portion of the first connecting member **101** is fixed to a site separated on the rear side from the dash panel **50** on the occupant-space-side

floor panel **41**, and an upper portion of the first connecting member **101** is fixed to a site separated on the rear side from the dash panel **50** of the center frame **80**. Accordingly, a closed cross-section structure is constituted in a side view by the center frame **80**, the first connecting member **101**, the occupant-space-side floor panel **41**, and the dash panel **50**. Specifically, the center frame **80**, the first connecting member **101**, the occupant-space-side floor panel **41**, and the dash panel **50** are connected to form an annular structure.

(120) As illustrated in, for example, FIG. **3**, the second connecting member **102** is separately disposed on the rear side of the first connecting member **101**. The lower portion of the first connecting member **101** and a lower portion of the second connecting member **102** are fixed to sites separated from each other in the front-rear direction on the occupant-space-side floor panel **41**. The upper portion of the first connecting member **101** and an upper portion of the second connecting member **102** are fixed to sites separated from each other in the front-rear direction of the center frame **80**. Accordingly, a closed cross-section structure is constituted in a side view by the center frame **80**, the first connecting member **101**, the occupant-space-side floor panel **41**, and the second connecting member **102**. The third connecting member **103** is separately disposed on the rear side of the second connecting member **102**.

(121) As illustrated in FIG. **20**, the first connecting member **101** includes a left-side member (left-side connecting member) **101A** and a right-side member (right-side connecting member) **101B**. Lower portions of the left-side member **101A** and the right-side member **101B** are fixed to the front-portion cross member **44A** but may be directly fixed to a body part of the occupant-space-side floor panel **41**. The left-side member **101A** extends at a tilt in a front view such that the left-side member **101A** is positioned farther on the left side at a position farther on the upper side from the front-portion cross member **44A**. An upper portion of the left-side member **101A** is fixed to the front portion of the left-side frame member **84A** of the center frame **80**. The upper portion of the left-side member **101A** may be fixed to the left-side connection portion **54a**. In this case, the left-side member **101A** connects the left-side connection portion **54a** and the occupant-space-side floor panel **41**.

(122) The right-side member **101B** extends at a tilt in a front view such that the right-side member **101B** is positioned farther on the right side at a position farther on the upper side from the front-portion cross member **44A**. An upper portion of the right-side member **101B** is fixed to the front portion of the right-side frame member **84B** of the center frame **80**. The upper portion of the right-side member **101B** may be fixed to the right-side connection portion **54b**. In this case, the right-side member **101B** connects the right-side connection portion **54b** and the occupant-space-side floor panel **41**. Since the front portion of the left-side frame member **84A** and the front portion of the right-side frame member **84B** are separated from each other in the right-left direction, most parts of the left-side member **101A** and the right-side member **101B** except for the lower portions thereof are separated from each other in the right-left direction, and accordingly, the interval between the left-side member **101A** and the right-side member **101B** in the right-left direction is larger at a position farther on the upper side.

(123) The first connecting member **101** may connect the rear portion of the left-side front frame **54A** to the occupant-space-side floor panel **41**. In this case, the upper portion of the left-side member **101A** of the first connecting member **101** is fixed to the rear portion of the left-side front frame **54A**, and the lower portion of the left-side member **101A** is fixed to the occupant-space-side floor panel **41**. The first connecting member **101** may connect the rear portion of the right-side front frame **54B** to the occupant-space-side floor panel **41**. In this case, the upper portion of the right-side member **101B** of the first connecting member **101** is fixed to the rear portion of the right-side front frame **54B**, and the lower portion of the right-side member **101B** is fixed to the occupant-space-side floor panel **41**.

(124) The dimension of the second connecting member **102** in the right-left direction is set to be longer than the dimension thereof in the front-rear direction and equal to or smaller than the

dimension of the center frame **80** in the right-left direction. Accordingly, right and left sides of the second connecting member **102** do not protrude from the center frame **80** in the right-left direction. A cross-section of the second connecting member **102** is set to be larger than a cross-section of the left-side member **101A** or the right-side member **101B**.

(125) The lower portion of the second connecting member **102** is fixed between the left-side seat rails **90** and the right-side seat rails **91** at the front-portion common bracket **45** included in the intermediate cross member **44B**. Specifically, the lower portion of the second connecting member **102** is fixed in a state of being inserted in the central fixation portion **45a** provided at the right-left direction central portion of the front-portion common bracket **45**. Thus, the common bracket **45** to which the left-side seat rails **90** and the right-side seat rails **91** are attached becomes a member having a high strength, and in addition, the dimension thereof in the vehicle width direction is long to some extent, and accordingly, a large range of fixation to a body part of the cross member **44B** is obtained and fixation strength increases. When the lower portion of the second connecting member **102** is fixed to the common bracket **45** having a high strength and a high fixation strength in this manner, the strength of connection of the center frame **80** by the second connecting member **102** is further increased. Note that the lower portion of the second connecting member **102** may be directly fixed to the body part of the occupant-space-side floor panel **41** or may be directly fixed to the intermediate cross member **44B**.

(126) The upper portion of the second connecting member **102** is fixed to the bend portion **80A** of the center frame **80**. Specifically, the upper portion of the second connecting member **102** is fixed to the lower wall portion **83b** of the connection member **83**. Accordingly, the second connecting member **102** extends from the bend portion **80A** of the center frame **80** toward the occupant-space-side floor panel **41**. Since the dimension of the lower wall portion **83b** of the connection member **83** in the front-rear direction is longer than the dimension of the upper wall portion **83a** in the front-rear direction, a large area of joint to the second connecting member **102** is obtained. When the connection member **83** is omitted, the upper portion of the second connecting member **102** may be directly fixed to the center frame **80**.

(127) Similarly to the second connecting member **102**, the third connecting member **103** has a cross-section that is long in the right-left direction. A lower portion of the third connecting member **103** is fixed to the recessed-portion front-side cross member **44C**. An upper portion of the third connecting member **103** is fixed to the lower wall portion of the rear-side frame member **82** of the center frame **80**. As illustrated in FIG. **8** as well, the third connecting member **103** is also fixed to the front portion of the floor frame **41c**.

(128) As illustrated in FIG. **4**, the rear portion of the center frame **80** is connected to the connection panel **43** and the rear-portion cross member **44E**. Specifically, a rear-portion connecting member **104** is fixed to the rear portion of the center frame **80**, and a right-left direction central portion of the rear-portion cross member **44E** is fixed to a lower portion of the rear-portion connecting member **104**. The rear portion of the center frame **80** and the rear-portion cross member **44E** are connected to each other through the rear-portion connecting member **104**.

(129) The rear side of the rear-portion connecting member **104** is fixed to the connection panel **43**. Accordingly, the rear portion of the center frame **80** is also connected to the connection panel **43** through the rear-portion connecting member **104**. The lower portion of the rear-portion connecting member **104** is also fixed to the rear portion of the occupant-space-side floor panel **41**. In other words, the dash panel **50** and the connection panel **43** are connected to each other through the center frame **80**. In this case, since the center frame **80** is positioned higher than and away from the occupant-space-side floor panel **41**, the occupant-space-side floor panel **41**, the dash panel **50**, the connection panel **43**, and the center frame **80** integrate and constitute a closed cross-section structure in a side view. Accordingly, the distortion stiffness of the vehicle body is sufficiently improved although the occupant-space-side floor panel **41** of a floor tunnel-less structure is included.

(130) In addition, the front portion of the left-side rear frame **111A** and the front portion of the right-side rear frame **111B** are fixed to the lower portion of the rear-portion connecting member **104**. Thus, the rear portion of the center frame **80** and the left-side rear-wheel suspension support member **110A** are connected to each other through the left-side rear frame **111A**, and the rear portion of the center frame **80** and the right-side rear-wheel suspension support member **110B** are connected to each other through the right-side rear frame **111B**. Accordingly, the stiffness of the rear-wheel suspension support members **110A** and **110B** can be increased, which improves maneuvering stability of the vehicle. In addition, the stiffness of the vehicle rear side including the connection panel **43** and the vicinity thereof is increased as well.

(131) FIGS. **18** and **19** are diagrams illustrating a case in which the tilt angle of the center frame **80** is large. In this example, the rear portion of the center frame **80** is connected to the rear portion of the floor frame **41c**. The center frame **80** has a straight shape including no bend portion, but a bend portion may be formed. The rear portion of the center frame **80** is arranged at a lower position than a vehicle front portion of the seat cushion of each rear seat RS. Accordingly, the rear portion of the center frame **80** is unlikely to interfere with passengers on the rear seats RS, and thus degradation of comfort of the rear-seat passengers is avoided. The rear portion of the center frame **80** is also fixed to the occupant-space-side floor panel **41**.

(132) In the example illustrated in FIG. **19**, the rear portion of the center frame **80** is also connected to a front portion of the rear reinforcement member **47**. In this example, since the recessed-portion rear-side cross member **44D** is provided at the rear portion of the recessed portion **41a**, the recessed portion **41a** and the vicinity thereof are reinforced by the recessed-portion rear-side cross member **44D**. The recessed portion **41a** and the vicinity thereof are also reinforced by the floor frame **41c**. In addition, since the center frame **80** positioned higher than and away from the occupant-space-side floor panel **41** is connected to the floor frame **41c**, the distortion stiffness of the vehicle body is sufficiently improved.

(133) As illustrated in FIG. **5**, the traveling motor M included in the rear-side powertrain PT is supported to each rear support frame **30** through the non-illustrated mounting member or the like and is disposed on the vehicle rear side of the rear portion of the center frame **80**. The height of the rear-side traveling motor M can optionally set in accordance with the height of attachment to each rear support frame **30**. In the present embodiment, the height of the rear-side traveling motor M is set such that the height of at least part of the range from an upper portion of the rear-side traveling motor M to a lower portion thereof is equal to the height of the rear portion of the center frame **80**. In addition, the height of a rotation center of the rear-side traveling motor M, in other words, the height of an up-down direction central portion of the traveling motor M is set to be lower than that of the rear portion of the center frame **80**. Since the rear-side powertrain PT is arranged in this manner, for example, a load toward the vehicle front side is applied to the rear portion of the center frame **80** when an impact load applied from the vehicle rear side is input to the traveling motor M and the traveling motor M is about to move toward the vehicle front side. In this case, since the rear portion of the center frame **80** is connected to the rear-portion cross member **44E**, the connection panel **43**, and the like and integrated with the occupant-space-side floor panel **41**, the movement of the traveling motor M toward the front side is prevented by the center frame **80**. The movement of the traveling motor M toward the front side is also prevented by the occupant-space-side floor panel **41** and the rear-portion cross member **44E**.

(134) Subsequently, a layout of the front-side powertrain PT will be described below based on FIG. **17**. The front-side powertrain PT is supported to each front support frame **20** through the non-illustrated mounting member or the like. The height of the front-side traveling motor M can be optionally set in accordance with the height of attachment to each front support frame **20**. The front-side powertrain PT is arranged on the front side of the first connecting member **101**. At least part of the air-conditioning device **120** is arranged between the first connecting member **101** and the powertrain PT.

(135) The air-conditioning device **120** includes a cooler (heat exchanger) **121** through which air-conditioned air passes, and an air conditioning casing **122** in which the cooler **121** is housed. The cooler **121** is a cooling heat exchanger including, for example, an evaporator for cooling air-conditioned air. The cooler **121** is not limited thereto, but a heating heat exchanger including a heater core or condenser that heats air-conditioned air may be used in place of the cooler **121**, and a cooler may be disposed at another part. The cooler **121** of the present embodiment is disposed on the front side of the dash panel **50**. Note that a compressor that compresses a coolant, an expansion valve that depressurizes the coolant, and the like constitute part of the air-conditioning device **120**.

(136) An up-down direction central portion of the cooler **121** is arranged at a higher position than a rotation center of the front-side traveling motor M. Specifically, for example, when the automobile **1** collides on the front side and an impact load toward the rear side is applied to the powertrain PT, the powertrain PT starts retracting depending on the magnitude of the impact load. Since the front-side powertrain PT is arranged as described above, the center frame **80** extending in the front-rear direction is arranged on the rear side of the powertrain PT in a state of being connected to the occupant-space-side floor panel **41** through the connecting members **101** to **103**. Accordingly, the retraction of the powertrain PT is suppressed by the center frame **80** and the connecting members **101** to **103**. Since the occupant-space-side floor panel **41** is also positioned on the rear side of the powertrain PT, the retraction of the powertrain PT is suppressed by the occupant-space-side floor panel **41** as well in some cases.

(137) Subsequently, a specific exemplary configuration of the air-conditioning device **120** will be described below. In addition to the above-described cooler **121**, a non-illustrated heater, an air mix damper **122a** for generating air-conditioned air at a desired temperature by changing the mixed ratio of cool air having passed through the cooler **121** and warm air having passed through the heater, and a vent direction switching damper **122b** for distributing the generated air-conditioned air at the desired temperature to each component of a vehicle cabin are housed inside the air conditioning casing **122** of the air-conditioning device **120**. Through operation of the vent direction switching dampers **122b**, the air-conditioned air can be supplied to the inner surface of a front window glass FG (illustrated in FIG. **1**), supplied to the upper body of a passenger, and supplied to the vicinity of the feet of a passenger. The operation of the vent direction switching damper **122b** has been conventionally well known.

(138) A front-side part of the air conditioning casing **122** is a part in which the cooler **121** and the air mix damper **122a** are housed, and is arranged on the front side of the dash panel **50**. A rear-side part of the air conditioning casing **122** is a part in which the vent direction switching damper **122b** is housed, and is arranged in the occupant space R1 through the dash panel **50**. Accordingly, the cooler **121** and the air mix damper **122a** are positioned closer to the powertrain PT than the vent direction switching damper **122b**. Note that the front-side part of the air conditioning casing **122** may be arranged on the rear side of the dash panel **50**.

(139) The rear-side part of the air conditioning casing **122** includes a vent portion **122c** having a duct shape through which the air-conditioned air generated inside the air conditioning casing **122** is vented out. The air conditioning casing **122** also includes an air introducing duct **122d** that provides communication between the vent portion **122c** and the inside of the center frame **80** and through which the air-conditioned air vented out of the vent portion **122c** is introduced to the inside of the center frame **80**. The air introducing duct **122d** is arranged at a higher position than a control device **130** to be described later and extends in the front-rear direction. A front portion of the air introducing duct **122d** is connected to the vent portion **122c**, and a rear portion of the air introducing duct **122d** is connected to the front portion of the front-side frame member **81** of the center frame **80**. Accordingly, the air-conditioned air generated by the air-conditioning device **120** is introduced to the inside of the center frame **80** through the air introducing duct **122d**. The air introducing duct **122d** may be a member that constitutes part of the center frame **80**.

(140) Since the center frame **80** extends in the front-rear direction, the air-conditioned air can be

guided to a desired place in the front-rear direction in the occupant space R1. In this case, since the air introducing duct **122d** is arranged at a higher position than the control device **130** and has a predetermined width in the right-left direction, direct sunlight is interrupted by the air introducing duct **122d** as well and further unlikely to reach the control device **130**. Moreover, since the center frame **80** is used as an air conditioning duct, an air conditioning duct does not need to be redundantly provided and the occupant space R1 can be enlarged as compared to a case in which an air conditioning duct is redundantly provided.

(141) As illustrated in FIG. 20, upper-side air sending portions **80b** for sending the air-conditioned air in the upper-left path T11 and the upper-right path T12 upward is provided at parts separated on the rear side from the air introducing duct **122d** at an upper wall portion of the center frame **80**. The upper-side air sending portions **80b** are positioned on the rear side of backrest portions of the front seats FS at the upper wall portion of the center frame **80** and provided on the right and left sides, respectively. The left-side upper-side air sending portion (left-side air sending portion) **80b** has a tubular shape that communicates with the inside of the upper-left path T11, and the right-side upper-side air sending portion (right-side air sending portion) **80b** has a tubular shape that communicates with the inside of the upper-right path T12. Downstream ends of the upper-side air sending portions **80b** are opened upward to face passengers sitting on the rear seats RS.

(142) As illustrated in FIG. 5, lower-side air sending portions **80c** for sending the air-conditioned air in the lower-left path T13 and the lower-right path T14 downward are provided at parts separated on the rear side from the air introducing duct **122d** at a lower wall portion of the center frame **80**. The lower-side air sending portions **80c** are positioned on the rear side of seat cushion portions of the front seats FS and provided on the right and left sides, respectively, of the lower wall portion of the center frame **80**. The left-side lower-side air sending portion **80c** has a tubular shape that communicates with the inside of the lower-left path T13, and the right-side lower-side air sending portion **80c** has a tubular shape that communicates with the inside of the lower-right path T14. Each lower-side air sending portion **80c** is constituted by a rear under-feet duct extending downward toward the recessed portion **41a**, and extending downward from the center frame **80** and then bending toward a vehicle-width-direction outer side. The rear under-feet duct may be referred to as a rear heat duct.

(143) Since the center frame **80** has a cross-section that is large enough to improve the distortion stiffness of the vehicle body, air sending noise can be maintained low when the amount of the air-conditioned air circulating inside the center frame **80** is increased. In particular, since the center frame **80** extends in a substantially straight shape, a path inside the center frame **80** has a substantially straight shape as well, and air sending noise can be maintained low for this reason as well. When the center frame **80** includes no heat insulation material nor the like, heat of the air-conditioned air circulating inside the center frame **80** is transferred to a wall portion of the center frame **80** and radiated from the outer surface of the wall portion to the occupant space R1. Accordingly, it is possible to perform desirable air conditioning by using radiation heat. Note that the center frame **80** may include a heat insulation material.

(144) (Layout of Control Device)

(145) The vehicle-body structure A includes the control device **130** (illustrated in, for example, FIGS. 9, 17, and 23) that controls control target units mounted on the automobile 1. Examples of the control target units include the powertrains PT, a brake device, an electric control suspension device, a lighting device, a navigation device, a head-up display device, an audio device, an in-vehicle monitor, and a television. The control device **130** that controls these control target units includes a high-performance CPU, a memory, and the like, and thus has an increased size and is weak against high heat and also weak against impact. For example, a water jacket through which cooling water circulates is provided as a heat generation measure in the control device **130**. An in-vehicle entertainment function (moving image playback function or music playback function) or the like is mounted in some cases, and in such a case as well, the size of the control device **130**

increases.

(146) The control device **130** of the present embodiment is arranged at a lower position than the front portion of the center frame **80** in the occupant space **R1**. As described above, since the height of the front portion of the center frame **80** is higher than the rear portion of the center frame **80**, the control device **130** having a large size can be arranged. As illustrated with a virtual line in FIG. **17**, an instrument panel **IP** to which meters and gauges are attached is arranged at a higher position than the front portion of the center frame **80**. The instrument panel **IP** extends in the right-left direction from the left side of the occupant space **R1** to the right side thereof. A front portion of the instrument panel **IP** reaches a lower portion of the front window glass **FG** (illustrated in FIG. **1**).

(147) The left-side member **101A** and the right-side member **101B** constituting the first connecting member **101** are arranged on the front side of the control device **130**. The second connecting member **102** is arranged on the rear side of the control device **130**. Accordingly, the control device **130** is arranged between the first connecting member **101** and the second connecting member **102**, and gaps are provided between the first connecting member **101** and the control device **130** and between the second connecting member **102** and the control device **130**, respectively.

(148) Since the control device **130** is arranged at a lower position than the center frame **80** in the occupant space **R1**, for example, direct sunlight from the outside is interrupted by the center frame **80** and unlikely to reach the control device **130**. Thus, the control device **130** can be arranged at a thermally advantageous place. Moreover, since the instrument panel **IP** is arranged at a higher position than the control device **130**, direct sunlight is interrupted by the instrument panel **IP** as well and further unlikely to reach the control device **130**. Since the control device **130** is covered by the instrument panel **IP**, the control device **130** is unlikely to be viewed from the outside, which is preferable in terms of security.

(149) The air introducing duct **122d** is disposed at a higher position than the control device **130**. Heat of the air-conditioned air is transferred to a wall portion of the air introducing duct **122d** and radiated as radiation heat from the outer surface of the wall portion toward the control device **130**. In this case, since the air-conditioned air having a temperature adjusted so that the occupant space **R1** becomes comfortable flows inside the air introducing duct **122d**, the radiation heat from the air introducing duct **122d** acts on to suppress temperature increase of the control device **130**. Moreover, direct sunlight can be interrupted by the air introducing duct **122d**.

(150) For example, when a case in which an impact load is applied from the front side is assumed, at least part of the impact load is absorbed by the center frame **80** and deformation of the vehicle body in the vicinity of the center frame **80** is suppressed since the center frame **80** extends in the front-rear direction. Accordingly, the control device **130** arranged at a lower position than the center frame **80** is protected against the impact load from the front side. This is same for an impact load from the rear side. In particular, at least two places of the center frame **80** can be solidly connected to the occupant-space-side floor panel **41** through the left-side member **101A** and the right-side member **101B**, and thus protection performance of the control device **130** can be increased.

(151) When a case in which an impact load is applied from a side of the vehicle is assumed, the impact load from a side is unlikely to be directly conveyed to the control device **130** since the control device **130** is arranged corresponding to the vehicle width direction central portion, and thus the control device **130** is protected against the impact load from a side as well. In addition, since the control device **130** is arranged between the first connecting member **101** and the second connecting member **102**, an impact load in the front-rear direction is unlikely to be applied to the control device **130** and the protection performance further improves.

(152) (Cooling Path)

(153) Subsequently, a cooling path will be described below. FIG. **21** is a diagram illustrating a schematic structure of a cooling path provided in the automobile **1**. The cooler **121** can be constituted by, for example, a cooling heat exchanger of the air-conditioning device **120**, but is not

limited thereto and may be a dedicated cooler provided separately from the air-conditioning device **120**. A path of cooling water as a heat exchange medium is formed in the cooler **121**, and the cooling water circulating through the path is cooled through heat exchange with a low-temperature coolant inside the cooler **121**. The vehicle-body structure A includes a supply pipe **131** for supplying the cooling water cooled by the cooler **121** to the water jacket included in the control device **130**, and a discharge pipe **132** for discharging the cooling water supplied to the control device **130**. The supply pipe **131** is provided with a pump P for transferring the cooling water to the control device **130**. The cooling water discharged from the discharge pipe **132** is cooled through the cooler **121** and then taken into the pump P. The control device **130** is cooled as the cooling water is circulated in this manner. The cooling water having cooled the control device **130** is used to cool the batteries FB and RB, used to cool the traveling motor M, and then returned to the cooler **121**. Note that a coolant may be used in place of the cooling water.

(154) As illustrated in FIG. **17**, the cooler **121** is disposed on the rear side of the front-side powertrain PT and positioned close to the dash panel **50**. Accordingly, the cooler **121** is positioned closer to the control device **130** than the front-side powertrain PT. Thus, the length of the supply pipe **131** can be short and a pipe path is simple, which leads to reduction of a pressure loss when the cooling water is supplied to the control device **130** and also leads to reduction of a cold loss between the cooler **121** and the control device **130**, and accordingly, the control device **130** can be efficiently cooled.

(155) As illustrated in FIG. **22**, the supply pipe **131** and the discharge pipe **132** extend through the dash panel **50** and are disposed between the left-side member **101A** and the right-side member **101B**. Since the supply pipe **131** and the discharge pipe **132** are disposed between the left-side member **101A** and the right-side member **101B**, the supply pipe **131** and the discharge pipe **132** are unlikely to be hit by the feet of a passenger or the like, and damage on the supply pipe **131** and the discharge pipe **132** is suppressed. The supply pipe **131** and the discharge pipe **132** extend in the front-rear direction below the air-conditioning device **120**.

(156) (Working Effects of Embodiment)

(157) As described above, according to the present embodiment, since the control device **130** is arranged at a lower position than the center frame **80** in the occupant space R1, for example, direct sunlight from the outside is interrupted by the center frame **80** and unlikely to reach the control device **130**. Thus, the control device **130** can be arranged at a thermally advantageous place.

(158) For example, when a case in which an impact load is applied from the vehicle front side is assumed, at least part of the impact load is absorbed by the center frame **80** and deformation of the vehicle body in the vicinity of the center frame **80** is suppressed since the center frame **80** extends in the front-rear direction. Accordingly, the control device **130** arranged at a lower position than the center frame **80** is protected against the impact load from the front side. This is same for an impact load from the vehicle rear side.

(159) When a case in which an impact load is applied from a side of the vehicle is assumed, the impact load from a side is unlikely to be directly conveyed to the control device **130** since the control device **130** is arranged corresponding to the vehicle width direction central portion, and thus the control device **130** is protected against the impact load from a side as well.

(160) The above-described embodiment is merely exemplary in any aspects and not to be interpreted in a restrictive manner. Furthermore, modifications and changes belonging to a scope equivalent to the claims are all included in the scope of the present disclosure.

INDUSTRIAL APPLICABILITY

(161) As described above, the present disclosure is applicable as, for example, a vehicle-body structure of an electric vehicle.

(162) The present disclosure is not limited to only the above-described embodiments, which are merely exemplary. It will be appreciated by those skilled in the art that the disclosed systems and/or methods can be embodied in other specific forms without departing from the spirit of the disclosure

or essential characteristics thereof. The presently disclosed embodiments are therefore considered to be illustrative and not restrictive. The disclosure is not exhaustive and should not be interpreted as limiting the claimed invention to the specific disclosed embodiments. In view of the present disclosure, one of skill in the art will understand that modifications and variations are possible in light of the above teachings or may be acquired from practicing of the disclosure.

(163) Reference to an element in the singular is not intended to mean “one and only one” unless explicitly so stated, but rather “one or more.” Moreover, where a phrase similar to “at least one of A, B, or C” is used in the claims, it is intended that the phrase be interpreted to mean that A alone may be present in an embodiment, B alone may be present in an embodiment, C alone may be present in an embodiment, or that any combination of the elements A, B and C may be present in a single embodiment; for example, A and B, A and C, B and C, or A and B and C.

(164) No claim element herein is to be construed under the provisions of 35 U.S.C. 112(f) unless the element is expressly recited using the phrase “means for.” As used herein, the terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

(165) The scope of the invention is indicated by the appended claims, rather than the foregoing description.

REFERENCE SIGNS LIST

(166) **1** automobile **41** occupant-space-side floor panel **43** connection panel **44A** front-portion cross member **50** dash panel **80** center frame **101** first connecting member **102** second connecting member **130** control device A vehicle-body structure **R1** occupant space **R3** trunk space

Claims

1. A vehicle-body structure provided in an automobile, the vehicle-body structure comprising: a floor panel constituting a floor of an occupant space including a seat on which a passenger sits; a center frame disposed to be higher than and away from the floor panel at a vehicle-width-direction central portion of the occupant space and extending in a vehicle front-rear direction; a controller that is configured to control a control target structure mounted on the automobile; and a connecting structure extending upward from the floor panel, having an upper portion fixed to the center frame, and connecting the center frame to the floor panel, wherein the controller is arranged at a lower position than a front portion of the center frame, the connecting structure includes a first connecting structure and a second connecting structure, the first connecting structure being provided on a vehicle front side of the controller, and the second connecting structure being provided on a vehicle rear side of the controller, the floor panel includes a cross structure extending in a vehicle width direction such that the cross structure intersects with the center frame in a plan view in the occupant space, the cross structure includes a front-portion cross structure and an intermediate cross structure, and the first connecting structure and the second connecting structure extend upward from the front-portion cross structure and the intermediate cross structure respectively, the first connecting structure and the second structure each have the upper portion fixed to the center frame, and connect the center frame to the front-portion cross structure and the intermediate cross structure respectively.

2. The vehicle-body structure according to claim 1, comprising: an air-conditioner provided on a vehicle front side of the center frame; and an air introducing duct that provides communication between a vent portion provided to the air-conditioner and inside of the center frame formed in a hollow shape and through which air-conditioned air vented out of the vent portion is introduced into the center frame, wherein the air introducing duct is arranged at a higher position than the controller.

3. The vehicle-body structure according to claim 2, wherein an instrument panel is arranged at a higher position than a front portion of the center frame.
 4. The vehicle-body structure according to claim 1, further comprising a dash panel extending upward from a front portion of the floor panel and partitioning a vehicle front portion of the occupant space, wherein the front portion of the center frame is connected to the dash panel.
 5. The vehicle-body structure according to claim 1, wherein an instrument panel is arranged at a higher position than the front portion of the center frame.
 6. The vehicle-body structure according to claim 2, wherein the air-conditioner is closer to the controller than a powertrain mounted on the automobile.
 7. The vehicle-body structure according to claim 1, wherein the center frame includes a left-side frame structure and a right-side frame structure constituting the front portion of the center frame, and the left-side frame structure and the right-side frame structure are provided at an interval from each other in the right-left direction.
 8. The vehicle-body structure according to claim 2, wherein the air introducing duct is a structure that constitutes part of the center frame.
 9. The vehicle-body structure according to claim 2, wherein the center frame includes a front-side frame structure extending in the front-rear direction, a rear-side frame structure disposed on the vehicle rear side of the front-side frame structure and extending toward the rear side, and a connection structure connecting a rear portion of the front-side frame structure and a front portion of the rear-side frame structure.
 10. The vehicle-body structure according to claim 9, wherein a front portion of the air introducing duct is connected to the vent portion, and a rear portion of the air introducing duct is connected to the front portion of the front-side frame structure of the center frame.
 11. The vehicle-body structure according to claim 9, wherein the front-side frame structure is tilted at a first tilt angle relative to a horizontal plane and extends straight, and the rear-side frame structure is tilted at a second tilt angle smaller than the first tilt angle relative to the horizontal plane and extends straight.
 12. The vehicle-body structure according to claim 9, wherein the front-side frame structure is positioned higher than the rear-side frame structure relative to the floor panel.
 13. The vehicle-body structure according to claim 10, wherein the air-conditioner is disposed on a front side of a front portion of the front-side frame structure.
 14. An automobile comprising the vehicle-body structure according to claim 1.
 15. The automobile of claim 14, wherein the automobile is an electric vehicle.
-