

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415724
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Tjärnehov; Emil Andreas et al.

Method for the preparation of synthesis gas

Abstract

Method for the preparation of synthesis gas combining electrolysis of water, tubular steam reforming and autothermal reforming of a hydrocarbon feed stock in parallel.

Inventors:	Tjärnehov; Emil Andreas (Limhamn, SE), Han; Pat A. (Smørum, DK)
Applicant:	Topsoe A/S (Kgs. Lyngby, DK)
Family ID:	1000008821389
Assignee:	Topsoe A/S (Kgs. Lyngby, DK)
Appl. No.:	17/800165
Filed (or PCT Filed):	February 24, 2021
PCT No.:	PCT/EP2021/054520
PCT Pub. No.:	WO2021/170628
PCT Pub. Date:	September 02, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230109188 A1	Apr. 06, 2023

Foreign Application Priority Data

DK	PA 2020 00259	Feb. 28, 2020
----	---------------	---------------

Publication Classification

Int. Cl.: C01B3/38 (20060101); C07C29/151 (20060101); C25B1/04 (20210101)

U.S. Cl.:

CPC **C01B3/382** (20130101); **C07C29/1518** (20130101); C01B2203/0233 (20130101);
C01B2203/0244 (20130101); C01B2203/061 (20130101); C01B2203/0833 (20130101);
C01B2203/1241 (20130101); C25B1/04 (20130101)

Field of Classification Search

CPC: C25B (1/04); C25B (1/042); C01B (3/382); C01B (29/1518); C01B (2203/0233); C01B
(2203/0244); C01B (2203/061); C01B (2203/0833); C01B (2203/1241); C01B
(2203/1276)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0184082	12/2014	Iijima	585/324	C10L 1/06
2017/0002281	12/2016	Aasberg-Petersen et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1 698 590	12/2005	EP	N/A
WO 2013/013895	12/2012	WO	N/A
WO 2014/209605	12/2013	WO	N/A
WO 2015/086752	12/2014	WO	N/A
WO 2019/011659	12/2018	WO	N/A
WO 2019/020376	12/2018	WO	N/A
WO 2019/020377	12/2018	WO	N/A
WO 2019/020378	12/2018	WO	N/A
WO 2019/020513	12/2018	WO	N/A
WO 2019/020515	12/2018	WO	N/A
WO 2019/020519	12/2018	WO	N/A

Primary Examiner: Parsa; Jafar F

Attorney, Agent or Firm: Blank Rome LLP

Background/Summary

(1) The present application is directed to the preparation of synthesis gas. More particular, the invention combines electrolysis of water, tubular steam reforming and autothermal reforming in parallel and optionally additionally heat exchange reforming of a hydrocarbon feed stock in the preparation of a hydrogen and carbon oxides containing synthesis gas.


(2) Preparation of synthesis gas e.g. for the methanol synthesis is typically carried out by steam reforming of hydrocarbons.

(3) The principal reaction of steam reforming is (given for methane):



(4) Similar reactions occur for other hydrocarbons. Steam reforming is normally accompanied by

the water gas shift reaction:



(5) Steam reforming is typically carried out by a combination of a tubular reformer (also called steam methane reformer, SMR) and autothermal reforming (ATR), also known as primary and secondary reforming or 2-step reforming. Alternatively, stand-alone SMR or stand-alone ATR can be used to prepare synthesis gas.

(6) The main elements of an ATR reactor are a burner, a combustion chamber, and a catalyst bed contained within a refractory lined pressure shell. In an ATR reactor, partial oxidation or combustion of a hydrocarbon feed by sub-stoichiometric amounts of oxygen is followed by steam reforming of the partially combusted hydrocarbon feed stream in a fixed bed of steam reforming catalyst. Steam reforming also takes place to some extent in the combustion chamber due to the high temperature.

(7) In 2-step reforming the steam methane reformer (SMR) must be large and a significant amount of heat is required to drive the endothermic steam reforming reaction. Hence, it is desirable if the size and duty of the steam reformer can be reduced. Furthermore, the ATR in the 2-step reforming concept requires oxygen. Today this is typically produced in a cryogenic air separation unit (ASU). The size and cost of this ASU is large. If the oxygen could be produced by other means, this would be desirable.

(8) SMR produces hydrogen in excess to what is required for a suitable methanol synthesis gas composition, while ATR produces hydrogen in less amounts.

(9) We have found that when combining tubular steam reforming and autothermal reforming in parallel together with electrolysis of water and/or steam, oxygen from the electrolysis can be used in the ATR and the expensive ASU becomes superfluous in the preparation of synthesis gas.

(10) At the same time, hydrogen from electrolysis contributes to the hydrogen required for methanol production, which will allow for addition of additional carbon dioxide to the process still resulting in a module required for methanol synthesis.

Description

(1) Thus, this invention provides a method for the preparation of synthesis gas comprising the steps of (a) providing a hydrocarbon feed stock; (b) preparing a separate hydrogen containing stream and a separate oxygen containing stream by electrolysis of water and/or steam; (c) steam reforming a first part of the hydrocarbon feed stock from step (a) in a tubular steam reformer to a tubular steam reformed gas comprising hydrogen, carbon monoxide and carbon dioxide; (d) autothermal reforming a second part of the hydrocarbon feed stock in an autothermal reformer with at least part of the oxygen containing stream obtained in step (b) to an autothermal reformed gas stream comprising hydrogen, carbon monoxide and carbon dioxide; (e) combining the steam reformed gas from step (c) with the autothermal reformed gas from step (d); (f) adding at least part of the separate hydrogen containing stream from step (b) into the hydrocarbon feed stock from step (a) and/or into the steam reformed gas stream from step (c) and/or into the autothermal reformed gas stream from step (d) and/or into the combined steam reformed gas and autothermal reformed gas stream from step (e); and (g) withdrawing the synthesis gas.

(2) Tubular steam reforming creates CO_2 in the flue gas from the burners in the tubular steam reforming. The CO_2 in the flue gas is in an embodiment of the invention recovered and added to the tubular steam reforming process.

(3) Thereby, the CO_2 footprint of the method according to the invention is advantageously lowered when the added CO_2 is utilized in the production methanol.

(4) To minimize CO_2 emissions further, a part of the feedstock can be heat exchange reformed in a heat exchange reformer downstream the tubular steam reformer and/or the tubular steam

reformed gas can be additionally heat exchange reformed to reduce fuel consumption.

(5) The electrolysis can be performed by various means known in the art such as by solid oxide based electrolysis or electrolysis by alkaline cells or polymer cells (PEM).

(6) When the power for the electrolysis is produced (at least in part) by sustainable sources, the CO₂-emissions is per unit of product produced by the method reduced.

(7) Preferably, the electrolysis of water and/or steam is powered solely by renewable energy.

(8) As already mentioned above, all the oxygen from the electrolysis unit is added to the autothermal reformer in step (d) and an ASU for the preparation of oxygen by separation of air is avoided.

(9) The method according to the invention is preferably employed for the production of methanol synthesis gas.

(10) Methanol synthesis gas has preferably a composition corresponding to a so-called module ($M = (H_2 - CO_2)/(CO + CO_2)$) of 1.90-2.20 or more preferably slightly above 2 (eg. 2.00-2.10).

(11) Thus when the method according to the invention is used in the preparation of methanol synthesis gas, the amount of hydrogen added to the feed stock upstream to the SMR or the ATR or to the reformed gas downstream step (e) can be tailored such that when the hydrogen is mixed with the synthesis gas generated by the reforming steps and the optionally CO₂ addition recovered from the tubular steam reformer a desired value of M of between 1.90 and 2.20 or preferably between 2.00 and 2.10 is achieved.

(12) In general, suitable hydrocarbon feedstocks for use in the various embodiments of the invention comprise natural gas, methane, LNG, naphtha or mixtures thereof either as such or pre-reformed and/or desulfurized.

(13) The method according to the invention can also be employed for producing synthesis gas for other applications where it is desirable to increase the hydrogen concentration in the feed gas and where the hydrogen and oxygen is favorably produced by electrolysis.

Claims

1. Method for the preparation of synthesis gas comprising the steps of: (a) providing a hydrocarbon feed stock; (b) preparing a separate hydrogen containing stream and a separate oxygen containing stream by electrolysis of water and/or steam; (c) steam reforming a first part of the hydrocarbon feed stock from step (a) in a tubular steam reformer to a tubular steam reformed gas comprising hydrogen, carbon monoxide and carbon dioxide, including recovering carbon dioxide in flue gas from burners in the tubular steam reformer and adding the recovered carbon dioxide to the steam reforming process; (d) autothermal reforming a second part of the hydrocarbon feed stock in an autothermal reformer with at least part of the oxygen containing stream obtained in step (b) to an autothermal reformed gas stream comprising hydrogen, carbon monoxide and carbon dioxide; (e) combining the steam reformed gas from step (c) with the autothermal reformed gas from step (d); (f) adding at least part of the separate hydrogen containing stream from step (b) into the hydrocarbon feed stock from step (a) and/or into the steam reformed gas stream from step (c) and/or into the autothermal reformed gas stream from step (d) and/or into the combined steam reformed gas and autothermal reformed gas stream from step (e); and (g) withdrawing the synthesis gas.

2. The method of claim 1, wherein the electrolysis of water and/or steam in step (b) is powered by renewable energy.

3. The method of claim 1, wherein the hydrogen stream is added to the combined tubular steam reformed gas and autothermal reformed gas stream in an amount to provide a module $M = (H_{2,sub} - CO_{sub,2})/(CO + CO_{sub,2})$ in the synthesis gas withdrawn in step (g) of between 1.9 and 2.2.

4. The method of claim 1, wherein the module $M = (H_{2,sub} - CO_{sub,2})/(CO + CO_{sub,2})$ in the

synthesis gas withdrawn in step (g) is in the range from 2 to 2.1.

5. The method of claim 1, comprising the further step of heat exchange reforming a part of the hydrocarbon feedstock from step (a) and/or the tubular steam reformed gas from step (c).

6. The method of claim 1, wherein the hydrocarbon feed stock comprises natural gas, methane, LNG, naphtha or mixtures thereof either as such or pre-reformed and/or desulfurized.

7. The method of claim 1, wherein the synthesis gas withdrawn in step (g) is in a further step converted to a methanol product.
