

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417512
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Oh; Dongkeun et al.

Method and apparatus for high-resolution image obtainment through artificial intelligence model

Abstract

An electronic device according to various embodiments of the disclosure may include: a camera module including a camera, a memory, and at least one processor electrically connected to the camera module and the memory, wherein the at least one processor may be configured to: successively obtain a plurality of first images through the camera module, align the plurality of first images, obtain a reference image based on the plurality of aligned first images, and obtain a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.

Inventors: Oh; Dongkeun (Suwon-si, KR), Kim; Nakhoon (Suwon-si, KR), Jeon; Hakjae (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008821486

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/884250

Filed: August 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230154132 A1	May. 18, 2023

Foreign Application Priority Data

KR	10-2021-0104654	Aug. 09, 2021
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06V10/24** (20220101); **G06T3/4053** (20240101); **G06T5/50** (20060101); **G06T5/70** (20240101); **G06T7/20** (20170101); **H04N23/69** (20230101)

U.S. Cl.:

CPC **G06T3/4053** (20130101); **G06T5/50** (20130101); **G06T5/70** (20240101); **G06T7/20** (20130101); **G06V10/24** (20220101); **H04N23/69** (20230101); G06T2207/20132 (20130101); G06T2207/20182 (20130101); G06T2207/20216 (20130101); G06T2207/30168 (20130101)

Field of Classification Search

CPC: H04N (23/69); G06T (5/70); G06T (3/4053); G06T (5/50); G06T (7/20); G06T (2207/20132); G06T (2207/20182); G06T (2207/20216); G06T (2207/30168); G06V (10/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0022642	12/2014	Appia et al.	N/A	N/A
2016/0292823	12/2015	Nagumo et al.	N/A	N/A
2016/0358314	12/2015	Ji	N/A	H04N 19/36
2020/0242515	12/2019	Reddy et al.	N/A	N/A
2020/0302576	12/2019	Xu et al.	N/A	N/A
2020/0380641	12/2019	Higaki	N/A	N/A
2021/0097646	12/2020	Choi et al.	N/A	N/A
2021/0133499	12/2020	Zhang	N/A	N/A
2021/0385383	12/2020	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106991646	12/2016	CN	N/A
109559276	12/2018	CN	N/A
2020-032072	12/2019	JP	N/A
2020-197915	12/2019	JP	N/A
10-2016-0142760	12/2015	KR	N/A
10-2019-0117416	12/2018	KR	N/A
10-2020-0048609	12/2019	KR	N/A
10-2169242	12/2019	KR	N/A
10-2021-0053121	12/2020	KR	N/A
2018/216207	12/2018	WO	N/A
2020/252764	12/2019	WO	N/A

OTHER PUBLICATIONS

Ooi, Y. K., & Ibrahim, H. (2021). Deep Learning Algorithms for Single Image Super-Resolution: A Systematic Review. *Electronics*, 10(7), 867. <https://doi.org/10.3390/electronics10070867> (Year: 2021). cited by examiner

Pan, Z., Tan, Z., & Lv, Q. (2021). A Deep Multi-Frame Super-Resolution Network for Dynamic Scenes. *Applied Sciences*, 11(7), 3285. <https://doi.org/10.3390/app11073285> (Year: 2021). cited by examiner

International Search Report mailed Nov. 4, 2022 issued in International Application No. PCT/KR2022/011711 with English translation (5 pages). cited by applicant

Written Opinion mailed Nov. 4, 2022 issued in International Application No. PCT/KR2022/011711 (4 pages). cited by applicant

Ooi, Yoong Khang et al., “Deep Learning Algorithms for Single Image Super-Resolution: A Systematic Review”, *Electronics* 2021, vol. 10, No. 7, pp. 1-33, Apr. 6, 2021. cited by applicant

Pan, Ze et al., “A Deep Multi-Frame Super-Resolution Network for Dynamic Scenes”, *Applied Sciences*. vol. 11, No. 7, pp. 1-11, Apr. 6, 2021. cited by applicant

B. Wronski et al., “Handheld Multi-Frame Super Resolution”, *ACM Transactions on Graphics*, vol. 38, No. 4, Article 28, Jul. 2019 (SIGGRAPH 2019), 73 pp. cited by applicant

Goutam Bhat et al., “Deep Burst Super-Resolution”, *Conference: 2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, Apr. 6, 2021, arXiv:2101.10997v2 [cs.CV], 15 pp. cited by applicant

Yulun Zhang et al., “Image Super-Resolution Using Very Deep Residual Channel Attention Networks”, *European Conference on Computer Vision (ECCV)*, Jul. 12, 2018, arXiv:1807.02758v2 [cs.CV], 16 pp. cited by applicant

Primary Examiner: Bella; Matthew C

Assistant Examiner: Hwang; Jinsu

Attorney, Agent or Firm: Nixon & Vanderhye P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/011711 designating the United States, filed on Aug. 5, 2022, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2021-0104654, filed on Aug. 9, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) The disclosure relates to a method for providing an image and an electronic device for supporting the same.

Description of Related Art

(2) With the release of a display having a high resolution (e.g., ultra-high definition (UHD)), interest in super-resolution techniques is increasing. The super-resolution technique is a method for converting a low-resolution image into a high-resolution image.

(3) In the super-resolution technique, a plurality of images may be used or a single image may be used. For example, the super-resolution technique includes a pixel shift method for obtaining a high-resolution image from a plurality of low-resolution images obtained by a camera while moving the camera (e.g., an image sensor) at intervals of one pixel or half a pixel and a single

image super-resolution (SISR) (also referred to as “single frame super-resolution (SFSR)”) method for obtaining one high-resolution image from one low-resolution image.

(4) The pixel shift method requires a component for moving a camera at intervals of one pixel or half a pixel from the aspect of hardware and may thus be difficult to implement in an electronic device (e.g., a smartphone). The SISR method uses one low-resolution image as an input may thus have limitation in obtaining an image having a high resolution from the one low-resolution image.

SUMMARY

(5) Embodiments of the disclosure relate to a method for providing an image and an electronic device for supporting the same, which align a plurality of images obtained through a camera of an electronic device, and obtains a high-resolution image using an artificial intelligence model, based on the plurality of aligned images and a reference image obtained from the plurality of aligned images.

(6) Technical aspects to be achieved in the disclosure are not limited to the technical aspects mentioned above, and other technical aspects not mentioned will be clearly understood by those skilled in the art from the following description.

(7) An electronic device according to various example embodiments of the disclosure may include: a camera module comprising a camera, a memory, and at least one processor electrically connected to the camera module and the memory, wherein the at least one processor may be configured to: successively obtain a plurality of first images through the camera module, align the plurality of first images, obtain a reference image based on the plurality of aligned first images, and obtain a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.

(8) A method for providing an image by an electronic device according to various example embodiments of the disclosure may include: successively obtaining a plurality of first images through a camera module of the electronic device, aligning the plurality of first images, obtaining a reference image based on the plurality of aligned first images, and obtaining a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.

(9) A method for providing an image and an electronic device for supporting the same according to various example embodiments of the disclosure may align a plurality of images obtained through a camera of an electronic device and may obtain a high-resolution image using an artificial intelligence model, based on the plurality of aligned images and a reference image obtained from the plurality of aligned images.

(10) Further, a method for providing an image and an electronic device for supporting the same according to various example embodiments of the disclosure may perform training using a low-resolution image and a high-resolution image obtained through an actual camera, thereby improving an artificial intelligence model for providing a super-resolution technique.

(11) In addition, a method for providing an image and an electronic device for supporting the same according to various example embodiments of the disclosure may obtain a high-resolution image in which high-frequency domain data is reconstructed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to various embodiments;

- (3) FIG. 2 is a block diagram illustrating a camera module according to various embodiments;
- (4) FIG. 3 is a block diagram illustrating an example configuration of an electronic device according to various embodiments;
- (5) FIG. 4 is a block diagram illustrating example components for performing an operation of providing an image according to various embodiments;
- (6) FIG. 5 is a diagram illustrating an example method for aligning a plurality of images according to various embodiments;
- (7) FIG. 6 is a flowchart illustrating an example method for providing an image according to various embodiments;
- (8) FIG. 7 is a flowchart illustrating an example method for providing an image according to various embodiments;
- (9) FIG. 8A is a diagram illustrating an example method for aligning a plurality of images according to various embodiments; and
- (10) FIG. 8B is a diagram illustrating an example method for aligning a plurality of images according to various embodiments.

DETAILED DESCRIPTION

(11) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments.

(12) Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(13) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(14) The auxiliary processor **123** may control, for example, at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the

communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active (e.g., executing an application) state. According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence model is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(15) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(16) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(17) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(18) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(19) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(20) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or an external electronic device (e.g., an electronic device **102** (e.g., a speaker or a headphone)) directly or wirelessly coupled with the electronic device **101**.

(21) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip

sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(22) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(23) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(24) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(25) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(26) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(27) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(28) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device **104** via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify or authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(29) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type

communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(30) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(31) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, an RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(32) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(33) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the external electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example.

The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(34) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(35) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B, or C”, “at least one of A, B, and C”, and “at least one of A, B, or C”, may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd”, or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(36) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic”, “logic block”, “part”, or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(37) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(38) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only

memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(39) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components or operations may be omitted, or one or more other components or operations may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(40) FIG. 2 is a block diagram **200** illustrating the camera module **180** according to various embodiments.

(41) Referring to FIG. 2, the camera module **180** may include a lens assembly **221**, a flash **222**, an image sensor **223**, an image stabilizer **224**, memory **225** (e.g., buffer memory), or an image signal processor **226**.

(42) The lens assembly **221** may collect light emitted or reflected from an object whose image is to be taken. The lens assembly **221** may include one or more lenses. According to an embodiment, the camera module **180** may include a plurality of lens assemblies **221**. In such a case, the camera module **180** may form, for example, a dual camera, a 360-degree camera, or a spherical camera. Some of the plurality of lens assemblies **221** may have the same lens attribute (e.g., view angle, focal length, auto-focusing, f number, or optical zoom), or at least one lens assembly may have one or more lens attributes different from those of another lens assembly. The lens assembly **221** may include, for example, a wide-angle lens or a telephoto lens.

(43) The flash **222** may emit light that is used to reinforce light reflected from an object. According to an embodiment, the flash **222** may include one or more light emitting diodes (LEDs) (e.g., a red-green-blue (RGB) LED, a white LED, an infrared (IR) LED, or an ultraviolet (UV) LED) or a xenon lamp. The image sensor **223** may obtain an image corresponding to an object by converting light emitted or reflected from the object and transmitted via the lens assembly **221** into an electrical signal.

(44) According to an embodiment, the image sensor **223** may include one selected from image sensors having different attributes, such as a RGB sensor, a black-and-white (BW) sensor, an IR sensor, or a UV sensor, a plurality of image sensors having the same attribute, or a plurality of image sensors having different attributes. Each image sensor included in the image sensor **223** may be implemented using, for example, a charged coupled device (CCD) sensor or a complementary metal oxide semiconductor (CMOS) sensor.

(45) The image stabilizer **224** may move the image sensor **223** or at least one lens included in the lens assembly **221** in a particular direction, or control an operational attribute (e.g., adjust the read-out timing) of the image sensor **223** in response to the movement of the camera module **180** or the electronic device **101** including the camera module **180**. This allows compensating for at least part of a negative effect (e.g., image blurring) by the movement on an image being captured. According to an embodiment, the image stabilizer **224** may sense such a movement by the camera module **180** or the electronic device **101** using a gyro sensor (not shown) or an acceleration sensor (not shown) disposed inside or outside the camera module **180**. According to an embodiment, the image

stabilizer **224** may be implemented, for example, as an optical image stabilizer.

(46) The memory **225** may store, at least temporarily, at least part of an image obtained via the image sensor **223** for a subsequent image processing task. For example, if image capturing is delayed due to shutter lag or multiple images are quickly captured, a raw image obtained (e.g., a Bayer-patterned image, a high-resolution image) may be stored in the memory **225**, and its corresponding copy image (e.g., a low-resolution image) may be previewed via the display module **160**. Thereafter, if a specified condition is met (e.g., by a user's input or system command), at least part of the raw image stored in the memory **225** may be obtained and processed, for example, by the image signal processor **226**. According to an embodiment, the memory **225** may be configured as at least part of the memory **130** or as a separate memory that is operated independently from the memory **130**.

(47) The image signal processor **226** may perform one or more image processing with respect to an image obtained via the image sensor **223** or an image stored in the memory **225**. The one or more image processing may include, for example, depth map generation, three-dimensional (3D) modeling, panorama generation, feature point extraction, image synthesizing, or image compensation (e.g., noise reduction, resolution adjustment, brightness adjustment, blurring, sharpening, or softening). Additionally or alternatively, the image signal processor **226** may perform control (e.g., exposure time control or read-out timing control) with respect to at least one (e.g., the image sensor **223**) of the components included in the camera module **180**. An image processed by the image signal processor **226** may be stored back in the memory **225** for further processing, or may be provided to an external component (e.g., the memory **130**, the display module **160**, the electronic device **102**, the electronic device **104**, or the server **108**) outside the camera module **180**. According to an embodiment, the image signal processor **226** may be configured as at least part of the processor **120**, or as a separate processor that is operated independently from the processor **120**. If the image signal processor **226** is configured as a separate processor from the processor **120**, at least one image processed by the image signal processor **226** may be displayed, by the processor **120**, via the display module **160** as it is or after being further processed.

(48) According to an embodiment, the electronic device **101** may include a plurality of camera modules **180** having different attributes or functions. In such a case, at least one of the plurality of camera modules **180** may form, for example, a wide-angle camera and at least another of the plurality of camera modules **180** may form a telephoto camera. Similarly, at least one of the plurality of camera modules may form, for example, a front camera and at least another of the plurality of camera modules may form a rear camera.

(49) FIG. 3 is a block diagram illustrating an example configuration of an electronic device **101** according to various embodiments.

(50) Referring to FIG. 3, in an embodiment, the electronic device **101** may include a display **210**, a camera module (e.g., a camera module including a camera) **220**, a memory **230**, and/or a processor (e.g., a processor including processing circuitry) **240**.

(51) In an embodiment, the display **210** may be included in the display module **160** of FIG. 1.

(52) In an embodiment, the display **210** may display an image obtained through the camera module **220**. For example, the display **210** may display a plurality of images successively obtained through the camera module **220**. In another example, when a plurality of images successively obtained through the camera module **220** is processed, the display **210** may display the images obtained through processing.

(53) In an embodiment, the camera module **220** may be included in the camera module **180** of FIG. 1 and FIG. 2.

(54) In an embodiment, the camera module **220** may include a camera and successively obtain a plurality of images. The plurality of successively obtained images may be images having different views (e.g., images having mutual parallax).

- (55) In an embodiment, the memory **230** may be included in the memory **130** of FIG. **1**.
- (56) In an embodiment, the memory **230** may include components for performing at least part of an operation of providing an image.
- (57) In an embodiment, the processor **240** may be included in the processor **120** of FIG. **1**.
- (58) In an embodiment, the processor **240** may include various processing circuitry and control the overall operation of providing the image. In an embodiment, the processor **240** may include one or more processors for performing the operation of providing the image.
- (59) In an embodiment, although FIG. **3** shows that the electronic device **101** includes the display **210**, the camera module **220**, the memory **230**, and/or the processor **240**, but the disclosure is not limited thereto. For example, the electronic device **101** may not include the display **210** according to an embodiment. In another example, the electronic device **101** may further include at least one component (e.g., the communication module **190**) among the components of the electronic device **101** illustrated in FIG. **1**.
- (60) FIG. **4** is a block diagram **400** illustrating example components for performing an operation of providing an image according to various embodiments.
- (61) Referring to FIG. **4**, in an embodiment, the components for performing the operation of providing the image may include a crop module (e.g., a crop module including various processing circuitry and/or executable program instructions) **310**, an upscaling module (e.g., an upscaling module including various processing circuitry and/or executable program instructions) **320**, an alignment module (e.g., an alignment module including various processing circuitry and/or executable program instructions) **330**, a weighted average module (e.g., a weighted average module including various processing circuitry and/or executable program instructions) **340**, and/or an artificial intelligence model (e.g., an artificial intelligence model including various processing circuitry and/or executable program instructions) **231**. In an embodiment, the crop module **310**, the upscaling module **320**, the alignment module **330**, the weighted average module **340**, and/or the artificial intelligence model **231** may be stored in a memory **230**.
- (62) In an embodiment, the artificial intelligence model **231** may include a concatenation module (e.g., a concatenation module including various processing circuitry and/or executable program instructions) **350**, a single frame super-resolution (SFSR) module (e.g., a SFSR module including various processing circuitry and/or executable program instructions) **360**, and/or a synthesis module (e.g., a synthesis module including various processing circuitry and/or executable program instructions) **370**. However, the disclosure is not limited thereto, and at least one of the concatenation module **350**, the single frame super-resolution (SFSR) module **360**, and the synthesis module **370** may be configured using a designated algorithm without using artificial intelligence.
- (63) In an embodiment, at least one of the crop module **310**, the upscaling module **320**, the alignment module **330**, or the weighted average module **340** may be included in the artificial intelligence model **231**.
- (64) In an embodiment, the crop module **310** may crop a plurality of images (which may be referred to hereinafter as “a plurality of first images”) successively obtained through a camera module **220**. In an embodiment, when a zoom input (e.g., a zoom-in input) associated with the camera module **220** is received from a user, the crop module **310** may crop the plurality of first images, based on zoom magnification associated with the camera module **220**. For example, when an input to increase the zoom magnification twice from a zoom magnification of 1.0× to a zoom magnification of 2.0×, the crop module **310** may crop a ¼ area of each image of the plurality of first images, obtained through the entire area of an image sensor of the camera module **220** (or an area of the image sensor corresponding to a currently displayed image), based on the center of the image (or the center of the image being currently displayed through a display **210**). In an embodiment, the crop module **310** may transmit a plurality of cropped first images (hereinafter, referred to as “a plurality of cropped first images”) to the upscaling module **320**.
- (65) In an embodiment, the upscaling module **312** may perform an operation of upscaling the

plurality of cropped first images.

(66) In an embodiment, the upscaling module **320** may upscale the plurality of cropped first images into a plurality of images (which may be referred to hereinafter as “a plurality of upscaled first images”) having a greater size than the size of the plurality of cropped first images.

(67) In an embodiment, the upscaling module **320** may perform the operation of upscaling the plurality of cropped first images, based on the zoom magnification associated with the camera module **220**. For example, when the $\frac{1}{4}$ area of each image of the plurality of first images based on the center of the image is cropped based on receiving the input to increase the zoom magnification twice from a zoom magnification of $1.0\times$ to a zoom magnification of $2.0\times$, the upscaling module **320** may upscale the plurality of cropped first images having a first size into the plurality of upscaled first images having a second size four times (e.g., twice in width and twice in length) greater than the first size.

(68) In an embodiment, the upscaling module **320** may perform the operation of upscaling the plurality of cropped first images using various algorithms. For example, the upscaling module **320** may perform the operation of upscaling the plurality of cropped first images using a nearest neighbor algorithm, a bicubic algorithm, or a bilinear algorithm. However, an algorithm used by the upscaling module **320** to perform the operation of upscaling the plurality of cropped first images is not limited to the foregoing algorithms.

(69) In an embodiment, the upscaling module **320** may not be included in a processor **240**, in which case an upscaling operation may be performed in the artificial intelligence model **231** (e.g., the SFSR module **360**).

(70) In an embodiment, the alignment module **330** may align the plurality of upscaled first images.

(71) In an embodiment, the alignment module **330** may align, based on one image among the plurality of upscaled first images (e.g., the position of the one image among the plurality of upscaled first images), images (e.g., the positions of the images) other than the one image as a reference among the plurality of upscaled first images. Hereinafter, a method in which the alignment module **330** aligns the plurality of upscaled first images will be described in greater detail below with reference to FIG. 5.

(72) FIG. 5 is a diagram **500** illustrating an example method for aligning a plurality of images according to various embodiments.

(73) Referring to FIG. 5, in an embodiment, reference numeral **501** may denote a plurality of upscaled first images. For example, the plurality of upscaled first images may include image **1 511**, image **2 512**, image **3 513**, and image **4 514**. Reference numeral **501** shows four upscaled first images as the plurality of upscaled first images, but is not limited thereto. In an embodiment, referring to reference numeral **501** and reference numeral **502**, image **1 511**, image **2 512**, image **3 513**, and image **4 514** may be images each having a Bayer pattern. For example, in image **1 511**, a first pixel **511-1** may be a pixel corresponding to red of RGB, a second pixel **511-2** and a third pixel **511-3** may be pixels corresponding to green of RGB, and a fourth pixel **511-4** may be a pixel corresponding to blue of RGB. However, the disclosure is not limited thereto, and the plurality of upscaled first images may be images having RGB data.

(74) In an embodiment, the alignment module **330** may obtain information about a movement of the camera module **220** while successively obtaining a plurality of first images through the camera module **220**. For example, the alignment module **330** may obtain (e.g., calculate) differences between a position of the camera module **220** at which a first image among the plurality of first images (e.g., an image obtained first among the plurality of first images) is obtained and positions of the camera module **220** at which images after the first image (e.g., images obtained after the first image is obtained) are obtained while successively obtaining the plurality of first images through the camera module **220**. In an embodiment, the alignment module **330** may obtain the information about the movement of the camera module **220** by comparing pixel values of the first image and pixel values of each of the images after the first image while successively obtaining the plurality of

first images through the camera module **220**.

(75) In an embodiment, the alignment module **330** may align the plurality of scaled first images, based on the obtained information about the movement of the camera module **220**. For example, as shown by reference numeral **502**, the alignment module **330** may align, based on one image (e.g., the image **511**) among the plurality of scaled first images, images (e.g., the images **512**, **513**, and **514**) other than the one image as a reference. In an embodiment, the alignment module **330** may shift the positions of the other images, based on the position of the one image as the reference among the plurality of scaled first images, based on the obtained information about the movement of the camera module **220**, thereby aligning the plurality of upscaled first images (hereinafter, the one image as the reference and the other images after the alignment are referred to as “a plurality of aligned first images”). In an embodiment, the alignment module **330** may transmit the plurality of aligned first images to the artificial intelligence model **231** (e.g., the concatenation module **350**).

(76) In an embodiment, the weighted average module **340** may average the plurality of aligned first images in view of a weight. For example, the weighted averaging module **340** may assign a weight to each of the plurality of aligned first images, based on the quality of each of the plurality of aligned first images (e.g., the degree to which each of the plurality of aligned first images is blurred and/or the peak signal-to-noise ratio (PSNR) of each of the plurality of aligned first images).

Weights assigned to the plurality of aligned first images may be the same or different.

(77) In an embodiment, the weighted average module **340** may average the plurality of aligned first images (e.g., pixel values of each of the plurality of aligned first images), based on the weights assigned to the plurality of aligned first images, thereby obtaining one image (hereinafter, referred to as a “reference image”).

(78) In an embodiment, the reference image may be an image in which the strength of an original signal (e.g., a pattern of each of the plurality of aligned first images) is increased in a high-frequency region and the strength of noise is reduced, compared to the plurality of aligned first images. In an embodiment, the reference image may be an image including data of the high-frequency region that is not included in the plurality of aligned first images. In an embodiment, the reference image may be an image including less noise (e.g., a Moiré signal) than the plurality of aligned first images. In an embodiment, the reference image may be an image from which at least part of noise included in the plurality of aligned first images is removed. In an embodiment, the reference image may be an image generated based on at least a portion of each of the plurality of aligned first images.

(79) In an embodiment, the weighted average module **340** may average all of the plurality of aligned first images or some images of the plurality of aligned first images in view of the weights. In an embodiment, the weighted average module **340** may transmit the reference image to the artificial intelligence model **231** (e.g., the concatenation module **350**).

(80) In an embodiment, the concatenation module **350** may obtain the plurality of aligned first images from the alignment module **330**, and may obtain the reference image from the weighted average module **340**. In an embodiment, the concatenation module **350** may convert the plurality of aligned first images and the reference image into one image. For example, the plurality of aligned first images and the reference image may each have a red channel, a green channel, and a blue channel. The concatenation module **350** may obtain one image having the channels of the plurality of aligned first images and the channels of the reference image from the plurality of aligned first images and the reference image.

(81) In an embodiment, the SFSR module **360** (also referred to as an “SFSR artificial intelligence model”) may output an image in which noise (e.g., a Moiré signal) is reduced (or removed) and data of the high-frequency region is restored as result data using the image converted from the plurality of aligned first images and the reference image as input data. For example, the SFSR module **360** may output an image in which each pixel to form the image has a red value, a green value, and a blue value, based on the one image having the channels of the plurality of aligned first

images and the channels of the reference image, similarly to the foregoing pixel shifting.

(82) In an embodiment, the SFSR module **360** may include an artificial intelligence model using, for example, very deep residual channel attention networks (RCAN). The RCAN may include a convolution layer for extracting a feature (e.g., a shallow feature) of input data, a skip connection (e.g., a long skip connection), a plurality of residual groups, and convolution layers for extracting a feature (e.g., a deep feature) from resulting data of the residual groups. Each residual group of the RCAN may include a plurality of channel attention blocks, a skip connection (e.g., a short skip connection), and a convolution layer, respectively. However, an artificial intelligence network used by the SFSR module **360** is not limited to the RCAN, and various artificial intelligence networks may be used. For example, the SFSR module **360** may use an SRCNN, an FSRCNN, an ESPCN, or a VDSR.

(83) In an embodiment, the synthesis module **370** may obtain a final image (also referred to as a “second image”), based on the image output from the artificial intelligence model **231** and the reference image input from the weighted average module **340**. In an embodiment, the second image may be an image in which noise (e.g., a Moiré signal) existing in the plurality of first images (e.g., aligned first images) or the reference image is reduced by cancelation and the data in the high-frequency region is amplified.

(84) Although FIG. 4 shows that the artificial intelligence model **231** include the SFSR module **360**, the disclosure is not limited thereto. In an embodiment, the artificial intelligence model **231** may include a denoising artificial intelligence model (e.g., a denoising CNN model) in addition to or in place of the SFSR module **360**. When the artificial intelligence model **231** uses the denoising artificial intelligence model **231**, noise may be removed from an image, thus obtaining an image having an improved image quality.

(85) An electronic device according to various example embodiments of the disclosure may include a camera module including a camera, a memory, and at least one processor electrically connected to the camera module and the memory, wherein the at least one processor may be configured to successively obtain a plurality of first images through the camera module, align the plurality of first images, obtain a reference image based on the plurality of aligned first images, and obtain a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.

(86) In various example embodiments, the at least one processor may be configured to obtain the reference image by performing a weighted average operation on the plurality of aligned first images.

(87) In various example embodiments, the second image may have a higher resolution than a resolution of the plurality of first images.

(88) In various example embodiments, the at least one processor may be configured to: crop the plurality of first images, upscale the plurality of cropped first images, and align the plurality of upscaled first images.

(89) In various example embodiments, the at least one processor may be configured to: crop the plurality of first images based on receiving an input to increase a zoom magnification associated with the camera module, and upscale the plurality of cropped first images based on the zoom magnification.

(90) In various example embodiments, the reference image may include an image in which a strength of an original signal is increased in a high-frequency region and a strength of noise is reduced compared to the plurality of upscaled first images.

(91) In various example embodiments, the at least one processor may be configured to: obtain information about a movement of the camera module while successively obtaining the plurality of first images through the camera module, and align the plurality of first images based on the information about the movement of the camera module.

(92) In various example embodiments, the at least one processor may be configured to: assign a

weight to each of the plurality of aligned first images based on a quality of each of the plurality of aligned first images, and perform an operation of averaging the plurality of aligned first images based on the weight.

(93) In various example embodiments, the artificial intelligence model may include a single frame super-resolution (SFSR) artificial intelligence model and a denoising artificial intelligence model.

(94) FIG. 6 is a flowchart 600 illustrating an example method for providing an image according to various embodiments.

(95) Referring to FIG. 6, in operation 601, in an embodiment, a processor 240 may successively obtain a plurality of first images through a camera module 220.

(96) In operation 603, in an embodiment, the processor 240 may align the plurality of obtained first images.

(97) In an embodiment, the processor 240 may align, based on one image among the plurality of first images, images (e.g., the positions of the images) other than the one image as a reference among the plurality of first images.

(98) In an embodiment, the processor 240 may obtain information about a movement of a camera module 220 while successively obtaining a plurality of first images through the camera module 220. For example, the processor 240 may obtain (e.g., calculate) differences between a position of the camera module 220 at which a first image among the plurality of first images (e.g., an image obtained first among the plurality of first images) is obtained and positions of the camera module 220 at which images after the first image (e.g., images obtained after the first image is obtained) are obtained while successively obtaining the plurality of first images through the camera module 220. In an embodiment, the processor 240 may obtain the information about the movement of the camera module 220 by comparing pixel values of the first image and pixel values of each of the images after the first image while successively obtaining the plurality of first images through the camera module 220.

(99) In an embodiment, the processor 240 may align the plurality of first images, based on the obtained information about the movement of the camera module 220.

(100) In an embodiment, the processor 240 may shift the positions of the other images, based on the position of the one image as a reference among the plurality of first images, based on the obtained information about the movement of the camera module 220, thereby aligning the plurality of first images

(101) In operation 605, in an embodiment, the processor 240 may obtain a reference image based on the plurality of aligned first images.

(102) In an embodiment, the processor 240 may average the plurality of aligned first images in view of a weight. For example, the processor 240 may assign a weight to each of the plurality of aligned first images, based on the quality of each of the plurality of aligned first images (e.g., the degree to which each of the plurality of aligned first images is blurred and/or the peak signal-to-noise ratio (PSNR) of each of the plurality of aligned first images). Weights assigned to the plurality of aligned first images may be the same or different. However, a method for obtaining the reference image based on the plurality of aligned first images is not limited to the foregoing example. The processor 240 may obtain the reference image using a median of the plurality of aligned first images.

(103) In an embodiment, the processor 240 may average the plurality of aligned first images (e.g., pixel values of each of the plurality of aligned first images) in view of the weights assigned to the plurality of aligned first images, thereby obtaining the reference image.

(104) In an embodiment, the reference image may be an image in which the strength of an original signal (e.g., a pattern of each of the plurality of aligned first images) is increased in a high-frequency region and the strength of a noise signal is reduced, compared to the plurality of aligned first images. In an embodiment, the reference image may be an image including data of the high-frequency region that is not included in the plurality of aligned first images. In an embodiment, the

reference image may be an image including less noise (e.g., a Moiré signal) than the plurality of aligned first images. In an embodiment, the reference image may be an image from which at least part of noise included in the plurality of aligned first images is removed. In an embodiment, the reference image may be an image generated based on at least a portion of each of the plurality of aligned first images.

(105) In an embodiment, the processor **240** may average all of the plurality of aligned first images or some images of the plurality of aligned first images in view of the weights. In an embodiment, a weighted average module **340** may transmit the reference image to an artificial intelligence model **231** (e.g., a concatenation module **350**).

(106) In operation **607**, in an embodiment, the processor **240** may obtain a second image (e.g., final image) using the artificial intelligence model **231**, based on the plurality of aligned first images and the reference image.

(107) In an embodiment, the processor **240** may convert the plurality of aligned first images and the reference image into one image using the artificial intelligence model **231**. For example, the plurality of aligned first images and the reference image may each have a red channel, a green channel, and a blue channel. The processor **240** may obtain one image having the channels of the plurality of aligned first images and the channels of the reference image from the plurality of aligned first images and the reference image using the artificial intelligence model **231**.

(108) In an embodiment, the processor **240** may output, using the artificial intelligence model **231** (e.g., an SFSR module **360**), an image in which noise (e.g., a Moiré signal) is reduced (or removed) and data of the high-frequency region is restored as result data using the image converted from the plurality of aligned first images and the reference image as input data. For example, the processor **240** may output, using the artificial intelligence model **231** (e.g., an SFSR module **360**), an image in which each pixel to form the image has a red value, a green value, and a blue value, based on the one image having the channels of the plurality of aligned first images and the channels of the reference image, similarly to the foregoing pixel shifting.

(109) In an embodiment, the SFSR module **360** may be an artificial intelligence model using, for example, very deep residual channel attention networks (RCAN). The RCAN may include a convolution layer for extracting a feature (e.g., a shallow feature) of input data, a skip connection (e.g., a long skip connection), a plurality of residual groups, and convolution layers for extracting a feature (e.g., a deep feature) from resulting data of the residual groups. Each residual group of the RCAN may include a plurality of channel attention blocks, a skip connection (e.g., a short skip connection), and a convolution layer, respectively. However, an artificial intelligence network used by the SFSR module **360** is not limited to the RCAN, and various artificial intelligence networks may be used. For example, the SFSR module **360** may use an SRCNN, an FSRCNN, an ESPCN, or a VDSR.

(110) In an embodiment, the artificial intelligence model **231** may include a denoising artificial intelligence model (e.g., a denoising CNN model) in addition to or in place of the SFSR module **360**. When the artificial intelligence model **231** uses the denoising artificial intelligence model **231**, noise may be removed from an image, thus obtaining the image having an improved image quality.

(111) In an embodiment, the processor **240** may obtain the second image, based on the image output from the artificial intelligence model **231** and the reference image. In an embodiment, the processor **240** may obtain the second image, based on the image output from the artificial intelligence model **231** and the reference image, using the artificial intelligence model **231**.

(112) In an embodiment, the second image may be an image in which noise (e.g., a Moiré signal) existing in the plurality of first images (e.g., aligned first images) or the reference image is reduced by cancelation and the data in the high-frequency region is amplified.

(113) Although FIG. **6** shows that the processor **240** aligns the plurality of first images and performs a weighted average operation on the plurality of aligned first images without using the artificial intelligence model **231** to thereby obtain the reference image, the disclosure is not limited

thereto. For example, the processor **240** may perform an operation of aligning the plurality of first images and/or a weighted average operation on the plurality of aligned first images using the artificial intelligence model **231**.

(114) FIG. **7** is a flowchart **700** illustrating an example method for providing an image according to various embodiments.

(115) Referring to FIG. **7**, in operation **701**, in an embodiment, a processor **240** may successively obtain a plurality of first images through a camera module **220**.

(116) In operation **703**, in an embodiment, the processor **240** may crop the plurality of first images. In an embodiment, the processor **240** may crop the plurality of first images. In an embodiment, when a zoom input (e.g., a zoom-in input) associated with the camera module **220** is received from a user, the processor **240** may crop the plurality of first images, based on zoom magnification associated with the camera module **220**. For example, when an input to increase the zoom magnification twice from a zoom magnification of $1.0\times$ to a zoom magnification of $2.0\times$, the processor **240** may crop a $\frac{1}{4}$ area of each image of the plurality of first images, obtained through the entire area of an image sensor of the camera module **220** (or an area of the image sensor corresponding to a currently displayed image), based on the center of the image (or the center of the image being currently displayed through a display **210**).

(117) In operation **705**, in an embodiment, the processor **240** may upscale the plurality of cropped first images.

(118) In an embodiment, the processor **240** may upscale the plurality of cropped first images into a plurality of images having a greater size than the size of the plurality of cropped first images.

(119) In an embodiment, the processor **240** may perform the operation of upscaling the plurality of cropped first images, based on the zoom magnification associated with the camera module **220**. For example, when the $\frac{1}{4}$ area of each image of the plurality of first images based on the center of the image is cropped based on receiving the input to increase the zoom magnification twice from a zoom magnification of $1.0\times$ to a zoom magnification of $2.0\times$, the processor **240** may upscale the plurality of cropped first images having a first size into the plurality of scaled first images having a second size four times (e.g., twice in width and twice in length) greater than the first size.

(120) In an embodiment, the processor **240** may perform the operation of upscaling the plurality of cropped first images using various algorithms. For example, the processor **240** may perform the operation of upscaling the plurality of cropped first images using a nearest neighbor algorithm, a bicubic algorithm, or a bilinear algorithm. However, an algorithm used by the processor **240** to perform the operation of upscaling the plurality of cropped first images is not limited to the foregoing algorithms.

(121) In an embodiment, the processor **240** may perform an upscaling operation using an artificial intelligence model **231**.

(122) In operation **707**, in an embodiment, the processor **240** may align the plurality of upscaled first images.

(123) In operation **709**, in an embodiment, the processor **240** may obtain a reference image, based on the plurality of aligned first images.

(124) In operation **711**, in an embodiment, a second image (e.g., final image) may be obtained using the artificial intelligence model **231**, based on the plurality of aligned first images and the reference image.

(125) Since operation **707** to operation **709** are at least partially the same as or similar to operation **603** to operation **607**, a detailed description thereof may not be repeated.

(126) FIG. **8A** is a diagram illustrating an example method for aligning a plurality of images according to various embodiments.

(127) FIG. **8B** is a diagram illustrating an example method for aligning a plurality of images according to various embodiments.

(128) Referring to FIG. **8A** and FIG. **8B**, in an embodiment, reference numeral **801** may denote one

image among a plurality of upscaled (e.g., upscaled by a bicubic method) first images. As shown by reference numeral **801**, the one image among the plurality of upscaled first images includes noise **811** (e.g., a Moiré signal) but may not include data of a high-frequency region in some areas.

(129) In an embodiment, reference numeral **802** may denote a reference image. Comparing reference numeral **801** and reference numeral **802**, the reference image may have reduced noise strength compared to the upscaled first image and may include the data in the high-frequency region that is not included in the upscaled first image.

(130) In an embodiment, reference numeral **803** may denote a final image obtained using an artificial intelligence model **231**, based on a plurality of aligned first images and one image among the plurality of aligned first images in place of the reference image. As shown by reference numeral **803**, the obtained final image includes noise **831**, and the data in the high-frequency region has not been restored in some areas of the obtained image.

(131) In an embodiment, reference numeral **804** may denote a second image. In the second image of reference numeral **804** compared with reference numerals **801** to **803**, the strength of noise is significantly reduced and the data of the high-frequency region has been restored.

(132) A method for providing an image by an electronic device according to various example embodiments of the disclosure may include: successively obtaining a plurality of first images through a camera module of the electronic device, aligning the plurality of first images, obtaining a reference image based on the plurality of aligned first images, and obtaining a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.

(133) In various example embodiments, the obtaining of the reference image may include obtaining the reference image by performing a weighted average operation on the plurality of aligned first images.

(134) In various example embodiments, the second image may have a higher resolution than a resolution of the plurality of first images.

(135) In various example embodiments, the method may further include cropping the plurality of first images and upscaling the plurality of cropped first images, and the aligning of the plurality of first images may include aligning the plurality of upscaled first images.

(136) In various example embodiments, the cropping of the plurality of first images may include cropping the plurality of first images based on receiving an input to increase the zoom magnification associated with the camera module, and the upscaling of the plurality of cropped first images may include upscaling the plurality of cropped first images, based on the zoom magnification.

(137) In various example embodiments, the reference image may include an image in which a strength of an original signal is increased in a high-frequency region and a strength of noise is reduced compared to the plurality of upscaled first images.

(138) In various example embodiments, the aligning of the plurality of first images may include: obtaining information about a movement of the camera module while successively obtaining the plurality of first images through the camera module, and aligning the plurality of first images based on the information about the movement of the camera module.

(139) In various example embodiments, the obtaining of the reference image may include: assigning a weight to each of the plurality of aligned first images based on a quality of each of the plurality of aligned first images, and performing an operation of averaging the plurality of aligned first images, based on the weight.

(140) In various example embodiments, the artificial intelligence model may include an SFSR artificial intelligence model and a denoising artificial intelligence model.

(141) In various example embodiments, the obtaining of the reference image may include obtaining the reference image using the artificial intelligence model.

(142) The structure of data used in the foregoing embodiments of the disclosure may be recorded in

a non-transitory computer-readable recording medium through various methods. The computer-readable recording medium includes a storage medium, such as a magnetic storage medium (e.g., ROM, floppy disk, and hard disk) and an optical reading medium (e.g., CD-ROM and DVD). (143) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device comprising: a camera module including a camera; a memory; and at least one processor, comprising processing circuitry, electrically connected to the camera module and the memory, wherein the at least one processor is individually and/or collectively configured to: successively obtain a plurality of first images through the camera module, obtain information about a movement of the camera module while successively obtaining the plurality of first images through the camera module, wherein the information about the movement of the camera module includes differences between a first position of the camera module at which a beginning image among the plurality of first images is obtained and second positions of the camera module at which images after the beginning image are obtained, wherein the information about the movement of the camera module is obtained by comparing a first pixel value of the beginning image and second pixel values of each of the images after the beginning image, based on receiving an input to increase a zoom magnification associated with the camera module, crop the plurality of first images, upscale the plurality of cropped first images based on the zoom magnification, based on the information about the movement of the camera module, align the plurality of upscaled first images, by shifting positions of the images after the beginning image, other than the beginning image, with respect to the first position of the camera module as a reference, based on the plurality of aligned first images, obtain a reference image by performing a weighted average operation on the plurality of aligned first images, wherein the reference image includes an image in which a strength of an original signal is increased in a high-frequency region and a strength of noise is reduced compared to the plurality of upscaled first images, and obtain a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.
2. The electronic device of claim 1, wherein the second image has a higher resolution than a resolution of the plurality of first images.
3. The electronic device of claim 1, wherein the at least one processor is configured to: assign a weight to each of the plurality of aligned first images based on a quality of each of the plurality of aligned first images, and perform an operation of averaging the plurality of aligned first images based on the weight.
4. The electronic device of claim 1, wherein the artificial intelligence model comprises a single frame super-resolution (SFSR) artificial intelligence model and a denoising artificial intelligence model.
5. The electronic device of claim 1, wherein the at least one processor is configured to obtain the reference image using the artificial intelligence model.
6. A method for providing an image by an electronic device, the method comprising: successively obtaining a plurality of first images through a camera module of the electronic device; obtaining information about a movement of the camera module while successively obtaining the plurality of first images through the camera module, wherein the information about the movement of the camera module includes differences between a first position of the camera module at which a

beginning image among the plurality of first images is obtained and second positions of the camera module at which images after the beginning image are obtained, wherein the information about the movement of the camera module is obtained by comparing a first pixel value of the beginning image and second pixel values of each of the images after the beginning image, based on receiving an input to increase a zoom magnification associated with the camera module, cropping the plurality of first images, upscaling the plurality of cropped first images based on the zoom magnification, based on the information about the movement of the camera module, aligning the plurality of upscaled first images, by shifting positions of the images after the beginning image, other than the beginning image, with respect to the first position of the camera module as a reference; based on the plurality of aligned first images, obtaining a reference image by performing a weighted average operation on the plurality of aligned first images, wherein the reference image includes an image in which a strength of an original signal is increased in a high-frequency region and a strength of noise is reduced compared to the plurality of upscaled first images; and obtaining a second image using an artificial intelligence model based on the plurality of aligned first images and the reference image.

7. The method of claim 6, wherein the second image has a higher resolution than a resolution of the plurality of first images.

8. The method of claim 6, wherein the obtaining of the reference image comprises: assigning a weight to each of the plurality of aligned first images based on a quality of each of the plurality of aligned first images, and performing an operation of averaging the plurality of aligned first images based on the weight.

9. The method of claim 6, wherein the artificial intelligence model comprises a single frame super-resolution (SFSR) artificial intelligence model and a denoising artificial intelligence model.

10. The method of claim 6, wherein the obtaining of the reference image comprises obtaining the reference image using the artificial intelligence model.
