

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418858
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yoshimura; Kohji

Information processing apparatus, information processing system, and recording medium

Abstract

An information processing apparatus includes: circuitry that measures at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals, determines, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds, and notifies each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal.

Inventors:	Yoshimura; Kohji (Kanagawa, JP)
Applicant:	Yoshimura; Kohji (Kanagawa, JP)
Family ID:	1000008821396
Assignee:	RICOH COMPANY, LTD. (Tokyo, JP)
Appl. No.:	18/048499
Filed:	October 21, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230147299 A1	May. 11, 2023

Foreign Application Priority Data

JP	2021-180960	Nov. 05, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: H04W48/18 (20090101); H04W24/08 (20090101); H04W24/10 (20090101)

U.S. Cl.:

CPC H04W48/18 (20130101); H04W24/08 (20130101); H04W24/10 (20130101);

Field of Classification Search

CPC: H04W (48/18); H04W (24/08); H04W (24/10)

USPC: 370/329

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9009344	12/2014	Nassor	709/224	H04L 47/12
9094380	12/2014	Shinohara	N/A	H04L 67/00
2015/0302096	12/2014	Iwasaki	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-283296	12/1997	JP	N/A
2004-054382	12/2003	JP	N/A
2014087024	12/2013	JP	N/A
5561297	12/2013	JP	G06F 3/1204
2015-207088	12/2014	JP	N/A
6100555	12/2016	JP	N/A
6180225	12/2016	JP	H04L 12/1432

Primary Examiner: Tran; Mong-Thuy T

Attorney, Agent or Firm: XSENSUS LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This patent application is based on and claims priority pursuant to 35 U.S.C. § 119(a) to Japanese Patent Application No. 2021-180960, filed on Nov. 5, 2021, in the Japan Patent Office, the entire disclosure of which is hereby incorporated by reference herein.

BACKGROUND

Technical Field

(2) The present disclosure relates to an information processing apparatus, an information processing system, and a recording medium.

Related Art

(3) In the related art, techniques are known in which when a plurality of users concurrently access a plurality of servers to refer to an identical file, which of the servers is optimum for each of the users to access is determined based on a communication speed.

(4) For example, a technique is disclosed in which a server that is optimum for using a plurality of servers to improve data processing efficiency and use efficiency of the plurality of servers is selected to select a server with a highest communication speed.

(5) However, in the above-described technique, when a plurality of users concurrently access an identical file in the plurality of servers, a server with the highest communication speed at that timing, that is, the same server, is selected. This leads to an increase in communication traffic of the selected server and thus a decrease in communication speed of the entire system.

SUMMARY

(6) According to an embodiment of the present disclosure, an information processing apparatus is provided which includes circuitry that measures at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals; determines, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds; and notifies each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal.

(7) According to an embodiment of the present disclosure, an information processing system is provided which includes circuitry that measures at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals; determines, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds, and notifies each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal.

(8) According to an embodiment of the present disclosure, a non-transitory recording medium is provided, storing a plurality of instructions which, when executed by one or more processors, causes the processors to perform an information processing method including measuring at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals; determining, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds; and notifying each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A more complete appreciation of the disclosure and many of the attendant advantages and features thereof can be readily obtained and understood from the following detailed description with reference to the accompanying drawings, wherein:
- (2) FIG. 1 is a diagram illustrating an example of a general arrangement of an information processing system according to an embodiment of the present disclosure;
- (3) FIG. 2 is a diagram for describing an overview of an operation of the information processing system according to the embodiment;
- (4) FIG. 3 is a diagram illustrating an example of a hardware configuration of a master personal computer (PC) according to the embodiment;
- (5) FIG. 4 is a diagram illustrating an example of a configuration of functional blocks of the master PC according to the embodiment;
- (6) FIG. 5 is a diagram for describing an operation of grouping PCs permitted to communicate with a server in accordance with communication speeds of the respective PCs in the information processing system according to the embodiment;
- (7) FIG. 6 is a diagram for describing an example of a result of grouping the PCs permitted to communicate with the server in accordance with the communication speeds of the respective PCs in the information processing system according to the embodiment;
- (8) FIG. 7 is a diagram for describing an operation of grouping PCs that are to communicate with each of servers in accordance with communication speeds of the respective servers in the information processing system according to the embodiment;
- (9) FIG. 8 is a diagram for describing an operation of grouping PCs that are to communicate with each of servers in accordance with communication speeds between the servers and the PCs in the information processing system according to the embodiment;
- (10) FIG. 9 is a diagram for describing an example of obtained communication speeds between the servers and the PCs in the information processing system according to the embodiment;
- (11) FIG. 10 is a diagram for describing an example of a result of grouping the PCs that are to communicate with each of the servers in accordance with the communication speeds between the servers and the PCs in the information processing system according to the embodiment; and
- (12) FIG. 11 is a diagram for describing an operation of changing PCs that are to communicate with each of servers in accordance with changes in communication speeds of the respective PCs over time in the information processing system according to the embodiment.
- (13) The accompanying drawings are intended to depict embodiments of the present invention and should not be interpreted to limit the scope thereof. The accompanying drawings are not to be considered as drawn to scale unless explicitly noted. Also, identical or similar reference numerals designate identical or similar components throughout the several views.

DETAILED DESCRIPTION

- (14) In describing embodiments illustrated in the drawings, specific terminology is employed for the sake of clarity. However, the disclosure of this specification is not intended to be limited to the specific terminology so selected and it is to be understood that each specific element includes all technical equivalents that have a similar function, operate in a similar manner, and achieve a similar result.
- (15) Referring now to the drawings, embodiments of the present disclosure are described below. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.
- (16) An information processing apparatus, an information processing system, an information processing method, and a program according to an embodiment of the present disclosure are described in detail below with reference to the accompanying drawings. The present disclosure, however, is not limited to the embodiment below, and the constituent elements in the embodiment

below include those easily conceivable by persons skilled in the art, those being substantially the same ones, and those being within equivalent ranges. Various omissions, substitutions, changes, and combinations of the constituent elements may be made without departing from the gist of the embodiment below.

(17) General Arrangement of Information Processing System

(18) FIG. 1 is a diagram illustrating an example of a general arrangement of an information processing system according to an embodiment of the disclosure. A description is given of a general arrangement of an information processing system 1 according to the embodiment of the present disclosure with reference to FIG. 1.

(19) As illustrated in FIG. 1, the information processing system 1 includes a master PC 10, servers 20a and 20b, and PCs 30a to 30c. The master PC 10, the servers 20a and 20b, and the PCs 30a to 30c perform data communication via a network N. The network N is a network including a local area network (LAN), a wide area network (WAN), or Internet. The network N may be a wired network or a wireless network. FIG. 1 illustrates two servers, i.e., the servers 20a and 20b.

However, the number of servers is not limited to two, and the information processing system 1 may include three or more servers. Any server among the servers 20a and 20b is referred to simply as “server 20”. In addition, the servers 20a and 20b are collectively referred to simply as “servers 20”. FIG. 1 illustrates three PCs, i.e., the PCs 30a to 30c. However, the number of PCs is not limited to three, and the information processing system 1 may include two PCs or four or more PCs. Any PC among the PCs 30a to 30c is referred to simply as “PC 30”. In addition, the PCs 30a to 30c are collectively referred to simply as “PCs 30”.

(20) The master PC 10 is an information processing apparatus that measures communication speeds of the respective servers 20 and communication speeds of the respective PCs 30 and determines which of the servers 20 each of the PCs 30 is to communicate with. The master PC 10 is not limited to a PC and may be an information processing apparatus of another type such as a workstation or a tablet terminal.

(21) Each of the plurality of servers 20 is a server device such as a file server that stores data of an identical file or the like. In response to a download request from any of the PCs 30, each of the servers 20 transmits target data to the PC 30.

(22) Each of the plurality of PCs 30 is an information terminal used by a user. When downloading specific data, each of the plurality of PCs 30 transmits a download request for the specific data to the server 20 which the PC 30 is notified of by the master PC 10 among the plurality of servers 20. Downloading is described as an example of communication performed between the PCs 30 and the servers 20. Alternatively, the communication may be uploading of data from the PCs 30 to the servers 20. In the description below, the communication performed between the PCs 30 and the servers 20 is downloading. Each of the PCs 30 is not limited to a PC and may be an information terminal of another type such as a workstation or a tablet terminal.

(23) Overview of Operation of Information Processing System

(24) FIG. 2 is a diagram for describing an overview of an operation of the information processing system according to the embodiment. A description is given of an overview of an operation of the information processing system 1 according to the embodiment with reference to FIG. 2.

(25) The master PC 10 in the information processing system 1 measures a communication speed between the master PC 10 and the server 20a ((1) measurement of communication speed). The master PC 10 also measures a communication speed between the master PC 10 and the server 20b ((2) measurement of communication speed). In this manner, the master PC 10 recognizes the communication speeds of the respective servers 20.

(26) The master PC 10 measures a communication speed between the master PC 10 and the PC 30 ((3) measurement of communication speed). FIG. 2 illustrates just one PC 30, which is one of the plurality of PCs 30. In this manner, the master PC 10 recognizes the communication speeds of the respective PCs 30.

(27) For each of the PCs **30**, the master PC **10** determines the server **20** that is to be a communication counterpart of the PC **30**, that is, the server **20** which the PC **30** is to communicate with, based on at least one of the communication speeds of the respective servers **20** or the communication speeds of the respective PCs **30**, and notifies the PC **30** of information on the server **20** ((4) notification of communication-counterpart server). This allows each of the PCs **30** to recognize the server **20**, among the plurality of servers **20**, from which the PC **30** is to download data in order to suppress a decrease in communication speed of the entire information processing system **1**.

(28) The PC **30** transmits a download request for the desired data to the server **20** which the PC **30** is notified of by the master PC **10**, and downloads the data from the server **20** ((5) download).

(29) Hardware Configuration of Master PC

(30) FIG. **3** is a diagram illustrating an example of a hardware configuration of the master PC according to the embodiment. A description is given of the hardware configuration of the master PC **10** according to the embodiment with reference to FIG. **3**.

(31) As illustrated in FIG. **3**, the master PC **10** includes a central processing unit (CPU) **501**, a read-only memory (ROM) **502**, a random access memory (RAM) **503**, an auxiliary storage device **505**, a medium drive **507**, a display **508**, a network interface (I/F) **509**, a keyboard **511**, a mouse **512**, and a digital versatile disc (DVD) drive **514**.

(32) The CPU **501** is an arithmetic device that controls operations of the entire master PC **10**. The ROM **502** is a nonvolatile storage device that stores a program such as an initial program loader (IPL) that is executed by the CPU **501** initially. The RAM **503** is a volatile storage device used as a work area for the CPU **501**.

(33) The auxiliary storage device **505** is a nonvolatile storage device that stores various kinds of data such as a program. The auxiliary storage device **505** is, for example, a hard disk drive (HDD) or a solid state device (SSD).

(34) The medium drive **507** is a device that controls reading of data from or writing of data to a recording medium **506** such as a flash memory.

(35) The display **508** is a liquid crystal display (LCD), an organic electroluminescence (EL) display, or the like that displays various kinds of information such as a cursor, a menu, a window, characters, or an image.

(36) The network I/F **509** is an interface for performing data communication via the network **N**. The network I/F **509** is, for example, a network interface card (NIC) that enables communication according to Transmission Control Protocol/Internet Protocol (TCP/IP). The network I/F **509** may be a communication interface having a wireless communication function based on a standard such as Wi-Fi®.

(37) The keyboard **511** is an example of an input device including a plurality of keys with which characters, numerical values, or various instructions are input. The mouse **512** is an example of an input device with which any of various instructions is selected or executed, a target of processing is selected, or a cursor is moved, for example.

(38) The DVD drive **514** is a device that controls reading of various kinds of data from or writing of various kinds of data to a DVD **513** that is an example of a removable storage medium. The DVD **513** is, for example, a digital versatile disc-rewritable (DVD-RW) or a digital versatile disc-recordable (DVD-R). The DVD **513** may be a compact disc-rewritable (CD-RW) or a compact disc-recordable (CD-R). In such case, the DVD drive **514** may be implemented by a CD drive.

(39) The CPU **501**, the ROM **502**, the RAM **503**, the auxiliary storage device **505**, the medium drive **507**, the display **508**, the network I/F **509**, the keyboard **511**, the mouse **512**, and the DVD drive **514** are communicably coupled to one another by a bus line **510** including an address bus, a data bus, and the like.

(40) The hardware configuration of the master PC **10** illustrated in FIG. **3** is an example. The master PC **10** does not necessarily include all the constituent devices or may include another

constituent device. The servers **20** and the PCs **30** each have a hardware configuration substantially the same as the hardware configuration illustrated in FIG. **3**.

(41) Configuration and Operation of Functional Blocks of Master PC

(42) FIG. **4** is a diagram illustrating an example of a configuration of functional blocks of the master PC according to the embodiment. A description is given of a configuration and an operation of the functional blocks of the master PC **10** according to the embodiment with reference to FIG. **4**.

(43) As illustrated in FIG. **4**, the master PC **10** includes a communication unit **101**, a communication speed measurement unit **102** (an example of measurement unit), a determination unit **103**, and a notification unit **104**.

(44) The communication unit **101** is a functional unit that performs data communication with the servers **20** and the PCs **30**. The communication unit **101** is implemented, for example, by the network I/F **509** illustrated in FIG. **3** and by execution of a program by the CPU **501** illustrated in FIG. **3**.

(45) The communication speed measurement unit **102** is a functional unit that measures communication speeds of the respective servers **20** and communication speeds of the respective PCs **30**. For example, the communication speed measurement unit **102** may measure actual communication speeds between the master PC **10** and the respective servers **20** and between the master PC **10** and the respective PCs **30**. The communication speed measurement unit **102** measures communication speeds between the servers **20** and the PCs **30** from the communication speeds of the respective servers **20** and the communication speeds of the respective PCs **30**. For example, the communication speed measurement unit **102** may predict communication speeds between the servers **20** and the PCs **30**, based on the communication speeds of the respective servers **20** and the communication speeds of the respective PCs **30**. The communication speed measurement unit **102** may regard, as the communication speed between one server **20** among the servers **20** and one PC **30** among the PCs **30**, a slower communication speed of the communication speed of the one server **20** and the communication speed of the one PC **30**. The communication speed measurement unit **102** is implemented, for example, by execution of a program by the CPU **501** illustrated in FIG. **3**.

(46) The determination unit **103** is a functional unit that determines, for each of the PCs **30**, the server **20** that is to be a communication counterpart of the PC **30**, that is, the server **20** which the PC **30** is to communicate with, based on at least one of the communication speeds (first communication speeds) of the respective servers **20** measured by the communication speed measurement unit **102**, the communication speeds (second communication speeds) of the respective PCs **30**, or the communication speeds (third communication speeds) between the servers **20** and the PCs **30**. The determination unit **103** is implemented, for example, by execution of a program by the CPU **501** illustrated in FIG. **3**.

(47) The notification unit **104** is a functional unit that notifies, via the communication unit **101**, each of the PCs **30** of information on the server **20** determined to be the communication counterpart of the PC **30** by the determination unit **103**. The notification unit **104** is implemented, for example, by execution of a program by the CPU **501** illustrated in FIG. **3**.

(48) The implementation of the communication speed measurement unit **102**, the determination unit **103**, and the notification unit **104** of the master PC **10** illustrated in FIG. **4** is not limited to implementation by execution of the respective programs by the CPU **501** illustrated in FIG. **3**. For example, the communication speed measurement unit **102**, the determination unit **103**, and the notification unit **104** of the master PC **10** illustrated in FIG. **4** may be implemented by hardware such as an integrated circuit or by a combination of software and hardware.

(49) The functional units of the master PC **10** illustrated in FIG. **4** are conceptually presented functions, and are not limited to such a configuration. For example, a plurality of functional units illustrated as independent functional units of the master PC **10** in FIG. **4** may be configured as a single functional unit. Conversely, the function of a single functional unit of the master PC **10**

illustrated in FIG. 4 may be divided and configured as a plurality of functional units.

(50) Each of the servers **20** or each of the PCs **30** may include the communication speed measurement unit **102**, the determination unit **103**, and the notification unit **104** included in the master PC **10**. This allows the information processing system **1** to be built without preparing the master PC **10** that is an information processing apparatus different from the servers **20** and the PCs **30**.

(51) Operation of Grouping PCs Permitted to Communicate with Server in Accordance with Communication Speeds of PCs

(52) FIG. 5 is a diagram for describing an operation of grouping PCs permitted to communicate with a server in accordance with communication speeds of the respective PCs in the information processing system according to the embodiment. FIG. 6 is a diagram for describing an example of a result of grouping the PCs permitted to communicate with the server in accordance with the communication speeds of the respective PCs in the information processing system according to the embodiment. With reference to FIGS. 5 and 6, a description is given of the operation of grouping the PCs **30** permitted to communicate with the server **20** in accordance with the communication speeds of the respective PCs **30** in the information processing system **1** according to the embodiment.

(53) In FIG. 5, the server **20** has a narrow communication band. Thus, the number of PCs **30** permitted to concurrently communicate with the server **20** is limited to two. The time in seconds indicating the communication speed in FIG. 5 represents, for example, a time taken to complete downloading of certain data.

(54) As illustrated in FIG. 5, the communication speed measurement unit **102** of the master PC **10** measures the communication speed of the PC **30a** as 20 seconds, measures the communication speed of the PC **30b** as 30 seconds, measures the communication speed of the PC **30c** as 40 seconds, and measures the communication speed of the PC **30d** as 50 seconds. In this case, to optimize the time taken to complete downloading of the certain data from the servers **20**, the determination unit **103** of the master PC **10** puts the PCs **30a** and **30d** in a group A and puts the PCs **30b** and **30c** in a group B as illustrated in FIG. 6.

(55) This makes the time taken by the PCs **30a** and **30d** to download the certain data from the server **20** equal to 70 seconds and makes the time taken by the PCs **30b** and **30c** to download the certain data from the server **20** equal to 70 seconds. Thus, the time taken for downloading in the entire information processing system **1** is successfully minimized. Consequently, a decrease in communication speed of the entire information processing system **1** is successfully suppressed.

(56) Operation of Grouping PCs to Communicate with Each Server in Accordance with Communication Speeds of Servers

(57) FIG. 7 is a diagram for describing an operation of grouping PCs that are to communicate with each of servers in accordance with communication speeds of the respective servers in the information processing system according to the embodiment. With reference to FIG. 7, a description is given of an operation of grouping the PCs **30** that are to communicate with each of the servers **20** in accordance with the communication speeds of the respective server **20** in the information processing system **1** according to the embodiment. In FIG. 7, seven PCs **30** (PCs **30a** to **30g**) access the servers **20a** and **20b**. The time in seconds indicating the communication speed in FIG. 7 represents, for example, a time taken to complete downloading of certain data.

(58) As illustrated in FIG. 7, the communication speed measurement unit **102** measures the communication speed of the server **20a** as 30 seconds and measures the communication speed of the server **20b** as 40 seconds. In this case, to optimize the time taken to complete downloading of the certain data from the servers **20**, the determination unit **103** determines that the PCs **30a** to **30d** are to communicate with the server **20a** and the PCs **30e** to **30g** are to communicate with the server **20b** as illustrated in FIG. 7. The notification unit **104** notifies each of the PCs **30a** to **30d** of information on the server **20a** that is the communication counterpart and notifies each of the PCs

30e to **30g** of information on the server **20b** that is the communication counterpart.

(59) This makes the time taken for downloading from the server **20a** equal to $30 \text{ seconds} \times 4 = 120$ seconds and makes the time taken for downloading from the server **20b** equal to $40 \text{ seconds} \times 3 = 120$ seconds. Thus, the time taken for downloading in the entire information processing system **1** is successfully minimized. Consequently, when the plurality of PCs **30** access the plurality of servers **20**, a decrease in communication speed of the entire information processing system **1** is successfully suppressed.

(60) Operation of Grouping PCs to Communicate with Each Server in Accordance with Communication Speeds between Servers and PCs

(61) FIG. **8** is a diagram for describing an operation of grouping PCs that are to communicate with each of servers in accordance with communication speeds between the servers and the PCs in the information processing system according to the embodiment. FIG. **9** is a diagram for describing an example of obtained communication speeds between the servers and the PCs in the information processing system according to the embodiment. FIG. **10** is a diagram for describing an example of a result of grouping the PCs that are to communicate with each of the servers in accordance with the communication speeds between the servers and the PCs in the information processing system according to the embodiment. With reference to FIGS. **8** to **10**, a description is given of an operation of grouping the PCs **30** that are to communicate with each of the servers **20** in accordance with communication speeds between the servers **20** and the PCs **30** in the information processing system **1** according to the embodiment. In FIG. **8**, seven PCs **30** (PCs **30a** to **30g**) access the servers **20a** and **20b**. The time in seconds indicating the communication speed in FIGS. **8** to **10** represents, for example, a time taken to complete downloading of certain data.

(62) The communication speed measurement unit **102** measures communication speeds of the PCs **30a** to **30g** and communication speeds of the servers **20a** and **20b**, and based on these communication speeds, measures communication speeds between the servers **20** and the PCs **30**. As a result, the communication speeds between the servers **20** and the PCs **30** are different from one another in the examples illustrated in FIGS. **8** and **9**. For example, the communication speeds between the server **20a** and the PCs **30a**, **30b**, **30c**, **30d**, **30e**, **30f**, and **30g** are 50 seconds, 60 seconds, 70 seconds, 80 seconds, 90 seconds, 100 seconds, and 110 seconds, respectively. In this case, to optimize the time taken to complete downloading of the certain data from the servers **20a** and **20b**, the determination unit **103** assigns the PCs **30** to the servers **20a** and **20b** so that the time taken by the seven PCs **30** to download the certain data from the servers **20a** and **20b** is minimized. For example, the determination unit **103** determines that the PCs **30b**, **30c**, and **30e** are to communicate with the server **20a** and the PCs **30a**, **30d**, **30f**, and **30g** are to communicate with the server **20b** as illustrated in FIG. **10**. The notification unit **104** notifies each of the PCs **30b**, **30c**, and **30e** of information on the server **20a** that is the communication counterpart and notifies each of the PCs **30a**, **30d**, **30f**, and **30g** of information on the server **20b** that is the communication counterpart.

(63) This makes the time taken for downloading from the server **20a** equal to $60 \text{ seconds} + 70 \text{ seconds} + 90 \text{ seconds} = 220 \text{ seconds}$ and makes the time taken for downloading from the server **20b** equal to $20 \text{ seconds} + 50 \text{ seconds} + 70 \text{ seconds} + 80 \text{ seconds} = 220 \text{ seconds}$. Thus, the times taken for downloading from the servers **20a** and **20b** are equal to each other, and the time taken for downloading in the entire information processing system **1** is successfully minimized.

Consequently, when the plurality of PCs **30** access the plurality of servers **20**, a decrease in communication speed of the entire information processing system **1** is successfully suppressed.

(64) Operation of Changing PCs to Communicate with Each Server in Accordance with Changes in Communication Speeds Over Time

(65) FIG. **11** is a diagram for describing an operation of changing PCs that are to communicate with each of servers in accordance with changes in communication speeds of the respective PCs over time in the information processing system according to the embodiment. With reference to FIG. **11**, a description is given of an operation of changing the PCs **30** that are to communicate with

each of the servers **20** in accordance with changes in communication speeds of the respective PCs **30** over time. In FIG. **11**, eight PCs **30** (PCs **30a** to **30h**) access the servers **20a** and **20b**. (66) For example, the communication speed measurement unit **102** measures a communication speed of each of the PCs **30** at certain time intervals (for example, at intervals of 5 seconds). The determination unit **103** determines the rankings of the communication speeds measured by the communication speed measurement unit **102** at the certain time intervals. FIG. **11** illustrates the rankings of the communication speeds between the servers **20** and the respective PCs **30** that change over time at intervals of 5 seconds. In FIG. **11**, “1” indicates the highest communication speed, and “8” indicates the lowest communication speed. The determination unit **103** changes assignment of the PCs **30** to the servers **20** and **20b** at the certain time intervals such that the sum of the communication speeds of the PCs **30** whose communication counterpart is the server **20a** is equal to the sum of the communication speeds of the PCs **30** whose communication counterpart is the server **20b**. In the example illustrated in FIG. **11**, the determination unit **103** assigns the PCs **30** with the communication speed rankings “1”, “3”, “5”, and “7” to the server **20a**, and assigns the PCs **30** with the communication speed rankings “2”, “4”, “6”, and “8” to the server **20b**. The term “equal” does not indicate that the sums of the communication speeds are strictly equal to each other but rather indicates a concept including a case where the sums are equal to and substantially equal to each other. The notification unit **104** notifies each of the PCs **30** of information on the server **20** assigned by the determination unit **103**.

(67) In the example illustrated in FIG. **11**, the determination unit **103** assigns the four PCs **30** to each of the servers **20a** and **20b** based on the communication speed rankings. However, the manner in which the PCs **30** are assigned is not limited to assigning the same number of PCs **30** to each server. Thus, the number of PCs **30** assigned to each of the servers **20** is not limited to any number as long as the sums of the communication speeds are “equal” to each other. In the example illustrated in FIG. **11**, the PCs **30** are assigned to each of the servers **20** based on the communication speeds of the PCs **30** measured by the communication speed measurement unit **102**. However, the criteria used in the assigning is not limited to the communication speeds of the PCs **30**, and the PCs **30** may be assigned to each of the servers **20** based on the communication speeds of the servers **20** measured by the communication speed measurement unit **102** or based on the communication speeds between the servers **20** and the PCs **30** measured by the communication speed measurement unit **102**.

(68) As described above, assignment of the PCs **30** is changed in accordance with the changes in the communication speeds over time such that the times taken for downloading from the respective servers **20a** and **20b** are “equal” to each other. Thus, the time taken for downloading in the entire information processing system **1** is successfully minimized. Consequently, when the plurality of PCs **30** access the plurality of servers **20**, a decrease in communication speed of the entire information processing system **1** is successfully suppressed.

(69) As described above, in the master PC **10** according to the embodiment, the communication speed measurement unit **102** measures at least one of communication speeds of the respective servers **20** or communication speeds of the respective PCs **30**, the determination unit **103** determines the corresponding server **20** that is to be a communication counterpart of each of the PCs **30** based on at least one of the communication speeds of the respective servers **20** or the communication speeds of the respective PCs **30**, and the notification unit **104** notifies each of the PCs **30** of the corresponding server **20** determined to be the communication counterpart by the determination unit **103**. Thus, when the plurality of PCs **30** access the plurality of servers **20**, a decrease in communication speed of the entire information processing system **1** is successfully suppressed.

(70) Each of the functions of the above-described embodiment can be implemented by one or more processing circuits. Herein, examples of the “processing circuits” include a processor programmed to implement the functions based on software such as a processor implemented by an electronic

circuit, and devices such as an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field-programmable gate array (FPGA), and a circuit module of the related art that are designed to implement the functions described above.

(71) The programs executed by the master PC **10** in the above-described embodiment may be preinstalled in the ROM or the like and provided to the master PC **10**.

(72) The programs executed by the master PC **10** in the above-described embodiment may be stored as a file in an installable format or an executable format on a computer-readable recording medium such as a CD-ROM, a flexible disk (FD), a CD-R, or a DVD and may be provided as a computer program product.

(73) The programs executed by the master PC **10** in the above-described embodiment may be stored on a computer connected to a network such as the Internet and may be downloaded via the network and provided to the master PC **10**. The programs executed by the master PC **10** in the above-described embodiment may be provided or distributed via a network such as the Internet.

(74) The programs executed by the master PC **10** in the above-described embodiment have a module configuration including the functional units described above. The CPU (processor) that is actual hardware reads the programs from the ROM and executes the program, so that the functional units described above are loaded to a main storage device and are generated in the main storage device.

(75) In one embodiment, an information processing method includes measuring at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals; determining, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds; and notifying each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal.

(76) The above-described embodiments are illustrative and do not limit the present invention. Thus, numerous additional modifications and variations are possible in light of the above teachings. For example, elements and/or features of different illustrative embodiments may be combined with each other and/or substituted for each other within the scope of the present invention. Any one of the above-described operations may be performed in various other ways, for example, in an order different from the one described above.

(77) The functionality of the elements disclosed herein may be implemented using circuitry or processing circuitry which includes general purpose processors, special purpose processors, integrated circuits, application specific integrated circuits (ASICs), digital signal processors (DSPs), field programmable gate arrays (FPGAs), conventional circuitry and/or combinations thereof which are configured or programmed to perform the disclosed functionality. Processors are considered processing circuitry or circuitry as they include transistors and other circuitry therein. In the disclosure, the circuitry, units, or means are hardware that carry out or are programmed to perform the recited functionality. The hardware may be any hardware disclosed herein or otherwise known which is programmed or configured to carry out the recited functionality. When the hardware is a processor which may be considered a type of circuitry, the circuitry, means, or units are a combination of hardware and software, the software being used to configure the hardware and/or processor.

Claims

1. An information processing apparatus comprising: circuitry configured to measure at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals, determine, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds, notify each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal, measure the first communication speeds and the one or more second communication speeds, measure third communication speeds between the plurality of servers and the one or more information terminals, based on the first communication speeds and the one or more second communication speeds, and determine, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the third communication speeds.
2. The information processing apparatus according to claim 1, wherein the circuitry is further configured to: measure at least the one or more second communication speeds, and determine, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the one or more second communication speeds.
3. The information processing apparatus according to claim 1, wherein the circuitry is further configured to: measure at least the first communication speeds, and determine, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the first communication speeds.
4. The information processing apparatus according to claim 1, wherein the circuitry is further configured to: change assignment of the one or more information terminals to the plurality of servers in accordance with at least one of changes in the first communication speeds over time or changes in the one or more second communication speeds over time.
5. The information processing apparatus according to claim 1, wherein the circuitry is further configured to: measure at least one of the first communication speeds or the one or more second communication speeds, based on respective times for uploading data.
6. An information processing system comprising: the information processing apparatus according to claim 1; the plurality of servers; and the one or more information terminals.
7. An information processing system comprising: circuitry configured to measure at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals, determine, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds, and notify each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal, measure the first communication speeds and the one or more second communication speeds, measure third communication speeds between the plurality of servers and the one or more information terminals, based on the first communication speeds and the one or more second communication speeds, and determine, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more

information terminals, based on the third communication speeds.

8. The information processing system according to claim 7, wherein the circuitry is further configured to: measure at least the one or more second communication speeds, and determine, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the one or more second communication speeds.

9. The information processing system according to claim 7, wherein the circuitry is further configured to: measure at least the first communication speeds, and determine, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the first communication speeds.

10. The information processing system according to claim 7, wherein the circuitry is further configured to: change assignment of the one or more information terminals to the plurality of servers in accordance with at least one of changes in the first communication speeds over time or changes in the one or more second communication speeds over time.

11. The information processing system according to claim 7, wherein the circuitry is further configured to: measure at least one of the first communication speeds or the one or more second communication speeds, based on respective times for uploading data.

12. A non-transitory recording medium which stores a plurality of instructions, when executed by one or more processors, causes the processors to perform an information processing method comprising: measuring at least one of first communication speeds of a plurality of servers that store identical data or one or more second communication speeds of one or more information terminals that access the identical data in at least one of the plurality of servers, each of the first communication speeds corresponding to a respective one of the plurality of servers, each of the one or more second communication speeds corresponding to a respective one of the one or more information terminals; determining, from among the plurality of servers, a corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on at least one of the first communication speeds or the one or more second communication speeds; notifying each of the one or more information terminals of the corresponding server determined to be the communication counterpart of the information terminal; measuring the first communication speeds and the one or more second communication speeds; measuring third communication speeds between the plurality of servers and the one or more information terminals, based on the first communication speeds and the one or more second communication speeds; and determining, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the third communication speeds.

13. The non-transitory recording medium according to claim 12, wherein the information processing method further comprises: measuring at least the one or more second communication speeds; and determining, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the one or more second communication speeds.

14. The non-transitory recording medium according to claim 12, wherein the information processing method further comprises: measuring at least the first communication speeds, and determining, from among the plurality of servers, the corresponding server that is to be a communication counterpart of each of the one or more information terminals, based on the first communication speeds.

15. The non-transitory recording medium according to claim 12, wherein the information processing method further comprises: changing assignment of the one or more information terminals to the plurality of servers in accordance with at least one of changes in the first communication speeds over time or changes in the one or more second communication speeds over time.

16. The non-transitory recording medium according to claim 12, wherein the information

processing method further comprises: measuring at least one of the first communication speeds or the one or more second communication speeds, based on respective times for uploading data.
