

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402769
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Bian; Zhuang et al.

Wet-and-dry floor brush for vacuum cleaner

Abstract

A wet-and-dry floor brush for a vacuum cleaner, including a floor brush body including at least one dust suction port at a bottom of the floor brush body, and a wet mopping device including a base plate for mounting a mop cloth, and a liquid supply tank located on an upper side of the base plate, the base plate including liquid discharge holes, and the liquid supply tank includes an air inlet in communication with the outside. The bottom of the liquid supply tank has a liquid outlet in fluid communication with liquid discharge holes. The liquid outlet includes a valve for opening and closing the liquid outlet, and the liquid supply tank includes an external action member, the action member and valve configured to allow the transmission of motion to open or close the liquid outlet by operating the action member.

Inventors:	Bian; Zhuang (Jiangsu, CN), Bodin; Pierre-Louis (Vernon, FR)
Applicant:	SEB S.A. (Ecully, FR)
Family ID:	69063789
Assignee:	SEB S.A. (N/A, FR)
Appl. No.:	17/618052
Filed (or PCT Filed):	December 20, 2019
PCT No.:	PCT/EP2019/086591
PCT Pub. No.:	WO2020/249248
PCT Pub. Date:	December 17, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220304537 A1	Sep. 29, 2022

Foreign Application Priority Data

Publication Classification

Int. Cl.: A47L11/40 (20060101); A47L5/12 (20060101)

U.S. Cl.:

CPC A47L11/4083 (20130101); A47L5/12 (20130101); A47L11/4088 (20130101);

Field of Classification Search

CPC: A47L (2501/01); A47L (2501/02); A47L (11/30); A47L (11/34); A47L (11/201); A47L (11/408); A47L (11/4083); A47L (11/4088); A47L (13/20); A47L (13/22); A47L (13/23); A47L (13/24); A47L (13/26); A47L (13/42)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1527224	12/1924	Riordan	N/A	N/A
6733199	12/2003	Dingert	401/1	A47L 13/22
11937752	12/2023	Shin	N/A	A47L 11/4069
2003/0051310	12/2002	Morgan	15/412	A47L 5/28
2004/0111822	12/2003	Syu	15/321	A47L 5/365
2016/0120388	12/2015	Liu	15/322	A47L 13/225
2017/0202421	12/2016	Hwang	N/A	A47L 13/26
2017/0231454	12/2016	Kingma et al.	N/A	N/A
2019/0328200	12/2018	Ko	N/A	A47L 11/2025

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1387818	12/2002	CN	A47L 11/03
105686771	12/2015	CN	A47L 13/225
107072460	12/2016	CN	N/A
102006061193	12/2007	DE	N/A
102006061192	12/2007	DE	N/A
1224899	12/2001	EP	N/A
3366182	12/2017	EP	N/A
58165558	12/1982	JP	N/A
2006102052	12/2005	JP	N/A
20100003536	12/2009	KR	A47L 11/16
101671116	12/2015	KR	A47L 11/34
2008096949	12/2007	WO	N/A

OTHER PUBLICATIONS

WIPO Translation DE 102006061193; Hard Floor Nozzle for Vacuum-Cleaning and Wiping of Hard Floor, Has Control Unit Permitting or Preventing Supply of Liquid to Wiper Depending on Operation of Nozzle During Operation Process of Suction of Low Pressure; Marko, Geis; Apr. 17, 2008 (Year: 2008). cited by examiner

PE2E Translation KR 101671116; Cleaner and Water Cleaning Device; Pyeong, Ji Heon; Oct. 31, 2016 (Year: 2016). cited by examiner

Description JPS58165558A Espacenet; Air Supply Mechanism for Liquid Tank; Sep. 30, 1983 (Year: 1983). cited by examiner

PE2E Translation CN-1387818; Device and Method for Cleaning Surfaces; Bauman, RW; Jan. 1, 2003 (Year: 2003). cited by examiner

PE2E Translation KR-20100003536; Multi-Purpose Cleaner; Apr. 1, 2010 (Year: 2010). cited by examiner

CN-105686771 Espacenet Translation; Surface Cleaning Device; Bian, Zhuang; Jun. 22, 2016 (Year: 2016). cited by examiner

International Search Report for Application No. PCT/EP2019/086591 mailed Apr. 9, 2020, pp. 1-3. cited by applicant

Primary Examiner: Keller; Brian D

Assistant Examiner: Full; Sidney D

Attorney, Agent or Firm: Lerner David LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is a national phase entry under 35 U.S.C. § 371 of International Application No. PCT/EP2019/086591 filed Dec. 20, 2019, which claims priority from Chinese Application Nos. 201910504305.9 and 201920874703.5, both filed on Jun. 12, 2019, all of which are incorporated herein by reference.

FIELD OF THE INVENTION

(2) The present invention relates to the technical field of cleaning equipment, and in particular to a wet-and-dry floor brush for a vacuum cleaner.

BACKGROUND OF THE INVENTION

(3) In daily life, vacuum cleaners are generally used for sucking particulate matter such as dust on floors to be cleaned, and are particularly suitable for cleaning rough floors, for example, for cleaning indoor carpets, wooden floors, etc. For the cleaning of smooth floors, such as floor tiles and ceramic tiles, cleaning mops are generally used to wipe the smooth floors with wet mop cloth to remove stains from the surface of the smooth floors. Such a cleaning approach inevitably requires a user to replace the cleaning tool multiple times to realize the cleaning operation of the surface to be cleaned, which is cumbersome to operate.

(4) In order to solve the above-mentioned technical problem, Chinese invention patent application with the publication number of CN 107072460A discloses a floor cleaning device capable of achieving a wet cleaning function by wetting a surface to be cleaned with a liquid while collecting dust. The device is provided with a liquid containing system which comprises an outlet having a plurality of openings to allow the liquid to be drawn by a capillary force when a mop base such as

cloth is mounted against the plurality of openings, and the liquid containing system is substantially closed except for the plurality of openings after filling. Since in the liquid containing system, the liquid is applied to the floor completely relying on the capillary force of the cloth, the cloth must be removed after completing the cleaning operation, otherwise the liquid will continue to be applied to the floor, causing the floor to be wet.

SUMMARY OF THE INVENTION

(5) In order to achieve the above object of the present invention, the present invention adopts the following technical solutions: a wet-and-dry floor brush for a vacuum cleaner, comprising: a floor brush body provided with at least one dust suction port at the bottom; and a wet mopping device comprising a base plate for having mop cloth mounted thereto, and a liquid supply tank located on an upper side of the base plate for supplying a cleaning liquid to the mop cloth, the base plate being provided with a number of liquid discharge holes, the liquid supply tank being provided with an air inlet in communication with the outside, and the bottom of the liquid supply tank being provided with a liquid outlet in fluid communication with the liquid discharge holes; the liquid outlet is provided with a valve for opening and closing the liquid outlet, and the liquid supply tank is externally provided with an action member which is operable by a user, the action member and the valve being disposed in a manner allowing the transmission of motion such that the user is able to open or close the liquid outlet by operating the action member.

(6) In the above technical solution, preferably, the base plate is provided with a cavity having a volume smaller than that of the liquid supply tank, and the liquid outlet, the cavity and the number of liquid discharge holes are in communication with one another in sequence.

(7) In a preferred embodiment, the base plate is provided with a venting pipe connecting the cavity with the liquid supply tank. The venting pipe protrudes from an upper surface of the base plate and up to higher than the maximum fill level of liquid in the liquid supply tank, so as to vent the air existing in the cavity when the liquid enters the cavity via the liquid outlet.

(8) In a preferred embodiment, the cavity is provided with at least one internal wall which reduces the volume of the cavity and thus reduces the latency to fill the cavity with water when the drain valve is actuated to its open position. The internal walls are, for example, at least one longitudinal projection protruding inside the cavity.

(9) In the above technical solution, preferably, the base plate has a detachable portion in which the cavity is formed.

(10) In the above technical solution, preferably, the number of liquid discharge holes are also provided in the detachable portion.

(11) In the above technical solution, preferably, the action member is a rotating member or a movable member.

(12) In the above technical solution, preferably, the action member is provided at the top of the liquid supply tank.

(13) In the above technical solution, preferably, the wet mopping device is detachably mounted to the floor brush body.

(14) In the above technical solution, preferably, the base plate and the liquid supply tank are integrally formed.

(15) In the above technical solution, preferably, the base plate is located at the bottom of the floor brush body, and the liquid supply tank is detachably mounted at the top of the floor brush body.

(16) In the above technical solution, preferably, the base plate is detachably mounted at the bottom of the floor brush body.

(17) In a preferred embodiment, the base plate is provided with at least one locking element which cooperates with a corresponding locker arranged on the floor brush body so as to lock the base plate with the floor brush body. The locking element is for example a hook. The base plate is preferably provided with two locking elements and more preferably with four. The locking elements may be integrally formed with the base plate or attached thereto.

- (18) In the above technical solution, preferably, the dust suction port is one in number and is located at a front portion of the floor brush body, and the base plate is located behind the dust suction port.
- (19) In the above technical solution, preferably, the bottom of the floor brush body is provided with a pair of dust suction ports, the pair of dust suction ports being respectively located on the front side and the rear side of the floor brush body, and the base plate is located between the pair of dust suction ports.
- (20) In the above technical solution, preferably, the top of the liquid supply tank is provided with a liquid filling port, and a tank cap is arranged at the liquid filling port, the tank cap being provided with an air inlet which communicates the outside with the interior of the liquid supply tank.
- (21) Alternatively and preferably, the top of the liquid supply tank is provided with a liquid filling port, a tank cap being arranged at the liquid filling port and comprising an air inlet open towards the interior of the liquid supply tank and an air opening open towards the outside of the liquid supply tank, the tank cap comprises a chicane shape formed by at least one baffle and forming an air inlet channel extending inside the tank cap from the air inlet to the air opening. The chicane shape constitutes an obstacle on the way from the interior of the liquid supply tank to the outside, so that water cannot leak outwards when the water tank is tilted.
- (22) In the above technical solution, preferably, the tank cap comprises a cover part and a lining part that is mounted to the cover part.
- (23) In the above technical solution, preferably, the cover part comprises said chicane shape.
- (24) In the above technical solution, preferably, at least one of the baffles is hollowed to define an intermediate air opening in the air inlet channel.
- (25) In a preferred embodiment, a cam surface is formed at a top portion of the valve plug to lock the drain valve in the closed or open position. To close the valve, the end of a lever arm of the action member should be forced to pass through the cam surface to push the valve plug in an axial direction against a spring force that tends to urge the valve plug upwards. Conversely, to open the valve, the end of the lever arm of the action member should be forced to pass through the cam surface.
- (26) In a preferred embodiment, the valve is provided with two sealings, a lower one formed by an O-ring for radial sealing and an upper one formed by a washer with axial lip for axial sealing, in order to reduce the effort needed to operate the plug of the valve.
- (27) Compared with the prior art, the present invention achieves the following beneficial effects: in the wet-and-dry floor brush of this application, a valve is provided at the liquid outlet of the liquid supply tank, and an action member for controlling the action of the valve is provided outside the liquid supply tank, such that the user can open or close the liquid outlet by operating the action member, and therefore, the user can close the liquid outlet of the liquid supply tank in a timely manner after using the floor brush to prevent the liquid from continuously flowing to the floor.
-

Description

DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic perspective view of the present invention;
- (2) FIG. 2 is a schematic exploded view of the present invention;
- (3) FIG. 3 is a schematic top view of a wet mopping device of the present invention;
- (4) FIG. 4 is a first schematic cross-sectional structural view of the wet mopping device of the present invention (after the user operates the action member in one direction, the valve closes the liquid outlet at the bottom of the liquid supply tank);
- (5) FIG. 5 is a second schematic cross-sectional structural view of the wet mopping device of the present invention (after the user operates the action member in the other direction, the valve opens

the liquid outlet at the bottom of the liquid supply tank);

(6) FIG. 6 is a schematic perspective view of another embodiment of the wet mopping device of the present invention;

(7) FIG. 7 is a cross-sectional structural view of the wet mopping device as shown in FIG. 6;

(8) FIG. 8 is a schematic exploded view of the liquid filling part of the wet mopping device as shown in FIG. 6;

(9) FIG. 9 is a schematic side view of the wet mopping device as shown in FIG. 6.

(10) wherein: **11**. Floor brush body; **111**. Dust suction port; **112**. Suction passage; **113**. Rotary connector; **12**. Wet mopping device; **121**. Base plate; **122**. Liquid supply tank; **123**. Liquid discharge hole; **124**. Cavity; **125**. Liquid outlet; **126**. tank cap; **127**. Liquid filling port; **128**. Air inlet; **129**. Action member; **130**. Valve; **131**. Plug; **132**. Spring; **133**. Rotating shaft; **134**. Sealing ring; **135**. Check valve; **136**. Mounting hole; **142**. Cover part; **146**. Lining part. **22**. Locking element; **24**. Venting pipe; **26**. Internal wall; **32**. Fixing hole; **33**. Screw hole; **36**. Chicane shape; **361**. Inner skirt; **362**. Ribs; **363**. intermediate air opening; **364**. first notch; **37**. Outer skirt; **373**. block; **374**. second notch; **38**. Air inlet; **41**. Cam surface; **42**. First edge; **43**. Protrusion; **44**. Second edge; **34**. Upper sealing ring; **50**. Lever arm.

DETAILED DESCRIPTION OF THE INVENTION

(11) The technical content, structural features, achieved objects and effects of the present invention will be described in detail below with reference to the embodiments and the accompanying drawings. The positional relationships of upper, lower, left, right, front, and rear described in this embodiment correspond to the respective positional relationships shown in FIG. 1, respectively.

(12) As shown in FIGS. 1 and 2, a wet-and-dry floor brush comprises a floor brush body **11** movable on a floor to be cleaned, a rotary connector **113** connected to the floor brush body **11**, a suction passage **112**, and a wet mopping device **12** fixedly mounted to the floor brush body **11**. A part of the suction passage **112** is received within the floor brush body **11**, and the other part thereof is provided on the rotary connector **113**. The bottom of the floor brush body **11** is provided with two dust suction ports **111** opposite in the front and rear direction. When the wet-and-dry floor brush is applied to a vacuum cleaner, the wet mopping device **12** is located between the two dust suction ports **111**, and the wet-and-dry floor brush is connected to the main body portion of the vacuum cleaner via the rotary connector **113**, for example, to a suction unit on the vacuum cleaner by means of a hard tube or a hose. The suction passage **112** can suck in particulate matter such as dust on the floor to be cleaned through the dust suction ports **111** by means of a suction force of the suction unit. Of course, it is also possible to provide only one dust suction port **111** at the front portion of the floor brush body **11**, and the dust suction port **111** is located in front of the wet mopping device **12**, that is, the function of first dusting and then mopping can be realized.

(13) As shown in FIGS. 3 and 4, the wet mopping device **12** comprises a base plate **121** for having mop cloth mounted thereto, and a liquid supply tank **122**. A lower portion of the liquid supply tank **122** is of an opening structure, and the base plate **121** is fixedly mounted at the lower portion of the liquid supply tank **122**, and closes the lower opening of the liquid supply tank **122**, so that the liquid supply tank **122** and the base plate **121** enclose a liquid storage chamber. Of course, in order to facilitate injection molding, the base plate **121** and the liquid supply tank **122** may also be integrally formed.

(14) In order to facilitate the user to add cleaning water, the wet mopping device **12** is to detachably mounted to the floor brush body **11**. Specifically, the liquid supply tank **122** has two housing portions opposite each other in the left and right direction, and a connection portion connected to the two housing portions, and the connection portion is of a hollow structure and is integrally formed with the two housing portions. The space between the two housing portions forms a snap groove, and the floor brush body **11** has a snap-in portion adapted to the snap groove, such that when the wet mopping device **12** is mounted to the floor brush body **11**, the snap-in portion of the floor brush body **11** is located in the snap groove of the wet mopping device **12**, and the liquid

supply tank **122** is located at the top of the floor brush body **11**.

(15) Of course, in order to facilitate the installation of the mop cloth, it is not necessary to completely detach the wet mopping device **12** from the floor brush body **11**; instead, it is only necessary that the liquid supply tank **122** is fixed to the floor brush body **11**, and the base plate **121** is detachably provided at the bottom of the liquid supply tank **122**. Specifically, the base plate **121** is connected to the liquid supply tank **122** in a snap-fit manner, wherein a lower edge of a side wall plate of the liquid supply tank **122** constitutes a connection portion, the base plate **121** is provided with a connection groove arranged in a circumferential direction and adapted to the lower edge of the side wall plate of the liquid supply tank **122**, and a waterproof sealing strip is provided in the connection groove.

(16) The base plate **121** is of an inner hollow structure, and its hollow interior forms a cavity **124**. A lower side wall plate of the base plate **121** is provided with a plurality of liquid discharge holes **123**, the side wall plate of the liquid supply tank **122** is provided with a liquid outlet **125**, and the liquid storage chamber, the liquid outlet **125**, the cavity **124**, and the liquid discharge holes **123** are in fluid communication with one another in sequence. In this way, the cleaning water in the liquid supply tank **122** can flow into the cavity **124** through the liquid outlet **125**, and then to each of the liquid discharge holes **123** from the cavity **124**. Of course, in order to facilitate the disassembly and assembly and for the convenience of cleaning, the base plate **121** may also be provided with a detachable portion in which the cavity **124** is formed.

(17) In order to facilitate the cleaning water in the liquid storage chamber easily flowing to the number of liquid discharge holes **123**, so as to guide same to the mop cloth, the liquid supply tank **122** is provided with an air inlet **128** for communicating the external environment with the internal liquid storage chamber, and a check valve **135** is installed at the air inlet **128**. Specifically, the top of the liquid supply tank **122** is provided with a liquid filling port **127** through which the cleaning liquid can be filled, the liquid filling port **127** is provided with a tank cap **126**, and the air inlet **128** is formed on the tank cap **126**. The check valve **135** is also mounted on the tank cap **126**. The check valve **135** only allows outside air to enter the liquid supply tank **122** from the outside, and does not allow the air and/or the cleaning water in the liquid supply tank **122** to escape from the interior of the liquid supply tank **122** to the outside environment. In this way, even if the liquid supply tank **122** is in an inverted state, the cleaning water in the liquid supply tank **122** cannot leak to the floor to be cleaned through the air inlet **128**, thereby effectively preventing defects of secondary contamination on the floor to be cleaned when the user replaces the cleaning water.

(18) In order to prevent the water in the liquid supply tank **122** from being continuously guided to the mop cloth through the liquid discharge holes **123** after completing the mopping operation, which results in the excessive water content in the mop cloth, thereby leaving a large area of water stain on the floor to be cleaned. As shown in FIGS. 4 and 5, a valve **130** for opening and closing the liquid outlet **125** is installed at the liquid outlet **125**, and an action member **129**, which is operable by the user and is in driving connection with the valve **130**, is provided at the upper portion of the liquid supply tank **122**. In use, the user operates the action member **129** to drive the valve **130** to perform an action, thereby opening or closing the liquid outlet **125** on the liquid supply tank **122**.

(19) Specifically, the liquid supply tank **122** is provided with a mounting hole **136**, and the valve **130** comprises a plug **131** and a spring **132** which are installed inside the mounting hole **136**. One end of the spring **132** is connected to the plug **131** and the other end thereof is connected inside the mounting hole **136**, and a sealing ring **134** is mounted at the lower end of the plug **131**. The action member **129** is a button member, wherein one end of the button member is mounted to the liquid supply tank **122** via a rotating shaft **133**, and the other end thereof constitutes a trigger portion for the user to press or step on, and the upper end of the plug **131** abuts against the button member. Of course, the action member **129** is not limited to the above-described button type rotating member, and may also be a movable member; and the structure of the valve **130** is not limited to the above-

described plug **131** moving in the up and down direction, and may be a cover plate moving in the horizontal direction. For example, the movable member is fixedly connected to the cover plate, and when in use, the user operates the movable member to drive the cover plate to move in the horizontal direction, so that the cover plate and the liquid outlet **125** are offset from or aligned with each other, thereby opening or closing the liquid outlet **125**.

(20) As shown in FIG. 4, when the valve **130** is closed, the water in the liquid supply tank **122** stops flowing into the cavity **124**, and the water in the cavity **124** continues to flow to the plurality of liquid discharge holes **123** until it drains.

(21) As shown in FIG. 5, when the valve **130** is opened, the water in the liquid supply tank **122** can continuously flow into the cavity **124** through the liquid outlet **125**, then flows to the plurality of liquid discharge holes **123**, and is finally applied to the mop cloth to continuously wet the mop cloth. In this way, when the user is about to complete the mopping operation, the water supply of the mop cloth is not immediately interrupted, but continues to use the small amount of water in the cavity **124** to continue to wet the floor to be cleaned, thereby having a buffering function. In addition, after the water in the liquid supply tank **122** is used up, the water flow in the cavity **124** can continue to wet the mop cloth, and the mop cloth is not easily dried too fast, thereby facilitating the user adding the cleaning water in a timely manner, and reducing the transition time for the user.

(22) FIG. 6 to FIG. 9 illustrate another embodiment of the wet mopping device **12** which includes several other aspects of the invention. It should be understood that these aspects may also be applied to the above described embodiment or combined with above described features to constitute new embodiments. In FIGS. 6-9, same reference numbers are used to designate the identical or similar parts to the embodiment shown in FIGS. 1-5.

(23) As shown in FIG. 6, the wet mopping device **12** comprises a base plate **121** and a liquid supply tank **122**, which are similar to those shown in FIG. 2. Two locking elements **22** are provided on each of the front and rear borders of the base plate **121**. In the illustrated embodiment, each locking element **22** is in the form of a hook having a recess **221** facing the center of the base plate **121**. The floor brush body **11** is provided with corresponding lockers respectively located on the rear surface of the front suction part and the front surface of the rear suction part (not shown in the figures). When the wet mopping device **12** is mounted to the floor brush body **11**, the locker arranged on the floor brush body **11** are snapped in the recess of the locking element **22** provided on the base plate **121**. This cooperation helps to ensure the fastening of the wet mopping device **12** to the floor brush body **11**, in addition or in alternative to the snap fit created by the snap groove formed by the water tanks and the snap-in portion of the floor brush body **11**. Moreover, the locking elements **22** also avoids that the mop cloth overlays completely the base plate **121**.

(24) As shown in FIG. 7, the base plate **121** is provided a venting pipe **24** protruding from the upper surface of the base plate **121** to above the maximum filling level of the liquid supply tank **122**. The venting pipe **24** connects the cavity **124** formed inside the base plate **121** with the liquid supply tank **122**. As shown in FIGS. 4, 5 and 7, the base plate **121** only has a liquid outlet **125** through which liquid exits the liquid supply tank **122** and enters the cavity **124** of the base plate **121**. It could be difficult for the air trapped in the cavity **124** to get out from the liquid outlet **125** and the filling of the cavity **124** can thus be obstructed. The venting pipe allows to vent the air existing in the cavity **124** when filling the cavity **124** and thus facilitates the filling.

(25) Also as shown in FIG. 7, the base plate **121** is provided with at least one internal wall **26**, in the form of a longitudinal projection protruding from the upper surface to the inside of the cavity **124**. The internal wall **26** occupies a part of the volume of the cavity **124** and thus reduces the volume of the cavity **124** that is occupied by water. Therefore, when the valve **130** is actuated to its open position, water can fill the cavity **124** more quickly and moisten the mop more quickly as well. In other words, the time response is decreased between the time the valve **130** is manually actuated and the time when the mop is moistened by water flowing from the liquid discharge holes **123**. The quantity and the location of the internal walls **26** can be modified according to actual

need. In addition, the internal walls **26** also serve as reinforcing elements of the base plate **121**.

(26) It can be seen from FIG. 7 that the drain valve **130** is provided with a lower sealing **134** realized by an O-ring for radial sealing and an upper sealing **34** realized by a washer with axial lip **341** for axial sealing, in order to reduce the effort needed to operate the plug **131** of the valve **130**. In the embodiment illustrated on FIG. 7, the valve **130** is entirely housed in the mounting hole **136**. The lower sealing **134** and the upper sealing **34** both locate between the mounting hole **136** and the plug **131** of the valve **130**.

(27) Different from the previous embodiments shown in FIGS. 1 to 5, in the embodiment as shown in FIGS. 6 to 8, the tank cap **126** does not comprise an air inlet orifice that is visible from outside or a check valve but defines an air inlet channel extending between an air inlet **38** open towards the interior of the liquid supply tank **122** and an air opening **364** open towards the outside of the liquid supply tank **122**. The air inlet channel is formed by a chicane shape **36** formed in the tank cap **126**. The tank cap **126** comprises a cover part **142** and a lining part **146** that is mounted to the cover part **142**. The chicane shape is formed on the top surface of the cover part **142** and protruding downwardly therefrom. In the illustrated embodiment, the chicane shape **36** comprises an inner skirt **361** forming a substantially rectangular contour and ribs **362** linking a screw hole **33** with the inner skirt **361**. The lining part **146** is mounted to the bottom of the cover part **142** and comprises a plate provided with an orifice as an air inlet **38** and an outer skirt **37** protruding upwards from the plate and surrounding the air inlet **38**. The lining part **146** is for instance mounted to the cover part **142** by means of a bolt (not shown) passing through a fixing hole **32** arranged in the plate of the lining part **146** and screwed in the screw hole **33** of the cover part **142**. In the illustrated embodiment, the fixing hole **32** is located in the center of the plate.

(28) When the cover part **142** and the lining part **146** are mounted by the bolt, the outer skirt **37** is sleeved outside the inner skirt **361**, with its side S facing the side S' of the inner skirt **361** as shown in FIG. 8. In addition, the height of the inner skirt **361** and the ribs **362** are dimensioned to allow them getting in contact with the plate of the lining part **146** when mounted, so that water could hardly pass through their interface with the plate of the lining part **146**. As shown in FIG. 8, in this embodiment, four ribs **362** are disposed in the form of a cross with the screw hole **33** in the center. The ribs **362** form the baffles for water and/or air. It should be understood that the quantity and the distribution of the ribs may vary. When the cover part **142** and the lining part **146** are mounted, the air inlet **38** is located between two ribs **362**, one of which is partially hollowed to leave an intermediate air opening **363** in the air inlet channel. Another rib adjacent to the hollowed rib is also hollowed to leave an intermediate air opening. The inner skirt **361** comprises a first notch **364** and the outer skirt **37** comprises a second notch **374** at the same location, so as to form an air opening. The first notch **364** extends on the whole height of the inner skirt **361** whilst the second notch **374** extends on a part of the height of the outer skirt **37**. Preferably, as shown in FIG. 8, the outer skirt **37** comprises a block **373** protruding inwardly and is inserted in the first notch **364** of the inner skirt **361** when mounted. The first notch **364** is located between the other two ribs **362**. In other words, the air inlet **38** and the air opening are located in diagonal quadrants defined by the four ribs. Thus, air entering the tank cap **126** passes firstly the air opening formed by the notches **364** and **374**, then passes the intermediate air openings **363** formed in two adjacent ribs **362**, and finally passes through the air inlet **38** to access the liquid tank. Conversely, when the liquid tank is tilted and the liquid tends to leak out through the tank cap **126**, it is trapped between the cover part **142** and the lining part **146** by the baffles formed by the ribs **362** and the block **373**. In another preferred embodiment, the intermediate air openings **363** may be located directly adjacent to the top surface of the cover part **142**, so that they may trap the water more efficiently.

(29) In order to lock the drain valve **130** in its closed or open position, a cam shape is formed at a top portion of the plug **131** of the drain valve **130**. The top portion comprises a stepped surface including a higher surface **45** and a lower surface **46** which are connected by a cam surface **41**. As shown on FIG. 9 wherein the drain valve **130** is in the open position, a lever arm **50** of the action

member **129** rests on the lower surface **46** of the top of the plug **131**. To switch the valve **130** to its closed position, the action member **129** should be rotated around its axis in the clockwise direction. The lever arm **50** of the action member **129** is thus pressed against the cam surface **41** by its first edge **42**. When the cam surface **41** and the first edge **42** are being forced through, the lever arm **50** is moved downwards against a spring force that tends to urge the drain valve plug upwards and comes to rest on the higher surface **45** of the top of the plug **131** which is thus pushed down to block the liquid outlet **125**. Preferably, a protrusion **43** is provided on the higher surface **45** of the top portion of the plug **131**, near the cam surface **41**. Conversely, to open drain valve **130**, the action member **129** should be rotated in the anticlockwise direction. The lever arm **50** is pressed against the protrusion **43** by its second edge **44**. Only when the protrusion **43** and the second edge **44** are forced through, can the plug **131** be pushed upwards by the spring **132** and thus opens the valve **130**.

(30) The above embodiments are merely illustrative of the technical concept and features of the present invention, and are intended to enable those skilled in the art to understand and therefore implement the content of the present invention, and the scope of protection of the present invention could not be limited thereto. Any equivalent variations or modifications made in accordance with the spirit of the present invention shall be included within the scope of protection of the present invention.

Claims

1. A wet-and-dry floor brush for a vacuum cleaner, comprising: a floor brush body including at least one dust suction port at a bottom of the floor brush body; and a wet mopping device comprising a base plate for having a mop cloth mounted thereto, and a liquid supply tank located on an upper side of the base plate for supplying a cleaning liquid to the mop cloth, the base plate including a number of liquid discharge holes, and a lower portion of the liquid supply tank including a liquid outlet in fluid communication with the number of liquid discharge holes; wherein the liquid outlet is provided with a valve for opening and closing the liquid outlet, and the liquid supply tank includes an external action member which is operable by a user, wherein the action member and the valve are disposed in a manner allowing a transmission of rotational motion such that the user is able to open or close the liquid outlet by operating the action member by applying a force on the action member toward the base plate such that the action member contacts a plug to open the valve; wherein the base plate includes a cavity and a venting pipe connecting the cavity with the liquid supply tank, the venting pipe protruding from an upper surface of the base plate and up to above a maximum fill level of liquid in the liquid supply tank.
2. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the base includes the cavity having a volume smaller than that of the liquid supply tank, and the liquid outlet, the cavity and the number of liquid discharge holes are in communication with one another in sequence.
3. The wet-and-dry floor brush for the vacuum cleaner according to claim 2, wherein the cavity includes at least one internal wall protruding inside the cavity.
4. The wet-and-dry floor brush for the vacuum cleaner according to claim 2, wherein the base plate has a detachable portion in which the cavity is formed.
5. The wet-and-dry floor brush for the vacuum cleaner according to claim 4, wherein the number of liquid discharge holes are included by the detachable portion.
6. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the action member is located at a top of the liquid supply tank.
7. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the wet mopping device is detachably mounted to the floor brush body.
8. The wet-and-dry floor brush for the vacuum cleaner according to claim 7, wherein the base plate

includes at least one locking element which cooperates with a corresponding locker arranged on the floor brush body so as to lock the base plate with the floor brush body.

9. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the base plate and the liquid supply tank are integrally formed.

10. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the base plate is located at the bottom of the floor brush body, and the liquid supply tank is detachably mounted at a top of the floor brush body.

11. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the base plate is detachably mounted at the bottom of the floor brush body.

12. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the at least one dust suction port is exactly one dust suction port and is located at a front portion of the floor brush body, and the base plate is located behind the dust suction port.

13. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the bottom of the floor brush body includes a pair of dust suction ports respectively located on a front side and a rear side of the floor brush body, and the base plate is located between the pair of dust suction ports.

14. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein a top of the liquid supply tank includes a liquid filling port, and a tank cap is arranged at the liquid filling port, wherein the tank cap includes an air inlet that communicates an outside with an interior of the liquid supply tank.

15. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein a top of the liquid supply tank includes a liquid filling port, and the cleaner includes a tank cap arranged at the liquid filling port and comprising an air inlet open towards an interior of the liquid supply tank and an air opening open towards an outside of the liquid supply tank, the tank cap comprises a chicane shape formed by at least one baffle and forming an air inlet channel extending inside the tank cap from the air inlet to the air opening.

16. The wet-and-dry floor brush for the vacuum cleaner according to claim 15, wherein the tank cap comprises a cover part and a lining part that is mounted to the cover part.

17. The wet-and-dry floor brush for the vacuum cleaner according to claim 16, wherein the cover part comprises said chicane shape.

18. The wet-and-dry floor brush for the vacuum cleaner according to claim 15, wherein at least one of the baffles is hollowed to define an intermediate air opening in the air inlet channel.

19. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein a cam shape is formed at a top portion of the valve to lock the valve in the closed or open position.

20. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the valve includes a lower sealing formed by an O-ring for radial sealing and an upper sealing formed by a washer with an axial lip for axial sealing.

21. The wet-and-dry floor brush for the vacuum cleaner according to claim 1, wherein the action member is configured such that the force applied on the action member toward the base plate causes rotation of the action member about a rotating shaft.
