

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404684
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Achard; Frederic et al.

Method for installation of a ceiling system

Abstract

A method is for installing a ceiling system attached to a structural ceiling surface. The method includes illuminating, in sequence and by a projector, different subsets of a set of optical sensors separately arranged in a known distribution pattern on the structural ceiling surface. Each optical sensor of the set of optical sensors is arranged to output a temporal signal indicative of a level of illumination. The method also includes determining an image plane relative to the projector based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, and displaying, by the projector, an image indicative of installation locations of the ceiling system at the image plane.

Inventors:	Achard; Frederic (Saint-Ouen, FR), Coat; Christopher (Ecos, FR), Chigot; Pierre (Helsingborg, SE)
Applicant:	SAINT-GOBAIN ECOPHON AB (Hyllinge, SE)
Family ID:	70154306
Assignee:	SAINT-GOBAIN ECOPHON AB (Hyllinge, SE)
Appl. No.:	17/907164
Filed (or PCT Filed):	March 30, 2021
PCT No.:	PCT/EP2021/058336
PCT Pub. No.:	WO2021/198280
PCT Pub. Date:	October 07, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230106808 A1	Apr. 06, 2023

Foreign Application Priority Data

EP 20167570 Apr. 01, 2020

Publication Classification

Int. Cl.: E04F21/18 (20060101); E04B9/06 (20060101); G01C15/00 (20060101); G06F30/13 (20200101)

U.S. Cl.:

CPC E04F21/1883 (20130101); E04B9/06 (20130101); G01C15/006 (20130101); G06F30/13 (20200101);

Field of Classification Search

CPC: E04B (1/00); E04B (9/06); E04F (21/1883); G01C (15/006); G06F (30/13)

USPC: 33/1G

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3775929	12/1972	Roodvoets	33/286	E04F 21/1838
8936367	12/2014	Jung	353/121	H04N 9/3185
9274635	12/2015	Birnbaum	N/A	G06F 3/016
2005/0030486	12/2004	Lee	348/E17.005	H04N 9/3185
2017/0275878	12/2016	Chigot	N/A	E04B 9/363
2023/0019423	12/2022	Nishita	N/A	G01C 15/008

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2 432 670	12/2006	GB	N/A
WO 2019/229716	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report issued Jun. 21, 2021 in PCT/EP2021/058336, filed on Mar. 30, 2021, 3 pages. cited by applicant
Canadian Office Action issued Jun. 27, 2024 in Canadian Patent Application No. 3,172,053, 3 pages. cited by applicant

Background/Summary

FILED OF THE INVENTION

(1) The present invention generally relates to a method for installation of a ceiling system attached to a structural ceiling surface.

BACKGROUND OF THE INVENTION

(2) A tile system in a room or in another accommodation may serve a variety of purposes. One purpose of having a tile system such as a suspended ceiling system or ceiling system attached to a structural ceiling may be to conceal an underside of a space, such as another room, which is located above the room. The tile system may hence be installed to improve the visual appearance of a room.

(3) Another purpose may be to provide improved noise absorption and/or noise attenuation in and outside of the room by having a tile system including acoustic elements. The tiles then typically are acoustic elements and may comprise a mineral fibre material, such as glass wool.

(4) A resulting plenum space located between a suspended ceiling and a structural ceiling of a room may further be utilized to accommodate e.g. wiring, piping, as well as devices related to heating, ventilation and air condition.

(5) Moreover, acoustic elements may be used to improve the acoustical environment in a room while at the same time improve the visual appearance of the room.

(6) The acoustic elements or tiles may be suspended from a surface in a room or may be attached to a surface in a room.

(7) Moreover, the mounting of the tile system or ceiling system must be very precise since even a slight misalignment of the ceiling system or an acoustic element may have a big visual impact on the aesthetical appearance of the ceiling.

(8) When the elements of the tile system or ceiling system are installed at oblique angles with respect to each other, it becomes even more difficult to precisely position and mount the elements of the ceiling system.

(9) Thus, the positioning of the elements must be carefully measured. This work typically involves cumbersome work performed on ladders or scaffoldings and is prone to errors.

(10) In one kind of a typical ceiling installation, a group of acoustic elements in form of tiles may be arranged in a grid of profiles. The profiles are typically attached to a surface in a room, such as a structural ceiling.

(11) When installing acoustic elements, which are arranged in a grid of profiles, the installation process is time consuming and complex. The grid of profiles must be precisely attached to the surface of the room or else the acoustic elements will not properly fit in the grid.

(12) Moreover, the mounting of the grid of profiles must be very precise since even a slight misalignment of the grid or an acoustic element may have a big visual impact on the aesthetical appearance of the ceiling.

(13) When the profiles of the grid are installed at oblique angles with respect to each other, it becomes even more difficult to precisely position and mount the profiles of the grid.

(14) Thus, the positioning of the profiles must be carefully measured. This work typically involves cumbersome work performed on ladders or scaffoldings and is prone to errors.

(15) Moreover, when a tile system is installed over a large area, workers installing the tile system typically will have to climb up and down on different ladders or scaffoldings in order to be able to

reach the complete area of installation. This work is even more cumbersome and may put safety at risk.

SUMMARY OF THE INVENTION

(16) In view of the above, it is an object of the present invention is to provide an improved method for installation of a ceiling system attached to a structural ceiling surface.

(17) A further object is to provide such a method which is less complex and less prone to errors when installing a ceiling system.

(18) It is also an object to provide a cost-effective method requiring less time and consequently less work labour for installing a ceiling system.

(19) It is also an object to provide a more versatile method allowing a greater flexibility when it comes to installing a ceiling system.

(20) To achieve at least one of the above objects and also other objects that will be evident from the following description, a method for installation of a ceiling system having the features defined in claim 1, is provided according to the present invention. Preferred embodiments will be evident from the dependent claims.

(21) More specifically, there is provided according to the present invention a method for installation of a ceiling system attached to a structural ceiling surface, the method comprising; in sequence illuminating, by a projector, different sub sets of a set of optical sensors separately arranged in a known distribution pattern on the structural ceiling surface, wherein each optical sensor of the set of optical sensors being arranged to output a temporal signal indicative of a level of illumination, determining an image plane relative to the projector based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, and displaying, by the projector, an image indicative of installation locations of the ceiling system at the image plane.

(22) Hereby an improved method for installation of a ceiling system is provided.

(23) The method is for installation of a ceiling system attached to a structural ceiling surface.

(24) The ceiling system may comprise a plurality of elements, such as ceiling tiles, absorber elements, acoustic elements, profiles or similar, so as to form a rectangular pattern. In other words, the plurality of elements may be arranged in a parallel manner.

(25) The ceiling system may comprise a plurality of elements arranged at oblique angles with respect to each other so as to form an irregular pattern of elements. In other words, the plurality of elements may be arranged in a non-parallel manner. The method comprises, in sequence illuminating, by a projector, different sub sets of a set of optical sensors separately arranged in a known distribution pattern on the structural ceiling surface.

(26) A set of optical sensors is therefore arranged on the structural ceiling surface. The sensors may be arranged directly on the structural ceiling surface or may be arranged indirectly for instance by being provided in a sensor housing which in turn is attached to the structural ceiling surface. The set of optical sensors are arranged in a known distribution pattern, meaning that the relative locations of the respective optical sensors are known. In other words, the mutual distances and the mutual directions of the respective optical sensors are known. The absolute locations of the optical sensors with respect to a reference location may additionally be known.

(27) Different subsets of the of a set of optical sensors are illuminated by a projector in sequence. Hence, different combinations of optical sensors may be illuminated by a projector. A single optical sensor may be included in more than one subset of optical sensors. Also, a single optical sensor may be regarded a subset. The different subsets are illuminated in sequence, meaning that the respective subsets are illuminated consecutively in time after each other.

(28) Different illumination sequences may be employed by the projector to illuminate the optical sensors in sequence. In practice, an illumination sequence may include a number of different illumination patterns employed by the projector in sequence. Each illumination pattern may then typically include a pattern of illuminated areas on the structural ceiling surface and consequently

also include non-illuminated areas of the structural ceiling surface. The same subset may be illuminated more than once when conducting the method.

(29) Each optical sensor of the set of optical sensors is arranged to output a temporal signal indicative of a level of illumination. Hence, each optical sensor is arranged to output a signal which varies in time with the illumination level detected by the optical sensor in question. The signal may be an analogue signal, a digital signal or a combination thereof. The signal level being outputted may be to scale with the illumination level detected by the optical sensor in question. The signal level being outputted may be subject to a mathematical transform applied to the illumination level detected by the optical sensor in question. The signal level being outputted may be subject to a threshold of the illumination level detected by the optical sensor in question, such that a signal is outputted or correspondingly interrupted when a detected illumination level exceeds a predetermined threshold value.

(30) An image plane is determined relative to the projector based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors. By illuminating subsets of the optical sensors in sequence with a series of known illumination patterns, it may be determined for which illumination patterns or pattern a specific optical sensor is illuminated. That is, a space angle range with respect to the projector may be established based on the illumination pattern at hand, where the illumination pattern includes an illuminated portion or portions being projected over a known space angle range. Hence, the optical sensor in question will output a temporal signal indicative of how the optical sensor is being illuminated during the illumination sequence. In a corresponding manner, all optical sensors will output a respective temporal signal indicative of how the respective optical sensors are illuminated during the illumination sequence.

(31) By combining the outputted temporal signals of each of the optical sensors with the known distribution pattern an image plane relative to the projector may be determined. The image plane may thus be determined by mathematical calculations. For example, the image plane relative the projector may be determined using homography algorithms as is known in the art. As is known, homography typically refer to the homography matrix which is the transfer matrix of projective transforms. The homography matrix is a linear transformation from a 2D plane to another. In the present case homography inversion, i.e. inverting the homography matrix, may advantageously be employed in determining the image plane.

(32) After having determined the image plane relative to the projector based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, an image indicative of installation locations of the ceiling system may be displayed by the projector at the determined image plane. In other words, the projector may display an image which is compensated so as to be displayed in a desired manner at the image plane. Hence, the image may be displayed such that installation locations of the ceiling system at the image plane are displayed in a desired manner corresponding to actual installation locations of the ceiling system at the image plane. This may be done by adjusting the input to the projector such that the image is projected with a correct scale at the image plane.

(33) The image may include simple indications of installation locations of the ceiling system. The image may visualise the complete installation of the ceiling system to be installed including indications of installation locations of elements such as tiles or primary profiles. The image may thus visualise a complete installation of the ceiling system to be installed including any tiles or absorber elements and indications of installation locations of primary profiles. The image may include additional information.

(34) Next, elements of the ceiling system are typically attached to the structural ceiling surface in locations corresponding to the installation locations indicated in the displayed image. The elements may be attached directly to the structural ceiling surface or may be suspended below at a distance from the structural ceiling surface.

(35) The ceiling system may comprise a grid of profiles comprising a plurality of primary profiles, and the act of displaying the image may comprise displaying information indicative of installation locations of the primary profiles at the image plane.

(36) The grid of profiles may comprise a plurality of profiles arranged so as to form a rectangular grid of profiles. In other words, the plurality of profiles may be arranged in a parallel manner. A rectangular grid of profiles typically includes a plurality of rectangular spaces for accommodating ceiling tiles, absorber elements, acoustic elements or similar.

(37) The grid of profiles may comprise a plurality of profiles arranged at oblique angles with respect to each other so as to form an irregular grid of profiles. In other words, the plurality of profiles may be arranged in a non-parallel manner. An irregular grid of profiles typically includes a plurality of irregular spaces of different sizes and shapes for accommodating ceiling tiles, absorber elements, acoustic elements or similar.

(38) The individual profiles of the grid of profiles are typically straight profiles. The individual profiles of the grid of profiles may have bent or curved shape. The profiles may be made of metal, plastic or any other suitable sufficiently rigid material.

(39) The grid of profiles typically comprises a plurality of primary profiles. The primary profiles typically extend in a non-interrupted manner along an installation of a ceiling system. The primary profiles may be formed of a plurality of detachable sections, jointly forming the primary profiles.

(40) The primary profiles may be attached directly to a structural ceiling surface or may be suspended below at a distance from the structural ceiling surface as is known in the art.

(41) The primary profiles are typically interconnected by cross runners or cross profiles. By utilizing cross runners interconnecting the plurality of main runners the main runners may be stabilized and less prone to run in an undesired curved fashion.

(42) Moreover there may be provided, a method for installation of a grid of profiles of a ceiling system attached to a structural ceiling surface, wherein the grid of profiles comprises a plurality of primary profiles, the method comprising; in sequence illuminating, by a projector, different sub sets of a set of optical sensors separately arranged in a known distribution pattern on the structural ceiling surface, wherein each optical sensor of the set of optical sensors being arranged to output a temporal signal indicative of a level of illumination, determining an image plane relative to the projector based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, and displaying, by the projector, an image indicative of installation locations of the primary profiles at the image plane.

(43) Hereby an improved method for installation of a grid of profiles of a ceiling system may be provided.

(44) The act of determining the image plane may comprise determining the image plane such that the image plane substantially includes physical locations of the optical sensors of the set of optical sensors. By determining the image plane such that the image plane substantially includes physical locations of the optical sensors of the set of optical sensors, the image plane may be determined such that it substantially coincides with the structural ceiling surface on which the set of optical sensors is arranged.

(45) The act of displaying the image may comprise displaying the image on the structural ceiling surface. Hence, the image displayed at the image plane may thus be displayed at the structural ceiling surface in a desired manner such that installation locations of the ceiling system at structural ceiling surface are displayed in a desired manner corresponding to actual installation locations of the elements of the ceiling system at the structural ceiling surface.

(46) The act of displaying the image may comprise calculating a projective transform based on a location of the projector relative to the image plane, and applying the projective transform to the image such that the displayed image is compensated for size and wrap with respect to the structural ceiling surface. The image transform may be calculated using a homography algorithm, as discussed above, and the image transform may then be applied to the image such that the image is

compensated for size and wrap with respect to the structural ceiling surface. More specifically, homography inversion, i.e. inverting the homography matrix, may advantageously be employed in determining the projective transform.

(47) In practice, the image transform may be applied to the image by adjusting the input to the projector accordingly. Hence, the projector may display an image which is compensated for size and wrap with respect to the structural ceiling surface so as to display the image in a desired manner at the structural ceiling surface. Hence, the image may be displayed such that installation locations of the elements of the ceiling system at the image plane are displayed in a desired manner corresponding to actual installation locations of the elements of the ceiling system at the structural ceiling surface.

(48) The act of determining the image plane may comprise determining a rotation of the projector relative to a desired direction of the installation locations of the ceiling system at the image plane based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, and wherein the act of displaying the image comprises compensating a rotation of the image based on the determined rotation. The image rotation may be calculated using a homography algorithm and a rotation compensation may then be applied to the image such that the image is compensated for rotation with respect to the structural ceiling surface. More specifically, homography inversion, i.e. inverting the homography matrix, may advantageously be employed in determining the rotation of the projector relative to a desired direction of e.g. installation locations of primary profiles at the image plane based.

(49) In practice, the rotation compensation may be applied to the image by adjusting the input to the projector accordingly. Hence, the projector may display an image which is compensated for size and wrap with respect to the structural ceiling surface so as to display the image in a desired manner at the structural ceiling surface. Hence, the image may be displayed such that installation locations of the elements of the ceiling system, such as primary profiles, at the image plane are displayed in a desired manner corresponding to actual installation locations of the elements of the ceiling system at the structural ceiling surface.

(50) The act of displaying the image may comprise adjusting a position of the image at the image plane based on building information model data, BIM data. By adjusting a position of the image at the image plane based on building information model data, BIM data, the position of the image may be adjusted such that the installation locations of the elements of the ceiling system are aligned with certain building features, such as walls or air outlets. Correspondingly, the position of the image may be adjusted such that installation locations of e.g. primary profiles are positioned at locations where there is a reduced risk of interfering with or damaging concealed features of the building, such as piping or electrical cables.

(51) The act of displaying the image may comprise adjusting a position of the image at the image plane based on a user-initiated input signal, which is advantageous in that a user may adjust the position of the image in a simple manner.

(52) The optical sensors of the set of optical sensors may be arranged at locations corresponding to junctions of the grid of profiles. By arranging the optical sensors of the set of optical sensors at locations corresponding to junctions of the grid of profiles, a person installing the grid of profiles may get a visual confirmation that the image is displayed correctly. Hence, a person installing the grid of profiles may easily verify that the junctions of the grid of profiles are displayed at locations where the optical sensors are located at the structural ceiling surface. In this way, a person installing the grid of profiles may also verify that the image plane has been correctly determined or else the junctions of the grid of profiles may incorrectly be displayed at locations where the optical sensors are not located.

(53) The optical sensors of the set of optical sensors may be arranged on a common substrate which is adapted to be arranged at the structural ceiling surface. By arranging the optical sensors of the set of optical sensors on a common substrate which is adapted to be arranged at the structural ceiling

surface, the distribution pattern of the set of optical sensors may be kept constant and fixed in a secure manner. Moreover, the distribution pattern of the set of optical sensors may not need to be measured or considered by a person installing the ceiling system since the distribution pattern of the set of optical sensors may be fixed by the common substrate. Hence, the mutual distances and directions between the optical sensors of the set of optical sensors may be fixed and thus well known. Also, the method may become more efficient since a person installing the ceiling system may not have to spend time on installing a plurality of individual optical sensors.

(54) The act of displaying the image may comprise displaying installation guidance based on building information model data, BIM data, which is advantageous in that installation guidance may be displayed while taking features of the building into account.

(55) The act of displaying the image may comprise displaying fix points of the ceiling system to be installed, which is advantageous in that fix points may be displayed at locations where there is a reduced risk of interfering with or damaging concealed features of the building, such as piping or electrical cables. Hence, a person installing the ceiling system may get a visual guidance regarding where to safely fix the elements of the ceiling system.

(56) The act of displaying the image may comprise displaying forbidden areas for fix points of the ceiling system to be installed, which is advantageous in that areas where fix points would risk interfering with or damaging concealed features of the building, such as piping or electrical cables, may be highlighted to a person installing the ceiling system. Hence, a person installing the ceiling system may get a visual guidance regarding where to not fix the elements of the ceiling system.

(57) The act of displaying the image may comprise displaying fix points of primary profiles to be installed, which is advantageous in that fix points may be displayed at locations where there is a reduced risk of interfering with or damaging concealed features of the building, such as piping or electrical cables. Hence, a person installing the grid of profiles may get a visual guidance regarding where to safely fix the grid of profiles.

(58) The act of displaying the image may comprise displaying forbidden areas for fix points of primary profiles to be installed, which is advantageous in that areas where fix points would risk interfering with or damaging concealed features of the building, such as piping or electrical cables, may be highlighted to a person installing the grid of profiles. Hence, a person installing the grid of profiles may get a visual guidance regarding where to not fix the grid of profiles.

(59) The act of displaying the image may further comprise displaying building information model data, BIM data, which is advantageous in that concealed features of the building, such as piping or electrical cables, may be displayed to a person installing the ceiling system. Also, features of the building, such as piping or electrical cables, that has not yet been installed may be displayed to a person installing the ceiling system. In this way a person installing the ceiling system may account for features to be installed and hence save enough room for the features to be installed.

(60) The act of in sequence illuminating different sub sets of the set of optical sensors may comprise; in sequence illuminating different sub sets of the set of optical sensors according to a first predetermined dichotomy pattern along a first major direction, and in sequence illuminating different sub sets of the set of optical sensors according to a second predetermined dichotomy pattern along a second major direction, the first major direction being perpendicular to the second major direction, which is advantageous in that the an accurate space angle range or space angle for each optical sensor with respect to the projector may be determined. In other words, the direction along which imaginary beam of the projector each optical sensor is located may be determined. By illuminating different sub sets of the set of optical sensors according along a first major direction and a second major direction, where the first major direction being perpendicular to the second major direction, the space angle range or space angle for each optical sensor with respect to the projector may be determined in series for the first major direction and the second major direction respectively.

(61) The method may further comprise, arranging a second projector, separate from the projector, at

a distance from the structural ceiling surface, and displaying, by the projector and the second projector, the image indicative of installation locations of the ceiling system at the image plane. By utilizing a projector and a second projector to jointly display the image indicative of installation locations of the ceiling system, such as elements and primary profiles, at the image plane, several advantages are achieved. For instance, an increased display area or installation area may be covered. Further, an increased redundancy may be achieved in case of failure of the projector or the second projector. Furthermore, the risk of certain areas of the image plane being shadowed, by for instance pillars, light armatures, inner walls or similar, may be reduced.

(62) Further features of, and advantages with, the present inventive concept will become apparent when studying the appended claims and the following description. The skilled person will realize that different features of the present inventive concept may be combined to create variants other than those described in the following, without departing from the scope of the present inventive concept.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The aspects of the inventive concept, including its particular features and advantages, will be readily understood from the following detailed description and the accompanying drawings, in which:

(2) FIG. 1 conceptually illustrates a room in which a ceiling system including a grid of profiles is to be installed using a method for installation of a ceiling system.

(3) FIG. 2 conceptually illustrates the room of FIG. 1 with a different sensor setup as compared to FIG. 1.

(4) FIGS. 3a-3i schematically illustrates an illumination sequence and temporal signals from two different sensors.

(5) FIG. 4 conceptually illustrates the room of FIG. 1 at a later stage of the method where installation locations of primary profiles of the grid of profiles are displayed at a structural ceiling surface.

(6) FIG. 5 conceptually illustrates the room of FIG. 1 while displaying additional information on a structural ceiling surface.

(7) FIG. 6 conceptually illustrates the room of FIG. 1 while using a second projector in addition to the projector.

(8) FIG. 7 is a flowchart of a method for installation of a ceiling system attached to a structural ceiling surface.

DETAILED DESCRIPTION

(9) The present inventive concept will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred variants of the inventive concept are shown and discussed. This inventive concept may, however, be embodied in many different forms and should not be construed as limited to the variants set forth herein; rather, these variants are provided for thoroughness and completeness, and fully convey the scope of the inventive concept to the skilled person. Like reference numerals refer to like elements throughout the description.

(10) As have been described above, the present inventive concept generally relates to installation of ceiling systems attached to structural ceiling surfaces. Hence, installations of any type of ceiling systems are encompassed by the present inventive concept. In the following description, the present inventive concept it will be described in conjunction with ceiling systems including a grid of profiles. However, the present inventive concept is equally applicable for with ceiling systems void of any grid of profiles.

(11) FIG. 1 conceptually illustrates a room **100** in which a grid of profiles is to be installed using a

method for installation of a grid of profiles of a ceiling system. A number of components used for executing the method will be described below in conjunction with describing the method. The method will be described sequentially below, and variants thereof will be discussed in-line. The components used for executing the method will sometimes be collectively referred to as a system.

(12) More specifically, a grid of profiles of a ceiling system is to be attached to the structural ceiling surface **102** of the room **100**. The grid of profiles to be installed comprises a plurality of primary profiles. The primary profiles are typically extending in a non-interrupted manner along an installation of a ceiling system. The method described for installation of a grid of profiles of a ceiling system includes displaying an image indicative of installation locations of the primary profiles. Primary profiles are thereafter typically attached to the structural ceiling surface **102** in locations corresponding to the installation locations indicated in the displayed image.

(13) In the room **100** there is provided a projector **104**. The projector **104** forming part of the system used for executing the method. The projector **104** is arranged on the floor **106** of the room **100**. The projector **104** may alternatively be arranged on a wall or at the ceiling of the room **100**. The projector **104** may be of any suitable kind. Examples of suitable projectors **104** include SD, HD and 4 K video projectors or beamers. Projectors **104** capable of displaying colour images are preferred while projectors **104** capable of displaying black and white images or monochromic images will suffice. Also, a laser projector **104** may be used to advantage. The projector **104** is connected to an image source **108**. The image source **108** may be any device capable of providing an image signal to the projector **104**. Examples of suitable image sources includes, computers, laptops, tablets and media players such as an Apple TV® to give a few non-limiting examples. The image source **108** may be connected to the projector **104** by a wired connection, a wireless connection or a combination thereof. In the depicted system, the image source **108** is connected by wired connection to the projector **104**.

(14) The image source **108** includes a processor **108a** capable of processing and altering image data. The processor **108a** is typically capable of processing an incoming image signal in order to feed out an image signal suitable for the projector **104** in question. Alternatively, or additionally, the image source **108** may include a memory **108b** having stored thereon image data used to produce an image signal for suitable for the projector **104** in question. The processor **108a** may alter or manipulate the image data so as to alter or manipulate the image displayed by the projector **104**.

(15) The image source **108** is preferably attached to the projector **104** so as to form a single unit. The image source **108** may be integral to the projector **104**. The image source **108** may be separate the projector **104**.

(16) The depicted system used for executing the method further includes a user device **110**. The user device **110** may be connected to the image source **108** by a wired connection, a wireless connection or a combination thereof. The depicted user device **110** is a handheld device which is connected to the image source **108** by a wireless connection. The user device **110** may be any suitable device such as computers, laptops, media players and tablets such as an iPad® to give a few non-limiting examples. The user device **110** is arranged to transmit an image signal to the image source **108** or to transmit data relevant for the image source **108** to produce an image signal for the projector **104**. The user device is typically capable of receiving different types of input from a user. The input may be input related to image adjustment, image manipulation, sensor locations, mutual distances, mutual directions, brightness, contrast, amount of image information, etc.

(17) The user device **110** and the image source **108** may be the same device.

(18) The depicted system used for executing the method further includes a set of optical sensors including four optical sensors **112a-d**. The optical sensors **112a-d** are arranged on the structural ceiling surface **102** of the room **100**. More specifically, the optical sensors **112a-d** are arranged on a common substrate **114**. Hence, the optical sensors **112a-d** are arranged indirectly on the structural ceiling surface **102** of the room **100**. The common substrate **114** is adapted to be arranged on the

structural ceiling surface **102**. The common substrate **114** may for example be a board of thin material, a plate or similar. The common substrate **114** may be foldable and may for that purpose include hinges, fold lines or similar. By the common substrate **114** the optical sensors **112a-d** are separately arranged in a known distribution pattern on the common substrate **114** and hence on the structural ceiling surface **102**. In other words, the mutual distances and mutual directions between the respective optical sensors **112a-d** are fixed by the common substrate **114** and hence the distribution pattern is known. The common substrate **114** is held at the structural ceiling surface **102** by means of a holder **116** in form of an adjustable tripod.

(19) In FIG. **1** four optical sensors **112a-d** are depicted. However, more optical sensors may be used, such as 5, 7, 10 or 50 optical sensors. By using more optical sensors, an increased accuracy may be achieved. However, in the following a system having four optical sensors **112a-d** will be described.

(20) Each of the four optical sensors **112a-d** are connected to the user device **110** by means of a wireless connection. Each optical sensor **112a-d** of the set of optical sensors being arranged to output a temporal signal indicative of a level of illumination. In other words, each optical sensor **112a-d** is arranged to output a time sequential signal which is dependent on a level of illumination impinging on the optical sensor **112a-112d** in question. The temporal signal indicative of a level of illumination will be discussed in greater detail below when referring to FIG. **3**.

(21) As an alternative, each optical sensor **112a-d** of the set of optical sensors may be attached by a respective wired connection to a common wireless transmitter. The wireless transmitter may in turn be connected to the user device **110** by means of a wireless connection. The wireless transmitter may in this case advantageously be arranged on the common substrate **114**.

(22) As a further alternative, each optical sensor **112a-d** of the set of optical sensors may be attached by a respective wired connection to a common wireless transmitter. The wireless transmitter may in turn be connected to the projector **104** by means of a wireless connection. The wireless transmitter may in this case advantageously be arranged on the common substrate **114**.

(23) As can be seen in FIG. **1**, the projector **104** illuminates a portion **118** of the structural ceiling surface **102** of the room **100**. The depicted illuminated portion **118** covers a major portion of the structural ceiling surface **102** of the room **100**. As depicted in FIG. **1**, the illuminated portion **118** of the structural ceiling surface **102** includes a bright area **118a** with high illumination intensity and a less bright area **118b** with a lower illumination intensity. The optical sensors **112a** and **112c** are present in the bright area **118a** with high illumination intensity whereas the sensors **112b** and **112d** are present in the less bright area **118b** with a lower illumination intensity. Hence, in the depicted moment of FIG. **1**, optical sensors **112a** and **112c** will output a respective signal indicative of a higher level of illumination as compared to optical sensors **112b** and **112d**. Signals outputted by the optical sensors **112a-112d** will be discussed in greater detail below when referring to FIG. **3**.

(24) Now referring to FIG. **2**, here room **100** is depicted with a different setup of optical sensors **212a-212d**. In order to avoid undue repetition, only differences in relation to FIG. **1** will be discussed below.

(25) The optical sensors **212a-d** are arranged on the structural ceiling surface **102** of the room **100**. More specifically, the optical sensors **212a-d** are arranged directly on the structural ceiling surface **102** of the room **100**. The respective optical sensors **212a-d** may for instance be glued to or screwed to the structural ceiling surface **102** of the room **100**. The optical sensors **212a-d** are separately arranged on the structural ceiling surface **103**. In other words, the mutual distances and directions between the respective optical sensors **212a-d** are fixed by the optical sensors **212a-d** being arranged on the structural ceiling surface **103**. However, in this case, the distribution pattern will not directly be known per se. This means that a user executing the method will have to carefully determine the mutual distances and directions between the respective optical sensors **112a-d** after the optical sensors **212a-d** have been arranged on the structural ceiling surface **103**, or the user executing the method will have to carefully arrange the optical sensors **212a-d** on the

structural ceiling surface **102** according to a predetermined known distribution pattern. Hence, the distribution pattern of the optical sensors **212a-d** may be known either from measurements of the actual locations or from the fact that the optical sensors **212a-d** are mounted according to a known distribution pattern.

(26) The optical sensors **212a-d** are connected to the projector **104** by respective wired connections. The projector **104** of FIG. 2 includes a user device **110** and an image source **108** integrally formed with the projector **104**. The user device **110** and an image source **108** fulfil corresponding purposes of those described in conjunction with FIG. 1 and will not be described in greater detail here.

(27) Now referring to FIGS. 3a-3i. According to the method, different sub sets of the set of optical sensors **112a-112d** (or **212a-d**) are illuminated in sequence by the projector **104**.

(28) In FIGS. 3a-3i it is schematically depicted how two optical sensors denoted S1, S2, corresponding to any of the optical sensors **112a-112d** (or **212a-d**), are illuminated in sequence by the projector **104**. In FIG. 3a-3i two sensors S1, S2 are depicted for reasons of simplicity. The same principle does however apply to the situation where more optical sensors are used. In FIG. 3a-3i, different subsets of the optical sensors S1 and S2 are illuminated in sequence by an illumination sequence including six different illumination patterns as depicted in FIGS. 3a-3f. The different subsets are corresponding to the actual optical sensors S1, S2 being illuminated at a certain point in time.

(29) In the following, FIGS. 3a-3i will be referred to as schemes a-i, where schema a refers to FIG. 3a, scheme b to FIG. 3b etc. All six schemes a-f shows the same area of a structural ceiling surface **102** on which the two optical sensors S1 and S2 are arranged. The respective schemes a-f shows the same area of the structural ceiling surface **102** at different points in time where scheme a corresponds to a first point in time and scheme f corresponds to a last point in time of the respective schemes. The sequential illumination of the optical sensors S1, S2 according to the illumination sequence including six different illumination patterns is performed. The six different illumination patterns will result in that each of the optical sensors S1, S2 outputs a temporal signal TS1, TS2 indicative of a level of illumination at the respective schemes a-f. The temporal signals TS1 and TS2 are depicted in the respective graphs g and h in FIG. 3.

(30) The outputted temporal signals TS1 and TS2 may in practice be used to determine in which directions the optical sensors S1, S2 are arranged in relation to the projector **104**. In practice, a space angle interval with respect to the projector may be determined for each optical sensor S1, S2. The space angle interval will in practice correspond an angle interval along a first major direction and an angle interval along a second major direction. The space angle intervals of the optical sensors S1, S2 will thus correspond to a respective area A1, A2 at the structural ceiling surface **102**. This is illustrated in scheme i in FIG. 3.

(31) In the following it will be described in greater detail how the respective directions to sensors S1, S2 are determined by illuminating different subsets of the sensors S1, S2 in sequence by the projector **104**.

(32) Before the first illumination of scheme a is employed a dark level signal with the projector tuned off is preferably recorded as a reference signal.

(33) In the first illumination pattern of scheme a, sensor S1 is illuminated while sensor S2 is not. In other words, sensor S1 is at scheme a located in an area with high illumination intensity while sensor S2 is located in an area with a lower illumination intensity such as a background illumination intensity. At the point in time corresponding to scheme a, sensor S1 will output a signal indicative of a higher level of illumination as compared to sensor S2. This is illustrated in schemes g and h where it may be seen that the temporal signal TS1 of sensor S1 has a higher signal level than the temporal signal TS2 of sensor S2 at point a. In fact, the temporal signal TS2 of sensor S2 is set to a zero since corresponding to a background illumination level.

(34) From the respective temporal signals TS1, TS2 and the illumination pattern at scheme a, it

may be concluded that sensor S1 is located somewhere in the area indicated by the bracket above scheme a. Correspondingly, it may be concluded that sensor S2 is located somewhere in the area indicated by the bracket below scheme a. This because sensor S1 is in the illuminated area at the right of scheme a, while sensor S2 is in the non-illuminated area at the left of scheme a.

(35) Followingly, the sensors S1, S2 are illuminated with a second illumination pattern of scheme b. Sensors S1 and S2 are not illuminated when the second illumination pattern scheme b is employed. In other words, both sensor S1 and sensor S2 are located in an area with a low illumination intensity such as a background illumination intensity. At the point in time corresponding to scheme b, sensors S1 and S2 will output signals indicative of a low level of illumination. This is illustrated in schemes g and h where it may be seen that the temporal signals TS1 and TS2 both have a low signal level at point b.

(36) Form the respective temporal signals TS1, TS2 and the illumination pattern at scheme b, it may be now be concluded that sensor S1 is located somewhere in the area indicated by the bracket above scheme b. Correspondingly, it may be concluded that sensor S2 is located somewhere in the area indicated by the bracket below scheme b.

(37) Followingly, sensors S1, S2 are illuminated with a third illumination pattern of scheme c. Sensors S1 and S2 are illuminated when the third illumination pattern of scheme c is employed. In other words, both sensor S1 and sensor S2 are located in an area which is illuminated by the projector 104. At the point in time corresponding to scheme c, sensors S1 and S2 will output signals indicative of a high level of illumination. This is illustrated in schemes g and h where it may be seen that the temporal signals TS1 and TS2 both have a high signal level at point c.

(38) Form the respective temporal signals TS1, TS2 and the illumination pattern at scheme c, it may be now be concluded that sensor S1 is located somewhere in the area indicated by the bracket above scheme c. Correspondingly, it may be concluded that sensor S2 is located somewhere in the area indicated by the bracket below scheme c.

(39) The three initial illumination patterns are more specifically predetermined dichotomy patterns along a first major direction.

(40) Followingly, a fourth illumination pattern of scheme d is employed. When employing the illumination pattern of scheme d sensor S1 is illuminated while sensor S2 is not. In other words, sensor S1 is at scheme d located in an area with high illumination intensity while sensor S2 is located in an area with a lower illumination intensity such as a background illumination intensity. At the point in time corresponding to scheme d, sensor S1 will output a signal indicative of a higher level of illumination as compared to sensor S2. This is illustrated in schemes g and h where it may be seen that the temporal signal TS1 of sensor S1 has a higher signal level than the temporal signal TS2 of sensor S2 at point d.

(41) Form the respective temporal signals TS1, TS2 and the illumination pattern at scheme d, it may be concluded that sensor S1 is located somewhere in the area indicated by the bracket to the right of scheme d. Correspondingly, it may be concluded that sensor S2 is located somewhere in the area indicated by the bracket to the left of scheme d.

(42) Followingly, the sensors S1, S2 are illuminated with a fifth illumination pattern of scheme e. Sensors S1 and S2 are not illuminated when the fifth illumination pattern scheme e is employed. In other words, both sensor S1 and sensor S2 are located in an area with a low illumination intensity such as a background illumination intensity. At the point in time corresponding to scheme e, sensors S1 and S2 will output signals indicative of a low level of illumination. This is illustrated in schemes g and h where it may be seen that the temporal signals TS1 and TS2 both have a low signal level at point e.

(43) Form the respective temporal signals TS1, TS2 and the illumination pattern at scheme e, it may now be concluded that sensor S1 is located somewhere in the area indicated by the bracket to the right of scheme e. Correspondingly, it may be concluded that sensor S2 is located somewhere in the area indicated by the bracket to the left of scheme e.

(44) Followingly, sensors **S1**, **S2** are illuminated with a sixth illumination pattern of scheme **f**. Sensors **S1** and **S2** are illuminated when the sixth illumination pattern of scheme **f** is employed. In other words, both sensor **S1** and sensor **S2** are located in an area which is illuminated by the projector **104**. At the point in time corresponding to scheme **f**, sensors **S1** and **S2** will output signals indicative of a high level of illumination. This is illustrated in schemes **g** and **h** where it may be seen that the temporal signals **TS1** and **TS2** both have a high signal level at point **f**.

(45) Form the respective temporal signals **TS1**, **TS2** and the illumination pattern at scheme **f**, it may be now be concluded that sensor **S1** is located somewhere in the area indicated by the bracket to the right of scheme **f**. Correspondingly, it may be concluded that sensor **S2** is located somewhere in the area indicated by the bracket to the left of scheme **f**.

(46) The three final illumination patterns of schemes **d-f** are more specifically predetermined dichotomy patterns along a second major direction, where the first major direction being perpendicular to the second major direction.

(47) It may be concluded from the temporal signal **TS1** of the six above described illumination patterns that the sensor **S1** is located in the area **A1** of scheme **i**. Correspondingly, it may be concluded from the temporal signal **TS2** of the six above described illumination patterns that the sensor **S2** is located in the area **A2** of scheme **i**. In practice, as described above the respective areas **A1** and **A2** of scheme **i** corresponds to in which directions the sensors **S1**, **S2** are arranged in relation to the projector **104**. In practice, the number of illumination patterns of the above type may be increased so as to more accurate determine the locations of the sensors **S1** and **S2**. In other words, by increasing the number of illumination patterns of the above type the areas **A1** and **A2** of scheme **i** may be reduced in size.

(48) As an alternative to predetermined dichotomy patterns, a relatively narrow light cone may scan the structural ceiling surface **102** on which the optical sensors **S1** and **S2** are attached. It may be then be recorded for what space angle the light cone impinges on the respective sensors **S1** and **S2**.

(49) As an alternative to predetermined dichotomy patterns, a laser beam may scan the structural ceiling surface **102** on which the optical sensors **S1** and **S2** are attached. It may be then be recorded for what directions the laser beam impinges on the respective sensors **S1** and **S2**.

(50) Other strategies may also be used to advantage for locating the optical sensors **S1** and **S2** attached to the structural ceiling surface **102**.

(51) Now referring back also to FIG. **1** and FIG. **2**, as previously indicated, sensor **S1** and sensor **S2** may correspond to any of the optical sensors **112a-112d** of FIG. **1** or the optical sensors **212a-f** of FIG. **2**. Hence, in a manner corresponding to what has been described above in conjunction to FIG. **3** it may be concluded how the respective optical sensors **112a-112d** (or **212a-d**) are located relative to the projector **104** in terms of in which directions the sensors **112a-112d** (or **212a-d**) are arranged in relation to the projector **104**.

(52) Based on determined directions of the respective sensors **112a-112d** (or **212a-d**) and the known distribution pattern an image plane relative to the projector may be now be determined by mathematical calculations. Needless to say, the directions of the respective sensors **112a-112d** (or **212a-d**) need not be determined. Rather, an image plane relative to the projector **104** may be determined based on the known distribution pattern of the set of optical sensors **112a-112d** (or **212a-d**) and the outputted temporal signals **TS1**, **TS2** of each of the optical sensors **112a-112d** (or **212a-d**).

(53) The image plane relative to the projector **104** may be determined using homography algorithms as is known in the art. The main purpose of determining the image plane relative to the projector **104** is to correct the image projected by the projector **104** to fit the plane of the structural ceiling surface **102** or to at least compensate the image projected by the projector **104** to become parallel with the plane of the structural ceiling surface **102**.

(54) The image plane relative to the projector **104** may be determined by inverting the homography matrix. In the subject case, the homography matrix includes elements relating to positions of at

least four optical sensors **112a-112d** (or **212a-d**).

(55) For instance, the optical sensors **112a-112d** may as depicted in FIG. 1 be positioned at equivalent distances around a centre point. Hence, in FIG. 1 the intersection of the adjustable holder **116** and the common substrate **114** may correspond to the centre point. The centre point may for reasons of simplicity is given the coordinates (0, 0), i.e. the centre point may be considered to be located at the origin of a coordinate system having an X-axis and a Y-axis. The respective optical sensors **112a-112d** may for reasons of simplicity be given the coordinates (1, 1), (-1, 1), (1, -1) and (-1, -1). That is, each optical sensor may be considered located one distance or length unit away from the centre point in each one of the X-direction and the Y-direction. All optical sensors **112a-112d** depicted in FIG. 1 are located in different directions with respect to the centre point which is reflected in the signs of the respective coordinates of the optical sensors **112a-112d**.

(56) Hence, using the outputted temporal signals TS1, TS2 of each of the optical sensors **112a-112d**, the position of each optical sensor of the optical sensors **112a-112d** in view of the projector **104** may be determined. The positions of each of the optical sensors **112a-112d** in the view of the projector may be denoted coordinates (X.sub.1, Y.sub.1), (X.sub.2, Y.sub.2), (X.sub.3, Y.sub.3) and (X.sub.4, Y.sub.4).

(57) Now considering the eight points (1, 1), (-1, 1), (1, -1), (-1, -1), (X.sub.1, Y.sub.1), (X.sub.2, Y.sub.2), (X.sub.3, Y.sub.3) and (X.sub.4, Y.sub.4) which may be included in a 3×3 homography matrix.

(58) The homography matrix including the eight points may now be inverted in order to determine the image plane relative to the projector **104**.

(59) More specifically, the inverted homography matrix will result in a transform matrix or projective transform which when applied, to e.g. an image, will place the point (X.sub.1, Y.sub.1) in the point (1, 1), the point (X.sub.2, Y.sub.2) in the point (-1, 1), the point (X.sub.3, Y.sub.3) in the point (1, -1) and the point (X.sub.4, Y.sub.4) in the point (-1, -1). The projective transform will consequently include translation, rotation and scale.

(60) The inversion of the homography matrix may for instance be calculated using the tool OpenCV which is a programming library mainly aimed at computer vision.

(61) Since a projective transform have 8 degrees of freedom the locations of at least four optical sensors **112a-112d** (or **212a-d**) need to be determined in relation to the projector **104**. The projective transform has 8 degrees of freedom for 9 coefficients (3×3 matrix). However, because such transforms are defined within a scaling factor, which removes one degree of freedom, one of the coefficients can be arbitrarily set to 1.

(62) After having determined the image plane relative to the projector **104**, the projector may display an image indicative of installation locations **120** of primary profiles at the image plane, as is shown in FIG. 4.

(63) More specifically, the user device **110** may determine the image plane relative to the projector **104** based on the known distribution pattern of the set of optical sensors **112a-112d** (or **212a-d**) and the outputted temporal signals TS1, TS2 of each of the optical sensors **112a-112d** (or **212a-d**). This may typically be determined by mathematical calculations performed in the user device **110**, e.g. according to the above example. The user device **110** may thus transmit a signal to the image source **108**. The signal may thus be constituted such that the displayed image of the projector **104** based on the image signal from the image source **108** is displayed at the determined image plane.

(64) In FIG. 4, it is illustrated how an image **122** is displayed at the structural ceiling surface **102** of the room **100**. Hence, the structural ceiling surface **102** corresponds to the determined image plane. The image **122** includes installation locations **120** of primary profiles of the grid of profiles. In FIG. 4 it is depicted how installation locations **120** of five primary profiles are indicated as straight parallel lines displayed on the structural ceiling surface **102** of the room **100**.

(65) The optical sensors **112a-d** have been removed in FIG. 4 but may very well be present at the time of displaying the image **122**.

(66) The displayed image **122** comprises displayed fix points **124** of the primary profiles to be installed. The fixpoints **124** may be indicated with image features such as dots or crosses at locations where it is appropriate to fix the primary profiles to be installed. The displayed fixpoints **124** may consequently be displayed at certain distances where a firm installation of the primary profiles will be achieved while not using an excessive amount of fix points **124**.

(67) Hence, in the situation depicted in FIG. **4** the image plane has been determined such that the image plane substantially includes physical locations of the optical sensors **112a-112d** (or **212a-d**) of the set of optical sensors. Moreover, the image **122** displayed by the projector **104** is displayed on the structural ceiling surface **102**. For this reason, a projective transform has been calculated based on a location of the projector **104** relative to the image plane. The projective transform may advantageously be calculated by the user device **110**. The projective transform has been applied to the displayed image **122** depicted in FIG. **4**. By applying the projective transform the displayed image **122** may be compensated for size and wrap with respect to the image plane and consequently to the structural ceiling surface **102** of the room **100**. In other words, the projective transform may be applied such that the image **122** is correctly displayed on the structural ceiling surface **102**, i.e. the displayed image **122** indicative of installation locations **120** of the primary profiles corresponds to actual and desired installation locations of the primary profiles to be installed.

(68) More specifically, the projective transform may be determined by inverting the homography matrix as described above.

(69) Also, the rotation of the projector **104** relative to a desired direction of the installation locations **120** of primary profiles at the image plane may be determined. The rotation may be determined by mathematical calculations based on the known distribution pattern of the set of optical sensors **112a-112c** (or **212a-d**) and the outputted temporal signals TS1, TS2 of each of the optical sensors **112a-112c** (or **212a-d**). The rotation may be calculated by the user device **110** and may consequently be transmitted to the image source **108** such that the rotation of the displayed image **122** is compensated based on the determined rotation.

(70) More specifically, the rotation of the projector **104** relative to a desired direction of the installation locations **120** of primary profiles at the image plane may be determined from the projective transform resulting from inversion of the homography matrix as described above.

(71) The position of the displayed image **122** of FIG. **4** may be adjusted based on building information model data, BIM data. By adjusting the position of the displayed image **122** based on BIM data the image **122** including the installation locations **120** of primary profiles at the image plane, i.e. at the structural ceiling surface **102**, may be adjusted sideways such that the installation locations **120** of primary profiles at the image plane are aligned with certain building features, such as walls or air outlets. Correspondingly, the position of the image **122** may be adjusted such that installation locations **120** of the primary profiles are positioned at locations where there is a reduced risk of interfering with or damaging concealed features of the building, such as piping or electrical cables. In order to achieve this, the user device **110** may include BIM data stored therein or the user device **110** may receive BIM data from a remote resource such as a server or a cloud service. The user device **110**, may thus based on the BIM data adjust the signal transmitted to the image source **108** such that the position of the displayed image **122** is adjusted sideways as desired.

(72) The position of the displayed image **122** of FIG. **4** may be adjusted based on a user-initiated input signal. Hence, a user may typically adjust the position of the displayed image **122** by an input on the user device **110**. The user device **110** may in response to the user input adjust the signal transmitted to the image source **108** such that the position of the displayed image **122** including the installation locations **120** of primary profiles at the image plane, i.e. at the structural ceiling surface **102**, is adjusted sideways as desired. By doing this, a user may adjust the position of the image **122** such that installation locations **120** of primary profiles at the image plane are aligned with certain building features, such as walls or air outlets. Correspondingly, the position of the image **122** may be adjusted such that installation locations **120** of the primary profiles are positioned at locations

where there is a reduced risk of interfering with or damaging concealed features of the building, such as piping or electrical cables.

(73) Correspondingly, a rotation of the displayed image **122** of FIG. **4** may be adjusted based on a user-initiated input signal.

(74) The optical sensors **112a-112c** (or **212a-d**) may be arranged at locations corresponding to junctions of the grid of profiles to be installed. By this, a user may get an instant and visual confirmation that the image **122** is displayed correctly, i.e. a user may verify that the sensors **112a-112c** (or **212a-d**) actually are aligned at locations corresponding to junctions of the grid of profiles in the displayed image **122**.

(75) Now referring to FIG. **5**, here room **100** is depicted with a different image **222** displayed at the structural ceiling surface **102**. In order to avoid undue repetition, only differences in relation to FIG. **4** will be discussed below.

(76) As can be seen in FIG. **5**, installation locations **220** of primary profiles to be installed are shown in the image **222**. The installation locations **220** of the of primary profiles to be installed are shown as straight lines extending at oblique angles with respect to each other. Hence, the installation locations **220** of the of primary profiles to be installed are shown as non-parallel lines in the image **222**.

(77) The image **222** includes more information as compared to the image **122** of FIG. **4**. The depicted image **222** of FIG. **5** includes installation guidance **126** based on BIM data. The installation guidance **126** is thus displayed as a part of the image **222**. The included installation guidance **126** is based on BIM data in the sense that the displayed installation guidance **126** is displayed in manner where features of the building is taken into account. The displayed installation guidance **126** may for instance take concealed features of the building into account. Not yet installed features of the building may be taken into account such that sufficient space is left for the features to be installed later on. The displayed installation guidance **126** may thus be positioned in areas which are suitable for installation of the primary profiles to be installed.

(78) The displayed image **122** may include may include fix points **128** of primary profiles to be installed. The fix points **128** may thus be displayed at suitable locations where there is a reduced risk of interfering with or damaging concealed features of the building. The fixpoints **128** may be indicated with image features such as dots or crosses at locations where it is appropriate to fix the primary profiles to be installed. The displayed fixpoints **128** may consequently be displayed at certain distances where a firm installation of the primary profiles will be achieved while not using an excessive amount of fix points **128**. The displayed fix points **128** is an example of displayed installation guidance **126**.

(79) The displayed image **122** may include forbidden areas **130** for fix points **128** of primary profiles to be installed. The forbidden areas **130** may be displayed in areas where fix points **128** would risk interfering with or damaging concealed features of the building, such as piping or electrical cables. The forbidden areas **130** may be displayed in areas where fix points **128** would risk interfering with features of the building that has not yet been installed. The displayed forbidden areas **130** is an example of displayed installation guidance **126**.

(80) The displayed image **122** may include building information model data, BIM data **132**. The displayed image **122** may consequently visualise concealed features **132** of the building, such as piping or electrical cables. The displayed image **122** may consequently visualise features **132** of the building that has not yet been installed. The image **122** may as a few non-limiting examples include visual representations **132** of cables, pipes, wires, airducts, air outlets, lighting appliances, heaters, smoke detectors, fans, wi-fi access points, sprinklers, interior walls and windows.

(81) The displayed installation guidance **126** may as a further example include a movie clip **134** showing an installation scheme how a typical primary profile is installed at the structural ceiling **102** of the room **100**. The movie clip **134**, may include indications on where to fix the primary profiles to be installed. That is the movie clip **134** may include information regarding fix points **128**

of the primary profiles to be installed. The movie clip **134** may also include information regarding suitable ways of drilling in the structural ceiling **102**, as well as which type of fasteners to suitably use for the structural ceiling **102** at hand. Hence, different drilling techniques and fasteners may be displayed based on the material of the structural ceiling **102** at hand. Information regarding the material of the structural ceiling **102** at hand may for instance be gathered by the user device **110** from a server having BIM data stored thereon.

(82) Now referring to FIG. **6**, here room **100** is depicted with two different projectors **104**, **204** used to display an image **322** at the structural ceiling surface **102**. In order to avoid undue repetition, only differences in relation to FIG. **4** will be discussed below.

(83) As is illustrated in FIG. **6**, a second projector **204** is arranged on the floor **106** of the room **100** in addition to the projector **104**. The second projector **204** is like the projector **104** arranged at a distance from the structural ceiling surface **102**. The image **322** is displayed at the image plane by the projector **104** and the second projector **204**. The image **322** is jointly formed by the projector **104** and the second projector **204**. The image source **108** connected to the projector and the image source **208** connected to the second projector **204** are both connected to the user device **110**. The user device **110** may thus distribute image data to the image source **108** and the image source **208** such that the image **322** is jointly formed by the projector **104** and the second projector **204**. Before, the image **322** may be displayed by the projector **104** and the second projector **204**, a common image plane is determined for each one of the projector **104** and the second projector **204** as described above.

(84) In the depicted setup of FIG. **6**, the image plane coincides with the structural ceiling surface **102**. Hence, the image **322** is displayed at the structural ceiling surface **102**. The image **322** includes installation locations **120** of primary profiles. The installation locations **120** are depicted as straight lines extending in parallel. However, different layouts of the installation locations **120** may be used to advantage when using a second projector **204** in addition to the projector **104**. Also, information of the kind described in conjunction with FIG. **5** may be displayed in image **322**. By utilising the projector **104** and the second projector **204** a larger installation area may be covered by the image **322** at the same time. Moreover, an increased redundancy may be achieved in case of failure of the projector **104** or the second projector **204**. Furthermore, the risk of certain areas of the structural ceiling surface **102** being shadowed, by for instance pillars, light armatures, inner walls or similar, may also be reduced.

(85) Now referring to FIG. **7** in addition to FIGS. **1-6**. In FIG. **7** is shown a flow scheme of a method **700** which may be used for installation of a grid of profiles of a ceiling system attached to a structural ceiling surface **102** as have been described above in conjunction with FIGS. **1-6**. The method **700** comprising; in sequence illuminating **702**, by a projector **104**, different sub sets of a set of optical sensors **112a-d**, **212a-d**, **S1**, **S2** separately arranged in a known distribution pattern on the structural ceiling surface **102**, wherein each optical sensor **112a-c**, **212a-c**, **S1**, **S2** of the set of optical sensors being arranged to output a temporal signal **TS1**, **TS2** indicative of a level of illumination, determining **704** an image plane relative to the projector **104** based on the known distribution pattern of the set of optical sensors **112a-c**, **212a-c**, **S1**, **S2** and the outputted temporal signals **TS1**, **TS2** of each of the optical sensors **112a-d**, **212a-d**, **S1**, **S2**, displaying **706**, by the projector **104**, an image **122**, **222**, **322** indicative of installation locations **120**, **220** of the primary profiles at the image plane.

(86) As is understood, the respective features and elements described in conjunction with the respective FIGS. **1-7** may be combined or interchanged to suit specific installation needs, when installing a grid of profiles for a ceiling system.

(87) Moreover, it will be appreciated that the concept of displaying an image indicative of installation locations at an image plane may advantageously be used in the course of installing other entities than primary profiles of a grid of profiles for a ceiling system.

(88) For instance, installation locations of ceiling tiles installed independently, i.e. without a grid of

profiles, may be displayed to advantage a determined image plane.

(89) Moreover, installation locations of sound absorbing baffles, such as ceiling or wall mounted baffles may advantageously be displayed a determined image plane.

(90) Also, installation locations of other devices, such as fans, lightings, loudspeakers, sprinklers, wi-fi transceivers and air inlets may be displayed to advantage at a determined image plane.

(91) It will be appreciated that the present inventive concept is not limited to the variants shown. Several modifications and variations are thus conceivable within the scope of the invention which thus is exclusively defined by the appended claims.

Claims

1. A method for installation of a ceiling system attached to a structural ceiling surface, the method comprising: illuminating, in sequence and by a projector, different subsets of a set of optical sensors separately arranged in a known distribution pattern on the structural ceiling surface, wherein each optical sensor of the set of optical sensors being arranged to output a temporal signal indicative of a level of illumination, determining an image plane relative to the projector based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, and displaying, by the projector, an image indicative of installation locations of the ceiling system at the image plane.
2. The method according to claim 1, wherein the ceiling system comprises a grid of profiles comprising a plurality of primary profiles, and wherein the displaying the image comprises displaying information indicative of installation locations of the primary profiles at the image plane.
3. The method according to claim 1, wherein the determining the image plane comprises determining the image plane such that the image plane includes physical locations of the optical sensors of the set of optical sensors.
4. The method according to claim 1, wherein the displaying the image comprises displaying the image on the structural ceiling surface.
5. The method according to claim 4, wherein the displaying the image comprises calculating a projective transform based on a location of the projector relative to the image plane, and applying the projective transform to the image such that the displayed image is compensated for size and wrap with respect to the structural ceiling surface.
6. The method according to claim 1, wherein the determining the image plane comprises determining a rotation of the projector relative to a desired direction of the installation locations of the ceiling system at the image plane based on the known distribution pattern of the set of optical sensors and the outputted temporal signals of each of the optical sensors, and wherein the displaying the image comprises compensating a rotation of the image based on the determined rotation.
7. The method according to claim 1, wherein the displaying the image comprises adjusting a position of the image at the image plane based on building information model (BIM) data.
8. The method according to claim 1, wherein the displaying the image comprises adjusting a position of the image at the image plane based on a user-initiated input signal.
9. The method according to claim 2, wherein the optical sensors of the set of optical sensors are arranged at locations corresponding to junctions of the grid of profiles.
10. The method according to claim 1, wherein the optical sensors of the set of optical sensors are arranged on a common substrate which is adapted to be arranged at the structural ceiling surface.
11. The method according to claim 1, wherein the displaying the image comprises displaying installation guidance based on building information model (BIM) data.
12. The method according to claim 11, wherein the displaying the image comprises displaying fix points of the ceiling system to be installed.

13. The method according to claim 11, wherein the displaying the image comprises displaying forbidden areas for fix points of the ceiling system to be installed.
 14. The method according to claim 11, wherein the displaying the image comprises displaying fix points of primary profiles to be installed.
 15. The method according to claim 11, wherein the displaying the image comprises displaying forbidden areas for fix points of primary profiles to be installed.
 16. The method according to claim 1, wherein the displaying the image further comprises displaying building information model (BIM) data.
 17. The method according to claim 1, wherein the illuminating different subsets of the set of optical sensors comprises: illuminating, in sequence, different subsets of the set of optical sensors according to a first predetermined dichotomy pattern along a first major direction, and illuminating, in sequence, different subsets of the set of optical sensors according to a second predetermined dichotomy pattern along a second major direction, the first major direction being perpendicular to the second major direction.
 18. The method according to claim 1, further comprising: arranging a second projector, separate from the projector, at a distance from the structural ceiling surface, and displaying, by the projector and the second projector, the image indicative of installation locations of the ceiling system at the image plane.
-