

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405134
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Jiang; Kai et al.

Electronic seal label apparatus, electric motor assembly and electronic seal label verification method

Abstract

Provided are an electronic seal label apparatus, an electric motor assembly with the electronic seal label apparatus, and an electronic seal label verification method. The electronic seal label apparatus includes: a magnet configured on a first component; and a sensing element configured on a second component and fixed opposite the magnet. When relative motion takes place between the first component and the second component, the sensing element generates a first signal according to the Wiegand effect, so that a disassembly or assembly state between the first component and the second component, which can be removed from each other, can be detected automatically.

Inventors:	Jiang; Kai (Nanjing, CN), Sun; Yao (Nanjing, CN)
Applicant:	Siemens Aktiengesellschaft (Munich, DE)
Family ID:	68985702
Assignee:	Siemens Aktiengesellschaft (Munich, DE)
Appl. No.:	17/254889
Filed (or PCT Filed):	June 28, 2018
PCT No.:	PCT/CN2018/093460
PCT Pub. No.:	WO2020/000321
PCT Pub. Date:	January 02, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210207978 A1	Jul. 08, 2021

Publication Classification

Int. Cl.: G01D5/244 (20060101); G01B7/04 (20060101); H02K11/215 (20160101)

U.S. Cl.:

CPC G01D5/244 (20130101); G01B7/04 (20130101); H02K11/215 (20160101);

Field of Classification Search

CPC: H02K (11/215); G01B (7/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5072181	12/1990	Burger	324/207.2	G01D 5/34738
5332895	12/1993	Rieder	250/237G	G01D 5/2455
6084400	12/1999	Steinich	324/207.13	G01P 3/4815
2009/0039872	12/2008	Fischer	324/207.13	G01D 5/145
2010/0050455	12/2009	Siraky	33/708	G01D 5/2457
2013/0057263	12/2012	Hosek	N/A	N/A
2015/0153203	12/2014	Simon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103794023	12/2013	CN	N/A
105673922	12/2015	CN	N/A
105759701	12/2015	CN	N/A
107016304	12/2016	CN	N/A
19637388	12/1997	DE	N/A
19634626	12/1997	DE	N/A
19933568	12/2000	DE	N/A
102008048780	12/2009	DE	N/A
0542088	12/1992	EP	N/A
3382857	12/2017	EP	H02K 11/215
2588076	12/1986	FR	G01B 7/02
2066883	12/1980	GB	E05B 47/00
2071334	12/1980	GB	H03K 17/97
2071335	12/1980	GB	H03K 17/97
2071336	12/1980	GB	G01D 5/204
2071337	12/1980	GB	G01D 5/14
2073428	12/1980	GB	G01P 3/4815
2074390	12/1980	GB	H03K 17/723
2018036138	12/2017	JP	N/A
2018054489	12/2017	JP	N/A

OTHER PUBLICATIONS

Wiegand Sensors (six pages) (Year: 2019). cited by examiner
Translation of EP-3382857-A1 (Year: 2018). cited by examiner
Translation of FR-2588076-A1 (Year: 1987). cited by examiner
Translation of DE 196 34 626 C1 (Year: 1998). cited by examiner
International Search Report PCT/ISA/210 for International Application No. PCT/CN2018/093460 dated Mar. 28, 2019. cited by applicant
Written Opinion PCT/ISA/2137 for International Application No. PCT/CN2018/093460 dated Mar. 28, 2019. cited by applicant

Primary Examiner: Patel; Paresh

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

PRIORITY STATEMENT

(1) This application is the national phase under 35 U.S.C. § 371 of PCT International Application No. PCT/CN2018/093460, which has an International filing date of Jun. 28, 2018, which designated the United States of America, the entire contents of which are hereby incorporated herein by reference.

FIELD

(2) Embodiments of the present application generally relate to the field of security protection, in particular to electronic sealing label technology.

BACKGROUND

(3) In order to prevent non-professionals from disassembling or dismantling various types of instrument apparatus, especially precision apparatuses, a sealing label device will often be provided on the instrument apparatus; in general, the sealing label device is arranged in an adjustable position on the instrument apparatus. At present, existing sealing label devices generally lack an automatic detection function; a person performing a check must use the naked eye for identification, to determine whether a sealed instrument apparatus has been dismantled; the error rate is high and efficiency is low. If an instrument apparatus that has been dismantled is put into service, there is a strong possibility that it will suffer a drop in performance or even damage as a result. To avoid these problems, there is an urgent need in the art for a better solution to eliminate these problems.

(4) Moreover, in the field of industrial drive for example, an encoder is arranged at one side of an electric machine, and recorded electric machine running information is transmitted to a driver. For the sake of electric machine precision, some specific compensation data of each electric machine will be stored in the encoder arranged thereon, therefore it is necessary to ensure matching between the electric machine and encoder. If the encoder is replaced at will, this might result in the compensation data of the new encoder being mismatched with the original electric machine, such that the electric machine performance is degraded. Thus, it is necessary that the abovementioned sealing label device be used for this kind of electric machine and encoder to monitor a disassembly/assembly state of both. However, due to the structural characteristics of electric machines and encoders, there will be special requirements for sealing label devices in such applications.

SUMMARY

(5) At least one embodiment of the present invention realizes an automatic detection function, to

increase the security and service life of the entire system, and effectively avoid problems such as a drop in performance or even damage during use of an instrument apparatus that has been dismantled. Moreover, at least one embodiment of the present invention does not require any major changes to the structural design of an existing instrument apparatus, so is a low-cost improvement, and has good application prospects.

(6) According to one embodiment of the present invention, an electronic sealing label device is provided, suitable for detecting a disassembly/assembly state between a first component and a second component that can be removed from each other, characterized in that the electronic sealing label device comprises: a magnet, arranged on the first component; and a sensing element, the sensing element being arranged on the second component and fixed in a position opposite the magnet, wherein the sensing element exploits the Wiegand effect to generate a signal when relative movement occurs between the first component and second component, thereby realizing automatic detection.

(7) According to another embodiment of the present invention, an electric machine assembly is provided, characterized in that the electric machine assembly comprises: an electric machine housing, an encoder and an electronic sealing label device, the encoder being arranged in the electric machine housing, and the electronic sealing label device comprising: a magnet, arranged on the electric machine housing; and a sensing element, the sensing element being arranged on the encoder and fixed in a position opposite the magnet, wherein the sensing element exploits the Wiegand effect to generate a signal when relative movement occurs between the electric machine housing and the encoder.

(8) According to another embodiment of the present invention, an electronic sealing label verification method is provided, suitable for an assembly comprising an electronic sealing label device and a first component and a second component that can be removed from each other, characterized by comprising the following steps: **S1**: when the assembly is started, reading sign information in a signal recording module, wherein, when relative movement occurs between the first component and second component, the electronic sealing label device exploits the Wiegand effect to generate a signal, and changes the sign information in the signal recording module according to the signal; **S2**: determining whether the first component and second component have been removed according to the sign information; and **S3**: if it is determined that removal has occurred, stopping the operation of the first component and/or the second component. Automatic detection is realized, and operation is stopped immediately upon discovering that removal has occurred, thus improving system security.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings are included to provide further understanding of the present invention; they are recorded and form part of the present application. The drawings show embodiments of the present invention, and together with this description serve to explain the principles of the present invention. In the drawings:

(2) FIG. 1 shows a schematic diagram of an electronic sealing label device according to an embodiment of the present invention.

(3) FIG. 2 shows a schematic diagram of an electric machine assembly according to an embodiment of the present invention.

(4) FIG. 3 shows a sectional view in the direction of line III-III in FIG. 2.

(5) FIG. 4 shows a partial circuit diagram of an electronic sealing label device according to an embodiment of the present invention.

(6) FIG. 5 shows a flow chart of an electronic sealing label verification method according to an

embodiment of the present invention.

KEY TO REFERENCE LABELS

(7) **1** electric machine housing **2** encoder **3** driver **10** electronic sealing label device **20** control device **12** magnet **14** sensing element **16** information recording module **162** ferroelectric memory **164** amplification circuit **166** filter circuit

DETAILED DESCRIPTION OF THE EXAMPLE EMBODIMENTS

(8) According to one embodiment of the present invention, an electronic sealing label device is provided, suitable for detecting a disassembly/assembly state between a first component and a second component that can be removed from each other, characterized in that the electronic sealing label device comprises: a magnet, arranged on the first component; and a sensing element, the sensing element being arranged on the second component and fixed in a position opposite the magnet, wherein the sensing element exploits the Wiegand effect to generate a signal when relative movement occurs between the first component and second component, thereby realizing automatic detection.

(9) According to one embodiment, in the electronic sealing label device, the sensing element is an inductive coil, and the signal is an electric signal pulse. The inductive coil is a magnetically sensitive sensor; when in a magnetic field, the inductive coil cuts magnetic induction lines to generate an induced voltage, with high sensitivity.

(10) According to one embodiment, in the electronic sealing label device, the sensing element is a Wiegand sensor. During operation, the Wiegand sensor does not need an external power supply, and has high operating stability, having relatively low requirements with regard to distance and temperature of the environment of use, etc.

(11) According to one embodiment, in the electronic sealing label device, the distance between the sensing element and the magnet is less than or equal to a preset distance, to ensure normal operation of the sensing element.

(12) According to one embodiment, the electronic sealing label device further comprises: a signal recording module, adapted to receive the signal, and generate and record sign information according to the signal.

(13) According to one embodiment, in the electronic sealing label device, the information recording module comprises: a ferroelectric memory, wherein the ferroelectric memory changes a sign data bit thereof according to the signal in order to record the sign information. The ferroelectric memory is capable of performing storage rapidly with a very low electric energy demand, and has non-volatile storage characteristics.

(14) According to one embodiment, in the electronic sealing label device, the signal recording module further comprises: an amplification circuit and/or filter circuit, connected between the sensing element and the ferroelectric memory, thereby enhancing the ability of the electronic sealing label device to withstand interference.

(15) According to another embodiment of the present invention, an electric machine assembly is provided, characterized in that the electric machine assembly comprises: an electric machine housing, an encoder and an electronic sealing label device, the encoder being arranged in the electric machine housing, and the electronic sealing label device comprising: a magnet, arranged on the electric machine housing; and a sensing element, the sensing element being arranged on the encoder and fixed in a position opposite the magnet, wherein the sensing element exploits the Wiegand effect to generate a signal when relative movement occurs between the electric machine housing and the encoder.

(16) According to one embodiment, in the electric machine assembly, the electronic sealing label device comprises: a signal recording module, adapted to receive the signal, and generate and record sign information according to the signal, wherein the signal recording module is arranged on the encoder.

(17) According to one embodiment, the electric machine assembly further comprises: a control

device, arranged on the encoder, wherein the control device generates disassembly/assembly state information of the encoder according to the sign information.

(18) According to one embodiment, the electric machine assembly further comprises: a driver, wherein the driver controls the startup/shutdown of an electric machine in the electric machine assembly according to the disassembly/assembly state information of the control device.

(19) According to one embodiment, in the electric machine assembly, the electronic sealing label device comprises two magnets, installed on the electric machine housing in two directions, specifically axial and radial directions of the electric machine housing respectively; and two sensing elements, arranged in directions corresponding to the two magnets respectively, are provided inside the encoder.

(20) According to one embodiment, in the electric machine assembly, the electronic sealing label device comprises one magnet and one sensing element; the magnet is installed on the electric machine housing in an axial 45-degree direction of the electric machine housing; one sensing element, arranged in a direction corresponding to the magnet, is provided inside the encoder.

(21) According to another embodiment of the present invention, an electronic sealing label verification method is provided, suitable for an assembly comprising an electronic sealing label device and a first component and a second component that can be removed from each other, characterized by comprising the following steps: **S1**: when the assembly is started, reading sign information in a signal recording module, wherein, when relative movement occurs between the first component and second component, the electronic sealing label device exploits the Wiegand effect to generate a signal, and changes the sign information in the signal recording module according to the signal; **S2**: determining whether the first component and second component have been removed according to the sign information; and **S3**: if it is determined that removal has occurred, stopping the operation of the first component and/or the second component. Automatic detection is realized, and operation is stopped immediately upon discovering that removal has occurred, thus improving system security.

(22) According to one embodiment, in the electronic sealing label verification method, after the step of stopping the operation of the first component and/or the second component, the method further comprises: **S4**: resetting the sign information in the signal recording module; and **S5**: when restarting the assembly, performing steps **S1-S3** again, wherein step **S4** is performed after reassembling and configuring the first component and second component. An initialization operation can be realized automatically each time installation is performed, thus improving efficiency.

(23) According to one embodiment, in the electronic sealing label verification method, step **S3** further comprises: generating an alarm signal at the same time as stopping the operation of the first component and/or the second component. If the first component and second component have been removed from each other, a warning prompt is issued to a user, thus improving system security.

(24) According to one embodiment, in the electronic sealing label verification method, the first component is an electric machine and the second component is an encoder, wherein step **S3** further comprises: if it is determined that removal has occurred, only stopping the operation of the electric machine.

(25) It should be understood that the above general description and the following detailed description of the present invention are both example and illustrative, and intended to provide further explanation of the present invention as described in the claims.

(26) Embodiments of the present invention are now described, making detailed reference to the drawings. Preferred embodiments of the present invention are now referred to in detail; examples thereof are shown in the drawings. Wherever possible, identical labels are used to denote identical or similar parts in all of the drawings. Moreover, although the terms used in the present invention are selected from well known terms in common use, some terms mentioned herein might be selected by the applicant according to his or her judgment; the detailed meanings thereof are

explained in the relevant parts of the description herein. Furthermore, it is necessary that the present invention be understood not just through the actual terms used, but also through the meaning contained in each term.

(27) The basic principles and preferred embodiments of the present invention are discussed in greater detail with reference to FIG. 1.

(28) Taking FIG. 1 as an example, an electronic sealing label device **10** according to the present invention mainly comprises a magnet **12** and a sensing element **14**, the magnet **12** being arranged on a first component, and the sensing element **14** being arranged on a second component, wherein the first component and second component can be removed from one another. The relative positions of the magnet **12** and sensing element **14** are fixed; that is, in a normal state of the first component and second component, the magnet **12** and sensing element **14** are both located in correct installation positions, but when relative movement occurs between the first component and second component due to dismantling or some other reason, causing the magnet **12** or sensing element **14** to deviate from the correct position, the sensing element **14** can exploit the Wiegand effect to generate a signal, i.e. the electronic sealing label device can detect a disassembly/assembly state between the first component and second component.

(29) The electronic sealing label device **10** may further comprise a signal recording module **16**; the signal recording module **16** is connected to the sensing element **14**, receives a signal from the sensing element **14**, and generates and records sign information according to the signal. The signal recording module **16** may further be connected to a control device **20**; the control device **20** may control an operating state of the first component and second component according to the sign information, to prevent the normal use of an instrument apparatus that has been illegally dismantled and interfered with.

(30) The sensing element **14** may be for example an inductive coil, which will generate an electric signal pulse when moving in the magnetic field of the magnet **12**. The inductive coil is a magnetically sensitive sensor; when in the magnetic field, the inductive coil cuts the magnetic induction lines to generate an induced voltage, with high sensitivity. Moreover, according to another embodiment, the sensing element **14** may be for example a Wiegand sensor. A Wiegand sensor is composed of a specially processed magnetically bistable functional alloy wire (sensitive wire) and an inductive coil wound outside the wire. When a magnetic field of a particular polarity (e.g. N pole) parallel to the sensitive wire attains an intensity which triggers magnetic induction, magnetic domains in the sensitive wire are excited and will move, with the magnetization directions instantaneously turning to the same direction; at the same time, the magnetic field in the space around the sensitive wire also undergoes an instantaneous change, and an electric pulse is thereby induced in the inductive coil. During operation, the Wiegand sensor does not need an external power supply, being able to output a voltage of 3-5 V, and can drive a microprocessor directly; furthermore, the Wiegand sensor has relatively low requirements with regard to the temperature of the environment of use, having an operating temperature range as wide as -196°C . to $+300^{\circ}\text{C}$. In general, in order to ensure the operating stability of the sensing element **14**, it is necessary to put the sensing element **14** in a certain magnetic field strength; thus, to ensure the magnetic field strength, the distance between the sensing element **14** and the magnet **12** is less than or equal to a preset distance. For example, in one embodiment, the distance between the magnet **12** and the sensing element is not less than 15 mm. When the operating distance between the Wiegand sensor and the magnet **12** reaches 15 mm, the voltage of the outputted electric signal is not lower than 3 V; when the operating distance between the Wiegand sensor and the magnet **12** reaches 30 mm, a voltage signal of more than 100 mV can still be outputted.

(31) In the circuit structure shown in FIG. 4, the control device **20** may for example be an MCU, and the information recording module **16** may for example be a ferroelectric memory **162**; the ferroelectric memory **162** changes a sign data bit **Dat0** thereof according to a signal in order to record sign information. The ferroelectric memory (FRAM, ferroelectric RAM) is a random access

memory, which is capable of performing storage rapidly with a very low electric energy demand, and can operate like RAM, with extremely low read-write power consumption; furthermore, the content of the ferroelectric memory will not be affected by external conditions such as magnetic field factors, can be used like an ordinary ROM memory, and has non-volatile storage characteristics. Taking FIG. 4 as an example, the ferroelectric memory **162** has two states, namely “read” and “write”; the read and write states thereof are controlled by a port WE. A switch K1 is a triple pole double throw switch; when the switch K1 is moved to a position **1** (the left-hand side position as shown in FIG. 4), the port WE is grounded, and the ferroelectric memory **162** is in the “write” state; at the same time, a signal generated by the Wiegand sensor **14** can be inputted to an input port VDD of the ferroelectric memory **162**, and the ferroelectric memory **162** can change the sign data bit Dat0 thereof according to the received signal in order to record sign information. In one embodiment, an initial setting of the sign data bit Dat0 of the ferroelectric memory **162** is “1”, and when the input port VDD receives the signal from the Wiegand sensor **14**, the ferroelectric memory **162** changes the sign data bit Dat0 thereof to “0”; when the switch K1 is moved to a position **2** (the right-hand side position as shown in FIG. 4), the port WE is energized, and the ferroelectric memory **162** is in the “read” state, i.e. the MCU can read sign information through the sign data bit Dat0 of the ferroelectric memory **162**.

(32) In a preferred embodiment, the signal recording module **16** may further comprise an amplification circuit **164** and/or a filter circuit **166** connected between the sensing element **14** and the ferroelectric memory **162**. The signal generated by the sensing element **14** will sometimes suffer interference from other factors, and secondary waves or glitches might occur; in order to eliminate the interference caused by secondary waves and glitches, the amplification circuit **164** and/or a filter circuit **166** can be used. After being amplified and shaped by the amplification circuit **164** and filter circuit **166**, the signal becomes an approximately rectangular pulse, and it is thus possible to ensure that what the signal recording module **16** receives is a main signal of the sensing element **14**, thereby enhancing the ability of the electronic sealing label device **10** to withstand interference.

(33) An embodiment of an electric machine assembly provided in the present invention is discussed in greater detail in conjunction with FIGS. 2 and 3. In FIGS. 2 and 3, an encoder **2** is a precision measurement apparatus, arranged in an electric machine housing **1**, wherein the encoder **2** can be installed by being connected to a shaft of the electric machine; the encoder is a sensor that measures mechanical displacement, by converting an angular displacement of mechanical rotation or linear displacement to an electric signal. If a non-professional disassembles or dismantles the encoder, this will result in a drop in the accuracy of compensation of electric machine torque disturbance during electric machine operation, in turn leading to a fall in electric machine performance.

(34) The electronic sealing label device **10** formed by the abovementioned magnet **12** and sensing element **14** is particularly suited to the anti-dismantling application scenario of the electric machine housing **1** and encoder **2**, where the separation is small and the internal installation space is limited. Specifically, the present invention provides an electric machine assembly; taking FIG. 2 as an example, the electric machine assembly comprises the electric machine housing **1**, the encoder **2** and the electronic sealing label device **10**. The encoder **2** is arranged in the electric machine housing **1**; the electronic sealing label device **10** comprises the magnet **12** arranged in the electric machine housing **1** and the sensing element **14** arranged on the encoder **2**. The relative positions of the sensing element **14** and the magnet **12** are fixed; when relative movement occurs between the electric machine housing **1** and the encoder **2**, the sensing element **14** generates a signal, and it is thereby possible to automatically detect whether the encoder **2** has been moved. In the electric machine assembly, the electronic sealing label device **10** may comprise the signal recording module **16** for generating and recording sign information; the signal recording module **16** is arranged in the encoder **2**. The electric machine assembly may further comprise a control device **20**; the control

device **20** is also arranged on the encoder **2**, and the control device **20** generates disassembly/assembly state information of the encoder **2** according to sign information recorded in the signal recording module **16**. In addition, in one embodiment, the electric machine assembly may further comprise a driver **3**; the driver **3** controls the startup/shutdown of an electric machine in the electric machine assembly according to the disassembly/assembly state information of the control device **20**, thereby ensuring that when the driver **3** drives the electric machine to operate, the electric machine and the encoder **2** both remain in the correct installation positions.

(35) Under the action of external forces, the encoder **2** might rotate around an axis, and might also experience displacement in the axial direction of the electric machine. When installation is carried out, any number of magnets **12** can be arranged on the electric machine housing **1** in any way, and the sensing element **14** is arranged in the encoder **2**, with the number and position(s) of the sensing element(s) **14** corresponding to the magnet(s) **12**; it is thus possible to ensure that when the encoder **2** rotates or moves, the sensing element **14** outputs an electric signal pulse. The positions in which the magnet **12** and the sensing element **14** are arranged can be optimized for the disassembly/assembly characteristics of the encoder **2**, to ensure that any dismantling action will cause the sensing element **14** to generate a signal, thus improving the precision of detection. In one embodiment, the electronic sealing label device **10** comprises one magnet **12** and one sensing element **14**; the magnet **12** is installed on the electric machine housing **1** in an axial 45-degree direction of the electric machine housing **1**; one sensing element **14**, arranged in a direction corresponding to the magnet **12**, is provided inside the encoder **2**. Alternatively, in another embodiment, the electronic sealing label device **10** comprises two magnets **12**, the two magnets **12** being installed on the electric machine housing **1** in two directions, specifically axial and radial directions of the electric machine housing **1** respectively; and two sensing elements **14**, arranged in directions corresponding to the two magnets **12** respectively, are provided inside the encoder **2**.

(36) FIG. 5 shows schematically a flow chart of an electronic sealing label verification method according to an embodiment of the present invention. In this embodiment, the electronic sealing label verification method mainly comprises three steps, S1-S3. Step S1: when an assembly is started, reading sign information in the signal recording module, wherein, when relative movement occurs between the first component and second component, the electronic sealing label device exploits the Wiegand effect to generate a signal, and changes the sign information in the signal recording module according to the signal; step S2: determining whether the first component and second component have been removed according to the sign information; and step S3: if it is determined that removal has occurred, stopping the operation of the first component and/or second component. In a preferred embodiment, if the first component and second component have been removed from each other, then at the same time as the stopping of operation of the first component and/or second component is controlled, it is also possible to generate an alarm signal to issue a warning prompt to a user, to improve system security.

(37) In one embodiment, in order to further realize automated control, after the step of stopping the operation of the first component and/or second component, the method further comprises: step S4: resetting the sign information in the signal recording module; and step S5: when restarting the assembly, performing steps S1-S3 again, wherein step S4 is performed after reassembling and configuring the first component and second component. Each time installation is carried out, an initialization operation of the electronic sealing label device can be automatically realized, to improve efficiency. In one particular embodiment, the first component is the electric machine and the second component is the encoder **2**, and the information recording module **16** of the electronic sealing label device is initialized after each installation of the encoder **2**; for example, the sign data bit Dat0 of the ferroelectric memory **162** is restored to the initial set value "1", and in step S3, if it is determined that the first component and second component have been removed, operation of the electric machine is stopped.

(38) It will be obvious to those skilled in the art that various amendments and alterations could be

made to the above example embodiments of the present invention without deviating from the spirit and scope of the present invention. Thus, it is intended that the present invention should cover amendments and alterations to the present invention that fall within the scope of the attached claims and their equivalent technical solutions.

Claims

1. An electronic sealing label device, suitable for detecting a disassembly/assembly state between a first component and a second component, removable from each other, the electronic sealing label device comprising: a magnet, arranged on the first component; a sensing element, arranged inside the second component and within the first component, the sensing element being fixed in a position opposite the magnet, the sensing element being configured to exploit a Wiegand effect to generate a signal upon relative movement occurring between the first component and second component; and a recording module, arranged in the second component, and adapted to receive the signal, and adapted to generate and record sign information according to the signal.
2. The electronic sealing label device of claim 1, wherein the sensing element is an inductive coil, and the signal is an electric signal pulse.
3. The electronic sealing label device of claim 2, wherein a distance between the sensing element and the magnet is less than or equal to a set distance.
4. The electronic sealing label device of claim 1, wherein the sensing element is a Wiegand sensor.
5. The electronic sealing label device of claim 1, wherein a distance between the sensing element and the magnet is less than or equal to a set distance.
6. The electronic sealing label device of claim 1, wherein the recording module comprises: a ferroelectric memory, configured to change a sign data bit of the ferroelectric memory according to the signal, in order to record the sign information.
7. The electronic sealing label device of claim 6, wherein the recording module further comprises: at least one of an amplification circuit and a filter circuit, connected between the sensing element and the ferroelectric memory.
8. The electronic sealing label device of claim 1, further comprising: a control device arranged on the second component, the control device being configured generate disassembly/assembly state information of the second component according to the generated the signal.
9. An electric machine assembly, comprising: an electric machine housing; a rotatable encoder, the rotatable encoder being arranged in the electric machine housing; and an electronic sealing label device, including: a magnet, arranged within the electric machine housing; a sensing element, the sensing element being arranged in the rotatable encoder and fixed in a position opposite the magnet, the sensing element being configured to exploit a Wiegand effect to generate a signal upon relative movement occurring between the electric machine housing and the rotatable encoder; and a driver, to control startup/shutdown of an electric machine in the electric machine assembly according to disassembly/assembly state information of a control device.
10. The electric machine assembly of claim 9, wherein the electronic sealing label device comprises: a recording module, adapted to receive the signal, and generate and record sign information according to the signal, wherein the recording module is arranged on the rotatable encoder.
11. The electric machine assembly of claim 10, further comprising: the control device, arranged on the rotatable encoder, to generate disassembly/assembly state information of the encoder according to the sign information.
12. The electric machine assembly of claim 9, wherein the electronic sealing label device comprises two magnets, installed on the electric machine housing in axial and radial directions of the electric machine housing respectively; and two sensing elements, arranged in directions corresponding to the two magnets respectively, provided inside the rotatable encoder.

13. The electric machine assembly of claim 9, wherein the electronic sealing label device comprises one magnet and one sensing element; the magnet is installed on the electric machine housing in an axial 45-degree direction of the electric machine housing; and one sensing element, arranged in a direction corresponding to the magnet, provided inside the rotatable encoder.
14. An electronic sealing label verification method, suitable for an assembly including an electronic sealing label device and a first component and a second component, removable from each other, the method comprising: reading, upon the assembly being started, sign information from a sensing element arranged inside the second component and recording the sign information in a recording module, wherein, upon relative movement occurring between the first component and second component, the electronic sealing label device exploits a Wiegand effect to generate a signal, and changes the sign information in the recording module according to the signal; determining whether the first component and second component have been removed according to the sign information; and stopping, upon the determining indicating that removal has occurred, operation of at least one of the first component and the second component.
15. The electronic sealing label verification method of claim 14, wherein, after the stopping of the operation of at least one of the first component and the second component, the method further comprises: resetting the sign information in the recording module; and performing, upon restarting the assembly, the reading, determining and stopping again, wherein the resetting is performed after reassembling and configuring the first component and second component.
16. The electronic sealing label verification method of claim 14, wherein the stopping further comprises: generating an alarm signal at a same time as the stopping of the operation of at least one of the first component and the second component.
17. The electronic sealing label verification method of claim 14, wherein the first component is an electric machine and the second component is an encoder, wherein the stopping further comprises: only stopping, upon the determining indicating that removal has occurred, the operation of the electric machine.
-