

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12405463
B2
September 02, 2025
Edwin; Lionel Ernest et al.

Waveguide-based illumination for head mounted display system

Abstract

A head-mounted display system is configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user. The head-mounted display system comprises at least one diffusive optical element, at least one out-coupling optical element, at least one mask comprising at least one mask opening, at least one illumination in-coupling optical element configured to in-couple light from at least one illumination source into a light-guiding component, an image projector configured to in-couple an image and an at least one illumination source is configured to in-couple light into at least one illumination in-coupling optical element, an eyepiece, a curved light-guiding component, a light-guiding component comprising a portion of a frame, and/or two light-guiding components disposed on opposite sides of at least one out-coupling optical element.

Inventors: Edwin; Lionel Ernest (Hollywood, FL), Yeoh; Ivan Li Chuen (Wesley Chapel, FL), Jia; Zhiheng (Weston, FL), Carlson; Adam C. (Miami, FL)

Applicant: Magic Leap, Inc. (Plantation, FL)

Family ID: 69059922

Assignee: MAGIC LEAP, INC. (Plantation, FL)

Appl. No.: 18/647479

Filed: April 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240295732 A1	Sep. 05, 2024

Related U.S. Application Data

continuation parent-doc US 17459958 20210827 US 12001016 child-doc US 18647479
continuation parent-doc US 16503323 20190703 US 11106033 20210831 child-doc US 17459958
us-provisional-application US 62694366 20180705

Publication Classification

Int. Cl.: G09G5/00 (20060101); F21V8/00 (20060101); G02B27/00 (20060101); G02B27/01 (20060101); G06F3/01 (20060101); G06T19/00 (20110101)

U.S. Cl.:

CPC **G02B27/0093** (20130101); **G02B6/0025** (20130101); **G02B6/0028** (20130101); **G02B6/0031** (20130101); **G02B27/0176** (20130101); **G06F3/013** (20130101); **G06T19/006** (20130101);
G02B2027/0138 (20130101); G02B2027/0174 (20130101)

Field of Classification Search

CPC: G02B (27/0093); G02B (6/0025); G02B (6/0028); G02B (6/0031)

USPC: 345/8

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6850221	12/2004	Tickle	N/A	N/A
9081426	12/2014	Armstrong	N/A	N/A
9215293	12/2014	Miller	N/A	N/A
9348143	12/2015	Gao et al.	N/A	N/A
9417452	12/2015	Schowengerdt et al.	N/A	N/A
9470906	12/2015	Kaji et al.	N/A	N/A
9547174	12/2016	Gao et al.	N/A	N/A
9671566	12/2016	Abovitz et al.	N/A	N/A
9740006	12/2016	Gao	N/A	N/A
9791700	12/2016	Schowengerdt	N/A	N/A
9851563	12/2016	Gao et al.	N/A	N/A
9857591	12/2017	Welch et al.	N/A	N/A
9874749	12/2017	Bradski et al.	N/A	N/A
11106033	12/2020	Edwin et al.	N/A	N/A
2005/0024558	12/2004	Toyooka	N/A	N/A
2006/0028436	12/2005	Armstrong	N/A	N/A
2007/0081123	12/2006	Lewis	N/A	N/A
2012/0127062	12/2011	Bar-Zeev et al.	N/A	N/A
2012/0162549	12/2011	Gao et al.	N/A	N/A
2013/0082922	12/2012	Miller	N/A	N/A
2013/0100362	12/2012	Saeedi et al.	N/A	N/A
2013/0101253	12/2012	Popovich	385/37	G02B 27/017
2013/0117377	12/2012	Miller	N/A	N/A
2013/0125027	12/2012	Abovitz	N/A	N/A
2013/0208234	12/2012	Lewis	N/A	N/A
2013/0242262	12/2012	Lewis	N/A	N/A
2014/0071539	12/2013	Gao	N/A	N/A
2014/0177023	12/2013	Gao et al.	N/A	N/A
2014/0218468	12/2013	Gao et al.	N/A	N/A
2014/0267420	12/2013	Schowengerdt et al.	N/A	N/A
2014/0306866	12/2013	Miller et al.	N/A	N/A
2014/0306878	12/2013	Bhakta	N/A	N/A
2014/0354953	12/2013	Chen et al.	N/A	N/A
2015/0016777	12/2014	Abovitz et al.	N/A	N/A
2015/0103306	12/2014	Kaji et al.	N/A	N/A
2015/0178939	12/2014	Bradski et al.	N/A	N/A
2015/0205126	12/2014	Schowengerdt	N/A	N/A
2015/0220231	12/2014	Keane	345/474	G06T 19/006
2015/0222883	12/2014	Welch	N/A	N/A
2015/0222884	12/2014	Cheng	N/A	N/A
2015/0235461	12/2014	Schowengerdt	N/A	N/A

2015/0268415	12/2014	Schowengerdt et al.	N/A	N/A
2015/0277125	12/2014	Hirano et al.	N/A	N/A
2015/0302652	12/2014	Miller et al.	N/A	N/A
2015/0309263	12/2014	Abovitz et al.	N/A	N/A
2015/0310670	12/2014	Grossinger	N/A	N/A
2015/0326570	12/2014	Publicover et al.	N/A	N/A
2015/0346490	12/2014	Tekolste et al.	N/A	N/A
2015/0346495	12/2014	Welch et al.	N/A	N/A
2016/0011419	12/2015	Gao	N/A	N/A
2016/0026253	12/2015	Bradski et al.	N/A	N/A
2016/0037146	12/2015	McGrew	353/38	G03H 1/28
2017/0007450	12/2016	Samec et al.	N/A	N/A
2017/0122725	12/2016	Yeoh et al.	N/A	N/A
2017/0227764	12/2016	Kim	N/A	G02B 27/0103
2017/0285344	12/2016	Benko et al.	N/A	N/A
2017/0295362	12/2016	Travis	N/A	N/A
2017/0299860	12/2016	Wall et al.	N/A	N/A
2017/0323485	12/2016	Samec et al.	N/A	N/A
2017/0330042	12/2016	Vaziri	N/A	G02B 27/0093
2018/0067318	12/2017	St. Hilaire	N/A	N/A
2018/0136471	12/2017	Miller et al.	N/A	N/A
2018/0203230	12/2017	Vallius	N/A	G02B 27/0172
2018/0252857	12/2017	Glik et al.	N/A	N/A
2018/0335628	12/2017	Hung et al.	N/A	N/A
2018/0365490	12/2017	Agrawal et al.	N/A	N/A
2019/0004325	12/2018	Connor	N/A	N/A
2019/0196199	12/2018	Matsuki et al.	N/A	N/A
2020/0012095	12/2019	Edwin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103890637	12/2013	CN	N/A
2015184561	12/2014	JP	N/A
WO 2016179246	12/2015	WO	N/A

OTHER PUBLICATIONS

ARToolKit:

<https://web.archive.org/web/20051013062315/http://www.hitl.washington.edu:80/artoolkit/documentation/hardware.htm>
archived Oct. 13, 2005. cited by applicant

Azuma, "A Survey of Augmented Reality," Teleoperators and Virtual Environments 6, 4 (Aug. 1997), pp. 355-385.

<https://web.archive.org/web/20010604100006/http://www.cs.unc.edu/~azuma/ARpresence.pdf>. cited by applicant

Azuma, "Predictive Tracking for Augmented Realty," TR95-007, Department of Computer Science, UNC-Chapel Hill, NC, Feb. 1995. cited by applicant

Bimber, et al., "Spatial Augmented Reality—Merging Real and Virtual Worlds," 2005.<https://web.media.mit.edu/~raskar/book/BimberRaskarAugmentedRealityBook.pdf>. cited by applicant

International Preliminary Report on Patentability for PCT Application No. PCT/US19/40633, issued Jan. 5, 2021. cited by applicant

International Search Report and Written Opinion for PCT Application No. PCT/US19/40633, mailed Sep. 24, 2019. cited by applicant

Jacob, "Eye Tracking in Advanced Interface Design," Human-Computer Interaction Lab Naval Research Laboratory, Washington, D.C. / paper/ in Virtual Environments and Advanced Interface Design, ed. by W. Barfield and T.A. Furness, pp. 258-288, Oxford University Press, New York (1995). cited by applicant

Tanriverdi et al., "Interacting With Eye Movements in Virtual Environments," Department of Electrical Engineering and Computer Science, Tufts University, Medford, MA—paper/Proc. ACM CHI 2000 Human Factors in Computing Systems Conference, pp. 265-272, Addison-Wesley/ACM Press (2000). cited by applicant

Background/Summary

PRIORITY CLAIM (1) This application is a continuation of U.S. patent application Ser. No. 17/459,958, filed Aug. 27, 2021, which is a continuation of U.S. patent application Ser. No. 16/503,323 filed Jul. 3, 2019, now U.S. Pat. No. 11,106,033, which claims the benefit of U.S. Provisional Patent Application No. 62/694,366 filed on Jul. 5, 2018. Each patent application referenced in this paragraph is hereby incorporated by reference herein in its entirety.

BACKGROUND

Field

(1) The present disclosure relates to display systems and, more particularly, to augmented and virtual reality display systems.

Description of the Related Art

(2) Modern computing and display technologies have facilitated the development of systems for so called “virtual reality” or “augmented reality” experiences, in which digitally reproduced images or portions thereof are presented to a user in a manner wherein they seem to be, or may be perceived as, real. A virtual reality, or “VR”, scenario typically involves the presentation of digital or virtual image information without transparency to other actual real-world visual input; an augmented reality, or “AR”, scenario typically involves presentation of digital or virtual image information as an augmentation to visualization of the actual world around the user. A mixed reality, or “MR”, scenario is a type of AR scenario and typically involves virtual objects that are integrated into, and responsive to, the natural world. For example, an MR scenario may include AR image content that appears to be blocked by or is otherwise perceived to interact with objects in the real world.

(3) Referring to FIG. 1, an augmented reality scene **10** is depicted. The user of an AR technology sees a real-world park-like setting **20** featuring people, trees, buildings in the background, and a concrete platform **30**. The user also perceives that he/she “sees” “virtual content” such as a robot statue **40** standing upon the real-world platform **30**, and a flying cartoon-like avatar character **50** which seems to be a personification of a bumble bee. These elements **50**, **40** are “virtual” in that they do not exist in the real world. Because the human visual perception system is complex, it is challenging to produce AR technology that facilitates a comfortable, natural-feeling, rich presentation of virtual image elements amongst other virtual or real-world imagery elements.

(4) Systems and methods disclosed herein address various challenges related to AR and VR technology.

(5) Physical LEDs for IR eye tracking are aesthetically bad and impose mechanical placement constraints such that eye tracking performance is sub-optimal. An improved system configuration for illuminating the user's eye with IR light without considerably affecting the mass, power, volume, and cost of the overall system is desired.

SUMMARY

(6) Various examples are provided below.

(7) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one diffusive optical element disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one diffusive optical element is configured to diffusively couple light from the at least one illumination source out of the light-guiding component.

(8) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one out-coupling optical element disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple

light from the at least one illumination source out of the light-guiding component and cause light coupled out of the light-guiding component to diverge in a manner consistent with light originating from a location a distance forward said light-guiding component.

(9) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one mask comprising at least one mask opening disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one mask and at least one mask opening are configured to couple light from the at least one illumination source out of the light-guiding component through the at least one mask opening.

(10) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, said at least one in-coupling optical element comprising a prism, wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component.

(11) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component, and wherein the image projector is configured to in-couple the image and the at least one illumination source is configured to in-couple light into the at least one illumination in-coupling optical element.

(12) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and an eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user, wherein said eyepiece comprises a waveguide and at least one image in-coupling optical element configured to in-couple light from the image projector into the waveguide so as to guide light from the image projector therein.

(13) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user, said light-guiding component being curved; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component.

(14) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user, said light-guiding component comprising a portion of said frame; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component.

(15) A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, and at least one out-coupling optical element disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the light-guiding component, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one out-coupling optical element.

(16) The system of any of the above Examples, wherein said image projector comprises a visible light source and modulator.

(17) The system of any of the above Examples, wherein the light modulator comprises a spatial light modulator.

(18) The system of any of the above Examples, wherein the at least one illumination source comprises an infrared (IR) light source configured to emit IR light.

(19) The system of any of the above Examples, wherein the at least one illumination source comprises a visible light source configured to emit visible light.

(20) The system of any of the Examples above, wherein said light-guiding component comprises a material that is transparent to visible light having a refractive index sufficient to guide light from said at least one illumination source in said light-guiding component by total internal reflection.

(21) The system of any of the Examples above, wherein at least a portion of said light-guiding component is transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user.

(22) The system of any of the Examples above, wherein the at least one illumination in-coupling optical element comprises at least one prism.

(23) The system of any of the Examples above, further comprising at least one image in-coupling optical element configured to in-couple light from the image projector into the light-guiding component so as to guide light from the image projector therein.

(24) The system of any of the Examples above, wherein the image projector is configured to in-couple the image and the at least one illumination source is configured to in-couple light into the at least one illumination in-coupling optical element.

(25) The system of any of the Examples above, further comprising an eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user.

(26) The system of any of the Examples above, wherein said eyepiece comprises a waveguide and at least one image in-coupling optical element configured to in-couple light from the image projector into the waveguide so as to guide light from the image projector therein.

(27) The system of any of the Examples above, wherein said light-guiding component is disposed on an inside portion of said eyepiece, wherein the inside portion is between the user's eye and the eyepiece.

(28) The system of any of the Examples above, wherein said light-guiding component is disposed on an outside portion of said eyepiece, wherein the outside portion is between the environment and the eyepiece.

(29) The system of any of the Examples above, wherein said light-guiding component is curved.

- (30) The system of any of the Examples above, wherein said light-guiding component has the shape of a portion of a cylinder.
- (31) The system of any of the Examples above, wherein said light-guiding component comprises a shield or visor attached to said frame.
- (32) The system of any of the Examples above, wherein said shield or visor is disposed on an inside portion of said display system.
- (33) The system of any of the Examples above, wherein said shield or visor is disposed on an outside portion of said display system.
- (34) The system of any of the Examples above, wherein said light-guiding component comprises a portion of said frame.
- (35) The system of any of the Examples above, wherein the at least one diffusive optical element is configured to couple light from the at least one illumination source out of the light-guiding component toward said user's eye.
- (36) The system of any of the Examples above, wherein the at least one diffusive optical element is configured to couple light from the at least one illumination source out of the light-guiding component toward the environment forward the user to the user's eye.
- (37) The system of any of the Examples above, wherein the at least one mask blocks light guided within said light-guiding component from exiting said light-guiding component.
- (38) The system of any of the Examples above, wherein said at least one mask reflects light from said at least one illumination source back into said light-guiding components.
- (39) The system of any of the Examples above, wherein said at least one mask is dichroic reflecting certain wavelengths emitted by said at least one illumination source and transmitting other wavelengths not emitted by said at least one illumination source.
- (40) The system of any of the Examples above, wherein said at least one mask is dichroic reflecting certain infrared wavelengths emitted by said at least one illumination source and transmitting other visible wavelengths not emitted by said at least one illumination source.
- (41) The system of any of the Examples above, wherein said at least one mask is configured to absorb light emitted by said illumination source.
- (42) The system of any of the Examples above, wherein said at least one mask opening is about 10 μm in diameter.
- (43) The system of any of the Examples above, wherein the at least one diffusive optical element extends across an area that is less than 5% the area of the at least one light-guiding component.
- (44) The system of any of the Examples above, wherein the at least one mask opening extends across an area that is less than 5% the area of the at least one light-guiding component.
- (45) The system of any of the Examples above, further comprising a light redirecting element configured to direct light received from said at least one illumination in-coupling optical element to within said light-guiding component such that said light-guiding component redirects said light to said at least one diffusive optical element.
- (46) The system of any of the Examples above, further comprising a light redirecting element configured to direct light received from said at least one illumination in-coupling optical element to within said light-guiding component such that said light-guiding component redirects said light to said at least one mask opening.
- (47) The system of any of the Examples above, further comprising a light redirecting element configured to direct light received from said at least one illumination in-coupling optical element to within said light-guiding component such that said light-guiding component redirects said light to said at least one out-coupling element.
- (48) The system of any of the Examples above, wherein said light redirecting element comprises an orthogonal pupil expander.
- (49) The system of any of the Examples above, further comprising at least one camera configured to image the user's eye using light from said at least one illumination source that is reflected from said eye.
- (50) The system of any of the Examples above, wherein said at least one camera comprises an eye tracking camera that is configured to communicate with electronics configured to track movement of said eye based on images from said at least one camera.
- (51) The system of any of the Examples above, wherein said light-guiding component has a circular shape.
- (52) The system of any of the Examples above, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one diffusive optical element.
- (53) The system of any of the Examples above, wherein said at least one light-guiding component comprises first and second light-guiding components disposed on opposite sides of a diffusive film.
- (54) The system of any of the Examples above, wherein said at least one diffusive optical element comprises a pair of diffusive optical elements disposed on opposite sides of said light-guiding component.

(55) The system of any of the Examples above, wherein said at least one diffusive optical element comprises first and second diffusive films disposed on opposite sides of said light-guiding component.

(56) The system of any of the Examples above, wherein said at least one diffusive optical element comprises first and second diffusive optical elements configured to direct light into distributions oriented in different first and second directions.

(57) The system of any of the Examples above, wherein said at least one diffusive optical element comprises first and second diffusive optical elements configured to selectively direct light having first and second wavelengths, respectively, into distributions oriented in different first and second directions, and said at least one illumination source comprising first and second light sources that selectively emits said first and second wavelengths respectively.

(58) The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources.

(59) The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one diffusive optical element directs light from different illumination sources into respective distributions oriented in different directions.

(60) The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one diffusive optical element directs light from different illumination sources as if originating from different respective locations forward said at least one light-guiding component.

(61) The system of any of the Examples above, wherein said at least one illumination source comprises a laser, LED, or vertical cavity surface emitting laser (VCSEL).

(62) The system of any of the Examples above, wherein said at least one illumination source further comprises at least one filter.

(63) The system of any of the Examples above, wherein said at least one diffusive optical element is refractive, reflective, diffractive, or any combination thereof.

(64) The system of any of the Examples above, wherein said at least one diffusive optical element comprises one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles, one or more irregular surfaces, one or more surface relieve structures, PTFE, Teflon, ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof.

(65) The system of any of the Examples above, wherein said at least one diffusive optical element is wavelength selective so as to substantially selectively diffuse one or more wavelengths of light emitted from the at least one illumination source and not others.

(66) The system of any of the Examples above, wherein the system comprises a plurality of diffusive optical elements and at least one illumination source emits a plurality of wavelength bands of light, and wherein different of the diffusive optical elements selectively diffuse respective ones of the plurality of wavelength bands from the at least one illumination source.

(67) The system of any of the Examples above, wherein said at least one diffusive optical element does not re-direct visible light from said environment.

(68) The system of any of the Examples above, wherein said at least one diffusive optical element is configured to direct light from said illumination source toward said environment.

(69) The system of any of the Examples above, wherein said at least one illumination source comprises an infrared source configured to output infrared light and said at least one diffusive optical element is configured to direct infrared light from said at least one illumination source toward said environment to provide depth sensing.

(70) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one diffusive optical element is configured to direct visible light from said at least one illumination source toward said environment to provide indicia to a non-user.

(71) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one diffusive optical element is configured to direct visible light from said at least one illumination source toward said eye to provide indicia to the user.

(72) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one diffusive optical element is configured to direct visible light from said at least one illumination source toward a periphery of an eye.

(73) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source, or both configured to output light and said at least one diffusive optical element is configured to direct the light from said at least one illumination source toward said environment to provide a signal or fiducial to an external sensor or external imaging sensor.

(74) The system of any of the Examples above, wherein said at least one illumination source comprises a visible

source, an infrared source or both configured to output light and said at least one diffusive optical element is configured to direct the light from said at least one illumination source toward said user to provide a signal or fiducial to an external sensor or external imaging sensor.

(75) The system of any of the Examples above, wherein the at least one out-coupling optical element extends across an area that is less than 5% the area of the at least one light-guiding component.

(76) The system of any of the Examples above, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one out-coupling optical element.

(77) The system of any of the Examples above, wherein said at least one light-guiding component comprises first and second light-guiding components disposed on opposite sides of an out-coupling optical film.

(78) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises a pair of out-coupling optical element disposed on opposite sides of said light-guiding component.

(79) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises first and second out-coupling optical films disposed on opposite sides of said light-guiding component.

(80) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises first and second out-coupling optical elements configured to direct light into distributions oriented in different first and second directions.

(81) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises first and second out-coupling optical elements configured to selectively direct light having first and second wavelengths, respectively, into distributions oriented in different first and second directions, and said at least one illumination source comprising first and second light sources that selectively emits said first and second wavelengths respectively.

(82) The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources.

(83) The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one out-coupling optical element directs light from different illumination sources into respective distributions oriented in different directions.

(84) The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one out-coupling optical element directs light from different illumination sources as if originating from different respective locations forward said at least one light-guiding component.

(85) The system of any of the Examples above, wherein said at least one illumination source comprises a laser, LED, or vertical cavity surface emitting laser (VCSEL).

(86) The system of any of the Examples above, wherein said at least one illumination source further comprises at least one filter.

(87) The system of any of the Examples above, wherein said at least one out-coupling optical element is refractive, reflective, diffractive, or any combination thereof.

(88) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles, one or more irregular surfaces, one or more surface relieve structures, PTFE, Teflon, ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof.

(89) The system of any of the Examples above, wherein said at least one out-coupling optical element is wavelength selective so as to substantially only interact with a wavelength band of light emitted from the at least one illumination source.

(90) The system of any of the Examples above, wherein the system comprises a plurality of out-coupling optical elements and at least one illumination source emits a plurality of wavelength bands of light, and wherein each out-coupling optical element is wavelength selective so as to substantially only interact with different wavelength bands of light emitted from the at least one illumination source.

(91) The system of any of the Examples above, wherein said at least one out-coupling optical element does not re-direct visible light from said environment.

(92) The system of any of the Examples above, wherein said at least one out-coupling optical element is configured to direct light from said illumination source toward said environment.

(93) The system of any of the Examples above, wherein said at least one illumination source comprises an infrared source configured to output infrared light and said at least one out-coupling optical element is configured to direct infrared light from said at least one illumination source toward said environment to provide depth sensing.

(94) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one out-coupling optical element is configured to direct

visible light from said at least one illumination source toward said environment to provide indicia to a non-user.

(95) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one out-coupling optical element is configured to direct visible light from said at least one illumination source toward said eye to provide indicia to the user.

(96) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one out-coupling optical element is configured to direct visible light from said at least one illumination source toward a periphery of an eye.

(97) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source, or both configured to output light and said at least one out-coupling optical element is configured to direct the light from said at least one illumination source toward said environment to provide a signal or a fiducial to an external sensor or external imaging sensor.

(98) The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source, or both configured to output light and said at least one out-coupling optical element is configured to direct the light from said at least one illumination source toward said user to provide a signal or a fiducial to a sensor or external imaging sensor.

(99) The system of any of the Claims above, wherein the image projector and the illumination source share the same in-coupling optical element and light-guiding component.

(100) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises at least one diffusive optical element or at least one diffusive film or any combination thereof.

(101) The system of any of the Examples above, wherein said at least one out-coupling optical element comprises at least one diffractive optical element or at least one holographical optical element or any combination thereof.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a user's view of augmented reality (AR) through an AR device.

(2) FIG. 2 illustrates a conventional display system for simulating three-dimensional imagery for a user.

(3) FIGS. 3A-3C illustrate relationships between radius of curvature and focal radius.

(4) FIG. 4A illustrates a representation of the accommodation-vergence response of the human visual system.

(5) FIG. 4B illustrates examples of different accommodative states and vergence states of a pair of eyes of the user.

(6) FIG. 4C illustrates an example of a representation of a top-down view of a user viewing content via a display system.

(7) FIG. 4D illustrates another example of a representation of a top-down view of a user viewing content via a display system.

(8) FIG. 5 illustrates aspects of an approach for simulating three-dimensional imagery by modifying wavefront divergence.

(9) FIG. 6 illustrates an example of a waveguide stack for outputting image information to a user.

(10) FIG. 7 illustrates an example of exit beams outputted by a waveguide.

(11) FIG. 8 illustrates an example of a stacked waveguide assembly in which each depth plane includes images formed using multiple different component colors.

(12) FIG. 9A illustrates a cross-sectional side view of an example of a set of stacked waveguides that each includes an incoupling optical element.

(13) FIG. 9B illustrates a perspective view of an example of the plurality of stacked waveguides of FIG. 9A.

(14) FIG. 9C illustrates a top-down plan view of an example of the plurality of stacked waveguides of FIGS. 9A and 9B.

(15) FIG. 9D illustrates an example of wearable display system.

(16) FIGS. 10A-10D illustrate perspective views of a light-guiding component configured to project light from an illumination source to a user's eye, such that the light appears to originate from virtual sources in front of the user's eye beyond the light-guiding component (e.g., in the far-field). In some designs, this light-guiding component comprises an eyepiece of a head-mounted display that is also configured to project images from a display into the user's eye.

(17) FIGS. 11A-11B illustrate perspective views of a light-guiding component having a mask with a plurality of openings therein through which light can exit the light-guiding component thereby producing localized (e.g., point) sources of illumination.

(18) FIGS. 12A-12B illustrate perspective views of a light-guiding component and one or more out-coupling optical elements comprising diffusive optical elements or scatter regions that scatter light guided within the light-

guiding component, in this example, producing a plurality of separate localized (e.g., point) sources of illumination.

(19) FIGS. 13A-13B illustrate the light-guiding component comprising an outer cover of an eyepiece of a head-mounted display. In this example, the light-guiding component comprising the outer cover is curved. Additionally, one or more out-coupling optical elements comprising diffusive optical elements scatter light guided within the light-guiding component out of the light-guiding component.

(20) FIGS. 14A-14B illustrate a light-guiding component comprising an inner cover for the eyepiece of a head-mounted display. One or more out-coupling optical elements comprising a plurality of diffusive optical elements are disposed with respect to the light-guiding component to cause light guided within the light-guiding component to be ejected therefrom.

(21) FIGS. 15A-15B illustrate a light-guiding component integrated in a frame of the head-mounted display system. In this example, one or more out-coupling optical elements comprising, e.g., diffusive optical elements or holes, are positioned on the light-guiding portion of the frame to cause light guided therein to be ejected out.

(22) FIG. 16 illustrates a circular shaped light-guiding component that includes a ring-shaped output coupling element comprising, for example, an annular shaped diffusing film or diffractive optical element.

(23) FIG. 17A illustrates first and second light-guiding components stacked on top of each other. In this example, the first and second light-guiding components are separated by an out-coupling optical element comprising, e.g., a diffusive optical element or a diffractive optical element, that is configured to couple light guided within the first and second light-guiding components out of the light-guiding components. In some implementations, the out-coupling is bi-directional, with light being ejected forward and rearward of the pair of light guiding components.

(24) FIG. 17B illustrates a light guiding component comprising first and second out-coupling optical elements disposed on either side of the light-guiding component to couple light guided within the light-guiding component out of the light-guiding component. In some examples, the first and second out-coupling optical elements may be configured to provide bidirectional out-coupling such that light is ejected forward and rearward of the light-guiding component and the pair of out-coupling optical elements.

(25) FIG. 17C illustrates first and second light-guiding components on opposite sides of one or more out-coupling optical elements comprising, e.g., a diffusive optical element or diffractive optical element, that is configured to couple light guided within the first and second light-guiding components out of the light-guiding components. In some implementations, the out-coupling is bi-directional, with light being ejected forward and rearward of the pair of light guiding components. As illustrated, the first and second light-guiding components are circularly shaped and the out-coupling optical element is annularly shaped.

(26) The drawings are provided to illustrate example embodiments and are not intended to limit the scope of the disclosure. Like reference numerals refer to like parts throughout.

DETAILED DESCRIPTION

(27) AR systems may display virtual content to a user, or viewer, while still allowing the user to see the world around them. Preferably, this content is displayed on a head-mounted display, e.g., as part of eyewear, that projects image information to the user's eyes. In addition, the display may also transmit light from the surrounding environment to the user's eyes, to allow a view of that surrounding environment. As used herein, it will be appreciated that a "head-mounted" or "head mountable" display is a display that may be mounted on the head of a viewer or user.

(28) In some AR systems, a plurality of waveguides may be configured to form virtual images at a plurality of virtual depth planes (also referred to simply a "depth planes" herein). Different waveguides of the plurality of waveguides may have different optical powers and may be formed at different distances from the user's eye. The display systems may also include a plurality lenses that provide or additionally provide optical powers. The optical powers of the waveguides and/or the lenses may provide images at different virtual depth planes.

Undesirably, each of the waveguides and lenses may increase the overall thickness, weight and cost of the display.

(29) Advantageously, in various embodiments described herein, an adaptive lens assembly may be utilized to provide variable optical power to, e.g., modify the wavefront divergence of light propagating through the lens assembly to provide virtual depth planes at different perceived distances from a user. The adaptive lens assembly may include a pair of waveplate lenses having a switchable waveplate disposed between them. Each of the first and second waveplate lenses may be configured to alter a polarization state of the light passing therethrough, and the switchable waveplate may be switchable between a plurality of states, e.g., a first state that allows light to pass without changing a polarization of the light and a second state that alters the polarization of the light (e.g., by changing the handedness of the polarization). In some embodiments, one or both of the waveplate lenses may be switchable between these first and second states and the intervening switchable waveplate noted above may be omitted.

(30) It will be appreciated that the adaptive lens assembly may comprise a stack of a plurality of waveplate lenses

and a plurality of switchable waveplates. For example, the adaptive lens assembly may comprise multiple subassemblies comprising a pair of waveplate lenses with an intervening switchable waveplate. In some embodiments, the adaptive lens assembly may include alternating waveplate lenses and switchable waveplates. Advantageously, such alternating arrangement allows a reduction in thickness and weight by having neighboring switchable waveplates share a common waveplate lens. In some embodiments, by switching the states of the various combinations of the switchable plates in the stack, more than two discrete levels of optical power may be provided.

(31) In some embodiments, the adaptive lens assembly forms a display device with a waveguide assembly to form images at different virtual depth planes. In various embodiments, the display device comprises a pair of adaptive lens assemblies interposed by a waveguide assembly. The waveguide assembly includes a waveguide configured to propagate light (e.g., visible light) therein (e.g., via total internal reflection) and to out-couple the light. For example, the light may be out-coupled along an optical axis direction normal to a major surface of the waveguide. One of the pair of adaptive lens assemblies may be formed on a first side of the waveguide assembly and may be configured to provide variable optical power to modify the wavefront of light passing through the adaptive lens assembly to form images at each of a plurality of virtual depth planes. For example, the adaptive lens assemblies may converge or diverge out-coupled light received from the waveguide assembly. To compensate for modifications of real world views due to the convergence or divergence of ambient light propagating through the adaptive lens assembly and/or the waveguide assembly, the other of the pair of adaptive lens assemblies is additionally provided on a second side of the waveguide assembly opposite the first side. When the switchable waveplates of each adaptive lens assembly assume a corresponding state, the adaptive lens assemblies may have optical powers with opposite signs, such that the other of the adaptive lens assemblies correct for distortions caused by the adaptive lens assembly on the first side of the waveguide assembly.

(32) Advantageously, relative to a continuously variable adaptive lens having continuously variable optical elements, utilizing a switchable waveplate that is switchable between two states simplifies the driving of the adaptive lens assembly and reduces the computational power needed to determine how to appropriately activate the adaptive lens assembly for a desired optical power. In addition, by allowing the adaptive lens assembly to modify the wavefront divergence of light outputted by a waveguide, the number waveguides needed to provide a plurality of depth planes is reduced relative to an arrangement in which each waveguide provides a particular amount of wavefront divergence.

(33) Reference will now be made to the drawings, in which like reference numerals refer to like parts throughout. Unless indicated otherwise, the drawings are schematic not necessarily drawn to scale.

(34) Example Display Systems

(35) FIG. 2 illustrates a conventional display system for simulating three-dimensional imagery for a user. It will be appreciated that a user's eyes are spaced apart and that, when looking at a real object in space, each eye will have a slightly different view of the object and may form an image of the object at different locations on the retina of each eye. This may be referred to as binocular disparity and may be utilized by the human visual system to provide a perception of depth. Conventional display systems simulate binocular disparity by presenting two distinct images **190, 200** with slightly different views of the same virtual object—one for each eye **210, 220**—corresponding to the views of the virtual object that would be seen by each eye were the virtual object a real object at a desired depth. These images provide binocular cues that the user's visual system may interpret to derive a perception of depth.

(36) With continued reference to FIG. 2, the images **190, 200** are spaced from the eyes **210, 220** by a distance **230** on a z-axis. The z-axis is parallel to the optical axis of the viewer with their eyes fixated on an object at optical infinity directly ahead of the viewer. The images **190, 200** are flat and at a fixed distance from the eyes **210, 220**. Based on the slightly different views of a virtual object in the images presented to the eyes **210, 220**, respectively, the eyes may naturally rotate such that an image of the object falls on corresponding points on the retinas of each of the eyes, to maintain single binocular vision. This rotation may cause the lines of sight of each of the eyes **210, 220** to converge onto a point in space at which the virtual object is perceived to be present. As a result, providing three-dimensional imagery conventionally involves providing binocular cues that may manipulate the vergence of the user's eyes **210, 220**, and that the human visual system interprets to provide a perception of depth.

(37) Generating a realistic and comfortable perception of depth is challenging, however. It will be appreciated that light from objects at different distances from the eyes have wavefronts with different amounts of divergence.

FIGS. 3A-3C illustrate relationships between distance and the divergence of light rays. The distance between the object and the eye **210** is represented by, in order of decreasing distance, **R1, R2, and R3**. As shown in FIGS. 3A-3C, the light rays become more divergent as distance to the object decreases. Conversely, as distance increases, the light rays become more collimated. Stated another way, it may be said that the light field produced by a point (the object or a part of the object) has a spherical wavefront curvature, which is a function of how far away the

point is from the eye of the user. The curvature increases with decreasing distance between the object and the eye **210**. While only a single eye **210** is illustrated for clarity of illustration in FIGS. **3A-3C** and other figures herein, the discussions regarding eye **210** may be applied to both eyes **210** and **220** of a viewer.

(38) With continued reference to FIGS. **3A-3C**, light from an object that the viewer's eyes are fixated on may have different degrees of wavefront divergence. Due to the different amounts of wavefront divergence, the light may be focused differently by the lens of the eye, which in turn may require the lens to assume different shapes to form a focused image on the retina of the eye. Where a focused image is not formed on the retina, the resulting retinal blur acts as a cue to accommodation that causes a change in the shape of the lens of the eye until a focused image is formed on the retina. For example, the cue to accommodation may trigger the ciliary muscles surrounding the lens of the eye to relax or contract, thereby modulating the force applied to the suspensory ligaments holding the lens, thus causing the shape of the lens of the eye to change until retinal blur of an object of fixation is eliminated or minimized, thereby forming a focused image of the object of fixation on the retina (e.g., fovea) of the eye. The process by which the lens of the eye changes shape may be referred to as accommodation, and the shape of the lens of the eye required to form a focused image of the object of fixation on the retina (e.g., fovea) of the eye may be referred to as an accommodative state.

(39) With reference now to FIG. **4A**, a representation of the accommodation-vergence response of the human visual system is illustrated. The movement of the eyes to fixate on an object causes the eyes to receive light from the object, with the light forming an image on each of the retinas of the eyes. The presence of retinal blur in the image formed on the retina may provide a cue to accommodation, and the relative locations of the image on the retinas may provide a cue to vergence. The cue to accommodation causes accommodation to occur, resulting in the lenses of the eyes each assuming a particular accommodative state that forms a focused image of the object on the retina (e.g., fovea) of the eye. On the other hand, the cue to vergence causes vergence movements (rotation of the eyes) to occur such that the images formed on each retina of each eye are at corresponding retinal points that maintain single binocular vision. In these positions, the eyes may be said to have assumed a particular vergence state. With continued reference to FIG. **4A**, accommodation may be understood to be the process by which the eye achieves a particular accommodative state, and vergence may be understood to be the process by which the eye achieves a particular vergence state. As indicated in FIG. **4A**, the accommodative and vergence states of the eyes may change if the user fixates on another object. For example, the accommodated state may change if the user fixates on a new object at a different depth on the z-axis.

(40) Without being limited by theory, it is believed that viewers of an object may perceive the object as being “three-dimensional” due to a combination of vergence and accommodation. As noted above, vergence movements (e.g., rotation of the eyes so that the pupils move toward or away from each other to converge the lines of sight of the eyes to fixate upon an object) of the two eyes relative to each other are closely associated with accommodation of the lenses of the eyes. Under normal conditions, changing the shapes of the lenses of the eyes to change focus from one object to another object at a different distance will automatically cause a matching change in vergence to the same distance, under a relationship known as the “accommodation-vergence reflex.” Likewise, a change in vergence will trigger a matching change in lens shape under normal conditions.

(41) With reference now to FIG. **4B**, examples of different accommodative and vergence states of the eyes are illustrated. The pair of eyes **222a** is fixated on an object at optical infinity, while the pair eyes **222b** are fixated on an object **221** at less than optical infinity. Notably, the vergence states of each pair of eyes is different, with the pair of eyes **222a** directed straight ahead, while the pair of eyes **222** converge on the object **221**. The accommodative states of the eyes forming each pair of eyes **222a** and **222b** are also different, as represented by the different shapes of the lenses **210a**, **220a**.

(42) Undesirably, many users of conventional “3-D” display systems find such conventional systems to be uncomfortable or may not perceive a sense of depth at all due to a mismatch between accommodative and vergence states in these displays. As noted above, many stereoscopic or “3-D” display systems display a scene by providing slightly different images to each eye. Such systems are uncomfortable for many viewers, since they, among other things, simply provide different presentations of a scene and cause changes in the vergence states of the eyes, but without a corresponding change in the accommodative states of those eyes. Rather, the images are shown by a display at a fixed distance from the eyes, such that the eyes view all the image information at a single accommodative state. Such an arrangement works against the “accommodation-vergence reflex” by causing changes in the vergence state without a matching change in the accommodative state. This mismatch is believed to cause viewer discomfort. Display systems that provide a better match between accommodation and vergence may form more realistic and comfortable simulations of three-dimensional imagery.

(43) Without being limited by theory, it is believed that the human eye typically may interpret a finite number of depth planes to provide depth perception. Consequently, a highly believable simulation of perceived depth may be achieved by providing, to the eye, different presentations of an image corresponding to each of these limited

numbers of depth planes. In some embodiments, the different presentations may provide both cues to vergence and matching cues to accommodation, thereby providing physiologically correct accommodation-vergence matching.

(44) With continued reference to FIG. 4B, two depth planes **240**, corresponding to different distances in space from the eyes **210**, **220**, are illustrated. For a given depth plane **240**, vergence cues may be provided by the displaying of images of appropriately different perspectives for each eye **210**, **220**. In addition, for a given depth plane **240**, light forming the images provided to each eye **210**, **220** may have a wavefront divergence corresponding to a light field produced by a point at the distance of that depth plane **240**.

(45) In the illustrated embodiment, the distance, along the z-axis, of the depth plane **240** containing the point **221** is 1 m. As used herein, distances or depths along the z-axis may be measured with a zero-point located at the exit pupils of the user's eyes. Thus, a depth plane **240** located at a depth of 1 m corresponds to a distance of 1 m away from the exit pupils of the user's eyes, on the optical axis of those eyes with the eyes directed towards optical infinity. As an approximation, the depth or distance along the z-axis may be measured from the display in front of the user's eyes (e.g., from the surface of a waveguide), plus a value for the distance between the device and the exit pupils of the user's eyes. That value may be called the eye relief and corresponds to the distance between the exit pupil of the user's eye and the display worn by the user in front of the eye. In practice, the value for the eye relief may be a normalized value used generally for all viewers. For example, the eye relief may be assumed to be 20 mm and a depth plane that is at a depth of 1 m may be at a distance of 980 mm in front of the display.

(46) With reference now to FIGS. 4C and 4D, examples of matched accommodation-vergence distances and mismatched accommodation-vergence distances are illustrated, respectively. As illustrated in FIG. 4C, the display system may provide images of a virtual object to each eye **210**, **220**. The images may cause the eyes **210**, **220** to assume a vergence state in which the eyes converge on a point **15** on a depth plane **240**. In addition, the images may be formed by a light having a wavefront curvature corresponding to real objects at that depth plane **240**. As a result, the eyes **210**, **220** assume an accommodative state in which the images are in focus on the retinas of those eyes. Thus, the user may perceive the virtual object as being at the point **15** on the depth plane **240**.

(47) It will be appreciated that each of the accommodative and vergence states of the eyes **210**, **220** are associated with a particular distance on the z-axis. For example, an object at a particular distance from the eyes **210**, **220** causes those eyes to assume particular accommodative states based upon the distances of the object. The distance associated with a particular accommodative state may be referred to as the accommodation distance, $A_{sub.d}$. Similarly, there are particular vergence distances, $V_{sub.d}$, associated with the eyes in particular vergence states, or positions relative to one another. Where the accommodation distance and the vergence distance match, the relationship between accommodation and vergence may be said to be physiologically correct. This is considered to be the most comfortable scenario for a viewer.

(48) In stereoscopic displays, however, the accommodation distance and the vergence distance may not always match. For example, as illustrated in FIG. 4D, images displayed to the eyes **210**, **220** may be displayed with wavefront divergence corresponding to depth plane **240**, and the eyes **210**, **220** may assume a particular accommodative state in which the points **15a**, **15b** on that depth plane are in focus. However, the images displayed to the eyes **210**, **220** may provide cues for vergence that cause the eyes **210**, **220** to converge on a point **15** that is not located on the depth plane **240**. As a result, the accommodation distance corresponds to the distance from the exit pupils of the eyes **210**, **220** to the depth plane **240**, while the vergence distance corresponds to the larger distance from the exit pupils of the eyes **210**, **220** to the point **15**, in some embodiments. The accommodation distance is different from the vergence distance. Consequently, there is an accommodation-vergence mismatch. Such a mismatch is considered undesirable and may cause discomfort in the user. It will be appreciated that the mismatch corresponds to distance (e.g., $V_{sub.d} - A_{sub.d}$) and may be characterized using diopters.

(49) In some embodiments, it will be appreciated that a reference point other than exit pupils of the eyes **210**, **220** may be utilized for determining distance for determining accommodation-vergence mismatch, so long as the same reference point is utilized for the accommodation distance and the vergence distance. For example, the distances could be measured from the cornea to the depth plane, from the retina to the depth plane, from the eyepiece (e.g., a waveguide of the display device) to the depth plane, and so on.

(50) Without being limited by theory, it is believed that users may still perceive accommodation-vergence mismatches of up to about 0.25 diopter, up to about 0.33 diopter, and up to about 0.5 diopter as being physiologically correct, without the mismatch itself causing significant discomfort. In some embodiments, display systems disclosed herein (e.g., the display system **250**, FIG. 6) present images to the viewer having accommodation-vergence mismatch of about 0.5 diopter or less. In some other embodiments, the accommodation-vergence mismatch of the images provided by the display system is about 0.33 diopter or less. In yet other embodiments, the accommodation-vergence mismatch of the images provided by the display system is about 0.25

diopter or less, including about 0.1 diopter or less.

(51) FIG. 5 illustrates aspects of an approach for simulating three-dimensional imagery by modifying wavefront divergence. The display system includes a waveguide **270** that is configured to receive light **770** that is encoded with image information, and to output that light to the user's eye **210**. The waveguide **270** may output the light **650** with a defined amount of wavefront divergence corresponding to the wavefront divergence of a light field produced by a point on a desired depth plane **240**. In some embodiments, the same amount of wavefront divergence is provided for all objects presented on that depth plane. In addition, it will be illustrated that the other eye of the user may be provided with image information from a similar waveguide.

(52) In some embodiments, a single waveguide may be configured to output light with a set amount of wavefront divergence corresponding to a single or limited number of depth planes and/or the waveguide may be configured to output light of a limited range of wavelengths. Consequently, in some embodiments, a plurality or stack of waveguides may be utilized to provide different amounts of wavefront divergence for different depth planes and/or to output light of different ranges of wavelengths. As used herein, it will be appreciated at a depth plane may be planar or may follow the contours of a curved surface.

(53) FIG. 6 illustrates an example of a waveguide stack for outputting image information to a user. A display system **250** includes a stack of waveguides, or stacked waveguide assembly, **260** that may be utilized to provide three-dimensional perception to the eye/brain using a plurality of waveguides **270, 280, 290, 300, 310**. It will be appreciated that the display system **250** may be considered a light field display in some embodiments. In addition, the waveguide assembly **260** may also be referred to as an eyepiece.

(54) In some embodiments, the display system **250** may be configured to provide substantially continuous cues to vergence and multiple discrete cues to accommodation. The cues to vergence may be provided by displaying different images to each of the eyes of the user, and the cues to accommodation may be provided by outputting the light that forms the images with selectable discrete amounts of wavefront divergence. Stated another way, the display system **250** may be configured to output light with variable levels of wavefront divergence. In some embodiments, each discrete level of wavefront divergence corresponds to a particular depth plane and may be provided by a particular one of the waveguides **270, 280, 290, 300, 310**.

(55) With continued reference to FIG. 6, the waveguide assembly **260** may also include a plurality of features **320, 330, 340, 350** between the waveguides. In some embodiments, the features **320, 330, 340, 350** may be one or more lenses. The waveguides **270, 280, 290, 300, 310** and/or the plurality of lenses **320, 330, 340, 350** may be configured to send image information to the eye with various levels of wavefront curvature or light ray divergence. Each waveguide level may be associated with a particular depth plane and may be configured to output image information corresponding to that depth plane. Image injection devices **360, 370, 380, 390, 400** may function as a source of light for the waveguides and may be utilized to inject image information into the waveguides **270, 280, 290, 300, 310**, each of which may be configured, as described herein, to distribute incoming light across each respective waveguide, for output toward the eye **210**. Light exits an output surface **410, 420, 430, 440, 450** of the image injection devices **360, 370, 380, 390, 400** and is injected into a corresponding input surface **460, 470, 480, 490, 500** of the waveguides **270, 280, 290, 300, 310**. In some embodiments, each of the input surfaces **460, 470, 480, 490, 500** may be an edge of a corresponding waveguide, or may be part of a major surface of the corresponding waveguide (that is, one of the waveguide surfaces directly facing the world **510** or the viewer's eye **210**). In some embodiments, a single beam of light (e.g. a collimated beam) may be injected into each waveguide to output an entire field of cloned collimated beams that are directed toward the eye **210** at particular angles (and amounts of divergence) corresponding to the depth plane associated with a particular waveguide. In some embodiments, a single one of the image injection devices **360, 370, 380, 390, 400** may be associated with and inject light into a plurality (e.g., three) of the waveguides **270, 280, 290, 300, 310**.

(56) In some embodiments, the image injection devices **360, 370, 380, 390, 400** are discrete displays that each produce image information for injection into a corresponding waveguide **270, 280, 290, 300, 310**, respectively. In some other embodiments, the image injection devices **360, 370, 380, 390, 400** are the output ends of a single multiplexed display which may, e.g., pipe image information via one or more optical conduits (such as fiber optic cables) to each of the image injection devices **360, 370, 380, 390, 400**. It will be appreciated that the image information provided by the image injection devices **360, 370, 380, 390, 400** may include light of different wavelengths, or colors (e.g., different component colors, as discussed herein).

(57) In some embodiments, the light injected into the waveguides **270, 280, 290, 300, 310** is provided by a light projector system **520**, which comprises a light module **530**, which may include a light emitter, such as a light emitting diode (LED). The light from the light module **530** may be directed to and modified by a light modulator **540**, e.g., a spatial light modulator, via a beam splitter **550**. The light modulator **540** may be configured to change the perceived intensity of the light injected into the waveguides **270, 280, 290, 300, 310** to encode the light with

image information. Examples of spatial light modulators include liquid crystal displays (LCD) including a liquid crystal on silicon (LCOS) displays. It will be appreciated that the image injection devices **360, 370, 380, 390, 400** are illustrated schematically and, in some embodiments, these image injection devices may represent different light paths and locations in a common projection system configured to output light into associated ones of the waveguides **270, 280, 290, 300, 310**. In some embodiments, the waveguides of the waveguide assembly **260** may function as ideal lens while relaying light injected into the waveguides out to the user's eyes. In this conception, the object may be the spatial light modulator **540** and the image may be the image on the depth plane.

(58) In some embodiments, the display system **250** may be a scanning fiber display comprising one or more scanning fibers configured to project light in various patterns (e.g., raster scan, spiral scan, Lissajous patterns, etc.) into one or more waveguides **270, 280, 290, 300, 310** and ultimately to the eye **210** of the viewer. In some embodiments, the illustrated image injection devices **360, 370, 380, 390, 400** may schematically represent a single scanning fiber or a bundle of scanning fibers configured to inject light into one or a plurality of the waveguides **270, 280, 290, 300, 310**. In some other embodiments, the illustrated image injection devices **360, 370, 380, 390, 400** may schematically represent a plurality of scanning fibers or a plurality of bundles of scanning fibers, each of which are configured to inject light into an associated one of the waveguides **270, 280, 290, 300, 310**. It will be appreciated that one or more optical fibers may be configured to transmit light from the light module **530** to the one or more waveguides **270, 280, 290, 300, 310**. It will be appreciated that one or more intervening optical structures may be provided between the scanning fiber, or fibers, and the one or more waveguides **270, 280, 290, 300, 310** to, e.g., redirect light exiting the scanning fiber into the one or more waveguides **270, 280, 290, 300, 310**.

(59) A controller **560** controls the operation of one or more of the stacked waveguide assembly **260**, including operation of the image injection devices **360, 370, 380, 390, 400**, the light source **530**, and the light modulator **540**. In some embodiments, the controller **560** is part of the local data processing module **140**. The controller **560** includes programming (e.g., instructions in a non-transitory medium) that regulates the timing and provision of image information to the waveguides **270, 280, 290, 300, 310** according to, e.g., any of the various schemes disclosed herein. In some embodiments, the controller may be a single integral device, or a distributed system connected by wired or wireless communication channels. The controller **560** may be part of the processing modules **140** or **150** (FIG. 9D) in some embodiments.

(60) With continued reference to FIG. 6, the waveguides **270, 280, 290, 300, 310** may be configured to propagate light within each respective waveguide by total internal reflection (TIR). The waveguides **270, 280, 290, 300, 310** may each be planar or have another shape (e.g., curved), with major top and bottom surfaces and edges extending between those major top and bottom surfaces. In the illustrated configuration, the waveguides **270, 280, 290, 300, 310** may each include out-coupling optical elements **570, 580, 590, 600, 610** that are configured to extract light out of a waveguide by redirecting the light, propagating within each respective waveguide, out of the waveguide to output image information to the eye **210**. Extracted light may also be referred to as out-coupled light and the out-coupling optical elements light may also be referred to light extracting optical elements. An extracted beam of light may be outputted by the waveguide at locations at which the light propagating in the waveguide strikes a light extracting optical element. The out-coupling optical elements **570, 580, 590, 600, 610** may, for example, be gratings, including diffractive optical features, as discussed further herein. While illustrated disposed at the bottom major surfaces of the waveguides **270, 280, 290, 300, 310**, for ease of description and drawing clarity, in some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** may be disposed at the top and/or bottom major surfaces, and/or may be disposed directly in the volume of the waveguides **270, 280, 290, 300, 310**, as discussed further herein. In some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** may be formed in a layer of material that is attached to a transparent substrate to form the waveguides **270, 280, 290, 300, 310**. In some other embodiments, the waveguides **270, 280, 290, 300, 310** may be a monolithic piece of material and the out-coupling optical elements **570, 580, 590, 600, 610** may be formed on a surface and/or in the interior of that piece of material.

(61) With continued reference to FIG. 6, as discussed herein, each waveguide **270, 280, 290, 300, 310** is configured to output light to form an image corresponding to a particular depth plane. For example, the waveguide **270** nearest the eye may be configured to deliver collimated light (which was injected into such waveguide **270**), to the eye **210**. The collimated light may be representative of the optical infinity focal plane. The next waveguide up **280** may be configured to send out collimated light which passes through the first lens **350** (e.g., a negative lens) before it may reach the eye **210**; such first lens **350** may be configured to create a slight convex wavefront curvature so that the eye/brain interprets light coming from that next waveguide up **280** as coming from a first focal plane closer inward toward the eye **210** from optical infinity. Similarly, the third up waveguide **290** passes its output light through both the first **350** and second **340** lenses before reaching the eye **210**; the combined optical power of the first **350** and second **340** lenses may be configured to create another

incremental amount of wavefront curvature so that the eye/brain interprets light coming from the third waveguide **290** as coming from a second focal plane that is even closer inward toward the person from optical infinity than was light from the next waveguide up **280**.

(62) The other waveguide layers **300**, **310** and lenses **330**, **320** are similarly configured, with the highest waveguide **310** in the stack sending its output through all of the lenses between it and the eye for an aggregate focal power representative of the closest focal plane to the person. To compensate for the stack of lenses **320**, **330**, **340**, **350** when viewing/interpreting light coming from the world **510** on the other side of the stacked waveguide assembly **260**, a compensating lens layer **620** may be disposed at the top of the stack to compensate for the aggregate power of the lens stack **320**, **330**, **340**, **350** below. Such a configuration provides as many perceived focal planes as there are available waveguide/lens pairings. Both the out-coupling optical elements of the waveguides and the focusing aspects of the lenses may be static (i.e., not dynamic or electro-active). In some alternative embodiments, either or both may be dynamic using electro-active features.

(63) In some embodiments, two or more of the waveguides **270**, **280**, **290**, **300**, **310** may have the same associated depth plane. For example, multiple waveguides **270**, **280**, **290**, **300**, **310** may be configured to output images set to the same depth plane, or multiple subsets of the waveguides **270**, **280**, **290**, **300**, **310** may be configured to output images set to the same plurality of depth planes, with one set for each depth plane. This may provide advantages for forming a tiled image to provide an expanded field of view at those depth planes.

(64) With continued reference to FIG. **6**, the out-coupling optical elements **570**, **580**, **590**, **600**, **610** may be configured to both redirect light out of their respective waveguides and to output this light with the appropriate amount of divergence or collimation for a particular depth plane associated with the waveguide. As a result, waveguides having different associated depth planes may have different configurations of out-coupling optical elements **570**, **580**, **590**, **600**, **610**, which output light with a different amount of divergence depending on the associated depth plane. In some embodiments, the light extracting optical elements **570**, **580**, **590**, **600**, **610** may be volumetric or surface features, which may be configured to output light at specific angles. For example, the light extracting optical elements **570**, **580**, **590**, **600**, **610** may be volume holograms, surface holograms, and/or diffraction gratings. In some embodiments, the features **320**, **330**, **340**, **350** may not be lenses; rather, they may simply be spacers (e.g., cladding layers and/or structures for forming air gaps).

(65) In some embodiments, the out-coupling optical elements **570**, **580**, **590**, **600**, **610** are diffractive features that form a diffraction pattern, or “diffractive optical element” (also referred to herein as a “DOE”). Preferably, the DOE's have a sufficiently low diffraction efficiency so that only a portion of the light of the beam is deflected away toward the eye **210** with each intersection of the DOE, while the rest continues to move through a waveguide via TIR. The light carrying the image information is thus divided into a number of related exit beams that exit the waveguide at a multiplicity of locations and the result is a fairly uniform pattern of exit emission toward the eye **210** for this particular collimated beam bouncing around within a waveguide.

(66) In some embodiments, one or more DOEs may be switchable between “on” states in which they actively diffract, and “off” states in which they do not significantly diffract. For instance, a switchable DOE may comprise a layer of polymer dispersed liquid crystal, in which microdroplets comprise a diffraction pattern in a host medium, and the refractive index of the microdroplets may be switched to substantially match the refractive index of the host material (in which case the pattern does not appreciably diffract incident light) or the microdroplet may be switched to an index that does not match that of the host medium (in which case the pattern actively diffracts incident light).

(67) In some embodiments, a camera assembly **630** (e.g., a digital camera, including visible light and infrared light cameras) may be provided to capture images of the eye **210** and/or tissue around the eye **210** to, e.g., detect user inputs and/or to monitor the physiological state of the user. As used herein, a camera may be any image capture device. In some embodiments, the camera assembly **630** may include an image capture device and a light source to project light (e.g., infrared light) to the eye, which may then be reflected by the eye and detected by the image capture device. In some embodiments, the camera assembly **630** may be attached to the frame **80** (FIG. **9D**) and may be in electrical communication with the processing modules **140** and/or **150**, which may process image information from the camera assembly **630**. In some embodiments, one camera assembly **630** may be utilized for each eye, to separately monitor each eye.

(68) With reference now to FIG. **7**, an example of exit beams outputted by a waveguide is shown. One waveguide is illustrated, but it will be appreciated that other waveguides in the waveguide assembly **260** (FIG. **6**) may function similarly, where the waveguide assembly **260** includes multiple waveguides. Light **640** is injected into the waveguide **270** at the input surface **460** of the waveguide **270** and propagates within the waveguide **270** by TIR. At points where the light **640** impinges on the DOE **570**, a portion of the light exits the waveguide as exit beams **650**. The exit beams **650** are illustrated as substantially parallel but, as discussed herein, they may also be redirected to propagate to the eye **210** at an angle (e.g., forming divergent exit beams), depending on the depth

plane associated with the waveguide **270**. It will be appreciated that substantially parallel exit beams may be indicative of a waveguide with out-coupling optical elements that out-couple light to form images that appear to be set on a depth plane at a large distance (e.g., optical infinity) from the eye **210**. Other waveguides or other sets of out-coupling optical elements may output an exit beam pattern that is more divergent, which would require the eye **210** to accommodate to a closer distance to bring it into focus on the retina and would be interpreted by the brain as light from a distance closer to the eye **210** than optical infinity.

(69) In some embodiments, a full color image may be formed at each depth plane by overlaying images in each of the component colors, e.g., three or more component colors. FIG. **8** illustrates an example of a stacked waveguide assembly in which each depth plane includes images formed using multiple different component colors. The illustrated embodiment shows depth planes **240a-240f**, although more or fewer depths are also contemplated. Each depth plane may have three or more component color images associated with it, including: a first image of a first color, G; a second image of a second color, R; and a third image of a third color, B. Different depth planes are indicated in the figure by different numbers for diopters (dpt) following the letters G, R, and B. Just as examples, the numbers following each of these letters indicate diopters (1/m), or inverse distance of the depth plane from a viewer, and each box in the figures represents an individual component color image. In some embodiments, to account for differences in the eye's focusing of light of different wavelengths, the exact placement of the depth planes for different component colors may vary. For example, different component color images for a given depth plane may be placed on depth planes corresponding to different distances from the user. Such an arrangement may increase visual acuity and user comfort and/or may decrease chromatic aberrations.

(70) In some embodiments, light of each component color may be outputted by a single dedicated waveguide and, consequently, each depth plane may have multiple waveguides associated with it. In such embodiments, each box in the figures including the letters G, R, or B may be understood to represent an individual waveguide, and three waveguides may be provided per depth plane where three component color images are provided per depth plane. While the waveguides associated with each depth plane are shown adjacent to one another in this drawing for ease of description, it will be appreciated that, in a physical device, the waveguides may all be arranged in a stack with one waveguide per level. In some other embodiments, multiple component colors may be outputted by the same waveguide, such that, e.g., only a single waveguide may be provided per depth plane.

(71) With continued reference to FIG. **8**, in some embodiments, G is the color green, R is the color red, and B is the color blue. In some other embodiments, other colors associated with other wavelengths of light, including magenta and cyan, may be used in addition to or may replace one or more of red, green, or blue.

(72) It will be appreciated that references to a given color of light throughout this disclosure will be understood to encompass light of one or more wavelengths within a range of wavelengths of light that are perceived by a viewer as being of that given color. For example, red light may include light of one or more wavelengths in the range of about 620-780 nm, green light may include light of one or more wavelengths in the range of about 492-577 nm, and blue light may include light of one or more wavelengths in the range of about 435-493 nm.

(73) In some embodiments, the light source **530** (FIG. **6**) may be configured to emit light of one or more wavelengths outside the visual perception range of the viewer, for example, infrared and/or ultraviolet wavelengths. In addition, the in-coupling, out-coupling, and other light redirecting structures of the waveguides of the display **250** may be configured to direct and emit this light out of the display towards the user's eye **210**, e.g., for imaging and/or user stimulation applications.

(74) With reference now to FIG. **9A**, in some embodiments, light impinging on a waveguide may need to be redirected to in-couple that light into the waveguide. An in-coupling optical element may be used to redirect and in-couple the light into its corresponding waveguide. FIG. **9A** illustrates a cross-sectional side view of an example of a plurality or set **660** of stacked waveguides that each includes an in-coupling optical element. The waveguides may each be configured to output light of one or more different wavelengths, or one or more different ranges of wavelengths. It will be appreciated that the stack **660** may correspond to the stack **260** (FIG. **6**) and the illustrated waveguides of the stack **660** may correspond to part of the plurality of waveguides **270, 280, 290, 300, 310**, except that light from one or more of the image injection devices **360, 370, 380, 390, 400** is injected into the waveguides from a position that requires light to be redirected for in-coupling.

(75) The illustrated set **660** of stacked waveguides includes waveguides **670, 680, and 690**. Each waveguide includes an associated in-coupling optical element (which may also be referred to as a light input area on the waveguide), with, e.g., in-coupling optical element **700** disposed on a major surface (e.g., an upper major surface) of waveguide **670**, in-coupling optical element **710** disposed on a major surface (e.g., an upper major surface) of waveguide **680**, and in-coupling optical element **720** disposed on a major surface (e.g., an upper major surface) of waveguide **690**. In some embodiments, one or more of the in-coupling optical elements **700, 710, 720** may be disposed on the bottom major surface of the respective waveguide **670, 680, 690** (particularly where the one or more in-coupling optical elements are reflective, deflecting optical elements). As illustrated, the in-coupling

optical elements **700, 710, 720** may be disposed on the upper major surface of their respective waveguide **670, 680, 690** (or the top of the next lower waveguide), particularly where those in-coupling optical elements are transmissive, deflecting optical elements. In some embodiments, the in-coupling optical elements **700, 710, 720** may be disposed in the body of the respective waveguide **670, 680, 690**. In some embodiments, as discussed herein, the in-coupling optical elements **700, 710, 720** are wavelength selective, such that they selectively redirect one or more wavelengths of light, while transmitting other wavelengths of light. While illustrated on one side or corner of their respective waveguide **670, 680, 690**, it will be appreciated that the in-coupling optical elements **700, 710, 720** may be disposed in other areas of their respective waveguide **670, 680, 690** in some embodiments. (76) As illustrated, the in-coupling optical elements **700, 710, 720** may be laterally offset from one another. In some embodiments, each in-coupling optical element may be offset such that it receives light without that light passing through another in-coupling optical element. For example, each in-coupling optical element **700, 710, 720** may be configured to receive light from a different image injection device **360, 370, 380, 390, and 400** as shown in FIG. 6, and may be separated (e.g., laterally spaced apart) from other in-coupling optical elements **700, 710, 720** such that it substantially does not receive light from the other ones of the in-coupling optical elements **700, 710, 720**.

(77) Each waveguide also includes associated light distributing elements, with, e.g., light distributing elements **730** disposed on a major surface (e.g., a top major surface) of waveguide **670**, light distributing elements **740** disposed on a major surface (e.g., a top major surface) of waveguide **680**, and light distributing elements **750** disposed on a major surface (e.g., a top major surface) of waveguide **690**. In some other embodiments, the light distributing elements **730, 740, 750**, may be disposed on a bottom major surface of associated waveguides **670, 680, 690**, respectively. In some other embodiments, the light distributing elements **730, 740, 750**, may be disposed on both top and bottom major surface of associated waveguides **670, 680, 690**, respectively; or the light distributing elements **730, 740, 750**, may be disposed on different ones of the top and bottom major surfaces in different associated waveguides **670, 680, 690**, respectively.

(78) The waveguides **670, 680, 690** may be spaced apart and separated by, e.g., gas, liquid, and/or solid layers of material. For example, as illustrated, layer **760a** may separate waveguides **670** and **680**; and layer **760b** may separate waveguides **680** and **690**. In some embodiments, the layers **760a** and **760b** are formed of low refractive index materials (that is, materials having a lower refractive index than the material forming the immediately adjacent one of waveguides **670, 680, 690**). Preferably, the refractive index of the material forming the layers **760a, 760b** is 0.05 or more, or 0.10 or less than the refractive index of the material forming the waveguides **670, 680, 690**. Advantageously, the lower refractive index layers **760a, 760b** may function as cladding layers that facilitate total internal reflection (TIR) of light through the waveguides **670, 680, 690** (e.g., TIR between the top and bottom major surfaces of each waveguide). In some embodiments, the layers **760a, 760b** are formed of air. While not illustrated, it will be appreciated that the top and bottom of the illustrated set **660** of waveguides may include immediately neighboring cladding layers.

(79) Preferably, for ease of manufacturing and other considerations, the material forming the waveguides **670, 680, 690** are similar or the same, and the material forming the layers **760a, 760b** are similar or the same. In some embodiments, the material forming the waveguides **670, 680, 690** may be different between one or more waveguides, and/or the material forming the layers **760a, 760b** may be different, while still holding to the various refractive index relationships noted above.

(80) With continued reference to FIG. 9A, light rays **770, 780, 790** are incident on the set **660** of waveguides. It will be appreciated that the light rays **770, 780, 790** may be injected into the waveguides **670, 680, 690** by one or more image injection devices **360, 370, 380, 390, 400** (FIG. 6).

(81) In some embodiments, the light rays **770, 780, 790** have different properties, e.g., different wavelengths or different ranges of wavelengths, which may correspond to different colors. The in-coupling optical elements **700, 710, 720** each deflect the incident light such that the light propagates through a respective one of the waveguides **670, 680, 690** by TIR. In some embodiments, the in-coupling optical elements **700, 710, 720** each selectively deflect one or more particular wavelengths of light, while transmitting other wavelengths to an underlying waveguide and associated in-coupling optical element.

(82) For example, in-coupling optical element **700** may be configured to deflect ray **770**, which has a first wavelength or range of wavelengths, while transmitting rays **780** and **790**, which have different second and third wavelengths or ranges of wavelengths, respectively. The transmitted ray **780** impinges on and is deflected by the in-coupling optical element **710**, which is configured to deflect light of a second wavelength or range of wavelengths. The ray **790** is deflected by the in-coupling optical element **720**, which is configured to selectively deflect light of third wavelength or range of wavelengths.

(83) With continued reference to FIG. 9A, the deflected light rays **770, 780, 790** are deflected so that they propagate through a corresponding waveguide **670, 680, 690**; that is, the in-coupling optical elements **700, 710,**

720 of each waveguide deflects light into that corresponding waveguide **670, 680, 690** to in-couple light into that corresponding waveguide. The light rays **770, 780, 790** are deflected at angles that cause the light to propagate through the respective waveguide **670, 680, 690** by TIR. The light rays **770, 780, 790** propagate through the respective waveguide **670, 680, 690** by TIR until impinging on the waveguide's corresponding light distributing elements **730, 740, 750**.

(84) With reference now to FIG. 9B, a perspective view of an example of the plurality of stacked waveguides of FIG. 9A is illustrated. As noted above, the in-coupled light rays **770, 780, 790**, are deflected by the in-coupling optical elements **700, 710, 720**, respectively, and then propagate by TIR within the waveguides **670, 680, 690**, respectively. The light rays **770, 780, 790** then impinge on the light distributing elements **730, 740, 750**, respectively. The light distributing elements **730, 740, 750** deflect the light rays **770, 780, 790** so that they propagate towards the out-coupling optical elements **800, 810, 820**, respectively.

(85) In some embodiments, the light distributing elements **730, 740, 750** are orthogonal pupil expanders (OPE's). In some embodiments, the OPE's deflect or distribute light to the out-coupling optical elements **800, 810, 820** and, in some embodiments, may also increase the beam or spot size of this light as it propagates to the out-coupling optical elements. In some embodiments, the light distributing elements **730, 740, 750** may be omitted and the in-coupling optical elements **700, 710, 720** may be configured to deflect light directly to the out-coupling optical elements **800, 810, 820**. For example, with reference to FIG. 9A, the light distributing elements **730, 740, 750** may be replaced with out-coupling optical elements **800, 810, 820**, respectively. In some embodiments, the out-coupling optical elements **800, 810, 820** are exit pupils (EP's) or exit pupil expanders (EPE's) that direct light in a viewer's eye **210** (FIG. 7). It will be appreciated that the OPE's may be configured to increase the dimensions of the eye box in at least one axis and the EPE's may be to increase the eye box in an axis crossing, e.g., orthogonal to, the axis of the OPEs. For example, each OPE may be configured to redirect a portion of the light striking the OPE to an EPE of the same waveguide, while allowing the remaining portion of the light to continue to propagate down the waveguide. Upon impinging on the OPE again, another portion of the remaining light is redirected to the EPE, and the remaining portion of that portion continues to propagate further down the waveguide, and so on. Similarly, upon striking the EPE, a portion of the impinging light is directed out of the waveguide towards the user, and a remaining portion of that light continues to propagate through the waveguide until it strikes the EP again, at which time another portion of the impinging light is directed out of the waveguide, and so on.

Consequently, a single beam of in-coupled light may be "replicated" each time a portion of that light is redirected by an OPE or EPE, thereby forming a field of cloned beams of light, as shown in FIG. 6. In some embodiments, the OPE and/or EPE may be configured to modify a size of the beams of light.

(86) Accordingly, with reference to FIGS. 9A and 9B, in some embodiments, the set **660** of waveguides includes waveguides **670, 680, 690**; in-coupling optical elements **700, 710, 720**; light distributing elements (e.g., OPE's) **730, 740, 750**; and out-coupling optical elements (e.g., EP's) **800, 810, 820** for each component color. The waveguides **670, 680, 690** may be stacked with an air gap/cladding layer between each one. The in-coupling optical elements **700, 710, 720** redirect or deflect incident light (with different in-coupling optical elements receiving light of different wavelengths) into its waveguide. The light then propagates at an angle which will result in TIR within the respective waveguide **670, 680, 690**. In the example shown, light ray **770** (e.g., blue light) is deflected by the first in-coupling optical element **700**, and then continues to bounce down the waveguide, interacting with the light distributing element (e.g., OPE's) **730** and then the out-coupling optical element (e.g., EPs) **800**, in a manner described earlier. The light rays **780** and **790** (e.g., green and red light, respectively) will pass through the waveguide **670**, with light ray **780** impinging on and being deflected by in-coupling optical element **710**. The light ray **780** then bounces down the waveguide **680** via TIR, proceeding on to its light distributing element (e.g., OPEs) **740** and then the out-coupling optical element (e.g., EP's) **810**. Finally, light ray **790** (e.g., red light) passes through the waveguide **690** to impinge on the light in-coupling optical elements **720** of the waveguide **690**. The light in-coupling optical elements **720** deflect the light ray **790** such that the light ray propagates to light distributing element (e.g., OPEs) **750** by TIR, and then to the out-coupling optical element (e.g., EPs) **820** by TIR. The out-coupling optical element **820** then finally out-couples the light ray **790** to the viewer, who also receives the out-coupled light from the other waveguides **670, 680**.

(87) FIG. 9C illustrates a top-down plan view of an example of the plurality of stacked waveguides of FIGS. 9A and 9B. As illustrated, the waveguides **670, 680, 690**, along with each waveguide's associated light distributing element **730, 740, 750** and associated out-coupling optical element **800, 810, 820**, may be vertically aligned. However, as discussed herein, the in-coupling optical elements **700, 710, 720** are not vertically aligned; rather, the in-coupling optical elements are preferably non-overlapping (e.g., laterally spaced apart as seen in the top-down view). As discussed further herein, this nonoverlapping spatial arrangement facilitates the injection of light from different resources into different waveguides on a one-to-one basis, thereby allowing a specific light source to be uniquely coupled to a specific waveguide. In some embodiments, arrangements including nonoverlapping

spatially-separated or in-coupling optical elements may be referred to as a shifted pupil system, and the in-coupling optical elements within these arrangements may correspond to sub pupils.

(88) FIG. 9D illustrates an example of wearable display system **60** into which the various waveguides and related systems disclosed herein may be integrated. In some embodiments, the display system **60** is the system **250** of FIG. 6, with FIG. 6 schematically showing some parts of that system **60** in greater detail. For example, the waveguide assembly **260** of FIG. 6 may be part of the display **70**.

(89) With continued reference to FIG. 9D, the display system **60** includes a display **70**, and various mechanical and electronic modules and systems to support the functioning of that display **70**. The display **70** may be coupled to a frame **80**, which is wearable by a display system user or viewer **90** and which is configured to position the display **70** in front of the eyes of the user **90**. The display **70** may be considered eyewear in some embodiments. In some embodiments, a speaker **100** is coupled to the frame **80** and configured to be positioned adjacent the ear canal of the user **90** (in some embodiments, another speaker, not shown, may optionally be positioned adjacent the other ear canal of the user to provide stereo/shapeable sound control). The display system **60** may also include one or more microphones **110** or other devices to detect sound. In some embodiments, the microphone is configured to allow the user to provide inputs or commands to the system **60** (e.g., the selection of voice menu commands, natural language questions, etc.), and/or may allow audio communication with other persons (e.g., with other users of similar display systems). The microphone may further be configured as a peripheral sensor to collect audio data (e.g., sounds from the user and/or environment). In some embodiments, the display system may also include a peripheral sensor **120a**, which may be separate from the frame **80** and attached to the body of the user **90** (e.g., on the head, torso, an extremity, etc. of the user **90**). The peripheral sensor **120a** may be configured to acquire data characterizing a physiological state of the user **90** in some embodiments. For example, the sensor **120a** may be an electrode.

(90) With continued reference to FIG. 9D, the display **70** is operatively coupled by communications link **130**, such as by a wired lead or wireless connectivity, to a local data processing module **140** which may be mounted in a variety of configurations, such as fixedly attached to the frame **80**, fixedly attached to a helmet or hat worn by the user, embedded in headphones, or otherwise removably attached to the user **90** (e.g., in a backpack-style configuration, in a belt-coupling style configuration). Similarly, the sensor **120a** may be operatively coupled by communications link **120b**, e.g., a wired lead or wireless connectivity, to the local processor and data module **140**. The local processing and data module **140** may comprise a hardware processor, as well as digital memory, such as non-volatile memory (e.g., flash memory or hard disk drives), both of which may be utilized to assist in the processing, caching, and storage of data. Optionally, the local processor and data module **140** may include one or more central processing units (CPUs), graphics processing units (GPUs), dedicated processing hardware, and so on. The data may include data a) captured from sensors (which may be, e.g., operatively coupled to the frame **80** or otherwise attached to the user **90**), such as image capture devices (such as cameras), microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, gyros, and/or other sensors disclosed herein; and/or b) acquired and/or processed using remote processing module **150** and/or remote data repository **160** (including data relating to virtual content), possibly for passage to the display **70** after such processing or retrieval. The local processing and data module **140** may be operatively coupled by communication links **170**, **180**, such as via a wired or wireless communication links, to the remote processing module **150** and remote data repository **160** such that these remote modules **150**, **160** are operatively coupled to each other and available as resources to the local processing and data module **140**. In some embodiments, the local processing and data module **140** may include one or more of the image capture devices, microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, and/or gyros. In some other embodiments, one or more of these sensors may be attached to the frame **80**, or may be standalone structures that communicate with the local processing and data module **140** by wired or wireless communication pathways.

(91) With continued reference to FIG. 9D, in some embodiments, the remote processing module **150** may comprise one or more processors configured to analyze and process data and/or image information, for instance including one or more central processing units (CPUs), graphics processing units (GPUs), dedicated processing hardware, and so on. In some embodiments, the remote data repository **160** may comprise a digital data storage facility, which may be available through the internet or other networking configuration in a “cloud” resource configuration. In some embodiments, the remote data repository **160** may include one or more remote servers, which provide information, e.g., information for generating augmented reality content, to the local processing and data module **140** and/or the remote processing module **150**. In some embodiments, all data is stored and all computations are performed in the local processing and data module, allowing fully autonomous use from a remote module. Optionally, an outside system (e.g., a system of one or more processors, one or more computers) that includes CPUs, GPUs, and so on, may perform at least a portion of processing (e.g., generating image information, processing data) and provide information to, and receive information from, modules **140**, **150**, **160**,

for instance via wireless or wired connections.

(92) Illumination

(93) In some instances, providing illumination, for example, to the eye may be useful. For example, it may be beneficial to project light to a user's eye for eye tracking. Eye tracking may in some implementations be accomplished by imaging the user's eye with one or more cameras. Illumination of the eye may aid in such imaging and eye tracking. Having a localized light source, such as a point source and knowing the location of that light source may also assist in executing the eye tracking algorithm. The location of the origins of the illumination may be the actual light source location or the location of the virtual light source where illumination appears to be coming from. Knowledge of such locations can be considered in processing the eye tracking algorithm in some approaches. These illumination sources may, in some implementations, comprise localized light sources such as point sources. Using multiple illumination sources separated by a distance from each other and thus at different/distinct locations (and knowing these locations) may also assist in processing the eye tracking algorithm. Accordingly, in some designs, a first illumination source directs light to the user's eye at a first time while a first image is obtained from an eye tracking camera, and a second illumination source directs light to the user's eye at a second time while a second image is obtained from the eye tracking camera. In some implementations, the second light illumination may not illuminate the eye when the first image is obtained, while the first light illumination may not illuminate the eye when the second image is obtained. This process may be referred to herein as multiplexing and may be beneficial in performing the eye tracking algorithm.

(94) Furthermore, the ability to project light to a user's eye from one or more locations in front of the eye that are more central (as opposed to from locations at the periphery) may also be helpful in some cases. In various examples, disclosed herein (e.g., FIGS. **10A-10D**), multiple light beams are projected from generally in front of the user's eye (e.g., from a location more central and less peripheral) using light-guiding components disposed directly in front of the user's eyes. The light-guiding components may be optically transparent to visible light such that the user can see through the light-guiding component disposed directly in front of his or her eye to view the environment and objects therein in front of the user. As discussed herein, the light guiding optical component may be configured to eject light guided therein out of the light guiding optical component to provide illumination, for example, to direct light to the user's eye to assist in eye tracking.

(95) In various situations, the light-guiding optical component is forward the eye and the environment with objects therein is forward the light-guiding optical component. Consequently, the terms “forward” and “in front of” may be used herein to describe locations more distal to the eye. Conversely, “rearward” and “in back of” may be used herein to describe locations more proximal to the eye.

(96) FIGS. **10A-10D** illustrate perspective views of a head-mounted display system configured to project light from an illumination source to a user's eye. FIG. **10A** illustrates a light guiding component **902** for guiding light therein to provide illumination, for example, to the eye (e.g., for eye tracking). An in-coupling element **908** is positioned to couple light from an illumination source to the light-guiding component. The light guiding component **902** is shown disposed in front of the eye **916**. In various implementations, the light guiding component is optically transparent to visible light such that the user can see through the light-guiding component disposed in front of the user's eye. The light guiding component may also comprise material having an index of refraction such that light from the illumination source can be guided therein.

(97) In some designs, the light-guiding component may comprise an eyepiece for presenting images from a display to a user's eye as discussed above. The eyepiece may comprise, for example, a waveguide to guide light from the display in the waveguide by total internal reflection. Likewise, this eyepiece for conveying an image from a display to the user's eye may be used as a conduit for providing light from the illumination source to, for example, the eye for illumination thereof (e.g., for eye tracking).

(98) The light-guiding component includes an out-coupling optical element **912** configured to eject light guided within the light-guiding component out of the light-guiding component. In some design, the light-guiding component and the out-coupling optical element are disposed with respect to the user's eye to direct light from the illumination source onto the user's eye. In the case where the light-coupling optical component comprises the eyepiece for also presenting image content to the user's eye, the out-coupling optical element may comprise, for example, an exit pupil expander **912** such as described above. A light distribution optical element **910** may be used to redirect light guided within the light guiding component **902** such that light is ejected from a particular location on the light-coupling optical element. In the case where the light-coupling optical component comprises the eyepiece for also presenting image content to the user's eye, the light distribution optical element may comprise, for example, an orthogonal pupil expander **910** such as described above. The light guiding component **902**, light distribution element (OPE) **910** and out-coupling optical element (OPE) **912** may be configured to operate in a similar manner to waveguides **670, 680, 690** shown in FIGS. **9A-9C**. Likewise, in various implementations, the light distribution element and the out-coupling optical element may comprise diffractive

optical elements such as diffractive gratings or holograms or both or other diffractive optical elements.

(99) Similarly, the light-guiding component may comprise, for example, one or more of the waveguides **670**, **680**, **690** shown in FIGS. **9A-9C**, or otherwise the eyepiece may be used as the light-guiding component to provide illumination to the eye in addition to providing display content. In some other implementations, however, the light-guiding component comprises an additional light-guiding component to any waveguide or waveguide used to convey image content to the user's eye such the waveguides **670**, **680**, **690** shown in FIGS. **9A-9C**.

(100) As shown in FIGS. **10A-10D**, the one or more illumination source provides light that is coupled into the light-guiding component **902** and ejected therefrom providing illumination, for example, to illuminate the user's eye. In some designs, the illumination source may comprises an invisible or visible light source such as an infrared or visible light source configured to selectively emit IR or visible wavelength light, respectively. The illumination source may comprise, for example, an LED or a laser or other type of emitter or light source. In some designs, the illumination source comprises a vertical-cavity surface-emitting laser (VCSEL). In some implementations, a filter may be included to provide for spectral narrowing. The filter may comprise, for example, a narrow band pass filter in some cases.

(101) In some implementations, the illumination source may comprise an emitter that outputs a divergent beam. In some such cases, additional collimating optics may increase the collimation of the light from the illumination source.

(102) In some designs, such as shown in FIG. **10A-10D**, the in-coupling element **908** comprises an in-coupling prism or other reflective coupling element. In some implementations, the in-coupling element is configured to in-couple light from at least one illumination source into the light guiding component at angle larger than the critical angle of the light guiding component. In some embodiments, the in-coupling element is configured to in-couple light from at least one illumination source into the light-guiding component at an angle of about 45°. A prism having an inclined reflective surface (e.g., providing reflection via total internal reflection) may be suitable to turn light from the illumination source into the light guiding component at 45° with respect to the light-guiding component (e.g., with respect to the major, top and bottom or front and rear, reflecting surfaces of the light guiding component that guide the light within the light-guiding component via total internal reflection). If the light propagates within the light-guiding component (such as a planar light guide plate, sheet, or film) at an angle of 45° with respect to the light-guiding component (e.g., with respect to major, top and bottom or front and rear, reflecting surfaces of the light-guiding components, and is not turned out of the light-guiding component) the light may reflect from the end of the light-coupling component and continue to be guided therein in the opposite direction via total internal reflection. In some implementations, the in-coupling optical element may comprise an in-coupling grating (ICG) or other diffractive optical element. In some designs, more than one in-coupling element may be employed.

(103) In some designs, the one or more illumination source comprises a plurality of illumination sources that produce a plurality of beams of light. In some implementations, illumination sources radiate light of different color than others of the illumination sources and the illumination sources may include multiple filters, wherein different filters produces a light beams of different wavelengths, respectively. Any number of illumination sources may be utilized such as, for example, 1, 2, 3, 4, 5, 10 or 20 illumination sources, or any range between any of these values. In some implementations, the plurality of light beams have respective spectral compositions or colors or wavelength bands.

(104) FIGS. **10A-10D** show three illumination sources **904A**, **904B** and **904C**, and a single collimating lens **906** configured to couple light into in-coupling optical element **908** (e.g., prism), and an out-coupling optical element configured to out-coupling light from the light-guiding component **902** to a user's eye **916**. In various implementations (see, e.g., FIG. **10B**), the light can be out-coupled from the out-coupling optical element **912** in a manner such that out-coupled light appears to originate from one or more virtual sources **992A** such as point sources. The light may, for example, diverge upon exiting the light-guiding component in a manner such that the light appears to emanate from a virtual source such as a localized source (e.g. point source) located a distance away from (e.g., forward) the light-guiding optical element.

(105) FIG. **10B-10D** each illustrate such a system in operation displaying light **926A**, **926B** and **926C** from light sources **904A**, **904B**, **904C** coupled into the light-guiding component **902** and out-coupled to an eye **916** in different directions as if emanating from differently spatially located localized virtual sources **922A**, **922B** and **922C** at a particular depth (e.g. a depth plane **914**). FIG. **10B**, for example, illustrates the first illumination source **904A** emitting a divergent beam of light **920A** that is coupled into the light-guiding component **902** via the prism **908**. The collimating lens **906** in the optical path between the illumination source **904A** and in-coupling element **908** collimates the light such that the light is substantially propagating along a common direction. Light from the first illumination source **920A** propagates within the light-guiding component **902** and is redirected by the light distribution element (e.g. OPE) **910** toward the out-coupling optical element **912** (e.g., EPE). The out-coupling

optical element ejects light guided within the light-guiding component **902** toward the user's eye **916**. The light exiting the light-guiding component **902** comprises a diverging beam that appears to emanate from a first virtual light source **922A** at a depth plane **914**. The direction that the divergent beam is directed causes the first virtual light source **922A** to appear to be located at a particular location, for example, on the depth plane **914**.

Accordingly, the out-coupled light **926A** is directed to the user's eye **916** as if the out-coupled light **926A** is emitted from the first virtual source **922A** originating from the depth plane **914**, wherein the virtual light **924A** is the virtual projection of out-coupled light **926A** between light-guiding component **902** and depth plane **914**.

(106) FIG. **10C** illustrates the second illumination source **904B** emitting a divergent beam of light **920B** that is coupled into the light-guiding component **902** via the prism **908**. The collimating lens **906** in the optical path between the second illumination source **904B** and in-coupling element **908** collimates the light such that the light is substantially propagating along a common direction. Light from the second light source **920B** propagates within the light-guiding component **902** and is redirected by the light distribution element (e.g. OPE) **910** toward the out-coupling optical element **912** (e.g., EPE). The out-coupling optical element ejects light guided within the light-guiding component **902** toward the user's eye **916**. The light exiting the light-guiding component **902** comprises a diverging beam that appears to emanate from a second virtual light source **922B** at a depth plane **914**. The direction that the divergent beam is directed causes the second virtual light source **922B** to appear to be located at a particular location, for example, on the depth plane **914**. Accordingly, the out-coupled light **926B** is directed to an eye **916** as if the out-coupled light **926B** is emitted from the second virtual source **922B** originating from the depth plane **914**, wherein the virtual light **924B** is the virtual projection of out-coupled light **926B** between light coupling component **902** and depth plane **914**.

(107) FIG. **10D** illustrates the third illumination source **904C** emitting a divergent beam of light **920C** that is coupled into the light-guiding component **902** via the prism **908**. The collimating lens **906** in the optical path between the third illumination source **904C** and in-coupling element **908** collimated the light such that the light is substantially propagating along a common direction. Light from the third illumination source **920C** propagated within the light-guiding component **902** and is redirected by the light distribution element (e.g. OPE) **910** toward the out-coupling optical element **912** (e.g., EPE). The out-coupling optical element ejects light guided within the light-guiding component **902** toward the user's eye **916**. The light exiting the light-guiding component **902** comprises a diverging beam that appears to emanate from a third virtual light source **922C** at a depth plane **914**. The direction that the divergent beam is directed causes the third virtual light source **922C** to appear to be located at a particular location, for example, on the depth plane **914**. Accordingly, the out-coupled light **926C** is directed to an eye **916** as if the out-coupled light **926C** is emitted from the third virtual source **922C** originating from the depth plane **914**, wherein the virtual light **924C** is the virtual projection of out-coupled light **926C** between light coupling component **902** and depth plane **914**.

(108) In various implementations, the out-coupling optical element comprises a diffractive optical element such as a grating structure or hologram or other diffractive optical element configured to turn light guided within the light-guiding component out of the light guiding component such that the light is not guided within the light-guiding optical component. In various implementations, the out-coupling optical element may be formed on either side of the light-guiding components and/or in the light guiding component. The out-coupling optical element may comprise, for example, one or more volume holograms, surface holograms, volume or surface diffractive optical elements and/or diffraction gratings. The diffractive optical element (e.g. grating or hologram), can be configured to cause the light exiting the light-guiding component to diverge and may be configured to cause the light to appear as if the light originated from a different location, for example, forward the light-guiding component. Accordingly, the out-coupling optical element can be considered to have optical power, such as negative optical power, to cause the light incident thereon to diverge as if originating from a different location or depth. Accordingly, in some cases, the out-coupling optical element may comprise a diffraction grating or diffractive optical element (e.g., hologram) with optical power, for example, negative optical power. Other types of out-coupling optical elements or the addition of additional optical elements such as a lens or lens arrays may be used to impart optical power, for example, to cause the light to diverge as if emanating from a virtual light source located in front (or rearward) of the light-guiding component.

(109) As discussed above, head-mounted display systems may include waveguides configured to receive light from one or more displays and direct the light to a user's eye so as to provide image content to the user. Optical power may be provided to optical elements (e.g. out-coupling optical elements or EPEs) to cause light ejected from the waveguides to diverge as if originating from different depth planes. Such system (e.g., waveguides) used to direct light from display into the eyes of user's and provide image content to the user may also be used to direct illumination from an illumination source (e.g., to the eye of the user). Similar structures (e.g., out-coupling optical element or EPEs) configured to cause the light from the display to diverge may be used to cause the light from the illumination source to be divergent as if originating from a localized virtual light source (e.g., point source) a

distance away from the light-coupling component. In such configurations, the light guiding optical element may receive light from both one or more displays and one or more illumination sources via one or more in-coupling optical elements. In some implementations, the same out-coupling optical element (e.g., EPE) is used to out-couple light from the light-guiding component(s) or waveguides(s). This out-coupling optical element may comprise a diffractive optical element such as a hologram, etc. in some implementations and/or may further be integrated with one or more lens to provide negative (or positive) optical power. In other implementations, the light-guiding component may be provided in addition to an eyepiece or other waveguide for conveying light from one or more displays to the user's eye. In some implementations, the out-coupling optical element may be diffusive. The out-coupling optical element may comprise, for example, a holographic diffuser.

(110) As illustrated in FIGS. **10B-10D**, the virtual sources from which light appears to be emanating may be located at different positions along a single virtual depth plane. Accordingly, a plurality of virtual sources may originate from a single virtual depth plane. Conversely, a plurality of virtual sources may originate from a plurality of virtual depth planes. In some designs, the virtual source may be a localized source of emission such as a virtual point source. In some implementations, the virtual source may have a maximum lateral extent of about 100 nm, 250 nm, 500 nm, about 1 μm , about 2 μm , about 3 μm , about 5 μm , about 10 μm or about 50 μm , or any range between any of these values. In some configurations, the virtual depth plane where the virtual source is located may be at about 5 mm, about 10 mm, about 15 mm, about 20 mm, about 30 mm, about 50 mm, about 100 mm or about 200 mm in front (or rearward) of the light coupling component or the user's eye, or any range between any of these values.

(111) In various implementations, the out-coupling optical element may produce a plurality of virtual sources such as, for example, 2, 3, 4, 5, 6, 10 or 20 virtual sources, or any range between any of these values. These virtual sources may be at different locations on a same depth plane, at different depth planes or a combination of both.

(112) Accordingly, the out-coupling optical element may produce out-coupled light in a plurality of directions. This may depend, for example, on which light source is outputting light. The different light sources having different positions with respect to the in-coupling optical element may provide different beams that are possibly collimated and directed in different directions within the light-guiding component and therefore are incident on the out-coupling optical element from different directions and possibly at different locations. The result is that the out-coupled beam has different direction. This may cause the virtual source from which the light appears to originate to be different (e.g., have a different location) for different illumination sources.

(113) As discussed above, having a plurality of light sources situated at different known locations can be used for eye tracking, knowledge of the location of the light sources, assisting in executing the eye tracking algorithm. Accordingly, different illuminations sources (and consequently different corresponding virtual sources) may be activated when a camera or sensor (e.g., eye tracking camera) captures an image. Light may be projected into the eye from different virtual sources at specific lateral positions and/or depths in front of the user's eye at different times when different images of the eye are captured by the camera. As more light beams with their different known virtual source positions and depths are utilized, the light beams may be multiplexed and eye tracking may be improved. Such a time-multiplexing approach may be used with the eye tracking camera to increase eye tracking robustness. In some cases, wavelength multiplexing may be used. For example, different illumination sources having different spectral output (or sent through wavelength filters) to provide different spectral distributions can be used to couple into different out-coupling optical elements designed to selectively operate on different wavelengths. Accordingly, as illustrated, the system may additionally comprise an eye tracking camera **918** to obtain images of the eye to track the user's eye **916**.

(114) In some configurations such as discussed above, the out-coupling optical element may be configured to direct out-coupled light to the user's eye. Such illumination may be provided to the eye, for example, to perform eye tracking. In other configurations, however, the out-coupling optical element may be configured to direct out-coupled light to the environment in front of the user's eye. Such illumination may be used, for example, for sensing the depth of objects in the environment in front of the user. Alternatively, such illumination may be used to provide others with notification of the state of the eyewear (e.g., taking video) or for aesthetic effects. Other uses may be possible.

(115) A wide range of variations are possible. For example, in some implementations a light distribution optical element (or OPE) may be used while in other implementations, the OPE may be absent. Similarly, the light distribution optical element (or OPE) may be formed on or in the light guiding component and may comprise a diffractive optical element or other optical structure.

(116) In some embodiments, the image projector of the head mounted display and the illumination source share the same in-coupling optical element and light-guiding component.

(117) Masks

(118) As discussed above, in some instances such as for eye tracking, projecting light onto the user's eye as if the light originated from multiple light sources may be beneficial. Furthermore, in some instances, projecting light from one or more light sources into the environment in front of the user's eye, for example, for depth sensing, may be useful. One or more illumination sources and a light guiding component may be employed to provide such illumination.

(119) FIGS. **11A-11B** illustrates a perspective view of a light-guiding component **1002** having a mask with openings configured to produce localized regions where light emanates. Specifically, FIG. **11A** shows a light-guiding component **1002** having an in-coupling element **1008** positioned to couple light therein. A light distribution element (e.g., OPE) **1010** and an out-coupling optical element **1012** (e.g., EPE) are disposed on or in the light-guiding component **1002**. Disposed with respect to (e.g., over or under) the out-coupling element **1012** is a mask **1014** comprising four mask holes or mask openings **1022A**, **1022B**, **1022C**, **1022D**. The light guiding component **1002**, light distribution element (OPE) **1010** and out-coupling optical element (EPE) **1012** may be configured to operate in a similar manner to waveguides **670**, **680**, **690** shown in FIGS. **9A-9C** and as discussed above with regard to FIGS. **10A-10D**. For example, in some implementations, one or both of the light distribution element (OPE) **1010** and out-coupling optical element (EPE) **1012** comprises diffractive optical elements, although the structure of these elements should not be so limited. Moreover, the out-coupling optical element need not be provided with optical power or otherwise configured to cause the light ejected from the light-guiding component **1002** by the out-coupling optical element to diverge. As will be discussed below, the openings in the mask may provide for such divergence in some implementations. Also as discussed above, the light-guiding component **1002** may comprise an eyepiece comprising one or more waveguides (such as the waveguides **670**, **680**, **690** shown in FIGS. **9A-9C**) that are configured to receive light from a display and to deliver image content to a user's eye or alternatively the light guiding component **1002** may supplement such an eyepiece configured to deliver image content to a user.

(120) FIG. **11B** shows an illumination source **1004** disposed with respect to the in-coupling optical element **1008** to couple light into the light guiding component **1002** such that the light is guided therein by total internal reflection. A light distribution element **1010** is disposed to receive light coupled into the light-guiding component **1002** by the in-coupling optical element and redirect the light toward the out-coupling optical element. The out-coupling optical element causes the light to be ejected from the light guiding component. As discussed above, the out-coupling optical element may comprise a diffractive optical element, diffractive features, scatter features or otherwise is configured to turn the light guided within the light-guiding component such that the light is not guided therein. For example, the light may be directed toward the user's eye at an angle such that the light will not be guided within the light-guiding component by total internal reflection. The mask may comprise material that is opaque (e.g., absorbing, reflective) to light emitted by the illumination source such that this light does not exit the light-guide, for example, toward the eyes unless the light passes through the one or more openings **1022A**, **1022B**, **1022C**, **1022D** in the mask. In some implementations, the mask may comprise a dielectric such as a dielectric coating and may be reflective at a specific wavelength or wavelengths. In some designs, by being more reflective and less absorptive, the mask may be more efficient.

(121) In some configurations, the openings in the mask are small compared to the mask. The reduced size may in some instances cause divergence of the beam exiting through the opening by diffraction. The openings may, for example, have lateral extent, e.g., widths or diameters of about 1 μm , about 5 μm , about 10 μm , about 20 μm , about 50 μm , about 100 μm , about 500 μm , about 1 mm or about 5 mm, or any range between any of these values. In some cases, the small opening can be considered to create point sources of light. Several such localized light sources spaced apart from each other may be created by the openings in the mask.

(122) FIG. **11B** illustrates out-coupled light **1026A**, **1026B**, **1026C**, **1026D**, propagated through the openings **1022A**, **1022B**, **1022C**, **1022D**, which may be point sources, as shown. FIG. **11B** specially depicts the illumination source **1004** emitting a divergent light beam **1020** to the in-coupling optical element **1008**. In-coupling element **1008** couples light into the light-guiding component **1002** such that the light is guided therein by total internal reflection. The light beam, however, may continue to diverge within the light-guiding optical element. The light in-coupled into the light-guiding component **1002** may propagate to the light distribution element or OPE **1010**. The light distribution element or OPE **1010** may redirect at least a portion of this light to the out-coupling optical element **1012**. As discussed above, the out-coupling optical element **1012** is configured to eject light from the light-guiding component **1002**. However, where the mask **1014** covers the out-coupling optical element **1012** or portions of the light-guiding component **1002** where light would be ejected by the out-coupling optical element, light may be blocked such that less light escapes through the mask. The openings **1022A**, **1022B**, **1022C**, **1022D** in the mask, however, allow light to pass therethrough. Light **1026A**, **1026B**, **1026C**, **1026D** may exit through the opening **1022A**, **1022B**, **1022C**, **1022D**, for example, to the user's eye (or to the environment in front of the user).

(123) The opening may be regions of the mask where the mask is transmissive and need not necessarily be regions devoid of material. For example, the mask may comprise regions that are substantially opaque (reflective and/or absorbing) and regions that are substantially less opaque (e.g., less reflective and/or absorbing). These latter regions are referred to herein as openings in the mask because more light will pass through these regions or openings. In configurations where the mask is reflective, light not transmitted through the opening may be potentially reflected back into the light-guiding component and be guided therein until being ejected in a process referred to herein as recycling or light recycling.

(124) In some implementations, the mask may be dichroic and/or wavelength selective. For example, the mask may absorb or reflect invisible (e.g., infrared) light thereby blocking and/or recycling light from the illumination source, which may be an infrared light source. The opening, however, would be configured to pass this infrared light. The mask may, however, be transmissive to visible light such that the user can see through the mask to the environment in front of the user.

(125) In some embodiments, a plurality of dichroic masks may be stacked with respect to the out-coupling element, for example, such that a first mask blocks a first wavelength or spectral range and second mask blocks a second wavelength or spectral range so that light at first wavelength(s) is blocked or substantially blocked by the first mask, however, passes through an opening the first mask. The first wavelength(s) will also be transmitted by the second mask. Similarly, the second wavelength(s) will be blocked or substantially blocked by the second mask, however, will pass through an opening in the second mask. The second wavelength(s) will also be transmitted by the first mask. As a result, first and second light sources configured to output light corresponding to the first and second wavelength regions, respectively, are produced. As discussed above, having different spatially separated light sources, possibly of known position, may improve eye tracking. Multiplex (time multiplexing and/or wavelength multiplexing) may be used to coordinate the image capture with the activation of the different respective light sources. In some implementations, different of the plurality of masks may comprise their own pattern and plurality of openings. A plurality of masks and opening patterns may be used in conjunction with multiple wavelength sources and/or filters, thereby allowing for selective wavelength-based out-coupling of light through selective openings of the plurality of masks.

(126) Accordingly, the illumination source may emit light of a wide variety of different wavelength, such as IR and/or visible wavelengths. As discussed above, the illumination source may comprise an LED or laser. In some implementations, the illumination source comprises a vertical-cavity surface-emitting laser (VCSEL). In some configurations, the illumination source may produce a divergent beam and/or a divergent beam is coupled into the light-guiding component. In some designs, the one or more illumination sources may comprise a plurality of illumination sources that produce a plurality of beams of light. In some implementations, the plurality of light beams have different respective wavelengths. In some configurations, a filter, such as a narrow band pass filter is employed to tailor the wavelength characteristics of the light. In some implementations, a plurality of illumination source include a plurality of filters, different filters producing light beams of different wavelengths. Any number of illumination sources may be utilized such as, for example, 1, 2, 3, 4, 5 or 10 illumination sources, or any range between any of these values.

(127) In some configurations, an in-coupling optical element may comprise an in-coupling grating (ICG). In some configurations, the in-coupling optical element comprises an in-coupling prism. In some implementations, the in-coupling element is configured to in-couple light from at least one illumination source into the light-guiding component at angle larger than the critical angle of the light guiding component. In some implementations, the in-coupling optical element is configured to in-couple light from at least one illumination source into the light-guiding component at an angle of about 45° . A prism having an inclined reflective surface (e.g., providing reflection via total internal reflection) may be suitable to turn light from the illumination source into the light guiding component at 45° with respect to the light-guiding component (e.g., with respect to the major, top and bottom or front and rear, reflecting surfaces of the light guiding component that guide the light within the light-guiding component via total internal reflection). If the light propagates within the light-guiding component (such as a planar light guide plate, sheet, or film) at an angle of 45° with respect to the light-guiding component (e.g., with respect to major, top and bottom or front and rear, reflecting surfaces of the light-guiding components), and is not turned out of the light-guiding component, the light may reflect from the end of the light-guiding component and continue to be guided therein in the opposite direction via total internal reflection. More than one in-coupling optical element may be employed.

(128) In various implementations, the light guiding component may comprise material optically transmissive to light from the one or more illumination sources. Light may be guided within the light-guiding component by total internal reflection. In some implementations, however, the light-guiding component comprises a hollow conduit having inner sidewalls from which the light is reflected to guide the light within the light-guiding component.

(129) In some implementations, the light distributing optical element or OPE may be formed on a light-guiding

component or in the light-guiding component. In some configurations, the light distributing optical element or OPE may be excluded.

(130) In some designs, the out-coupling optical element may be formed on or in the light-guiding component. The out-coupling optical element may comprise one or more diffractive optical elements such as one or more diffraction gratings and/or holograms. The out-coupling optical element may comprise one or more diffusing or scattering features or layers. For example, the out-coupling optical element may comprise one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles or particle layers, one or more irregular surfaces, one or more surface relieve structures, PTFE, Teflon, ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof. The out-coupling optical element may cause the light guided within the light-guiding optical element to be directed toward the mask and opening(s) in the mask such that at least some of the light can exit through the opening(s).

(131) In some implementations, the out-coupling optical element encompasses the entire area of the mask and/or vice versa. In some implementations, the out-coupling optical element is larger than the mask or the mask is larger than the out-coupling optical element. In some implementations, the out-coupling optical element encompasses the area of the mask openings.

(132) In some configurations, the out-coupling optical element may be excluded. For example, light may simply leak out of the light guiding optical element by not being total internally reflected therein. For example, the inner side walls of the light guiding element may be reflective but allow some light guided within the light-guiding component to pass therethrough. Other variations are possible.

(133) As discussed above, in some configurations, light is ejected out of the light-guiding optical element towards the user's eye to illuminate the user's eye, for example, with infrared light for tracking. In some implementations, one or more cameras are used to capture the images of the eye illuminated by the illumination source. In some configurations, a time-multiplexing approach may be used with a camera to increase eye tracking robustness.

(134) In some configurations, light is ejected out of the light-guiding component towards the environment in front of the user possibly to illuminate objects in the environment, for example, to provide for depth sensing.

(135) Accordingly, one or more eye tracking cameras, depth sensor(s), or other components may additionally be included. Likewise, one or more displays for projecting image content into the eye of the users may also be included. Similarly, any of the features, structures, variations, applications, uses, benefits, etc. described above may be used in connection with or are applicable to implementations that employ the mask and one or more openings in the mask to provide illumination.

(136) In some embodiments, the image projector of the head mounted display and the illumination source share the same in-coupling optical element and light-guiding component.

(137) Diffusive Optical Elements

(138) In various implementations, the out-coupling optical element may comprise a diffusive optical element.

(139) FIGS. 12A-12B, for example, illustrates a perspective view of a light-guiding component **1102** including a plurality of diffusive optical elements, diffusive regions, or scatter regions for ejecting light guided within the light-guiding component **1102**. Specifically, FIG. 12A shows a light-guiding component **1102** having an in-coupling element **1108** positioned to couple light therein. A light distribution element (e.g., OPE) **1110** and an out-coupling optical element **1112** (e.g., EPE) comprising a plurality of diffusive optical elements or scatter regions **1122A**, **1122B**, **1122C**, **1122D** (e.g., four diffusive optical element shown) for ejecting light guided within the light-guiding component **1102** are disposed on or in the light-guiding component **1102**. The light guiding component **1102**, light distribution element (OPE) **1110** and out-coupling optical element (EPE) **1112** may be configured to operate in a similar manner to waveguides **670**, **680**, **690** shown in FIGS. 9A-9C and as discussed above with regard to FIGS. 10A-10D. For example, in some implementations, the light distribution element (OPE) **1010** comprises diffractive optical elements although the structure of these elements should not be so limited. Also as discussed above, the light-guiding component may further comprise an eyepiece comprising one or more waveguides (such as the waveguides **670**, **680**, **690** shown in FIGS. 9A-9C) that are configured to receive light from a display and to deliver image content to a user's eye or alternatively the light guiding component may supplement such an eyepiece configured to deliver image content to a user. In some implementations, however, the light-guiding component may comprise the eye piece that is also used to convey image content to a user. For example, the light-guiding component may comprise a waveguide that guides light from the illumination source (e.g., to the user's eye or to the environment forward the user) as well as light from a projector or display to the user's eye to present images to the user's eye. In certain designs, for example such as where the light-guiding component is used to both convey illumination from the illumination source as well as light from an image projector or display, both the out-coupling optical element (EPE) **1112** comprising the diffusive optical elements (or diffractive optical elements) as well as an out-coupling optical element (EPE) for out-coupling light from the

display or the image projector may be included. In some cases, either or both the out-coupling optical element (EPE) **1112** comprising the diffusive optical elements (or diffractive optical elements) and/or the out-coupling optical element (EPE) for out-coupling light from the display or image projector are wavelength selective. For example, the out-coupling optical element (EPE) **1112** comprising the diffusive optical elements (or diffractive optical elements) may be configured to selectively out-couple a first wavelength or group of wavelengths and the out-coupling optical element (EPE) for out-coupling light from the display or image projector may be configured to selectively out-couple a second wavelength or group of wavelengths. In some such cases, the out-coupling optical element (EPE) **1112** comprising the diffusive optical elements (or diffractive optical elements) may be configured to not out-couple light having the second wavelength or group of wavelengths and the out-coupling optical element (EPE) for out-coupling light from the display or image projector may be configured not to out-couple light having the first wavelength or group of wavelengths. The first wavelength or group of wavelengths may include infrared wavelengths and not visible wavelengths and the second wavelength or group of wavelengths may include visible wavelengths and not infrared wavelengths. In such cases, for example, the out-coupling optical element (EPE) **1112** comprising the diffusive optical elements (or diffractive optical elements) may out-couple infrared and not visible light while the out-coupling optical element (EPE) for out-coupling light from the display or image projector may out-couple visible light and not the infrared light or at least the infrared light output by the illumination source. Accordingly, in some designs, the out-coupling optical elements **1112** may be wavelength-selective, such that, for example, the out-coupling optical elements only out-couples select wavelengths (e.g. IR) guided therein and do not interact with or out-couple other wavelengths (e.g. visible) guided therein. Other approaches are possible. For example, in some implementations, the out-coupling optical element (EPE) for out-coupling light from the display or image projector may have openings or breaks corresponding with the lateral placement or location of the out-coupling optical element (EPE) **1112** comprising the diffusive optical elements (or diffractive optical elements).

(140) FIG. **12B** shows an illumination source **1104** disposed with respect to the in-coupling optical element **1108** to couple light into the light guiding component **1102** such that the light is guided therein by total internal reflection. The light distribution element **1210** is disposed to receive the light coupled into the light-guiding component **1102** by the in-coupling optical element and redirect the light toward the out-coupling optical element comprising the diffusive optical elements or scatter regions. The out-coupling optical element, namely, the diffusive optical elements or scatter regions, cause light from the illumination source to be ejected from the light guiding component **1102**. As discussed above, the out-coupling optical element may comprise diffusive features or scatter features configured to turn the light guided within the light-guiding component **1102** such that the light is not guided therein. For example, the light may be directed toward the user's eye at an angle such that the light will not be guided within the light-guiding component **1102** by total internal reflection. The scatter features **1122A**, **1122B**, **1122C**, **1122D** may be disposed in localized regions such that the light appears to emanate from localized light sources (e.g., point sources) that may be located on or at the light-guiding component, for example, a surface thereof.

(141) Accordingly, in some configurations, the diffusive regions **1122A**, **1122B**, **1122C**, **1122D** are small compared to light-guiding component **1102**. The reduced size may in some instances cause divergence of the beam by diffraction. One of the diffusive regions **1122A**, **1122B**, **1122C**, **1122D** may, for example, have lateral extents, e.g., widths or diameters of about 1 μm , about 5 μm , about 10 μm , about 20 μm , about 50 μm , about 100 μm , about 500 μm , about 1 mm or about 5 mm, or any range between any of these values. In some cases, one of the diffusive regions **1122A**, **1122B**, **1122C**, **1122D** can be considered to create a point source of light. Several such localized light sources spaced apart from each other may be created by the plurality of diffusive regions **1122A**, **1122B**, **1122C**, **1122D**.

(142) FIG. **12B** illustrates out-coupled light **1126A**, **1126B**, **1126C**, **1126D**, ejected by the diffusive regions **1122A**, **1122B**, **1122C**, **1122D**, which may correspond to point sources, as shown. FIG. **12B** specially depicts the illumination source **1104** emitting a divergent light **1020** to the in-coupling optical element **1108**. In-coupling element **1108** couples the light into the light-guiding component **1102** such that the light is guided therein by total internal reflection. The light beam, however, may continue to diverge within the light-guiding optical element. The light in-coupled into the light-guiding component **1102** may propagate to the light distribution element or OPE **1110**. The light distribution element or OPE **1010** may redirect at least a portion of this light to the out-coupling optical element **1112** comprising the plurality of diffusive optical elements or scatter regions **1122A**, **1122B**, **1122C**, **1122D**. As discussed above, the out-coupling optical element **1112** comprising the plurality of diffusive optical elements or scatter regions **1122A**, **1122B**, **1122C**, **1122D** is configured to eject light from the light-guiding component **1102**. Light **1126A**, **1126B**, **1126C**, **1126D** may be ejected by diffusive optical elements or scatter regions **1122A**, **1122B**, **1122C**, **1122D**, for example, to the user's eye (or to the environment in front of the user).

(143) In some implementations, a plurality of light beams illuminate a plurality of out-coupling optical elements comprising a plurality of diffusive optical elements. For example, in some designs, reflection off an opposite edge and/or splitting of the beam directs the beam towards different out-coupling optical elements comprising different diffusive optical elements. In various implementations, for example, different light beams of the plurality of light beams comprises different wavelengths of light and different ones of the plurality of out-coupling optical elements selectively out-couple respective ones of these wavelengths, such that different light beams having different wavelengths are out-coupled through different respective out-coupling optical elements. In some designs, these plurality of light beams can be turned or out-coupled simultaneously or sequentially.

(144) The illumination source may emit light of a wide variety of different wavelengths, such as IR and/or visible wavelengths. As discussed above, the illumination source may comprise an LED or laser. In some implementations, the illumination source comprises a vertical-cavity surface-emitting laser (VCSEL). In some embodiments, the illumination source may produce a divergent beam and/or a divergent beam is coupled into the light-guiding component. In some configurations, the one or more illumination sources may comprise a plurality of illumination sources that produce a plurality of beams of light. In some implementations, the plurality of light beams have different respective wavelengths. In some configurations, a filter, such as a narrow band pass filter is employed to tailor the wavelength characteristics of the light. In some designs, a plurality of illumination source include a plurality of filters, different filters producing light beams of different wavelengths. Any number of illumination sources may be utilized, for example, such as 1, 2, 3, 4, 5 or 10 illumination sources, or any range between any of these values. In some embodiments, a plurality of light beams can be turned simultaneously or sequentially.

(145) In some configurations, an in-coupling element may comprise an in-coupling grating (ICG). In some configurations, the in-coupling element comprises an in-coupling prism. In some implementations, the in-coupling element is configured to in-couple light from at least one illumination source into the light guiding component at angle larger than the critical angle of the light guiding component. In some designs, the in-coupling element is configured to in-couple light from at least one illumination source into the light guiding component at an angle of about 45° . A prism having an inclined reflective surface (e.g., providing reflection via total internal reflection) may be suitable to turn light from the illumination source into the light guiding component at 45° with respect to the light-guiding component (e.g., with respect to the major, top and bottom or front and rear, reflecting surfaces of the light guiding component that guide the light within the light-guiding component via total internal reflection). If the light propagates within the light-guiding component (such as a planar light guide plate, sheet, or film) at an angle of 45° with respect to the light-guiding component (e.g., with respect to major, top and bottom or front and rear, reflecting surfaces of the light-guiding components), and is not turned out of the light-guiding component, the light may reflect from the end of the light-coupling component and continue to be guided therein in the opposite direction via total internal reflection. More than one in-coupling element may be employed.

(146) In various implementations, the light-guiding component may comprise material optically transmissive to light from the one or more illumination sources. Light may be guided within the light-guiding component by total internal reflection. In some implementations, however, the light-guiding component comprises a hollow conduit having inner sidewalls from which the light is reflected to guide the light within the light-guiding component.

(147) In some implementations, the light distributing optical element or OPE may be formed on the light-guiding component or in the light guiding component. In some configurations, the light distributing optical element or OPE may be excluded.

(148) In some configurations, a majority of the out-coupled light exits from the light-guiding component from the diffusive optical elements. In some designs, the diffusive optical elements may scatter out light. In some configurations, the diffusive optical elements are refractive, reflective, diffractive, or any combination thereof. In some designs, the out-coupling optical element may be formed on or in the light-guiding component. In some designs, for example, the diffusive optical elements are disposed on the top surface of the light guiding component. In some implementations, a diffusive optical element such as a diffusing sheet or film or portion thereof or diffusing material or particles is placed on a surface of the light guiding component. In some configurations, the diffusive optical elements are disposed within the volume of the light guiding component. In some embodiments, the out-coupling optical element may comprise the diffusive optical elements. In some embodiments, a plurality of out-coupling optical elements are employed comprising a plurality of diffusive optical elements. In some embodiments, the out-coupling optical elements (or plurality of diffusive optical element) selectively out-couple a light from different spectral regions respectively.

(149) The out-coupling optical element may comprise one or more diffusing or scattering features or layers. For example, the out-coupling optical element may comprise one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles or layer of particles, one or more irregular surfaces, one or more surface relief structures,

polytetrafluoroethylene (e.g., PTFE and/or Teflon.), ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof. In some implementations, the diffusive optical elements only extend across a small portion of the light-guiding component. The diffusive optical element may, for example, extend across an area of the light-guiding component that is less than 10%, less than 5%, less than 3%, less than 2%, less than 1%, less than 0.5% or less than 1%, or any range between any of these values. The out-coupling optical element may cause the light guided within the light-guiding component to be directed such that at least some of the light can exit.

(150) As discussed above, in some configurations, light is ejected out of the light-guiding optical element towards the user's eye to illuminate the user's eye, for example, with infrared light for eye tracking. In some implementations, one or more cameras are used to capture the images of the eye illuminated by the illumination source. In some configurations, a time-multiplexing approach may be used with a camera to increase eye tracking robustness.

(151) In some configurations, light is ejected out of the light-guiding optical element towards the environment in front of the user possibly to illuminate objects in the environment, for example, to provide for depth sensing.

(152) In some implementations, at least one illumination source may emit visible light and be out-coupled from the light-guiding optical element to provide visual indicia (e.g., alerts, notifications, etc.) to the user and/or the user's environment. For example, in some embodiments, the visible light may be out-coupled (e.g., to bystanders other than the user) to provide a blinking color (e.g., red) illumination pattern. In some configurations, for example, the blinking illumination pattern may indicate that the eyepiece is recording video. In some designs, the visible light may be out-coupled (e.g., to the user) to provide a pulsating color (e.g., green) illumination pattern. In some designs, for example, the pulsating (e.g. green) illumination pattern may indicate that the user has an unread message (e.g. email, text message) or may be used to provide another form of alert.

(153) In some implementations, at least one illumination sources may emit visible light and be out-coupled from the light-guiding optical element to provide aesthetic enhancements and/or entertainment-driven special visual effects. For example, in some designs, the visible light may be out-coupled to surround the user's visual periphery with a glowing and/or fluctuating color (e.g., blue) aura, for example, while the user is engaged an activity such as in a deep sea diving mixed reality experience, thereby creating a greater sense of immersion.

(154) In some configurations, at least one illumination sources may emit visible and/or invisible (e.g. IR or UV) light and be out-coupled from the light-guiding optical element to the user and/or the user's environment and produce illumination patterns that may serve to provide one or more signals or fiducial points recognizable to external imaging sensors located in the environment (e.g., third party cameras, other head mounted displays, etc.).

(155) Accordingly, one or more eye tracking cameras, depth sensor(s), or other components may additionally be included. Likewise, one or more displays for projecting image content into the eye of the users may also be included. Similarly, any of the features, structures, variations, applications, uses, benefits, etc. described above may be used in connection with or are applicable to implementations that employ the diffusive optical element or scatter regions to provide illumination.

(156) In some embodiments, the image projector of the head mounted display and the illumination source share the same in-coupling optical element and light-guiding component.

(157) Outer and Inner Covers or Shields

(158) As described above, in some implementations, the light-guiding component for providing illumination (e.g., to the eye for eye tracking) supplements the eyepiece comprising one or more waveguides for directing light from one or more displays to the eye to provide image content thereto. FIGS. **13A-13B** show an example of such a configuration wherein the light-guiding component comprises a cover or shield.

(159) In particular, FIG. **13A** illustrate the light-guiding component comprising an outer cover or shield **1200** in front of the light guiding element **1202**. In this particular example, the outer cover **1200** is curved. FIG. **13A** also shows a waveguide **1202** having an in-coupling grating (ICG), a light distribution element (OPE) **1210** and out-coupling optical element (EPE) **1212** configured to receive light from a display (not shown) and direct light from the display to the user's eye to present image content thereto. FIG. **13A** also shows the outer cover **1200** in front of the waveguide **1202**. An in-coupling element **1208** is positioned to couple light from an illumination source into the light-guiding component **1200** comprising the outer cover.

(160) The system further comprises an illumination source **1204** configured to couple light into an in-coupling optical element **1208** such that light is guided within the light-guiding component **1200**. FIG. **13B** shows the light-guiding component/cover **1200** without the eyepiece comprising the waveguide **1202** rearward of the light-guiding component/cover **1200**. FIG. **13B** also shows light ejected out from the light-guiding component/cover **1200** to a user's eye (not shown) with diffusive optical elements **1222A**, **1222B**, **1222C**, **1222D**, **1222E** disposed in or on the outer cover **1200**. These diffusive optical elements **1222A**, **1222B**, **1222C**, **1222D**, **1222E** have relatively small lateral extent, for example, compared to the light-guiding component/cover **1200**. Consequently,

light ejected from the light-guiding component/cover **1200** by the diffusive optical elements **1222A**, **1222B**, **1222C**, **1222D**, **1222E** can be considered to be emanating effectively from a plurality of respective point sources. (161) In various implementations the light-guiding component/cover **1200** comprises a protective cover for the eyepiece **1202**. The light-guiding component/cover **1200** may comprises, for example, plastic, such as polycarbonate and/or acrylic, and glass or any combination thereof. As illustrated, the cover **1200** is forward the eyepiece **1202**, which is forward the user's eye. The cover **1200**, however, is rearward of the environment in front of the user. The cover **1200** may be supported by a frame, not shown. The cover **1200** may protect the eyepiece **1202** from the environment forward the user. In the example illustrated in FIGS. **13A-13B**, the cover **1200** is curved more in one direction than in the other (e.g., orthogonal) direction. The cover **1200** has a cylindrical shape. In particular, the cover **1200** is curved on one direction (vertical) and not the other orthogonal direction (horizontal). The cover **1200** has a shape of a portion of a right circular cylinder. Although the cover is shown as curved, the cover need not be curved or need not have the particular curved shape shown.

(162) In some embodiments, the outer cover may be disposed over the eyepiece to act as a shield. In some embodiments, a head mounted display may include a visor, wherein the visor comprises the outer cover that comprises the light-guiding component. Accordingly, in various implementations, an outer cover and/or a light visor is configured to guide the illumination from the illumination to the user's eye or to the environment (e.g., using total internal reflection.)

(163) As described above, the light-guiding component for providing illumination (e.g., to the eye for eye tracking) can supplement the eyepiece comprising one or more waveguides for directing light from one or more displays to the eye to provide image content thereto. In particular, the light-guiding component can comprise a cover or shield and this cover or shield may be disposed rearward of the eyepiece.

(164) The FIGS. **14A-14B**, in particular, show a light-guiding component comprising an inner cover or shield **1300** rearward of the eyepiece (e.g., light guiding element configured to display image content) **1302**. In this particular example, the inner cover **1300** is not curved but is planar. FIG. **14A** also shows a waveguide **1302** having an in-coupling grating (ICG), a light distribution element (OPE) **1310** and out-coupling optical element (EPE) **1312** configured to receive light from a display (not shown) and direct light from the display to the user's eye to present image content thereto. FIG. **14A** also shows the inner cover **1300** rearward of the waveguide **1302**.

(165) The system further comprises an illumination source **1304** configured to couple light into an in-coupling optical element (e.g., prism) **1308** such that light is guided within the light-guiding component **1300**. FIG. **14B** shows the light-guiding component/cover **1300** without the eyepiece comprising the waveguide **1202** forward of the light-guiding component/cover **1300**. FIG. **14B** also shows light ejected out from the light-guiding component/cover **1300** to a user's eye (not shown) with diffusive optical elements **1322A**, **1322B**, **1322C**, **1322D**, **1322E** disposed in or on the inner cover **1300**. These diffusive optical elements **1322A**, **1322B**, **1322C**, **1322D**, **1322E** have relatively small lateral extent, for example, compared to the light-guiding component/cover **1300**. Consequently, light ejected from the light-guiding component/cover **1300** by the diffusive optical elements **1322A**, **1322B**, **1322C**, **1322D**, **1322E** can be consider to be emanating effectively from a plurality of respective point sources.

(166) In various implementations the light-guiding component/cover **1300** comprises a protective cover for the eyepiece **1302**. The light-guiding component/cover **1300** may comprises for example plastic, such as polycarbonate and/or acrylic, and glass or any combination thereof. As illustrated, the cover **1300** is rearward the eyepiece **1202**, both of which are forward the user's eye and rearward the environment in front of the user. The cover **1200** may be supported by a frame, not shown. The cover **1200** may protect the rearward side of the eyepiece **1202**. Although the cover **1200** is shown as flat or planar, the cover need not be flat but may be curved and may be curved in one direction more than the orthogonal direction (e.g., cylindrical).

(167) In some implementations, a display includes one or more covers. In some designs, the cover may be cosmetic, tinted, impact resistant or combinations thereof. For example, the cover(s) can obscure the system components behind the covers for a cleaner (e.g., less cluttered) look to the display. In some configurations, the display may also include a front band and a sensor cover to protect the system components while forming a contiguous front of the display around the external lenses. The covers may have a 50% to 70% transparency (which may in some cases be provided by tint) that may in some instances potentially improve or optimize an AR experience involving light from both virtual objects and real-world physical objects.

(168) In some designs, the display may further include on or more (e.g., a pair) of inner covers to protect the system components and/or form a protective inner surface for the display adjacent the user's face. In some implementations, the display may include one or more optional prescription lenses to accommodate users requiring corrective lenses. In some designs, a mounting structure may house a cover, disposed either on the environment side or the user's side of the viewing optics assembly.

(169) In some implementations, the cover or cover lens may comprise anti-scratch material or other protective

covering to prevent contact of the display such as with oils from fingertips or dust and debris from the external environment. In some configurations, the cover or cover lens may include light modifiers, such as polarized lens to reflect or absorb certain light. In some designs, displays comprise such a protective cover or cover lens in addition to the plurality of waveguides.

(170) Any of these covers or lenses may comprise the light-guiding component and be configured to guide light from the illumination source (e.g., via total internal reflection).

(171) Variations in design and configuration are possible. For example, out-coupling could be provided by diffractive optical elements such as holograms and may provide for virtual light sources disposed on a separate depth plane than the cover. Similarly, a mask with openings may be employed. Still other arrangements, configurations, and combinations are possible.

(172) Frame

(173) As illustrated in FIGS. **15A-15B**, the light-guiding component may comprise a portion of the frame. Accordingly, the light-guiding component for providing illumination (e.g., to the eye for eye tracking) can supplement the eyepiece comprising one or more waveguides for directing light from one or more displays to the eye to provide image content thereto.

(174) FIGS. **15A-15B**, in particular, show a light-guiding component **1400** comprising a portion of the frame surrounding the eyepiece (e.g., waveguide configured to display image content) **1402**. FIG. **15A** also shows an eyepiece/waveguide **1402** having a light distribution element (OPE) **1410** and out-coupling optical element (EPE) **1412** configured to receive light from a display (not shown) and direct light from the display to the user's eye to present image content thereto.

(175) FIG. **15A** also shows parts of the frame surrounding the eyepiece/waveguide **1402**. One of the portions of the frame comprises the light-guiding component **1400** for conveying light therethrough. FIG. **15A** also shows an illumination source **1404** configured to couple light into an in-coupling optical element (e.g., prism) **1408** such that light is guided within the light-guiding component **1400** included in a portion of the frame.

(176) In some implementations, the portion of the frame comprising the light guiding component **1400** may comprise a material that is transmissive to light output by the illumination source **1404** and may have an index of refraction sufficient to cause such light to be guided therein by total internal reflection. In some alternative implementations, the portion of the frame comprising the light-guiding component **1400** may comprise a hollow cavity having sidewalls from which light from the illumination source **1404** may reflect thereby propagating light within the light-guiding component.

(177) FIG. **15B** also shows light ejected out from the light-guiding component **1400** to a user's eye (not shown) with diffusive optical elements **1422A**, **1422B**, **1422C**, **1422D**, **1422E** disposed in or on the light-coupling component **1300**. These diffusive optical elements **1422A**, **1422B**, **1422C**, **1422D**, **1422E** have relatively small lateral extent, for example, compared to the light-guiding component **1400**. Consequently, light ejected from the light-guiding component **1400** by the diffusive optical elements **1422A**, **1422B**, **1422C**, **1422D**, **1422E** can be considered to be emanating effectively from a plurality of respective point sources.

(178) In some embodiments, the diffusive optical elements **1422A**, **1422B**, **1422C**, **1422D**, **1422E** are disposed on the surface of the frame, which may be solid or hollow. The diffusive optical elements may also be disposed within a hollow frame or the volume of a solid frame.

(179) In some instances, wherein the light-guiding component **1400** comprises a portion on the frame and the out-coupling optical elements are included on this portion of the frame, light may be emitted from a peripheral region in contrast to the light-guiding components discussed above, which are more centrally located with respect to the field-of-view of the user's eye. In this example, multiple light beams are projected to the user's eye from diffusive optical elements. Furthermore, the multiple beams are arranged along a line. Other designs are possible. For example, less beams (e.g., even a single beam) may be used. Additionally, the beams need not be arranged in a line. Likewise, although the portion of the frame comprising the light-guiding component **1400** is generally linear, the shape may be non-linear. Other non-linear light guiding shapes and structures may be used. In some implementations, the frame may comprise a plurality of arms configured to contact and/or secure the frame to the user's head, wherein light may be in-coupled and/or out-coupled from one or more arms of the frame.

(180) Variations in design and configuration are possible. For example, out-coupling could be provided by diffractive optical elements such as holograms and may provide for virtual light sources disposed on a separate depth plane than the frame. Similarly, a mask with openings may be employed. Still other arrangements, configurations, and combinations are possible.

(181) Other Shapes

(182) Multiple patterns and/or geometries of light-guiding components, out-coupling elements, masks and mask opening openings, and diffusive optical elements may be used. FIG. **16** illustrates a circularly shaped light-guiding component. FIG. **16** also illustrates an annular or ring-shaped diffusive optical element pattern. A region

comprising diffusive optical elements or scatter features may be configured to extract light from the light-coupling component. Light ejected may thus be emitted from this annular or ring-shaped region. Other shapes are possible. Additionally, although in this example, the region comprises diffusive optical elements, the region could otherwise comprise one or more diffractive optical elements or holograms or a mask with openings such as described above. Combinations of these types of features are also possible.

(183) Other shapes are possible. For example, although the light-guiding component is circular in shape, the light-guiding component may be elliptical or oval in shape, square, rectangular or other regular or irregular shapes. The light-guiding component may be flat, e.g., planar or may be curved.

(184) In some implementations, out-coupling elements, mask openings and/or diffusive optical elements are peripherally located on the light-guiding component. In some designs, out-coupling elements, mask openings and/or diffusive optical elements are centrally located on the light-guiding component. In some configurations, the shape of the distribution of the out-coupling elements, mask openings and/or diffusive optical elements over light-guiding component is annular or circular or has other shapes such as linear.

(185) In some implementations, the density of the distribution of the out-coupling elements, mask openings and/or diffusive optical elements over light-guiding component is 1 element/mm.^{sup.2}, 5 elements/mm.^{sup.2}, 10 elements/mm.^{sup.2}, 50 elements/mm.^{sup.2}, 100 elements/mm.^{sup.2}, 500 elements/mm.^{sup.2}, 1000 elements/mm.^{sup.2}, 10000 elements/mm.^{sup.2}, 1 element/μm.^{sup.2}, 5 elements/μm.^{sup.2}, 10 elements/μm.^{sup.2}, 50 elements/μm.^{sup.2}, 100 elements/μm.^{sup.2}, 500 elements/μm.^{sup.2}, 1000 elements/μm.^{sup.2} or 10000 elements/μm.^{sup.2}, or any range between any of these values. Other variations are possible.

(186) Stacking of Light-Guiding Components and/or Out-Coupling Optical Elements

(187) In some instances, a stack of a plurality of light guiding components and/or out-coupling elements may be employed.

(188) FIG. 17A, for example, illustrates first and second light-guiding components stacked on top of each other. In this example, the first and second light-guiding components are separated by an out-coupling optical element comprising, e.g., a diffusive optical element or a diffractive optical element, that is configured to couple light guided within the first and second light-guiding components out of the light-guiding components. In some implementations, the out-coupling is bi-directional, with light being ejected forward and rearward of the pair of light guiding components.

(189) FIG. 17B illustrates a light guiding component comprising first and second out-coupling optical elements disposed on either side of the light-guiding component to couple light guided within the light-guiding component out of the light-guiding component. In some examples, the first and second out-coupling optical elements may be configured to provide bidirectional out-coupling such that light is ejected forward and rearward of the light-guiding component and the pair of out-coupling optical elements.

(190) FIG. 17C illustrates first and second light-guiding components on opposite sides of one or more out-coupling optical elements comprising, e.g., a diffusive optical element or diffractive optical element, that is configured to couple light guided within the first and second light-guiding components out of the light-guiding components. In some implementations, the out-coupling is bi-directional, with light being ejected forward and rearward of the pair of light guiding components. As illustrated, the first and second light-guiding components are circularly shaped and the out-coupling optical element is annularly shaped.

(191) Although diffusive optical elements may be used in these example, in other implementations, the out-coupling optical element may comprise diffractive optical elements. Other components such as masks with one or more openings or other features or structures described herein may be used. Also, the shapes and distributions may vary. Other features may also vary.

(192) In some embodiments, directing light from illumination source toward said environment may provide depth sensing. In some embodiments, directing light toward the user and/or to the environment may provide an indication to the user and/or to world. For example, the light may indicate that the wearable is recording video. For example, in some implementations, the visible light may be out-coupled to provide a blinking (e.g., red) illumination pattern to indicate that the eyepiece is recording video. In another example, in some configurations, the visible light may be out-coupled to provide a pulsating (e.g., green) illumination pattern to indicate that the user has an unread message (e.g. email, text message) or provide another message or alert.

(193) In some implementations, directing light toward the user and/or to the environment may be for aesthetic purposes and/or provide special effects. For example, in some designs, the visible light may be out-coupled to surround the user's visual periphery with a glowing and/or fluctuating (e.g., blue) aura while the user is engaged in a certain activity such as a deep sea diving mixed reality experience, thereby creating a greater sense of immersion.

(194) In some configurations, at least one illumination source may emit visible and/or invisible (e.g. IR or UV) light and be out-coupled from the light-guiding optical element to the user and/or the user's environment and

produce illumination patterns that may serve to provide one or more fiducial points or signals recognizable to external imaging sensors located in the environment (e.g., third party cameras, head mounted displays, etc.). (195) In some embodiments, the light is out-coupled using a virtual light source architecture. In some embodiments, the light is out-coupled using a mask architecture. In some embodiments, the light is out-coupled using a diffusive optical element architecture.

EXAMPLES

(196) Various examples are provided below. 1. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one diffusive optical element disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one diffusive optical element is configured to diffusively couple light from the at least one illumination source out of the light-guiding component. 2. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one out-coupling optical element disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the light-guiding component and cause light coupled out of the light-guiding component to diverge in a manner consistent with light originating from a location a distance forward said light-guiding component. 3. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one mask comprising at least one mask opening disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one mask and at least one mask opening are configured to couple light from the at least one illumination source out of the light-guiding component through the at least one mask opening. 4. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, said at least one in-coupling optical element comprising a prism, wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component. 5. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component, and wherein the image projector is configured to in-couple the image and the at least one illumination source is configured to in-couple light into the at least one illumination in-coupling optical element. 6. A head-mounted

display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and an eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user, wherein said eyepiece comprises a waveguide and at least one image in-coupling optical element configured to in-couple light from the image projector into the waveguide so as to guide light from the image projector therein.

7. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user, said light-guiding component being curved; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component.

8. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user, said light-guiding component comprising a portion of said frame; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, wherein said light-guiding component is configured such that light from the illumination source guided within the light-guiding component is coupled out of the light-guiding component.

9. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; and at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein, and at least one out-coupling optical element disposed on the light-guiding component so as to be positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the light-guiding component, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one out-coupling optical element.

10. The system of any of the above Examples, wherein said image projector comprises a visible light source and modulator.

11. The system of any of the above Examples, wherein the light modulator comprises a spatial light modulator.

12. The system of any of the above Examples, wherein the at least one illumination source comprises an infrared (IR) light source configured to emit IR light.

13. The system of any of the above Examples, wherein the at least one illumination source comprises a visible light source configured to emit visible light.

14. The system of any of the Examples above, wherein said light-guiding component comprises a material that is transparent to visible light having a refractive index sufficient to guide light from said at least one illumination source in said light-guiding component by total internal reflection.

15. The system of any of the Examples above, wherein at least a portion of said light-guiding component is transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user.

16. The system of any of the Examples above, wherein the at least one illumination in-coupling optical element comprises at least one prism.

17. The system of any of the Examples above, further comprising at least one image in-coupling optical element configured to in-couple light from the image projector into the light-guiding component so as to guide light from the image projector therein.

18. The system of any of the Examples above, wherein the image projector is configured to in-couple the image and the at least one illumination source is

configured to in-couple light into the at least one illumination in-coupling optical element. 19. The system of any of the Examples above, further comprising an eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user. 20. The system of any of the Examples above, wherein said eyepiece comprises a waveguide and at least one image in-coupling optical element configured to in-couple light from the image projector into the waveguide so as to guide light from the image projector therein. 21. The system of any of the Examples above, wherein said light-guiding component is disposed on an inside portion of said eyepiece, wherein the inside portion is between the user's eye and the eyepiece. 22. The system of any of the Examples above, wherein said light-guiding component is disposed on an outside portion of said eyepiece, wherein the outside portion is between the environment and the eyepiece. 23. The system of any of the Examples above, wherein said light-guiding component is curved. 24. The system of any of the Examples above, wherein said light-guiding component has the shape of a portion of a cylinder. 25. The system of any of the Examples above, wherein said light-guiding component comprises a shield or visor attached to said frame. 26. The system of any of the Examples above, wherein said shield or visor is disposed on an inside portion of said display system. 27. The system of any of the Examples above, wherein said shield or visor is disposed on an outside portion of said display system. 28. The system of any of the Examples above, wherein said light-guiding component comprises a portion of said frame. 29. The system of any of the Examples above, wherein the at least one diffusive optical element is configured to couple light from the at least one illumination source out of the light-guiding component toward said user's eye. 30. The system of any of the Examples above, wherein the at least one diffusive optical element is configured to couple light from the at least one illumination source out of the light-guiding component toward the environment forward the user to the user's eye. 31. The system of any of the Examples above, wherein the at least one mask blocks light guided within said light-guiding component from exiting said light-guiding component. 32. The system of any of the Examples above, wherein said at least one mask reflects light from said at least one illumination source back into said light-guiding components. 33. The system of any of the Examples above, wherein said at least one mask is dichroic reflecting certain wavelengths emitted by said at least one illumination source and transmitting other wavelengths not emitted by said at least one illumination source. 34. The system of any of the Examples above, wherein said at least one mask is dichroic reflecting certain infrared wavelengths emitted by said at least one illumination source and transmitting other visible wavelengths not emitted by said at least one illumination source. 35. The system of any of the Examples above, wherein said at least one mask is configured to absorb light emitted by said illumination source. 36. The system of any of the Examples above, wherein said at least one mask opening is about 10 μm in diameter. 37. The system of any of the Examples above, wherein the at least one diffusive optical element extends across an area that is less than 5% the area of the at least one light-guiding component. 38. The system of any of the Examples above, wherein the at least one mask opening extends across an area that is less than 5% the area of the at least one light-guiding component. 39. The system of any of the Examples above, further comprising a light redirecting element configured to direct light received from said at least one illumination in-coupling optical element to within said light-guiding component such that said light-guiding component redirects said light to said at least one diffusive optical element. 40. The system of any of the Examples above, further comprising a light redirecting element configured to direct light received from said at least one illumination in-coupling optical element to within said light-guiding component such that said light-guiding component redirects said light to said at least one mask opening. 41. The system of any of the Examples above, further comprising a light redirecting element configured to direct light received from said at least one illumination in-coupling optical element to within said light-guiding component such that said light-guiding component redirects said light to said at least one out-coupling element. 42. The system of any of the Examples above, wherein said light redirecting element comprises an orthogonal pupil expander. 43. The system of any of the Examples above, further comprising at least one camera configured to image the user's eye using light from said at least one illumination source that is reflected from said eye. 44. The system of any of the Examples above, wherein said at least one camera comprises an eye tracking camera that is configured to communicate with electronics configured to track movement of said eye based on images from said at least one camera. 45. The system of any of the Examples above, wherein said light-guiding component has a circular shape. 46. The system of any of the Examples above, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one diffusive optical element. 47. The system of any of the Examples above, wherein said at least one light-guiding component comprises first and second light-guiding components disposed on opposite sides of a diffusive film. 48. The system of any of the Examples above, wherein said at least one diffusive optical element comprises a pair of diffusive optical elements disposed on opposite sides of said light-guiding component. 49. The system of any of

the Examples above, wherein said at least one diffusive optical element comprises first and second diffusive films disposed on opposite sides of said light-guiding component. 50. The system of any of the Examples above, wherein said at least one diffusive optical element comprises first and second diffusive optical elements configured to direct light into distributions oriented in different first and second directions. 51. The system of any of the Examples above, wherein said at least one diffusive optical element comprises first and second diffusive optical elements configured to selectively direct light having first and second wavelengths, respectively, into distributions oriented in different first and second directions, and said at least one illumination source comprising first and second light sources that selectively emits said first and second wavelengths respectively. 52. The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources. 53. The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one diffusive optical element directs light from different illumination sources into respective distributions oriented in different directions. 54. The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one diffusive optical element directs light from different illumination sources as if originating from different respective locations forward said at least one light-guiding component. 55. The system of any of the Examples above, wherein said at least one illumination source comprises a laser, LED, or vertical cavity surface emitting laser (VCSEL). 56. The system of any of the Examples above, wherein said at least one illumination source further comprises at least one filter. 57. The system of any of the Examples above, wherein said at least one diffusive optical element is refractive, reflective, diffractive, or any combination thereof. 58. The system of any of the Examples above, wherein said at least one diffusive optical element comprises one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles, one or more irregular surfaces, one or more surface relieve structures, PTFE, Teflon, ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof. 59. The system of any of the Examples above, wherein said at least one diffusive optical element is wavelength selective so as to substantially selectively diffuse one or more wavelengths of light emitted from the at least one illumination source and not others. 60. The system of any of the Examples above, wherein the system comprises a plurality of diffusive optical elements and at least one illumination source emits a plurality of wavelength bands of light, and wherein different of the diffusive optical elements selectively diffuse respective ones of the plurality of wavelength bands from the at least one illumination source. 61. The system of any of the Examples above, wherein said at least one diffusive optical element does not re-direct visible light from said environment. 62. The system of any of the Examples above, wherein said at least one diffusive optical element is configured to direct light from said illumination source toward said environment. 63. The system of any of the Examples above, wherein said at least one illumination source comprises an infrared source configured to output infrared light and said at least one diffusive optical element is configured to direct infrared light from said at least one illumination source toward said environment to provide depth sensing. 64. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one diffusive optical element is configured to direct visible light from said at least one illumination source toward said environment to provide indicia to a non-user. 65. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one diffusive optical element is configured to direct visible light from said at least one illumination source toward said eye to provide indicia to the user. 66. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one diffusive optical element is configured to direct visible light from said at least one illumination source toward a periphery of an eye. 67. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source, or both configured to output light and said at least one diffusive optical element is configured to direct the light from said at least one illumination source toward said environment to provide a signal or fiducial to an external sensor or external imaging sensor. 68. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source or both configured to output light and said at least one diffusive optical element is configured to direct the light from said at least one illumination source toward said user to provide a signal or fiducial to an external sensor or external imaging sensor. 69. The system of any of the Examples above, wherein the at least one out-coupling optical element extends across an area that is less than 5% the area of the at least one light-guiding component. 70. The system of any of the Examples above, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one out-coupling optical element. 71. The system of any of the Examples above, wherein said at least one light-guiding component comprises first and second light-guiding components disposed on opposite sides of an out-coupling optical film. 72. The system of any of the Examples above, wherein said at least one out-coupling

optical element comprises a pair of out-coupling optical element disposed on opposite sides of said light-guiding component. 73. The system of any of the Examples above, wherein said at least one out-coupling optical element comprises first and second out-coupling optical films disposed on opposite sides of said light-guiding component. 74. The system of any of the Examples above, wherein said at least one out-coupling optical element comprises first and second out-coupling optical elements configured to direct light into distributions oriented in different first and second directions. 75. The system of any of the Examples above, wherein said at least one out-coupling optical element comprises first and second out-coupling optical elements configured to selectively direct light having first and second wavelengths, respectively, into distributions oriented in different first and second directions, and said at least one illumination source comprising first and second light sources that selectively emits said first and second wavelengths respectively. 76. The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources. 77. The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one out-coupling optical element directs light from different illumination sources into respective distributions oriented in different directions. 78. The system of any of the Examples above, wherein said at least one illumination source comprises a plurality of illuminations sources and said at least one out-coupling optical element directs light from different illumination sources as if originating from different respective locations forward said at least one light-guiding component. 79. The system of any of the Examples above, wherein said at least one illumination source comprises a laser, LED, or vertical cavity surface emitting laser (VCSEL). 80. The system of any of the Examples above, wherein said at least one illumination source further comprises at least one filter. 81. The system of any of the Examples above, wherein said at least one out-coupling optical element is refractive, reflective, diffractive, or any combination thereof. 82. The system of any of the Examples above, wherein said at least one out-coupling optical element comprises one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles, one or more irregular surfaces, one or more surface relieve structures, PTFE, Teflon, ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof. 83. The system of any of the Examples above, wherein said at least one out-coupling optical element is wavelength selective so as to substantially only interact with a wavelength band of light emitted from the at least one illumination source. 84. The system of any of the Examples above, wherein the system comprises a plurality of out-coupling optical elements and at least one illumination source emits a plurality of wavelength bands of light, and wherein each out-coupling optical element is wavelength selective so as to substantially only interact with different wavelength bands of light emitted from the at least one illumination source. 85. The system of any of the Examples above, wherein said at least one out-coupling optical element does not re-direct visible light from said environment. 86. The system of any of the Examples above, wherein said at least one out-coupling optical element is configured to direct light from said illumination source toward said environment. 87. The system of any of the Examples above, wherein said at least one illumination source comprises an infrared source configured to output infrared light and said at least one out-coupling optical element is configured to direct infrared light from said at least one illumination source toward said environment to provide depth sensing. 88. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one out-coupling optical element is configured to direct visible light from said at least one illumination source toward said environment to provide indicia to a non-user. 89. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one out-coupling optical element is configured to direct visible light from said at least one illumination source toward said eye to provide indicia to the user. 90. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source configured to output visible light and said at least one out-coupling optical element is configured to direct visible light from said at least one illumination source toward a periphery of an eye. 91. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source, or both configured to output light and said at least one out-coupling optical element is configured to direct the light from said at least one illumination source toward said environment to provide a signal or a fiducial to an external sensor or external imaging sensor. 92. The system of any of the Examples above, wherein said at least one illumination source comprises a visible source, an infrared source, or both configured to output light and said at least one out-coupling optical element is configured to direct the light from said at least one illumination source toward said user to provide a signal or a fiducial to a sensor or external imaging sensor. 93. The system of any of the Examples above, wherein the image projector and the illumination source share the same in-coupling optical element and light-guiding component. 94. The system of any of the Examples above, wherein said at least one out-coupling optical element comprises at least one diffusive optical element or at least one diffusive film or any combination thereof. 95. The system of any of the Examples above, wherein said at least one out-coupling optical

element comprises at least one diffractive optical element or at least one holographical optical element or any combination thereof.

Additional Considerations

(197) In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than restrictive sense.

(198) Indeed, it will be appreciated that the systems and methods of the disclosure each have several innovative aspects, no single one of which is solely responsible or required for the desirable attributes disclosed herein. The various features and processes described above may be used independently of one another, or may be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this disclosure.

(199) Certain features that are described in this specification in the context of separate embodiments also may be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment also may be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially exemplified as such, one or more features from an exemplified combination may in some cases be excised from the combination, and the exemplified combination may be directed to a subcombination or variation of a subcombination. No single feature or group of features is necessary or indispensable to each and every embodiment.

(200) It will be appreciated that conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. In addition, the articles “a,” “an,” and “the” as used in this application and the appended examples are to be construed to mean “one or more” or “at least one” unless specified otherwise. Similarly, while operations may be depicted in the drawings in a particular order, it is to be recognized that such operations need not be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Further, the drawings may schematically depict one more example processes in the form of a flowchart. However, other operations that are not depicted may be incorporated in the example methods and processes that are schematically illustrated. For example, one or more additional operations may be performed before, after, simultaneously, or between any of the illustrated operations. Additionally, the operations may be rearranged or reordered in other embodiments. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products. Additionally, other embodiments are within the scope of the following examples. In some cases, the actions recited in the examples may be performed in a different order and still achieve desirable results.

(201) Accordingly, the disclosure are not intended to be limited to the embodiments shown herein, but are to be accorded the widest scope consistent with this disclosure, the principles and the novel features disclosed herein.

Claims

1. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component having a circular disc shape and being configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source

therein; and at least one out-coupling optical element having an annular shape and being disposed around a periphery of the light-guiding component to encircle a central portion of the light-guiding component, and being positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the periphery of the light-guiding component.

2. The head-mounted display system of claim 1, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one out-coupling optical element.

3. The head-mounted display system of claim 1, wherein said at least one out-coupling optical element comprises at least one diffusive optical element that is configured to diffusively couple light from the at least one illumination source out of the periphery of the light-guiding component.

4. The head-mounted display system of claim 3, wherein said light-guiding component comprises two light-guiding components disposed on opposite sides of said at least one diffusive optical element.

5. The head-mounted display system of claim 1, wherein said light-guiding component comprises first and second light-guiding components disposed on opposite sides of a diffusive film.

6. The head-mounted display system of claim 1, wherein said at least one out-coupling optical element comprises first and second diffusive optical elements configured to direct light into distributions oriented in different first and second directions.

7. The head-mounted display system of claim 1, wherein said at least one out-coupling optical element comprises first and second diffusive optical elements configured to selectively direct light having first and second wavelengths, respectively, into distributions oriented in different first and second directions, and said at least one illumination source comprising first and second light sources that selectively emits said first and second wavelengths respectively.

8. The head-mounted display system of claim 1, wherein said at least one out-coupling optical element is refractive, reflective, diffractive, or any combination thereof.

9. The head-mounted display system of claim 1, wherein the at least one illumination source comprises an infrared (IR) light source configured to emit IR light.

10. The head-mounted display system of claim 1, wherein said light-guiding component comprises a material that is transparent to visible light and has a refractive index sufficient to guide light from said at least one illumination source in said light-guiding component by total internal reflection.

11. The head-mounted display system of claim 1, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the light-guiding component toward said user's eye.

12. The head-mounted display system of claim 1, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the light-guiding component toward the environment forward the user.

13. The head-mounted display system of claim 1, wherein said at least one out-coupling optical element comprises one or more diffuser sheets, one or more light shaping diffusers, one or more diffuser films, one or more etchings, one or more transmissive optical elements, one or more particles, one or more irregular surfaces, one or more surface relieve structures, PTFE, Teflon, ground glass, opal glass, greyed glass, one or more white surfaces, colored gel, one or more holograms or any combination thereof.

14. The head-mounted display system of claim 1, wherein said at least one out-coupling optical element is wavelength selective so as to substantially selectively diffuse one or more wavelengths of light emitted from the at least one illumination source and not others.

15. The head-mounted display system of claim 1, wherein said at least one diffusive optical element does not re-direct visible light from said environment.

16. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component being circularly shaped and configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one out-coupling optical element disposed around a periphery of the light-guiding component and positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the periphery of the light-guiding component, and wherein said at least one out-coupling optical element comprises a pair of diffusive optical elements disposed on opposite sides of said light-guiding component.

17. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component being circularly shaped and configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one out-coupling optical element disposed around a periphery of the light-guiding component and positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the periphery of the light-guiding component, and wherein said at least one out-coupling optical element comprises first and second diffusive films disposed on opposite sides of said light-guiding component.

18. A head-mounted display system configured to project light to an eye of a user wearing the head-mounted display system to display content in a vision field of said user, said head-mounted display system comprising: a frame configured to be supported on a head of the user; an image projector configured to project an image; at least one illumination source; a light-guiding component, said light-guiding component being circularly shaped and configured so as to be positioned forward one of the user's eyes when the frame is worn by the user; at least one illumination in-coupling optical element configured to in-couple light from the at least one illumination source into the light-guiding component so as to guide light from the at least one illumination source therein; and at least one out-coupling optical element disposed around a periphery of the light-guiding component and positioned forward one of the user's eyes when the frame is worn by the user, wherein the at least one out-coupling optical element is configured to couple light from the at least one illumination source out of the periphery of the light-guiding component, and wherein at least a portion of said light-guiding component is transparent and disposed at a location forward the user's eye when the user wears said frame such that said transparent portion transmits light from the environment forward the user to the user's eye to provide a view of the environment forward the user.
