

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent

12406561

Kind Code

B1

Date of Patent

September 02, 2025

Inventor(s)

Subramanian; Kartik et al.

---

### Remote trigger for security system

---

#### Abstract

Techniques for automatically securing receptacles of a retailer via an electronic lock include receiving a user request to reserve a receptacle, selecting a suitable receptacle based on one or more conditions, some of which may be specified by the user, and transmitting an electronic locking signal to secure, and thereby reserve, the selected receptacle. An association between the reserved receptacle and the user is stored, and the user is electronically notified. Subsequently, an electronic signal indicative of the identification of the user (or of the user's agent) is locally received. Upon determination that the user is expected and associated with the reserved receptacle, the techniques include causing an electronic unlocking signal to be transmitted to the electronic lock, thereby unlocking the receptacle. Further subsequently, upon receiving an electronic locking instruction, the receptacle may automatically be secured via its corresponding electronic lock, and a retailer agent may be electronically notified.

---

**Inventors:** Subramanian; Kartik (Chicago, IL), Schweinfurth; Andrew David (Chicago, IL), Kim; Raymond (Chicago, IL), Anderson; Bryan (Chicago, IL)

**Applicant:** WALGREEN CO. (Deerfield, IL)

**Family ID:** 69951466

**Assignee:** WALGREEN CO. (Deerfield, IL)

**Appl. No.:** 18/651382

**Filed:** April 30, 2024

#### Related U.S. Application Data

continuation parent-doc US 17982194 20221107 US 12008875 child-doc US 18651382

continuation parent-doc US 17148312 20210113 US 11495104 20221108 child-doc US 17982194

continuation parent-doc US 16809200 20200304 US 10964185 20210330 child-doc US 17148312

continuation parent-doc US 16379506 20190409 US 10607465 20200331 child-doc US 16809200

continuation parent-doc US 16184698 20181108 US 10593179 20200317 child-doc US 16268268

continuation parent-doc US 15689469 20170829 US 10192417 20190129 child-doc US 16184698  
continuation parent-doc US 15194725 20160628 US 9779603 20171003 child-doc US 15689469  
continuation-in-part parent-doc US 16268268 20190205 US 10438469 20191008 child-doc US  
16379506

---

**Publication Classification**

**Int. Cl.:** **G08B13/14** (20060101); **G07C9/00** (20200101); **G08B13/24** (20060101); **H04L67/306**  
(20220101)

**U.S. Cl.:**

**CPC** **G08B13/2454** (20130101); **G07C9/00309** (20130101); **G07C9/00571** (20130101);  
**H04L67/306** (20130101);

**Field of Classification Search**

**CPC:** G08B (13/2454); G07C (9/00309); G07C (9/00571); H04L (67/306)

**USPC:** 340/572.1

---

**References Cited**

**U.S. PATENT DOCUMENTS**

| Patent No.   | Issued Date | Patentee Name       | U.S. Cl. | CPC          |
|--------------|-------------|---------------------|----------|--------------|
| 6885281      | 12/2004     | McGunn et al.       | N/A      | N/A          |
| 6999825      | 12/2005     | Inomata             | N/A      | N/A          |
| 7275864      | 12/2006     | Thompson            | N/A      | N/A          |
| 7552467      | 12/2008     | Lindsay             | N/A      | N/A          |
| 8943187      | 12/2014     | Saylor              | N/A      | N/A          |
| 9536236      | 12/2016     | Hay                 | N/A      | N/A          |
| 9706835      | 12/2016     | Zaniker             | N/A      | G06Q 20/352  |
| 9710987      | 12/2016     | Scoggins et al.     | N/A      | N/A          |
| 9779603      | 12/2016     | Subramanian et al.  | N/A      | N/A          |
| 10192417     | 12/2018     | Subramanian et al.  | N/A      | N/A          |
| 10474797     | 12/2018     | Lowenthal           | N/A      | G07F 9/001   |
| 11195355     | 12/2020     | Goetz et al.        | N/A      | N/A          |
| 2002/0080030 | 12/2001     | Inomata             | 340/542  | G07F 17/0014 |
| 2003/0040980 | 12/2002     | Nakajima et al.     | N/A      | N/A          |
| 2004/0246130 | 12/2003     | Lambright et al.    | N/A      | N/A          |
| 2006/0250235 | 12/2005     | Astrin              | N/A      | N/A          |
| 2007/0176739 | 12/2006     | Raheman             | N/A      | N/A          |
| 2012/0038550 | 12/2011     | Lemmey et al.       | N/A      | N/A          |
| 2012/0062362 | 12/2011     | Rudduck             | 340/5.64 | G07F 17/13   |
| 2013/0144428 | 12/2012     | Irwin               | 700/218  | G07F 17/10   |
| 2014/0085089 | 12/2013     | Rasband et al.      | N/A      | N/A          |
| 2015/0179035 | 12/2014     | Christianson et al. | N/A      | N/A          |
| 2015/0371187 | 12/2014     | Irwin et al.        | N/A      | N/A          |
| 2016/0005284 | 12/2015     | Batra et al.        | N/A      | N/A          |

*Primary Examiner:* Nguyen; Tai T

*Attorney, Agent or Firm:* MARSHALL, GERSTEIN & BORUN LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/982,194 filed Nov. 7, 2022 (which issued as U.S. Pat. No. 12,008,875 on Jun. 11, 2024) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation of U.S. application Ser. No. 17/148,312 filed Jan. 13, 2021 (which issued as U.S. Pat. No. 11,495,104 on Nov. 8, 2022) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation of U.S. application Ser. No. 16/809,200 filed Mar. 4, 2020 (which issued as U.S. Pat. No. 10,964,185 on Mar. 30, 2021) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation of U.S. application Ser. No. 16/379,506, filed Apr. 9, 2019 (which issued as U.S. Pat. No. 10,607,465 on Mar. 31, 2020) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation-in-part of U.S. application Ser. No. 16/268,268, filed Feb. 5, 2019 (which issued as U.S. Pat. No. 10,438,469 on Oct. 8, 2019) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation of U.S. application Ser. No. 16/184,698, filed Nov. 8, 2018 (which issued as U.S. Pat. No. 10,593,179 on Mar. 17, 2020) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation of U.S. application Ser. No. 15/689,469, filed Aug. 29, 2017 (which issued as U.S. Pat. No. 10,192,417 on Jan. 29, 2019) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” which is a continuation of U.S. application Ser. No. 15/194,725, filed Jun. 28, 2016 (which issued as U.S. Pat. No. 9,779,603 on Oct. 3, 2017) and entitled “REMOTE TRIGGER FOR SECURITY SYSTEM,” the entire disclosures of which are incorporated herein by reference.

## **TECHNICAL FIELD**

(1) This application generally relates to mitigating or preventing retail theft. In particular, this application relates to automatically and/or triggering the remote locking and unlocking of receptacles for customer access.

## **BACKGROUND**

(2) Presently, in certain retail locations, specific products are secured to help deter or prevent theft. Items may be stored in locked receptacles, or items may be individually secured to a receptacle, such as a container, bin, shelf, rack, or other object. For example, battery-operated shaving razors and higher-end cosmetics may be housed within locked receptacles. If a customer would like to examine and/or purchase an item that is secured at such a receptacle, the customer must find a store manager or associate to physically unlock the item so that the customer is able to physically examine the product. If the customer desires to purchase the product, he or she takes it up to the register to complete the transaction. Irrespective of whether or not the customer purchases the product, the store manager or associate must physically re-secure the receptacle or the other items at the receptacle.

(3) Portable electronic devices such as smart phones and tablet devices are becoming more ubiquitous as underlying technology and device capability improves. These devices incorporate numerous components that support various device functions and applications. For example, current smart phones include components that enable network connections as well as location modules capable of detecting device location.

## **SUMMARY**

- (4) In an embodiment, a method for mitigating retail theft includes determining an identity of a customer based on a wireless transmission delivered directly between a personal electronic device (PED) of the customer and a transceiver at or corresponding to a receptacle at which an item is secured via an electronic lock. For example, the customer's PED may automatically discover a beacon signal being transmitted by a transceiver corresponding to the receptacle and/or to the secured item, and the customer's PED may automatically establish a wireless connection with the transceiver. Alternatively, the customer's PED may alert the customer to the discovered beacon, and the customer may manually instruct the PED to request the remote unlocking of the electronic lock, e.g., via the establishment of a wireless connection with the transceiver. The customer's identity may be determined based on information included in the header and/or the payload of the wireless transmission, for example.
- (5) Based on the determined customer identity, a risk profile of the customer may be accessed, and a risk score corresponding to the customer accessing the secured item may be determined based on the risk profile (and, optionally, based on a profile of the item secured at the receptacle). The method may include determining whether or not the risk score is indicative of an acceptable risk. If the risk is determined to be acceptable, the method may include automatically sending an electronic signal to trigger the remote unlocking of the electronic lock, thereby remotely causing the item to be unsecured for access by the customer. If the risk is determined to be unacceptable, the method may include sending an electronic signal to a device operated by an agent of the retailer or enterprise providing the item, and the agent may then manually unsecure the item so that the customer is provided access to the item in the presence of the agent. Alternatively, the agent may choose to send an electronic signal from his or her device to remotely trigger the remote unlocking of the electronic lock, and thereby may remotely cause the item to be unsecured for access by the customer.
- (6) In an embodiment, a system for mitigating retail theft includes a wireless transceiver disposed at or in the proximity of a receptacle, and an electronic lock that secures an item within, at, or to the receptacle. Additionally, the system includes a security system to which the wireless transceiver and electronic lock are communicatively connected. The security system may include one or more data storage entities that store a plurality of risk profiles corresponding to a plurality of customers of an enterprise or retailer that provides the secured item. The security system may generate an electronic signal corresponding to unlocking the electronic lock based on a risk score corresponding to a particular customer accessing the secured item. The identity of the particular customer may be determined automatically based on a wireless transmission delivered between a Personal Electronic Device (PED) of the customer and the wireless transceiver.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying figures, where like reference numerals refer to identical or functionally similar elements throughout the separate views, together with the detailed description below, are incorporated in and form part of the specification, and serve to further illustrate embodiments of concepts that include the claimed embodiments, and explain various principles and advantages of those embodiments.
- (2) FIGS. 1A-1D illustrate various front end and back end devices and components of an example system for mitigating retail theft, and connections therebetween, in accordance with some embodiments.
- (3) FIG. 2 depicts an example layout of an example physical retail store of a retailer or enterprise.
- (4) FIG. 3 depicts an example portion of the system of FIG. 1 in greater detail.
- (5) FIG. 4 illustrates an example signal diagram associated with mitigating the risk of retail theft at

a physical store of a retailer or enterprise which, inter alia, includes an example signal flow for remotely unlocking a secured receptacle.

(6) FIGS. 5A-5B illustrate a flowchart of an example method for mitigating the risk of retail theft at a physical store of a retailer or enterprise.

(7) FIG. 6A illustrates an example arrangement of a plurality of receptacles, each of which is individually securable.

(8) FIG. 6B illustrates another example arrangement of a plurality of receptacles, each of which is individually securable.

(9) FIG. 7 depicts a flow chart of an example method of securing a receptacle.

(10) FIG. 8 depicts a flow chart of an example method of providing access to a secured receptacle.

#### DETAILED DESCRIPTION

(11) The systems, methods, and techniques disclosed herein relate generally to mitigating and/or preventing retail theft. In particular, the systems, methods, and techniques disclosed herein relate to the automatic and/or remote trigger of the unlocking of a secured item, e.g., that is disposed within a locked receptacle, so that a customer may examine and/or access the item. According to certain aspects, the systems and methods may leverage communications and other hardware and software capabilities of electronic devices to provide the automatic and/or remote unlocking of secured items while simultaneously mitigating the risk to a retailer or enterprise.

(12) In an embodiment, a wireless transceiver or equivalent (e.g., a transmitter and receiver pair) may be disposed on, near, proximate to, or at a secured item. The secured item may be provided by an enterprise or a retailer, and may be an item that is offered for sale. The item may be secured via an electronic lock in any number of ways. For example, the item may be housed within a receptacle, typically along with other inventory, and an opening or door of the receptacle may be secured or locked by the electronic lock. In another example, the item may be individually secured to a receptacle (which may be a container, bin, shelf, rack, or some other object) via an electronic lock. The wireless transceiver may be disposed on, at, or proximate to the secured item or receptacle. For example, the wireless transceiver may be fixedly attached to the item, to the receptacle, or to some other object within the vicinity of the secured item.

(13) Generally speaking, the wireless transceiver is configured to wirelessly communicate with any known wireless computing devices, such as smart phones, tablets, laptops, and/or personal electronic devices (“PEDs”). For example, the wireless transceiver may be configured to operate using any number of known common air interface protocols, such as cellular communication protocols (e.g., GSM, CDMA, PCS, LTE, etc.), wireless networking protocols (e.g., Wi-Fi and/or other IEEE 802.11 protocols, etc.), short-range communication protocols (e.g., Bluetooth, infrared communication, Zigbee, etc.), and any other known wireless protocol utilized by personal electronic devices. Further, the wireless transceiver is positioned, disposed, located, and/or configured so that it has the ability to receive wireless signals over any one or more of these common air interface protocols from a personal electronic device when the PED is in the vicinity or proximity of the secured item. A wireless signal that is detected or received by the wireless transceiver may have been automatically generated by a PED, for example, as a result of the PED and the wireless transceiver automatically discovering each other via Bluetooth or some other suitable discovery protocol. Additionally or alternatively, a wireless signal that is detected or received by the wireless transceiver may have been generated manually at a PED, e.g., upon a user's activation of a user control at the PED in response to being notified that the PED is within proximity of the transceiver, and therefore within proximity of the secured item.

(14) A wireless signal that is received at a transceiver corresponding to a secured item may include contents that are indicative of a particular customer of the retailer or enterprise. For example, the wireless signal may include an identification of the PED, an identification of the customer, an identification of an account that the customer has with the retailer or enterprise, and/or an identification of an application that is executing on the PED and that corresponds to the retailer or

enterprise. The particular customer's identity may be utilized to access the customer's risk profile, which may include data corresponding to previous interactions that a particular customer has had with the retailer or enterprise. The data stored in the particular customer's risk profile may in turn be utilized to determine a risk score corresponding to the particular customer accessing the secured item. If the risk score indicates an acceptable risk, the item may be automatically and remotely unsecured (e.g., the electronic lock may be automatically and remotely unlocked) so that the particular customer is able to access and handle the item. On the other hand, if the risk score indicates an unacceptable risk, an agent of the retailer enterprise (e.g., an employee, a store associate, security personnel, etc.) may be notified so that the electronic lock may be manually unlocked for the particular customer in the presence of the agent. As such, the systems, methods, and techniques described herein allow a retailer enterprise to remotely permit access to a customer for high-value items/goods based on a risk profile of the customer, thereby decreasing the risk of theft as well as decreasing the length of time that a qualified customer must wait in order to access secured items, as will be described below.

(15) Turning now to FIG. 1, FIG. 1 illustrates an overall system **100** including various components configured to implement various embodiments for mitigating the risk of retail theft. In particular, the system **100** may include various components configured to trigger the remote unlocking of secured receptacles in a manner that mitigates the risk of retail theft. The system **100** may include a combination of hardware and software components, as well as various data communication channels for communicating data between and among the various hardware and software components. The system **100** may be roughly divided into front-end components **102** and back-end components **104**. At least one of the front-end components **102** may be primarily disposed within a retail network **110** that may include one or more physical retail stores **112** of an enterprise or retailer. The physical retail stores **112** may be located, by way of example rather than limitation, in separate geographic locations from each other, including different areas of the same city, different cities, or even different states. According to the present embodiments, each of the physical retail stores **112** may be a "brick and mortar" store that may include one or more physical buildings or structures, where each of the physical retail stores **112** may accommodate shoppers and customers. A brick and mortar store may be distinguished from a mail-order store of the retailer enterprise, and may be distinguished from an electronic store, on-line store, or website of the retailer or enterprise.

(16) The front-end components **102** may include a number of workstations **128** or computing devices. The workstations **128** may be local computers located in the various physical retail stores **112** throughout the retail network **110** and may be capable of executing various applications. Retail store personnel or agents (not shown) may use the applications executing at the workstations **128** to, for example, access customer information, access images, enter payment information, and/or perform other data management functions associated with the physical retail stores **112**.

(17) Personal electronic devices (PEDs, also referred to herein as mobile devices or client devices) **206-216** (e.g., personal computers, cellular phones, smart phones, tablets, other handheld electronic devices, etc.) may be communicatively connected to the physical retail stores **112** and/or to the back end components **104** through one or more digital networks **130**, as described below. The client devices **206-216** may, but need not be, disposed within the retail network **110**. Further, particular ones of the client devices **206-216** may be operated by customers of the retailer or enterprise, while other ones of the client devices **206-216** may be operated by agents of the retailer or enterprise, e.g., as mobile instances of the workstations **128**.

(18) Those of ordinary skill in the art will recognize that the front-end components **102** may also comprise a plurality of facility servers **126** disposed at the plurality of physical retail stores **112** instead of, or in addition to, a plurality of workstations **128**. In an example configuration, each of the physical retail stores **112** may include one or more facility servers **126** that may facilitate communications between the workstations **128** of the physical retail stores **112** via the digital network(s) **130**, and may store information for a plurality of customers/employees/accounts/etc.

associated with each facility. Of course, a local digital network **184** may also operatively connect each of the workstations **128** to the facility server **126**. Unless otherwise indicated, any discussion of the workstations **128** may also refer to the facility servers **126**, and vice versa. Moreover, environments other than the physical retail stores **112** may employ the workstations **128** and the servers **126**.

(19) The front-end components **102** may communicate with the back-end components **104** via the digital communication network(s) **130**. One or more of the front-end components **102** may be excluded from communicating with the back-end components **104** by configuration or by limiting access due to security concerns. For example, certain ones of the client devices **206-216** may be excluded from direct access or only provided with limited access to the back-end components **104**. In some embodiments, the physical retail stores **112** may communicate with the back-end components via the digital network(s) **130**. In other embodiments, the physical retail stores **112** and the client devices **206-216** may communicate with the back-end components **104** via the same portions of the digital network **130**, but digital access rights, IP masking, and other network configurations may deny access to the client devices **206-216**. In an embodiment, the network **130** may include respective, local wireless communication networks provided in or near the physical retail stores **112** via which client devices **206-216** may communicatively connect to other front-end components **102** and/or to the back-end components **104**. The network **130** may additionally or alternatively support communicative connections between applications **118** executing on the devices **206-216** and the back-end components **104**. For example, the applications **118** may include a web-browser and/or a downloaded retailer client application that may communicate with one or more back-end components **104** via the network **130**.

(20) The digital network(s) **130** may be a proprietary network, a secure public Internet, a virtual private network or some other type of network, such as dedicated access lines, plain ordinary telephone lines, satellite links, wireless links, wired links, combinations of these, etc. Where the digital network **130** comprises the Internet, data communication may take place over the digital network **130** via an Internet communication protocol. In addition to one or more servers **202** that are configured to communicate with client or front-end applications (e.g., as described below), the back-end components **104** may include the central processing system **140**.

(21) Of course, the physical retail stores **112** may be communicatively connected to different back-end components **104** having one or more functions or capabilities that are similar to the central processing system **140**. The central processing system **140** may include one or more computer processors **162** adapted and configured to execute various software applications and components of the system **100**, in addition to other software applications. The central processing system **140** may further include one or more databases **146**. The database(s) **146** may comprise one or more data storage devices that are adapted to store data related to the operation of the system **100**, such as product data and/or customer data. In particular, the database(s) **146** may store information associated with items/products and/or services that are available for sale in various ones of the physical retail stores **112**. For example, the database(s) **146** may store locations of the items/products (e.g., aisle number or other information), pricing information, availability and inventory information, coupon(s) associated with the items/products and/or services, and more detailed information associated with the items/products and/or services (e.g., product descriptions). Additionally or alternatively, the database(s) **146** may store information related to various customers or users associated with the retailer, e.g., user accounts. The central processing system **140** may access data stored in the database(s) **146** when executing various functions and tasks associated with the operation of the system **100**. The central processing system **140** may also maintain and update the data stored in the database(s) **146**. For example, the central processing system **140** may generate coupons for the items/products and/or services, update availability and inventory information (such as if a certain product is purchased from one of the physical retail stores **112**), and/or update passwords, user preferences, and default payment methods for various

users.

(22) To support the mitigation of the risk of retail theft at the physical retail stores **112**, the database(s) **146** may include a customer risk profile data store **148** and an item profile data store **150**. The customer risk profile store **148** may store therein customer-specific data that is or may be indicative of whether or not a particular customer is associated with an increased level of risk to the retailer or enterprise. As such, a particular customer's risk profile that is stored in the risk profile store **148** may include data corresponding to the customer's on-line browsing habits, purchases, returns, and/or other electronic interactions with the enterprise or retailer, and the particular customer's risk profile may include data corresponding to the customer's bricks-and-mortar storefront purchases, returns, and/or other interactions with the enterprise or retailer at retail store locations. For example, a particular customer's risk profile may include data indicative of whether or not the customer has a past history of unpaid items, whether or not the customer has a past history of returning items, whether or not a customer has had a check returned with insufficient funds, etc. The item profile store **150** may store therein item-specific data that is indicative of whether or not a particular item is associated with increased level of risk. For example, a particular item profile stored in the item profile store **150** may include data indicative of the value of the particular item, whether or not the particular item has a history of being shoplifted or stolen, etc.

(23) With regard to the database(s) **146**, it should be appreciated that additional data and additional techniques for maintaining and updating the data are appreciated. It should also be appreciated that although the database(s) **146** is shown as a single entity in FIG. **1A**, the database **146** may be implemented using any one or more databases and any one or more data storage devices. For example, the database(s) **146** may be implemented by a data bank or a data cloud.

(24) Further, although FIG. **1A** depicts the system **100** as including the central processing system **140** in communication with three physical retail stores **112** and various client devices **206-216**, it should be understood that different numbers of processing systems, retail stores, and devices may be utilized. For example, the digital network(s) **130** (or other digital networks, not shown) may interconnect the central processing system **140** to a plurality of included central processing systems **140**, hundreds of physical retail stores **112**, and thousands of client devices **206-216**. According to the disclosed example, this configuration may provide several advantages, such as, for example, enabling near real-time uploads and downloads of information as well as periodic uploads and downloads of information. This may provide for a primary backup of all the information generated in supported functionalities. Alternatively, some of the physical retail stores **112** may store data locally on the facility server **126** and/or the workstations **128**.

(25) FIG. **1A** also depicts one possible embodiment of the central processing system **140**. The central processing system **140** may have a controller **155** operatively connected to the database **146** via a link **156** connected to an input/output (I/O) circuit **166**. It should be noted that, while not shown, additional databases may be linked to the controller **155** in a known manner.

(26) The controller **155** may include a program memory **160**, the processor **162** (which may be called a microcontroller or a microprocessor), a random-access memory (RAM) **164**, and the input/output (I/O) circuit **166**, all of which may be interconnected via an address/data bus **165**. It should be appreciated that although only one microprocessor **162** is shown, the controller **155** may include multiple microprocessors **162**. Similarly, the memory of the controller **155** may include multiple RAMs **164** and multiple program memories **160**. Although the I/O circuit **166** is shown as a single block, it should be appreciated that the I/O circuit **166** may include a number of different types of I/O circuits. The RAM(s) **164** and the program memories **160** may be implemented as semiconductor memories, magnetically readable memories, and/or optically readable memories, for example. A link **135** may operatively connect the controller **155** to the digital network **130** through the I/O circuit **166**.

(27) The program memory **160** may also contain or be configured with machine-readable instructions (i.e., software) **171**, for execution by the processor **162**. The software **171** may perform



the various tasks associated with operation of the retail stores, and may be a single module **171** or a plurality of modules **171A**, **171B**. While the software **171** is depicted in FIG. **1A** as including two modules, **171A** and **171B**, the software **171** may include any number of modules accomplishing tasks related to retail store operation. The central processing system **140** may implement a server application **113** for providing data to a user interface application **111** operating on the workstations **128**.

(28) Further, although FIG. **1A** illustrates the central processing system **140** as including only one controller **155**, it is understood that this is for ease of illustration and is not meant to be limiting. Indeed, in some embodiments of the system **100**, the central processing system **140** may be implemented using multiple controllers **155** that have a unitary or integral logical appearance. For example, the central processing system **140** may be implemented as a bank of servers or on a computing cloud.

(29) As shown in FIG. **1A**, the system **100** for mitigating the risk of retail theft may include one or more security modules **152**. Typically, each facility server **126** may include a respective security module **152**. However, in some implementations, security modules **152** may be disposed at the front end **102** in one or more workstations **128** and/or in one or more client devices **206-216**, e.g., as a portion of a client application provided by the retailer or enterprise or as a separate application **118**. In some implementations, security modules **152** may be disposed at the back end **104** at the central processing system **140**, e.g., as a portion of a server application or as a separate application **113**, and/or as one of the software modules **171**.

(30) Some security modules **152** each may be disposed at a single location or device. Some security modules **152** each may be disposed across multiple locations and/or devices, such as when a particular instance of a security module **152** is instantiated by a first portion downloaded onto a client device **206-216** and a second portion executing at a facility server **126**. Generally speaking, the one or more security modules **152** included in the system **100** may operate in conjunction with the risk profile store **148** (and optionally the item profile store **150**) to mitigate the risk of retail theft at brick-and-mortar retail store locations **112**, as will be described in more detail in later sections. Accordingly, the one or more security modules **152**, the risk profile store **148**, and optionally the item profile store **150** may comprise a security system or security subsystem included in the system **100** for mitigating the risk of retail theft. Of course, other components illustrated in and/or discussed with respect to FIGS. **1A-1D** may also be included in the security system or security subsystem, in some embodiments.

(31) At any rate, for purposes of implementing the system **100**, a user may interact with the server **202** and the retail store systems (e.g., the central processing system **140**, the facility servers **126**, the workstations **128**, etc.) via one of the client devices **206-216** via a mobile device application, a specialized application, or one or more web pages **118**. In an example, FIG. **1B** depicts the server **202** connected via the network **130** to the client devices **206-216** executing or running applications **118** through which a user may initiate and interact with the system **100** (as shown in FIG. **1A**). The client devices or PEDs **206-216** may include, by way of example, a tablet computer **206**, an internet-enabled cell phone **208**, a personal digital assistant (PDA) **210**, a smart phone **212**, a laptop computer **214**, a desktop computer **216**, a portable media player (not shown), and/or others. Further, each application **118** executing on its respective host device **206-216** may be a web browser, a client application provided by the retailer or enterprise, or some other client application via which a communicative connection or session may be established with the server **202**, e.g., to access the electronic retail store of the retailer, and/or to access user account information. In an embodiment, one or more security modules **152** may be incorporated into a client application **118**, or may be implemented as a stand-alone application or module **118** executing on the client device **206-216**.

(32) The client devices **206-216** need not necessarily communicate with the network **130** via a wired connection. In some instances, the client devices **206-216** may communicate with the

network **130** via wireless signals **220** and, in some instances, may communicate with the network **130** via an intervening wireless or wired device **218**, which may be a wireless router, a wireless repeater, a wireless access point, a base transceiver station of a mobile telephony provider, etc. Each of the client devices **206-216** may interact with the server **202** to receive web pages or server data from the server **202** and may display the web pages or server data via its respective client application **118** (described below). For example, the mobile device **212** may display a home screen **222** (i.e., the root or start page at which users enter the client application) of the retailer client application **118** to the user, may receive an input from the user, and may interact with the server **202** depending on the type of user-specified input. It will be appreciated that although only one server **202** is depicted in FIG. **1B**, multiple servers **202** may be provided for the purpose of distributing server load, serving different web pages, implementing different portions of the electronic retail store web interface, servicing different retailer client applications, etc. These multiple servers **202** may include a web server, an entity-specific server (e.g. an Apple® server, etc.), a server that is disposed in a retail or proprietary network, an independent third-party server that is not under the control of the entity, a bank of servers, a cloud computing platform, or others.

(33) Turning now to FIG. **1C**, the server **202**, like the facility server **126**, may include a controller **224**. Similar to the controllers **155** and **170**, the controller **224** may include a program memory **226**, a microcontroller or a microprocessor (MP) **228**, a random-access memory (RAM) **230**, and an input/output (I/O) circuit **234**, all of which may be interconnected via an address/data bus **232**. In some embodiments, the controller **224** may also include, or otherwise be communicatively connected to, a database **239** or other data storage mechanism (e.g., one or more hard disk drives, optical storage drives, solid state storage devices, etc.). The database **239** may include data such as customer web profiles, product data, mobile device application data, web page templates and/or web pages, and other data that may be used to interact with the user through the network **130**. According to embodiments, the database **239** may store the same or similar data as that stored by the database **146** as discussed with respect to FIG. **1A**. For example, the database **239** may include at least a portion of the customer risk profile data store **148** and/or at least a portion of the item profile data store **150**. Further, the database **239** may be implemented on one or more data storage devices.

(34) As discussed with reference to the controllers **155** and **170**, it should be appreciated that although FIG. **1C** depicts only one microprocessor **228**, the controller **224** may include multiple microprocessors **228**. Similarly, the memory of the controller **224** may include multiple RAMs **230** and multiple program memories **226**. Although the FIG. **1C** depicts the I/O circuit **234** as a single block, the I/O circuit **234** may include a number of different types of I/O circuits. The controller **224** may implement the RAM(s) **230** and the program memories **226** as semiconductor memories, magnetically readable memories, and/or optically readable memories, for example.

(35) In addition to being connected through the network **130** to the client devices **206-216**, as depicted in FIG. **1B**, FIG. **1C** illustrates that the server **202** may also be connected through the network **130** to the central processing system **140** and/or one or more facility servers **126**. As described below, the connection of the server **202** to the central processing system **140** may assist in facilitating various functionalities. As a result, the server **202** may act as a routing or interfacing server between the plurality of client devices **206-216** and a destination server, namely, the central processing system **140**. For example, the server **202** may be configured to communicate with the central processing system **140** and with the client devices **206-216** via a multitude of protocols, such as packet-switched protocols, web services, web APIs (Application Programming Interface), etc. The server **202** may also convert (if necessary) and route client application data (not shown) to the appropriate server, such as the central process system **140** for example. Additionally, the server **202** may act as the destination server and need not route any data from the internet-enabled device **206-216**.

(36) As shown in FIG. **1C**, the program memory **226** and/or the RAM **230** may store various

applications for execution by the microprocessor **228**. For example, a user-interface application **236** may provide a user interface to the server **202**, which user interface may, for example, enable a network administrator to configure, troubleshoot, or test various aspects of the server's operation, or otherwise to access information thereon. A server application **238** may operate to populate and transmit client application data and web pages to the client devices **206-216**, receive information from the user transmitted back to the server **202**, and forward appropriate data to the central processing system **140** and the facility servers **126**.

(37) Like the software **171** of FIGS. **1A** and **1B**, the server application **238** may be a single module **238** or a plurality of modules **238A**, **238B**. While the server application **238** is depicted in FIG. **1C** as including two modules, **238A** and **238B**, the server application **238** may include any number of modules that may facilitate tasks related to the implementation of the server **202**. By way of example, the module **238A** may populate and transmit the client application data and/or may receive and evaluate inputs from the user to receive a data access request, while the module **238B** may communicate with one or more of the back end components **104** to fulfill a data access request. In an embodiment, one or more security modules **152** may be incorporated into a server application **238**, or may be implemented as a stand-alone application or module **238**.

(38) Referring now to FIG. **1D**, the mobile device **212** (or any of the client devices **206-216**) may include a display **240**, a Global Positioning System (GPS) unit **244** (which may include respective one or more sensors), a communication unit **258** (which may include respective one or more interfaces and/or transceivers, at least some of which may be wireless), an image capture device **256**, a user-input device (not shown), and, like the server **202**, a controller **242**. Similar to the controllers **155** and **224**, the controller **242** includes a program memory **246**, one or more microcontroller or a microprocessor (MP) **248**, a random-access memory (RAM) **250**, and an input/output (I/O) circuit **254**, all of which may be interconnected via an address/data bus **252**.

(39) The program memory **246** may include an operating system **260**, a data storage **262**, a plurality of software applications **264**, and a plurality of software routines **268**. The operating system **260**, for example, may include one of a plurality of mobile platforms such as the iOS®, Android™, Palm® webOS, Windows Mobile/Phone, BlackBerry® OS, or Symbian® OS mobile technology platforms, developed by Apple® Inc., Google® Inc., Palm® Inc. (now Hewlett-Packard Company®), Microsoft Corporation®, Research in Motion® (RIM), and Nokia®, respectively. The data storage **262** may include data such as user profiles, application data for the plurality of applications **264**, routine data for the plurality of routines **268**, and other data necessary to interact with the server **202**, the facility servers **126**, or the server applications **113** through the digital network **130**. In some embodiments, the controller **242** may also include, or otherwise be communicatively connected to, other data storage mechanisms (e.g., one or more hard disk drives, optical storage drives, solid state storage devices, etc.) that may reside within the mobile device **212**.

(40) The GPS unit **244** may use “Assisted GPS” (A-GPS), satellite GPS, or any other suitable global positioning protocol, transceivers, sensors, or system that locates the position of the mobile device **212**. For example, A-GPS utilizes terrestrial cell phone towers or Wi-Fi hotspots (e.g., wireless router points) to more accurately and more quickly determine location of the mobile device **212** while satellite GPS generally may be more useful in more remote regions that may lack cell towers or Wi-Fi hotspots. The communication unit or module **258** may communicate with the server **202** and other devices via one or more transceivers that support any one or more suitable wireless communication protocol network or networks, such as a wireless cellular telephony network (e.g., GSM, CDMA, LTE, etc.), a WLAN network (or other similar network according to 802.11 standards), a WiMAX network, a short-range wireless communication network (e.g., Bluetooth, Zigbee, infrared, etc.), and/or others.

(41) The image capture device **256** may be a built-in camera within the mobile device **212** or may be an external camera, such as a webcam, that is communicatively coupled with the mobile device

**212** (or any other internet-enabled device **206-216**) The user-input device or generally a user interface (not shown) may include a “soft” keyboard that is displayed on the display **240** of the mobile device **212**, an external hardware keyboard communicating via a wired or a wireless connection (e.g., a Bluetooth keyboard), an external mouse, or any other suitable user-input device. The user interface (which may include the display **240**) may be configured to present information to the user and/or receive inputs from the user, and may accordingly include a set of I/O components (e.g., capacitive or resistive touch sensitive input panels, keys, buttons, lights, LEDs, cursor control devices, haptic devices, and others). In embodiments, the display **240** may be a touchscreen display using singular or combinations of display technologies and can include a thin, transparent touch sensor component superimposed upon a display section that is viewable by a user. For example, such displays include capacitive displays, resistive displays, surface acoustic wave (SAW) displays, optical imaging displays, and the like.

(42) As discussed with reference to the controllers **155** and **224**, it should be appreciated that although FIG. **1D** depicts only one microprocessor **248**, the controller **242** may include multiple microprocessors **248**. Similarly, the memory of the controller **242** may include multiple RAMs **250** and multiple program memories **246**. Although the FIG. **1D** depicts the I/O circuit **254** as a single block, the I/O circuit **254** may include a number of different types of I/O circuits. The controller **242** may implement the RAM(s) **250** and the program memories **246** as semiconductor memories, magnetically readable memories, and/or optically readable memories, for example.

(43) The one or more processors **248** may be adapted and configured to execute any one or more of the plurality of software applications **264** and/or any one or more of the plurality of software routines **268** residing in the program memory **242**, in addition to other software applications. One of the plurality of applications **264** may be a client application **266** that may be implemented as a series of machine-readable instructions for performing the various tasks associated with receiving information at, displaying information on, and transmitting information from the mobile device **212**. One of the plurality of applications **264** may be a native web browser **270**, such as, for example, Apple's Safari®, Google Android™ mobile web browser, Microsoft Internet Explorer® for Mobile, Opera Mobile™, that may be implemented as a series of machine-readable instructions for receiving, interpreting, and displaying web page information from the server **202**, the facility servers **126**, or the server applications **113** while also receiving inputs from the user.

(44) Another application of the plurality of applications **264** may include a location awareness application **276** that may be implemented as a series of machine-readable instructions for receiving, interpreting, and displaying location information of the mobile device **212** (or any other internet-enabled device **206-216**), e.g., as determined based on information detected or determined by the GPS unit **244** and/or by the communication unit or module **258**. One of the plurality of routines **268** may include an image capture routine **272** that coordinates with the image capture device **256** to retrieve image data for use with one or more of the plurality of applications, such as the client application **266**, or for use with other routines. Another routine in the plurality of routines **268** may include an image display routine **274** that receives and interprets image data of any type or format for display. Likewise, the image display routine **274** may coordinate with the image capture routine **272** to obtain image data and process the image data into a displayable format for use with the client application **266**.

(45) Yet another application of the plurality of applications **264** may include a client application **266** that allows a user to interact with the enterprise or retailer, either electronically and/or to enhance the customer's retail experience within a bricks-and-mortar store. The customer or user may launch the client application **266** from an internet-enabled device, such as one of the client devices **206-216**, to access the server **202** cooperating with the central processing system **140** and the retail network **110**. Additionally, the customer or the user may also launch or instantiate any other suitable user interface application **118** (e.g., the web browser **270**, or any other one of the plurality of software applications **264**) to access the server **202**, the facility servers **126**, or the

server applications **113**. Generally, the term “user” is used when referring to a person who is operating one of the client devices **206-216** and is not exclusive of the term “customer.” For example, multiple users may utilize a particular customer's account, such as when children utilize their parent's account. As described above, one or both of the databases **146** and **239**, illustrated in FIGS. **1A** and **1C**, respectively, may include various information about the retail store's customers, as well as basic biographical information about the customer, such as a customer name, a customer address, a customer phone number, coupons redeemed by the customer, and the like. Customer account records are among the exemplary data that the system **100** may store on the databases **146** and **239**.

(46) In an embodiment, the client application **266** may include a security module **152** that operates in conjunction with the client application **266** to mitigate the risk of retail theft for the enterprise or retailer. In other embodiments, the security module **152** may be implemented as a separate application **264** which may or may not be in communicative connection with the client application **266**.

(47) In general, a computer program product in accordance with an embodiment includes a computer usable storage medium (e.g., standard random access memory (RAM), an optical disc, a universal serial bus (USB) drive, or the like) having computer-readable program code embodied therein, wherein the computer-readable program code is adapted to be executed by the processor **248** (e.g., working in connection with the operating system **260**) to facilitate the functions as described herein. In this regard, the program code may be implemented in any desired language, and may be implemented as machine code, assembly code, byte code, interpretable source code or the like (e.g., via C, C++, Java, Actionscript, Objective-C, Javascript, CSS, XML, and/or others).

(48) Referring now to FIG. **2**, FIG. **2** depicts an example layout of an example physical retail store **272** of a retailer or enterprise (such as the physical retail store **112** as described with respect to FIG. **1A**). In the example depicted in FIG. **2**, the physical retail store **272** may include different departments or sections (as shown: photo, pharmacy, health, and food/drink); however it should be appreciated that other types of retail stores and general environments are envisioned. Each of the different departments or sections may include various components, devices, or the like. For example, as depicted in store **272**, the photo section may include one or more printers **289** that may be configured to print digital images.

(49) Customers or users **280**, **282** may enter the retail store, browse in the various departments or sections, and/or purchase any desired items/products or services. Each of the customers **280**, **282** may be equipped with a respective electronic device **281**, **283** (such as one of the client devices **206-216** as described with respect to FIG. **1A**). Each electronic device **281**, **283** may be any type of portable electronic device, for example, a notebook computer, a tablet, a mobile phone, a Personal Digital Assistant (PDA), a smart phone, a tablet computer, a multimedia player, an MP3 or MP4 player, a digital or analog broadcast receiver, a remote controller, or any other electronic apparatus.

(50) According to embodiments, the physical retail store **272** may support various wireless local area networks (WLAN) and/or wireless personal area networks (WPAN) to which the electronic devices **281**, **283** may connect, either in a secured or unsecured manner. In an embodiment, one or more wireless local area networks and/or wireless personal area networks that are accessible within or near the physical retail store may be included in the network **130** of FIG. **1**. In one particular implementation, the physical retail store **272** may include one or more wireless access points (AP) **284** to which the electronic devices **281**, **283** may connect, e.g. via a suitable transceiver and a WLAN connection. Accordingly, when the electronic devices **281**, **283** are connected to the AP **284**, the electronic devices **281**, **283** may be connected to the local area network implemented within the physical retail store **272** (i.e., the physical retail store **272** may be a “hotspot” and/or may provide Wi-Fi connectivity to the devices **281**, **283**).

(51) The physical retail store **272** may also be configured with a plurality of transmitters or transceivers **285**, **286**, **287**, **288** (e.g., “beacons”) that may be disposed throughout the area of the

physical retail store **272**. Although FIG. 2 depicts the physical retail store **272** supporting four (4) transmitters **285-288**, it should be appreciated that the physical retail store **272** may support fewer or additional transmitters. The plurality of transmitters **285-288** may be disposed in various locations of the physical retail store **272**. Each of the plurality of transmitters **285-288** may be secured to various components of the physical retail store **272** (e.g., shelves, ceiling, receptacles, containers, doors, etc.). Each of the plurality of transmitters **285-288** may include any combination of hardware and software components, including a module for transmitting or broadcasting signals. Further, each of the plurality of transmitters **285-288** may be configured to be powered by a battery or via another power source.

(52) According to embodiments, each of the plurality of transmitters or transceivers **285-288** may support one or more short-range communication protocols as radio-frequency identification (RFID), Bluetooth®, Bluetooth® low energy (BLE), Infrared Data Association (IrDA), near field communication (NFC), ZigBee, other protocols defined under the IEEE 802 standard, and/or other technologies. Each of the plurality of transmitters **285-288** may also be configured to broadcast or transmit a signal that may include any stored data. In one embodiment, each of the plurality of transmitters **285-288** may continuously broadcast a signal that may include a unique identifier of the corresponding transmitter **285-288**.

(53) The signals that the transmitters or transceivers **285-288** broadcast may have an associated detection range depending on the type of communication protocol. Generally, Bluetooth® signals have a range of 100 meters and BLE (Bluetooth Low Energy) signals have a range of 50 meters. The detection range of the signal that the transmitters **285-288** broadcast may also vary and may be programmable. For example, the range of a first signal that is broadcast by the transmitter **285** may be fifteen (15) meters while the range of a second signal that is broadcast by the transmitter **286** may be twenty-five (25) meters.

(54) When one of the electronic devices **281, 283** is within broadcast range of one of the transmitters/transceivers **285-288**, the electronic devices **281, 283** can detect and receive the signal, e.g., via a suitable transceiver of the electronic device **281, 283**. In particular, a communication module of the electronic devices **281, 283** that supports a short range communication protocol (e.g., a BLE chip) can detect and receive the signal. For example, FIG. 1 depicts an example communication module **258** which may be included in the device **281** and/or **283**, and FIG. 2 depicts the electronic device **281** detecting the signal broadcast by the transmitter **285** via its communication module **258**.

(55) According to embodiments, the electronic devices **281, 283** (and any application executing thereon) may facilitate various features to mitigate the risk of retail theft when connected to various ones of the connections within the physical retail store **272**. In particular, the electronic devices **281, 283** may detect one or more of the transmitters/transceivers **285-288**, and/or may connect to (or may detect the availability of) the access point **284**. Based on the electronic presence of the electronic devices **281, 283** within the physical retail store **272**, the facility server **126** may in turn connect to an on-site server or a remote server to facilitate the mitigation of the risk of retail theft, as is described in more detail below.

(56) FIG. 3 depicts an example portion **300** of the system **100** of FIG. 1 in greater detail. The portion **300** includes an area or section **302** of the example physical retail store **272** of FIG. 2 that includes therein a portion of the front end-system **102** of FIG. 1. The portion **300** also includes a portion **304** of the backend system **104** of FIG. 1. The portion **300** may operate to mitigate the risk of retail theft in the physical retail store **272**, for example. Thus, for ease of discussion, FIG. 3 is discussed with simultaneous reference to FIGS. 1A-1D and FIG. 2.

(57) As illustrated in FIG. 3, the area or section **302** of the physical retail store **272** may include one or more receptacles **305**, each of which respectively houses or stores one or more items **308** therein, such as retail items offered for sale by the retailer. The items **308** are secured within their respective receptacle **305** via an electronic lock **310** that may be electronically activated and deactivated. For

example, as depicted in FIG. 3, the receptacle **305a** stores one or more items **308a** therein, and the receptacle **305a** as a whole is secured via a single electronic lock **310a**, e.g., by locking a cover, flap, slot, or door of the receptacle **305a** using the electronic lock **310a**. Also as illustrated in FIG. 3, the receptacle **305b** stores one or more items **308b** therein, however, the receptacle **305b** as a whole is not secured by an electronic lock **310**. Rather, each item **308b** is secured to the receptacle **305b** via a respective electronic lock **310b**, either individually and/or in groups of items. For example, the receptacle **305b** may be a shelf, rack, bin, or other type of receptacle.

(58) Typically, the types of items **308** that are secured within or to the receptacles **305** in the retail store **272** have particular characteristics that render the items **308** as having a higher risk of being shoplifted or stolen. Such characteristics may include, for example, a relatively high value or cost, a relatively high black market or resale value or demand, a history of being shoplifted, a requirement for checking customer's age before purchase, etc.

(59) Additionally, each receptacle **305** in the area or section **302** of the example physical retail store **272** is associated with a corresponding wireless transceiver **312**. The wireless transceiver **312** may be disposed or located on or at the receptacle **305** (as is illustrated by the transceiver **312a**), or the transceiver may be disposed or located proximate to the receptacle **305**, e.g., within sufficient proximity of the receptacle **305** so that a mobile device **315**, when operated by a customer who is in vicinity of the receptacle **305** and who may be interested in handling the items **308** stored therein, is able to detect signals generated by the wireless transceiver **312**, e.g., when the customer device **315** is within the detection range of the transceiver **312** (as is illustrated by the transceiver **312b**). The customer device **315** may be one of the mobile devices **206-214** or **281, 283**, for example, and the wireless transceiver **312** may be one of the transmitters **285-288** which may support a short-range communication protocol such as radio-frequency identification (RFID), Bluetooth®, Bluetooth® low energy (BLE), Infrared Data Association (IrDA), near field communication (NFC), ZigBee, other protocols defined under the IEEE 802 standard, and/or other technologies. For example, the wireless transceiver **312** may transmit (e.g., continuously or intermittently) a beacon signal using a short-range communication protocol, or may transmit some other suitable wireless signal that is able to be detected and/or discovered by the customer device **315** when the customer device **315** is within the detection range of the wireless transceiver **312**.

(60) As further shown in FIG. 3, the transceivers **312** and the electronic locks **310** within the physical retail store **272** may be communicatively connected to the store's facility server **126**, e.g., in a manner such as previously discussed with respect to FIG. 2. Typically, the transceivers **312** and the electronic locks **310** may be connected to the facility server **126** via any number of in-store wired and/or wireless network connections or network(s) **318**, and the connections via which the transceivers **312** and the electronic locks **310** may be secured and are not accessible to the public. In some configurations, the transceivers **312** and/or the electronic locks **310** may be additionally or alternatively communicatively connected via the in-store network(s) **318** and one or more external networks **130** to one or more components of the backend system **104**, such as to the central processing system **140**.

(61) Still further as shown in FIG. 3, one or more devices **320** that are being operated by agents of the retailer or enterprise (e.g., store associates, risk management personnel, etc.) may be communicatively connected to the in-store network(s) **318**. The agent device **320** may be one of the devices **206-216** or **281, 283**, for example, and may be a mobile device or may be a stationary device. As such, the agent device **320** may be communicatively connected to the facility server **126**, the workstations **128**, and/or to the electronic locks **310**, e.g., via a wireless access point **284** or a wired connection **322**, both of which may be included in the in-store network(s) **318**. In some situations, multiple agent devices **320** may be communicatively connected to the in-store network(s) **318**. Typically, the connections via which the agent devices **320** are connected to the in-store network(s) **318** may be secured and not accessible to the public.

(62) To mitigate the risk of retail theft, the facility server **126** may execute thereon a local server

security application **325a** which, in some embodiments, includes the security module **152** of FIG. **1** or an instance thereof. In some embodiments, one or more agent devices **320** may execute thereon a respective local device security application **325b**. The local server security application **325a** may operate in conjunction with one or more local device security applications **325b** to mitigate the risk of retail theft within the store **272**. In some configurations, though, either the local server security application **325a** or the local device security applications **325b** may be omitted.

(63) Now turning to the portion **304** of the backend system **104** depicted in FIG. **3**, the portion **304** may include one or more applications and/or routines **328** that support the retailer or enterprise. At least some of the applications **328** may be, for example, a server application **113** or software module **171** at the central processing system **140**, and/or at least some of the applications **328** may be an application or module **238** at the server **202**. At any rate, the applications/routines **328** included in the portion **304** of the backend system **104** may include a customer authentication/verification module **330** that, when executed, authenticates and verifies an electronic presence of a customer, a server application **332** that operates in conjunction with client applications **118** that are provided by the retailer enterprise and downloaded to various customer devices **315**, an application that manages a loyalty card or incentive program **335** provided by the retailer or enterprise, an application that manages an electronic or web-based account of customers of the retailer or enterprise **338**, and/or other applications/routines **340**.

(64) As further illustrated in FIG. **3**, the application/routines **328** may have access to at least a portion of the data stored in the database(s) **146**. For example, the loyalty program application **335** may access data indicative transactions and rewards that have been issued to customers, and the electronic customer account application **338** may access stored credit card information.

(65) To mitigate the risk of retail theft, the applications/routines **328** may include a remote security application **342**. In an embodiment, the remote security application **342** includes an instance of the security module **152** of FIG. **1**. In some embodiments, the remote security application **342** may be integrally implemented with one or more other applications **328**, such as with the customer authentication and verification application **330** or the server application **332**. The remote security application **342** may operate in conjunction with the local security application(s) **342** and may access data stored in the customer risk profile store **148** and optionally data stored in the item profile store **150** to utilize in mitigating the risk of retail theft, which may include the remote triggering of secured receptacles, as is described below.

(66) Specifically, FIG. **4** depicts an example signal diagram **400** associated with mitigating the risk of retail theft at a physical store of a retailer or enterprise, e.g., by automatically triggering the unlocking or un-securing of items for particular customers. For ease of discussion, and not for limitation purposes, FIG. **4** is discussed with simultaneous reference to FIGS. **1A-1D**, FIG. **2**, and FIG. **3**, although the signal diagram **400** of FIG. **4** may be utilized with other systems and other computing devices.

(67) The signal diagram **400** indicates a personal electronic device (PED) **405** and a server **408**. A user or customer of a retailer may operate the personal electronic device **405**, for example, and the device **405** may be a smart phone, tablet, laptop, or other PED that is configured with wireless capabilities. For example, the personal electronic device **405** may be one of the devices **206-214** of FIGS. **1A** and **1B**. The server **408** may comprise one or more of the frontend components **102** of the retailer. For example, the server **408** may include a facility server **126** and/or one or more workstations **128**.

(68) The signal diagram **400** also indicates a receptacle **410** disposed within a physical retail store, into or in which one or more items are secured via one or more electronic locks. For example, the receptacle **410** may be one of the receptacles **305** storing one or more items **308** that are secured via one or more electronic locks **310**, as illustrated in FIG. **3**. Additionally, the receptacle **410** may include a transmitter and/or a transceiver disposed thereon, or within sufficient proximity of the receptacle **410** so that the PED **405**, when operated by a customer who may be interested in



handling the items stored within the receptacle **410** and is in the vicinity of the receptacle **410**, is able to detect signals generated by the transceiver/transmitter. The transmitter and/or transceiver associated with the receptacle **410** may be the transceiver **312** illustrated in FIG. 3, in an embodiment.

(69) Additionally, the signal diagram **400** indicates a backend system **412**. In an embodiment, the backend system **412** is the back end portion **104** of the system **100** shown in FIG. 1A, and as such may include the central processing system **140** and/or the server **202**. At any rate, FIG. 4 illustrates a database or data store **415** in which customer risk profiles are maintained, and a database or data store **418** in which item profiles are maintained. The data stores **415**, **418** may be included in the backend system **412**, or the data stores **415**, **418** may be excluded from but nonetheless accessible to the backend system **412**. In an embodiment, the data store **415** comprises the risk profile store **148** of FIG. 1A, and the data store **418** comprises the item profile store **150** of FIG. 1A.

(70) The transceiver associated with the receptacle **410** may emit a beacon signal **420**, and when the PED **405** is disposed within the detection range of the transceiver, the PED **405** may automatically detect the beacon and thereby discover the transceiver associated with the receptacle **410** (reference **422**), thereby establishing a wireless communication connection between the PED **405** and transceiver associated with the receptacle **410**. In some embodiments, the wireless connection may be automatically established, that is, the user of the PED **405** may not have initiated the discovery process and indeed, may be unaware of the discovery process.

(71) In some embodiments, though, the establishment of the wireless connection between the PED **405** and the transceiver associated with the receptacle **410** may be triggered by the user of the PED **405**. For example, the user may wish to access the items secured at the receptacle **410**, and may utilize an application executing on the device **405** to trigger the unlocking or un-securing of the items. The application may be an application **118** that is provided by the retailer or enterprise, e.g., a retailer client application, a loyalty card client application, etc. Alternatively, the application may be a web browser or equivalent via which the user accesses his or her electronic or web-based account with the retailer or enterprise. At any rate, via the application executing on the Personal Electronic Device **405**, the user may activate a user control thereby initiating the discovery of the transceiver corresponding to the receptacle **410** (reference **422**), and the eventual establishment of the wireless connection between the PED **405** and the transceiver corresponding to the receptacle **410**.

(72) Via the established wireless connection between the PED **405** and the transceiver associated with the receptacle **410**, the PED **405** may transmit or send an indication of an identity of a user or customer (reference **425**). The indication of the customer identity may comprise, for example, an identifier of the personal electronic device **405**, such as an International Mobile Station Equipment Identity (IMEI), a Mobile Equipment Identifier (MEID), an International Mobile Subscriber Identity (IMSI), an Electronic Serial Number (ESN), an integrated circuit card identifier (ICC-ID) of a card or chip of the PED **405**, a Telephone Number (TN), and/or other suitable identifier. Such types of identifiers may be automatically transmitted or sent from the PED **405** to the transceiver corresponding to the receptacle **410** upon establishment of the wireless connection, e.g., as part of the header and/or payload in the signaling that is exchanged to establish the wireless connection. In these situations, the communication **425** may be omitted, as the indication of the customer identity is included in the communication **422**.

(73) In some scenarios, the indication of the customer identity may comprise an identification of an account of the customer with the retailer or enterprise (e.g., a loyalty account, an electronic or web-based account, etc.), and/or of a user ID or login ID associated therewith. In some scenarios, such as when a retailer client application is executing on the PED **405**, the indication of the customer identity may comprise an identifier of the client application itself, e.g., as tracked by a server of the retailer or enterprise. At any rate, the indication of the customer identity may be automatically sent from the PED **405** to the transceiver of the receptacle **410**, or may be sent upon request of the user

or customer, e.g., by activating a user control at the PED **405**.

(74) Upon reception of the indication of the customer identity (reference **428**), the transceiver corresponding to the receptacle **410** may cause the customer identity indication (reference **430**) and optionally an indication of the type of item secured at the receptacle **410** to be transmitted or sent to the backend system **412**. In the scenario illustrated in FIG. **4**, the transceiver corresponding to the receptacle **410** has a priori knowledge of the types of items being secured of the receptacle **410**, and sends an indication of the type of item along with the customer identity indication directly to the backend system **412** (reference **430**), e.g., via the network **130**. In some embodiments (not shown), the transceiver corresponding to the receptacle **410** may send an indication of the obtained customer identity information to the local server **408** servicing the particular physical retail store, and the server **408** may determine the type of item being secured at the receptacle **410** (e.g., by accessing a store plan or database that maps receptacles to items), and the server **408** may transmit or send the customer identity indication and an indication of the type of item to the back end system **412**, e.g., via the network **130**.

(75) Upon reception of the customer identity indication and the indication of the type of item (reference **432**), the back end server **412** may authenticate and verify the customer based on the customer identity indication (reference **435**). For example, the back end server **412** may utilize the authentication and verification application **330** to verify the received customer identity indication against customer data stored in the customer risk profile database **415** (as shown in FIG. **4**), or against customer data stored in some other suitable database. Using the authenticated and verified customer identity, the backend server **412** may determine a risk score corresponding to the identified customer (reference **438**). The risk score may be determined (**438**) based on risk profile data corresponding to the customer identity and stored in the database **415**. As previously discussed, the customer's risk profile may include data or information pertaining to the customer's product purchases, product returns, bounced checks, payment history, on-line browsing habits, and/or other historical actions/events that the customer has had with the retailer or enterprise. In some embodiments, the risk score of the identified customer may be determined (**438**) further based on item profile data corresponding to the identified item and stored in the database **418**, such as data indicative of the value of the item, whether or not the item has a history of theft or being stolen, etc. Different types of customer risk profile data and/or item profile data may be weighted differently to determine the risk score, if desired. In an embodiment, the customer risk profile database **415** may comprise the customer risk profile data store **148** of FIG. **1A**, and the item profile database **418** may comprise the item profile data store **150** of FIG. **1A**.

(76) The signal diagram **400** depicts the determined risk score being transmitted or sent from the back end server **412** to the local server **408** that is servicing the physical retail store in which the receptacle **410** is disposed (reference **440**). At the local server **408**, a determination may be made as to whether or not the risk score is indicative of an acceptable risk or of an unacceptable risk (reference **442**). If the risk score is indicative of an acceptable risk, the electronic lock(s) securing the items at the receptacle **410** may be automatically and remotely unlocked. For example, the local store server **408** may send a remote unlock signal, command, or instruction **445** to the electronic lock(s) associated with the receptacle **410**, e.g., via the in-store network(s) **318**. A notification that the items have been remotely unsecured/unlocked may be sent to the customer device **405**, e.g., by the transceiver proximate to the receptacle **410** as shown in FIG. **4**, or by the local server **408** (not shown in FIG. **4**). Additionally or alternatively, an indication that the items have been remotely unsecured/unlocked may be locally provided at or near the receptacle, e.g. via a light, display screen, or other indicator.

(77) If the risk score is indicative of an unacceptable risk for an automatic unlocking of the receptacle **410**, an agent of the retailer may be notified. For example, the local server **408** may transmit or send, to an agent device **450**, a notification including an indication of the risk score, the receptacle **410**, the item secured at the receptacle **410**, the value of the item secured at the

receptacle **410**, and/or the electronic lock(s) associated with the receptacle **410** (reference **448**). Upon reception of the notification, an agent operating the device **450** may evaluate the received information and make a decision as to whether he or she is to remotely unlock the receptacle **410** for the customer by causing a remote unlock signal, command, or instruction to be sent to the electronic lock (reference **452**), or whether he or she is to physically walk over to the receptacle **410** and manually open the electronic lock(s) so that the agent may monitor customer's behavior. In an embodiment, the agent may remotely unlock the receptacle **410** by activating a user control at his or her device **450**, thereby causing an unlock signal to be transmitted via the in-store network **318** to the electronic lock(s) (reference **452**), and thus causing the items at the receptacle **410** to be automatically unsecured and made accessible to the customer. A notification that the items have been remotely unsecured/unlocked may be sent to the customer device **405**, e.g., by the transceiver proximate to the receptacle **410** or by the agent device **450** (not shown in FIG. 4). Additionally or alternatively, an indication that the items have been remotely unsecured/unlocked may be locally provided at or near the receptacle, e.g. via a light, display screen, or other indicator.

(78) In some configurations of the system **100**, when the items at the receptacle **410** are automatically unsecured (e.g., via the remote unlock signal, command, or instruction **445** or the remote unlock signal, command, or instruction **452**), a sensor disposed at the receptacle **410** may detect the removal of items (reference **460**) and may indicate the occurrence or event of the removal to the local server **408** (reference **462**). For example, the sensor may be an RFID (Radio-Frequency Identification) or other suitable detector that is positioned to detect a movement of a corresponding tag that is affixed to an item that is secured at the receptacle **410**. For example, as shown in FIG. 3, a sensor **455a** corresponding to receptacle **305a** is disposed at a location that enables the sensor **455a** to detect the removal of items **308a** via their affixed tags **458a**, and a sensor **455b** corresponding to receptacle **305b** is disposed at a location that enables the sensor **455b** to detect the removal of items **308b** via their affixed tags **458b**. In FIG. 4, upon the detection of the removal of an item at the receptacle **410** (reference **460**), the sensor may cause a signal indicative of the item's removal to be transmitted to the store server **126** (reference **462**), e.g., via the in-store network(s) **318**, so that the item may be tracked.

(79) For example, the local server **408** may set a timer (reference **465**) corresponding to when the item was removed from the receptacle **410**. The server **408** may start the timer when the server **408** receives the signal **462**, or the server **408** may set the timer in accordance with a timestamp included in the signal **462**. The duration of the time interval for which the timer is set may be determined a priori, and the duration may be modifiable. At any rate, if the item is purchased and/or otherwise scanned at a register within the retail store before the timer expires, the server **408** may cancel the timer (reference **468**) and cause the purchase and/or the scanning of the item to be reflected in the customer's risk profile stored at the database **415** (references **470a**, **470b**). On the other hand, if the item has not been purchased and/or otherwise scanned at any register in the retail store when the timer expires, as denoted in FIG. 4 by the reference **472**, this event may be indicative of theft or some other undesirable condition relating to the removed item. Accordingly, in this situation **472**, the server **408** may alert an agent of the retailer by sending an alert to the agent's device **450** (reference **475**). The alert may include an indication of the removed item, the receptacle **410**, the time at which the item was removed from the receptacle, and/or other data. Upon viewing the alert, the agent may take the appropriate steps to recover the item and/or prevent loss of the item.

(80) In some scenarios, after the item and/or receptacle **410** has been remotely unlocked or unsecured, the item and/or the receptacle **410** may automatically be re-secured. For example, after reception of a remote unlock signal **445**, **452**, a timer may be set, and the electronic lock may automatically re-lock after the timer's expiration (reference **478**). The duration of the timer may be configurable and modifiable, if desired. Additionally or alternatively, the electronic lock may automatically re-lock after the detection of the removal of an item (reference **462**), and/or when

instructed to do so by an agent device **450** (reference **480**), e.g., upon activation of a corresponding user control at the agent device **450**. In these manners, the maximum time during which an item is unsecured may be controlled to mitigate the risk of the item being shoplifted or stolen.

(81) FIGS. **5A-5B** illustrate a flow chart of an example method **500** of mitigating the risk of retail theft at physical retail stores of a retailer or enterprise. The method **500** may operate in conjunction with embodiments of the system **100** of FIGS. **1A-1D**, the physical retail store **272** of FIG. **2**, the system portion **300** of FIG. **3**, the signal diagram **400** of FIG. **4**, and/or other systems, stores, and/or signal diagrams. For ease of discussion, though, and not for limitation purposes, the method **500** is discussed with simultaneous reference to FIGS. **1A-1D** and FIGS. **2-4**.

(82) In FIG. **5A**, at a block **502**, the method **500** may include determining an identity of a customer based on a wireless transmission that is delivered directly between (i) a transceiver corresponding to receptacle in or at which an item is housed and secured via an electronic lock, and (ii) a wireless electronic device, such as a customer's Personal Electronic Device, that is located within communication range of the transceiver. For example, referring to FIG. **3**, the transceiver may be one of the wireless transceiver **312**, and the receptacle may be one of the receptacles **305** in or at which items **308** are housed and secured via one of the electronic locks **310**.

(83) In some embodiments, determining the identity of the customer based on wireless transmission may be based on the content of the payload of the wireless transmission. In some embodiments, determining the identity of the customer based on wireless position may be based on the content of the header of the wireless transmission. At any rate, whether the customer's identity is based on the wireless transmission's payload and/or header, the identity of the customer may be determined based on an identification of the wireless electronic device, such as an IMEI, and MEID, and IMSI, and ESN, an ICC-ID of a card or chip included in the wireless electronic device, a TN, and/or another suitable identifier. Additionally or alternatively, the identity of the customer may be determined based on an identification of an account of the customer with a retailer or enterprise, such as a loyalty account, and electronic or web-based account, etc., and/or of a user ID, login ID, or other customer-specific indicia associated therewith. In some embodiments, the identity of the customer may be determined based on an identifier of the client application that is executing on the customer device, e.g. as tracked by a server of the retailer or enterprise.

(84) At a block **505**, the method **500** may include determining, based on the determined customer identity and on a risk profile of the customer, a risk score corresponding to the customer accessing the secured item. The risk profile of the customer may be stored at one or more memories or data storage devices included in a backend system of the retailer or enterprise, and may include data that is indicative of a history of unpaid items corresponding to the customer, a history of returning items corresponding to the customer, a history of non-payment or insufficient funds, history of alleged theft, etc. For example, the risk profile may be stored at the customer risk profile data store **148** illustrated in FIG. **1A**.

(85) In an embodiment, determining the risk score corresponding to the customer accessing the secured item (block **505**) may be further based on an item profile of the secured item. The identity or type of the secured item may be ascertained from the wireless transmission, e.g., from contents of the payload identifying the secured item, and/or by identifying the transceiver that received the wireless transmission. The profile of the secured item may be stored at one or memories or data storage devices included in the backend system of the retailer or enterprise, and may include data that is indicative of a value of the item, a likelihood of theft of the item, a resale market or demand for the item, etc. For example, the item profile of the secured item may be stored at the item profile store **150** illustrated in FIG. **1A**.

(86) The method **500** may additionally include determining whether or not the risk score is indicative of an acceptable risk (block **508**). For example, the determined risk score may be compared to a threshold to determine whether or not the risk score is indicative of an acceptable risk. At the block **508**, if the risk score is determined as being indicative of an acceptable risk, the

method **500** may include automatically sending an electronic signal to trigger the remote unlocking of the electronic lock at the receptacle at which the item is secured (block **510**). The electronic signal may include a remote unlock command or instruction, for example, and the electronic signal may be automatically sent to the electronic lock to release the secured item (e.g., in a manner such as previously discussed with respect to the signal **445** of FIG. **4**). Alternatively, an electronic signal indicating that the electronic lock may be remotely unlocked may be automatically sent to a device being operated by an agent of the retailer or enterprise, and the operating agent may cause a remote unlock signal or command to be transmitted from the agent device to the electronic lock (e.g., in a manner such as previously discussed with respect to the signal **452** of FIG. **4**).

(87) On the other hand, if at the block **508** the risk score is determined as being indicative of an unacceptable risk, the method **500** may include sending an electronic signal to a device being operated by an agent of the retailer or enterprise (block **512**). The signal may include an indication that the secured item is to be manually unlocked, or that the situation requires an agent evaluation. If the signal indicates that the secured item is to be manually unlocked, e.g., as determined at the block **515**, the agent may physically go to the receptacle and manually unlock the secured item so that the customer's handling of the item may be monitored in the presence of the agent (block **518**).

(88) In some scenarios, as determined at the block **515**, the signal received at the agent device may indicate that an agent evaluation is needed. In this situation, the signal may include data that is indicative of the determined risk score, an indication of the identity of the customer, an indication of the item, an indication of the receptacle, etc. The agent may evaluate the received data (block **520**). Based on his or her evaluation, the agent may decide to physically unlock the electronic lock so that the customer's handling of the item may be monitored in the presence of the agent (block **518**), or the agent may decide to cause electronic lock to be remotely unlocked (e.g., in a manner such as previously discussed with respect to the signal **452** of FIG. **4**) so that the customer has access to the secured item. For example, the agent may activate a user control at the agent device that causes an electronic signal to be sent from the agent device to trigger the remote unlocking of the electronic lock at the receptacle at which the item is secured (block **510**).

(89) Turning now to FIG. **5B**, the method **500** may optionally include blocks **520-530**, in some embodiments. As shown in FIG. **5B**, the blocks **520-530** may be executed when a remote unlock signal is sent to the electronic lock (block **510**). At the block **520**, the method **500** may include determining that an item has been removed from the receptacle. This determination may be made, for example, based on a detection, by a sensor, of the movement of an electronic tag that is attached to the item, in a manner such as previously described with respect to reference **460** in FIG. **4**. In an embodiment, the sensor and the electronic tag may comprise RFID technology or some other suitable sensing technology.

(90) At the block **522**, the method **500** may include starting a timer for a pre-determined time interval. The duration of the pre-determined time interval may be set a priori, and may be configurable. The start time of the pre-determined time interval may correspond to a time at which the item removal was detected (block **520**) and/or may correspond to a time at which the item removal was indicated to the facility server **126**, for example.

(91) At the block **525**, the method **500** may include determining whether or not the removed item has been purchased, scanned, and/or otherwise processed or detected by a workstation **128**, the facility server **126**, and/or some other device within the in-store network **318** within the pre-determined interval. If the removed item has not been processed or detected within the pre-determined time interval, the method **500** may include sending an alert to a device being operated by an agent of the retailer or enterprise (block **528**), e.g., in a such as previously described with references **472**, **475** of FIG. **4**. The alert may include therein data indicative of the removed item, the time of the item's removal, the receptacle, the customer, etc. Based on the alert, the agent may take appropriate loss prevention actions. Further, the customer's risk profile may be updated to reflect the occurrence of the timer expiration (block **530**).

(92) If, at the block **525**, the removed item has been processed or otherwise detected within the pre-determined time interval, the method **500** may proceed to update the risk profile of the customer accordingly (block **530**).

(93) Thus, based on the events that transpire after the removal of the item from the receptacle was detected or determined at the block **520**, the customer's risk profile may be updated (block **530**). The updated customer risk profile may then be utilized in determining an updated risk score corresponding to automatically triggering the remote unlocking of items for the customer in the future.

(94) In some embodiments, at least a portion of the method **500** may be performed by one or more frontend components **102** of the system **100**, and at least another portion of the method **500** may be performed by one or more backend components **104** of the system **100**. In other embodiments, such as when a facility server **126** of a retail store **112** is virtually implemented external to the physical retail store **112**, the entirety of the method **500** may be performed by one or more backend components **104** of the system **100** that provide a virtual facility server **126** to service the physical retail store **112**.

(95) Returning again to FIG. **3**, in some scenarios, the secured receptacle **305a** may be particular to a customer, and may securely house items that have been offered for sale and have been and/or are to be purchased by the particular customer. For example, the secured receptacle **305a** may be designated to be unlocked by only the particular customer (or by his/her agent), e.g., to pick up an item that the customer has previously ordered, such as a filled prescription, an on-line order that is to be picked up at the receptacle **305a**, and the like. In these scenarios, typically the receptacle **305a** is secured as a whole by a single electronic lock **310a**.

(96) Indeed, referring now to FIG. **6A**, the retailer or enterprise may support a plurality of receptacles **600** whose customer-facing secured access mechanisms (e.g., doors, covers, flaps, slots, etc.) are individually secured/locked. For example, the plurality of secured receptacles **600** may be a bank of lockers, cubicles, boxes, bins, cabinets, etc. of different sizes (e.g., different lengths, widths, depths), each of which may be electronically secured, e.g., in a manner similar to that described for receptacle **305a** and electronic lock **310a** of FIG. **3**. The bank of secured receptacles **600** may be located at the physical retail store **372**, or may be located at an alternate location. In some arrangements, the retailer or enterprise may support multiple banks of secured receptacles across multiple locations at which customers can access and pick up secured items. Customers may electronically gain access to a particular secured receptacle (e.g., receptacle **602** with electronic lock **605**) via the customer mobile device **315**, such as in a manner described above. Alternatively, customers may electronically gain access to a particular secured receptacle (e.g., receptacle **602** with electronic lock **605**) via an on-site electronic device **608** corresponding to the bank of receptacles **600**, or via the customer mobile device **315** operating in conjunction with the on-site receptacle management electronic device **608**, as is described in more detail later in this disclosure. The on-site receptacle management electronic device **608** may be communicatively connected to each electronic lock included in the bank of receptacles **600**, the facility server **126**, and/or the back-end server **328** via the network **130**, for example.

(97) For retail or enterprise personnel to load and secure customer items into respective receptacles to await customer pickup, retail/enterprise personnel may unlock/access appropriate receptacles via the customer-facing access mechanisms (albeit via an enterprise mobile device using electronic security parameters that are different than those of the customer) to gain access to and load the receptacles. Additionally or alternatively, enterprise personnel may gain access to and load the receptacles via enterprise-facing access mechanisms. FIG. **6B** illustrates an embodiment of the latter, in which a bank of receptacles **620** is built into a wall **622**. Respective, secured customer-facing access mechanisms (e.g., **625a-625c**) for each of the receptacles **620** are disposed on one side of the wall **622**, and enterprise-facing access mechanisms **628** (e.g., doors, flaps, slots, covers, openings, etc., which are not visible in FIG. **6B**) are disposed on the other side of the wall **622**. If

desired, the enterprise-facing mechanisms **628** need not be individually secured, such as when the enterprise-facing mechanisms **628** of the bank of receptacles **620** are disposed in a locked back room that is accessible to only retail/enterprise personnel and not to the public.

(98) FIG. 7 illustrates a flow chart of an example method **700** of securing a receptacle. The method **700** may operate in conjunction with embodiments of the system **100** of FIGS. 1A-1D, the physical retail store **272** of FIG. 2 or remote locations associated therewith, the system **300** of FIG. 3, the banks of receptacles **600**, **620** of FIGS. 6A-6B, and/or other systems, stores, locations, and receptacles. For ease of discussion, though, and not for limitation purposes, the method **700** is discussed with simultaneous reference to FIGS. 1A-1D, 2, 3, and 6A-6B. In an embodiment, at least a portion of the method **700** is performed by executing computer-executable instructions stored on one or more memories of the central processing system **140** and/or the facility server **126**. For example, instructions that are executable to perform at least a portion of the method **700** may be included in the applications/routines **325** and/or in the applications/routines **328**.

(99) FIG. 7 illustrates two of numerous example embodiments of the method **700** for securing a receptacle associated with a retailer or enterprise. In a first embodiment, at a block **702**, the method **700** may include determining that a customer or user desires to pick up one or more items via a secured receptacle provided by the enterprise. The one or more items may include, for example, a prescription fill or refill, a retail item that the customer purchased on-line, a replacement item provided by the retailer or enterprise, etc. As such, determining that the customer desires to pick up one or more items via a secured receptacle (block **702**) may include receiving an electronic signal including an indication of the preference of the customer/user to utilize a secured receptacle for item pick-up. For example, the electronic signal may be received from an application via which the customer/user has made a purchase and/or otherwise has designated item pick-up via secured receptacle (e.g., enterprise application **118**, website, browser, etc.), or the electronic signal may be received from an agent device **320**, facility server **126**, and/or central processing system **140**, such as when an agent of the enterprise (e.g., a pharmacist, pharmacy technician, customer service representative, etc.) indicates, e.g., via an enterprise device or user interface **320**, **126**, **140**, that the customer/user is to pick-up item(s) via a secured receptacle.

(100) Based on the determination that the customer/user desires to pick up one or more items via a secured receptacle (block **702**), the method **700** includes automatically selecting a target receptacle (block **705**), e.g., into which the one or more items are to be loaded and secured for pick-up by the customer or an authorized agent of the customer. The receptacle may be automatically selected (block **705**) based on one or more preferred characteristics or conditions of receptacles that are indicated by the customer/user, e.g., a particular location of a receptacle (e.g., at a particular retail store **272**, at a particular alternate location, etc.), a particular height of a receptacle from the floor (e.g., to accommodate shorter customers and/or customers seated in mobility devices), etc. Additionally or alternatively, the receptacle may be automatically selected (block **705**) based on one or characteristics of the one or more items that are to be secured within the target receptacle, such as a size, dimension, and/or geometry of the one or more items (individually and/or cumulatively), temperature control requirements, etc. Still additionally or alternatively, the receptacle may be automatically selected (block **705**) based on respective availabilities of different types of receptacles within one or more banks of receptacles disposed at one or more different locations, etc.

(101) At a block **708**, an indication of the selected receptacle may be delivered to an electronic device situated at the location at which the receptacle is disposed, where the electronic device is operable by or otherwise accessible to local personnel or agents of the retailer or enterprise supporting the bank of receptacles in which the selected receptacle is included. For example, at the block **708**, the indication of the selected receptacle may be delivered to the facility server **126**, one or more agent devices **320**, the on-site receptacle management electronic device **608**, and/or another computing device operated by enterprise personnel to thereby indicate that the selected

receptacle is ready for receiving the customer's item(s). Based on the received indication, the enterprise personnel may manually initiate an electronic unlocking of the selected receptacle, e.g., by causing an electronic unlock command to be sent to the electronic lock securing the selected receptacle via the facility server **126**, the one or more agent devices **320**, the on-site receptacle management electronic device **608**, and/or another computing device operated by enterprise personnel. Alternatively, the selected receptacle may be automatically unlocked by the system **100** upon its selection, and the transmitted indication of the selected receptacle to the electronic device of the local enterprise agent is for notification purposes.

(102) Upon loading the one or more items of the customer into the selected receptacle, the enterprise personnel may issue an electronic lock instruction via the on-site receptacle management electronic device **608** or via an agent device **320** or facility server **126** that is communicatively connected to the receptacle management electronic device **608** (e.g., via one or more wired and/or wireless communication networks **318**). Alternatively, the enterprise personnel may issue the electronic lock instruction directly at the electronic lock securing the selected receptacle. As such, the method **700** may include receiving the electronic lock instruction corresponding to the selected receptacle (block **710**).

(103) It is noted that the enterprise personnel receiving the indication of the selected receptacle and loading the items into the selected receptacle need not be human beings. For example, an indication of the selected receptacle may be delivered to a robot disposed at the location of the bank of receptacles, and in response to the received indication, the robot may automatically load the customer's items into the selected receptacle and issue the electronic lock command.

(104) The method **700** may include automatically securing or locking the selected receptacle (block **712**), e.g., based on the reception of the electronic locking instruction (block **710**), and storing an indication of an association between the selected receptacle and the customer/user (block **715**). For example, at the block **712**, electronically securing the reserved receptacle may include causing an electronic signal including a lock command to be delivered to the electronic lock and, upon receiving the lock command, the electronic lock may automatically lock or secure the receptacle. At the block **715**, storing the indication of the association between the selected receptacle and the customer/user may include storing the association at the product/customer database **146**, and/or at a facility server **126**. In some embodiments, other information may be stored in conjunction with the association, such as an indication of the identity of the customer, an indication of the identity of an agent of the customer who is authorized to pick up the items on behalf of the customer, an access or security code that is to be utilized to access the secured receptacle, etc.

(105) Additionally, the method **700** may include automatically sending an electronic notification to the customer (block **718**), where the notification may indicate that his or her secured item(s) are ready to be picked up. For example, at the block **718**, the electronic notification may be delivered to the customer or to an application that corresponds to the customer (e.g., via email, text message, enterprise client application **118**, etc.) and that executes at one or more PEDs **206**, **208**, **210**, **212**, **214**, **216** associated with the customer. The electronic notification typically may include the physical location of receptacle (e.g., at a particular physical store or at some other location at which the receptacle is disposed), but may or may not include the specific identity of the receptacle itself. In some implementations, the notification may include an access code via which the customer is able to access the secured receptacle. The access code may be, for example, a series of alphanumeric characters, a QR code, a bar code, etc.

(106) In a second embodiment of securing a receptacle illustrated in FIG. 7, the method **700** includes determining that a customer or user desires to reserve a securable receptacle (block **720**), e.g., for returning or otherwise providing an item for securing within the reserved receptacle. For example, the customer or user may desire to reserve a receptacle provided by the retailer or enterprise to return or exchange a previously purchased item, or the customer/user may desire to reserve a receptacle provided by the retailer or enterprise via which the customer/user may securely



deliver or provide one or more items for other purposes. As such, determining that the customer/user desires to reserve a securable receptacle (block **720**) may include receiving an electronic signal including an indication of a request of the customer/user to reserve a receptacle that is securable. For example, electronic signal may be received from a website, browser, email, enterprise application **118**, or other application executing at a customer PED **206, 208, 210, 212, 214, 216**.

(107) Based on the determination that the customer desires to reserve a securable receptacle (block **720**), the method **750** may include selecting a target receptacle from a plurality of receptacles (block **705**), e.g., for reservation and into which the customer may load and secure one or more items. The target receptacle may be automatically selected (block **705**) based on one or more conditions. For example, the target receptacle may be automatically selected (block **705**) based on one or more preferred characteristics or conditions of receptacles that are indicated by the customer/user, e.g., a particular receptacle location (e.g., at a particular retail store **272**, at a particular alternate location, etc.), a maximum distance or height from the floor (e.g., to accommodate shorter customers and/or customers seated in mobility devices), a minimum receptacle size, dimension, and/or geometry, a temperature control requirement, and/or one or more other characteristics of receptacles. Additionally or alternatively, the target receptacle may be automatically selected (block **705**) based on one or more conditions other than customer preferences, such as the availability of different types and sizes of receptacles at different locations.

(108) Upon selection of the target receptacle (block **705**), the second embodiment of the method **700** may include reserving the selected receptacle, e.g., by electronically securing the reserved receptacle (block **712**), storing an indication of an association between the selected receptacle and the customer/user (block **715**), and electronically notifying the customer/user (block **718**), e.g., that a receptacle has been reserved and secured based on the reservation request. For example, at the block **712**, electronically securing the reserved receptacle may include causing an electronic signal including an electronic lock command to be delivered to the electronic lock and, upon receiving the lock command, the electronic lock may automatically lock or secure the receptacle. At the block **715**, storing the indication of the association between the selected receptacle and the customer/user may include storing the association at the product/customer database **146**, and/or at a facility server **126**. In some embodiments, other information may be stored in conjunction with the association, such as an indication of the identity of the customer, the identity of an agent of the customer who is authorized to pick up the items on behalf of the customer, an access or security code that is to be utilized to access the secured receptacle, etc.

(109) At the block **718**, electronically notifying the customer/user of the reserved, secured receptacle may include transmitting an electronic notification (e.g., via one or more communication networks **318, 130**) to an electronic device and/or an application corresponding to the customer, where the electronic notification includes an indication that a receptacle has been reserved in response to the reservation request. For example, such an electronic notification may be delivered to one or more PEDs **206, 208, 210, 212, 214, 216** associated with the customer/user via email, text message, enterprise client application **118**, etc. In some implementations, the notification may include an indication of the physical store or other location at which the reserved receptacle is disposed, and optionally may include an access code which the customer (or an authorized agent of the customer) may utilize to gain access to the secured receptacle. The access code may be of any suitable format, such as a series of alphanumeric characters, a QR code, a bar code, etc. The electronic notification may or may not include the specific identity of the receptacle itself.

(110) Note that the first and second embodiments of the method **700** for securing a receptacle share common blocks. However, the first embodiment omits the block **720**, whereas the second embodiment omits the blocks **702, 708, and 710**. Of course, other embodiments of the method **700** are possible, which may include fewer, additional, and/or alternative blocks other than those illustrated in FIG. 7.

(111) FIG. 8 illustrates a flow chart of an example method **800** of providing access to a secured receptacle associated with a retailer or enterprise. The method **800** may operate in conjunction with embodiments of the system **100** of FIGS. 1A-1D, the physical retail store **272** of FIG. 2 and/or remote locations associated therewith, the system **300** of FIG. 3, the signal diagram **400** of FIG. 4, the banks of receptacles **600**, **620** of FIG. 6A-6B, the method **700** of FIG. 7, and/or other systems, stores, locations, signal diagrams, receptacles and methods. For example, the method **800** may be performed after or subsequent to a completion of an execution of the method **700**. For ease of discussion, though, and not for limitation purposes, the method **800** is discussed with simultaneous reference to FIGS. 1A-1D, FIGS. 2-4, 6A-6B, and 7. Generally speaking, the method **800** may be performed when a customer or user (or an agent of the customer/user) arrives at a location at which a secured receptacle is situated, e.g., the customer/user arrives at the receptacle bank **600** or **620**.

(112) As shown in FIG. 8, the method **800** may include receiving an electronic signal (block **802**) and determining an identity of the customer based on the received electronic signal (block **805**). The electronic signal may be received via a local interface of the system **100**, that is, via an interface of the system **100** that is locally disposed at a location in which receptacles are situated. For example, the local interface may be included in the on-site receptacle management device **608** or in the customer PED **315**.

(113) In an example scenario, receiving the electronic signal (block **802**) may include, for example, receiving an access code which was previously provided to the customer (e.g., such as at the block **718** of the method **700**). The access code may be received via the on-site receptacle management electronic device **608**, for example, either manually via direct entry at a manual user interface of the device **608**, or optically, such as by the customer scanning a QR code, bar code, or other type of electronic code at a scanner interface of the device **608**. The customer may provide the electronic code for scanning via a personal electronic device **315**, via paper, or via some other suitable medium. In this example scenario, determining the identity of the customer based on the electronic signal (block **802**) may include verifying that the access code is a valid access code, and optionally that the access code corresponds to a secured receptacle situated at the location.

(114) In another example scenario, receiving the electronic signal (block **802**) includes receiving biometric information, such as a fingerprint or facial scan that is received at a scanning or camera interface of the on-site receptacle management electronic device **608**. Accordingly, in this example scenario, determining the identity of the customer based on the received electronic signal (block **805**) may include processing the biometric information and comparing the processed biometric information to stored biometric information.

(115) In yet another example scenario, receiving the electronic signal (block **802**) includes receiving a wireless transmission that is delivered directly between (i) a transceiver of the system **100** corresponding to receptacle, and (ii) a transceiver interface of a wireless electronic device that is located within wireless communication range of the transceiver corresponding to the receptacle, such as the customer's personal electronic device **315**. The transceiver corresponding to the receptacle may be a wireless transceiver that is disposed at the bank of receptacles **600** and that is communicatively coupled to the on-site receptacle management electronic device **608**, and optionally to the facility server **126** and/or the central processing system **140**. In some arrangements, each secured receptacle within the bank **600** may have its own respective wireless transceiver that is locally disposed at the receptacle, such as the wireless transceiver **312a** corresponding to and disposed at receptacle **305a** shown in FIG. 3. In some arrangements, a single wireless transceiver of the system **100** (not shown) may service multiple receptacles included in the bank of receptacles **600**. For example, a single wireless transceiver of the system **100** may be disposed proximate to or at the bank of receptacles **600** and may communicate with customer PEDs **315**, enterprise agent devices **320**, and other devices on behalf of any receptacle included in the bank **600**.

(116) In this example scenario, determining the identity of the customer (block **805**) based on the

received wireless transmission may be similar to that described previously with respect to block **502** of FIG. 5A. For instance, determining the customer's identity **805** may be based on the received wireless transmission's payload and/or header, an identification of the wireless electronic device (such as an IMEI, and MEID, and IMSI, and ESN, an ICC-ID of a card or chip included in the wireless electronic device, a TN, and/or another suitable identifier), an identification of an account of the customer with a retailer or enterprise, such as a loyalty account, an electronic or web-based account, etc., and/or of a user ID, login ID, or other customer-specific indicia associated therewith. In some embodiments, the identity of the customer may be determined based on an identifier of the client application **118** that is executing on the customer device **315**, e.g. as tracked by a server of the retailer **126** or enterprise **140**.

(117) At a block **808**, the method **800** may include determining whether or not the identified customer is an expected customer. For example, one or more stored associations between secured receptacles and customer/users may be accessed to determine whether or not the identified customer is associated with a secured receptacle disposed at the location. If the customer is determined to be an unexpected customer (e.g., the “no” leg of block **808**), the method **800** may include sending an electronic signal to a device **320** being operated by an agent of the retailer or enterprise (block **810**) to mitigate the situation. For example, the signal sent to the agent device (block **810**) may include an indication that the secured receptacle is to be manually unlocked, or that the situation requires an agent evaluation. Based on the signal, the agent may physically (or virtually, such as via a remote feed) dialog with the customer to resolve the situation, which may result in the agent manually unlocking the secured receptacle or remotely triggering an electronic unlocking of the secured receptacle, in some cases.

(118) At the block **808**, if the customer is determined to be an expected customer (e.g., the “yes” leg of block **808**), the method **800** may include automatically determining the corresponding receptacle and sending an electronic signal to trigger the unlocking of the electronic lock at the secured receptacle (block **812**). For example, automatically determining the receptacle corresponding to the identified, expected customer may include accessing a stored indication of an association between the identified, expected customer and a particular secured receptacle. The electronic signal sent to the electronic lock of the secured receptacle corresponding to the identified, expected customer may include an electronic unlock command or instruction, for example, and the electronic signal may be automatically sent to the electronic lock to unlock the secured receptacle (e.g., in a manner such as previously discussed with respect to the signal **445** of FIG. 4). Alternatively, an electronic signal indicating that the electronic lock may be remotely unlocked may be automatically sent to a device being operated by an agent of the retailer or enterprise, and the operating agent may cause a remote unlock signal or command to be transmitted from the agent device to the electronic lock (e.g., in a manner such as previously discussed with respect to the signal **452** of FIG. 4), to thereby unlock the receptacle so that the customer is able to access the receptacle.

(119) Further, at any time during the unlocking and accessing of the reserved receptacle (e.g., after the execution of the block **812**), should the customer require assistance, the customer may electronically request the physical and/or virtual assistance of enterprise agents and/or personnel, as indicated by the reference **815**. For example, the customer may request assistance (reference **815**) via the customer's PED **315** and/or via the on-site receptacle management device **805**, which may result in the method **800** sending an electronic signal to a device **320** being operated by an agent of the enterprise (block **810**) to notify the agent that customer assistance has been requested.

(120) Returning now to block **812**, in scenarios in which access to the secured receptacle is provided for the purposes of customer item pickup, upon execution of the block **810**, the method **800** may include the blocks **520-530** of FIG. 5B, e.g., to determine and/or verify that the items secured within the receptacle were indeed removed.

(121) At the block **812**, in scenarios in which access to the secured receptacle is provided for the

purposes of the customer loading one or more items into the receptacle, after triggering the unlocking of the reserved receptacle (block **812**), the customer may thereby have access to the unlocked, reserved receptacle. After the customer has finished loading the one or items into the receptacle, the customer may issue an electronic lock instruction, e.g., via the on-site receptacle management electronic device **608**, via the customer's PED **315**, or merely by closing the door, panel, lid, or other aperture cover of the receptacle. Accordingly, in these scenarios, the method **800** may include receiving an electronic lock instruction initiated by the customer (block **818**), and automatically locking and securing the receptacle based on the reception of the received lock instruction (block **820**). For example, at the block **820**, an electronic locking command may be sent to the electronic lock of the reserved receptacle, thereby causing the reserved receptacle to be locked and secured.

(122) In some scenarios, one or more sensors associated with the receptacle may detect the loading of the items into the receptacle. For example, the sensor **455a** and/or another type of sensor disposed at the receptacle **305a** (e.g., a weight sensor, an optical sensor, etc.) may detect the loading of items into the receptacle **305a**, and signals generated by the sensor(s) may be utilized in determining whether or not the receptacle should be secured, whether or not the customer and/or enterprise agent should be notified, etc.

(123) Based on the automatic securing of the receptacle (block **820**), the method **800** may include automatically sending an electronic notification to an agent of the retailer or enterprise (block **822**), where the notification may indicate that the customer's items have been secured within the reserved receptacle. For example, at the block **822**, the electronic notification may be delivered to an agent device **320**, the facility server **126**, and/or the central processing system **140**. At some time thereafter, enterprise personnel may access the secured receptacle to retrieve the items that have been loaded therein by the customer.

(124) This disclosure is intended to explain how to fashion and use various embodiments in accordance with the technology rather than to limit the true, intended, and fair scope and spirit thereof. The foregoing description is not intended to be exhaustive or to be limited to the precise forms disclosed. Modifications or variations are possible in light of the above teachings. The embodiment(s) were chosen and described to provide the best illustration of the principle of the described technology and its practical application, and to enable one of ordinary skill in the art to utilize the technology in various embodiments and with various modifications as are suited to the particular use contemplated. All such modifications and variations are within the scope of the embodiments as determined by the appended claims, as may be amended during the pendency of this application for patent, and all equivalents thereof, when interpreted in accordance with the breadth to which they are fairly, legally and equitably entitled.

## Claims

1. A method of automatically securing receptacles associated with an enterprise, the method comprising: receiving, via a wireless local interface associated with a security system, a wireless electronic signal directly delivered between a personal electronic device (PED) operated by an agent of a customer and the wireless local interface, the wireless local interface disposed at a location at which a plurality of receptacles associated with the enterprise is situated and secured by a plurality of electronic locks, and the PED located within wireless transmission range of a wireless transceiver of the wireless local interface; determining, by one or more processors of the security system, an identity of the agent of the customer and a particular receptacle, of the plurality of receptacles, that corresponds to the agent and into which an item corresponding to the customer has been received, the determination based on the received electronic signal and stored data that is indicative of interactions of the customer with the enterprise; and transmitting, via one or more communication interfaces communicatively connecting the security system with the plurality of

electronic locks, a deactivating instruction to a particular electronic lock securing the particular receptacle, thereby unsecuring the particular receptacle.

2. The method of claim 1, further comprising storing, in one or more data storage devices, associations between the plurality of receptacles and corresponding customers; and wherein the determining of the identity of the agent of the customer and the particular receptacle into which the item corresponding to the customer has been received is based on the stored associations.

3. The method of claim 1, further comprising, prior to the receiving of the wireless electronic signal, transmitting an activating instruction to the particular electronic lock thereby securing the particular receptacle into which the item has been received.

4. The method of claim 3, wherein the securing of the particular receptacle is based on a signal generated by a sensor, the signal indicating that the item has been received into the particular receptacle.

5. The method of claim 1, wherein the unsecuring of the particular receptacle is for a retrieval of the item from the particular receptacle, and the method further comprises re-securing the particular receptacle after the item has been retrieved from the particular receptacle.

6. The method of claim 1, wherein the determining of the identity of the agent of the customer is based on an access code.

7. The method of claim 1, further comprising determining, by the one or more processors and based on the identity of the agent of the customer, whether the agent is an expected agent of the customer, and wherein the transmitting of the deactivating instruction is responsive to determining that the agent of the customer is the expected agent of the customer.

8. The method of claim 1, wherein the particular electronic lock secures an agent-facing access mechanism of the particular receptacle, and the particular receptacle further includes an enterprise-facing access mechanism.

9. The method of claim 8, wherein the enterprise-facing access mechanism of the particular receptacle is secured by a respective electronic lock, and the method further comprises transmitting at least one of an activating instruction or a deactivating instruction to the respective electronic lock, thereby respectively at least one of securing or unsecuring the enterprise-facing access mechanism of the particular receptacle.

10. A system for automatically securing receptacles associated with an enterprise, the system comprising: one or more communication interfaces communicatively connecting the system to a plurality of electronic locks securing a plurality of receptacles associated with the enterprise; one or more processors; and one or more tangible, non-transitory computer-readable media storing computer-readable instructions that, when executed by the one or more processors, cause the system to: receive a wireless electronic signal directly delivered between a personal electronic device (PED) operated by an agent of a customer and a wireless local interface disposed at a location at which the plurality of receptacles associated with the enterprise is situated, the PED located within wireless transmission range of a wireless transceiver of the wireless local interface; determine, based on the wireless electronic signal, an identity of the agent of the customer and a particular receptacle, of the plurality of receptacles, that corresponds to the agent and into which an item corresponding to the customer has been received, the determination further based on stored data that is indicative of interactions of the customer with the enterprise; and transmit, via the one or more communication interfaces, a deactivating instruction to a particular electronic lock securing the particular receptacle, thereby unsecuring the particular receptacle.

11. The system of claim 10, further comprising one or more data storage devices storing associations between the plurality of receptacles and corresponding customers, and wherein the determination of the identity of the agent of the customer is based on the stored associations.

12. The system of claim 10, wherein the computer-readable instructions are further executable to: prior to the reception of the wireless electronic signal, transmit an activating instruction to the particular electronic lock to thereby secure the particular receptacle into which the item has been

received.

13. The system of claim 12, wherein the transmission of the activating instruction is based on a signal generated by a sensor, the signal indicating that the item has been received into the particular receptacle.

14. The system of claim 10, wherein the unsecuring of the particular receptacle is for a retrieval of the item from the particular receptacle, and the computer-readable instructions are further executable to re-secure the particular receptacle after the item has been retrieved from the particular receptacle.

15. The system of claim 10, wherein the determination of the identity of the agent of the customer is based on an access code.

16. The system of claim 10, wherein: the computer-readable instructions are further executable to determine, based on the identity of the agent of the customer, whether the agent is an expected agent of the customer; and the transmission of the deactivating instruction is responsive to a determination that the agent of the customer is the expected agent of the customer.

17. The system of claim 10, wherein the particular electronic lock secures an agent-facing access mechanism of the particular receptacle, and the particular receptacle further includes an enterprise-facing access mechanism.

18. The system of claim 17, further comprising a respective electronic lock securing the enterprise-facing access mechanism of the particular receptacle.

---