

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408002
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Wu; Zhibin et al.

Transmission with indication of geographic area

Abstract

An improved manner of transmitting and receiving messages in sidelink communication is presented in which a wireless device receives sidelink control information (SCI) that indicates a zone ID associated with a sidelink message. The wireless device determines a location of the wireless device and determines whether to send feedback for the sidelink message based, at least in part, on the zone ID associated with the sidelink message and the location of the wireless device. The feedback may include hybrid automatic repeat request (HARQ) feedback, and the sidelink message may include a groupcast message. The wireless device may further receive an indication of an intended range in the SCI and may determine whether to send the feedback based on a combination of the zone ID and the intended range for the sidelink message.

Inventors: Wu; Zhibin (Los Altos, CA), Baghel; Sudhir Kumar (Hillsborough, NJ), Gulati; Kapil (Hillsborough, NJ), Bharadwaj; Arjun (Cupertino, CA), Cheng; Hong (Bridgewater, NJ), Patil; Shailesh (San Diego, CA), Li; Junyi (Chester, NJ)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 69883837

Assignee: QUALCOMM Incorporated (San Diego, CA)

Appl. No.: 16/861894

Filed: April 29, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200260214 A1	Aug. 13, 2020

Related U.S. Application Data

continuation parent-doc US 16549453 20190823 PENDING child-doc US 16861894

Publication Classification

Int. Cl.: **H04W4/02** (20180101); **H04L5/00** (20060101); **H04W4/12** (20090101); **H04W4/40** (20180101); **H04W28/02** (20090101); **H04W72/20** (20230101)

U.S. Cl.:

CPC **H04W4/02** (20130101); **H04L5/0055** (20130101); **H04W4/12** (20130101); **H04W4/40** (20180201); **H04W28/0268** (20130101); **H04W72/20** (20230101);

Field of Classification Search

CPC: H04W (4/02); H04W (4/40); H04W (72/0406); H04W (4/12); H04W (28/0268); H04L (5/0055)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7089264	12/2005	Guido et al.	N/A	N/A
9363782	12/2015	Tenny	N/A	N/A
9961487	12/2017	Miao	N/A	H04W 4/029
10694460	12/2019	Ingale	N/A	H04W 48/20
11546095	12/2022	Kim	N/A	H04L 1/1812
11563528	12/2022	Ryu	N/A	H04W 4/023
11616629	12/2022	Kim	370/329	H04W 72/20
2011/0305158	12/2010	Kim et al.	N/A	N/A
2014/0105121	12/2013	Jose et al.	N/A	N/A
2015/0011230	12/2014	Noh et al.	N/A	N/A
2015/0045061	12/2014	Da	N/A	N/A
2015/0327201	12/2014	He et al.	N/A	N/A
2016/0056940	12/2015	Chae	370/312	H04L 5/0055
2016/0302137	12/2015	Escott et al.	N/A	N/A
2016/0323923	12/2015	Wei	N/A	N/A
2016/0337935	12/2015	Patil et al.	N/A	N/A
2016/0338095	12/2015	Faurie	N/A	H04W 72/23
2017/0048922	12/2016	Lee	N/A	H04W 76/38
2017/0134080	12/2016	Rahman	N/A	H04L 5/0048
2017/0150314	12/2016	Hwang et al.	N/A	N/A
2017/0195163	12/2016	Chae et al.	N/A	N/A
2018/0054693	12/2017	Agiwal et al.	N/A	N/A
2018/0115911	12/2017	Huang et al.	N/A	N/A
2018/0124574	12/2017	Byun et al.	N/A	N/A
2018/0124771	12/2017	Mok et al.	N/A	N/A
2018/0139724	12/2017	Loehr et al.	N/A	N/A
2018/0152927	12/2017	Kim et al.	N/A	N/A
2018/0213382	12/2017	Tabet et al.	N/A	N/A

2018/0254820	12/2017	Chae et al.	N/A	N/A
2018/0270022	12/2017	Sun et al.	N/A	N/A
2018/0367261	12/2017	Gonzalves Serrano et al.	N/A	N/A
2019/0007974	12/2018	Nguyen	N/A	H04L 67/12
2019/0044667	12/2018	Guo et al.	N/A	N/A
2019/0052436	12/2018	Desai	N/A	H04L 1/18
2019/0053194	12/2018	Wei	N/A	H04B 17/318
2019/0053204	12/2018	Lien	N/A	H04L 1/0023
2019/0059071	12/2018	Khoryaev	N/A	H04W 4/021
2019/0075447	12/2018	Lee et al.	N/A	N/A
2019/0090250	12/2018	Lee et al.	N/A	N/A
2019/0116475	12/2018	Lee et al.	N/A	N/A
2019/0158993	12/2018	Kwon	N/A	N/A
2019/0174271	12/2018	Fujishiro et al.	N/A	N/A
2019/0174479	12/2018	Yamazaki et al.	N/A	N/A
2019/0320358	12/2018	Knapp	N/A	H04W 52/0241
2019/0335532	12/2018	Kim	N/A	H04W 4/90
2019/0364402	12/2018	Lee	N/A	H04W 4/80
2019/0394786	12/2018	Parron	N/A	H04L 27/0006
2020/0029318	12/2019	Guo	N/A	H04W 88/023
2020/0040867	12/2019	Leege	N/A	F03C 1/0686
2020/0092685	12/2019	Fehrenbach	N/A	H04B 7/2606
2020/0099476	12/2019	Park	N/A	H04L 1/1812
2020/0100048	12/2019	Wu et al.	N/A	N/A
2020/0100167	12/2019	Cheng	N/A	H04W 4/40
2020/0100255	12/2019	Wu et al.	N/A	N/A
2020/0106566	12/2019	Yeo	N/A	H04W 28/04
2020/0162864	12/2019	Lee	N/A	H04L 5/0055
2020/0178290	12/2019	Lee et al.	N/A	N/A
2020/0196279	12/2019	Thomas et al.	N/A	N/A
2020/0228951	12/2019	Chun	N/A	H04W 76/50
2020/0296796	12/2019	Uchiyama	N/A	H04W 72/02
2020/0323023	12/2019	Miao	N/A	H04W 76/14
2020/0351033	12/2019	Ryu	N/A	H04L 1/1861
2021/0068071	12/2020	Wu	N/A	G01S 19/51
2021/0112445	12/2020	Wu	N/A	H04W 28/04
2021/0168648	12/2020	Lee et al.	N/A	N/A
2021/0203453	12/2020	Kim	N/A	H04L 1/1819
2021/0235246	12/2020	Hovey	N/A	H04W 80/02
2021/0242975	12/2020	Kim	N/A	H04L 27/2607
2021/0266212	12/2020	Chae et al.	N/A	N/A
2021/0266921	12/2020	Wang	N/A	H04B 17/318
2021/0314126	12/2020	Bae et al.	N/A	N/A
2021/0351877	12/2020	Xu	N/A	H04W 72/0446

2022/0190966	12/2021	Hosseini	N/A	H04L 5/0055
2022/0393834	12/2021	Thomas	N/A	H04W 72/20
2023/0102142	12/2022	Kim	370/329	H04W 72/0446
2023/0292397	12/2022	Kung	370/311	H04W 42/1263

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102754459	12/2011	CN	N/A
104661177	12/2014	CN	N/A
116366221	12/2022	CN	N/A
3644644	12/2019	EP	N/A
2012178016	12/2011	WO	N/A
2014062459	12/2013	WO	N/A
2017103662	12/2016	WO	N/A
2017146534	12/2016	WO	N/A
2017155320	12/2016	WO	N/A
2018084608	12/2017	WO	N/A
2018125686	12/2017	WO	N/A
2020033089	12/2019	WO	N/A
2020064304	12/2019	WO	N/A
WO-2021091089	12/2020	WO	N/A
WO-2021141408	12/2020	WO	N/A

OTHER PUBLICATIONS

Park Foreign priority application data; Sep. 21, 2018, KT Corporation (Year: 2018). cited by examiner

International Search Report and Written Opinion—PCT/US2019/048171—ISA/EPO—dated Nov. 14, 2019. cited by applicant

Kondo T., et al., “A Design and Evaluation of a Geolocation-Aware Reliable Multi cast System on Wireless Networks”, Applications and the Internet (SAINT) 2011 IEEE/IPSJ 11th International Symposium on, IEEE, Jul. 18, 2011, pp. 408-413, XP032047114, DOI: 10.1109/SAINT.2011.77, ISBN: 978-1-4577-0531-1, section III, figures 3-6. cited by applicant

Taiwan Search Report—TW108130447—TIPO—dated Oct. 5, 2022. cited by applicant

OPPO., et al., “Correction for Zoning”, R2-1811097, 3GPP TSG-RAN WG2 Meeting#103, Gothenburg, Sweden, Aug. 20-24, 2018, 6 Pages. cited by applicant

OPPO., et al., “Correction for Zoning”, R2-1813185, 3GPP TSG-RAN WG2 Meeting#103, Gothenburg, Sweden, Aug. 20-24, 2018, 7 Pages. cited by applicant

ONE2ONE, et al., “Proposed Version 2 of TR 21.905, 3GPP Vocabulary”, 3GPP TSG SA S1#7, S1-000091, Sofia Antipolis, Feb. 9-11, 2000, 33 Pages. cited by applicant

European Search Report—EP23208107—Search Authority—The Hague—Apr. 25, 2024. cited by applicant

Taiwan Search Report—TW112140105—TIPO—Aug. 1, 2024. cited by applicant

Primary Examiner: Belur; Deepa

Attorney, Agent or Firm: Procopio, Cory, Hargreaves & Savitch LLP/QUALCOMM Incorporated

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a Continuation of U.S. patent application Ser. No. 16/549,453, entitled “TRANSMISSION WITH INDICATION OF GEOGRAPHIC AREA” and filed on Aug. 23, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/737,086, entitled “Transmission with Indication of Geographic Area” and filed on Sep. 26, 2018, which are expressly incorporated by reference herein in their entirety.

INTRODUCTION

(1) The present disclosure relates generally to communication systems, and more particularly, to a vehicle-to-vehicle (V2V), vehicle-to-everything (V2X), or other device-to-device (D2D) communication.

(2) Wireless communication systems are widely deployed to provide various telecommunication services such as telephony, video, data, messaging, and broadcasts. Typical wireless communication systems may employ multiple-access technologies capable of supporting communication with multiple users by sharing available system resources. Examples of such multiple-access technologies include code division multiple access (CDMA) systems, time division multiple access (TDMA) systems, frequency division multiple access (FDMA) systems, orthogonal frequency division multiple access (OFDMA) systems, single-carrier frequency division multiple access (SC-FDMA) systems, and time division synchronous code division multiple access (TD-SCDMA) systems.

(3) These multiple access technologies have been adopted in various telecommunication standards to provide a common protocol that enables different wireless devices to communicate on a municipal, national, regional, and even global level. An example telecommunication standard is 5G New Radio (NR). 5G NR is part of a continuous mobile broadband evolution promulgated by Third Generation Partnership Project (3GPP) to meet new requirements associated with latency, reliability, security, scalability (e.g., with Internet of Things (IoT)), and other requirements. 5G NR includes services associated with enhanced mobile broadband (eMBB), massive machine type communications (mMTC), and ultra reliable low latency communications (URLLC). Some aspects of 5G NR may be based on the 4G Long Term Evolution (LTE) standard. There exists a need for further improvements in 5G NR technology. These improvements may also be applicable to other multi-access technologies and the telecommunication standards that employ these technologies.

SUMMARY

(4) The following presents a simplified summary of one or more aspects in order to provide a basic understanding of such aspects. This summary is not an extensive overview of all contemplated aspects, and is intended to neither identify key or critical elements of all aspects nor delineate the scope of any or all aspects. Its sole purpose is to present some concepts of one or more aspects in a simplified form as a prelude to the more detailed description that is presented later.

(5) In an aspect of the disclosure, a method, a computer-readable medium, and an apparatus are provided for wireless communication at a wireless device. The wireless device receives sidelink control information (SCI) that indicates a zone ID associated with a sidelink message. The wireless device determines a location of the wireless device. The wireless device determines whether to send feedback for the sidelink message based, at least in part, on the zone ID associated with the sidelink message and the location of the wireless device.

(6) In another aspect of the disclosure, a method, a computer-readable medium, and an apparatus are provided for wireless communication at a wireless device. The wireless device determines a geographic location of the wireless device. The wireless device transmits SCI associated with a sidelink message, the SCI comprising a zone ID based, at least in part, on the geographic location of the wireless device.

(7) To the accomplishment of the foregoing and related ends, the one or more aspects comprise the features hereinafter fully described and particularly pointed out in the claims. The following description and the annexed drawings set forth in detail certain illustrative features of the one or more aspects. These features are indicative, however, of but a few of the various ways in which the principles of various aspects may be employed, and this description is intended to include all such aspects and their equivalents.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram illustrating an example of a wireless communications system and an access network.
- (2) FIG. 2 illustrates example aspects of a sidelink slot structure.
- (3) FIG. 3 is a diagram illustrating an example of a first device and a second device involved in wireless communication based, e.g., on V2V, V2X, and/or device-to-device communication.
- (4) FIG. 4 illustrates an example of communication between UEs.
- (5) FIG. 5 illustrates an example communication flow between UEs.
- (6) FIG. 6 is a flowchart of a method of wireless communication.
- (7) FIG. 7 is a conceptual data flow diagram illustrating the data flow between different means/components in an example apparatus.
- (8) FIG. 8 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.
- (9) FIG. 9 is a flowchart of a method of wireless communication.
- (10) FIG. 10 is a conceptual data flow diagram illustrating the data flow between different means/components in an example apparatus.
- (11) FIG. 11 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system.
- (12) FIG. 12 illustrates an example interaction between different layers at a transmitting device and a receiving device.
- (13) FIG. 13 illustrates an example interaction between different layers at a transmitting device and a receiving device.

DETAILED DESCRIPTION

(14) The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well known structures and components are shown in block diagram form in order to avoid obscuring such concepts.

(15) Several aspects of telecommunication systems will now be presented with reference to various apparatus and methods. These apparatus and methods will be described in the following detailed description and illustrated in the accompanying drawings by various blocks, components, circuits, processes, algorithms, etc. (collectively referred to as “elements”). These elements may be implemented using electronic hardware, computer software, or any combination thereof. Whether such elements are implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system.

(16) By way of example, an element, or any portion of an element, or any combination of elements may be implemented as a “processing system” that includes one or more processors. Examples of processors include microprocessors, microcontrollers, graphics processing units (GPUs), central

processing units (CPUs), application processors, digital signal processors (DSPs), reduced instruction set computing (RISC) processors, systems on a chip (SoC), baseband processors, field programmable gate arrays (FPGAs), programmable logic devices (PLDs), state machines, gated logic, discrete hardware circuits, and other suitable hardware configured to perform the various functionality described throughout this disclosure. One or more processors in the processing system may execute software. Software shall be construed broadly to mean instructions, instruction sets, code, code segments, program code, programs, subprograms, software components, applications, software applications, software packages, routines, subroutines, objects, executables, threads of execution, procedures, functions, etc., whether referred to as software, firmware, middleware, microcode, hardware description language, or otherwise.

(17) Accordingly, in one or more examples, the functions described may be implemented in hardware, software, or any combination thereof. If implemented in software, the functions may be stored on or encoded as one or more instructions or code on a computer-readable medium.

Computer-readable media includes computer storage media. Storage media may be any available media that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise a random-access memory (RAM), a read-only memory (ROM), an electrically erasable programmable ROM (EEPROM), optical disk storage, magnetic disk storage, other magnetic storage devices, combinations of the aforementioned types of computer-readable media, or any other medium that can be used to store computer executable code in the form of instructions or data structures that can be accessed by a computer.

(18) Wireless communication may involve transmissions from a transmitting device for receipt by at least one receiving device. For example, a transmitting device may transmit a message via V2V/V2X/D2D to a receiving vehicle. As an example, the message may be multicast from the transmitting device and should be reliably received by certain receiving devices, e.g., devices for a corresponding service group, within a certain area including the transmitting device. In order to ensure that the message is reliably delivered to the receiving device(s), the transmitting device may listen for feedback from receiving devices(s) to determine whether the message was received correctly. Receiving device(s) may provide feedback. For example, receiving device(s) that do not successfully receive the message may respond to the transmitting device, e.g., with a Negative Acknowledgement (NACK). The NACK may prompt the transmitting device to retransmit the message. However, a receiving device that is distant from the transmitting device may respond with a NACK causing the transmitting device to retransmit the message in futile. Such feedback and wasted retransmissions for receiving devices that are at an undesirable proximity to the transmitting device degrade system performance. This problem may be especially challenging in a V2X/V2V/D2D environment due to the highly mobile nature of transmitters and/or receivers.

(19) Aspects presented herein provide solutions in which feedback can be limited from receivers outside of an intended geographical area by providing information from the transmitting device to the receiving device that enables the receiving device to determine whether it is an intended receiver of the message. The receiving device can then determine whether to send feedback based on whether or not the receiving device is an intended receiver of the message in order to limit feedback from a receiving device that is not within the intended area.

(20) FIG. 1 is a diagram illustrating an example of a wireless communications system and an access network **100**. The wireless communications system (also referred to as a wireless wide area network (WWAN)) includes base stations **102**, UEs **104**, an Evolved Packet Core (EPC) **160**, and a Core Network (e.g., 5GC) **190**. The base stations **102** may include macro cells (high power cellular base station) and/or small cells (low power cellular base station). The macro cells include base stations. The small cells include femtocells, picocells, and microcells.

(21) The base stations **102** configured for 4G LTE (collectively referred to as Evolved Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access Network (E-UTRAN)) may interface with the EPC **160** through backhaul links **132** (e.g., S1 interface). The base stations **102**

configured for NR (collectively referred to as Next Generation RAN (NG-RAN)) may interface with Core Network **190** through backhaul links **184**. In addition to other functions, the base stations **102** may perform one or more of the following functions: transfer of user data, radio channel ciphering and deciphering, integrity protection, header compression, mobility control functions (e.g., handover, dual connectivity), inter-cell interference coordination, connection setup and release, load balancing, distribution for non-access stratum (NAS) messages, NAS node selection, synchronization, radio access network (RAN) sharing, multimedia broadcast multicast service (MBMS), subscriber and equipment trace, RAN information management (RIM), paging, positioning, and delivery of warning messages. The base stations **102** may communicate directly or indirectly (e.g., through the EPC **160** or Core Network **190**) with each other over backhaul links **134** (e.g., X2 interface). The backhaul links **134** may be wired or wireless.

(22) The base stations **102** may wirelessly communicate with the UEs **104**. Each of the base stations **102** may provide communication coverage for a respective geographic coverage area **110**. There may be overlapping geographic coverage areas **110**. For example, the small cell **102'** may have a coverage area **110'** that overlaps the coverage area **110** of one or more macro base stations **102**. A network that includes both small cell and macro cells may be known as a heterogeneous network. A heterogeneous network may also include Home Evolved Node Bs (eNBs) (HeNBs), which may provide service to a restricted group known as a closed subscriber group (CSG). The communication links **120** between the base stations **102** and the UEs **104** may include uplink (UL) (also referred to as reverse link) transmissions from a UE **104** to a base station **102** and/or downlink (DL) (also referred to as forward link) transmissions from a base station **102** to a UE **104**. The communication links **120** may use multiple-input and multiple-output (MIMO) antenna technology, including spatial multiplexing, beamforming, and/or transmit diversity. The communication links may be through one or more carriers. The base stations **102**/UEs **104** may use spectrum up to Y MHz (e.g., 5, 10, 15, 20, 100, 400, etc. MHz) bandwidth per carrier allocated in a carrier aggregation of up to a total of Yx MHz (x component carriers) used for transmission in each direction. The carriers may or may not be adjacent to each other. Allocation of carriers may be asymmetric with respect to DL and UL (e.g., more or less carriers may be allocated for DL than for UL). The component carriers may include a primary component carrier and one or more secondary component carriers. A primary component carrier may be referred to as a primary cell (PCell) and a secondary component carrier may be referred to as a secondary cell (SCell).

(23) Certain UEs **104** may communicate with each other using device-to-device (D2D) communication link **158**. The D2D communication link **158** may use the DL/UL WWAN spectrum. The D2D communication link **158** may use one or more sidelink channels, such as a physical sidelink broadcast channel (PSBCH), a physical sidelink discovery channel (PSDCH), a physical sidelink shared channel (PSSCH), and a physical sidelink control channel (PSCCH). D2D communication may be through a variety of wireless D2D communications systems, such as for example, FlashLinQ, WiMedia, Bluetooth, ZigBee, Wi-Fi based on the IEEE 802.11 standard, LTE, or NR.

(24) The wireless communications system may further include a Wi-Fi access point (AP) **150** in communication with Wi-Fi stations (STAs) **152** via communication links **154** in a 5 GHz unlicensed frequency spectrum. When communicating in an unlicensed frequency spectrum, the STAs **152**/AP **150** may perform a clear channel assessment (CCA) prior to communicating in order to determine whether the channel is available.

(25) The small cell **102'** may operate in a licensed and/or an unlicensed frequency spectrum. When operating in an unlicensed frequency spectrum, the small cell **102'** may employ NR and use the same 5 GHz unlicensed frequency spectrum as used by the Wi-Fi AP **150**. The small cell **102'**, employing NR in an unlicensed frequency spectrum, may boost coverage to and/or increase capacity of the access network.

(26) A base station **102**, whether a small cell **102'** or a large cell (e.g., macro base station), may

include an eNB, gNodeB (gNB), or other type of base station. Some base stations, such as gNB **180** may operate in a traditional sub 6 GHz spectrum, in millimeter wave (mmW) frequencies, and/or near mmW frequencies in communication with the UE **104**. When the gNB **180** operates in mmW or near mmW frequencies, the gNB **180** may be referred to as an mmW base station. Extremely high frequency (EHF) is part of the RF in the electromagnetic spectrum. EHF has a range of 30 GHz to 300 GHz and a wavelength between 1 millimeter and 10 millimeters. Radio waves in the band may be referred to as a millimeter wave. Near mmW may extend down to a frequency of 3 GHz with a wavelength of 100 millimeters. The super high frequency (SHF) band extends between 3 GHz and 30 GHz, also referred to as centimeter wave. Communications using the mmW/near mmW radio frequency band has extremely high path loss and a short range. The mmW base station **180** may utilize beamforming **182** with the UE **104** to compensate for the extremely high path loss and short range.

(27) Devices may use beamforming to transmit and receive communication. For example, FIG. **1** illustrates that a base station **180** may transmit a beamformed signal to the UE **104** in one or more transmit directions **182'**. The UE **104** may receive the beamformed signal from the base station **180** in one or more receive directions **182''**. The UE **104** may also transmit a beamformed signal to the base station **180** in one or more transmit directions. The base station **180** may receive the beamformed signal from the UE **104** in one or more receive directions. The base station **180**/UE **104** may perform beam training to determine the best receive and transmit directions for each of the base station **180**/UE **104**. The transmit and receive directions for the base station **180** may or may not be the same. The transmit and receive directions for the UE **104** may or may not be the same. Although beamformed signals are illustrated between UE **104** and base station **102/180**, aspects of beamforming may similarly may be applied by UE **104** or RSU **107** to communicate with another UE **104** or RSU **107**, such as based on V2X, V2V, or D2D communication.

(28) The EPC **160** may include a Mobility Management Entity (MME) **162**, other MMEs **164**, a Serving Gateway **166**, a Multimedia Broadcast Multicast Service (MBMS) Gateway **168**, a Broadcast Multicast Service Center (BM-SC) **170**, and a Packet Data Network (PDN) Gateway **172**. The MME **162** may be in communication with a Home Subscriber Server (HSS) **174**. The MME **162** is the control node that processes the signaling between the UEs **104** and the EPC **160**. Generally, the MME **162** provides bearer and connection management. All user Internet protocol (IP) packets are transferred through the Serving Gateway **166**, which itself is connected to the PDN Gateway **172**. The PDN Gateway **172** provides UE IP address allocation as well as other functions. The PDN Gateway **172** and the BM-SC **170** are connected to the IP Services **176**. The IP Services **176** may include the Internet, an intranet, an IP Multimedia Subsystem (IMS), a PS Streaming Service, and/or other IP services. The BM-SC **170** may provide functions for MBMS user service provisioning and delivery. The BM-SC **170** may serve as an entry point for content provider MBMS transmission, may be used to authorize and initiate MBMS Bearer Services within a public land mobile network (PLMN), and may be used to schedule MBMS transmissions. The MBMS Gateway **168** may be used to distribute MBMS traffic to the base stations **102** belonging to a Multicast Broadcast Single Frequency Network (MBSFN) area broadcasting a particular service, and may be responsible for session management (start/stop) and for collecting eMBMS related charging information.

(29) The Core Network **190** may include an Access and Mobility Management Function (AMF) **192**, other AMFs **193**, a Session Management Function (SMF) **194**, and a User Plane Function (UPF) **195**. The AMF **192** may be in communication with a Unified Data Management (UDM) **196**. The AMF **192** is the control node that processes the signaling between the UEs **104** and the Core Network **190**. Generally, the AMF **192** provides QoS flow and session management. All user Internet protocol (IP) packets are transferred through the UPF **195**. The UPF **195** provides UE IP address allocation as well as other functions. The UPF **195** is connected to the IP Services **197**. The IP Services **197** may include the Internet, an intranet, an IP Multimedia Subsystem (IMS), a PS

Streaming Service, and/or other IP services.

(30) The base station may also be referred to as a gNB, Node B, evolved Node B (eNB), an access point, a base transceiver station, a radio base station, a radio transceiver, a transceiver function, a basic service set (BSS), an extended service set (ESS), a transmit reception point (TRP), or some other suitable terminology. The base station **102** provides an access point to the EPC **160** or Core Network **190** for a UE **104**. Examples of UEs **104** include a cellular phone, a smart phone, a session initiation protocol (SIP) phone, a laptop, a personal digital assistant (PDA), a satellite radio, a global positioning system, a multimedia device, a video device, a digital audio player (e.g., MP3 player), a camera, a game console, a tablet, a smart device, a wearable device, a vehicle, an electric meter, a gas pump, a large or small kitchen appliance, a healthcare device, an implant, a sensor/actuator, a display, or any other similar functioning device. Some of the UEs **104** may be referred to as IoT devices (e.g., parking meter, gas pump, toaster, vehicles, heart monitor, etc.). The UE **104** may also be referred to as a station, a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology.

(31) Some wireless communication networks may include vehicle-based communication devices that can communicate from vehicle-to-vehicle (V2V), vehicle-to-infrastructure (V2I) (e.g., from the vehicle-based communication device to road infrastructure nodes such as a Road Side Unit (RSU)), vehicle-to-network (V2N) (e.g., from the vehicle-based communication device to one or more network nodes, such as a base station), and/or a combination thereof and/or with other devices, which can be collectively referred to as vehicle-to-anything (V2X) communications. Referring again to FIG. **1**, in certain aspects, a UE **104**, e.g., a transmitting Vehicle User Equipment (VUE) or other UE, may be configured to transmit messages directly to another UE **104**. The communication may be based on V2V/V2X/V2I or other D2D communication, such as Proximity Services (ProSe), etc. Communication based on V2V, V2X, V2I, and/or D2D may also be transmitted and received by other transmitting and receiving devices, such as Road Side Unit (RSU) **107**, etc. Aspects of the communication may be based on PC5 or sidelink communication e.g., as described in connection with the example in FIG. **2**. Although the following description may provide examples for V2X/D2D communication in connection with 5G NR, the concepts described herein may be applicable to other similar areas, such as LTE, LTE-A, CDMA, GSM, and other wireless technologies.

(32) Referring again to FIG. **1**, in certain aspects, a UE **104** may be configured to transmit messages directly to another UE **104**, e.g., UE. The communication may be based on V2V/V2X or other D2D communication, such as Proximity Services (ProSe). Aspects presented herein improve reliability of communication between the devices, e.g., engaged in PC5 based communication, while avoiding inefficient use of resources to retransmit to distant receivers. For example, the transmitting device, whether a UE, RSU, or base station, may determine its geographic location and may comprise a message component **198** that is configured to generate a message for a service group having a first indication of a geographic area associated with the message, the geographic area based at least in part on the geographic location of the mobile transmitting device. The message may also comprise group ID information. The transmitting device may then transmit the message, e.g. via V2X/V2V/D2D, to the service group. A receiving device, whether a UE, RSU, or base station, may receive the message. The message may comprise an indication of a geographic area associated with the message. The receiving device, e.g., UE **104**, may determine a geographic location of the UE **104**. The UE **104** may include a determination component **199** configured to determine whether to send a feedback for the message based on the first indication of the geographic area associated with the multicast message and the geographic location of the receiving device.

(33) FIG. 2 illustrates example diagrams **200** and **210** illustrating examples slot structures that may be used for wireless communication between UE **104** and UE **104'**, e.g., for sidelink communication. The slot structure may be within a 5G/NR frame structure. Although the following description may be focused on 5G NR, the concepts described herein may be applicable to other similar areas, such as LTE, LTE-A, CDMA, GSM, and other wireless technologies. This is merely one example, and other wireless communication technologies may have a different frame structure and/or different channels. A frame (10 ms) may be divided into 10 equally sized subframes (1 ms). Each subframe may include one or more time slots. Subframes may also include mini-slots, which may include 7, 4, or 2 symbols. Each slot may include 7 or 14 symbols, depending on the slot configuration. For slot configuration 0, each slot may include 14 symbols, and for slot configuration 1, each slot may include 7 symbols. Diagram **200** illustrates a single slot transmission, e.g., which may correspond to a 0.5 ms transmission time interval (TTI). Diagram **210** illustrates an example two-slot aggregation, e.g., an aggregation of two 0.5 ms TTIs. Diagram **200** illustrates a single RB, whereas diagram **210** illustrates N RBs. In diagram **210**, 10 RBs being used for control is merely one example. The number of RBs may differ.

(34) A resource grid may be used to represent the frame structure. Each time slot may include a resource block (RB) (also referred to as physical RBs (PRBs)) that extends **12** consecutive subcarriers. The resource grid is divided into multiple resource elements (REs). The number of bits carried by each RE depends on the modulation scheme. As illustrated in FIG. 2, some of the REs may comprise control information, e.g., along with demodulation RS (DMRS). FIG. 2 also illustrates that symbol(s) may comprise CSI-RS. The symbols in FIG. 2 that are indicated for DMRS or CSI-RS indicate that the symbol comprises DMRS or CSI-RS REs. Such symbols may also comprise REs that include data. For example, if a number of ports for DMRS or CSI-RS is 1 and a comb-2 pattern is used for DMRS/CSI-RS, then half of the REs may comprise the RS and the other half of the REs may comprise data. A CSI-RS resource may start at any symbol of a slot, and may occupy 1, 2, or 4 symbols depending on a configured number of ports. CSI-RS can be periodic, semi-persistent, or aperiodic (e.g., based on DCI triggering). For time/frequency tracking, CSI-RS may be either periodic or aperiodic. CSI-RS may be transmitted in bursts of two or four symbols that are spread across one or two slots. The control information may comprise Sidelink Control Information (SCI). At least one symbol may be used for feedback, as described herein. A symbol prior to and/or after the feedback may be used for turnaround between reception of data and transmission of the feedback. Although symbol **12** is illustrated for data, it may instead be a gap symbol to enable turnaround for feedback in symbol **13**. Another symbol, e.g., at the end of the slot may be used as a gap. The gap enables a device to switch from operating as a transmitting device to prepare to operate as a receiving device, e.g., in the following slot. Data may be transmitted in the remaining REs, as illustrated. The data may comprise the data message described herein. The position of any of the SCI, feedback, and LBT symbols may be different than the example illustrated in FIG. 2. Multiple slots may be aggregated together. FIG. 2 also illustrates an example aggregation of two slots. The aggregated number of slots may also be larger than two. When slots are aggregated, the symbols used for feedback and/or a gap symbol may be different than for a single slot. While feedback is not illustrated for the aggregated example, symbol(s) in a multiple slot aggregation may also be allocated for feedback, as illustrated in the one slot example.

(35) FIG. 3 is a diagram of a first wireless communication device **310** in communication with a second wireless communication device **350** via V2V/V2X/D2D communication, e.g., via sidelink. The device **350** may comprise a UE communicating with other another device **350** via V2V/V2X/D2D communication, e.g., via sidelink. The first wireless communication device **310** may comprise a UE communicating with another UE, e.g., device **350**, via sidelink. In addition to the other components illustrated in FIG. 3, devices **310** and **350** may each comprise a message component **391**, **393** and/or a determination component **392**, **394**. The message component **391**, **393** may be configured to generate a message having a first indication of a geographic area

associated with the message, the geographic area based at least in part on the geographic location of the device **310**, **350** that transmits the message. The determination component **392**, **394** may be configured to determine whether to send a feedback for the message based on the first indication of the geographic area associated with the multicast message and the geographic location of the receiving device. Packets may be provided to a controller/processor **375** that implements layer 3 and layer 2 functionality. Layer 3 includes a radio resource control (RRC) layer, and layer 2 includes a packet data convergence protocol (PDCP) layer, a radio link control (RLC) layer, and a medium access control (MAC) layer.

(36) The transmit (TX) processor **316** and the receive (RX) processor **370** implement layer 1 functionality associated with various signal processing functions. Layer 1, which includes a physical (PHY) layer, may include error detection on the transport channels, forward error correction (FEC) coding/decoding of the transport channels, interleaving, rate matching, mapping onto physical channels, modulation/demodulation of physical channels, and MIMO antenna processing. The TX processor **316** handles mapping to signal constellations based on various modulation schemes (e.g., binary phase-shift keying (BPSK), quadrature phase-shift keying (QPSK), M-phase-shift keying (M-PSK), M-quadrature amplitude modulation (M-QAM)). The coded and modulated symbols may then be split into parallel streams. Each stream may then be mapped to an OFDM subcarrier, multiplexed with a reference signal (e.g., pilot) in the time and/or frequency domain, and then combined together using an Inverse Fast Fourier Transform (IFFT) to produce a physical channel carrying a time domain OFDM symbol stream. The OFDM stream is spatially precoded to produce multiple spatial streams. Channel estimates from a channel estimator **374** may be used to determine the coding and modulation scheme, as well as for spatial processing. The channel estimate may be derived from a reference signal and/or channel condition feedback transmitted by the device **350**. Each spatial stream may then be provided to a different antenna **320** via a separate transmitter **318TX**. Each transmitter **318TX** may modulate an RF carrier with a respective spatial stream for transmission.

(37) At the device **350**, each receiver **354RX** receives a signal through its respective antenna **352**. Each receiver **354RX** recovers information modulated onto an RF carrier and provides the information to the receive (RX) processor **356**. The TX processor **368** and the RX processor **356** implement layer 1 functionality associated with various signal processing functions. The RX processor **356** may perform spatial processing on the information to recover any spatial streams destined for the device **350**. If multiple spatial streams are destined for the device **350**, they may be combined by the RX processor **356** into a single OFDM symbol stream. The RX processor **356** then converts the OFDM symbol stream from the time-domain to the frequency domain using a Fast Fourier Transform (FFT). The frequency domain signal comprises a separate OFDM symbol stream for each subcarrier of the OFDM signal. The symbols on each subcarrier, and the reference signal, are recovered and demodulated by determining the most likely signal constellation points transmitted by device **310**. These soft decisions may be based on channel estimates computed by the channel estimator **358**. The soft decisions are then decoded and deinterleaved to recover the data and control signals that were originally transmitted by device **310** on the physical channel. The data and control signals are then provided to the controller/processor **359**, which implements layer 3 and layer 2 functionality.

(38) The controller/processor **359** can be associated with a memory **360** that stores program codes and data. The memory **360** may be referred to as a computer-readable medium. The controller/processor **359** may provide demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, and control signal processing. The controller/processor **359** is also responsible for error detection using an ACK and/or NACK protocol to support HARQ operations.

(39) Similar to the functionality described in connection with the transmission by device **310**, the controller/processor **359** may provide RRC layer functionality associated with system information

(e.g., MIB, SIBs) acquisition, RRC connections, and measurement reporting; PDCP layer functionality associated with header compression/decompression, and security (ciphering, deciphering, integrity protection, integrity verification); RLC layer functionality associated with the transfer of upper layer PDUs, error correction through ARQ, concatenation, segmentation, and reassembly of RLC SDUs, re-segmentation of RLC data PDUs, and reordering of RLC data PDUs; and MAC layer functionality associated with mapping between logical channels and transport channels, multiplexing of MAC SDUs onto TBs, demultiplexing of MAC SDUs from TBs, scheduling information reporting, error correction through HARQ, priority handling, and logical channel prioritization.

(40) Channel estimates derived by a channel estimator **358** from a reference signal or feedback transmitted by device **310** may be used by the TX processor **368** to select the appropriate coding and modulation schemes, and to facilitate spatial processing. The spatial streams generated by the TX processor **368** may be provided to different antenna **352** via separate transmitters **354TX**. Each transmitter **354TX** may modulate an RF carrier with a respective spatial stream for transmission.

(41) The transmission is processed at the device **310** in a manner similar to that described in connection with the receiver function at the device **350**. Each receiver **318RX** receives a signal through its respective antenna **320**. Each receiver **318RX** recovers information modulated onto an RF carrier and provides the information to a RX processor **370**.

(42) The controller/processor **375** can be associated with a memory **376** that stores program codes and data. The memory **376** may be referred to as a computer-readable medium. The controller/processor **375** provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, control signal processing. The controller/processor **375** is also responsible for error detection using an ACK and/or NACK protocol to support HARQ operations.

(43) Wireless communication may include multicast communication directly between UEs. As an example, multicast sidelink communication may be performed via a PC5 interface. UEs may communicate using sidelink multicast based on V2X communication, V2V communication, or D2D communication, for example. A multicast may involve a transmission from one UE that is intended to be decoded by UEs that are part of a service group. A service group may comprise one or more UEs. A group ID identifying the service group may be comprised in the message, e.g., in Sidelink Control Information (SCI) of the multicast message, and/or as part of the MAC layer destination address.

(44) In a PC5 multicast, a transmitting UE may ensure that all intended receivers in the service group and in proximity of the transmitting UE accurately receive the message. If the intended receivers in the service group that are in the proximity of the transmitting UE do not receive the message accurately, the transmitting UE may retransmit the message in order to ensure accurate receipt of the message.

(45) In order to improve reliability, feedback may be sent back from the receiving UEs in the service group. For example, if a particular UE in the service group does not correctly receive the message, the UE may transmit a NACK, e.g., via sidelink, indicating to the transmitting UE that there was an error in receiving the message. In response to the NACK, the transmitting UE may retransmit the message.

(46) FIG. 4 illustrates an example of communication **400** between multiple UEs, e.g., based on V2X/V2V/D2D communication. UE **402** may be a transmitting UE that multicasts message **414** for a service group. UEs **404**, **406**, and **408** may be associated with the service group. UE **404** may have correctly received the message **414** and does not transmit a NACK. UE **406** may have experienced an error in receiving the message. Thus, UE **406** may transmit a NACK **416** indicating to UE **402** that the message was not accurately received. In response to the NACK **416**, the transmitting UE **402** may determine, e.g., at **424**, to retransmit the message **414**. However, negative feedback, e.g., NACK(s), may be received from far away receivers that are outside the desired

proximity of the transmitting UE **402**. As illustrated in FIG. 4, the UE may intend for UEs within range/area **401** to receive the message reliably. UE **408** that is outside the intended area **401** and that is not proximate to UE **402** may receive at least a part of the message and send a NACK **420** to UE **402**. However, UE **408** may be at such a distance that UE **408** will likely never receive the message **414** correctly even with a retransmission from UE **402**. Additionally, based on the service requirement, there may be no need for the UE at that distance, e.g. UE **408**, to receive the message, because the message becomes irrelevant.

(47) Thus, NACK(s) may be received from receiving UEs associated with the service group yet that are at such a distance that the transmitter would retransmit the message in futile. Such futile retransmissions would degrade overall system performance through an inefficient use of wireless resources and through unnecessary potential interference to other wireless communication. While a group ID, e.g., a common destination ID, may be used to identify a multicast service group, in an ad hoc V2X/V2V/D2D environment, it may be difficult to manage or establish a common group identifier that is known only to vehicles in the service group that are also in the proximity of the transmitting UE because of the highly mobile nature of the transmitters and/or receivers.

(48) Aspects are presented that limit feedback from receivers, e.g., receiving UEs, outside of an intended geographical area by providing information that enables a receiver to determine whether it is an intended receiver of the message. The receiver can then determine whether to send feedback based on whether or not the receiver is an intended receiver of the message. A transmitting device, e.g., **402**, may indicate geographic area information in each multicast message indicating that receivers, e.g., **404**, **406** that are within the indicated geographic area, e.g., **401**, are intended to receive the message reliably and should send feedback to help improve the multicast. This may help a receiver outside of the intended area, e.g., UE **408**, to determine that it does not need to send feedback. Thus, the geographic area information helps to limit feedback from receivers in the service group that are not in proximity to the transmitter. While the problems have been described using an illustration of V2X/V2V/D2D communication between UEs **402**, **404**, **406**, **408**, the concepts are equally applicable to a base station, RSU, mobile UE, vehicle UE etc. that are engaged in PC5 based communication.

(49) In order to reduce the amount of overhead to encode the geographic area information in the message, the geographic area may be indicated using predefined zones or areas. For example, a zone ID or an area ID may be encoded in the message. In one example, the zone/area intended to reliably receive the message may comprise a circular area centered on the location of the transmitting device, e.g., UE **402** or other transmitter engaged in PC5 communication, and extending to a radius indicated to the receiving devices. In another example, predefined zones may have a non-circular shape, e.g., with a region divided into a set of rectangular, hexagon, or other shaped zones, each having a corresponding zone ID. In yet another example, the predefined zones may have a customized shape. For example, the predefined zones may follow a contour of a road, a driving direction, a shape of a geographic feature, etc. In another example, hierarchical zones may be organized in different layers. Each layer corresponds to zones of a different size. For example, first layer may correspond to zones having a radius of 50 m, a width of 50 m, etc. A second layer may correspond to zones having a radius of 100 m, a width of 100 m, etc. A third layer may correspond to zones having a radius of 500 m, a width of 500 m, etc. Thus, the transmitting device and receiving device may identify the zone/area that is intended for reliable reception of the message based on a combination of a layer ID and a zone ID corresponding to the layer ID. In another example, zone divisions may be pre-configured to the receiving devices. For example, the zone divisions may be based on global coordinates of the geographic location. Then, the transmitting device may select a corresponding zone from among the pre-configured zone divisions. Receiving and transmitting devices may receive occasional updates for the pre-configured zone divisions.

(50) FIG. 5 illustrates an example communication flow **500** between a transmitting device **502** and

a receiving device 504. The communication may be based on V2X/V2V/D2D communication, e.g., PC5 multicast communication. In some aspects, the communication may be based on other D2D direct communication, such as ProSe. Although FIG. 5 illustrates an example of communication between a transmitting device 502 and a receiving device 504 that are illustrated as UEs, the concepts are equally applicable to a base station, an RSU, a mobile UE, a vehicle UE, etc. that are engaged in PC5 based communication, V2X/V2V communication or other direct D2D communication. As part of generating a service group message for transmission, e.g., via V2X/V2V/D2D, the transmitting device 502 may determine a zone/area/range for which the message is intended to be reliably received by a receiver in the service group. This may provide a way for the transmitting device 502 to limit feedback to only a receiver(s) within the intended zone/area/range. The transmitting device may determine its current geographic location, at 503, and may use the current location to determine an area/zone/range that is intended to receive the message and for which the transmitting device should receive HARQ feedback. For example, the transmitting device may identify a preconfigured zone in which the transmitting device is currently located. In another example, the zone may be centered on the transmitting device with a selected radius. In another example, the transmitting device may define the zone in another manner or otherwise select the area/range/zone.

(51) As one example, a range may be selected, e.g., based on a Quality of Service (QoS) parameter associated with the multicast. For example, the 5QI for different services may indicate QoS information such as any of a resource type, a priority level for communication, a packet delay budget (PDB) indicating an amount of time that a packet can be delayed, a Packet Error Rate (PER) that indicates a limit on a rate of packet losses, an averaging window, a data burst volume parameter that indicates a limit on the amount of data to be served within a period of time. In addition, the application may indicate a range requirement for the traffic. For example, the range could be in the form of absolute distance, e.g. 500 meters, or in relative levels, e.g. long, medium, or short.

(52) The transmitting device may indicate its current location and a surrounding range in the message. These may be indicated as a zone ID based on the transmitting device's geographical location and a range of the surrounding zones. For example, the transmitting device may indicate an amount or a number, N, of adjacent surrounding zones that are intended to receive the message reliably. If N=1, then the receiving device would need to be within the same zone as the transmitting device in order to be expected to reliably receive the message. If N=2, then a receiving device within the same zone as the transmitting device and within a zone directly adjacent to the zone of the transmitting device would be expected to reliably receive the message. For example, if the zones are of a rectangular shape, the devices expected to reliably receive the message should be in the same zone of the transmitting device and the 8 adjacent zones. If the zones are of a hexagon shape, the devices expected to reliably receive the message should be in the same zone of the transmitting device and the 6 adjacent zone. N may be selected to be any number.

(53) Once the transmitting device has determined the zone/area/range intended to reliably deliver the message and within which a receiver should send feedback, the transmitting device may generate the message. The message may comprise a control portion and a data portion. The control portion may comprise in the Sidelink Control Information (SCI) an indication of the area/zone/range intended to reliably receive the message. The SCI may also include group ID information corresponding to the service group for the multicast. The group ID information may enable the message to be decoded by receivers that are associated with the service group and that know the group ID. The group ID may be the same as a destination ID or may be different than a destination ID. The group ID may be provided by an application layer, or a mid-ware layer of the UE, or mapped by the V2X layer from the ID provided by the application layer. The group ID may correspond to a higher layer ID or an ID mapped from the higher layer ID, whereas the destination ID corresponds to a lower layer ID. The group ID may be mapped to a destination ID.

(54) FIGS. 12 and 13 illustrate examples of interaction between different layers at a transmitting device and a receiving device for the use of a zone ID for V2X/V2V communication. Although the aspects are presented for a V2X example, the aspects may be applied to other direct D2D communication. In the example 1200 in FIG. 12, Application layer **1202**, Layer 3 for D2D communication, e.g., a V2X layer, **1204**, and Access Stratum (AS) layer **1206** are for the transmitting device, e.g., **502**. In one example Layer 3 may comprise a V2X layer. In other examples, aspects may be applied to other D2D direct communication, such as ProSe. Application layer **1208**, Layer 3 for D2D communication, e.g., a V2X layer, **1210**, and AS layer **1212** are for the receiving device, e.g., **504**. At the transmitting device, the application layer may provide a group ID and a QoS profile for a particular service group to the Layer 3. The QoS profile may include any of an indication of 5QI for the service group, a rate for the service group, and/or a range for the service group. The application layer **1202** may also provide data to the Layer 3 to be transmitted in a message, e.g., a multicast message, to the service group. The data may be provided with a corresponding group ID. The application layer may provide a Provider Service Identifier (PSID) with the data. The Layer 3 may map the group ID received from the application layer to a Destination L2 ID (Dst. L2 ID) for the service group. The Layer 3 may also store the QoS profile for the service group. If the Layer 3 does not provide a QoS Profile to the Layer 3, the Layer 3 may use the PSID to determine a corresponding QoS Profile, e.g., mapping the PSID to a QoS profile. As well, if the application layer does not provide a Group ID to the Layer 3, the Dst. L2 ID determined by the Layer 3 may be based on a mapping of the PSID to the Dst. L2 ID. Such mapping information can be pre-configured on the UE, stored in the (U)SIM card, or provisioned from the network via a dynamic provisioning mechanism, e.g. Open Mobile Alliance (OMA) Device Management (DM) OMA-DM or UE Policy delivery mechanism. The AS layer may receive the Dst. L2 ID, a Source L2 ID, the QoS profile (e.g., including the 5QI and/or range), and data for the service group from the Layer 3. The AS layer may determine whether to use an acknowledgement mode for the multicast, e.g., a NACK mode, based on the 5QI from the QoS profile or local policy. For example, if the 5QI indicates a requirement for high reliability, e.g., very low PER value, the transmitting UE may choose to use the acknowledgement to achieve such high reliability. In the NACK mode, the transmitting device may monitor for feedback, e.g. NACK(s), in order to determine whether to retransmit the message. The AS layer **1206** may also determine a zone ID to use in the message. The zone ID may correspond to a zone in which the transmitting device is currently located. The AS layer **1206** may also determine a range to use in the message. The range may indicate an additional range either surrounding the transmitting device, or the zone or list of zones in which the receiving device is located, for which the transmitting device intends the message to be reliably received. The range may inform a receiver whether or not it should provide feedback. The transmitting device may then transmit the message, comprising SCI **1214** and data **1216**. The SCI may include information indicating group ID or Dst. L2 ID, the zone ID determined by the AS, and/or the range determined by the AS.

(55) At the receiving device, the application layer **1208** provides a group ID, for a service group of which the receiving device is associated, to the Layer **1210**. The Layer **1210** determines a Dst. L2 ID based on the group ID, similar to the mapping performed by the transmitting device's Layer **1204**. The AS layer **1212** at the receiving device determines its own zone ID, e.g. for the zone in which the receiving device is currently located. When the receiving device receives the message, including the SCI **1214** and the data **1216**, the receiving device determines whether to send feedback, e.g., a NACK, if the data part of the message is not received correctly. The receiving device may determine whether to send the NACK based on whether the Dst. L2 ID determined by Layer **1210** matches the Dst. L2 ID indicated in the SCI **1214** of the message and/or based on whether the zone ID for the receiving device that was determined by the AS **1212** matches the zone ID indicated in the SCI **1214** or falls within the range of the zone ID indicated in the SCI **1214**. If the Dst. L2 IDs match and the zone ID of the receiving device falls within the indicated range of

the zone ID of the transmitting device, the receiving device may provide a NACK if the data portion of the message is not received, for example. If no Dst. L2 ID is not provided from the Layer **1210** to the AS layer **1212** at the receiving device, the receiving device may determine not to send a NACK. The SCI may carry the information regarding the Zone ID, Dst. L2 ID, and range in different forms. For example, the zone ID and Dst. L2 ID of the SCI may be hashed to reduce the overhead required to send the message. In that case, the SCI may be of a different format than that used for other V2X message transmission, e.g. broadcast messages. Therefore, an additional bit in SCI may be included in order to differentiate the format of the message, e.g., whether the message is broadcast, multicast, or unicast.

(56) The example 1300 in FIG. **13** is similar to the example in FIG. **12**. The application layer **1302** and the Layer 3 for D2D communication, e.g., a V2X layer, **1304** at the transmitting device may function similarly to the example in FIG. **12**. In one example Layer 3 may comprise a V2X layer. In other examples, aspects may be applied to other D2D multicast communication, such as ProSe. However, in FIG. **13**, the range might not be determined or indicated by the AS layer **1306** at the transmitting device. Instead, application layer **1308** at the receiving device may provide a QoS profile for the service group to layer **1310** at the receiving device. The 5QI and range information may be provided from the layer **1310** to the AS layer **1312** of the receiving device. The AS layer at the receiving device may then determine not only its own zone ID based on the receiving device's current location, but also the range to be used in determining whether to send feedback. Thus, the SCI **1314** sent along with the data **1316** from the transmitting device might not include information indicating the range. The receiving device may determine whether to send feedback based on any combination of whether the Dst. L2 ID of the SCI matches that determined by the layer **1310**, whether the zone ID determined by the AS **1312** is within either the zone ID indicated in the SCI **1314** plus the range determined by the AS layer **1312**. Alternatively, the receiving device may determine a range based on its own zone ID, and verify if the zone ID indicated in SCI **1314** is within the range. For example, the receiving device might determine not to send a NACK if the Zone ID in the SCI **1314** is not in the range of its own zone ID. As explained above, the SCI may include other information to support the operation. For example, it may include an indication of whether the message is a retransmitted message, and a sequence number for the message. In this case, the receiving device may determine whether to send a NACK based on whether it has already received the original transmission of the same message.

(57) In order to further reduce the overhead of transmitting the zone/area/range information in the message, the transmitting device may hash the group ID and the zone ID, at **507**, to generate a shortened ID, e.g., an Information Element (IE). The IE may then be embedded in the SCI of the message as part of the generation of the message at **509**. After generation at **509**, the transmitting device **502** may transmit the message **511**, along with the IE.

(58) Receiving device **504** decodes at least a portion of the message, at **519**, in order to determine the indication of the range/area/zone intended to receive the message reliably, e.g., zone ID information. The receiving device might receive the control portion of the message, but might not correctly receive the data portion of the message. As the message is not received correctly, the receiving device **504** may need to determine whether to send HARQ feedback, e.g., a NACK, to the transmitting device **502**. The receiving device may determine, at **521**, whether to send a NACK based on a current location of the receiving device and based on the indication, included in the message, of the range/area/zone intended to receive the message reliably. Thus, the receiving device may determine its current location, at **517** and may determine to send a NACK when the receiving device **504** is within the indicated range/area/zone. For example, the receiving device may send a NACK if the receiving device is in the same zone as the transmitting device, e.g., when $N=1$, or within a list of surrounding zones, when $N>1$. The surrounding zones may be based on a range/number/amount indicated to the receiving device **504**. In another example, the range/number/amount of surrounding zones may be a function of a QoS for the multicast service.

The QoS may be configured via RRC or via an upper layer.

(59) The area/zone/range indicated in the message **511** may reference at least one preconfigured zone, the preconfigured zones being preconfigured and stored at the receiving device. As illustrated at **513**, the receiving device may receive an update of the preconfigured zone(s)/area(s)/range(s). Although not illustrated, the transmitting device **502** may receive similar updates of the preconfigured zone(s)/area(s)/range(s). At times a device may operate as a transmitting device, and at other times, the same device may operate as a receiving device.

(60) When the indication of the area and/or group ID is comprised in an IE, the receiving device **504** may monitor for at least one IE in SCI of any received messages, at **515**. The IE(s) for which the receiving device monitors, at **515**, may be based on a predetermined hash of any group ID for multicast services with which the receiving UE is associated hashed with surrounding zone IDs. As the receiving device may be mobile, the surrounding zone IDs may be updated based on the receiving device's current location.

(61) If the UE determines, at **521**, that the UE is within the area/zone/range of intended reliable receipt of the message, and the UE has not correctly received the message **511**, the UE may respond with a NACK **523** to the transmitting device **502**. The UE may determine whether to send the NACK based on additional aspects, e.g., whether the receiver is associated with the service group corresponding to a group ID comprised in the message, etc. In response to the NACK **523**, the transmitting device **502** may retransmit the message **525** in order to ensure reliable receipt of the message by the receiving device **504**.

(62) FIG. **6** is a flowchart **600** of a method of wireless communication. The method may be performed by a transmitting device or a component of a transmitting device, e.g., a UE **104**, **402**, **1050**; a base station **102**, **180**; an RSU **107**; transmitting device **310**, **502**; the apparatus **702**, **702'**; processing system **814**. The transmitting device may transmit directly to receiving devices, e.g., to UE(s), RSU(s), base station(s), based on V2V or V2X communication, or other direct D2D communication. The transmitting device may comprise any device engaged in PC5 communication. Optional aspects are illustrated with a dashed line. The method improves system performance through improved efficiency in the use of wireless resources and by avoiding unnecessary interference that may be caused through retransmissions to unintended receivers that are not proximate to the transmitting device.

(63) At **602**, the transmitting device determines a geographic location of the transmitting device. The location may be determined, e.g., by location component **708** of apparatus **702**. The transmitting device may determine the geographic location based on any of Global Positioning System (GPS), etc. A geographic area for message(s) transmitted by the transmitting device may be based, at least in part, on the geographic location of the transmitting device.

(64) At **610**, the transmitting device transmits the message to the service group, e.g., via V2X/V2V/D2D communication. The transmission may be performed, e.g., by transmission component **706** and/or message component **710** of apparatus **702**. FIG. **5** illustrates an example transmission of a message **511**. The message may be transmitted for a service group, and may include a first indication of a geographic area associated with the message. A service group may include one or more UEs. The message may include a multicast message for a service group, such as described in connection with FIG. **4**. The transmitting device may rely on feedback in order to ensure reliable receipt of the message by a receiver that is both associated with the service group and in proximity to the transmitting device. The indication of the geographic area associated with the message may inform a receiving device about the intended range of reliable receipt for the message. Thus, the first indication of the geographic area may indicate a range in which feedback is requested from a receiving device. The message may further comprise group ID information for the service group.

(65) The geographic area indicated by the first indication may comprise a reference to a preconfigured area, e.g., that is known by the transmitting device and a receiving device. For

example, global zones may be divided into preconfigured zones, and the transmitting device may indicate at least one of the preconfigured zones, e.g., through the use of a zone ID. In another example, the first indication of the geographic area may indicate an area determined by the transmitting device. The first indication of the geographic area may indicate a radius surrounding the geographic location of the transmitting device. In another example, the first indication of the geographic area may indicate a non-circular area. The first indication of the geographic area may be determined based on a QoS parameter associated with the message. Likewise, a range surrounding the geographic, e.g., N, area may similarly be determined based on a QoS parameter associated with the message.

(66) The first indication of the geographic area may be in a form of a zone ID comprising reduced information for the geographic area, e.g., using a last M number of bits of a global zone ID. The first indication of the geographic area may be in a form of a zone ID based on a modulo operation performed on the geographic area information, e.g., to only include remainders of the zone ID. The first indication of the geographic area may be based on a hierarchical layer of areas. Thus, the first indication may comprise a layer ID and an area ID corresponding to the layer ID.

(67) The first indication of the geographic area may indicate a zone ID. Reference to a zone ID may reduce an amount of overhead required in the message to indicate the area to receiving device(s). Thus, the transmitting device may determine a zone ID based on the geographic location of the transmitting device, at **604**. The zone ID may be determined, e.g., by zone ID component **712** of apparatus **702**. The zone ID may correspond to a zone in which the transmitter device is currently located. The transmitting device may further indicate, at **608**, a second indication of a parameter indicating a range of at least one zone surrounding a zone of the Zone ID from which feedback is requested. The indication of the range may indicate a number/amount, e.g., N, of adjacent zones surrounding the zone in which the transmitter device is located and for which reliable receipt of the message is intended. N may be equal to one or more. If N=1, then the parameter may indicate that feedback is only requested from receivers located in the same zone as the transmitting device. If N>1, the parameter may indicate that feedback is requested for adjacent layers of zones surrounding the zone in which the transmitting device is located. For example, if N=2, feedback may be requested from the zone of the transmitting device and a surrounding layer of zones that are directly adjacent to the transmitting device's zone. If N=3, feedback may be requested from an additional group of surrounding zones.

(68) The first indication of the geographic area and/or the group ID information may be comprised in a control portion of the message, e.g., in SCI. In order to further reduce the overhead needed to indicate the group ID and/or the intended range/area/zone, the transmitting device may hash the first indication of the geographic area and/or the group ID, at **606**, to generate at least one IE. The hash may be performed, e.g., by hash component **714** of apparatus **702**. In one example, the group ID and a zone ID may be hashed to form a single IE. In another example, the group ID may be hashed to form a first IE and the zone ID may be hashed to form a second IE. In another example, one of the group ID or the zone ID may be hashed to form an IE and the other of the zone ID or the group ID may be indicated in the control information in another manner. The IE(s) may be comprised in the message, e.g., embedded in SCI.

(69) As described in connection with FIG. 5, if the transmitting device receives negative feedback from at least one receiver that is in the service group, and in proximity based on the indicated area information, the transmitting device may retransmit the message, e.g., **525**. Feedback may be received, e.g., by feedback component **720** of apparatus **702**. Retransmission(s) may be performed, e.g., by message component **710** and/or transmission component **706** of apparatus **702**.

(70) FIG. 7 is a conceptual data flow diagram **700** illustrating the data flow between different means/components in an example apparatus **702**. The apparatus may be a transmitting device, e.g., a UE or a component of a UE (e.g., UE **104**, **402**; device **310**, **502**). In other examples, the transmitting device may comprise a base station **102**, **180**, or an RSU **107** engaged in PC5

communication. The mobile transmitting device may transmit directly to mobile receiving devices, e.g., to other UEs based on V2V/V2X/D2D communication. The apparatus includes a reception component **704** that receives communication from other UEs **750**, RSUs, and/or base stations, e.g., based on PC5 communication. The apparatus includes a transmission component **706** that transmits communication to the other UEs **750**, RSUs, and/or base stations, e.g., based on PC5 communication. The communication may be transmitted and received as sidelink communication. Although the apparatus **702** and **1002** are illustrated separately, a single device may operate at times as a transmitter and at other times as a receiver. Thus, a single device may comprise each of the components described in connection with FIGS. **7** and **10**.

(71) The apparatus may include a location component **708** configured to determine a geographic location of the transmitting device (e.g., as described in connection with **503** in FIGS. **5** and **602** in FIG. **6**). The apparatus may include a message component **710** configured to generate a message for a service group, the message comprising a first indication of a geographic area associated with the message (e.g., as described in connection with **509** in FIGS. **5** and **610** in FIG. **6**). The indication of the geographic area may be based at least in part on the geographic location of the transmitting device. Thus the location component **708** may provide the determined location to the message component **710**. The message may further comprise group ID information, e.g., as identified by group ID component **716** that may provide group ID information to the message component for inclusion in the message. The transmission component **706** may be configured to transmit the message to a service group, e.g., via V2V/V2X/D2D communication (e.g. as described in connection with **511** in FIGS. **5** and **612** in FIG. **6**). The transmission component **706** may receive the message for transmission, as generated by the message component **710**. The indication of the geographic area may be indicated using a zone ID. Thus, the apparatus may include a zone ID component **712** configured to determine the zone ID based on the geographic location of the transmitting device (e.g., as described in connection with **505** in FIGS. **5** and **604** in FIG. **6**) and to provide the zone ID to the message component **710** for inclusion in the message. In other examples, the first indication included in the message may be based on the current location of the apparatus without use of a zone ID. The apparatus may include a surrounding zone component **718** configured to transmit, e.g., via transmission component **706**, a second indication of a parameter indicating a range of at least one zone surrounding a zone of the Zone ID from which feedback is requested (e.g., as described in connection with **608** in FIG. **6**). The range indication may be sent separately from the message, or may be provided to the message component for inclusion in the message. The apparatus may include a hash component **714** configured to hash the first indication of the geographic area (e.g., from zone ID component **712**) with the group ID (determined by group ID component **716**) to generate an information element IE having a reduced size that can be included in the message, e.g., by providing the generated IE to the message component **710**. In another example, the hash component **714** may be configured to hash the group ID to form a first IE and/or to hash the zone ID to form a second IE. In other examples, the group ID may be provided to the message component **710** separately from the hashed IE and may be indicated in the message in another manner. The apparatus may further include a feedback component **720** that is configured to receive feedback from at least one receiving device (e.g., as described in connection with **523** in FIG. **5**). The feedback may comprise positive or negative feedback. In response to negative feedback, and/or the absence of positive feedback, the feedback component **720** may provide an indication to the message component **710** to retransmit the message. The message component **710** may be configured to retransmit the message based on the feedback.

(72) The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIGS. **5** and **6**. As such, each block in the aforementioned flowcharts of FIGS. **5** and **6** may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a

processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

(73) FIG. 8 is a diagram **800** illustrating an example of a hardware implementation for an apparatus **702'** employing a processing system **814**. The processing system **814** may be implemented with a bus architecture, represented generally by the bus **824**. The bus **824** may include any number of interconnecting buses and bridges depending on the specific application of the processing system **814** and the overall design constraints. The bus **824** links together various circuits including one or more processors and/or hardware components, represented by the processor **804**, the components **704**, **706**, **708**, **710**, **712**, **714**, **716**, **718**, **720**, and the computer-readable medium/memory **806**. The bus **824** may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

(74) The processing system **814** may be coupled to a transceiver **810**. The transceiver **810** is coupled to one or more antennas **820**. The transceiver **810** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **810** receives a signal from the one or more antennas **820**, extracts information from the received signal, and provides the extracted information to the processing system **814**, specifically the reception component **704**. In addition, the transceiver **810** receives information from the processing system **814**, specifically the transmission component **706**, and based on the received information, generates a signal to be applied to the one or more antennas **820**. The processing system **814** includes a processor **804** coupled to a computer-readable medium/memory **806**. The processor **804** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **806**. The software, when executed by the processor **804**, causes the processing system **814** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **806** may also be used for storing data that is manipulated by the processor **804** when executing software. The processing system **814** further includes at least one of the components **704**, **706**, **708**, **710**, **712**, **714**, **716**, **718**, **720**. The components may be software components running in the processor **804**, resident/stored in the computer readable medium/memory **806**, one or more hardware components coupled to the processor **804**, or some combination thereof. The processing system **814** may be a component of the device **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**. Alternatively, the processing system may comprise the entire device, e.g., an entire UE.

(75) In one configuration, the apparatus **702/702'** for wireless communication includes means for determining a geographic location of the transmitting device (e.g., at least location component **708**); means for generating a message for a service group, the message comprising a first indication of a geographic area associated with the message, the geographic area based at least in part on the geographic location of the transmitting device (e.g., at least message component **710**); means for transmitting the message to the service group via V2X communication (e.g. at least transmission component **706**); means for determining the zone ID based on the geographic location of the transmitting device (e.g., at least zone ID component **712**); means for transmitting a second indication of a parameter indicating a range of at least one zone surrounding a zone of the Zone ID from which feedback is requested (e.g., at least surrounding zone component **718**); and/or means for hashing the first indication of the geographic area with the group ID to generate an information element IE (e.g., at least hash component **714**). The aforementioned means may be one or more of the aforementioned components of the apparatus **702** and/or the processing system **814** of the apparatus **702'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **814** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured

to perform the functions recited by the aforementioned means.

(76) FIG. 9 is a flowchart **900** of a method of wireless communication. The method may be performed by a receiving device, e.g., a UE or a component of a UE (e.g., UE **104**, **404**, **406**, **408**, **750**), a base station **102**, **180**, an RSU **107**, receiving device **504**, device **310**, **350**; apparatus **1002**, **1002'**; processing system **1114**, etc. The receiving device may receive communication directly from transmitting devices, e.g., from other UEs, RSUs, base stations, etc. based on V2V, V2X, or D2D communication. The method may be performed by any receiving device engaged in a PC5 communication. Optional aspects are illustrated with a dashed line. The method improves system performance through improved efficiency in the use of wireless resources and by avoiding unnecessary interference that may be caused through retransmissions to unintended receivers that are not proximate to the transmitting device.

(77) At **906**, the receiving device receives a message for a service group, e.g., via V2X/V2V communication or other D2D communication, the message comprising a first indication of a geographic area associated with the message. The indication of the geographic area may be based at least in part on a location of the transmitting device. The reception may be performed, e.g., by reception component **1004** and/or message component **1008** of apparatus **1002**.

(78) At **910**, the receiving device determines a geographic location of the receiving device. The current location may be based on any of GPS, etc. The geographic location of the receiving device may be determined, e.g., by location component **1018** of apparatus **1002**. Although illustrated as occurring after receipt of the message at **906**, the location of the receiving device may also be determined prior to receipt of the message. The first indication of the geographic area may comprise a zone ID. The receiving device determines to send the feedback, at **916**, if the geographic location of the receiving device, as determined at **910**, is within the geographic area indicated by the zone ID. The determination may be performed, e.g., by determination component **1010** based on information from zone ID component **1020** of apparatus **1002**. The receiving device may also determine to send the feedback, at **916**, if the geographic location of the receiving device is within a range of at least one zone surrounding a zone of the zone ID. The surrounding zone may be determined, e.g., by surrounding zone component **1022** of apparatus **1002**. For example, the receiving device may receive, at **908**, a second indication of a parameter indicating the range of at least one zone, e.g., N, as described in connection with FIGS. 5 and 6. The parameter may indicate a number of adjacent zones, wherein the receiving device determines to send the feedback if the geographic location of the receiving device is within the range based on the number of adjacent zones surrounding the zone of the zone ID. The range may be derived from SCI for the message.

(79) The first indication of the geographic area may be in a form of a zone ID comprising reduced information for the geographic area, e.g., using a last M number of bits of a globally zone ID. The first indication of the geographic area may be in a form of a zone ID based on a modulo operation performed on the geographic area information, e.g., to only include remainders of the zone ID. The first indication of the geographic area may be based on a hierarchical layer of areas. Thus, the first indication may comprise a layer ID and an area ID corresponding to the layer ID.

(80) At **916**, the receiving device determines whether to send a feedback for the message based on the first indication of the geographic area associated with the message and the geographic location of the receiving device. The determination may be performed, e.g., by determination component **1010**. For example, the receiving device may determine to send the feedback, at **916**, if the geographic location of the receiving device is within an intended range based on the first indication of the geographic area associated with the message. The receiving device may then proceed to transmit a feedback, at **918**. The feedback may be transmitted by feedback component **1012** and/or transmission component **1006** of apparatus **1002**. The feedback may include a NACK, as an example. The determination regarding whether to send the feedback may be further based on a determination of whether the message is received correctly, at **912**. Correct reception may be determined, e.g., by receipt component **1016** of apparatus **1002**. The receiving device may

determine to refrain from sending the feedback, at **916**, if the geographic location of the receiving device is outside of an intended range based on the first indication of the geographic area associated with the message. Then, the UE may refrain from transmitting the feedback at **914**, or might otherwise not be required to transmit the feedback. While this example is described in connection with providing negative feedback, the UE may also determine to send positive feedback when a message is properly received. The message may further comprise group ID information for the service group, and the receiving device may determine whether to send the feedback for the message, at **916**, further based on the group ID information comprised in the message. For example, the receiving device might only send feedback if the group ID is for a service group to which the receiving device corresponds.

(81) The geographic area indicated by the first indication may comprise a reference to a preconfigured area, e.g., that is known by the transmitting device and a receiving device. For example, global zones may be divided into preconfigured zones, and the transmitting device may indicate at least one of the preconfigured zones, e.g., through the use of a zone ID. At **902**, the receiving device may receive an update of the preconfigured area. The update may be received, e.g., by update component **1024** of apparatus **1002**. In another example, the first indication of the geographic area may indicate an area determined by the transmitting device. The first indication of the geographic area may indicate a radius surrounding the geographic location of the transmitting device. In another example, the first indication of the geographic area may indicate a non-circular area. The first indication of the geographic area may be determined based on a QoS parameter associated with the message. Likewise, a range surrounding the geographic, e.g., N, area may similarly be determined based on a QoS parameter associated with the message.

(82) The message may comprise at least one IE based on a hash of a zone ID and/or a group ID, e.g., comprised in SCI of the message. In one example, the group ID and a zone ID may be hashed to form a single IE. In another example, the group ID may be hashed to form a first IE and the zone ID may be hashed to form a second IE. In another example, one of the group ID or the zone ID may be hashed to form an IE and the other of the zone ID or the group ID may be indicated in the control information in another manner. Thus, the receiving device may monitor, at **904**, for at least one IE based on at least one pre-determined hash that is based on the group ID for the service group and/or zone IDs surrounding the geographic location of the receiving device. For example, monitor component **1014** of apparatus **1002** may monitor for the IE(s). As described in connection with **515** in FIG. 5, the receiving device may use group ID(s) for at least one service group to which the receiving device is associated along with zone IDs for a surrounding range of zones to form a set of at least one IE. Then, the UE may monitor for the IE(s) to be included in any received message. Based on the monitoring, the UE may quickly identify messages for which the UE should transmit feedback.

(83) FIG. 10 is a conceptual data flow diagram **1000** illustrating the data flow between different means/components in an example apparatus **1002**. The apparatus may be a mobile receiving device, e.g., a UE or a component of a UE (e.g., UE **104**, **404**, **406**, **408**, **504**, device **310**). In other examples, the receiving device may comprise a UE, a base station, or an RSU engaged in PC5 communication. The receiving device may receive communication directly from transmitting devices, based on V2V/V2X/D2D communication. The apparatus **1002** includes a reception component **1004** that receives communication from other UEs **1050**, RSUs, and/or base stations, e.g., based on PC5 communication. The apparatus includes a transmission component **1006** that transmits communication to the other UEs **1050**, RSUs, and/or base stations, etc., e.g., based on PC5 communication. The communication may be transmitted and received as sidelink communication. Although the apparatus **702** and **1002** are illustrated separately, a single device may operate at times as a transmitter and at other times as a receiver. Thus, a single device may comprise each of the components described in connection with FIGS. 7 and 10.

(84) The apparatus may include a message component **1008** configured to receive a message for a

service group, e.g., via V2V/V2X communication or other D2D communication, the message comprising a first indication of a geographic area associated with the message (e.g., as described in connection with **511** in FIGS. **5** and **906** in FIG. **9**). The apparatus may include a location component **1018** configured to determine a geographic location of the receiving device (e.g., as described in connection with **517** in FIGS. **5** and **910** in FIG. **10**). The apparatus may include a determination component **1010** configured to determine whether to send a feedback for the message based on the first indication of the geographic area associated with the message and the geographic location of the receiving device (e.g., as described in connection with **916** in FIGS. **9** and **521** in FIG. **5**). Information from the message component **1008** may be provided to the determination component, e.g., including an IE, a group ID, a zone ID, etc. As well, the current location determined by the location component **1018** may be provided to the determination component **1010**. The apparatus may further include a zone ID component **1020** configured to determine a zone ID for a zone in which the apparatus is currently located, e.g., based on the determination of the location by the location component **1018**. The zone ID may similarly be provided to the determination component for use in determining whether to send feedback. The apparatus may include a feedback component **1012** configured to transmit feedback, e.g., a NACK if the message is not received correctly and based on the determination made by the determination component (e.g., as described in connection with **918** in FIGS. **9** and **523** in FIG. **5**). The apparatus may include a surrounding zone component **1022** configured to receive a second indication of a parameter indicating the range of at least one zone (e.g., as described in connection with **908** in FIG. **9**). The range of surrounding zones, whether one or more, may be provided to the determination component **1010** for use in determining whether to send feedback. The apparatus may include an update component **1024** configured to receive an update of the preconfigured area (e.g., as described in connection with **513** in FIGS. **5** and **902** in FIG. **9**). Any updates may be provided to the determination component. The apparatus may include a monitor component **1014** configured to monitor for at least one of the first IE, the second IE, or the third IE based on at least one pre-determined hash based on at least one of the group ID for the service group or zone IDs surrounding the geographic location of the receiving device (e.g., as described in connection with **515** in FIGS. **5** and **904** in FIG. **9**). The monitor component **1014** may determine at least one IE for which the apparatus should send feedback and may monitor for the IE(s) in any received messages. If an IE is detected, the monitor component **1014** may provide an indication to the determination component **1010**. The apparatus may further include a receipt component **1016** configured to determine whether the message is received correctly. The determination as to whether the message is received correctly may be provided to the determination component for use in determining whether to provide feedback.

(85) The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIGS. **5** and **9**. As such, each block in the aforementioned flowcharts of FIGS. **5** and **9** may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

(86) FIG. **11** is a diagram **1100** illustrating an example of a hardware implementation for an apparatus **1002'** employing a processing system **1114**. The processing system **1114** may be implemented with a bus architecture, represented generally by the bus **1124**. The bus **1124** may include any number of interconnecting buses and bridges depending on the specific application of the processing system **1114** and the overall design constraints. The bus **1124** links together various circuits including one or more processors and/or hardware components, represented by the processor **1104**, the components **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, **1016**, **1018**, **1020**, **1022**, **1024**, and the computer-readable medium/memory **1106**. The bus **1124** may also link various other

circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

(87) The processing system **1114** may be coupled to a transceiver **1110**. The transceiver **1110** is coupled to one or more antennas **1120**. The transceiver **1110** provides a means for communicating with various other apparatus over a transmission medium. The transceiver **1110** receives a signal from the one or more antennas **1120**, extracts information from the received signal, and provides the extracted information to the processing system **1114**, specifically the reception component **1004**. In addition, the transceiver **1110** receives information from the processing system **1114**, specifically the transmission component **1006**, and based on the received information, generates a signal to be applied to the one or more antennas **1120**. The processing system **1114** includes a processor **1104** coupled to a computer-readable medium/memory **1106**. The processor **1104** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory **1106**. The software, when executed by the processor **1104**, causes the processing system **1114** to perform the various functions described supra for any particular apparatus. The computer-readable medium/memory **1106** may also be used for storing data that is manipulated by the processor **1104** when executing software. The processing system **1114** further includes at least one of the components **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, **1016**, **1018**, **1020**, **1022**, **1024**. The components may be software components running in the processor **1104**, resident/stored in the computer readable medium/memory **1106**, one or more hardware components coupled to the processor **1104**, or some combination thereof. The processing system **1114** may be a component of the device **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**. Alternatively, the processing system may comprise the entire device, e.g., an entire UE.

(88) In one configuration, the apparatus **1002/1002'** for wireless communication includes means for receiving a message for a service group via V2X communication, the message comprising a first indication of a geographic area associated with the message (e.g., at least message component **1008** and/or reception component **1004**); means for determining a geographic location of the receiving device (e.g., at least location component **1018**); means for determining whether to send a feedback for the message based on the first indication of the geographic area associated with the message and the geographic location of the receiving device (e.g., at least determination component **1010**); means for transmitting feedback, e.g., a NACK if the message is not received correctly (e.g., at least feedback component **1012**); means for receiving a second indication of a parameter indicating the range of at least one zone (e.g., at least surrounding zone component **1022**); means for receiving an update of the preconfigured area (e.g., at least update component **1024**); and means for monitoring for the IE based on at least one pre-determined hash based on the group ID for the service group and zone IDs surrounding the geographic location of the receiving device (e.g., at least monitor component **1014**). The aforementioned means may be one or more of the aforementioned components of the apparatus **1002** and/or the processing system **1114** of the apparatus **1002'** configured to perform the functions recited by the aforementioned means. As described supra, the processing system **1114** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the aforementioned means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the aforementioned means.

(89) It is understood that the specific order or hierarchy of blocks in the processes/flowcharts disclosed is an illustration of example approaches. Based upon design preferences, it is understood that the specific order or hierarchy of blocks in the processes/flowcharts may be rearranged. Further, some blocks may be combined or omitted. The accompanying method claims present elements of the various blocks in a sample order, and are not meant to be limited to the specific order or hierarchy presented.

(90) The previous description is provided to enable any person skilled in the art to practice the

various aspects described herein. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but is to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects. Unless specifically stated otherwise, the term “some” refers to one or more. Combinations such as “at least one of A, B, or C,” “one or more of A, B, or C,” “at least one of A, B, and C,” “one or more of A, B, and C,” and “A, B, C, or any combination thereof” include any combination of A, B, and/or C, and may include multiples of A, multiples of B, or multiples of C. Specifically, combinations such as “at least one of A, B, or C,” “one or more of A, B, or C,” “at least one of A, B, and C,” “one or more of A, B, and C,” and “A, B, C, or any combination thereof” may be A only, B only, C only, A and B, A and C, B and C, or A and B and C, where any such combinations may contain one or more member or members of A, B, or C. All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. The words “module,” “mechanism,” “element,” “device,” and the like may not be a substitute for the word “means.” As such, no claim element is to be construed as a means plus function unless the element is expressly recited using the phrase “means for.”

Claims

1. A method of wireless communication at a first wireless device, comprising: receiving sidelink control information (SCI), from a second wireless device, that indicates a zone identifier (ID) for a zone associated with a sidelink groupcast message; determining a location of the first wireless device; and determining whether to send a feedback for the sidelink groupcast message based on the location of the first wireless device and the zone ID received in the SCI, the zone ID indicating the zone associated with the sidelink groupcast message.
2. The method of claim 1, wherein the feedback comprises hybrid automatic repeat request (HARQ) feedback.
3. The method of claim 1, wherein the zone ID is based in part on a geographic location of the second wireless device that is a source of the sidelink groupcast message.
4. The method of claim 1, further comprising: sending the feedback if the location of the first wireless device is within a range based on the zone ID associated with the sidelink groupcast message.
5. The method of claim 4, further comprising: receiving an indication of the range in the SCI for the sidelink groupcast message.
6. The method of claim 1, further comprising: determining that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and transmitting the feedback for the sidelink groupcast message when the first wireless device is unsuccessful in correctly receiving the sidelink groupcast message and the location of the first wireless device is within the range.
7. The method of claim 1, further comprising: determining whether the sidelink groupcast message is received correctly; determining that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and transmitting the feedback for the sidelink groupcast message when the first wireless device is unsuccessful in correctly receiving the sidelink

groupcast message and the location of the first wireless device is within the range.

8. The method of claim 1, further comprising: refraining from sending the feedback if the location of the first wireless device is outside of a range based on the zone ID associated with the sidelink groupcast message.

9. The method of claim 1, wherein the SCI further comprises a group identifier (ID) representing a service group, and wherein the determining whether to send the feedback for the sidelink groupcast message is further based on the group ID comprised in the SCI.

10. The method of claim 1, wherein the determining whether to send the feedback for the sidelink groupcast message includes determining to send the feedback if the location of the first wireless device is within a geographic area indicated by the zone ID.

11. The method of claim 1, wherein the determining whether to send the feedback for the sidelink groupcast message includes determining to send the feedback based on the location of the first wireless device and a combination of the zone ID and a range for the sidelink groupcast message.

12. The method of claim 1, wherein the zone ID is based on a modulo operation performed on geographic area information.

13. The method of claim 1, wherein a geographic area indicated by the zone ID comprises a preconfigured area.

14. The method of claim 13, further comprising: receiving an update of the preconfigured area.

15. The method of claim 1, wherein the zone ID corresponds to a non-circular area.

16. The method of claim 1, wherein a range is based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message.

17. The method of claim 16, wherein determining whether to send the feedback for the sidelink groupcast message includes determining to send the feedback based on the location of the first wireless device and a combination of the zone ID and the range for the sidelink groupcast message.

18. The method of claim 1, wherein the sidelink groupcast message is for a service group, and wherein a range is indicated in a Quality of Service (QoS) profile for the service group.

19. The method of claim 1, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

20. A method of wireless communication at a wireless device, comprising: determining a geographic location of the wireless device; transmitting sidelink control information (SCI) associated with a sidelink groupcast message, the SCI comprising: a zone identifier (ID) for a zone associated with the sidelink groupcast message, the zone ID being based in part on the geographic location of the wireless device, and a range for feedback, the range being based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message; and transmitting the sidelink groupcast message.

21. The method of claim 20, wherein the feedback comprises hybrid automatic repeat request (HARQ) feedback.

22. The method of claim 20, wherein the SCI further comprises a group identifier (ID) representing a service group.

23. The method of claim 20, wherein the zone ID is based on a modulo operation performed on geographic area information.

24. The method of claim 20, wherein a geographic area indicated by the zone ID comprises a preconfigured area.

25. The method of claim 20, further comprising: receiving the feedback for the sidelink groupcast message, the feedback being based on the zone ID and the range indicated in the SCI.

26. The method of claim 20, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

27. An apparatus for wireless communication at a first wireless device, comprising: memory; and at least one processor coupled to the memory and being configured to: receive sidelink control information (SCI), from a second wireless device, that indicates a zone identifier (ID) for a zone

associated with a sidelink groupcast message; determine a location of the first wireless device; and determine whether to send a feedback for the sidelink groupcast message based on the location of the first wireless device and the zone ID received in the SCI, wherein the zone ID indicates the zone associated with the sidelink groupcast message.

28. The apparatus of claim 27, wherein the at least one processor is further configured to: send the feedback if the location of the first wireless device is within a range based on the zone ID associated with the sidelink groupcast message.

29. The apparatus of claim 28, wherein the at least one processor is further configured to: receive an indication of the range in the SCI for the sidelink groupcast message.

30. The apparatus of claim 27, wherein the feedback comprises hybrid automatic repeat request (HARQ) feedback.

31. The apparatus of claim 27, wherein the zone ID is based in part on a geographic location of the second wireless device that is a source of the sidelink groupcast message.

32. The apparatus of claim 27, wherein the at least one processor is further configured to: determine that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and transmit the feedback for the sidelink groupcast message when the first wireless device is unsuccessful to correctly receive the sidelink groupcast message and the location of the first wireless device is within the range.

33. The apparatus of claim 27, wherein the at least one processor is further configured to: determine whether the sidelink groupcast message is received correctly; determine that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and transmit the feedback for the sidelink groupcast message when the first wireless device is unsuccessful to correctly receive the sidelink groupcast message and the location of the first wireless device is within the range.

34. The apparatus of claim 27, further comprising: a transceiver coupled to the memory and the at least one processor.

35. The apparatus of claim 27, wherein a range is based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message.

36. The apparatus of claim 35, wherein to determine whether to send the feedback for the sidelink groupcast message, the at least one processor is configured to determine to send the feedback based on the location of the first wireless device and a combination of the zone ID and the range for the sidelink groupcast message.

37. The apparatus of claim 27, wherein the sidelink groupcast message is for a service group, and wherein a range is indicated in a Quality of Service (QoS) profile for the service group.

38. The apparatus of claim 27, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

39. The apparatus of claim 27, wherein the at least one processor is individually or collectively configured to receive the SCI, determine the location of the first wireless device, and determine whether to send the feedback.

40. An apparatus for wireless communication at a wireless device, comprising: memory; and at least one processor coupled to the memory and configured to: determine a geographic location of the wireless device; transmit sidelink control information (SCI) associated with a sidelink groupcast message, wherein the SCI comprises: a zone identifier (ID) for a zone associated with the sidelink groupcast message, wherein the zone ID is based in part on the geographic location of the wireless device, and a range for feedback, wherein the range is based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message; and transmit the sidelink groupcast message.

41. The apparatus of claim 40, wherein the feedback comprises hybrid automatic repeat request (HARQ) feedback.

42. The apparatus of claim 40, wherein the at least one processor is further configured to: receive

the feedback for the sidelink groupcast message, wherein the feedback is based on the zone ID and the range indicated in the SCI.

43. The apparatus of claim 40, further comprising: a transceiver coupled to the memory and the at least one processor.

44. The apparatus of claim 40, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

45. The apparatus of claim 40, wherein the at least one processor is individually or collectively configured to determine the geographic location of the wireless device, transmit the SCI, and transmit the sidelink groupcast message.

46. An apparatus for wireless communication at a first wireless device, comprising: means for receiving sidelink control information (SCI), from a second wireless device, that indicates a zone identifier (ID) for a zone associated with a sidelink groupcast message; means for determining a location of the first wireless device; and means for determining whether to send a feedback for the sidelink groupcast message based on the location of the first wireless device and the zone ID received in the SCI, the zone ID indicating the zone associated with the sidelink groupcast message.

47. The apparatus of claim 36, wherein the feedback comprises hybrid automatic repeat request (HARQ) feedback.

48. The apparatus of claim 36, wherein the zone ID is based in part on a geographic location of the second wireless device that is a source of the sidelink groupcast message.

49. The apparatus of claim 36, further comprising: means for sending the feedback if the location of the first wireless device is within a range based on the zone ID associated with the sidelink groupcast message.

50. The apparatus of claim 39, further comprising: means for receiving an indication of the range in the SCI for the sidelink groupcast message.

51. The apparatus of claim 46, further comprising: means for determining that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and means for transmitting the feedback for the sidelink groupcast message when the first wireless device is unsuccessful in correctly receiving the sidelink groupcast message and the location of the first wireless device is within the range.

52. The apparatus of claim 46, further comprising: means for determining whether the sidelink groupcast message is received correctly; means for determining that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and means for transmitting the feedback for the sidelink groupcast message when the first wireless device is unsuccessful in correctly receiving the sidelink groupcast message and the location of the first wireless device is within the range.

53. The apparatus of claim 46, wherein a range is based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message.

54. The apparatus of claim 53, wherein the means for determining whether to send the feedback for the sidelink groupcast message are configured to determine to send the feedback based on the location of the first wireless device and a combination of the zone ID and the range for the sidelink groupcast message.

55. The apparatus of claim 46, wherein the sidelink groupcast message is for a service group, and wherein a range is indicated in a Quality of Service (QoS) profile for the service group.

56. The apparatus of claim 46, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

57. A non-transitory computer-readable storage medium storing computer executable code for wireless communication at a first wireless device, the code when executed by at least one processor cause the at least one processor to: receive sidelink control information (SCI), from a second wireless device, that indicates a zone identifier (ID) for a zone associated with a sidelink groupcast

message; determine a location of the first wireless device; and determine whether to send a feedback for the sidelink groupcast message based on the location of the first wireless device and the zone ID received in the SCI, the zone ID indicating the zone associated with the sidelink groupcast message.

58. The computer-readable storage medium of claim 57, wherein the feedback comprises hybrid automatic repeat request (HARQ) feedback.

59. The computer-readable storage medium of claim 57, wherein the zone ID is based in part on a geographic location of the second wireless device that is a source of the sidelink groupcast message.

60. The computer-readable storage medium of claim 57, further storing the computer executable code that when executed by the at least one processor cause the at least one processor to: send the feedback if the location of the first wireless device is within a range based on the zone ID associated with the sidelink groupcast message.

61. The computer-readable storage medium of claim 60, further storing the computer executable code that when executed by the at least one processor cause the at least one processor to: receive an indication of the range in the SCI for the sidelink groupcast message.

62. The computer-readable storage medium of claim 57, further storing the computer executable code that when executed by the at least one processor cause the at least one processor to: determine that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and transmit the feedback for the sidelink groupcast message when the first wireless device is unsuccessful in correctly receiving the sidelink groupcast message and the location of the first wireless device is within the range.

63. The computer-readable storage medium of claim 57, further storing the computer executable code that when executed by the at least one processor cause the at least one processor to: determine whether the sidelink groupcast message is received correctly; determine that the location of the first wireless device is within a range for the sidelink groupcast message based on the zone ID; and transmit the feedback for the sidelink groupcast message when the first wireless device is unsuccessful in correctly receiving the sidelink groupcast message and the location of the first wireless device is within the range.

64. The computer-readable storage medium of claim 57, wherein a range is based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message.

65. The computer-readable storage medium of claim 64, wherein to determine whether to send the feedback for the sidelink groupcast message, the code, when executed by the at least one processor further cause the at least one processor to determine to send the feedback based on the location of the first wireless device and a combination of the zone ID and the range for the sidelink groupcast message.

66. The computer-readable storage medium of claim 57, wherein the sidelink groupcast message is for a service group, and wherein a range is indicated in a Quality of Service (QoS) profile for the service group.

67. The computer-readable storage medium of claim 43, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

68. An apparatus for wireless device, comprising: means for determining a geographic location of the wireless device; means for transmitting sidelink control information (SCI) associated with a sidelink groupcast message, the SCI comprising: a zone identifier (ID) for a zone associated with the sidelink groupcast message, the zone ID being based in part on the geographic location of the wireless device, and a range for feedback, the range being based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message; and means for transmitting the sidelink groupcast message.

69. The apparatus of claim 68, wherein the feedback is a Negative Acknowledgement (NACK) feedback.

70. A non-transitory computer-readable storage medium storing computer executable code for wireless communication at a wireless device, the code when executed by at least one processor cause the at least one processor to: determine a geographic location of the wireless device; transmit sidelink control information (SCI) associated with a sidelink groupcast message, the SCI comprising: a zone identifier (ID) for a zone associated with the sidelink groupcast message, the zone ID being based in part on the geographic location of the wireless device, and a range for feedback, the range being based on a Quality of Service (QoS) parameter associated with the sidelink groupcast message; and transmit the sidelink groupcast message.

71. The computer-readable storage medium of claim 70, wherein the feedback is a Negative Acknowledgement (NACK) feedback.
