

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281950

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

MEKID; Samir et al.

VESSEL CLEANING ROBOTIC SYSTEM

Abstract

A vessel cleaning robotic system includes a robotic cleaner having a cylindrical central unit from which three retractable legs extend. Each leg includes an omni-directional wheel at its distal end, a motor, up to three joints for articulation, and a collar for attachment to the central unit at a proximal end. An arm, also extending from the central unit, is configured to rotate around it, with a cleaning sub-unit at its distal end and a collar at its proximal end. The arm includes a vacuum pipe and a spraying device for cleaning purposes. Integrated within the retractable legs and the arm is a monitoring unit comprising sensors for operational monitoring.

Inventors: MEKID; Samir (Dhahran, SA), NASIR; Ali (Dhahran, SA), MYSOREWALA; Muhammad Faizan (Dhahran, SA)

Applicant: KING FAHD UNIVERSITY OF PETROLEUM AND MINERALS (Dhahran, SA)

Family ID: 1000007773377

Assignee: KING FAHD UNIVERSITY OF PETROLEUM AND MINERALS (Dhahran, SA)

Appl. No.: 18/621246

Filed: March 29, 2024

Foreign Application Priority Data

SA 1020241241

Mar. 11, 2024

Publication Classification

Int. Cl.: B08B9/08 (20060101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

[0001] The present disclosure claims the benefit of Saudi patent application Ser. No. 1020241241 filed on Mar. 11, 2024, with the Saudi Authority for Intellectual Property Office, which is incorporated herein by reference in its entirety.

BACKGROUND

Technical Field

[0002] The present disclosure is directed to robotic cleaning systems, particularly to an automated robotic system for the cleaning of vessel tanks used in oil-water-gas separation processes.

Description of Related Art

[0003] The “background” description provided herein is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent it is described in this background section, as well as aspects of the description which may not otherwise qualify as prior art at the time of filing, are neither expressly nor impliedly admitted as prior art against the present invention.

[0004] In oil and gas plants, large sized vessel are used as storage tanks. These vessels are typically made of carbon steel and last for many years. These vessel tanks need internal inspection and cleaning on a regular basis. Large-scale industrial cleaning of the vessel tanks involves removing various types of residues, including oil, sludge, and sediments, from the interior surfaces of storage tanks. These residues pose significant challenges due to their chemical composition, viscosity, and the tendency to adhere strongly to the surfaces of storage tanks. Over the years, there have been introductions of various mechanical, chemical, and manual cleaning methods in the oil and gas industry. These methods range from simple manual scraping and washing techniques to more sophisticated methods involving high-pressure water jets, chemical cleaning agents, and automated machinery designed to enter and clean the tanks.

[0005] Despite these technological advancements, the state of the art in vessel tank cleaning faces significant challenges. One primary challenge is the inherent risk to human workers who are often required to enter the confined and hazardous spaces, exposing them to toxic substances and potentially dangerous conditions. The complexity of cleaning the large tanks with intricate internal structures also poses a challenge, as reaching all areas effectively can be difficult. Furthermore, the use of chemicals and large volumes of water in traditional cleaning processes raises environmental concerns. These factors, combined with the time-consuming nature of existing cleaning methods, lead to increased operational downtime and higher costs.

[0006] Some solutions have been developed to address the aforementioned challenges. For instance, CN 105457960A discloses a large, sealed storage container cleaning intelligent robot. This publication describes a system comprising a control system, a power system, a transmission system, and a cleaning system, all interconnected. The transmission system includes a support frame, a main transmission device, hoisting mechanism, rotary mechanism, stretching mechanism, and at least one mechanical arm equipped with a cleaning device. The mechanical arm, featuring a transmission arm motor and several hinged movable arms, is designed to clean the inner cavity of a storage container. A cleaning system having a cylindrical central unit with retractable and extendable legs and capability to integrate a jetting nozzle with a plurality of sensors is not disclosed.

[0007] U.S. Pat. No. 9,205,470B2 describes a robotic tank cleaning device and a method for cleaning a tank. A robotic body equipped with at least one motor attached to at least one wheel and

a cleaning head attached to the robotic body is described. The method provides for a maneuverable robotic device capable of entering a tank through a standard entry point. However, a cleaning system having a cylindrical central unit with retractable and extendable legs and capability to integrate a jetting nozzle with a plurality of sensors is not disclosed.

[0008] Accordingly, it is one object of the present disclosure to provide a solution for cleaning vessel tanks that addresses the shortcomings of existing techniques by minimizing or eliminating the need for human entry into hazardous environments, ensuring thorough and consistent cleaning of complex tank structures, reducing the use of hazardous chemicals, and minimizing operational downtime. The present disclosure includes integration of remote monitoring system and automated control system to a robotic cleaning device for enhanced efficiency of cleaning operations in an oil vessel tank which reduces the need for human entry into hazardous environments and improves the overall safety of the cleaning process.

SUMMARY

[0009] In an exemplary embodiment, a vessel tank cleaning system is provided. The vessel tank cleaning system comprises a robotic cleaner. The robotic cleaner comprises a cylindrical central unit. The robotic cleaner further comprises three retractable legs extending from the central unit. Herein, each of the retractable legs comprises an omni directional wheel at a distal end, a collar at an end proximal to the central unit, up to three joints and a motor. The robotic cleaner further comprises an arm extending from the central unit configured to rotate about the central unit. Herein, a distal end of the arm comprises a cleaning sub-unit, an end proximal to the central unit comprises a collar. Further, herein, a vacuum pipe and a spraying device are connected to the arm. In the robotic cleaner, each of the retractable legs and the arm are attached to the central unit by the collar. Herein, the collars of the retractable legs and the arm are positioned over the central unit. The vessel tank cleaning system further comprises a monitoring unit integrated in the retractable legs and the arm of the robotic cleaner, and comprising a plurality of sensors. Herein, the monitoring unit includes a controller having a processor with instructions configured to monitor operation of the robotic cleaner. The vessel tank cleaning system further comprises a control unit integrated in the central unit of the robotic cleaner and connected to the monitoring unit. Herein, the instructions of the processor are configured to communicate with the monitoring unit and control movement of the robotic cleaner. The vessel tank cleaning system further comprises a control terminal configured to communicate with the control unit of the robotic cleaner through a control cable. Herein, the control cable extends from the control terminal to the central unit. The vessel tank cleaning system further comprises a pump connected to the arm of the robotic cleaner through a fluid hose and a vacuum hose.

[0010] In some embodiments, the motor on each of the retractable legs of the robotic cleaner is coupled to an encoder.

[0011] In some embodiments, the control unit of the robotic cleaner is configured to communicate with the encoder.

[0012] In some embodiments, the plurality of sensors of the monitoring unit includes force sensors integrated in each of the retractable legs of the robotic cleaner.

[0013] In some embodiments, the plurality of sensors of the monitoring unit comprises a set of inertial sensors. Herein, the inertial sensors are integrated in the retractable legs. Further, the processor is further configured with instructions to control a position of the retractable legs. In some embodiments, the plurality of sensors of the monitoring unit comprises an image sensor integrated in the arm of the robotic cleaner. The processor of the control unit is further configured with instructions to monitor a position of the arm with the image sensor.

[0014] In some embodiments, the plurality of sensors of the monitoring unit comprises a set of displacement sensors. The processor of the control unit is further configured with instructions to monitor a movement of the robotic cleaner.

[0015] In some embodiments, the plurality of sensors of the monitoring unit comprises a set of IR

sensors.

[0016] In some embodiments, the arm of the robotic cleaner comprises four joints wherein each joint provides a degree of rotation.

[0017] In some embodiments, the arm and the retractable legs are rotational 360-degree around an axis of the central unit.

[0018] In some embodiments, the cleaning sub-unit of the arm comprises a scraper and a degreaser.

[0019] In some embodiments, the spraying device at the arm of the robotic cleaner is connected to the pump through the fluid hose. Herein, a first end of the fluid hose is connected to the pump and a second end is connected to an inlet of the spraying device.

[0020] In some embodiments, the vacuum pipe at the arm of the robotic cleaner is connected to the pump through the vacuum hose. Herein, a first end of the vacuum hose is connected to the pump and a second end is connected to the vacuum pipe.

[0021] In some embodiments, the central unit of the robotic cleaner is an elongated cylindrical unit, with the retractable legs and the arm extending from the elongated cylindrical unit along the same axis.

[0022] In some embodiments, the central unit of the robotic cleaner comprises an actuator.

[0023] In some embodiments, the control unit comprises an energy management sub-unit and a lighting sub-unit.

[0024] In some embodiments, the control unit comprises a decision support sub-unit configured to perform fault checking of a plurality of components of the robotic cleaner.

[0025] In some embodiments, the decision support sub-unit is further configured to isolate one or more components having a fault.

[0026] In some embodiments, the control unit comprises a safety check sub-unit comprising an overheat protector and a short-circuit protector.

[0027] In some embodiments, the control terminal is configured to have a two-way communication with the control unit.

[0028] The foregoing general description of the illustrative embodiments and the following detailed description thereof are merely exemplary aspects of the teachings of this disclosure, and are not restrictive.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] A more complete appreciation of this disclosure and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

[0030] FIG. 1 is an exemplary schematic block diagram of a vessel tank cleaning system, according to certain embodiments;

[0031] FIG. 2 is an exemplary simplified schematic diagram of the vessel tank cleaning system, according to certain embodiments;

[0032] FIG. 3 is an exemplary diagrammatic front planar view of a robotic cleaner of the vessel tank cleaning system, according to certain embodiments;

[0033] FIG. 4 is an exemplary diagrammatic side planar view of the robotic cleaner, according to certain embodiments;

[0034] FIG. 5 is an exemplary simplified depiction of the robotic cleaner, according to certain embodiments;

[0035] FIG. 6 is an exemplary side planar schematic of the vessel tank cleaning system during operation in an oil vessel, according to certain embodiments;

[0036] FIG. 7 is an exemplary front planar schematic of the vessel tank cleaning system during operation in the oil vessel, according to certain embodiments;

[0037] FIG. 8 is a flowchart depicting an exemplary control scheme for the robotic cleaner, according to certain embodiments;

[0038] FIG. 9 is a flowchart depicting an exemplary decision-making strategy for the operational protocol of the robotic cleaner, according to certain embodiments;

[0039] FIG. 10 is a schematic diagram depicting exemplary interactions between components of the robotic cleaner, according to certain embodiments;

[0040] FIG. 11 is an illustration of a non-limiting example of details of computing hardware used in the computing system, according to certain embodiments;

[0041] FIG. 12 is an exemplary schematic diagram of a data processing system used within the computing system, according to certain embodiments;

[0042] FIG. 13 is an exemplary schematic diagram of a processor used with the computing system, according to certain embodiments; and

[0043] FIG. 14 is an illustration of a non-limiting example of distributed components which may share processing with the controller, according to certain embodiments.

DETAILED DESCRIPTION

[0044] In the drawings, like reference numerals designate identical or corresponding parts throughout the several views. Further, as used herein, the words “a”, “an” and the like generally carry a meaning of “one or more”, unless stated otherwise.

[0045] Furthermore, the terms “approximately,” “approximate”, “about” and similar terms generally refer to ranges that include the identified value within a margin of 20%, 10%, or preferably 5%, and any values therebetween.

[0046] Aspects of this disclosure are directed to a vessel tank cleaning robotic system for maintenance and cleaning of large storage tanks, particularly in industries such as oil and gas. The vessel tank cleaning robotic system preferably integrates advanced robotics, precise control mechanisms, and multiple sensors for a fully automated, robotic approach to tank cleaning that includes testing a validation of the robotic system. In particular, the vessel tank cleaning robotic system includes a robotic cleaner with adaptable mobility, capable of navigating and operating within complex tank structures. The vessel tank cleaning robotic system significantly reduces the need for hazardous manual labor and also ensures a level of operational efficiency and safety by following a cleaning protocol based on commercial standards, while providing environmental sustainability, overcoming limitations of conventional methods for industrial tank cleaning. The vessel tank cleaning robotic system performs detection, isolation and response actions to various predetermined and unknown fault conditions using sensors and timers.

[0047] Referring to FIG. 1, illustrated is a schematic block diagram view of a vessel tank cleaning robotic system, as represented by reference numeral **100** (and thus, hereinafter, sometimes, interchangeably referred to as “vessel tank cleaning system **100**” without any limitations) of the present disclosure. The vessel tank cleaning system **100** provides a robotic solution for cleaning of industrial tanks, particularly for industries such as oil and gas. In particular, the vessel tank cleaning system **100** provides an integrated approach that combines advanced robotics with precise control and monitoring capabilities to automate the cleaning of oil vessels used in oil-water separation (as depicted in FIGS. 5 and 6, and discussed later in more detail).

[0048] As illustrated, the vessel tank cleaning system **100** includes a robotic cleaner **102**. In the present disclosure, the robotic cleaner **102** is the automated device that can enter a vessel tank for cleaning the entire volume of the vessel tank. The robot cleaner **102** has a central unit **118**. The central unit **118** forms the core of the robotic cleaner **102**, housing the primary operational and control components. The central unit **118** is designed to be capable of withstanding the harsh environmental conditions within oil tanks. The movement of the central unit **118** within the vessel tank is supported by a group of legs (shown as one leg **120** in FIG. 1 for simplicity) extending from

the central unit **118**. In addition, the central unit **118** has a rotational arm **122** for cleaning the internal surface of the vessel tank. In particular, the rotational arm **122** includes a mopping device and jetting nozzles. The vessel tank cleaning system **100** further includes a pump **116**, located external to the robotic cleaner **102**, and connected to the rotational arm **122** of the robotic cleaner **102** through one or more hoses. In particular, the pump **116** is connected to the mopping device and the jetting nozzles of the rotational arm **122**. The robotic cleaner **102** is integrated with a monitoring unit **104**. In particular, the monitoring unit **104** includes a controller **106** having a processor **108** with instructions configured to monitor operation of the robotic cleaner **102**. The robotic cleaner **102** further includes a control unit **110** connected to the monitoring unit **104**. Herein, the instructions of the processor **108** are configured to communicate with the monitoring unit **104** and control movement of the robotic cleaner **102**. The control unit **110** of the vessel tank cleaning system **100** may include several sub-units that enhance the functionality and safety of the robotic cleaner **102**, such as, energy management sub-unit **150**, lighting sub-unit **152**, decision support sub-unit **154**, and safety check sub-unit **156**. The vessel tank cleaning system **100** also includes a control terminal **112** configured to communicate with the control unit **110** of the robotic cleaner **102** through a control cable **114**. The details of each of these components, shown in FIG. 1, are provided further in the proceeding paragraphs.

[0049] Referring to FIG. 2, illustrated is a simplified high-level schematic of the vessel tank cleaning system **100** depicting the control unit **110** of the robotic cleaner **102** in communication with the control terminal **112**. Herein, the control unit **110** of the robotic cleaner **102** is disposed in communication with the control terminal **112** through a control cable **114**. The control terminal **112** may be operated by an operator to control the operations and general movement of the robotic cleaner **102**. In the present embodiments, the control terminal **112** is configured to have a two-way communication with the control unit **110**. This way the operator may send control instructions, via the control terminal **112**, to the control unit **110** for controlling operations of the robotic cleaner **102**; and may further receive data, such as data indicative of status of operations of the robotic cleaner **102**, in the control terminal **112**. In the present illustration, the control terminal **112** is represented as a computer (laptop); however, it may be appreciated that the control terminal **112** may be implemented as any suitable computing device for present purposes (as discussed later in more detail) without any limitations. The control unit **110**, as discussed, is integrated in the central unit **118** of the robotic cleaner **102**. In particular, the control unit **110** may be housed inside the central unit **118**. In an example, the control unit may be a circuitry configured to have a two-way communication with the control terminal **112**. Housing the control unit **110** inside the central unit **118** may protect circuitry of the control unit **110** when the robotic cleaner **102** is performing cleaning operation inside the vessel tank. Further, as shown in FIG. 2, the control terminal **112** is connected to the control unit **110** through a control cable **114**, i.e., the control cable **114** extends from the control terminal **112** to the central unit **118**. The control cable **114** may be in the form of a flexible, long cable used typically for communication, capable of carrying control instructions. The control cable **114** extends from the control terminal **112**, which may usually be located outside of the vessel tank, as being controlled by an operator, to the central unit **118**, passing through an entry of the vessel tank, located inside the vessel tank during operation of the robotic cleaner **102**. The control cable **114** transmits the control instructions from the control terminal **112** to the control unit **110** integrated with the central unit **118**, for controlling operation of the robotic cleaner **102**.

[0050] Referring to FIGS. 3, illustrated is a diagrammatic front planar view of the robotic cleaner **102**. FIG. 4 illustrates a side planar view of the robotic cleaner **102**. As illustrated, the robotic cleaner **102** primarily includes a central unit **118**, a group of retractable legs **120**, for example, three retractable legs as shown in FIG. 3 and an arm **122**. The central unit **118** as shown in FIG. 4 is an elongated structure, typically a cylindrical structure (hereinafter, sometimes, referred to as “cylindrical central unit **118**” without any limitations). In the present embodiments, the central unit **118** of the robotic cleaner **102** is an elongated cylindrical unit, with three retractable legs **120**. It is

to be noted that the three retractable legs **120** are similar in their physical properties, such as, for example, the length, shape, circumference, etc., however, they are also distinct because they are arranged in tandem in a specific order on the cylindrical central unit **118**, as shown in FIG. **4**, the retractable legs **120** could be **120-1**, **120-2**, **120-3** (the reference numerals not shown in FIG. **3** and FIG. **4**). Each of the three retractable legs **120** may have the capability to move separately based on the positioning of the robotic cleaner **102**. The elongated cylindrical unit further has an arm **122** extending from the elongated cylindrical unit **118** along a central axis, as shown in FIG. **4**. The elongated structure of the central unit **118** provides a balance and distribution of weight, for maintaining stability for the robotic cleaner **102** during the cleaning operation. The cylindrical shape of the central unit **118** also facilitates smooth rotation and movement for the robotic cleaner **102**, for maneuvering within the confined and complex spaces of the oil vessel **10**. Herein, the alignment of the retractable legs **120** and the arm **122** along the same axis ensures a balanced design. This allows for the retractable legs **120** and the arm **122** to deploy and retract without interfering with each other. Further, herein, the arm **122** and the retractable legs **120** are rotational 360-degree around an axis of the central unit **118**. This rotational capability greatly enhances the flexibility and reach of the robotic cleaner **102**. For the arm **122**, 360-degree rotation means it can access and clean all areas of the vessel tank without the need for the entire robotic cleaner **102** to reposition itself. Similarly, the 360-degree rotation of the retractable legs **120** enables the robotic cleaner **102** to maneuver effectively within the vessel tank, allowing for precise positioning as may be required during the cleaning process.

[0051] In the present embodiment, the robotic cleaner **102** includes three retractable legs **120** extending from the central unit **118** as shown in FIG. **3** and FIG. **4**. The robotic cleaner **102** includes three retractable legs for a standard vessel tank. In an example, for a vessel tank with larger or more complex internal space, the robotic cleaner **102** may include more than three legs, i.e., six or even up to 12 retractable legs **120** for the arm **122** to reach all corners of a complex vessel tank. The legs **120** are retractable, meaning the legs are designed to be extended or retracted as needed, for navigating the various contours and obstacles within the vessel tank **10**. The retractable legs **120** have an elongated shaft like structure. In an embodiment, the elongated shaft (retractable leg **120**) may be narrow. In an embodiment, the elongated shaft (retractable leg **120**) may have a wider inner diameter. In an embodiment, the retractable leg **120** may be hollow. In an embodiment, the retractable leg **120** may be a solid (not hollow) elongated shaft.

[0052] FIG. **5** illustrates a detailed diagrammatic view of the robotic cleaner **102**, depicting its various components, while showing only one retractable leg **120** for simplicity and clarity. Each of the retractable legs **120** has a distal end **120a** (i.e., the end farthest from where the corresponding retractable leg **120** connects to the central unit **118**) and a proximal end **120b** (i.e., the end closest to the central unit **118**). In general, each of the three retractable legs **120** are identical in design and configuration for purposes of the present disclosure. The retractable legs **120** provide stability and adaptability to the robotic cleaner **102**, when in operation. Each of the retractable legs **120** includes an omni directional wheel **124** at the distal end **120a**. The omni directional wheels **124**, as employed, are wheels capable of moving in multiple directions, not just forward and backward. Each retractable leg **120**, fitted with the omni directional wheel **124**, allows for movement of the robotic cleaner **102** in various directions, for navigating the complex inner surfaces of the vessel tank, enhancing the overall mobility of the robotic cleaner **102**. Also, each of the retractable legs **120** is connected to the central unit **118** through a collar **126** or a leg collar **126** at the proximal end **120b**. The collars **126** serves as connecting points between each corresponding retractable leg **120** and the central unit **118**. The collar **126** also plays a role in the retracting mechanism of the corresponding retractable leg **120**, allowing the retractable leg **120** to extend or retract smoothly while maintain a secure connection with the central unit **118** during operation. Further, each of the retractable legs **120** includes joints (as generally represented by reference numeral **128**). Each retractable legs **120** may include multiple joints, for example, up to three joints **128**. The inclusion

of the multiple joints **128** in each retractable leg **120** adds a significant degree of flexibility and articulation. This feature enables each of the retractable legs **120** to bend at the multiple joints **128** in order to bend (curl) the retractable leg **120** inward or outward as may be required for adjusting the stance and position of the robotic cleaner **102** to conform to the internal structure of the vessel tank. This adaptability ensures that the robotic cleaner **102** can reach all areas inside the vessel tank. Furthermore, each of the retractable legs **120** includes a motor **130**. The motor **130** in each retractable leg **120** may control the extension, retraction, and articulation of the corresponding retractable leg **120**, allowing for precise and controlled movement. This provides the robotic cleaner **102** with the ability to position itself optimally within the oil vessel tank for effective cleaning. The motor **130** in each retractable leg **120** contributes to the autonomous nature of the robotic cleaner **102**, reducing the need for manual adjustment and intervention. The motor **130** is typically a servo motor or a stepper motor, which receive control signals as input to function. When a servo motor or a stepper motor is commanded to move, it will move to the position and hold that position. In an embodiment, instructions from the monitoring unit or the control unit is used as control signals for the motor **130**, in order to move the retractable legs **120**. In an example, the motor **130** can be a DC motor.

[0053] In some embodiments, as better illustrated in FIG. 5, the motor **130** on each of the retractable legs **120** of the robotic cleaner **102** is coupled to an encoder **132**. As discussed, the primary function of the motors **130** is to control the movement of the retractable legs **120**. This includes extending, retracting, and maneuvering the retractable legs **120** to facilitate the navigation and stability of the robotic cleaner **102** within the oil vessel **10**. The encoder **132**, as employed, converts motion (as provided by the corresponding motor **130**) into an electrical signal, which may be transmitted to a control circuitry of the robotic cleaner **102**. In present embodiment, the control unit **110** of the robotic cleaner **102** is configured to communicate with the encoder **132** (i.e., each of the encoders **132**). In some examples, the encoders **132** may transmit their readings to the monitoring unit **104** integrated in the retractable legs **120** of the robotic cleaner **102**, which, in turn, may transmit these readings to the control unit **110** of the robotic cleaner **102**. In present configuration, the encoders **132** may provide feedback on the position of each retractable leg **120**. This information may be utilized to understand how much each leg has extended or retracted and its current position. The encoder **132** may also monitor the speed at which the corresponding motor **130** of the retractable leg **120** is operating. This allows control of the speed of movement of the retractable leg **120**, ensuring smooth and controlled navigation. It may be contemplated that with each retractable leg **120** having the motor **130** and the encoder **132**, the control unit **110** can synchronize the movement of all of the retractable legs **120**, for coordinated movement of the robotic cleaner **102**, especially for maintaining balance and stability while navigating uneven surfaces inside the vessel tank.

[0054] The robotic cleaner **102** further includes the arm **122** extending from the central unit **118**, as shown in FIG. 3, FIG. 4, and FIG. 5. The arm **122** is a structural element of the robotic cleaner **102**, extending outward from the central unit **118**. The primary role of the arm **122** is to perform the actual (e.g., direct contact) cleaning tasks within the vessel tank. The design of the arm **122** allows it to reach various parts of the vessel tank. The arm **122** is configured to rotate about the central unit **118**. This rotational capability provides the arm **122** with the flexibility to maneuver around the central unit **118**. In particular, the rotation adds to the efficiency and effectiveness of the cleaning process by allowing the arm **122** to access and clean various angles and corners of the oil vessel **10**. This enables the arm **122** to cover a wide area within the oil vessel tank, reaching different sections without the need for the entire robotic cleaner **102** to reposition itself.

[0055] As illustrated in FIG. 5, the arm **122** has a distal end **122a** (i.e., the end farthest from where the arm **122** connects to the central unit **118**) and a proximal end **122b** (i.e., the end closest to the central unit **118**). As shown, the distal end **122a** of the arm **122** includes a cleaning sub-unit **134**. The cleaning sub-unit **134** is the component that directly engages with interior of the oil vessel tank

for cleaning. The cleaning sub-unit **134** may include various cleaning tools and mechanisms, such as brushes, scrapers, nozzles for spraying cleaning agents, or suction devices for removing residues. The configuration of the cleaning sub-unit **134** is designed to effectively remove sludge, oil residues, and other contaminants from the surfaces of the vessel tank. Further, the end **122b** proximal to the central unit **118** includes a collar or an arm collar **136**. The collar **136** serves as a junction or connection between the arm **122** and the central unit **118**. The collar **136** is also integral to rotational mechanism of the arm **122**, providing a stable and secure connection that allows the arm **122** to rotate smoothly while maintaining its attachment to the central unit **118**. In some examples, the collar **136** may include bearings or other mechanical components that facilitate the smooth rotation of the arm **122**.

[0056] As better illustrated in FIG. 5, each of the retractable legs **120** and the arm **122** are attached to the central unit **118** by the collars **126**, **136**. Herein, the collars **126** and **136** of the retractable legs **120** and the arm **122**, respectively, are positioned over the central unit **118**. This design configuration helps with the overall stability, mobility, and operational efficiency of the robotic cleaner **102**. The collars **126**, **136** are designed to allow for both secure attachment and the movement necessary for the operation of the retractable legs **120** and the arm **122**. As discussed, the retractable legs **120** and the arm **122** are each connected to the central unit **118** of the robotic cleaner **102**, with the central unit **118** acting as the core or the main body of the robotic cleaner **102**, from which these components extend. The connection provided by the collars **126**, **136** ensures that both the retractable legs **120** and the arm **122** are securely attached to the central unit **118** while allowing for the necessary movement and flexibility required for their functions. In the case of the retractable legs **120**, the collars **126** enable them to extend, retract, and possibly rotate or articulate as needed for maneuverability. For the arm **122**, the collar **136** allows for rotational movement of the arm **122** for effectively performing the cleaning of entire circumferences along planes of inner surfaces of the oil vessel **10**.

[0057] Further the arm **122** of the robotic cleaner **102** comprises multiple joints (not shown). Herein, each joint provides a degree of rotation. The incorporation of multiple joints in the design of the arm **122** is aimed at enhancing flexibility and reach of the arm **122**, similar to the multiple joints of the three retractable legs **120**. The multiple joints of the arm **122** may have the capability to bend individually so as to promote bending/curling of the arm **122** inward or outward as to position the arm **122** for cleaning. The multiple joints promote the moving of the arm **122** to clean all corners of the oil vessel **10**. In an embodiment, the arm **122** comprises two, three or up to four joints. Each of these multiple joints provides a degree of rotation, this adds a level of dexterity to movements of the arm **122**. The rotation at each joint of the multiple joints means that the arm **122** can bend and twist in various directions, allowing it to adjust its angle and position as required for effective cleaning.

[0058] In some embodiments, the central unit **118** of the robotic cleaner **102** comprises an actuator (not shown). The actuator may be responsible for providing mechanical power for the operation of various parts of the robotic cleaner **102**. The actuator within the central unit **118** may also be responsible for converting control signals received from processor **108** into appropriate mechanical motion. The actuator may facilitate various types of motion, including linear and rotational movements. For instance, the actuator may extend or retract the retractable legs **120**, rotate the arm **122** or adjust its angle, and possibly control other mechanical components necessary for the cleaning process, in the robotic cleaner **102**. Further, the monitoring unit **104** is integrated in the retractable legs **120** and the arm **122** of the robotic cleaner **102** (schematically illustrated in FIG. 5). As discussed, the monitoring unit **104** is configured to monitor operation of the robotic cleaner **102**. For this purpose, the monitoring unit **104** includes a plurality of sensors (as represented by reference numeral **146** in FIG. 5) that are placed at varied positions on the retractable legs **120** and on the arm **122**.

[0059] In an embodiment, the plurality of sensors **146** of the monitoring unit **104** includes force

sensors integrated in each of the retractable legs **120** of the robotic cleaner **102**. In an embodiment, a group of force sensors may be attached at multiple positions, at a distance from each other, and on all sides of the retractable legs **120**. The group of sensors may be attached to an internal surface of the shaft like structure of the retractable legs **120**. In an example, the group of sensors may be attached to the retractable legs **120** externally. These force sensors may be configured for assessing the contact pressure exerted by the retractable legs **120** on surfaces of the oil vessel **10**. This information may be utilized for maintaining the stability of the robotic cleaner **102** as it navigates the interior of the oil vessel **10**. By constantly monitoring the force exerted, the monitoring unit **104** can adjust the extension or retraction of the retractable legs **120** to ensure optimal grip and balance, preventing slips or falls that could disrupt the cleaning process or damage interior of the oil vessel **10**. In another embodiment, the plurality of sensors **146** of the monitoring unit **104** comprises a set of inertial sensors. Herein, the inertial sensors are integrated in the retractable legs **120**. In an embodiment, a group of inertial sensors may be attached. These inertial sensors may be configured for detecting changes in movement and orientation of the retractable legs **120**, providing data on the position of the robotic cleaner **102** within the oil vessel **10**. The processor **108** is further configured with instructions to control the position of the retractable legs **120**. This control helps in navigating complex tank environments, allowing for adjustments in stance and movement of the robotic the cleaner **102** to optimize cleaning coverage and maneuverability. In yet another embodiment, the plurality of sensors **146** of the monitoring unit **104** comprises an image sensor integrated in the arm **122** of the robotic cleaner **102**. The image sensor is attached to an external surface of the arm **122**, such that, the image sensor can capture images of internal space of the oil vessel **10**. The image sensor may be configured for visual monitoring, providing real-time imagery of position of the arm **122** and the areas it is cleaning. Herein, the processor of the control unit (which may be same as the processor **108**) is further configured with instructions to monitor the position of the arm **122** with the image sensor. The processor **108** of the control unit **110** uses the data from the image sensor to adjust the position of the arm **122**, ensuring it reaches and effectively cleans all required areas of the oil vessel **10**. In still another embodiment, the plurality of sensors **146** of the monitoring unit **104** comprises a set of displacement sensors. The set of displacement sensors may be configured for tracking the movement of the robotic cleaner **102** within the oil vessel **10**. In an embodiment, the displacement sensors may be attached to a top side of the central unit **118**. Herein, the processor **108** of the control unit **110** is further configured with instructions to monitor a movement of the robotic cleaner **102**. That is, the data gathered by the set of displacement sensors is processed to monitor progress and path of the robotic cleaner **102**, ensuring that it covers the entire interior surface of the oil vessel **10** without unnecessary repetition or missed spots. In still another embodiment, the plurality of sensors **146** of the monitoring unit **104** comprises a set of IR (infrared) sensors. These IR sensors (or alternatively, ultrasonic sensors) are particularly useful for detecting obstacles, measuring distances, and assessing internal conditions of the oil vessel **10**, such as presence of the sludge **12** on its internal surfaces. In an embodiment, the IR sensors are located on the retractable legs **120**, the arm **122** and the central unit **118**. In general, the integration of the plurality of sensors **146** based on such diverse technologies with the monitoring unit **104** of the robotic cleaner **102** enhances its functionality significantly.

[0060] FIG. **6** and FIG. **7** illustrate the vessel tank cleaning system **100** in operation, with the robotic cleaner **102** being located inside the oil vessel (as represented by referenced numeral **10**). The oil vessel **10**, herein, may generally be in the form of a large cylindrical pipe of a circular circumference or rectangular circumference, with sufficient radius (along 'r') and length (along 'z') to accommodate the robotic cleaner **102** (which in itself could expand or contract, as discussed later, to move within the oil vessel **10** for its cleaning purposes). The oil vessel **10** includes an opening (manway **14**), generally built for a human to enter for manual cleaning. The manway **14** is a way for the robotic cleaner **102** to enter the oil vessel **10** in the present disclosure. As discussed, the arm **122** of the robotic cleaner **102**, in general, is implemented for cleaning purposes. Herein, a

vacuum pipe and a spraying device (not shown for simplicity) are connected to the arm **122**. The vacuum pipe may be configured for generating vacuum to suck out sludge (as represented by reference numeral **12** in FIGS. **6** and **7**) for its effective removal from the interior of the oil vessel **10**. The vacuum pipe, on the arm **122**, enables the robotic cleaner **102** to not only dislodge but also efficiently evacuate the sludge **12** from the oil vessel **10**, as may be required for thorough cleaning. The spraying device may be configured with applying cleaning agents such as water or specialized solvents to the interior surfaces of the oil vessel **10**. Thereby, the spraying device may help with in breaking down stubborn residues in the sludge **12** and ensuring even distribution of cleaning agents across the surfaces of the oil vessel **10**. In an example configuration, the vacuum pipe and the spraying device may form part of the cleaning sub-unit **134** of the arm **122**, in the robotic cleaner **102**, without departing from the spirit and the scope of the present disclosure. It may also be appreciated that the impurities generally consist of oil-based substances, sand, and small stones forms the sludge **12** in the oil vessel **10**.

[0061] Further, the pump **116** (as shown in FIG. **6**) may be configured for facilitating the movement of fluids to and from the arm **122** within the robotic cleaner **102**. The integration of the pump **116** with the arm **122** is achieved through a set of hoses, specifically designed for their respective purposes. Herein, the pump **116** is connected to the arm **122** of the robotic cleaner **102** through a fluid hose **142** and a vacuum hose **144**, passing through the manway **14** in the oil vessel **10**. Specifically, the spraying device at the arm **122** of the robotic cleaner **102** is connected to the pump **116** through the fluid hose **142**. In an embodiment, the inlet of the spraying device and the vacuum pipe are located at the intersection of the central unit **118** and the arm **122**. Herein, a first end **142a** of the fluid hose **142** is connected to the pump **116** and a second end **142b** is connected to an inlet of the spraying device. The fluid hose **142** connects the pump **116** to the spraying device on the arm **122**, for transporting the cleaning agents from the pump **116** to the spraying device. Further, the vacuum pipe at the arm **122** of the robotic cleaner **102** is connected to the pump **116** through the vacuum hose **144**. Herein, a first end **144a** of the vacuum hose **144** is connected to the pump **116** and a second end **144b** is connected to the vacuum pipe **138**. The vacuum hose **144** connects the pump **116** to the vacuum pipe, for removal of debris and liquids collected by the vacuum pipe away from the oil vessel **10**. The pump **116** provides the driving force for the transportation of cleaning agents to the spraying device through the fluid hose **142**, and the evacuation of dislodged materials of the sludge **12**, via the vacuum pipe, and through the vacuum hose **144**.

[0062] In an embodiment, the cleaning sub-unit **134** of the arm **122** comprises a scraper (as shown in FIG. **7** by a triangular structure at the cleaning sub-unit **134** of the arm **122**) and a degreaser (not shown in the accompanied drawings). As discussed, in the vessel tank cleaning system **100**, the cleaning sub-unit **134** of the arm **122** is specifically designed to handle the task of cleaning the interior surfaces of the oil vessel **10**. The scraper, as part of the cleaning sub-unit **134**, may have the primary function to physically dislodge and remove tough, adherent residues from surfaces of the oil vessel **10**, such as hardened sludge, rust, and other forms of buildup that are difficult to remove. Further, the degreaser, as part of the cleaning sub-unit **134**, may have the primary function to break down and remove oily and greasy residues, which are common in the oil vessel **10** (when used in industries like oil and gas). The use of degreaser may involve the application of chemical agents or solvents that dissolve or emulsify grease and oil, making them easier to remove. The degreaser may be a tube (or pipe) like structure attached to the arm **122**, the tube (or pipe) filled with the chemical agent or solvents and having a capability to apply the chemical agent or solvents to the internal walls of the oil vessel **10**. Thus, the combination of the scraper and the degreaser in the cleaning sub-unit **134** provides a comprehensive approach to cleaning of the oil vessel **10**.

[0063] In the vessel tank cleaning system **100**, as described earlier, the control unit **110** may include several sub-units that enhance the functionality and safety of the robotic cleaner **102**. In an embodiment, as illustrated in FIG. **1**, the control unit **110** comprises an energy management sub-

unit **150** and a lighting sub-unit **152**. The energy management sub-unit **150** is responsible for optimizing the energy consumption of the robotic cleaner **102**. The energy management sub-unit **150** ensures that the robotic cleaner **102** operates efficiently, minimizing energy waste and extending the duration of cleaning operations. The lighting sub-unit **152** provides illumination within the oil vessel **10**, aiding the operator to effectively navigate the robotic cleaner **102** for cleaning the oil vessel **10**, particularly in low-light conditions typically found inside industrial tanks. In another embodiment, the control unit **110** comprises a decision support sub-unit **154** configured to perform fault checking of a plurality of components of the robotic cleaner **102**. The decision support sub-unit **154** may continuously monitor the status of various components and identify any operational anomalies or faults. Herein, the decision support sub-unit **154** is further configured to isolate one or more components having a fault. That is, upon detecting the fault, the decision support sub-unit **154** is further configured to isolate the affected component(s), for maintaining the operational integrity of the robotic cleaner **102** and for preventing minor issues from escalating into major failures. In yet another embodiment, the control unit **110** comprises a safety check sub-unit **156** comprising an overheat protector and a short-circuit protector (not shown). Herein, the overheat protector may prevent the robotic cleaner **102** from overheating, which can be a significant risk given the electrical components and the potentially flammable environment in which the robotic cleaner **102** operates. Similarly, the short-circuit protector safeguards the robotic cleaner **102** against electrical faults, for preventing any electrical hazards. The control cable **114** extends from the control terminal **112** to the central unit **118**, passing the oil vessel **10** through a manway **14** (which is in the form of an opening in the oil vessel **10**). The sub-units of the control unit **118** are in communication with the control terminal **112**, to send information collected by the sub-units to the control terminal **112** and to receive instructions from the control terminal **112**. In an example, the decision support sub-unit **154** collects information on faults in the system, communicates the information from the control unit **110** (decision support sub-unit **154**) to the control terminal **112**. Based on the fault type or a degree of impact of the fault, an operator at the control terminal **112** can accordingly send back instructions to the decision support sub-unit **154** through the control cable **114** on isolation of the faults.

[0064] In the present disclosure, a general cleaning process is followed which includes inspection and cleaning of a vessel tank in oil and gas industry. General maintenance and inspection of the oil and gas plant are followed, which are isolating the oil vessel tank that requires cleaning, opening of all entry nozzles of the vessel tank, performing external/internal initial inspection, inspecting for hydro-jetting, removing any internals of the vessel tank such as, trays, filters, distributors, deflectors, vortex breaker depleted anodes, defective insulation kits of anode monitoring system (AMS), etc., weighing any content of the vessel tank, cleaning the internal space of the vessel tank using the robotic cleaner **102**, repairing and replacing any components of the vessel tank as required, coating the internals, conducting a final inspection, seeking approval for closing manways, closing the vessel tank.

[0065] In the present disclosure, a method for cleaning the internal space of the vessel tank using the vessel tank cleaning system **100** is defined. A preliminary step of the method includes drainage of the contents of the vessel tank **10** such as, the oil and depressurizing the tank. Next step is to open manway of such a vessel tank **10** and enter the robotic cleaner **102** through the manway. The robotic cleaner **102** is then initialized and set to cleaning by the control unit **110** to perform hydro jetting using the fluid hose **142** connected to the arm **122** and the pump **116**, and removing any sludge **12** using the arm **122** and other inputs such as demulsifier, liquid chemicals, and further suction the sludge through vacuum hose **142** or a drain of the vessel tank **10**. The removal of sludge is performed as the robotic cleaner navigates through the entire internal space of the vessel tank by controlling movement of the robotic cleaner **102** through the control terminal **112**, the control unit **110** and the monitoring unit **104**. The robotic cleaner further performs steam cleaning with a degreaser connected to the arm **122**. The robotic cleaner finally performs inspection of the vessel

tank using the plurality of sensors **146**, typically the image sensor and instructions from the control terminal **112**. A few additional steps may be performed as part of the method for cleaning the internal space of the vessel tank, such as, drying of the internal space, and in-line scraping methods. [0066] Referring now to FIG. **8**, illustrated is a flowchart (as represented by reference numeral **800**) depicting an exemplary control scheme for the robotic cleaner **102**, outlining the processes involved in both the translational motion of the central unit **118** using the retractable legs **120** and the motion of the arm **122** therein. For controlling motion of the retractable legs **120**, a two-level control system may be implemented. At the upper level, camera imaging and ultrasonic sensors (of the plurality of sensors **146**) of the monitoring unit **104** contribute to the determination of desired location of the robotic cleaner **102**. The image sensors, inertial sensors, and IR sensors **146** gather visual and distance data, which inform the control unit **110** for an operation decision and obstacle avoidance strategy. In an example, the control unit **110** receives information from the plurality of sensors **146** of the monitoring unit **104**. In an example, the processor **108** of the controller **106** of the monitoring unit **104** processes the information from the plurality of sensors **146** and generates instructions for the retractable legs **120**. Based on this input, a trajectory for the retractable legs **120** is generated, creating a planned path that accounts for current tasks and the surrounding environment of the robotic cleaner **102**. Simultaneously, an Inertial Measurement Unit (IMU) and force sensors **146** (of the monitoring unit **104**) provide stabilization data to the leg stabilization controller **106** (of the monitoring unit **104**). These sensors **146** detect the orientation of the robotic cleaner **102** and the forces acting upon it, allowing for real-time adjustments to maintain balance and stability. Further, at the lower control level, inverse kinematics for the motor joints of the retractable legs **120** are used to calculate the desired joint angles necessary for the retractable legs **120** to achieve the generated trajectory. The encoders **132** for the motors **130** then provide feedback to the controller **108** for motors **130**, ensuring that the actual movement matches the desired trajectory. This feedback loop provides precision and allows the robotic cleaner **102** to adapt its movement in response to the physical constraints of the environment.

[0067] Controlling motion of the arm **122** for the robotic cleaner **102** involves a similar process as shown in FIG. **8**. Camera imaging and ultrasonic sensors using image sensors **146** of the monitoring unit **104**, input into the determination of the desired end effector location, again informed by operational decisions and the need for obstacle avoidance by controller **108** of the monitoring unit **104** and/or the control unit **110**. Inverse kinematics are employed to determine the desired joint angles for the multiple joints of the arm **122** that will position the end effector at the required location. The encoders **132** provide positional feedback to the controller **108** and/or the control unit **110** for motors of the arm **122**, to achieve the precise movement. This feedback ensures that motion of the arm **122** is accurate and the actual joint angles of the multiple joints of the arm **122** correspond to the desired angles calculated by the inverse kinematics. In both control processes, the actuators execute the commands from their respective controllers, driving the retractable legs **120** and the arm **122** to perform the necessary movements. This integrated control system enables the robotic cleaner **102** to navigate and clean effectively, adjusting its position and the position of its cleaning sub-unit **134** in response to the internal environment and any obstacles present in the oil vessel **10**.

[0068] Referring now to FIG. **9**, illustrated is a flowchart (as represented by reference numeral **900**) depicting an exemplary decision-making strategy for the operational protocol of the robotic cleaner **102**. This strategy is integral to the functioning of the robotic cleaner **102**, especially in ensuring efficient, safe, and autonomous operation. At startup, the robotic cleaner **102** initiates a system check to evaluate the health status of its components. If a manual check is deemed necessary, it is conducted before the count check, which determines if the system checks have been completed the required number of times. If the system check results are satisfactory, the robotic cleaner **102** transitions into normal operation mode. During normal operation, the robotic cleaner **102** continuously monitors its functionality through the decision support sub-unit **154**, which is a high-

level autonomous entity. The decision support sub-unit **154** utilizes inputs from various sensors and measuring instruments to assess the condition of the robotic cleaner **102**. The decision support sub-unit **154** operates on pre-defined thresholds and critical time durations to activate, deactivate, or modify operation conditions for the robotic cleaner **102**. If the decision support sub-unit **154** detects a fault during operation, it employs fault diagnosis algorithms to identify the issue. Upon fault detection, the decision support sub-unit **154** is programmed to isolate the affected component or operational mode. For instance, if a motor fails, the operations that rely on that motor are disabled, and a fault flag is raised. If the fault affects a non-critical component like a broom or mop, the system may either disable the specific cleaning mode or switch to a redundant tool. For example, an algorithm implemented by the decision support sub-unit **154** for the vessel tank cleaning system **100** of the present disclosure, specifically for the robotic cleaner **102** therein, is as shown in Table 1.

TABLE-US-00001 TABLE 1 Algorithm implemented by decision support sub-unit Algorithm steps
Process Main Routine Robot is initiated, the robot controller is START instructed to perform a system (robot) check: InitiateRobot (1) On passing the system check, the robot is SystemCheck instructed to initiate mount; (2) On failing the WaitForSystemCheck system check, the fault is compared to a If (SystemCheck == Okay) threshold; a warning is generated and robot is InitiateMount instructed to be on standby when fault is greater Else than threshold; Robot is initiated again when StartupFail + + fault is less than threshold. If (StartupFail ≥ Threshold.sub.1) StartupWarningOn RobotStandby Else Goto: InitiateRobot InitiateMount Robot mount is initiated, initial scan is WaitForMount performed: (1) On successful mount, scan 1 is If (Mount == Okay) initiated; (2) If mount fails, fault is compared to InitiateScan1 threshold, warning is generated, and robot is on Else standby when fault is greater than threshold; MountFail + + mount is initiated again when fault is less than If (MountFail ≥ Threshold.sub.2) threshold. MountWarningOn RobotStandby Else Goto: InitiateMount WaitForScan1 Scan 1 is initiated: (1) If scan 1 is successful, If (Scan1 == Okay) robot is instructed to initiate cleaning; (2) If InitiateCleaning scan 1 fails, fault is compared to threshold, Else warning is generated, and robot is on standby Scan1Fail + + when fault is greater than threshold; scan 1 is If (Scan1Fail ≥ Threshold.sub.3) initiated again when fault is less than threshold. Scan1WarningOn Else Goto: InitiateScan1 WaitForCleaning Cleaning is initiated: (1) On successful If (Cleaning == Okay) cleaning, scan 2 is initiated; (2) If cleaning fails, InitiateScan2 fault is compared to threshold, warning is Else generated, and robot is on standby when fault is CleaningFail + + greater than threshold; cleaning is initiated If (CleaningFail ≥ Threshold.sub.4) again when fault is less than threshold. CleaningWarningOn RobotStandby Else Goto: InitiateCleaning WaitForScan2 Scan 2 is initiated: (1) If scan 2 is successful, If (Scan2 == Okay) robot is instructed to generate report of CompileCleaningReport complete cleaning and shutdown; (2) If scan 2 InitiateShutdown fails, fault is compared to threshold, warning is Else generated, and robot is on standby and wait for Scan2Fail + + shutdown is initiated. If shutdown operation If (Scan2Fail ≥ Threshold.sub.5) fails, warning is generated, and robot is on Scan2WarningOn standby. RobotStandby WaitForShutdown If(ShutdownFail) ShutdownWarningOn RobotStandby END Interrupt Routine 1 (Fault Detection Identification Intermediate checks are performed for all and Reconfiguration) sensors: (1) On successful check of all sensors, for (AllSensorData) operation of robot is continued; (2) On CheckRange detecting a failure of one or more sensors, a If (OutOfRange) FDIR (Fault Detection Identification and InitiateFDIR Reconfiguration) routine is initiated. end for END Sub Routine FDIR Initiation of FDIR, pre-defined fault check is for (AllPreDefinedFaults) performed for preconditions: CheckPreCondition (1)Reconfiguration is performed when If (PreCondition == Satisfied) preconditions are successful; (2) Warning is FaultFlagOn generated, and robot is on standby. CheckReconfiguration If (Reconfiguration == Available) ActivateReconfiguration end for If (NoFaultFlag) UnknownFaultWarningOn RobotStandby END Interrupt Routine 2 (Energy Management) Intermediate check for energy

management is If (IdleTime $\geq$ Threshold.sub.6) performed: When robot is idle for a time longer IdleWarningOn than threshold, warning is generated, and robot RobotStandby is on standby. Interrupt Routine 3 (Safety) Intermediate check for safety is performed: If (CurrentSensor When a sensor has a current value (1) higher $\geq$ Threshold.sub.7 or CurrentSensor == NaN) than threshold or (2) Zero, emergency power EmergencyPowerCut cut is initiated.

[0069] In the present disclosure, the decision-making strategy within normal operation and post-fault scenarios is optimized by a mix of model-based and rule-based decision policies. Model-based policies depend on the operational states and state transitions of the robotic cleaner **102**, while rule-based policies are applied hierarchically for situations not covered by the model. For safety, the robotic cleaner **102** is equipped with systems like overheat protection and short-circuit protection, which are integrated parts of the onboard decision support system. These systems are designed to prevent damage to the robot and ensure safe operation within the potentially hazardous environment of the oil vessel **10**. Energy management is another crucial function of the control unit **110**. It conserves energy during operation by managing the duration of various operational modes and deactivating power supply to components not needed for the current mode. The system prevents overuse or inefficient use of energy, such as when a broom is detected cleaning the same spot for too long, by generating a warning and potentially interrupting operation if no change is detected within a specified time.

[0070] Referring to FIG. **10**, illustrated is a schematic (as represented by reference numeral **1000**) depicting exemplary interactions between the controller **108** of the monitoring unit **104** and/or the control unit **110** and the mechanical parts, such as, the plurality of sensors **146**, actuators, and motor drives of the robotic cleaner **102**, for controlling the retractable legs **120** and the arm **122** thereof. The control of motion of the retractable legs **120** involves a high-level, two-layer operation. Initially, the trajectory generation for the retractable legs **120** is planned by a remote operator, for example, at the control terminal **112**, who monitors interior of the oil vessel **10** using a camera (of image sensor of plurality of sensors **146**) installed on the arm **122**. The operator selects a location for the robotic cleaner **102** to reach, and this input is received from the control terminal **112** by the control unit **110**. To navigate the robotic cleaner **102** to the desired location, the control unit **110** generates motion trajectories for all three retractable legs **120**, ensuring coordinated movement and communicates the motion trajectories to the controller **108** of the monitoring unit **104**. The processor **106** of the controller **108** accordingly generates instructions for the retractable legs **120** and the arm **122**. During this process, data from ultrasonic sensors **146** on the retractable legs **120** is used to adjust the motion trajectories, avoiding obstacles, and ensuring feasible movement. Concurrently, the stabilization control for the retractable legs **120** maintains balance for the robotic cleaner **102**. The gait for the retractable legs **120**, involving the sequence of lifting and placing, is adjusted to keep the robotic cleaner **102** steady during both movement and cleaning operations. Stability is managed by the stabilization controller for the retractable legs **120**, which processes measurements from force sensors and IMUs indicating the tilt angles of the retractable legs **120**.

[0071] Subsequently, the low-level control takes over, utilizing the inverse kinematics of the retractable legs **120** to calculate the desired joint angles for the motors **130** therein. A PID controller at the control unit **110** generates commands for the motors **130** via the monitoring unit **104** adjusting the motors **130** to achieve these angles. Feedback from the IMUs and force sensors **146**, resulting from the motion, is provided to the high-level stabilization controller of the control unit **110** to refine the stability process. The upper part of the retractable legs **120**, which includes a telescopic linear actuation mechanism, extends to anchor itself onto surfaces of the oil vessel **10**. A force sensor **146** and the control unit **110** at the end of this mechanism ensures that the necessary holding force is applied to maintain position of the robotic cleaner **102** during operation.

[0072] Further, the control of the arm **122** using the control unit **110**, a multiple-joint limb (up to four-joint limb) with 360° rotation capability, follows a procedure where the operator at the control

terminal **112** selects the desired end-effector configuration for the cleaning task. The control unit **110** receives this input from the control terminal **112** via the control cable **114** and processes it, with ultrasonic sensors **146** of the monitoring unit **104** ensuring a clear path. The motion of the arm **122** is managed through inverse kinematics calculations for the joint angles of the multiple joints of the arm **122** and a PID feedback controller of the control unit **110** that sends precise commands to its motors. A force sensor **146** at the end-effector ensures the application of sufficient force for cleaning, while feedback from a displacement sensor **146** is used to attain the desired motion of the end effector, facilitating the cleaning operation.

[0073] The vessel tank cleaning system **100** of the present disclosure provides several advantages over the existing manual and semi-automated cleaning methods. The automation of the cleaning process significantly reduces the need for human intervention, thereby minimizing the risks associated with manual cleaning in hazardous environments. The design of the vessel tank cleaning system **100**, featuring the robotic cleaner **102** with the retractable legs **120** and the arm **122**, provides required reach and maneuverability, ensuring a thorough and efficient cleaning process. The use of omni directional wheels **124** in the retractable legs **120** allows for smooth and versatile movement within the oil vessel **10**, a significant improvement over the limited mobility of traditional cleaning methods. The integration of the sensors **146** in the monitoring unit **104** provides a level of situational awareness and operational precision that is unattainable with manual or semi-automated systems. Moreover, the advanced control mechanisms **150-156** within the control unit **110**, ensure a high degree of reliability and safety, enhancing ability of the vessel tank cleaning system **100** to adapt to different cleaning scenarios and further improving its effectiveness compared to traditional methods.

[0074] Further details of the hardware description of the computing environment according to exemplary embodiments is described with reference to FIG. **11**. In FIG. **11**, a controller **1100** is described as representative of control systems for the vessel tank cleaning system **100** in which the controller **1100** is a computing device which includes a CPU **1101** which performs the processes described above/below. The process data and instructions may be stored in memory **1102**. These processes and instructions may also be stored on a storage medium disk **1104** such as a hard drive (HDD) or portable storage medium or may be stored remotely.

[0075] Further, the claims are not limited by the form of the computer-readable media on which the instructions of the inventive process are stored. For example, the instructions may be stored on CDs, DVDs, in FLASH memory, RAM, ROM, PROM, EPROM, EEPROM, hard disk or any other information processing device with which the computing device communicates, such as a server or computer.

[0076] Further, the claims may be provided as a utility application, background daemon, or component of an operating system, or combination thereof, executing in conjunction with CPU **1101**, **1103** and an operating system such as Microsoft Windows 7, Microsoft Windows 10, Microsoft Windows 11, UNIX, Solaris, LINUX, Apple MAC-OS, and other systems known to those skilled in the art.

[0077] The hardware elements in order to achieve the computing device may be realized by various circuitry elements, known to those skilled in the art. For example, CPU **1101** or CPU **1103** may be a Xenon or Core processor from Intel of America or an Opteron processor from AMD of America, or may be other processor types that would be recognized by one of ordinary skill in the art. Alternatively, the CPU **1101**, **1103** may be implemented on an FPGA, ASIC, PLD or using discrete logic circuits, as one of ordinary skill in the art would recognize. Further, CPU **1101**, **1103** may be implemented as multiple processors cooperatively working in parallel to perform the instructions of the inventive processes described above.

[0078] The computing device in FIG. **11** also includes a network controller **1106**, such as an Intel Ethernet PRO network interface card from Intel Corporation of America, for interfacing with network **1160**. As can be appreciated, the network **1160** can be a public network, such as the

Internet, or a private network such as an LAN or WAN network, or any combination thereof and can also include PSTN or ISDN sub-networks. The network **1160** can also be wired, such as an Ethernet network, or can be wireless such as a cellular network including EDGE, 3G, 4G and 5G wireless cellular systems. The wireless network can also be Wi-Fi, Bluetooth, or any other wireless form of communication that is known.

[0079] The computing device further includes a display controller **1108**, such as a NVIDIA GeForce GTX or Quadro graphics adaptor from NVIDIA Corporation of America for interfacing with display **1110**, such as a Hewlett Packard HPL2445w LCD monitor. A general purpose I/O interface **1112** interfaces with a keyboard and/or mouse **1114** as well as a touch screen panel **1116** on or separate from display **1110**. General purpose I/O interface also connects to a variety of peripherals **1118** including printers and scanners, such as an OfficeJet or DeskJet from Hewlett Packard.

[0080] A sound controller **1120** is also provided in the computing device such as Sound Blaster X-Fi Titanium from Creative, to interface with speakers/microphone **1122** thereby providing sounds and/or music.

[0081] The general-purpose storage controller **1124** connects the storage medium disk **1104** with communication bus **1126**, which may be an ISA, EISA, VESA, PCI, or similar, for interconnecting all of the components of the computing device. A description of the general features and functionality of the display **1110**, keyboard and/or mouse **1114**, as well as the display controller **1108**, storage controller **1124**, network controller **1106**, sound controller **1120**, and general purpose I/O interface **1112** is omitted herein for brevity as these features are known.

[0082] The exemplary circuit elements described in the context of the present disclosure may be replaced with other elements and structured differently than the examples provided herein. Moreover, circuitry configured to perform features described herein may be implemented in multiple circuit units (e.g., chips), or the features may be combined in circuitry on a single chipset, as shown on FIG. **12**.

[0083] FIG. **12** shows a schematic diagram of a data processing system, according to certain embodiments, for performing the functions of the exemplary embodiments. The data processing system is an example of a computer in which code or instructions implementing the processes of the illustrative embodiments may be located.

[0084] In FIG. **12**, data processing system **1200** employs a hub architecture including a north bridge and memory controller hub (NB/MCH) **1225** and a south bridge and input/output (I/O) controller hub (SB/ICH) **1220**. The central processing unit (CPU) **1230** is connected to NB/MCH **1225**. The NB/MCH **1225** also connects to the memory **1245** via a memory bus, and connects to the graphics processor **1250** via an accelerated graphics port (AGP). The NB/MCH **1225** also connects to the SB/ICH **1220** via an internal bus (e.g., a unified media interface or a direct media interface). The CPU Processing unit **1230** may contain one or more processors and even may be implemented using one or more heterogeneous processor systems.

[0085] For example, FIG. **13** shows one implementation of CPU **1230**. In one implementation, the instruction register **1338** retrieves instructions from the fast memory **1340**. At least part of these instructions are fetched from the instruction register **1338** by the control logic **1336** and interpreted according to the instruction set architecture of the CPU **1230**. Part of the instructions can also be directed to the register **1332**. In one implementation the instructions are decoded according to a hardwired method, and in another implementation the instructions are decoded according to a microprogram that translates instructions into sets of CPU configuration signals that are applied sequentially over multiple clock pulses. After fetching and decoding the instructions, the instructions are executed using the arithmetic logic unit (ALU) **1334** that loads values from the register **1332** and performs logical and mathematical operations on the loaded values according to the instructions. The results from these operations can be feedback into the register and/or stored in the fast memory **1340**. According to certain implementations, the instruction set architecture of the

CPU **1230** can use a reduced instruction set architecture, a complex instruction set architecture, a vector processor architecture, a very large instruction word architecture. Furthermore, the CPU **1230** can be based on the Von Neuman model or the Harvard model. The CPU **1230** can be a digital signal processor, an FPGA, an ASIC, a PLA, a PLD, or a CPLD. Further, the CPU **1230** can be an x86 processor by Intel or by AMD; an ARM processor, a Power architecture processor by, e.g., IBM; a SPARC architecture processor by Sun Microsystems or by Oracle; or other known CPU architecture.

[0086] Referring again to FIG. **12**, the data processing system **1200** can include that the SB/ICH **1220** is coupled through a system bus to an I/O Bus, a read only memory (ROM) **1256**, universal serial bus (USB) port **1264**, a flash binary input/output system (BIOS) **1268**, and a graphics controller **1258**. PCI/PCIe devices can also be coupled to SB/ICH **1288** through a PCI bus **1262**.

[0087] The PCI devices may include, for example, Ethernet adapters, add-in cards, and PC cards for notebook computers. The Hard disk drive **1260** and CD-ROM **1266** can use, for example, an integrated drive electronics (IDE) or serial advanced technology attachment (SATA) interface. In one implementation the I/O bus can include a super I/O (SIO) device.

[0088] Further, the hard disk drive (HDD) **1260** and optical drive **1266** can also be coupled to the SB/ICH **1220** through a system bus. In one implementation, a keyboard **1270**, a mouse **1272**, a parallel port **1278**, and a serial port **1276** can be connected to the system bus through the I/O bus. Other peripherals and devices that can be connected to the SB/ICH **1220** using a mass storage controller such as SATA or PATA, an Ethernet port, an ISA bus, a LPC bridge, SMBus, a DMA controller, and an Audio Codec.

[0089] Moreover, the present disclosure is not limited to the specific circuit elements described herein, nor is the present disclosure limited to the specific sizing and classification of these elements. For example, the skilled artisan will appreciate that the circuitry described herein may be adapted based on changes on battery sizing and chemistry, or based on the requirements of the intended back-up load to be powered.

[0090] The functions and features described herein may also be executed by various distributed components of a system. For example, one or more processors may execute these system functions, wherein the processors are distributed across multiple components communicating in a network. The distributed components may include one or more client and server machines, which may share processing, as shown by FIG. **14**, in addition to various human interface and communication devices (e.g., display monitors, smart phones, tablets, personal digital assistants (PDAs)). The network may be a private network, such as a LAN or WAN, or may be a public network, such as the Internet. Input to the system may be received via direct user input and received remotely either in real-time or as a batch process. Additionally, some implementations may be performed on modules or hardware not identical to those described. Accordingly, other implementations are within the scope that may be claimed.

[0091] The above-described hardware description is a non-limiting example of corresponding structure for performing the functionality described herein.

[0092] Numerous modifications and variations of the present disclosure are possible in light of the above teachings. It is therefore to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described herein.

Claims

1. A vessel tank cleaning system, comprising: a robotic cleaner, comprising: a cylindrical central unit; three retractable legs extending from the cylindrical central unit, wherein the three retractable legs are in a tandem arrangement, wherein each of the three retractable legs comprises an omni directional wheel at a distal end, a leg collar at an end proximal to the cylindrical central unit, up to three joints and a motor; an arm extending from the cylindrical central unit configured to rotate

about the cylindrical central unit, wherein the arm comprises a cleaning sub-unit at a distal end and an arm collar at an end of the arm proximal to the cylindrical central unit, and wherein a vacuum pipe and a spraying device are connected to the arm; wherein the leg collar of each the three retractable legs and the arm collar of the arm are positioned over the cylindrical central unit, wherein each of the three retractable legs and the arm are attached to the cylindrical central unit by the respective leg collar and arm collar; a monitoring unit integrated in the three retractable legs and the arm, comprising a plurality of sensors, wherein the monitoring unit includes a controller having a processor with instructions configured to monitor an operation of the robotic cleaner; and a control unit integrated in the cylindrical central unit and in communication with the controller of the monitoring unit, wherein the processor is configured with instructions to communicate a set of information from the plurality of sensors with the control unit, wherein the control unit is configured to communicate to the controller of the monitoring unit to control movement of the robotic cleaner based on the set of information from the plurality of sensors; a control terminal configured to communicate a set of commands with the control unit of the robotic cleaner through a control cable, wherein the control cable is connected between the control terminal and the cylindrical central unit; and a pump connected to the arm of the robotic cleaner through a fluid hose and a vacuum hose.

2. The vessel tank cleaning system of claim 1, wherein the motor on each of the three retractable legs of the robotic cleaner is coupled to an encoder.
3. The vessel tank cleaning system of claim 2, wherein the control unit of the robotic cleaner is configured to communicate with the encoder for a movement of the robotic cleaner.
4. The vessel tank cleaning system of claim 1, wherein the plurality of sensors of the monitoring unit includes one or more force sensors integrated in each of the three retractable legs of the robotic cleaner.
5. The vessel tank cleaning system of claim 1, wherein the plurality of sensors of the monitoring unit comprises a set of inertial sensors, wherein the inertial sensors are integrated in the three retractable legs and configured to generate an orientation of each of the three retractable legs, and wherein the processor is further configured with instructions to monitor the orientation of one or more of the three retractable legs.
6. The vessel tank cleaning system of claim 1, wherein the plurality of sensors of the monitoring unit comprises an image sensor integrated in the arm of the robotic cleaner, and wherein the processor is further configured with instructions to monitor a position of the arm with a set of images generated by the image sensor.
7. The vessel tank cleaning system of claim 1, wherein the plurality of sensors of the monitoring unit comprises a set of displacement sensors integrated in the three retractable legs and the arm of the robotic cleaner, wherein the displacement sensors are configured to generate a location data of each of the three retractable legs and the arm of the robotic cleaner, and wherein the processor is further configured with instructions to monitor a movement of the robotic cleaner with the generated location data.
8. The vessel tank cleaning system of claim 1, wherein the plurality of sensors of the monitoring unit comprises a set of IR sensors.
9. The vessel tank cleaning system of claim 1, wherein the arm of the robotic cleaner comprises four joints, wherein each joint is configured to bend at an angle.
10. The vessel tank cleaning system of claim 1, wherein the arm and each of the three retractable legs are configured to rotate around a central axis of the cylindrical central unit to up to 360 degrees.
11. The vessel tank cleaning system of claim 1, wherein the cleaning sub-unit of the arm comprises a scraper and a degreaser.
12. The vessel tank cleaning system of claim 1, wherein the spraying device at the arm of the robotic cleaner is connected to the pump through the fluid hose, wherein a first end of the fluid

hose is connected to the pump and a second end is connected to an inlet of the spraying device.

13. The vessel tank cleaning system of claim 1, wherein the vacuum pipe at the arm of the robotic cleaner is connected to the pump through the vacuum hose, wherein a first end of the vacuum hose is connected to the pump and a second end is connected to the vacuum pipe.

14. The vessel tank cleaning system of claim 1, wherein the cylindrical central unit of the robotic cleaner is an elongated cylindrical unit centered at an axis, with the three retractable legs and the arm extending from the elongated cylindrical unit along the axis.

15. The vessel tank cleaning system of claim 1, wherein the cylindrical central unit of the robotic cleaner comprises an actuator.

16. The vessel tank cleaning system of claim 1, wherein the control unit comprises an energy management sub-unit and a lighting sub-unit.

17. The vessel tank cleaning system of claim 1, wherein the control unit comprises a decision support sub-unit configured to perform fault checking of a plurality of components of the robotic cleaner.

18. The vessel tank cleaning system of claim 13, wherein the decision support sub-unit is further configured to isolate one or more components having a fault.

19. The vessel tank cleaning system of claim 1, wherein the control unit comprises a safety check sub-unit comprising an overheat protector and a short-circuit protector.

20. The vessel tank cleaning system of claim 1, wherein the control terminal is configured to have a two-way communication with the control unit.
