

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283753

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Krasniqi; Veton

Portable Scale Device

Abstract

A portable scale device for weighing and transporting materials while inhibiting the materials from physically contacting the scale includes a scale including a weighing platform and a processor. A weight sensor is electrically coupled to the processor to measure a weight of a material positioned on the weighing platform. A display panel is electrically coupled to the processor to display the weight of the material. A container is releasably couplable to the scale to hold the material while the weight sensor is measuring the weight of the material. The container includes a base that is positioned over the weighing platform to inhibit the material from physically contacting the scale. A sleeve is releasably couplable to the base. A lid is releasably couplable to the sleeve and is designed to inhibit access to the material that is held within the container.

Inventors: Krasniqi; Veton (Brooklyn, NY)

Applicant: Krasniqi; Veton (Brooklyn, NY)

Family ID: 1000007756463

Appl. No.: 18/601753

Filed: March 11, 2024

Publication Classification

Int. Cl.: G01G21/22 (20060101)

U.S. Cl.:

CPC G01G21/22 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

[0003] Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

[0004] Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR

[0005] Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

[0006] The disclosure relates to scales and more particularly pertains to a new scale for weighing and transporting materials while inhibiting the materials from physically contacting the scale.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

[0007] The prior art relates to scales. Scales are used in a wide array of situations, for weighing various items and materials. For example, digital pocket scales provide portability and are often used to measure ingredients for meals. However, such scales often include sensitive electronic equipment that can be damaged by debris from the ingredients or other materials being weighed. Additionally, the ingredients or materials themselves are often lightweight, making it easy for the materials to fall off of the scale. Finally, although pocket scales themselves are portable, people need to remove the weighed material from the scale and put the weighed material in a secondary container if the weighed material needs to be transported to a secondary location. Thus, there is a need in the art for a pocket scale with a container that can hold the material being weighed, to protect the components of the scale and to facilitate transport of the material.

BRIEF SUMMARY OF THE INVENTION

[0008] An embodiment of the disclosure meets the needs presented above by generally comprising a scale including a weighing platform and a processor that is operationally coupled to the weighing platform. A weight sensor is electrically coupled to the processor wherein the weight sensor is configured to measure a weight of a material that is positioned on the weighing platform. A display panel is electrically coupled to the processor wherein the display panel is configured to display the weight of the material being measured by the weight sensor. A container is releasably couplable to the scale. The container is configured to hold the material while the weight sensor is measuring the weight of the material. The container includes a base that is positioned over the weighing platform when the base is coupled to the scale wherein the base is configured to inhibit the material from physically contacting the scale while the weight sensor is measuring the weight of the material. A sleeve is releasably couplable to the base. The sleeve has an upper end and a lower end. Each of the upper end and the lower end is open wherein the upper end and the lower end are each configured to facilitate placement of the material within the container. A lid is releasably couplable to the sleeve. The lid is positionable over the upper end of the sleeve wherein the lid is configured to inhibit access to the material being held within the container.

[0009] There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

[0010] The objects of the disclosure, along with the various features of novelty which characterize

the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

[0011] The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

[0012] FIG. **1** is an exploded view of a portable scale device according to an embodiment of the disclosure.

[0013] FIG. **2** is a bottom isometric view of an embodiment of the disclosure.

[0014] FIG. **3** is a detail bottom isometric view of an embodiment of the disclosure.

[0015] FIG. **4** is a detail bottom isometric view of an embodiment of the disclosure.

[0016] FIG. **5** is a detail side view of an embodiment of the disclosure.

[0017] FIG. **6** is an in-use view of an embodiment of the disclosure.

[0018] FIG. **7** is a detail view of an embodiment of the disclosure.

[0019] FIG. **8** is a detail view of an embodiment of the disclosure.

[0020] FIG. **9** is an isometric view of an embodiment of the disclosure.

[0021] FIG. **10** is an isometric view of an embodiment of the disclosure.

[0022] FIG. **11** is an isometric view of an embodiment of the disclosure.

[0023] FIG. **12** is a block diagram view of an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0024] With reference now to the drawings, and in particular to FIGS. **1** through **12** thereof, a new scale embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral **10** will be described.

[0025] As best illustrated in FIGS. **1** through **12**, the portable scale device **10** generally comprises a scale **12**. For example, the scale **12** may have a top panel **14**, a bottom panel **16**, and a side panel **18** that is coupled to and extends between the top panel **14** and the bottom panel **16**. Generally, the bottom panel **16** is planar so that the scale **12** can stably rest on a surface to measure a weight of an item. The side panel **18** may have a threaded upper portion **20** extending downwardly from the top panel **14**. The threaded upper portion **20** is generally positioned on an outer surface **22** of the scale **12**.

[0026] The scale **12** may further comprise a weighing platform **24**. For example, the weighing platform **24** may be coupled to the top panel **14**. The weighing platform **24** may be planar. The weighing platform **24** may extend upwardly from the top panel **14**. The weighing platform **24** may be movably coupled to the top panel **14** wherein a position of the weighing platform **24** is vertically adjustable relative to the top panel **14**.

[0027] A processor **26** may be positioned inside the scale **12**. The processor **26** is operationally coupled to the weighing platform **24**.

[0028] A weight sensor **28** is electrically coupled to the processor **26** wherein the weight sensor **28** is configured to measure a weight of a material **30** that is positioned on the weighing platform **24**. The weight sensor **28** is generally positioned inside of the scale **12** and may be operationally coupled to the weighing platform **24**.

[0029] A power source **32** may be electrically coupled to the processor **26**. The power source **32** may include a battery, for example a rechargeable battery. The power source **32** may be positioned inside of the scale **12**.

[0030] An access door **34** may be coupled to the scale **12**. For example, the access door **34** may be positioned on the bottom panel **16** of the scale **12**. The access door **34** may be movably or pivotably

coupled to the bottom panel **16** and is generally aligned with the power source **32** wherein the access door **34** is openable to facilitate access to the power source **32**.

[0031] A charging port **36** may be electrically coupled to the power source **32** wherein the charging port **36** is configured to receive a charging cable **38** for recharging the power source **32**. The charging port **36** may be inset into the side panel **18** of the scale **12** and exposed within the side panel **18** of the scale **12**, for example to facilitate use of the scale while the power source **32** is being recharged. Alternatively, the charging port **36** may be positioned on the bottom panel **16** of the scale **12**.

[0032] A display panel **40** is electrically coupled to the processor **26** wherein the display panel **40** is configured to display the weight of the material **30** that is measured by the weight sensor **28**. For example, the display panel **40** is coupled to the side panel **18** of the scale **12**.

[0033] A control panel **42** may be electrically coupled to the processor **26** wherein the processor **26** is configured to actuate the weight sensor **28** when the control panel **42** is manipulated. The processor **26** may also be configured to tare the weight sensor **28** when the control panel **42** is manipulated. The control panel **42** may be coupled to the side panel **18** of the scale **12**, for example adjacent to the display panel **40**. In some embodiments, the control panel **42** comprises a button.

[0034] A container **44** is releasably couplable to the scale **12**. The container **44** is configured to hold the material **30** while the weight sensor **28** is measuring the weight of the material **30**, such that the material **30** does not need to be placed directly on the scale **12**. The container **44** therefore helps to keep the scale **12** clean, inhibiting the material **30** from clogging or damaging components of the scale **12**. The container **44** can also be used to transport the material **30** once the material **30** has been weighed. For example, the container **44** can be removed from the scale **12** to transport the material **30**, or the container **44** can remain attached to the scale **12** for simultaneous transport of the scale **12**, the container **44**, and the material **30**.

[0035] The container **44** generally includes a base **46** that is releasably couplable to the scale **12**. The base **46** is generally positioned over the weighing platform **24** when the base **46** is coupled to the scale **12** wherein the base **46** is configured to inhibit the material **30** from physically contacting the scale **12**, for example while the weight sensor **28** is measuring the weight of the material **30**.

[0036] The base **46** may further comprise a peripheral wall **48** that has a top edge **50** and a bottom edge **52**. The peripheral wall **48** extends upwardly from the scale **12** when the base **46** is coupled to the scale **12** wherein the bottom edge **52** is positioned proximate to the scale **12** and the top edge **50** is positioned above the scale **12**.

[0037] A central wall **54** may be coupled to the peripheral wall **48**. The central wall **54** is generally spaced from both the top edge **50** and the bottom edge **52** of the peripheral wall **48** wherein the central wall **54** is positionable on top of the weighing platform **24** when the base **46** is coupled to the scale **12** and wherein the base **46** is configured to hold the material **30** on top of the central wall **54**. The central wall **54** is in physical contact with the weighing platform **24** of the scale **12** wherein the weight sensor **28** is configured to measure the weight of the material **30** that is positioned on top of the central wall **54** when the base **46** is coupled to the scale **12**. For example, the central wall **54** may comprise a flexible material wherein the weighing platform **24** is configured to exert upward pressure on the central wall **54** when the base **46** is coupled to the scale **12** and wherein the central wall **54** is configured to exert a downward pressure on the weighing platform **24** when the material **30** is positioned on top of the central wall **54**. The weight sensor **28** is configured to measure the weight of the material **30** based on the downward pressure that is exerted on the weighing platform **24** by the central wall **54** and the material **30**. For example, the flexible material of the central wall **54** may include rubber or silicone. The central wall **54** is generally coextensive with the weighing platform **24** wherein the base **46** is configured to inhibit the material **30** from physically contacting the weighing platform **24** of the scale **12** when the base **46** is coupled to the scale **12**.

[0038] A top threading **56** may extend downwardly from the top edge **50** of the peripheral wall **48**

of the base **46** toward the central wall **54**. The top threading **56** may be positioned on an interior surface **58** of the base **46**.

[0039] A bottom threading **60** may extend upwardly from the bottom edge **52** of the peripheral wall **48** of the base **46** toward the central wall **54**. The bottom threading **60** may be positioned on the interior surface **58** of the base **46**. The bottom threading **60** is complementary to the threaded upper portion **20** of the side panel **18** of the scale **12** wherein the base **46** is threadably couplable to the scale **12**. In alternative embodiments, the base **46** may snap onto the scale **12** for a friction fit rather than a threaded coupling, for example as shown in FIG. **11**.

[0040] A base gasket **62** may be coupled to the base **46**. The base gasket **62** is generally positioned on the bottom edge **52** of the peripheral wall **48**. The base gasket **62** may be coextensive with the bottom edge **52** of the peripheral wall **48**. The base gasket **62** may comprise a rubber material **30** wherein the base gasket **62** is configured to seal a junction between the base **46** and the scale **12** when the base **46** is coupled to the scale **12** whereby the base gasket **62** is configured to inhibit airflow into the container **44**.

[0041] A sleeve **64** is releasably couplable to the base **46**. The sleeve **64** generally includes an upper end **66** and a lower end **68**. Each of the upper end **66** and the lower end **68** is typically open wherein the upper end **66** and the lower end **68** are each configured to facilitate placement of the material **30** within the container **44**. The sleeve **64** may extend upwardly from the base **46** when the sleeve **64** is coupled to the base **46** wherein the sleeve **64** is configured to increase an amount of the material **30** that can be held within the container **44**. The sleeve **64** may have a height exceeding a height of the base **46**.

[0042] The sleeve **64** may further include an upper end threading **70** that extends downwardly from the upper end **66**. The upper end threading **70** may be positioned on an external surface **72** of the sleeve **64**.

[0043] A lower end threading **74** may extend upwardly from the lower end **68** of the sleeve **64**. The lower end threading **74** may be positioned on the external surface **72** of the sleeve **64**. The lower end threading **74** may be spaced from the upper end threading **70**. The lower end threading **74** is complementary to the top threading **56** on the peripheral wall **48** of the base **46** wherein the sleeve **64** is threadably couplable to the base **46**. In alternative embodiments, the sleeve **64** may snap onto the base **46** for a friction fit rather than a threaded coupling.

[0044] The sleeve **64** may include a resiliently compressible material extending between the upper end **66** and the lower end **68** wherein a height of the sleeve **64** is compressible to facilitate transportation and storage of the container **44**, as shown in FIG. **10**.

[0045] A lid **76** is releasably couplable to the sleeve **64**. The lid **76** is positionable over the upper end **66** of the sleeve **64** wherein the lid **76** is configured to inhibit access to the material **30** that is held within the container **44**.

[0046] For example, the lid **76** may include an upper plate **78** that may be parallel to the central wall **54** when the sleeve **64** is coupled to the base **46** and when the lid **76** is coupled to the sleeve **64**. A lateral plate **80** may be coupled to and extend downwardly from the upper plate **78**. The lateral plate **80** may have a terminal edge **82** that is spaced from the upper plate **78**.

[0047] A lid threading **84** may extend upwardly from the terminal edge **82** of the lateral plate **80**. The lid threading **84** may be positioned on an internal face **86** of the lateral plate **80**. The lid threading **84** is complementary to the upper end threading **70** of the sleeve **64** wherein the lid **76** is threadably couplable to the sleeve **64**. In alternative embodiments, the lid **76** may snap onto the sleeve **64** for a friction fit rather than a threaded coupling.

[0048] A handle **88** may be coupled to the upper plate **78**. For example, the handle **88** may extend upwardly from the upper plate **78** wherein the handle **88** is configured to facilitate a user in gripping the lid **76**.

[0049] A lid gasket **90** may be coupled to the lid **76**. The lid gasket **90** is generally positioned on the terminal edge **82** of the lateral plate **80** of the lid **76**. The lid gasket **90** may be coextensive with

the terminal edge **82** of the lateral plate **80**. The lid gasket **90** may comprise a rubber material wherein the lid gasket **90** is configured to seal a junction between the lid **76** and the sleeve **64** when the lid **76** is coupled to the sleeve **64** whereby the lid gasket **90** is configured to inhibit airflow into the container **44**.

[0050] A lid retainer **92** may releasably couple the lid **76** to the base **46** when the sleeve **64** is compressed. For example, the lid retainer **92** may include a lid strap **94** that is coupled to the upper plate **78** of the lid **76**. The lid strap **94** may extend downwardly from the upper plate **78** of the lid **76**. A first retaining member **96** may be attached to the lid strap **94**. The first retaining member **96** may be positioned proximate to a free end **98** of the lid strap **94**. A second retaining member **100** may be releasably engageable with the first retaining member **96**. The second retaining member **100** may be coupled to an exterior surface **112** of the peripheral wall **48** of the base **46**. The second retaining member **100** is alignable with the first mating member when the sleeve **64** is compressed. In some embodiments, each of the first retaining member **96** and the second retaining member **100** comprise a snap. Alternatives for each of the first retaining member **96** and the second retaining member **100**, such as a hook and loop material, a magnet, or a button and buttonhole, are also contemplated.

[0051] A base retainer **102** may releasably couple the base **46** to the scale **12**. For example, the base retainer **102** may include a base strap **104** that is coupled to the peripheral wall **48** of the base **46**. The base strap **104** may extend downwardly past the bottom edge **52** of the peripheral wall **48**. A first fastening piece **106** may be attached to the base strap **104**. A second fastening piece **108** may be releasably engageable with the first fastening piece **106**. The second fastening piece **108** may be coupled to the side panel **18** of the scale **12**. The second fastening piece **108** is alignable with the first fastening piece **106** when the base **46** is coupled to the scale **12**. Each of the first fastening piece **106** and the second fastening piece **108** may comprise a snap. Alternatives for each of the first fastening piece **106** and the second fastening piece **108**, such as a hook and loop material, a magnet, or a button and buttonhole, are also contemplated.

[0052] The outer surface **22** of the scale **12** may be coplanar with the exterior surface **112** of the base **46** when the base **46** is coupled to the scale **12**. The exterior surface **112** of the base **46** may be coplanar with the external surface **72** of the sleeve **64** when the sleeve **64** is coupled to the base **46**. The external surface **72** of the sleeve **64** may be coplanar with an external face **110** of the lid **76** when the lid **76** is coupled to the sleeve **64**.

[0053] Each of the peripheral wall **48** of the base **46** and the lid **76** may comprise a rigid material that is configured to inhibit damage to the material **30** when the material **30** is held within the container **44** and when the sleeve **64** is compressed. For example, rigid materials may include plastic, wood, glass, or other natural or synthetic materials.

[0054] The figures show the scale **12** and container **44** are generally cylindrical, which facilitates threadably coupling each of the pieces together. In alternative embodiments, particularly those using a friction fit where the pieces snap together, the pieces may have alternative shapes.

[0055] In use, the container **44** may be coupled to the scale **12**. For example, the base **46** may be coupled to the scale **12**, or the base **46** and the sleeve **64** may be coupled together, then coupled to the scale **12**. The material **30** may be positioned on top of the central wall **54** of the base **46**. The material **30** then exerts a downward pressure on the central wall **54** and the weighing platform **24** of the scale **12** so that the weight sensor **28** can determine the weight of the material **30**. The lid **76** may be coupled to the sleeve **64** to keep the material **30** safely enclosed within the container **44** during transport, either while the container **44** is coupled to the scale **12** or while the container **44** is decoupled from the scale **12**. In some embodiments, the sleeve **64** may be compressed to reduce the size of the container **44** and facilitate transport.

[0056] With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily

apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

[0057] Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A scale assembly comprising: a scale comprising: a weighing platform; a processor being operationally coupled to the weighing platform; a weight sensor being electrically coupled to the processor wherein the weight sensor is configured to measure a weight of a material being positioned on the weighing platform; a display panel being electrically coupled to the processor wherein the display panel is configured to display the weight of the material being measured by the weight sensor; a container being releasably couplable to the scale, the container being configured to hold the material while the weight sensor is measuring the weight of the material, the container comprising: a base being positioned over the weighing platform when the base is coupled to the scale wherein the base is configured to inhibit the material from physically contacting the scale while the weight sensor is measuring the weight of the material; a sleeve being releasably couplable to the base, the sleeve having an upper end and a lower end, each of the upper end and the lower end being open wherein the upper end and the lower end are each configured to facilitate placement of the material within the container; and a lid being releasably couplable to the sleeve, the lid being positionable over the upper end of the sleeve wherein the lid is configured to inhibit access to the material being held within the container.
2. The scale assembly of claim 1, the base of the container further comprising: a peripheral wall having a top edge and a bottom edge, the peripheral wall extending upwardly from the scale when the base is coupled to the scale wherein the bottom edge is positioned adjacent to scale and the top edge is positioned above the scale; and a central wall being coupled to the peripheral wall, the central wall being spaced from the top edge and the bottom edge of the peripheral wall wherein the central wall is positionable on top of the weighing platform when the base is coupled to the scale and wherein the base is configured to hold the material on top of the central wall, the central wall being in physical contact with the weighing platform of the scale wherein the weight sensor is configured to measure the weight of the material being positioned on top of the central wall when the base is coupled to the scale, the central wall comprising a flexible material wherein the weighing platform is configured to exert upward pressure on the central wall when the base is coupled to the scale and wherein the central wall is configured to exert a downward pressure on the weighing platform when the material is positioned on top of the central wall, the weight sensor being configured to measure the weight of the material based on the downward pressure being exerted on the weighing platform by the central wall.
3. The scale assembly of claim 2, wherein the central wall is coextensive with the weighing platform wherein the base is configured to inhibit the material from physically contacting the weighing platform of the scale when the base is coupled to the scale.
4. The scale assembly of claim 2, the base of the container further comprising a top threading extending downwardly from the top edge of the peripheral wall of the base toward the central wall,

the sleeve of the container further comprising a lower end threading extending upwardly from the lower end of the sleeve, the lower end threading being complementary to the top threading on the peripheral wall of the base wherein the sleeve is threadably couplable to the base.

5. The scale assembly of claim 2, further comprising: a threaded upper portion extending downwardly from a top panel of the scale; and a bottom threading extending upwardly from the bottom edge of the peripheral wall of the base toward the central wall, the bottom threading being complementary to the threaded upper portion of the side panel of the scale wherein the base is threadably couplable to the scale.

6. The scale assembly of claim 1, further comprising a base gasket being coupled to the base, the base gasket comprising a rubber material wherein the base gasket is configured to seal a junction between the base and the scale when the base is coupled to the scale whereby the base gasket is configured to inhibit airflow into the container when the base is coupled to the scale.

7. The scale assembly of claim 1, the sleeve further comprising a resiliently compressible material extending between the upper end and the lower end wherein a height of the sleeve is compressible to facilitate transportation and storage of the container.

8. The scale assembly of claim 7, further comprising a lid retainer releasably coupling the lid to the base when the sleeve is compressed, the lid retainer including: a lid strap being coupled to the lid; a first retaining member being attached to the lid strap; and a second retaining member being releasably engageable with the first retaining member, the second retaining member being coupled to the base, the second retaining member being alignable with the first mating member when the sleeve is compressed.

9. The scale assembly of claim 1, the sleeve further comprising an upper end threading extending downwardly from the upper end.

10. The scale assembly of claim 9, the lid further comprising: an upper plate being parallel to the central wall of the base when the sleeve is coupled to the base and when the lid is coupled to the sleeve; a lateral plate being coupled to and extending downwardly from the upper plate, the lateral plate having a terminal edge being spaced from the upper plate; and a lid threading extending upwardly from the terminal edge of the lateral plate, the lid threading being complementary to the upper end threading of the sleeve wherein the lid is threadably couplable to the sleeve.

11. The scale assembly of claim 1, the lid further comprising: an upper plate; and a lateral plate being coupled to and extending downwardly from the upper plate.

12. The scale assembly of claim 11, the lid further comprising a handle being coupled to the upper plate, the handle extending upwardly from the upper plate wherein the handle is configured to facilitate a user in gripping the lid.

13. The scale assembly of claim 1, further comprising a lid gasket being coupled to the lid, the lid gasket comprising a rubber material wherein the lid gasket is configured to seal a junction between the lid and the sleeve when the lid is coupled to the sleeve whereby the lid gasket is configured to inhibit airflow into the container.

14. The scale assembly of claim 1, further comprising a base retainer releasably coupling the base to the scale, the base retainer including: a base strap being coupled the base; a first fastening piece being attached to the base strap; and a second fastening piece being releasably engageable with the first fastening piece, the second fastening piece being coupled to the scale, the second fastening piece being alignable with the first fastening piece when the base is coupled to the scale.

15. A scale assembly comprising: a scale having a top panel, a bottom panel, and a side panel being coupled to and extending between the top panel and the bottom panel, the bottom panel being planar, the side panel having a threaded upper portion extending downwardly from the top panel, the threaded upper portion being positioned on an outer surface of the scale, the scale further comprising: a weighing platform being coupled to the top panel, the weighing platform being movably coupled to the top panel wherein a position of the weighing platform is vertically adjustable relative to the top panel; a processor being positioned inside the scale, the processor

being operationally coupled to the weighing platform; a weight sensor being electrically coupled to the processor wherein the weight sensor is configured to measure a weight of a material being positioned on the weighing platform, the weight sensor being positioned inside of the scale; a power source being electrically coupled to the processor, the power source comprising a battery, the battery being rechargeable, the power source being positioned inside of the scale; an access door being coupled to the scale, the access door being positioned on the bottom panel of the scale, the access door being pivotably coupled to the bottom panel and being aligned with the power source wherein the access door is openable to facilitate access to the power source; a charging port being electrically coupled to the power source wherein the charging port is configured to receive a charging cable for recharging the power source, the charging port being inset into the side panel of the scale, the charging port being exposed within the side panel of the scale; a display panel being electrically coupled to the processor wherein the display panel is configured to display the weight of the material being measured by the weight sensor, the display panel being coupled to the side panel of the scale; a control panel being electrically coupled to the processor wherein the processor is configured to actuate the weight sensor when the control panel is manipulated, the processor being configured to tare the weight sensor when the control panel is manipulated, the control panel being coupled to the side panel of the scale, the control panel being positioned adjacent to the display panel, the control panel comprising a button; a container being releasably couplable to the scale, the container being configured to hold the material while the weight sensor is measuring the weight of the material, the container comprising: a base being releasably couplable to the scale, the base being positioned over the weighing platform when the base is coupled to the scale wherein the base is configured to inhibit the material from physically contacting the scale while the weight sensor is measuring the weight of the material, the base further comprising: a peripheral wall having a top edge and a bottom edge, the peripheral wall extending upwardly from the scale when the base is coupled to the scale wherein the bottom edge is positioned adjacent to scale and the top edge is positioned above the scale; a central wall being coupled to the peripheral wall, the central wall being spaced from the top edge and the bottom edge of the peripheral wall wherein the central wall is positionable on top of the weighing platform when the base is coupled to the scale and wherein the base is configured to hold the material on top of the central wall, the central wall being in physical contact with the weighing platform of the scale wherein the weight sensor is configured to measure the weight of the material being positioned on top of the central wall when the base is coupled to the scale, the central wall comprising a flexible material wherein the weighing platform is configured to exert upward pressure on the central wall when the base is coupled to the scale and wherein the central wall is configured to exert a downward pressure on the weighing platform when the material is positioned on top of the central wall, the weight sensor being configured to measure the weight of the material based on the downward pressure being exerted on the weighing platform by the central wall, the central wall being coextensive with the weighing platform wherein the base is configured to inhibit the material from physically contacting the weighing platform of the scale when the base is coupled to the scale; a top threading extending downwardly from the top edge of the peripheral wall of the base toward the central wall, the top threading being positioned on an interior surface of the base; a bottom threading extending upwardly from the bottom edge of the peripheral wall of the base toward the central wall, the bottom threading being positioned on the interior surface of the base, the bottom threading being complementary to the threaded upper portion of the side panel of the scale wherein the base is threadably couplable to the scale; a base gasket being coupled to the base, the base gasket being positioned on the bottom edge of the peripheral wall, the base gasket being coextensive with the bottom edge of the peripheral wall, the base gasket comprising a rubber material wherein the base gasket is configured to seal a junction between the base and the scale when the base is coupled to the scale whereby the base gasket is configured to inhibit airflow into the container; a sleeve being releasably couplable to the base, the sleeve having an upper end and a lower end, each of the upper end and the lower end being open

wherein the upper end and the lower end are each configured to facilitate placement of the material within the container, the sleeve extending upwardly from the base when the sleeve is coupled to the base wherein the sleeve is configured to increase an amount of the material being held in the container, the sleeve having a height exceeding a height of the base, the sleeve further comprising: an upper end threading extending downwardly from the upper end, the upper end threading being positioned on an external surface of the sleeve; a lower end threading extending upwardly from the lower end, the lower end threading being positioned on the external surface of the sleeve, the lower end threading being spaced from the upper end threading, the lower end threading being complementary to the top threading on the peripheral wall of the base wherein the sleeve is threadably couplable to the base; a resiliently compressible material extending between the upper end and the lower end wherein a height of the sleeve is compressible to facilitate transportation and storage of the container; a lid being releasably couplable to the sleeve, the lid being positionable over the upper end of the sleeve wherein the lid is configured to inhibit access to the material being held within the container, the lid including: an upper plate being parallel to the central wall when the sleeve is coupled to the base and when the lid is coupled to the sleeve; a lateral plate being coupled to and extending downwardly from the upper plate, the lateral plate having a terminal edge being spaced from the upper plate; a lid threading extending upwardly from the terminal edge of the lateral plate, the lid threading being positioned on an internal face of the lateral plate, the lid threading being complementary to the upper end threading of the sleeve wherein the lid is threadably couplable to the sleeve; a handle being coupled to the upper plate, the handle extending upwardly from the upper plate wherein the handle is configured to facilitate a user in gripping the lid; a lid gasket being coupled to the lid, the lid gasket being positioned on the terminal edge of the lateral plate of the lid, the lid gasket being coextensive with the terminal edge of the lateral plate, the lid gasket comprising the rubber material wherein the lid gasket is configured to seal a junction between the lid and the sleeve when the lid is coupled to the sleeve whereby the lid gasket is configured to inhibit airflow into the container; a lid retainer releasably coupling the lid to the base when the sleeve is compressed, the lid retainer including: a lid strap being coupled to the upper plate of the lid, the lid strap extending downwardly from the upper plate of the lid; a first retaining member being attached to the lid strap, the first retaining member being positioned proximate to a free end of the lid strap; a second retaining member being releasably engageable with the first retaining member, the second retaining member being coupled to an exterior surface of the peripheral wall of the base, the second retaining member being alignable with the first mating member when the sleeve is compressed; wherein each of the first retaining member and the second retaining member comprise a snap; a base retainer releasably coupling the base to the scale, the base retainer including: a base strap being coupled to the peripheral wall of the base, the base strap extending downwardly past the bottom edge of the peripheral wall; a first fastening piece being attached to the base strap; a second fastening piece being releasably engageable with the first fastening piece, the second fastening piece being coupled to the side panel of the scale, the second fastening piece being alignable with the first fastening piece when the base is coupled to the scale; wherein each of the first fastening piece and the second fastening piece comprise a snap; wherein the outer surface of the scale is coplanar with the exterior surface of the base when the base is coupled to the scale; wherein the exterior surface of the base is coplanar with the external surface of the sleeve when the sleeve is coupled to the base; wherein the external surface of the sleeve is coplanar with an external face of the lid when the lid is coupled to the sleeve; and wherein each of the base and the lid comprises a rigid material being configured to inhibit damage to the material when the material is being held within the container and when the sleeve is compressed, the rigid material comprising plastic.
