

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284509

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Chen; Dong et al.

CULTURALLY-INTELLIGENT METAVERSE

Abstract

A computer-implemented process for generating a modified scene using a culturally-intelligent platform having a dynamic library includes the following operations. A scene associated with a particular user is received in real-time. The scene is processed in real-time to identify participants associated with the scene. Intelligent recognition performed on the scene to identify a cultural item within the scene in real-time and using the dynamic library. The scene is modified based upon a description of the identified cultural item within the dynamic library to generate a modified scene that includes the description. A usefulness of the identified cultural item is determined, and an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item is updated based upon the scene being modified for the particular user.

Inventors: Chen; Dong (Beijing, CN), Zhang; Ming Lei (Beijing, CN), Zhang; Yuan Jie (Ningbo, CN), Guo; Yin Xi (Hai Dian District, CN), Zhan; Ting Ting (Beijing, CN)

Applicant: INTERNATIONAL BUSINESS MACHINES CORPORATION (Armonk, NY)

Family ID: 96949335

Appl. No.: 18/601273

Filed: March 11, 2024

Publication Classification

Int. Cl.: G06F9/451 (20180101)

U.S. Cl.:

CPC G06F9/454 (20180201);

Background/Summary

BACKGROUND

[0001] The present invention relates to the metaverse, and more specifically, to analyzing cultural items in a metaverse scene and modifying the scene based upon the analysis.

[0002] The metaverse is generally recognized as a network of shared 3D experiences that blur the divide between the digital world and the physical world. Typically, the metaverse is accessed using Extended Reality (XR), which is an umbrella term used to describe a number of related, albeit different technologies used to augment human senses. These technologies include augmented reality (AR), virtual reality (VR), and mixed reality (MR). AR typically involves overlaying digital elements onto a real world view. In other words, a real world view (e.g., a still photo or video) is altered to include additional digital elements that have some perceived relationship with the real world view. VR typically involves the creation of an immersive completely digital environment that can be viewed and interacted with by a user. In MR, aspects of both AR and VR are mixed. These technologies are typically device dependent. For example, a smartphone can be used with AR whereas VR typically requires a head mounted display/headset. MR devices can include transparent wearable glasses that present an overlay of digital content that interacts with real world objects in real-time. As used herein, the term “XR device” or “XR system” refers to a particular computer-implemented hardware device including one or more of AR, VR, and MR technologies.

SUMMARY

[0003] A computer-implemented process for generating a modified scene using a culturally-intelligent platform having a dynamic library includes the following operations. A scene associated with a particular user is received in real-time. The scene is processed in real-time to identify participants associated with the scene. Intelligent recognition performed on the scene to identify a cultural item within the scene in real-time and using the dynamic library. The scene is modified based upon a description of the identified cultural item within the dynamic library to generate a modified scene that includes the description. A usefulness of the identified cultural item is determined, and an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item is updated based upon the scene being modified for the particular user.

[0004] In other aspects of the process, the usefulness is determined based upon comparing a usefulness value for the identified cultural item to a threshold value. Additionally, the usefulness value is based upon a base usefulness value for the identified cultural item, and decreases based upon an increased number of instances in which the scene is modified based upon the identified cultural item. The identified cultural item is a visual object displayed within the scene or a human gesture displayed within the scene. The scene is a computer data structure that represents a particular environment in which the users interact. The intelligent recognition employs machine learning to identify the cultural items.

[0005] A computer hardware system for generating a modified scene using a culturally-intelligent platform having a dynamic library includes a hardware processor configured to perform the following executable operations. A scene associated with a particular user is received in real-time. The scene is processed in real-time to identify participants associated with the scene. Intelligent recognition performed on the scene to identify a cultural item within the scene in real-time and using the dynamic library. The scene is modified based upon a description of the identified cultural item within the dynamic library to generate a modified scene that includes the description. A usefulness of the identified cultural item is determined, and an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item is updated based upon the scene being modified for the particular user.

[0006] In other aspects of the system, the usefulness is determined based upon comparing a usefulness value for the identified cultural item to a threshold value. Additionally, the usefulness value is based upon a base usefulness value for the identified cultural item, and decreases based

upon an increased number of instances in which the scene is modified based upon the identified cultural item. The identified cultural item is a visual object displayed within the scene or a human gesture displayed within the scene. The scene is a computer data structure that represents a particular environment in which the users interact. The intelligent recognition employs machine learning to identify the cultural items.

[0007] A computer program product includes a computer readable storage medium having stored therein program code for generating a modified scene. The program code, which when executed by a computer hardware system including a culturally-intelligent platform having a dynamic library, cause the computer hardware system to perform the following. A scene associated with a particular user is received in real-time. The scene is processed in real-time to identify participants associated with the scene. Intelligent recognition performed on the scene to identify a cultural item within the scene in real-time and using the dynamic library. The scene is modified based upon a description of the identified cultural item within the dynamic library to generate a modified scene that includes the description. A usefulness of the identified cultural item is determined, and an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item is updated based upon the scene being modified for the particular user.

[0008] In other aspects of the computer program product, the usefulness is determined based upon comparing a usefulness value for the identified cultural item to a threshold value. Additionally, the usefulness value is based upon a base usefulness value for the identified cultural item, and decreases based upon an increased number of instances in which the scene is modified based upon the identified cultural item. The identified cultural item is a visual object displayed within the scene or a human gesture displayed within the scene. The scene is a computer data structure that represents a particular environment in which the users interact. The intelligent recognition employs machine learning to identify the cultural items.

[0009] This Summary section is provided merely to introduce certain concepts and not to identify any key or essential features of the claimed subject matter. Other features of the inventive arrangements will be apparent from the accompanying drawings and from the following detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1A is a block diagram of a culturally-aware metaverse architecture according to an aspect of the present invention.

[0011] FIG. 1B is a block diagram further illustrating the architecture of a culturally-intelligent platform according to an aspect of the present invention.

[0012] FIG. 2 illustrates a scene on a XR system.

[0013] FIGS. 3A, 3B respectively illustrate a methodology of employing the culturally-intelligent platform of FIG. 1B to generate cultural item object instances and employing the same to generate a modified scene according to an aspect of the present invention.

[0014] FIG. 4 illustrates a cultural item object instance according to an aspect of the present invention.

[0015] FIG. 5 illustrates a data structure including cultural object instances according to an aspect of the present invention.

[0016] FIGS. 6A and 6B respectively illustrate alternative approaches to modifying a scene according to an aspect of the present invention.

[0017] FIG. 7 is a block diagram illustrating an example of computer hardware system for implementing the culturally-intelligent platform of FIGS. 1A and 1B.

[0018] FIG. 8 is a block diagram illustrating an example computer hardware system for

implementing the XR system of FIG. 1A.

DETAILED DESCRIPTION

[0019] Reference is made to FIGS. 1A-1B and 3, which respectively illustrate a culturally-aware metaverse architecture **100** and methodology **300A**, **300B** for generating cultural item object instances **400** (see FIG. 4) and employing the same to generate a modified scene **185**. The metaverse can be characterized with a new set of values such as copresence (i.e., the desire to be with others), collaboration (i.e., the need for interaction, voice, and co-creation), and connection (i.e., the need for persistent/omnipresent experiences). Whether in a work, educational, and/or social context, the metaverse can bring together individuals from many different geographic regions and/or cultures. One aspect of the metaverse is its capability of transmitting gestures (e.g., body movements) to others, which oftentimes have meanings that can differ from one culture to another. For example, in India, there are many types of head movements (called Shirobheda) for which different meanings are attached. One movement, the Parivahitam, involves shaking the head to the left and right and means harmony or agreement but could appear to a Western viewer as being similar to a head shake that means “no.” As another example, in China, pointing with a single finger (e.g., the index or pinkie finger) can be considered rude. These cultural differences can lead to communication and understanding misunderstandings when used in the metaverse.

[0020] In general, the computer-implemented process **300B** for generating a modified scene **185** uses a culturally-intelligent platform **120** having a dynamic library **120**. A scene **125** associated with a particular user **105A** is received in real-time by an interface **130** of the culturally-intelligent platform **120**. The scene **125** is processed in real-time to identify participants **105A-C** associated with the scene **125**, and intelligent recognition is performed on the scene **125** by the intelligent recognition processor **140** to identify a cultural item (CI) within the scene **125** in real-time while using the dynamic library **145**. The scene **125** is modified by the cultural processor **150** based upon a description of the identified CI within the dynamic library **145** to generate a modified scene **185** that includes the description. A usefulness of the identified CI can be determined, and an entry in the dynamic library **145** associated with the particular user **105A** regarding the usefulness of the identified CI can be updated based upon the scene **125** being modified for the particular user **105A**. The modified scene **185** is ultimately provided to the particular user **105A**. The culturally-intelligent platform **120** and XR system **110** are respectively further described with regard to FIGS. 7 and 8.

[0021] Additionally, the usefulness can be determined based upon comparing a usefulness value for the identified CI to a threshold value. Also, the usefulness value can be based upon a base usefulness value for the identified CI, and decreases based upon an increased number of instances in which the scene **125** is modified based upon the identified CI. The identified CI can be a visual object displayed within the scene **125** or a human gesture displayed within the scene **125**. The scene **125** is a computer data structure that represents a particular environment in which the users **105A-C** interact. The intelligent recognition can employ machine learning to identify the CIs.

[0022] By employing the architecture **100** and methodology **300A**, **300B** of the present invention, cultural differences between different countries and regions can easily be reflected in the user's viewing process. If there are relevant audio or text descriptions in the environment or scene in the metaverse, focusing on the cultural differences that exist in different countries and regions can provide an improved experience for the users **105A-C**. Additionally, the architecture **100** and methodology **300A**, **300B** can provide improved accessibility quality.

[0023] As used herein, a “scene” **125** is defined as a computer data structure that represents a particular environment in which users **105A-C** of the metaverse interact either indirectly (e.g., by viewing the scene **125**) or directly. The scene **125** can include, but is not limited to, information describing the virtual environment in which the users **105A-C** interact, the users **105A-C** themselves, gestures performed by the users **105A-C**, and virtual objects (e.g., totems) with which users **105A-C** can interact. A cultural item (CI), as used herein, can be a virtual object or a gesture

that has a cultural connotation that may differ depending upon the cultural identity (e.g., country/region) of the user perceiving the CI. As used herein, a “gesture” is defined as a movement/action, associated with a particular user **105A**, that is capable of being viewed by other users **105B-C** within the virtual environment. A gesture can also include a perceptible representation (e.g., visual/audio/tactile) of speech/text generated by the particular user **105A**. Although the present architecture **100** and methodology **300A**, **300B** is discussed with regard to the metaverse, the same approach can be employed for a particular user **105A** watching content (e.g., a movie or video). Although this disclosure pertains to the collection of personal data (e.g., gestures), in certain embodiments and as further described below, users **105A-C** opt-into the system **100**. Additionally, the users **105A-C** can be informed as to what personal data is being collected by the system **100** and how the personal data is being used. Also, any collected personal data may be encrypted while being used, and that a particular user **105A** can opt-out of using the system **100** at any time. Additionally, if a particular user **105A** opts-out, the personal data of the particular user **105A** is deleted.

[0024] Referring to FIG. **1B**, the culturally-intelligent platform **120** can include one or more functional components **130-170** and one or more storage systems **145**, **155**, **165** that can be used to implement the methodology **300A**, **300B**. Although the culturally-intelligent platform **120** is illustrated as including the functional components **130-170** and one or more storage systems **145**, **155**, **165**, one or more of these components **130-170** and one or more storage systems **145**, **155**, **165** may be external to the culturally-intelligent platform **120**. For example, the dynamic library/user profile **145**, cultural library **155**, training corpus **165**, and machine learning engine **160** could be located in the cloud, as described in more detail with regard to FIG. **7**.

[0025] Additionally, the culturally-intelligent platform **120** can be part of (or interact with a metaverse service platform **122** that supports the creation of the metaverse). The aforementioned scenes **125** can be received from this metaverse service platform **122** and/or directly from the XR systems **110**. The metaverse service platform **122** is not limited to a particular type of technology/service, and can be any known provider that supports implementation of the metaverse. [0026] Prior to performing the process **300B** of generating a modified scene **185** illustrated in FIG. **3B**, the cultural library **155** can be generated using the process **300A** illustrated in FIG. **3A**. The cultural library **155** includes data representing CIs in the form of cultural item (CI) object instances **400**, which are further discussed with regard to FIG. **4**. These CI object instances **400** are generated for each CI. The CI object instances **400** identify the CI using attribute information, in what circumstances the CI is applicable (e.g., a particular country/region), and a description of the CI that can be subsequently used to modify the scene **125** to generate the modified scene **185**.

[0027] FIG. **4** illustrates an example of a CI object instance **400**, which is a specific data structure associated with the CI. The CI object instance **400** can include an object header **402**, object data **404**, and optionally object padding **406**. Object padding **406** is a known technique for adding empty bytes to a data structure to ensure proper alignment and promote efficient memory access. Although not limited to this specific information, the object data **404** can include: (i) country/region to which the CI object instance **400** applies, (ii) group ID that identifies the type of CI (e.g., gesture, action, totem, animal), (iii) CI-ID, which is a specific identifier associated with the CI object instance, and (iv) a description of the CI. The object data **404** can also include a measure of usefulness (e.g., usefulness value). The usefulness value can be used to determine, in operation **360**, whether to modify the scene **125**.

[0028] An example process **300A** for generating the CI object instances **400** for the cultural library **155** is illustrated with regard to FIG. **3A**. In **305**, a scene **125** from the training corpus **165** is received, and in **310**, participants **105A-C** within that scene **125** are identified similar to the manner discussed with regard to operation **310** in FIG. **3B**. The identification of the participants **105A-C** can also include an identification of cultural identity (e.g., country/region) of the participants **105A-C**. In **330**, an intelligent recognition operation **330** is performed on the scene **125** to identify CIs

within the scene **125**. In **340**, a determination is made whether one or more CIs exists within the scene **125**. If not, the process **300A** returns to operation **305** to receive and subsequently analyze another scene **125**. However, if a CI exists, in **350**, a determination is made whether a CI description (e.g., the CI object instance **400**) exists for the CI. If the CI description already exists, the process **300A** returns to operation **305** to receive and subsequently analyze another scene **125**. However, if a CI object instance **400** does not exist for a particular CI, then the CI object instance **400** is generated in operation **355**.

[0029] The CI object instances **400** stored within the cultural library **155** are not limited in the manner in which they are generated. However, in certain aspects the CI object instances **400** stored within cultural library **155** are generated using a machine learning engine **160** in conjunction with the training corpus **165** of prior scenes (e.g., videos). Many different artificial intelligence approaches can be used to train the machine learning engine **160** and generate a library of objects, and the culturally-intelligent platform **120** is not limited as to a particular approach. For example, the machine learning engine **160** can employ supervised learning where a human can annotate images derived from the training corpus **165**. Additionally, a deep learning approach using a convolution neural network (CNN) can be employed. Regardless of the approach employed, the cultural library **155** is populated with CI object instances **400** that will subsequently be used to identify CIs within real-time received scenes **125**, as further described in FIG. 3B.

[0030] The dynamic library/user profile **145** is a storage system that can be used to store information regarding each user **105A-C**. Although described separately, the dynamic library/user profile **145** can be combined together. The user profile **145** can include information that establishes a cultural identity of a particular participant **105A**. For example, the user profile **145** may indicate that the particular participant **105A** identifies with a particular cultural region or location. Additionally, the user profile **145** for a particular participant **105A** may also include an indicator (e.g., ON or OFF) whether the participant **105A** has chosen to opt into use of the culturally-intelligent platform **120** to generate a modified scene **185**. The user profile **145** can be generated by the user and/or automatically generated based upon information associated with the user (e.g., a particular IP address may indicate a user is from a particular geographic region).

[0031] An example of the data contained within the dynamic library **145** is illustrated with regard to FIG. 5. As illustrated, the dynamic library **145** can include, for each user **105A-C**, data indicating what CI each user **105A-C** has been exposed to in addition to information pertaining to the CI (e.g., the CI object instance **400**) and information that can be used to determine a usefulness value for the CI (e.g., the number of times that the CI has been called).

[0032] Referring specifically to FIG. 3B, the process **300B** of generating a modified scene **185** is further described. In **305**, a scene **125** is received, in real-time, by the interface **130** of the culturally-intelligent platform **120**. In **310**, participants **105A-C** in the scene **125** are identified in real-time by the intelligent recognition processor **140**. Identifying participants **105A-C** of a scene **125** in the metaverse is a known technology, and any technique so capable is acceptable for use with the culturally-intelligent platform **120**. The participants **105A-C** can be users who are themselves represented in the scene **125** (e.g., by using an avatar). Additionally, the participants **105A-C** can be users who are just viewing the scene **125**.

[0033] In **320**, once the identities of the participants in the scene **125** are established, the intelligent recognition processor **140** can optionally make a determination as whether to perform intelligent recognition of CIs within the current scene **125**. This determination can be performed using information stored within the user profile **145** of each of the participants **105A-C**.

[0034] Based upon the information stored with the user profile **145**, a determination is made whether to employ the culturally-intelligent platform **120** to perform intelligent recognition of CIs within the current scene **125** and subsequently generate a modified scene **185**. For example, if all of the participants **105A-C** are from the same geographic region and have the same cultural identity, the culturally-intelligent platform **120** can determine that there is no need to generate a modified

scene **185**. Alternatively, if all of the participants **105A-C** have chosen to opt out of using the culturally-intelligent platform **120**, then the process **300B** returns to operation **305** to perform the real-time receipt of a new scene **125** and identification of participants in that scene **125** in operation **310**. However, if the participants **105A-C** have different cultural identities and one or more of the participants **105A-C** have opted into using the culturally-intelligent platform **120** to generate a modified scene **185**, the process **300B** proceeds to the real-time intelligent recognition operation **330**.

[0035] In **330**, based upon the determination in **320**, intelligent recognition of the current scene **125** is performed in real-time by the intelligent recognition processor **140** of the culturally-intelligent platform **120** in conjunction with the machine learning engine **160** and the cultural library **155**. In other words, as the scene **125** changes and new CIs are possibly displayed, the intelligent recognition processor **140** can continually monitor, in real-time, the scene **125** and recognize, using the CI object instances **400** stored within the cultural library **155**, any new CIs as they appear within the scene **125**. The manner in which the intelligent recognition processor **140** operates is not limited as to a particular approach.

[0036] For example, the intelligent recognition processor **140** can employ known technology (e.g., video object detection (VOD)) to identify objects within the scene **125**. Although not limited in this manner, the intelligent recognition processor **140** can use the machine learning engine **160** along with the information contained within the cultural library **155** to perform the identification of the CIs within the scene **125**. As discussed above with regard to the process **300A** of generating the cultural library **155**, the machine learning engine **160** can use any number of known artificial intelligence techniques to identify CIs. Consequently, the intelligent recognition processor **140** can be configured to identify, amongst all objects identified within the scene **125**, specific CIs.

[0037] Additionally, the intelligent recognition processor **140** can be configured to identify CIs in the form of human actions, for example, by performing human post estimation, which includes extracting human body key points from the scene **125** while using lines and/or skeletons to represent human postures. According to changes in the identified human postures, each frame or segment in the scene **125** can be divided into different action categories (e.g., head movement, hand movement). Using the different action categories, a particular human action, as a CI, can be identified. Many other approaches to identifying human actions from a video are known, and the intelligent recognition processor **140** is not limited as to a particular approach so capable.

[0038] In **360**, a determination is made as to the usefulness associated with a particular CI. As discussed above, an initial usefulness value can be associated with each particular CI and modified based upon user information associated with a particular user **105A**. In particular, the usefulness value can be compared to a predetermined threshold value (either preset or set by the particular user **105A**), and based upon that comparison, a determination can be made whether to modify the scene **125**. For example, if the threshold value is 30% and the usefulness value is determined to be 40%, then a determination can be made to modify the scene **125**.

[0039] There are multiple possible approaches for determining the usefulness value, and the culturally-intelligent platform **120** is not limited as to a particular approach. One possible approach would involve assigning a base usefulness value to a particular CI that can be modified based upon how many times a particular description of the CI has been presented to a user **105A-C**. A data structure **500** associated with a particular user, as illustrated in FIG. 5, for example, can include a number of times (e.g., Call_Times) the particular description of a CI has been presented to the particular user **105A**. The number of calls can then be modified by some predetermined value (either preset or set by the particular user **105A**) and used to modify the base usefulness value. For example, if the base usefulness value is 100%, the number of calls is 3, and the predetermined value is 15%, then the modified usefulness value is $(100\% - (3 \times 15\%))$ or 55%, which can then be compared to the threshold value. This approach is based upon an assumption that the utility of a particular description of the CI is reduced the more times a particular user **105A** views the

description of the CI.

[0040] In another approach, the threshold value can be based upon user feedback **175** provided in operation **390**. For example, after the scene **125** was modified to include a description of the CI, the feedback processor **170** of the culturally-intelligent platform **120** can request feedback **175** from the particular user **105A**. Although not limited in this manner, the feedback **175** can be in the form of providing a ranking for the description of between 1 to 5 stars. This feedback information can be stored within the dynamic library/user profile **145** in operation **395**. By way of example, if the threshold value is 40%, the culturally-intelligent platform **120** can subsequently determine, in operation **370**, that modification of the scene **125** to include the description will not be performed.

[0041] In yet another approach, the culturally-intelligent platform **120** can cause the XR system **110** associated with the particular user **105A** to prompt, in real-time, the user **105A** as to whether a description of the CI is desired by the particular user **105A**. The user **105A** then has the option to receive (or not receive) a description of the CI as part of a modified scene **185**.

[0042] The real-time intelligent recognition operation **330** and usefulness determination operation **360** can be performed until all CIs within the scene **125** have been identified and usefulness determined. If no CIs were determined to be useful in **360**, the process **300B** returns to operation **305** to continue receipt real-time receipt and subsequent analysis of a new scene **125**. Otherwise, the process **300B** proceeds to operation **380** to modify the scene **125** to generate a modified scene **185**.

[0043] In **380**, the cultural processor **150** of the culturally-intelligent platform **120** modifies the scene **125** to generate a modified scene **185** that will be subsequently provided to the particular user **105A**. The manner in which the modified scene **185** is not limited as to a particular approach. For example, the modified scene **185** can include both the original scene **125** and the description of one or more CIs that met the usefulness determination in operation **360**. In another example, the modified scene **185** can include just an identification of the one or more CIs within the scene **125** as well as the description of the CIs to be subsequently added to the scene **125**. This information can be transmitted and subsequently combined with the original scene **125** by the XR system **110** and/or metaverse service platform **122** and presented to the particular user **105A**. Examples of modified scenes **185** are illustrated in FIGS. **6A** and **6B**. In each instance, the modified scenes **185** can include visual representations **190** of the description of the CI. Although not illustrated, the modification to the original scene **125** can include, additionally or alternatively, modifications to the CI themselves. For example, a particularly-offensive CI could be blurred and/or modified to be more culturally sensitive. For example, in Chinese cultural, gesturing with a single finger (e.g., a little finger) can be considered offensive and that gesture (i.e., CI) could be replaced with a whole-hand gesture, which is more culturally-accepted. The modified scene **185**, once generated, can then be forwarded to the metaverse service platform **122** and/or the XR systems **110** of the particular user **105A**.

[0044] In **390**, after the scene **125** has been modified to generate a modified scene **185**, the particular user **105A** can optionally be provided with an opportunity to provide feedback **175** to the culturally-intelligent platform **120**, as already discussed above. Many different approaches can be used, and the culturally-intelligent platform **120** is not limited as to a particular approach. For example, the culturally-intelligent platform **120** can use the feedback processor **170** to request and/or receive feedback **175** as to the modified scene **185** from the XR system **110** associated with the particular user **105A**. This feedback **175** can include a rating of the usefulness of the description of the CI. The feedback **175**, however, is not limited in this manner. The feedback **175** can also include suggested modifications to the description of the CI.

[0045] In **395**, the dynamic library/user profile **145** can be updated. For example, the number of times a particular CI description has been called by a particular user **105A** can be modified. Additionally, based upon the feedback **175**, the usefulness value of a particular CI description to a particular user **105A** can be modified. The process **300B** then returns to operation **305** to continue

receipt real-time receipt and subsequent analysis of a new scene **125**.

[0046] As defined herein, the term “responsive to” means responding or reacting readily to an action or event. Thus, if a second action is performed “responsive to” a first action, there is a causal relationship between an occurrence of the first action and an occurrence of the second action, and the term “responsive to” indicates such causal relationship.

[0047] As defined herein, the terms “real-time” or “real time” mean a level of processing responsiveness that a user or system senses as sufficiently immediate for a particular process or determination to be made, or that enables the processor to keep up with some external process.

[0048] As defined herein, the term “automatically” means without user intervention.

[0049] Referring to FIG. 7, computing environment **700** contains an example of an environment for the execution of at least some of the computer code involved in performing the inventive methods, such as code block **750** for implementing the operations of the culturally-intelligent platform **120**. Computing environment **700** includes, for example, computer **701**, wide area network (WAN) **702**, end user device (EUD) **703**, remote server **704**, public cloud **705**, and private cloud **706**. In certain aspects, computer **701** includes processor set **710** (including processing circuitry **720** and cache **721**), communication fabric **711**, volatile memory **712**, persistent storage **713** (including operating system **722** and method code block **750**), peripheral device set **714** (including user interface (UI), device set **723**, storage **724**, and Internet of Things (IoT) sensor set **725**), and network module **715**. Remote server **704** includes remote database **730**. Public cloud **705** includes gateway **740**, cloud orchestration module **741**, host physical machine set **742**, virtual machine set **743**, and container set **744**.

[0050] Computer **701** may take the form of a desktop computer, laptop computer, tablet computer, smart phone, smart watch or other wearable computer, mainframe computer, quantum computer or any other form of computer or mobile device now known or to be developed in the future that is capable of running a program, accessing a network or querying a database, such as remote database **730**. As is well understood in the art of computer technology, and depending upon the technology, performance of a computer-implemented method may be distributed among multiple computers and/or between multiple locations. However, to simplify this presentation of computing environment **700**, detailed discussion is focused on a single computer, specifically computer **701**. Computer **701** may or may not be located in a cloud, even though it is not shown in a cloud in FIG. 7 except to any extent as may be affirmatively indicated.

[0051] Processor set **710** includes one, or more, computer processors of any type now known or to be developed in the future. As defined herein, the term “processor” means at least one hardware circuit (e.g., an integrated circuit) configured to carry out instructions contained in program code. Examples of a processor include, but are not limited to, a central processing unit (CPU), an array processor, a vector processor, a digital signal processor (DSP), a field-programmable gate array (FPGA), a programmable logic array (PLA), an application specific integrated circuit (ASIC), programmable logic circuitry, and a controller. Processing circuitry **720** may be distributed over multiple packages, for example, multiple, coordinated integrated circuit chips. Processing circuitry **720** may implement multiple processor threads and/or multiple processor cores. Cache **721** is memory that is located in the processor chip package(s) and is typically used for data or code that should be available for rapid access by the threads or cores running on processor set **710**. Cache memories are typically organized into multiple levels depending upon relative proximity to the processing circuitry. Alternatively, some, or all, of the cache for the processor set may be located “off chip.” In certain computing environments, processor set **710** may be designed for working with qubits and performing quantum computing.

[0052] Computer readable program instructions are typically loaded onto computer **701** to cause a series of operational steps to be performed by processor set **710** of computer **701** and thereby effect a computer-implemented method, such that the instructions thus executed will instantiate the methods specified in flowcharts and/or narrative descriptions of computer-implemented methods

discussed above in this document (collectively referred to as “the inventive methods”). These computer readable program instructions are stored in various types of computer readable storage media, such as cache **721** and the other storage media discussed below. The program instructions, and associated data, are accessed by processor set **710** to control and direct performance of the inventive methods. In computing environment **700**, at least some of the instructions for performing the inventive methods may be stored in code block **750** in persistent storage **713**.

[0053] A computer program product embodiment (“CPP embodiment” or “CPP”) is a term used in the present disclosure to describe any set of one, or more, storage media (also called “mediums”) collectively included in a set of one, or more, storage devices that collectively include machine readable code corresponding to instructions and/or data for performing computer operations specified in a given CPP claim. A “storage device” is any tangible, hardware device that can retain and store instructions for use by a computer processor. Without limitation, the computer readable storage medium may be an electronic storage medium, a magnetic storage medium, an optical storage medium, an electromagnetic storage medium, a semiconductor storage medium, a mechanical storage medium, or any suitable combination of the foregoing. Some known types of storage devices that include these mediums include: diskette, hard disk, random access memory (RAM), read-only memory (ROM), erasable programmable read-only memory (EPROM or Flash memory), static random access memory (SRAM), compact disc read-only memory (CD-ROM), digital versatile disk (DVD), memory stick, floppy disk, mechanically encoded device (such as punch cards or pits/lands formed in a major surface of a disc) or any suitable combination of the foregoing.

[0054] A computer readable storage medium, as that term is used in the present disclosure, is not to be construed as storage in the form of transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide, light pulses passing through a fiber optic cable, electrical signals communicated through a wire, and/or other transmission media. As will be understood by those of skill in the art, data is typically moved at some occasional points in time during normal operations of a storage device, such as during access, de-fragmentation or garbage collection, but this does not render the storage device as transitory because the data is not transitory while it is stored.

[0055] Communication fabric **711** is the signal conduction paths that allow the various components of computer **701** to communicate with each other. Typically, this communication fabric **711** is made of switches and electrically conductive paths, such as the switches and electrically conductive paths that make up busses, bridges, physical input/output ports and the like. Other types of signal communication paths may be used for the communication fabric **711**, such as fiber optic communication paths and/or wireless communication paths.

[0056] Volatile memory **712** is any type of volatile memory now known or to be developed in the future. Examples include dynamic type random access memory (RAM) or static type RAM. Typically, the volatile memory **712** is characterized by random access, but this is not required unless affirmatively indicated. In computer **701**, the volatile memory **712** is located in a single package and is internal to computer **701**. In addition to alternatively, the volatile memory **712** may be distributed over multiple packages and/or located externally with respect to computer **701**.

[0057] Persistent storage **713** is any form of non-volatile storage for computers that is now known or to be developed in the future. The non-volatility of the persistent storage **713** means that the stored data is maintained regardless of whether power is being supplied to computer **701** and/or directly to persistent storage **713**. Persistent storage **713** may be a read only memory (ROM), but typically at least a portion of the persistent storage **713** allows writing of data, deletion of data and re-writing of data. Some familiar forms of persistent storage **713** include magnetic disks and solid state storage devices. Operating system **722** may take several forms, such as various known proprietary operating systems or open source Portable Operating System Interface type operating systems that employ a kernel. The code included in code block **750** typically includes at least some

of the computer code involved in performing the inventive methods.

[0058] Peripheral device set **714** includes the set of peripheral devices for computer **701**. Data communication connections between the peripheral devices and the other components of computer **701** may be implemented in various ways, such as Bluetooth connections, Near-Field Communication (NFC) connections, connections made by cables (such as universal serial bus (USB) type cables), insertion type connections (for example, secure digital (SD) card), connections made through local area communication networks and even connections made through wide area networks such as the internet.

[0059] In various aspects, UI device set **723** may include components such as a display screen, speaker, microphone, wearable devices (such as goggles and smart watches), keyboard, mouse, printer, touchpad, game controllers, and haptic devices. Storage **724** is external storage, such as an external hard drive, or insertable storage, such as an SD card. Storage **724** may be persistent and/or volatile. In some aspects, storage **724** may take the form of a quantum computing storage device for storing data in the form of qubits. In aspects where computer **701** is required to have a large amount of storage (for example, where computer **701** locally stores and manages a large database) then this storage **724** may be provided by peripheral storage devices designed for storing very large amounts of data, such as a storage area network (SAN) that is shared by multiple, geographically distributed computers. Internet-of-Things (IoT) sensor set **725** is made up of sensors that can be used in IoT applications. For example, one sensor may be a thermometer and another sensor may be a motion detector.

[0060] Network module **715** is the collection of computer software, hardware, and firmware that allows computer **701** to communicate with other computers through a Wide Area Network (WAN) **702**. Network module **715** may include hardware, such as modems or Wi-Fi signal transceivers, software for packetizing and/or de-packetizing data for communication network transmission, and/or web browser software for communicating data over the internet. In certain aspects, network control functions and network forwarding functions of network module **715** are performed on the same physical hardware device. In other aspects (for example, aspects that utilize software-defined networking (SDN)), the control functions and the forwarding functions of network module **715** are performed on physically separate devices, such that the control functions manage several different network hardware devices. Computer readable program instructions for performing the inventive methods can typically be downloaded to computer **701** from an external computer or external storage device through a network adapter card or network interface included in network module **715**.

[0061] WAN **702** is any Wide Area Network (for example, the internet) capable of communicating computer data over non-local distances by any technology for communicating computer data, now known or to be developed in the future. In some aspects, the WAN **702** may be replaced and/or supplemented by local area networks (LANs) designed to communicate data between devices located in a local area, such as a Wi-Fi network. The WAN **702** and/or LANs typically include computer hardware such as copper transmission cables, optical transmission fibers, wireless transmission, routers, firewalls, switches, gateway computers and edge servers.

[0062] End user device (EUD) **703** is any computer system that is used and controlled by an end user (for example, a customer of an enterprise that operates computer **701**), and may take any of the forms discussed above in connection with computer **701**. EUD **703** typically receives helpful and useful data from the operations of computer **701**. For example, in a hypothetical case where computer **701** is designed to provide a recommendation to an end user, this recommendation would typically be communicated from network module **715** of computer **701** through WAN **702** to EUD **703**. In this way, EUD **703** can display, or otherwise present, the recommendation to an end user. In certain aspects, EUD **703** may be a client device, such as thin client, heavy client, mainframe computer, desktop computer and so on.

[0063] As defined herein, the term “client device” means a data processing system that requests

shared services from a server, and with which a user directly interacts. Examples of a client device include, but are not limited to, a workstation, a desktop computer, a computer terminal, a mobile computer, a laptop computer, a netbook computer, a tablet computer, a smart phone, a personal digital assistant, a smart watch, smart glasses, a gaming device, a set-top box, a smart television and the like. Network infrastructure, such as routers, firewalls, switches, access points and the like, are not client devices as the term “client device” is defined herein. As defined herein, the term “user” means a person (i.e., a human being).

[0064] Remote server **704** is any computer system that serves at least some data and/or functionality to computer **701**. Remote server **704** may be controlled and used by the same entity that operates computer **701**. Remote server **704** represents the machine(s) that collect and store helpful and useful data for use by other computers, such as computer **701**. For example, in a hypothetical case where computer **701** is designed and programmed to provide a recommendation based on historical data, then this historical data may be provided to computer **701** from remote database **730** of remote server **704**. As defined herein, the term “server” means a data processing system configured to share services with one or more other data processing systems.

[0065] Public cloud **705** is any computer system available for use by multiple entities that provides on-demand availability of computer system resources and/or other computer capabilities, especially data storage (cloud storage) and computing power, without direct active management by the user. Cloud computing typically leverages sharing of resources to achieve coherence and economies of scale. The direct and active management of the computing resources of public cloud **705** is performed by the computer hardware and/or software of cloud orchestration module **741**. The computing resources provided by public cloud **705** are typically implemented by virtual computing environments that run on various computers making up the computers of host physical machine set **742**, which is the universe of physical computers in and/or available to public cloud **705**.

[0066] The virtual computing environments (VCEs) typically take the form of virtual machines from virtual machine set **743** and/or containers from container set **744**. It is understood that these VCEs may be stored as images and may be transferred among and between the various physical machine hosts, either as images or after instantiation of the VCE. Cloud orchestration module **741** manages the transfer and storage of images, deploys new instantiations of VCEs and manages active instantiations of VCE deployments. Gateway **740** is the collection of computer software, hardware, and firmware that allows public cloud **705** to communicate through WAN **702**.

[0067] VCEs can be stored as “images,” and a new active instance of the VCE can be instantiated from the image. Two familiar types of VCEs are virtual machines and containers. A container is a VCE that uses operating-system-level virtualization. This refers to an operating system feature in which the kernel allows the existence of multiple isolated user-space instances, called containers. These isolated user-space instances typically behave as real computers from the point of view of programs running in them. A computer program running on an ordinary operating system can utilize all resources of that computer, such as connected devices, files and folders, network shares, CPU power, and quantifiable hardware capabilities. However, programs running inside a container can only use the contents of the container and devices assigned to the container, a feature which is known as containerization.

[0068] Private cloud **706** is similar to public cloud **705**, except that the computing resources are only available for use by a single enterprise. While private cloud **706** is depicted as being in communication with WAN **702**, in other aspects, a private cloud **706** may be disconnected from the internet entirely (e.g., WAN **702**) and only accessible through a local/private network. A hybrid cloud is a composition of multiple clouds of different types (for example, private, community or public cloud types), often respectively implemented by different vendors. Each of the multiple clouds remains a separate and discrete entity, but the larger hybrid cloud architecture is bound together by standardized or proprietary technology that enables orchestration, management, and/or data/application portability between the multiple constituent clouds. In this aspect, public cloud

705 and private cloud **706** are both part of a larger hybrid cloud.

[0069] FIG. **8** is an example of an example of the XR system **110** previously illustrated in FIG. **1A**. As shown, the XR system **110** includes an audio/video (A/V) headset **818**, as referred to as smart glasses, augmented reality device or an extended reality headset. The XR system **300** also includes a XR computer **810**. Although illustrated as being separate from the headset **818**, one or more portions of the XR computer **810** can be embedded within the headset **818**. The example XR system **300**, and/or components thereof, are not intended to be necessarily limiting as to the present disclosure.

[0070] The XR computer **810** can include one or more XR processors **812**, **814**, which can be a single processor or a multi-threaded processor, a general purpose or a special purpose processor, a co-processor, or any of a variety of processing devices that can execute computing instructions. If one or more portions of the XR computer **810** are separate from the headset **818**, interface **816** couples XR computer **810** to the headset **818**. The XR processors **812**, **814** can be connected by memory interface **820** to memory **830**, which can be a cache memory, a main memory, a flash memory, or a combination of these or other varieties of electronic hardware devices capable of storing information and, optionally, making the information, or locations storing the information within the memory, accessible to the XR processors **812**, **814**. The XR computer **810** can include an IO bridge **350**, which can be connected to the memory **830** and/or XR processors **812**, **814** by a memory interface **320**. The IO bridge **850** can interface with the memory interface **820** to IO devices, such as IO device **860**. The interface **822** can be any of a variety of IO interfaces, such as a PCI-Express (PCI-E) bus, and IO bridge **850** can, correspondingly, be a PCI-E bridge, and IO device **860** can be a PCI-E device (e.g., a disk drive), or PCI-E adapter (e.g., a network interface card, or a disk adapter). The IO devices **860**-an be any of a variety of peripheral IO devices or IO adapters connecting to peripheral IO devices. For example, IO device **860** can be a graphic card, keyboard or other input device, a hard drive or other storage device, a network interface card, etc. Additionally, the XR system **110** can communicate with other devices, such as the culturally-intelligent platform **120** illustrated in FIGS. **1A-B**, using the IO device **860**.

[0071] The XR computer **810** can include instructions executable by one or more of the XR processors (or, processing elements, such as threads of a XR processor) **812**, **814**. As illustrated, XR computer **810** includes a plurality of programs, such as XR programs **804A**, **804B**, **804C** (collectively, “XR programs **804**”), and **808**, and operating systems OS **802** and **806**. The XR programs **804** can be, for example, an application program (e.g., an application for generating XR expressions), a function of an operating system (e.g., a device driver capable of operating an IO device, such as **860**), or a utility or built-in function of a computer, such as **810**. A XR program **804** can be a hypervisor, and the hypervisor can, for example, manage sharing resources of the computer (e.g., a XR processor or regions of a memory, or access to an IO device) among a plurality of programs or OSes. A XR program **804** can be a program that embodies the methods, or portions thereof, of the disclosure. For example, a XR program **804** can be a program that executes on a XR processor **812**, **814** of XR computer **810** to perform method **300** of FIG. **3**, or portions and/or modifications thereof, within the scope of the present disclosure.

[0072] Various aspects of the present disclosure are described by narrative text, flowcharts, block diagrams of computer systems and/or block diagrams of the machine logic included in computer program product (CPP) embodiments. With respect to any flowcharts, depending upon the technology involved, the operations can be performed in a different order than what is shown in a given flowchart. For example, again depending upon the technology involved, two operations shown in successive flowchart blocks may be performed in reverse order, as a single integrated step, concurrently, or in a manner at least partially overlapping in time.

[0073] As another example, two blocks shown in succession may, in fact, be accomplished as one step, executed concurrently, substantially concurrently, in a partially or wholly temporally overlapping manner, or the blocks may sometimes be executed in the reverse order, depending

upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts or carry out combinations of special purpose hardware and computer instructions. Each block in the flowchart or block diagrams may represent a module, segment, or portion of instructions, which comprises one or more executable instructions for implementing the specified logical function(s).

[0074] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this disclosure, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0075] Reference throughout this disclosure to “one embodiment,” “an embodiment,” “one arrangement,” “an arrangement,” “one aspect,” “an aspect,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment described within this disclosure. Thus, appearances of the phrases “one embodiment,” “an embodiment,” “one arrangement,” “an arrangement,” “one aspect,” “an aspect,” and similar language throughout this disclosure may, but do not necessarily, all refer to the same embodiment.

[0076] The term “plurality,” as used herein, is defined as two or more than two. The term “another,” as used herein, is defined as at least a second or more. The term “coupled,” as used herein, is defined as connected, whether directly without any intervening elements or indirectly with one or more intervening elements, unless otherwise indicated. Two elements also can be coupled mechanically, electrically, or communicatively linked through a communication channel, pathway, network, or system. The term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms, as these terms are only used to distinguish one element from another unless stated otherwise or the context indicates otherwise.

[0077] The term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context. As used herein, the terms “if,” “when,” “upon,” “in response to,” and the like are not to be construed as indicating a particular operation is optional. Rather, use of these terms indicate that a particular operation is conditional. For example and by way of a hypothetical, the language of “performing operation A upon B” does not indicate that operation A is optional. Rather, this language indicates that operation A is conditioned upon B occurring.

[0078] The foregoing description is just an example of embodiments of the invention, and variations and substitutions. While the disclosure concludes with claims defining novel features, it is believed that the various features described herein will be better understood from a consideration of the description in conjunction with the drawings. The process(es), machine(s), manufacture(s) and any variations thereof described within this disclosure are provided for purposes of illustration. Any specific structural and functional details described are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the features described in virtually any appropriately detailed structure. Further,

the terms and phrases used within this disclosure are not intended to be limiting, but rather to provide an understandable description of the features described.

Claims

- 1.** A computer-implemented method by a culturally-intelligent platform including a dynamic library for generating a modified scene, comprising: receiving, in real-time, a scene associated with a particular user; processing, in real-time, the scene to identify participants associated with the scene; performing, in real-time and using the dynamic library, intelligent recognition on the scene to identify a cultural item within the scene; and modifying the scene, based upon a description of the identified cultural item within the dynamic library, to generate a modified scene that includes the description.
- 2.** The method of claim 1, further comprising: determining a usefulness of the identified cultural item; and updating an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item based upon the scene being modified for the particular user.
- 3.** The method of claim 2, wherein the usefulness is determined based upon comparing a usefulness value for the identified cultural item to a threshold value.
- 4.** The method of claim 3, wherein the usefulness value is based upon a base usefulness value for the identified cultural item, and decreases based upon an increased number of instances in which the scene is modified based upon the identified cultural item.
- 5.** The method of claim 1, wherein the identified cultural item is a visual object displayed within the scene.
- 6.** The method of claim 1, wherein the identified cultural item is a human gesture displayed within the scene.
- 7.** The method of claim 1, wherein the scene is a computer data structure that represents a particular environment in which the users interact.
- 8.** The method of claim 1, wherein the intelligent recognition employs machine learning to identify the cultural items.
- 9.** A computer hardware system including a culturally-intelligent platform having a dynamic library for generating a modified scene, comprising: a hardware processor configured to perform the following executable operations: receiving, in real-time, a scene associated with a particular user; processing, in real-time, the scene to identify participants associated with the scene; performing, in real-time and using the dynamic library, intelligent recognition on the scene to identify a cultural item within the scene; and modifying the scene, based upon a description of the identified cultural item within the dynamic library, to generate a modified scene that includes the description.
- 10.** The system of claim 9, wherein the hardware processor is further configured to perform: determining a usefulness of the identified cultural item; and updating an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item based upon the scene being modified for the particular user.
- 11.** The system of claim 10, wherein the usefulness is determined based upon comparing a usefulness value for the identified cultural item to a threshold value.
- 12.** The system of claim 11, wherein the usefulness value is based upon a base usefulness value for the identified cultural item, and decreases based upon an increased number of instances in which the scene is modified based upon the identified cultural item.
- 13.** The system of claim 9, wherein the identified cultural item is a visual object displayed within the scene.
- 14.** The system of claim 9, wherein the identified cultural item is a human gesture displayed within the scene.
- 15.** The system of claim 9, wherein the scene is a computer data structure that represents a

particular environment in which the users interact.

16. The system of claim 9, wherein the intelligent recognition employs machine learning to identify the cultural items.

17. A computer program product, comprising: a computer readable storage medium having stored therein program code for generating a modified scene, the program code, which when executed by a computer hardware system including a culturally-intelligent platform having a dynamic library, causes the computer hardware system to perform: receiving, in real-time, a scene associated with a particular user; processing, in real-time, the scene to identify participants associated with the scene; performing, in real-time and using the dynamic library, intelligent recognition on the scene to identify a cultural item within the scene; and modifying the scene, based upon a description of the identified cultural item within the dynamic library, to generate a modified scene that includes the description.

18. The computer program product of claim 17, wherein the program code further causes the computer hardware system to perform: determining a usefulness of the identified cultural item; and updating an entry in the dynamic library associated with the particular user regarding the usefulness of the identified cultural item based upon the scene being modified for the particular user.

19. The computer program product of claim 18, wherein the usefulness is determined based upon comparing a usefulness value for the identified cultural item to a threshold value.

20. The computer program product of claim 19, wherein the usefulness value is based upon a base usefulness value for the identified cultural item, and decreases based upon an increased number of instances in which the scene is modified based upon the identified cultural item.
