

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284868

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Koltenbah; Benjamin et al.

COMPUTING SYSTEM FOR PREDICTING SUBSTRATE TEMPERATURES DURING LASER OPERATION

Abstract

A computing system inputs parameters of a laser and a substrate to be subjected to operation of the laser to an ablation stage portion of a model to calculate a first segment of laser operation. The calculation outputs an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse, and an updated temperature value of the substrate after being subjected to the at least one laser pulse. The system inputs the updated values to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air, and iteratively switches between the ablation and thermodynamic stage portions through a final segment of laser operation to output a final predicted temperature value of the substrate.

Inventors: Koltenbah; Benjamin (Federal Way, WA), Gregersen; Kimberly-Alice (Seattle, WA), Froning; Marc (Seattle, WA), Kearschner; Madison (Seattle, WA)

Applicant: The Boeing Company (Arlington, VA)

Family ID: 1000007773220

Appl. No.: 18/599012

Filed: March 07, 2024

Publication Classification

Int. Cl.: G06F30/28 (20200101); G06F30/23 (20200101); G06F119/08 (20200101)

U.S. Cl.:

CPC G06F30/28 (20200101); G06F30/23 (20200101); G06F2119/08 (20200101)

Background/Summary

FIELD

[0001] The present disclosure relates generally to laser operation and more particularly to model-based engineering (MBE) tools for supporting development of laser ablation processes of materials.

BACKGROUND

[0002] Laser systems are commonly in use for operations such as laser ablation, in which material is removed from a substrate by laser. In one application, laser ablation is used to remove paint from a surface and/or prepare the surface for repainting. During this process, a layer of paint is removed by the energy of the laser. The laser can also be configured to remove impurities such as oxidation from the surface and/or to impart a desired surface roughness. New paint applied to surfaces treated in this manner has the expectation of better application, adhesion, and lifespan. However, for highly regulated industries such as aerospace, any changes to an already approved process or development of a brand-new process often requires significant investment in qualifying the updated or new process with the appropriate regulatory agencies. This may apply to updated laser technology, new materials, changed operation settings, and more. For example, one laser system for a specific application may take several years and detailed analysis of the laser system operating on hundreds of fatigue coupons to obtain full qualification and approval.

SUMMARY

[0003] To address the above issues, according to one aspect of the present disclosure, a computing system for predicting substrate temperatures during simulated laser operation is provided herein. In this aspect, the computing system includes processing circuitry configured to retrieve parameters of a laser and parameters of a substrate to be subjected to operation of the laser, and input the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation. As used herein, the “substrate” is the item or material subjected to the laser operation and may include one or more distinct layers and/or one or more coatings, or be formed of a single uniform material. The first calculation outputs an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse, and an updated temperature value of the substrate after being subjected to the at least one laser pulse. The processing circuitry is further configured to input the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air. The processing circuitry is further configured to iteratively switch between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a final predicted temperature value of the substrate.

[0004] Another aspect of the present disclosure relates to a method for predicting substrate temperatures during simulated laser operation. In this aspect, the method includes retrieving parameters of a laser and parameters of a substrate to be subjected to operation of the laser, and inputting the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation. The calculation outputs an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse, and an updated temperature value of the substrate after being subjected to the at least one laser pulse. The method includes inputting the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air. The method includes iteratively switching between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to

output a final predicted temperature value of the substrate.

[0005] Still another aspect of the present disclosure relates to a computing system for predicting substrate temperatures during simulated laser operation. The computing system includes processing circuitry configured to retrieve respective parameters of a laser and parameters of a plurality of substrates to be separately subjected to operation of the laser, and input the respective parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation. The calculation outputs a respective updated geometry of each substrate after a predicted ablation of material from the substrate via at least one laser pulse, and a respective updated temperature value of each substrate after being subjected to the at least one laser pulse. The processing circuitry is further configured to input the respective updated geometry and the respective updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs a respective updated temperature value of each substrate after heat transfer through the substrate and from the substrate to ambient air. The processing circuitry is further configured to iteratively switch between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a respective final predicted temperature value of each substrate. The processing circuitry is further configured to identify a respective maximum temperature predicted to be experienced by each substrate during the entire laser operation, compare the respective maximum temperature to the respective parameters of each substrate, and based on the comparison, output a prediction of whether each substrate of the plurality of substrates is to be damaged by the laser operation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates an example laser operation modeled by a computing system for predicting substrate temperatures during simulated laser operation according to one implementation of the present disclosure.

[0007] FIG. 2 is a schematic illustration of an example of the computing system used to model the laser operation of FIG. 1.

[0008] FIG. 3 is a flowchart of a method for predicting substrate temperatures during simulated laser operation.

[0009] FIG. 4 is a schematic view of an example computing environment in which the computing system of FIG. 2 may be enacted.

DETAILED DESCRIPTION

[0010] To address the issues discussed above, FIG. 1 illustrates an example laser operation modeled by a computing system for predicting substrate temperatures during simulated laser operation according to one implementation of the present disclosure. Here, a laser system **10** including one or more lasers is subjecting a substrate **12** to a laser operation. For example, the laser operation could be depainting, removal of another type of layer other than paint, surface preparation, boring, etching, etc. When the purpose of the laser operation is to remove or treat only a top surface, the substrate **12** may include a top layer **12A** and a bottom layer **12B**, as shown separated by a dashed line in FIG. 1 for illustration. Examples of materials of the top layer **12A** may include, but are not limited to, paint, ink, epoxy, ceramic coating, and various plastics.

[0011] Before the laser operation, the substrate **12** may be generally flat. As illustrated, the laser system **10** has emitted a laser pulse at three locations during the laser operation. Each laser pulse may leave a crater **14** in a top surface of the substrate **12** as material is ablated from the substrate **12**, as shown via straight lines on each side of a laser beam **16**. Generally, the laser beam **16** may have any suitable profile such as super-Gaussian (rounded top-hat), as may the temporal profile of the laser beam **16**. A cloud **18** of ash and vaporized residue may billow up around the laser beam **16**.

as it heats the material of the substrate **12** into plasma, which may be collected by a fume extractor and safely filtered. Any suitable type of laser may be modeled, such as an ultraviolet (UV) laser or a near infrared (near-IR) laser.

[0012] Notably, as each crater **14** is formed, heat from the laser beam **16** is imparted to the remaining substrate **12**, and as the laser system **10** moves along to the next site, residual heat from the earlier craters **14** continues spreading throughout the substrate **12** and dissipating to ambient air. A temperature profile of the craters **14** is illustrated with a color gradient, reproduced in FIG. **1** in grayscale. In addition, as shown in the right half of FIG. **1**, a three-dimensional (3D) rendering of the modeled laser operation disclosed herein may include a mesh **20** following the topography of the substrate **12** as it is altered by the laser system **10**. Because a flat surface will hold and spread heat differently than a cratered surface, the mesh **20** may be updated throughout the modeled laser operation in three dimensions to increase the accuracy of the final output. Alternatively, the modeling may be simplified to output a two-dimensional (2D) rendering when suitable.

[0013] Next, FIG. **2** is a schematic illustration of an example of a computing system **22** used to model the laser operation of FIG. **1**. The computing system **22** for predicting substrate temperatures during simulated laser operation includes at least one computing device **24** having processing circuitry **26** configured to execute instructions stored in memory **28** to perform various functions. At a basic level, the computing device **24** receives input parameters **30** from a source such as internal or external storage, user input, measurements, etc., performs calculation using a model **32**, and outputs as output **34** any number of values, data, and/or renderings based on predicted laser operation determined by the model **32**.

[0014] In more detail, the processing circuitry **24** is configured to retrieve parameters **30A** of a laser and parameters **30B** of a substrate to be subjected to operation of the laser, and input the parameters **30A**, **30B** of the laser and the substrate to an ablation stage portion **32A** of the model **32** to calculate a first segment of laser operation. The ablation stage portion **32A** of the model **32** may be simplified as a one-dimensional (1D) equation-based model that couples together a dozen or more physical processes such as photothermal decomposition and photodissociative bond breaking, depending on the materials used. In this case, the substrate **12** depth is discretized in 1D into segments as time also advances in discretized steps. The top layer **12A** of the substrate in some implementations is simplified as a polymer represented as a system of chemical moieties with two possible electronic states, and the populations of these states are tracked in time as energy is deposited into the substrate **12** from the laser beam **16**. There are further laser-induced chemical modifications resulting in a modified polymer, the concentration of which is monitored in each 1D segment to denote onset of ablation, that is, when the material is separated and removed from the rest of the substrate **12**. It is noted that in other implementations, the ablation stage portion **32A** of the model **32** may be expanded to 2D or 3D as needed, and/or may be built to correspond to different physical mechanisms for different materials and scenarios as appropriate.

[0015] Through the course of a single pulse of the laser beam **16** and the onset of ablation occurring deeper into the substrate **12**, the full ablation depth (crater depth) for that pulse is calculated. By incorporating the parameters **30A** such as the spot size and distribution, the 1D results can be expanded to hybridized 2D results for ablation depth and rate, and even 3D. The resulting temperature and ablation depth is highly dependent on the power (irradiance) of the laser system **10**, in addition to other settings in the parameters **30A** of the laser inputted to the model **32**, employing a form of the Beer-Lambert Law. For example, the parameters **30A** of the laser may include one or more of target ablation depth, frequency, power setting, efficiency, power delivery, spot diameter, spot area, pulse duration, pulse energy, peak power, spot fluence, irradiance, pulse overlap, line speed, row spacing, spot spacing, and/or dosage. Using a combination of these parameters **30A**, **30B**, for the first segment of laser operation, the ablation stage portion **32A** of the model may be configured to an updated geometry **36** of the substrate **12** (e.g., a mathematical description of the mesh **20** with one crater **14**) after a predicted ablation of material from the

substrate via at least one laser pulse, and an updated temperature value **38** of the substrate **12** after being subjected to the at least one laser pulse. Accordingly, further calculations can be made based on updated values for both heat and geometry after each ablation stage, increasing the accuracy of the model. As mentioned above, the model may describe the ablation in 2D or 3D, and therefore the updated geometry **36** of the substrate **12** may be 2D or 3D according to design considerations.

[0016] In some implementations, the at least one laser pulse may be one single laser pulse such that the model **32** calculates the impact of the laser operation one pulse at a time. This may allow the model **32** to accurately calculate changes in temperature in between each pulse. However, multiple laser pulses may be grouped together instead. In some implementations, such as for hole boring, multiple laser pulses may be performed at the same position on the substrate **12** rather than moving along the surface as illustrated in FIG. **1**. Additionally, for depainting, the substrate **12** may include the top layer **12A** of paint and the bottom layer **12B** of metal alloy, and the ablated material may include the paint. In this case, paint removal from a variety of components such as aircraft parts can be carefully and thoroughly performed to exact specifications and damage to the metal alloy can be avoided. The top layer **12A** to be removed may also be a resin formed on top of a composite bottom layer in other implementations, and the parameters **30B** of the substrate **12** utilized by the model **32** may be adjusted accordingly. For example, the top layer **12A** may be a degraded resin that is removed. It will be appreciated that the explanation of the laser operation herein is made from a top-down perspective where the laser operates downward onto a top surface or the top layer **12A**, but most substrates **12** are capable of being flipped over so that a bottom surface or the bottom layer **12B** can be subjected to the laser operation additionally or alternatively. Furthermore, the laser system **10** may be oriented in any feasible direction rather than strictly downward.

Alternatively, the laser operation may be surface preparation of the substrate **12** prior to painting, in order to provide a clean and suitable surface for a long-lasting, smooth, and consistent paint layer.

[0017] Next, the processing circuitry **26** may be configured to input the updated geometry **36** and the updated temperature value **38** to a thermodynamic stage portion **32B** of the model **32** to calculate a second segment of laser operation which outputs an updated temperature value **40** of the substrate **12** after heat transfer through the substrate **12** and from the substrate **12** to ambient air. For example, the thermodynamic stage portion **32B** may calculate heat transfer including natural convection, conduction, and radiation by use of one or more heat transfer equations, among other calculations. The computing system **22** may be configured to receive user input selecting which calculations should be included as settings. In some cases, the system may include one or more backside temperature sensors **42** (see FIG. **1**) configured to sample the temperature on a bottom surface of the substrate **12**, and the model **32** may be configured to output a predicted top surface temperature based on measurements from the temperature sensors **42**.

[0018] The processing circuitry **26** maybe be further configured to input the parameters **30A**, **30B** of the laser and the substrate to the thermodynamic stage portion **32B** of the model **32**, so that the thermodynamic effects between pulses of the laser beam **16** can be accurately accounted for. Here, the parameters **30B** of the substrate **12** may include one or more of initial geometry, a composition of a material of the substrate, thermodynamic properties of the material, mechanical properties of the material, phase transformation properties of the material, and/or glass transition properties of the material, which may increase the accuracy of the model **32** by accounting for a variety of affects. Preferably, the parameters **30B** of the substrate **12** include temperature-dependent properties of the material of the substrate **12**, to increase the accuracy of the model calculations in consideration of the wide range of temperatures that will be experienced during and after ablation. Generally, the thermodynamic stage portion **32B** of the model **32** utilizes density, thermal conductivity, and specific heat, among other parameters of the substrate **12**. In some implementations, the thermodynamic stage portion **32B** may also perform temperature-induced stress calculations, which utilize the linear expansion coefficient, Poisson's ratio, and Young's modulus of the substrate **12** as well.

[0019] Next, the processing circuitry **26** may be configured to iteratively switch between the ablation stage portion **32A** and the thermodynamic stage portion **32B** through a final (n) segment of laser operation to output a final predicted temperature value **44** of the substrate after n iterations of switching through both portions **32A**, **32B**. For example, if the number of laser pulses calculated per ablation stage is one, and the thermodynamic stage portion **32B** calculates the heat transfer between or after pulses, then for a laser operation of x pulses, $n=x$, or the number of total segments of laser operation= $2x$. By breaking the modeling down to small segments and iteratively switching between the two portions **32A**, **32B**, the model **32** is a comprehensive model that is able to more accurately calculate the changes occurring at each stage based on the changes just calculated in the prior stage, even though each stage is modeling different mechanisms.

[0020] The final predicted temperature value **44** and intermediate values calculated throughout the modeling process may be used in a variety of ways. For example, the processing circuitry **26** may be further configured to output a maximum temperature **46** predicted to be experienced by the substrate **12**, which may be the final predicted temperature value **44**, or may be a prior stored temperature value before heat loss reduced the temperature to the final predicted temperature value **44**. Similarly, the processing circuitry **26** may be further configured to output a predicted material removal rate **48** of material from the substrate **12**. The removal rate may be, for example, a rate at which the material is ablated over time, which may be measured as depth of material removed over time. The removal rate **48** may be incorporated into further calculations using additional logic **50** or another computing device **24** to provide recommendations to the user, control an actual laser operation, or scale up or otherwise alter the laser operation with other parameters. Any of the simulation data in the output **34**, including intermediate values, may be collected and stored to build a database of parameters that may be used to build a “digital twin” of actual devices and components. Such a digital twin could be used, for example, to avoid parameters that are predicted to cause problems by the model **32** in future design considerations.

[0021] The computing system **22** may be configured to generate other items as the output **34** of the model **32** using the additional logic **50**. For example, the processing circuitry **26** may be further configured to output a predicted structural effect **52** on the substrate based on a comparison between the maximum temperature **46** and the parameters **30B** of the substrate **12**. For example, one of the parameters **30B** may be indicative of a phase change, other structural change, or failure point of the material of the substrate **12**, such as a melt zone. By determining that the maximum temperature **46** has met or exceeded this parameter during the simulation, optionally for a specified amount of time, the processing circuitry **26** may be able to predict that the substrate **12** has experienced the predicted structural effect **52** such as melting, warping, weakening, cracking, fatigue acceleration, etc.

[0022] Based on at least the predicted structural effect **52**, the processing circuitry **26** may be configured to determine whether either the laser system **10** or the material has passed or failed the simulated test, where a predetermined negative structural effect is a failure. Thus, while a single test has been described above using one laser system **10** and one substrate **12**, the processing circuitry **26** may be configured to retrieve respective parameters **30A** of the laser and parameters **30B** of a plurality of substrates **12** to be separately subjected to operation of the laser, input the respective parameters **30A**, **30B** to the ablation stage portion **32A** to output a respective updated geometry **36** of each substrate **12** and a respective updated temperature value **38** of each substrate **12**. Similarly, the processing circuitry **26** may be configured to input the respective updated geometry **36** and the respective updated temperature value **38** to the thermodynamic stage portion **32B** to output a respective updated temperature value **40** of each substrate **12**, and as before, iteratively switch between the ablation stage portion **32A** and the thermodynamic stage portion **32B** through the final segment of laser operation to output a respective final predicted temperature value **44** of each substrate **12**.

[0023] Thus, the processing circuitry may be configured to identify the respective maximum

temperature **46** predicted to be experienced by each substrate **12** during the entire laser operation, compare the respective maximum temperature **46** to the respective parameters **30B** of each substrate **12**, and based on the comparison, output a prediction **54** of whether each substrate **12** of the plurality of substrates **12** is to be damaged by the laser operation. In this way, a variety of substrates **12** can be tested under simulation with the same laser system **10** and the user can be informed whether any given substrate **12** would be successful or fail when subjected to operation by the given laser system **10**. Accordingly, the user can make a more informed decision when developing new systems, components, and materials, and then actual testing can be reserved for validating the output **34** of the model **32**, interpolating, or directed testing according to a recommendation **56** of the model **32**, etc. Testing a plurality of substrate **12** coupons under circumstances that would typically use 350 coupons for full qualification and approval may with use of the model **32** reduce actual testing to validation with only 15-30 coupons, which presents significant savings in terms of cost, time, labor, and use and wear of laser systems **10**. Furthermore, rather than a variety of substrates **12**, a plurality of laser systems **10** with respective parameters **30A** may be similarly modeled instead, so that a new laser system **10** can be investigated and a corresponding recommendation **56** can be made. In addition, the output **34** may be output to a client device, an associated display device, internal or external storage, directly to a production system for controlling an actual operation, etc. Thus, the output **34** may be used manually by the user at the time of output or at a later date, or the output **34** may be used automatically by the computing system **22** without further user input.

[0024] FIG. **3** is a flowchart of a method **300** for predicting substrate temperatures during simulated laser operation. At **302**, the method **300** may include retrieving parameters of a laser and parameters of a substrate to be subjected to operation of the laser. At **304**, the method **300** may include inputting the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation which outputs, at **306**, an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse, and at **308**, an updated temperature value of the substrate after being subjected to the at least one laser pulse. Optionally, at **310**, the method **300** may include inputting the parameters of the laser and the substrate to a thermodynamic stage portion of the model. At **312**, the method **300** may include inputting the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air. Accordingly, based on a variety of parameters, each portion of the model may be able to account for different factors that may affect the domain of the other portion of the model. Thus, at **314**, the method **300** may include iteratively switching between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a final predicted temperature value of the substrate, thereby accounting for the effects of each portion of the model in small increments when proceeding to the other portion.

[0025] As mentioned above, the at least one laser pulse may one single laser pulse, so that the ablation stage portion can account for the ablation of a single crater and then the thermodynamic stage portion can account for the heat transfer occurring between ablations. Alternatively, multiple laser pulses may be grouped together. In some cases, the substrate may have a top layer of paint and a bottom layer of metal alloy, and the ablated material may include the paint. In others, the laser operation may be surface preparation of the substrate prior to painting. Additional use cases are also possible. Optionally, at **316**, the method **300** may include outputting a maximum temperature predicted to be experienced by the substrate. The maximum temperature can be used in many different ways, such as monitoring physical changes to the substrate and predicting failure of the laser operation. For example, at **318**, the method **300** may include outputting a predicted structural effect on the substrate based on a comparison between the maximum temperature and the parameters of the substrate. The predicted structural effect may include, for example, melting,

warping, weakening, cracking, or fatigue acceleration. At **320**, the method **300** may include outputting a predicted material removal rate of material from the substrate. The removal rate may be a useful metric by which applicability and scalability of the simulated laser operation may be considered for putting to practical use. The method **300** may result in further predictions and outputs, such as recommendation of materials or laser settings, and so on.

[0026] In some embodiments, the methods and processes described herein may be tied to a computing system of one or more computing devices. In particular, such methods and processes may be implemented as a computer-application program or service, an application-programming interface (API), a library, and/or other computer-program product. Examples of such programs may include, but are not limited to, COMSOL and MATLAB.

[0027] FIG. **4** schematically shows a non-limiting embodiment of a computing system **400** that can enact one or more of the methods and processes described above. Computing system **400** is shown in simplified form. Computing system **400** may embody the computing system **1** described above and illustrated in FIG. **1**. Components of computing system **400** may be included in one or more personal computers, server computers, tablet computers, home-entertainment computers, network computing devices, video game devices, mobile computing devices, mobile communication devices (e.g., smartphone), and/or other computing devices, and wearable computing devices such as smart wristwatches and head mounted augmented reality devices.

[0028] Computing system **400** includes a logic processor **402** volatile memory **404**, and a non-volatile storage device **406**. Computing system **400** may optionally include a display subsystem **408**, input subsystem **410**, communication subsystem **412**, and/or other components not shown in FIG. **4**.

[0029] Logic processor **402** includes one or more physical devices configured to execute instructions. For example, the logic processor may be configured to execute instructions that are part of one or more applications, programs, routines, libraries, objects, components, data structures, or other logical constructs. Such instructions may be implemented to perform a task, implement a data type, transform the state of one or more components, achieve a technical effect, or otherwise arrive at a desired result.

[0030] The logic processor may include one or more physical processors configured to execute software instructions. Additionally or alternatively, the logic processor may include one or more hardware logic circuits or firmware devices configured to execute hardware-implemented logic or firmware instructions. Processors of the logic processor **402** may be single-core or multi-core, and the instructions executed thereon may be configured for sequential, parallel, and/or distributed processing. Individual components of the logic processor optionally may be distributed among two or more separate devices, which may be remotely located and/or configured for coordinated processing. Aspects of the logic processor may be virtualized and executed by remotely accessible, networked computing devices configured in a cloud-computing configuration. In such a case, these virtualized aspects are run on different physical logic processors of various different machines, it will be understood.

[0031] Non-volatile storage device **406** includes one or more physical devices configured to hold instructions executable by the logic processors to implement the methods and processes described herein. When such methods and processes are implemented, the state of non-volatile storage device **406** may be transformed—e.g., to hold different data.

[0032] Non-volatile storage device **406** may include physical devices that are removable and/or built in. Non-volatile storage device **406** may include optical memory, semiconductor memory, and/or magnetic memory, or other mass storage device technology. Non-volatile storage device **406** may include nonvolatile, dynamic, static, read/write, read-only, sequential-access, location-addressable, file-addressable, and/or content-addressable devices. It will be appreciated that non-volatile storage device **406** is configured to hold instructions even when power is cut to the non-volatile storage device **406**.

[0033] Volatile memory **404** may include physical devices that include random access memory. Volatile memory **404** is typically utilized by logic processor **402** to temporarily store information during processing of software instructions. It will be appreciated that volatile memory **404** typically does not continue to store instructions when power is cut to the volatile memory **404**.

[0034] Aspects of logic processor **402**, volatile memory **404**, and non-volatile storage device **406** may be integrated together into one or more hardware-logic components. Such hardware-logic components may include field-programmable gate arrays (FPGAs), program- and application-specific integrated circuits (ASICs), program- and application-specific standard products (PSSP/ASSPs), system-on-a-chip (SOC), and complex programmable logic devices (CPLDs), for example.

[0035] The terms “module,” “program,” and “engine” may be used to describe an aspect of computing system **400** typically implemented in software by a processor to perform a particular function using portions of volatile memory, which function involves transformative processing that specially configures the processor to perform the function. Thus, a module, program, or engine may be instantiated via logic processor **402** executing instructions held by non-volatile storage device **406**, using portions of volatile memory **404**. It will be understood that different modules, programs, and/or engines may be instantiated from the same application, service, code block, object, library, routine, API, function, etc. Likewise, the same module, program, and/or engine may be instantiated by different applications, services, code blocks, objects, routines, APIs, functions, etc. The terms “module,” “program,” and “engine” may encompass individual or groups of executable files, data files, libraries, drivers, scripts, database records, etc.

[0036] When included, display subsystem **408** may be used to present a visual representation of data held by non-volatile storage device **406**. The visual representation may take the form of a graphical user interface (GUI). As the herein described methods and processes change the data held by the non-volatile storage device, and thus transform the state of the non-volatile storage device, the state of display subsystem **408** may likewise be transformed to visually represent changes in the underlying data. Display subsystem **408** may include one or more display devices utilizing virtually any type of technology. Such display devices may be combined with logic processor **402**, volatile memory **404**, and/or non-volatile storage device **406** in a shared enclosure, or such display devices may be peripheral display devices.

[0037] When included, input subsystem **410** may comprise or interface with one or more user-input devices such as a keyboard, mouse, touch screen, camera, or microphone.

[0038] When included, communication subsystem **412** may be configured to communicatively couple various computing devices described herein with each other, and with other devices. Communication subsystem **412** may include wired and/or wireless communication devices compatible with one or more different communication protocols. As non-limiting examples, the communication subsystem may be configured for communication via a wired or wireless local- or wide-area network, broadband cellular network, etc. In some embodiments, the communication subsystem may allow computing system **400** to send and/or receive messages to and/or from other devices via a network such as the Internet.

[0039] Further, the disclosure comprises configurations according to the following clauses. One aspect provides a computing system for predicting substrate temperatures during simulated laser operation. The computing system comprises processing circuitry configured to retrieve parameters of a laser and parameters of a substrate to be subjected to operation of the laser, input the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation which outputs an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse and an updated temperature value of the substrate after being subjected to the at least one laser pulse, input the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat

transfer through the substrate and from the substrate to ambient air, and iteratively switch between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a final predicted temperature value of the substrate. In this aspect, additionally or alternatively, the at least one laser pulse is one single laser pulse. In this aspect, additionally or alternatively, the substrate has a top layer of paint and a bottom layer of metal alloy, and the ablated material includes the paint. In this aspect, additionally or alternatively, the laser operation is surface preparation of the substrate prior to painting. In this aspect, additionally or alternatively, the processing circuitry is further configured to input the parameters of the laser and the substrate to the thermodynamic stage portion of the model. In this aspect, additionally or alternatively, the processing circuitry is further configured to output a maximum temperature predicted to be experienced by the substrate. In this aspect, additionally or alternatively, the processing circuitry is further configured to output a predicted structural effect on the substrate based on a comparison between the maximum temperature and the parameters of the substrate. In this aspect, additionally or alternatively, the processing circuitry is further configured to output a predicted material removal rate of material from the substrate. In this aspect, additionally or alternatively, the parameters of the laser include one or more of target ablation depth, frequency, power setting, efficiency, power delivery to a top surface of the substrate, spot diameter, spot area, pulse duration, pulse energy, peak power, spot fluence, irradiance, pulse overlap, line speed, row spacing, spot spacing, and dosage. In this aspect, additionally or alternatively, the parameters of the substrate include one or more of initial geometry, a composition of a material of the substrate, thermodynamic properties of the material, mechanical properties of the material, and phase transformation properties of the material. In this aspect, additionally or alternatively, the parameters of the substrate include temperature-dependent properties of a material of the substrate.

[0040] Another aspect provides a method for predicting substrate temperatures during simulated laser operation. The method comprises retrieving parameters of a laser and parameters of a substrate to be subjected to operation of the laser, inputting the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation which outputs an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse and an updated temperature value of the substrate after being subjected to the at least one laser pulse, inputting the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air, and iteratively switching between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a final predicted temperature value of the substrate. In this aspect, additionally or alternatively, the at least one laser pulse is one single laser pulse. In this aspect, additionally or alternatively, the substrate has a top layer of paint and a bottom layer of metal alloy, and the ablated material includes the paint. In this aspect, additionally or alternatively, the laser operation is surface preparation of the substrate prior to painting. In this aspect, additionally or alternatively, the method further includes inputting the parameters of the laser and the substrate to the thermodynamic stage portion of the model. In this aspect, additionally or alternatively, the method further includes outputting a maximum temperature predicted to be experienced by the substrate. In this aspect, additionally or alternatively, the method further includes outputting a predicted structural effect on the substrate based on a comparison between the maximum temperature and the parameters of the substrate. In this aspect, additionally or alternatively, the method further includes outputting a predicted material removal rate of material from the substrate.

[0041] Another aspect provides a computing system for predicting substrate temperatures during simulated laser operation. The computing system comprises processing circuitry configured to retrieve respective parameters of a laser and parameters of a plurality of substrates to be separately subjected to operation of the laser, input the respective parameters of the laser and the substrate to

an ablation stage portion of a model to calculate a first segment of laser operation which outputs a respective updated geometry of each substrate after a predicted ablation of material from the substrate via at least one laser pulse and a respective updated temperature value of each substrate after being subjected to the at least one laser pulse, input the respective updated geometry and the respective updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs a respective updated temperature value of each substrate after heat transfer through the substrate and from the substrate to ambient air, iteratively switch between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a respective final predicted temperature value of each substrate, identify a respective maximum temperature predicted to be experienced by each substrate during the entire laser operation, compare the respective maximum temperature to the respective parameters of each substrate, and based on the comparison, output a prediction of whether each substrate of the plurality of substrates is to be damaged by the laser operation. In this aspect, additionally or alternatively, the updated geometries are each three dimensional.

[0042] “And/or” as used herein is defined as the inclusive or V, as specified by the following truth table:

TABLE-US-00001 A B A V B True True True True False True False True True False False False

[0043] It will be understood that the configurations and/or approaches described herein are exemplary in nature, and that these specific embodiments or examples are not to be considered in a limiting sense, because numerous variations are possible. The specific routines or methods described herein may represent one or more of any number of processing strategies. As such, various acts illustrated and/or described may be performed in the sequence illustrated and/or described, in other sequences, in parallel, or omitted. Likewise, the order of the above-described processes may be changed.

[0044] The subject matter of the present disclosure includes all novel and non-obvious combinations and sub-combinations of the various processes, systems and configurations, and other features, functions, acts, and/or properties disclosed herein, as well as any and all equivalents thereof.

Claims

1. A computing system for predicting substrate temperatures during simulated laser operation, the computing system comprising: processing circuitry configured to: retrieve parameters of a laser and parameters of a substrate to be subjected to operation of the laser; input the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation which outputs: an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse; and an updated temperature value of the substrate after being subjected to the at least one laser pulse; input the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air; and iteratively switch between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a final predicted temperature value of the substrate.
2. The computing system of claim 1, wherein the at least one laser pulse is one single laser pulse.
3. The computing system of claim 1, wherein the substrate has a top layer of paint and a bottom layer of metal alloy, and the ablated material includes the paint.
4. The computing system of claim 1, wherein the laser operation is surface preparation of the substrate prior to painting.
5. The computing system of claim 1, wherein the processing circuitry is further configured to input

the parameters of the laser and the substrate to the thermodynamic stage portion of the model.

6. The computing system of claim 1, wherein the processing circuitry is further configured to output a maximum temperature predicted to be experienced by the substrate.

7. The computing system of claim 1, wherein the processing circuitry is further configured to output a predicted structural effect on the substrate based on a comparison between the maximum temperature and the parameters of the substrate.

8. The computing system of claim 1, wherein the processing circuitry is further configured to output a predicted material removal rate of material from the substrate.

9. The computing system of claim 1, wherein the parameters of the laser include one or more of target ablation depth, frequency, power setting, efficiency, power delivery to a top surface of the substrate, spot diameter, spot area, pulse duration, pulse energy, peak power, spot fluence, irradiance, pulse overlap, line speed, row spacing, spot spacing, and dosage.

10. The computing system of claim 1, wherein the parameters of the substrate include one or more of initial geometry, a composition of a material of the substrate, thermodynamic properties of the material, mechanical properties of the material, and phase transformation properties of the material.

11. The computing system of claim 1, wherein the parameters of the substrate include temperature-dependent properties of a material of the substrate.

12. A method for predicting substrate temperatures during simulated laser operation, the method comprising: retrieving parameters of a laser and parameters of a substrate to be subjected to operation of the laser; inputting the parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation which outputs: an updated geometry of the substrate after a predicted ablation of material from the substrate via at least one laser pulse; and an updated temperature value of the substrate after being subjected to the at least one laser pulse; inputting the updated geometry and the updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs an updated temperature value of the substrate after heat transfer through the substrate and from the substrate to ambient air; and iteratively switching between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a final predicted temperature value of the substrate.

13. The method of claim 12, wherein the at least one laser pulse is one single laser pulse.

14. The method of claim 12, wherein the substrate has a top layer of paint and a bottom layer of metal alloy, and the ablated material includes the paint.

15. The method of claim 12, wherein the laser operation is surface preparation of the substrate prior to painting.

16. The method of claim 12, further comprising inputting the parameters of the laser and the substrate to the thermodynamic stage portion of the model.

17. The method of claim 12, further comprising outputting a maximum temperature predicted to be experienced by the substrate.

18. The method of claim 12, further comprising outputting a predicted structural effect on the substrate based on a comparison between the maximum temperature and the parameters of the substrate.

19. The method of claim 12, further comprising outputting a predicted material removal rate of material from the substrate.

20. A computing system for predicting substrate temperatures during simulated laser operation, the computing system comprising: processing circuitry configured to: retrieve respective parameters of a laser and parameters of a plurality of substrates to be separately subjected to operation of the laser; input the respective parameters of the laser and the substrate to an ablation stage portion of a model to calculate a first segment of laser operation which outputs: a respective updated geometry of each substrate after a predicted ablation of material from the substrate via at least one laser pulse; and a respective updated temperature value of each substrate after being subjected to the at

least one laser pulse; input the respective updated geometry and the respective updated temperature value to a thermodynamic stage portion of the model to calculate a second segment of laser operation which outputs a respective updated temperature value of each substrate after heat transfer through the substrate and from the substrate to ambient air; iteratively switch between the ablation stage portion and the thermodynamic stage portion through a final segment of laser operation to output a respective final predicted temperature value of each substrate; identify a respective maximum temperature predicted to be experienced by each substrate during the entire laser operation; compare the respective maximum temperature to the respective parameters of each substrate; and based on the comparison, output a prediction of whether each substrate of the plurality of substrates is to be damaged by the laser operation.

21. The computing system of claim 20, wherein the updated geometries are each three dimensional.
