

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408790
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Eisenberg; Toby

French coffee press

Abstract

An improved French coffee press apparatus, system, and method that utilizes a locking ring to engage with a locking base that can be removed from the carafe, along with any coffee grounds. The locking ring is connected to the pressing rod, which also includes a filter system above the locking ring. The pressing rod fits through an opening in the carafe lid, and the carafe lid secures the liquid inside the carafe. The combination of the filtering system assists in the filtering and capture of any coffee grounds into the locking base for cleaning, and the locking ring assists in the removal of the locking base.

Inventors:	Eisenberg; Toby (Dallas, TX)
Applicant:	Eisenberg; Toby (Dallas, TX)
Family ID:	61971119
Appl. No.:	18/375801
Filed:	October 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240090698 A1	Mar. 21, 2024

Related U.S. Application Data

continuation parent-doc US 17081951 20201027 US 11771257 child-doc US 18375801
continuation parent-doc US 15790964 20171023 US 10820739 20201103 child-doc US 17081951
us-provisional-application US 62412130 20161024

Publication Classification

Int. Cl.: A47J31/20 (20060101); A47J31/38 (20060101); A47J31/44 (20060101)

U.S. Cl.:

CPC A47J31/20 (20130101); A47J31/38 (20130101); A47J31/44 (20130101)

Field of Classification Search

CPC: A47J (31/38); A47J (31/20); A47J (31/44)

USPC: 99/297

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
482299	12/1891	Comstock	99/317	A47J 31/20
512675	12/1893	Appleberg	99/299	A47J 31/02
882183	12/1907	Wells	99/319	A47J 31/20
1346485	12/1919	Manuel	99/287	A47J 31/20
2053021	12/1935	Cassol	99/287	A47J 31/20
2078561	12/1936	Cavalletti	99/302R	A47J 31/0576
2086463	12/1936	Bram	108/65	A47B 3/0917
2109363	12/1937	William	99/310	A47J 31/20
2211486	12/1939	Zoia	99/287	A47J 31/20
2562433	12/1950	Moore	99/300	A47J 31/20
2900896	12/1958	Bondanini	99/287	A47G 19/14
3020823	12/1961	Ferdinando	426/433	A47J 31/20
3098425	12/1962	Falla	99/317	A47J 31/053
3113533	12/1962	Snow	108/134	A47B 5/04
3158084	12/1963	Cohn	99/297	A47J 31/20
3279351	12/1965	Cohn	99/297	A47J 31/20
3307474	12/1966	Kasher	99/298	A47J 31/20
3413908	12/1967	Nadelson	99/297	A47J 31/20
3657993	12/1971	Close	99/297	A47J 31/20
3927608	12/1974	Doyel	99/298	A47J 31/20
3935318	12/1975	Mihailide	426/282	B65D 85/812
4365544	12/1981	Howitt	D7/317	A47J 31/20
4381696	12/1982	Koral	219/689	A47J 31/106
4650583	12/1986	Bondanini	210/474	A47J 31/20
4737036	12/1987	Offermann	366/256	A47J 43/1081
4856843	12/1988	Elliott	296/26.05	B60P 3/42
4927107	12/1989	Mateo Maria	248/240.4	A47B 5/04
4962615	12/1989	Birdling	49/383	E05D 1/02
4998484	12/1990	Groetzinger	108/115	A47B 5/04
5461968	12/1994	Portman	99/287	A47J 31/20
5478586	12/1994	Connor	426/433	A47J 31/20
5544592	12/1995	Leezer	108/123	A47B 5/06
5570623	12/1995	Lin	99/285	A47J 41/0077
5588697	12/1995	Yoshida	297/188.17	A47B 13/16

5618570	12/1996	Banks	99/287	A47J 31/20
5635233	12/1996	Levinson	426/433	A47J 36/027
5713404	12/1997	Ladewig	108/42	B25H 1/12
5770074	12/1997	Pugh	210/477	A47J 31/20
5780087	12/1997	Brady	426/570	A23C 9/1524
5809867	12/1997	Turner	99/287	A47J 31/20
5887510	12/1998	Porter	99/287	A47J 31/20
5911810	12/1998	Kawabata	99/289P	A47J 31/34
5932098	12/1998	Ross	210/473	A47J 31/605
5939122	12/1998	Brady	N/A	N/A
5943946	12/1998	Chen	99/323	A47J 31/20
5952028	12/1998	Lesser	426/77	A47J 31/0636
5979299	12/1998	Hornsby	426/433	A47J 31/20
6039416	12/1999	Lambert	D6/684	A47B 5/06
6079316	12/1999	Barden	99/287	A47J 31/20
6161486	12/1999	Boots	297/14	B25H 1/04
6231909	12/2000	Levinson	426/585	A23L 15/00
6240833	12/2000	Sham	99/287	A47J 31/20
6324966	12/2000	Joergensen	99/287	A47J 31/20
6334400	12/2001	Nien	108/115	A47B 3/087
6343834	12/2001	Wurmlinger	297/14	A47C 9/06
6374726	12/2001	Melton	99/275	A47G 19/16
6422133	12/2001	Brady	99/287	A47J 31/20
6705235	12/2003	Gerutto	108/47	A47B 5/00
6725763	12/2003	Cai	99/287	A47J 31/4407
6797160	12/2003	Huang	99/289P	A47J 31/20
6797304	12/2003	McGonagle	426/433	A47J 31/20
7040218	12/2005	Biolchini, Jr.	99/287	A47J 31/20
7093531	12/2005	Tardif	99/287	A47J 31/20
7194751	12/2006	Fujii	N/A	G11B 23/40
7194951	12/2006	Porter	99/287	A47J 31/44
7213507	12/2006	Glucksman	99/287	A47J 31/20
7337705	12/2007	Catena	99/287	A47J 31/20
7389720	12/2007	Haverstock	99/287	A47J 31/20
7461587	12/2007	Guerrero	210/474	A47J 31/02
7475644	12/2008	Strong	108/132	F16B 12/24
7578231	12/2008	Liu	99/287	A47J 31/20
7634969	12/2008	Neunzert	108/132	A47B 3/00
7745759	12/2009	Long	219/490	A47J 31/20
7849784	12/2009	Adler	99/287	A47J 31/02
8051766	12/2010	Yu	99/287	A47J 31/20
8156875	12/2011	Neunzert	108/132	F16B 12/24
8267017	12/2011	Michael	248/240.4	A47B 5/04
8313644	12/2011	Harris	210/205	C02F 1/002
8375846	12/2012	Baccetti	99/297	A47J 31/20
8402888	12/2012	Baccetti	99/287	A47J 31/20
8887623	12/2013	Giordano	N/A	N/A
9392900	12/2015	McLean	N/A	A47J 31/38
9480279	12/2015	Fogelin	N/A	A47J 31/06
9492027	12/2015	Morse	N/A	A47J 31/20

9526369	12/2015	Velasquez	N/A	A47J 31/38
10251508	12/2018	Pan	N/A	N/A
10264911	12/2018	McLean	N/A	A47J 31/18
10369258	12/2018	Hensler	N/A	A61M 1/60
10398255	12/2018	Constantine	N/A	A23C 3/037
2003/0070979	12/2002	Huang	99/279	A47J 31/20
2004/0094076	12/2003	Jin	108/132	A47B 3/087
2004/0154471	12/2003	Tardif	99/279	A47J 31/20
2005/0005826	12/2004	Strong	108/132	A47B 13/003
2005/0120803	12/2004	Sokol	73/801	G01N 29/2418
2005/0139091	12/2004	Haverstock	99/495	A47J 31/20
2005/0199129	12/2004	Glucksman et al.	N/A	N/A
2005/0241551	12/2004	Neunzert	108/132	F16B 12/24
2006/0021524	12/2005	Liu	100/116	A47J 31/20
2006/0124628	12/2005	Long	99/283	A47J 31/20
2007/0028779	12/2006	Pigliacampo	99/297	A47J 31/20
2007/0151461	12/2006	Edmark	99/279	A47J 31/20
2007/0235433	12/2006	Osicki	219/125.1	B23K 37/0461
2007/0240580	12/2006	Lusareta	99/279	B65D 47/06
2008/0245237	12/2007	Haverstock	99/298	A47J 31/20
2009/0020018	12/2008	Melzer	99/288	A47J 31/20
2009/0044460	12/2008	Medley	52/741.1	E04B 1/3444
2009/0263550	12/2008	Navarini et al.	N/A	N/A
2010/0005979	12/2009	Baccetti	99/287	A47J 31/38
2010/0192780	12/2009	Bodum	N/A	N/A
2010/0319549	12/2009	Kelty	99/297	A47J 31/20
2011/0056385	12/2010	McLean	99/297	A47J 31/20
2011/0088561	12/2010	Bodum	99/297	A47J 31/20
2011/0168644	12/2010	Harris et al.	N/A	N/A
2011/0239549	12/2010	Medley	52/79.5	E04B 1/3444
2012/0042904	12/2011	Galbis	N/A	N/A
2013/0233177	12/2012	Lambert	99/295	A47J 31/407
2013/0284030	12/2012	Katz et al.	N/A	N/A
2014/0072684	12/2013	Madden	426/431	A47J 31/005
2015/0059592	12/2014	Richardson	N/A	N/A
2015/0196158	12/2014	Velasquez	99/297	A47J 31/38
2015/0272378	12/2014	Sands	N/A	N/A
2016/0037960	12/2015	McLean et al.	N/A	N/A
2016/0058235	12/2015	Blair	99/297	A47J 31/4403
2016/0135639	12/2015	Sacks	N/A	N/A
2016/0166103	12/2015	Morse	99/297	A47J 31/20
2017/0295987	12/2016	Habram	N/A	N/A
2017/0325617	12/2016	Dujmich	N/A	A47J 31/20
2017/0360240	12/2016	Morse	N/A	A47J 31/20
2018/0064284	12/2017	Ryan	N/A	N/A
2018/0110357	12/2017	Eisenberg	N/A	N/A
2018/0213967	12/2017	Liu	N/A	A47J 31/20
2018/0289200	12/2017	Bodum	N/A	A47J 31/20
2018/0303269	12/2017	Yakos	N/A	A47J 31/20
2019/0082880	12/2018	Kaufman	N/A	A47J 31/20

2019/0223649	12/2018	Yakos	N/A	N/A
2019/0254463	12/2018	McLean	N/A	B01D 11/0253
2019/0290048	12/2018	Albanese	N/A	N/A
2019/0365136	12/2018	Farkas	N/A	A47J 31/20
2019/0387916	12/2018	Tempelis	N/A	A47J 31/20
2020/0015619	12/2019	Chimezie	N/A	N/A
2020/0113369	12/2019	Bardot et al.	N/A	N/A
2021/0038015	12/2020	Eisenberg	N/A	N/A
2021/0085121	12/2020	Liang et al.	N/A	N/A

Primary Examiner: Chou; Jimmy

Attorney, Agent or Firm: Carstens, Allen & Gourley, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of U.S. Non-Provisional application Ser. No. 17/081,951, filed on Oct. 27, 2020, which is a continuation application of U.S. Non-Provisional application Ser. No. 15/790,964 filed Oct. 23, 2017, which claims the benefit of and priority to U.S. Provisional Application No. 62/412,130 filed Oct. 24, 2016, the disclosure of which is incorporated herein by reference.

FIELD OF THE DISCLOSURE

(1) The present invention generally relates to the field of a coffee or brewed drink maker. Specifically in its preferred embodiments, the present invention discloses a French coffee press with a removable base.

BACKGROUND

(2) The topic of coffee making is often thought of at the start of the day as a person gets ready with a cup of their favorite blend. There is also a variety of manners in which to make a cup of coffee. The one most quickly thought of by many people would be a trip to Starbucks® or a from a single cup coffee maker like a Keurig™. However, for those who like the experience or the science of coffee making they will often use alternative methods, such as drip brewing or steeping. One method of steeping includes the French press. In a French press, a piston with an attached filter is pushed through the steeping liquid to push the coffee grounds or other brewing material to the bottom of the cylinder in which it was brewed.

(3) One of the major deficiencies of French coffee presses today is the difficulty in cleaning. The traditional French coffee press is a tall, skinny cylinder in which the coffee grounds are pressed down and compacted into the bottom the cylinder. While brushes and water jets can assist in the cleaning process it is still difficult to remove the coffee grounds, in particular if a person is trying to avoid putting them down a sink, disposal, or dishwasher. Because of the difficulties in cleaning, one of the objectives of the present invention is to provide an improved French coffee press that is easily cleaned.

BRIEF SUMMARY

(4) The present invention as embodied in an apparatus and method permits a user to brew coffee utilizing a French press, and steeping without the difficulties in cleaning that are commonplace with traditional French coffee presses. Thus, the present invention comprises a carafe, a lid for the carafe, a pressing rod, a filter system, and includes a locking base and a locking ring that is attached to the pressing rod. The locking ring and locking base provide the user with the ability to remove the coffee grounds from the carafe, without major difficulty.

(5) The locking ring and locking base are secured together in a manner that allows the locking base to be removed from the carafe base. Once it is removed, then the locking base and locking ring can easily be separated from each other.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A provides a perspective view of a Prior Art French press coffee maker.
- (2) FIG. 1B provides a perspective view of a Prior Art French press filter system.
- (3) FIG. 2A illustrates a perspective view of an improved French press coffee maker.
- (4) FIG. 2B illustrates a perspective view of an improved French press filter system.
- (5) FIG. 3A shows a perspective view of the improved French press filter system in the filtering stage.
- (6) FIG. 3B shows a perspective view of the improved French press filter system in the compression stage.
- (7) FIG. 3C shows a perspective view of the improved French press filter system in the removal stage.
- (8) FIG. 4A shows a side view of the improved French press coffee maker in use in the filtering stage.
- (9) FIG. 4B illustrates the beginning of the compression stage of the improved French press coffee maker.
- (10) FIG. 5A illustrates the securing stage of the improved French press coffee maker.
- (11) FIG. 5B shows a perspective view of the locking base being removed from the carafe of the improved French press coffee maker.
- (12) FIG. 6A shows a top view of a first preferred embodiment of the locking base of the improved French press coffee maker.
- (13) FIG. 6B shows a top view of a second preferred embodiment of the locking base of the improved French press coffee maker.
- (14) FIG. 6C shows a top view of a third preferred embodiment of the locking base of the improved French press coffee maker.
- (15) FIG. 7A illustrates a side view of a first preferred embodiment of the locking base, and the locking base lip(s).
- (16) FIG. 7B illustrates a side view of a second preferred embodiment of the locking base, and the locking base lip(s).
- (17) FIG. 8A illustrates a side view of a first preferred embodiment of the locking ring, and the locking ring lip(s).
- (18) FIG. 8B illustrates a side view of a second preferred embodiment of the locking ring, and the locking ring lip(s).
- (19) FIG. 9A shows the top view of a first preferred embodiment of the locking ring, and the locking ring lip(s).
- (20) FIG. 9B shows the top view of a second preferred embodiment of the locking ring, and the locking ring lip(s).
- (21) FIG. 9C shows the top view of a third preferred embodiment of the locking ring, and the locking ring lip(s).
- (22) FIG. 10 illustrates a perspective view of a first alternative embodiment of the improved French press coffee maker.
- (23) FIG. 11 shows a side view of the locking base with removable grounds container.
- (24) FIG. 12A shows a perspective view of an alternative embodiment of the locking ring lip(s) and the locking base lip(s) in the filtering stage.

(25) FIG. 12B illustrates a perspective view of an alternative embodiment of the locking ring lip(s) and the locking base lip(s) in the removal stage.

DETAILED DESCRIPTION

(26) In FIG. 1A a traditional French press coffee maker **100A** is presented. For a coffee drinker who is a purest a French press is one of the best ways to brew coffee. The carafe **2** is filled with your most delicious blend of ground coffee beans, the hot water, and the grounds are now ready to be filtered away by the filter system **12** after the desired brewing time has been completed. The filter system **12** is connected to the pressing rod **14** through known methods of connection such as one-piece manufacturing, press fit, or threaded connector. In some designs, there is also the pressing rod bulb **18** that can be connected to the pressing rod **14** by similar methods as the filter system **12**. The carafe **2** and the carafe lid **16** help to prevent heat from escaping or the freshly brewed coffee from spilling from the inevitable bump. In addition, the carafe lid **16** provides stability to the press rod **14** during operation of the French press coffee maker.

(27) The components **100B** of the French press filter system **12** are seen in FIG. 1B. The French press filter system **12** is comprised of the upper retainer ring **22** that typically has a spring or other mechanism around the outer edge of the upper retainer ring **22** to assist in pressing the mesh filter **24** to the inner wall of the carafe **2**. This pressing of the mesh filter **24** to the inner wall allows there to be some amount of pressure on the mesh filter **24**, and the inner wall of the carafe **2**, in order to prevent the coffee grounds or other brewing material from slipping around the mesh filter and returning to the filtered liquid. In addition, both the upper retainer ring **22** and the lower retainer ring **26** are an open design (holes or spokes) and not completely solid in order to allow the coffee or other liquid to flow through the mesh filter **24**. Neither the upper retaining ring **22** nor the lower retaining ring **26** perform any filtering. The mesh filter **24** is placed between the upper retaining ring **22** and the lower retaining ring **26** to provide it support as it is pushed through the brewing coffee in order to filter the coffee grounds from the liquid brewed coffee.

(28) In FIG. 2A, the improved French coffee press **200A** can be seen in a perspective view and in a partially pressed state. Starting from the outside, the carafe **202** can be made of any material capable of handling hot or cold liquids, such as glass, or stainless steel. Inside and fit to the bottom of the carafe **202** is a locking base **204** designed to capture brewing materials (not shown) at the end of the brewing process and assist in removing them from the carafe **202**. The locking base **204** is made of a heat tolerant material that allows the locking base **204** to be semi-rigid. The locking base **204** is rigid except for the locking base lip(s) **206**. The locking base lip(s) **206** are flexible enough to allow a locking ring lip(s) **210** to pass by and secure a locking ring **208** within the locking base **204** and the locking base lip(s) **206** for removal of the locking base **204** from the carafe **202**.

(29) The locking ring lip(s) **210** is the outer edge of the locking ring **208**, which is made of a material that provides rigid strength and allows the locking ring lip(s) **210** to be flexible. In addition to the locking ring **208**, there is also a filter system **212** in a preferred embodiment. While typically constructed of metal, the filter system **212** can also be constructed of plastics, glass, or other materials. The locking ring **208** and the filter system **212** in a preferred embodiment will be in close relation with each other, allowing the filter system **212** to filter brewing materials (not shown) and assist in pushing them into the locking base **204** at the end of the brewing process. When the locking ring **208** and locking ring lip(s) **210** engage with the locking base **204** and locking base lip(s) **206**, a secure latching occurs allowing a user to remove the locking base **204** and captured brewing materials (not shown) from the carafe **202** easily. The locking ring **208** and the locking ring lip(s) **210** can be made of the same or a similar material as the locking base **204** and the locking base lip(s) **206**. The bottom or a portion of the sides of the locking base **204** can be made of a solid or fine mesh material that would allow liquid to pass but will not allow any brewing material to leave the locking base **204**. The mesh or solid material could make up a portion or the entire bottom or wall of the locking base **204**. The material of the locking ring **208** and the locking

base **204** also allow the locking ring **208** to be removably attached to the locking base **204**.

(30) The filter system **212** and the locking ring **208** are attached to a pressing rod **214** via a threaded connection or a press fit connection. In one embodiment, the filter system **212** would be attached to a threaded portion of the pressing rod **214**, and adjacent to that threaded portion would be a second threaded portion of smaller diameter for the locking ring **208** to attach to. However, in alternative embodiments the locking ring **208** could be made of one piece manufacture with the filtering system **212**, or be connected to the pressing rod **214** through other methods of connection.

(31) In FIG. **2B** the improved French press filter system **200B** components could be retrofitted to any traditional French press coffee maker along with other pieces of the improved French press **200A**. One embodiment of the improved French press filter system **200B** is comprised of the upper retainer ring **222**, the mesh filter **224**, the lower retaining ring **226**, and the locking ring **208**. It is noted that there could be a plurality of upper retainer rings, a plurality of mesh filters, and a plurality of lower retaining rings in the improved French press filter system **200B**. The upper retainer ring **222** typically has a spring or other mechanism around the outer edge of the upper retainer ring **222** to assist in pressing the mesh filter **224** to the inner wall of the carafe **202**. This pressing of the mesh filter **224** to the inner wall allows there to be some amount of pressure on the mesh filter **224**, and the inner wall of the carafe **202**, in order to prevent the coffee grounds or other brewing material from slipping around the mesh filter and returning to the filtered liquid. The mesh filter **224** can be comprised of a single or multiple layers of filter material, such as wire mesh or replaceable organic material to provide the majority of the filtering, though other components can aid even if not designed to aid in the filtering process. The mesh filter **224** is placed between the upper retaining ring **222** and the lower retaining ring **226** to provide it support as it is pushed through the brewing coffee in order to filter the coffee grounds from the liquid brewed coffee. Both the upper retainer ring **222** and the lower retainer ring **226** are an open design (holes or spokes) and not completely solid in order to allow the coffee or other liquid to flow through the mesh filter **224**. Neither the upper retaining ring **222** nor the lower retaining ring **226** are designed perform any filtering. Likewise, the locking ring **208** can be an open design (spokes) and not completely solid in order to allow the coffee or other liquid to flow unimpeded so that only the mesh filter **224** performs any filtering. In addition, the locking ring **208** can be connected to or manufactured together with the lower retaining ring **226** to form a replaceable piece for traditional French press filter systems. All of these components are connected to the pressing rod **214** through a form of connection such as a threading, press fit, or manufactured as one piece.

(32) Returning to FIG. **2A**, the pressing rod **214** is used to press the filter system **212** and locking ring **208** in tandem through the liquid (not shown) being brewed to remove the brewing materials (not shown) from the liquid. The pressing rod **214** in a preferred embodiment is constructed of metal, but in alternative embodiments, can also be constructed of plastic, glass, or other hard material that is capable of withstanding the hot or cold liquid temperatures and the force required to securely mate the locking ring **208** and the locking base **204**. The pressing rod **214** passes through the carafe lid **216** at the carafe lid opening **217**. The carafe lid **216** is mated with the carafe **202**, through a threaded or press fit connection in preferred embodiments, additionally other methods of securing a liquid within an enclosed volume could also be used. In some embodiments, the carafe **202** or the carafe lid **216** may also have an opening to allow the filtered liquid to be poured from the carafe **202** or the carafe **202** may have a pour spout. The carafe lid **216** can be made of the same material as the carafe **202** or a different material. In order to allow the carafe lid **216** to be removed from the pressing rod **214**, there is the securing bulb **218**, however in other embodiments the securing bulb **218** may not be removable from the pressing rod **214**, as the carafe lid **216** can be removed from the lower end of the pressing rod **214** when the filtering system **212** and the locking ring **208** are removed. The securing bulb **218** is attached to the pressing rod **214** through known methods of attachment such as, but not limited to a threaded or a press fitting manner.

(33) FIG. **3A** illustrates the filter stage **300A** of the improved French press. During the filtering

process, the filter system **312** strains and filters the brewed materials, such as coffee grounds or tea leaves, away from the brewed liquid. Some level of downward pressure **330** must be applied to the pressing rod **314** in order to move the combined filter system **312** and locking **308** through the liquid. As the locking ring **308** gets closer to the locking base **304**, the locking ring lip(s) **310** begins to mate with the locking base lip(s) **306**.

(34) In FIG. **3B** the compressing stage **300B** of the improved French press is shown. At the end of the filtering stage **300A**, the locking ring lip(s) **310** and the locking base lip(s) **306** are touching along the desired mating points. In order to move the locking ring **308** through the compression stage **300B** there must be a specific amount of downward pressure **332** placed on the pressing rod **314** in an amount to compress the locking base lip(s) **306** enough to allow the locking ring **308** and locking ring lip(s) **310** to pass into the void of the locking base **304**. Once enough downward pressure **332** is used to move the locking ring lip(s) **310** past the compressed locking base lip(s) **306** then the locking base lip(s) **306** will decompress, thus allowing the decompressed locking ring lip(s) **310** to be secured against the locking base lip(s) **306** during the removal stage.

(35) FIG. **3C** illustrates the removal stage **300C** of the improved French press. When the locking ring lip(s) (not shown) are within the void of the locking base **304**, and both the locking ring lip(s) (not shown) and the locking base lip(s) **306** have decompressed then the removal stage **300C** can begin. The locking ring lip(s) (not shown) can be used to pull, when an upward force **334** is applied via the pressing rod **314**, on the underside of the locking base lip(s) **306** in order to remove the locking base **304** from the carafe (not shown). In a preferred embodiment, the locking ring **308** will rest within the locking base **304**, and the filter system **312** will be resting on top of the locking base lip(s) **306**, thus providing a way for the majority of the filtered brewing material to be channeled into the locking base **304**.

(36) In FIG. **4A** the improved coffee press **400A** is being used to remove brewing materials **401** from the brewed liquid **403**, in a filter stage similar to that of FIG. **3A**. As pressure is applied to the securing bulb **418**, and the pressing rod **414**, which slides through the opening in the carafe lid **416**, the filter system **412** and locking ring **408** are moved through the brewed liquid **403**. The filtering system **412** in some embodiments may be attached to the pressing rod **414** at a first connection point **421**, and the locking ring **408** is attached at a second connection point **420**. The connection points **420**, **421** may be a press fit, or threaded connection point, or alternatively could also be of a single piece manufacturing design. As the brewed liquid **403** is separated from the brewing material **401**, the brewing material **401** is driven towards the locking base **404** by the filter system **412**. In addition, in some embodiments the locking ring **408** provides some assistance in the driving of the brewed materials towards the locking base **404** without providing filtering, though alternatively it may also be combined with the filtering system **412** to provide filtering as well.

(37) In FIG. **4B**, the compression stage of the locking ring **408** and locking base **404** of the improved coffee press **400B** is shown. As the locking ring **408** approaches the locking base **404**, the locking ring lip(s) **410** and the locking base lip(s) **406** compress against each other. With sufficient pressure applied to the pressing rod **414** and securing bulb **418**, the locking ring lip(s) **410** will be compressed inward towards the pressing rod **414**, and the locking base lip(s) **406** will be compressed outward towards the wall(s) of the carafe **402**. As the locking ring **408** is pushed through the compressed stage it leads to the secured stage shown in FIG. **5A**.

(38) As seen in FIGS. **5A** & **5B**, the secured stage of the improved coffee press **500A** will allow the locking base **504** to be removed from the carafe **502**. One of the improvements of the improved coffee press **500A** is the collection of the brewing materials **501** in the locking base **504**, thus making the brewing materials **501** easier to remove from the carafe **502**. With the locking ring **508** being pushed via the pressing rod **514** through the compression stage **400B**, to the securing stage **500A**, the locking ring lip(s) **510** decompress along with decompressing of the locking base lip(s) **506** in order to form a secure connection when a pulling force is applied to the pressing rod **514**. When a user pulls on the pressing rod **514**, in order to remove the locking base **504**, the locking

ring lip(s) **510** slips into the opening **505** formed between the curved portion of the locking base lip(s) **506**, and the locking base **504**. Thus providing leverage for the removal of the locking base **504** from the carafe **502**. In a preferred embodiment illustrated, the locking ring lip(s) **510** slips inside the opening **505**.

(39) During the removal stage of the improved coffee press **500B**, the secured connection formed by the locking base lip(s) **506**, and the locking ring lip(s) **510**, in the opening **505** assist the user in removing the locking base **504** via the pressing rod **514**. In a preferred embodiment, the filtering system **512** rests on top of or just above the locking base lip(s) **506** during the removal stage **500B**, thus allowing the uncaptured brewing material **501** to be captured between the filtering system **512** and the locking base **504**. The result of the capture of the brewing materials **501**, is the clean carafe **502** seen in the lower portion of FIG. 5B.

(40) In FIGS. 6A-6C a top view of locking base **604** and locking base lip(s) **606** in a set of advantageous embodiments is shown. In FIG. 6A, a first preferred embodiment **600A** is illustrated that allows the pressing rod (not shown) and the locking ring (not shown) to be shifted to one side to allow the locking ring to be released from the locking base **604** and the locking base lip(s) **606**. In a second preferred embodiment **600B**, there are two locking base lip(s) **606** shown. In this embodiment the pressing rod (not shown) and the locking ring (not shown) can be shifted to either of the two sides to allow the locking ring to be released from the locking base **604** and the locking base lip(s) **606**. In a third preferred embodiment **600C**, four locking base lip(s) **606** are shown. In this embodiment, the locking ring (not shown) can be released from the locking base **604** by aligning the locking ring lip(s) (not shown) with the locking base gaps **607**. While embodiments have been illustrated that utilize one, two or four lip(s) or wings, other embodiments that include at least one lip(s) or wings are also possible. It could also be understood by someone skilled in the art how the locking base **604** and locking ring (not shown) connection could be achieved through additional means, such as, a threaded configuration, a press fit configuration, a snapping configuration, or other manners known for making a secure physical connection.

(41) A side view of the locking base **704** and locking base lip(s) **706** are seen in FIGS. 7A & 7B. The locking base **704** is configured to capture brewing material (not shown), such as, coffee grounds, tealeaves, pulp from fruits, or other brewable elements. In a first preferred embodiment **700A**, the locking base lip(s) **706** curve downward from the upward wall of the locking base **704**. The curve of the locking base lip(s) **706** allows for the compression that is created when the locking ring (not shown) is pushed through compression stage to the securing stage, resulting in the locking ring being in the void of the locking base **704**. In a second preferred embodiment **700B**, the locking base lip(s) **706** are at or below a ninety-degree angle from the wall of the locking base **704**.

(42) In FIGS. 8A & 8B, two side views of the locking ring **808** are illustrated. A first preferred embodiment **800A**, includes locking ring lip(s) **810** that are upturned from the plane of the locking ring **808**. In order to assist in the capture of brewing materials (not shown) the upturned locking ring lip(s) **810** aid in the compression of the locking base lip(s) (not shown) as the locking ring **808** is moved from the compression stage to the securing stage. In a second preferred embodiment **800B**, the locking ring **808** and the locking ring lip(s) **810** are in the same plane. This advantageous embodiment works best with the locking base (not shown) with straight or slightly angled locking ring lip(s) (not shown), however it can also be used with the curved locking base lip(s) embodiment as well.

(43) A top view of the locking ring **908** is shown in FIGS. 9A-9C. In a first preferred embodiment **900A**, the locking ring **908** is configured to closely match with the inner dimensions of the carafe **902**, though along two opposing edges there is a gap **911** between the edge of the locking ring **908** and the carafe **902** to allow for the locking ring lip(s) **910** to compress and become secure against the locking base lip(s) (not shown). In a second preferred embodiment **900B**, there are large gaps **911** between the carafe **902** and the locking ring **908**, on opposing sides. This second preferred embodiment **902** also is configured to work with the first and second preferred embodiments of the

locking base (not shown). However, it would be understood by someone with skill in the art that multiple embodiments and configurations are possible. In a third preferred embodiment **900C**, the locking ring **908** is shown with four wings that form the locking ring lip(s) **910**. The wings extend outward from the pressing rod connection **909**. While illustrated in this advantageous embodiment with four wings, the improved coffee press is not limited to four wings, there is to be at least one wing and up to as many necessary to provide support in removing the locking base (not shown).

(44) In FIG. **10**, an alternative advantageous embodiment of the improved coffee press **1000** is shown. In this alternative embodiment **1000**, the locking ring **1008** is comprised of four wings that form the locking ring lip(s) **1010**. In addition, the locking base **1004** is comprised of four locking base lip(s) **1006** that are turned slightly downward, and four locking base lip(s) gaps **1007**. To start the brewing process the carafe **1002** is filled with brewing material (not shown) and liquid. Once the liquid has been poured into the carafe **1002** the brewing process begins for the proper amount of time. At any time after the brewing process has been started, the pressing rod **1014**, locking ring **1008** and filter system **1012** combination is inserted to the carafe **1002** and attached to the carafe **1002** via the carafe lid **1016**. As a pressure is applied to the pressing rod **1014**, the filter system **1012** and the locking ring **1008** move in tandem further downward into the carafe **1002**, removing the brewing material (not shown) from the liquid (not shown). Once the locking ring **1008** has made contact with the locking base **1004**, the locking base lip(s) **1006** and the locking ring lip(s) **1010** are touching. The next step is for the user to increase pressure in order to cause the compression necessary to allow the locking ring **1008** and locking ring lip(s) **1010** to move through the locking base lip(s) **1006**. In addition, a user may also rotate the pressing rod **1014** in order to rotate the locking ring **1008** so that it aligns with the locking base lip(s) gaps **1007** of the locking base **1004**. Once the locking ring **1008** and locking ring lip(s) **1010** have moved past the locking base lip(s) **1006**, and the brewing materials are captured in the locking base **1004**, the locking base **1004** and the locking ring **1008** can be secured together.

(45) In FIG. **11**, a side view of the locking base **1104** is shown with a supplemental base **1140** is shown that can be both removable and/or disposable. The supplemental base **1140** is designed to give the user a way to decrease the amount of cleaning that would be required for the locking base **1104**. As coffee grounds collect in the supplemental base **1140**, the grounds then do not collect in the locking base, thus allowing the locking base **1104** to be used multiple times without cleaning if so desired. This supplemental base **1140** can be made of paper, metal, plastic, or other organic or synthetic materials.

(46) In FIGS. **12A** and **12B**, an alternative advantageous embodiment of the improved coffee press **1200A** and **1200B** is shown in different stages. The locking base lip(s) **1206** in these embodiment are the straight or slightly downturned version, in order to assist the removal of the locking base **1204**. In addition, the locking ring **1208** is an oblong oval shape, and a straight plane that is configured to move through, the opening created by the locking base lip(s) **1206** when the locking ring **1208** is rotated so that it will move between the locking base lip(s) **1206** with ease. The combination of the dual locking base lip(s) **1206**, and the oblong locking ring **1208** allow the user to remove the locking base **1204**, by inserting the locking ring **1208** into the locking base **1204** through the gap between the locking base lip(s) or compression and rotating until the locking ring lip(s) **1210** are below the locking base lip(s) **1206** as shown in FIG. **12B**. The filtering system **1212** is set some distance above the locking ring **1208**, on the pressing rod **1214** in order to remove the remaining brewing materials (not shown) from the liquid during the removal stage. In a preferred embodiment, the filtering system **1212** rests on top of or just above the locking base lip(s) **1206** during the removal stage, thus allowing the brewing material (not shown) to be captured between the filtering system **1212** and the locking base **1204**.

(47) The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The

embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated. It will be understood by one of ordinary skill in the art that numerous variations will be possible to the disclosed embodiments without going outside the scope of the invention as disclosed in the claims.

Claims

1. A French press filter system for use with a carafe comprising: a filtering system slidably engaged to a pressing rod, wherein the pressing rod comprises an interface for holding the filtering system in place; a locking ring fixedly attached to a terminal end of the pressing rod; and a locking base configured to engage with the locking ring such that the locking base may be removed from the carafe, wherein the locking base comprises a set of lips.
2. The French press filter system of claim 1, wherein the filtering system comprises an upper retaining ring.
3. The French press filter system of claim 1, wherein the filtering system comprises a filter mesh.
4. The French press filter system of claim 1, wherein the filtering system comprises a lower retaining ring.
5. The French press filter system of claim 1, wherein the filtering system comprises an upper retaining ring removably coupled to a pressing rod; a filter mesh located below the upper retaining ring; a lower retaining ring located below the filter mesh and removably engaged with the upper retaining ring to provide support for the filter mesh.
6. The French press filter system of claim 1, wherein the locking base is sized to fit within the carafe with such that brewing material cannot pass between the locking base and the carafe.
7. The French press filter system of claim 1, wherein the set of lips are flexible.
8. The French press filter system of claim 1, wherein the locking ring comprises a set of lips.
9. The French press filter system of claim 8, wherein the set of lips are flexible.
10. A French press filter system comprising: an upper retaining ring slidably engaged to a pressing rod; a filter mesh slidably engaged to the pressing rod, the filter mesh located below the upper retaining ring; a lower retaining ring slidably engaged to the pressing rod, the lower retaining ring being located below the filter mesh and removably engaged with the upper retaining ring to provide support for the filter mesh; and a locking ring fixedly attached to a terminal end of the pressing rod, wherein the locking ring is configured to engage with a locking base.
11. The French press filter system of claim 10, wherein the locking ring includes a lip along an outer edge of the locking ring.
12. The French press filter system of claim 11, wherein the lip is flexible.
13. The French press filter system of claim 10, wherein the locking base includes a flexible lip that allows the locking ring to pass through.
14. The French press filter system of claim 10, wherein the locking base is sized to fit within a carafe.
15. A French press apparatus comprising: a carafe; a filter system sized to fit within the carafe, the filter system including an upper retaining ring, a mesh filter below the upper retaining ring, a lower retaining ring supporting the mesh filter, and a locking ring below the lower retaining ring; a pressing rod slidably engaged to the filter system, wherein the locking ring is fixedly attached to a terminal end of the pressing rod; and a locking base configured to receiving the locking ring when the pressing rod is advanced downward.
16. The French press apparatus of claim 15, wherein the locking base is sized to fit within the carafe such that brewing material cannot pass between the locking base and the carafe.

17. The French press apparatus of claim 15, wherein the locking ring includes a lip that is flexible.
 18. The French press apparatus of claim 15, wherein the locking base includes a lip that is flexible.
-