

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409028
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Rosen; Robert et al.

Systems and methods for correcting photic phenomenon from an intraocular lens and using refractive index writing

Abstract

Systems and methods for improving vision of a subject implanted with an intraocular lens (IOL). In some embodiments, a method includes determining at least one photic phenomenon experienced by the subject after implantation of the IOL; and applying a plurality of laser pulses to the IOL, the laser pulses being configured to produce, by refractive index writing on the IOL, a phase shift in the IOL to compensate for the photic phenomenon.

Inventors: Rosen; Robert (Groningen, NL), Gounou; Franck Emmanuel (Groningen, NL), Canovas Vidal; Carmen (Groningen, NL), Alarcon Heredia; Aixa (Groningen, NL)

Applicant: AMO Groningen B.V. (Groningen, NL)

Family ID: 70224367

Assignee: AMO Groningen B.V. (N/A, NL)

Appl. No.: 18/171341

Filed: February 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230200975 A1	Jun. 29, 2023

Related U.S. Application Data

continuation parent-doc US 16837670 20200401 US 11583389 child-doc US 18171341
us-provisional-application US 62830242 20190405

Publication Classification

Int. Cl.: A61F2/16 (20060101); A61F9/008 (20060101); A61B17/00 (20060101)

U.S. Cl.:

CPC A61F2/1627 (20130101); A61F9/008 (20130101); A61B2017/00181 (20130101); A61F2009/00848 (20130101)

Field of Classification Search

CPC: A61B (2017/00181); A61F (2/1627); A61F (9/008); A61F (2240/002); A61F (2250/0009); A61F (2250/0026); A61F (2250/0036)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2250597	12/1940	Moulton	N/A	N/A
3542535	12/1969	Hensler et al.	N/A	N/A
3610924	12/1970	Sinai	N/A	N/A
4039827	12/1976	Zdrok et al.	N/A	N/A
4061486	12/1976	Jahn	N/A	N/A
4073579	12/1977	Deeg et al.	N/A	N/A
4300818	12/1980	Schachar	N/A	N/A
4477158	12/1983	Pollock et al.	N/A	N/A
4540672	12/1984	Boudot et al.	N/A	N/A
4611892	12/1985	Kawashima et al.	N/A	N/A
4650845	12/1986	Hegel	N/A	N/A
4691715	12/1986	Tanne	N/A	N/A
4720286	12/1987	Bailey et al.	N/A	N/A
4856889	12/1988	Guilino et al.	N/A	N/A
4985472	12/1990	Aosai et al.	N/A	N/A
5015523	12/1990	Kawashima et al.	N/A	N/A
5066301	12/1990	Wiley	N/A	N/A
5074942	12/1990	Kearns et al.	N/A	N/A
5116111	12/1991	Simpson et al.	N/A	N/A
5172143	12/1991	Baude et al.	N/A	N/A
5196026	12/1992	Barrett et al.	N/A	N/A
5229797	12/1992	Futhey et al.	N/A	N/A
5233007	12/1992	Yang	N/A	N/A
5296305	12/1993	Baude et al.	N/A	N/A
5319007	12/1993	Bright	N/A	N/A
5357024	12/1993	Leclaire	N/A	N/A
5424339	12/1994	Zanka et al.	N/A	N/A
5460627	12/1994	O'Donnell, Jr.	N/A	N/A
5476515	12/1994	Kelman et al.	N/A	N/A
5521656	12/1995	Portney	N/A	N/A
5541278	12/1995	Raleigh et al.	N/A	N/A

5648402	12/1996	Nunez et al.	N/A	N/A
5694195	12/1996	Engardio et al.	N/A	N/A
5728156	12/1997	Gupta et al.	N/A	N/A
5762836	12/1997	Bos et al.	N/A	N/A
5830578	12/1997	Ono et al.	N/A	N/A
5873931	12/1998	Scholz et al.	N/A	N/A
5891931	12/1998	Leboeuf et al.	N/A	N/A
5908876	12/1998	Fujii et al.	N/A	N/A
5910537	12/1998	Feingold et al.	N/A	N/A
5928663	12/1998	Peyman	N/A	N/A
5973192	12/1998	Woodbury et al.	N/A	N/A
6075652	12/1999	Ono et al.	N/A	N/A
6086204	12/1999	Magnante	N/A	N/A
6099123	12/1999	Engardio et al.	N/A	N/A
6139146	12/1999	Zhang	N/A	N/A
6248285	12/2000	Henry et al.	N/A	N/A
6256152	12/2000	Coldrey et al.	N/A	N/A
6270698	12/2000	Pope	N/A	N/A
6300464	12/2000	Morijiri et al.	N/A	N/A
6313187	12/2000	LeBoeuf et al.	N/A	N/A
6313316	12/2000	Kitahara et al.	N/A	N/A
6339505	12/2001	Bates	N/A	N/A
6450642	12/2001	Jethmalani et al.	N/A	N/A
6454408	12/2001	Morris et al.	N/A	N/A
6464484	12/2001	Powers et al.	N/A	N/A
6478792	12/2001	Hansel	N/A	N/A
6528005	12/2002	Amagai et al.	N/A	N/A
6655946	12/2002	Foreman et al.	N/A	N/A
6676398	12/2003	Foreman et al.	N/A	N/A
6676399	12/2003	Foreman	N/A	N/A
6695880	12/2003	Roffman et al.	N/A	N/A
6699953	12/2003	Oshikiri et al.	N/A	N/A
6706894	12/2003	Okubo et al.	N/A	N/A
6723260	12/2003	Powers et al.	N/A	N/A
6746632	12/2003	Houston et al.	N/A	N/A
6747090	12/2003	De Groot et al.	N/A	N/A
6749632	12/2003	Sandstedt et al.	N/A	N/A
6749779	12/2003	Soane et al.	N/A	N/A
6758663	12/2003	Foreman et al.	N/A	N/A
6770735	12/2003	Tanaka et al.	N/A	N/A
6776934	12/2003	Lai	N/A	N/A
6790022	12/2003	Foreman	N/A	N/A
6790024	12/2003	Foreman	N/A	N/A
6793340	12/2003	Morris et al.	N/A	N/A
6808381	12/2003	Foreman et al.	N/A	N/A
6840619	12/2004	Dreher	N/A	N/A
6851804	12/2004	Jethmalani et al.	N/A	N/A
6852793	12/2004	Salamone et al.	N/A	N/A
6863518	12/2004	Powers	N/A	N/A
6863848	12/2004	Engardio et al.	N/A	N/A

6875005	12/2004	Foreman	N/A	N/A
6893245	12/2004	Foreman et al.	N/A	N/A
6899831	12/2004	Foreman	N/A	N/A
6923802	12/2004	Williams et al.	N/A	N/A
6942924	12/2004	He et al.	N/A	N/A
6962669	12/2004	Foreman et al.	N/A	N/A
6964479	12/2004	Buazza et al.	N/A	N/A
7001374	12/2005	Peyman	N/A	N/A
7004740	12/2005	Foreman	N/A	N/A
7009024	12/2005	Salamone et al.	N/A	N/A
7009031	12/2005	Yoshimura et al.	N/A	N/A
7025910	12/2005	Lattis et al.	N/A	N/A
7044429	12/2005	Foreman et al.	N/A	N/A
7045081	12/2005	Foreman et al.	N/A	N/A
7052262	12/2005	Foreman et al.	N/A	N/A
7060095	12/2005	Ho et al.	N/A	N/A
7060208	12/2005	Foreman et al.	N/A	N/A
7066597	12/2005	Miller et al.	N/A	N/A
7066955	12/2005	Lowery	N/A	N/A
7081272	12/2005	Sasaki et al.	N/A	N/A
7083404	12/2005	Foreman et al.	N/A	N/A
7083851	12/2005	Faris	N/A	N/A
7090349	12/2005	Perrott et al.	N/A	N/A
7104648	12/2005	Dahi et al.	N/A	N/A
7124995	12/2005	Foreman et al.	N/A	N/A
7169874	12/2006	Salamone et al.	N/A	N/A
7172285	12/2006	Altmann et al.	N/A	N/A
7186266	12/2006	Peyman	N/A	N/A
7207998	12/2006	Feingold	N/A	N/A
7217778	12/2006	Verbruggen	N/A	N/A
7234810	12/2006	Warden et al.	N/A	N/A
7239451	12/2006	Suzuki et al.	N/A	N/A
7279538	12/2006	Lai et al.	N/A	N/A
7293871	12/2006	Dreher et al.	N/A	N/A
7297160	12/2006	Salamone et al.	N/A	N/A
7301705	12/2006	Yoshimura et al.	N/A	N/A
7341345	12/2007	Azar et al.	N/A	N/A
7393101	12/2007	Blum et al.	N/A	N/A
7399524	12/2007	Suzuki et al.	N/A	N/A
7423108	12/2007	Kunzler et al.	N/A	N/A
7423801	12/2007	Kaufman et al.	N/A	N/A
7446157	12/2007	Mentak et al.	N/A	N/A
7452074	12/2007	Kumar et al.	N/A	N/A
7457507	12/2007	Kuramoto et al.	N/A	N/A
7499221	12/2008	Nishioka	N/A	N/A
7507358	12/2008	Morris et al.	N/A	N/A
7563827	12/2008	Koyama et al.	N/A	N/A
7576920	12/2008	Downing et al.	N/A	N/A
7598196	12/2008	Friz et al.	N/A	N/A
7632904	12/2008	Salamone et al.	N/A	N/A

7701641	12/2009	Dreher et al.	N/A	N/A
7708402	12/2009	Ribak	N/A	N/A
7714090	12/2009	Iwamoto et al.	N/A	N/A
7735998	12/2009	Volk	N/A	N/A
7767779	12/2009	Jallouli et al.	N/A	N/A
7782537	12/2009	Naito et al.	N/A	N/A
7789910	12/2009	Knox et al.	N/A	N/A
7806526	12/2009	Bourdoncle et al.	N/A	N/A
7808707	12/2009	Cano et al.	N/A	N/A
7854508	12/2009	Nakajima et al.	N/A	N/A
7857848	12/2009	Mentak	N/A	N/A
7878649	12/2010	Archambeau et al.	N/A	N/A
7883540	12/2010	Niwa et al.	N/A	N/A
7901787	12/2010	Miyakawa	N/A	N/A
7922325	12/2010	Toda et al.	N/A	N/A
7926940	12/2010	Blum et al.	N/A	N/A
7931371	12/2010	Dai	N/A	N/A
7935212	12/2010	Jiang et al.	N/A	N/A
7950398	12/2010	Schroeder et al.	N/A	N/A
7959284	12/2010	Lai	N/A	N/A
7959286	12/2010	Plummer	N/A	N/A
7968204	12/2010	Koh et al.	N/A	N/A
7992997	12/2010	Varnas	N/A	N/A
8003022	12/2010	Diggins et al.	N/A	N/A
8034262	12/2010	Lai et al.	N/A	N/A
8043370	12/2010	Bretthauer et al.	N/A	N/A
8052278	12/2010	Bovet et al.	N/A	N/A
8109999	12/2011	Hampp	N/A	N/A
8113651	12/2011	Blum et al.	N/A	N/A
8153248	12/2011	Naito	N/A	N/A
8158712	12/2011	Your	N/A	N/A
8167427	12/2011	Guillon et al.	N/A	N/A
8169716	12/2011	Zalevsky et al.	N/A	N/A
8172397	12/2011	Ballet et al.	N/A	N/A
8216309	12/2011	Azar	N/A	N/A
8231217	12/2011	Ballet et al.	N/A	N/A
8240849	12/2011	Widman et al.	N/A	N/A
8262646	12/2011	Frey et al.	N/A	N/A
8292952	12/2011	Bille	N/A	N/A
8329763	12/2011	Werner	N/A	N/A
8361353	12/2012	Brait et al.	N/A	N/A
8403483	12/2012	Klink et al.	N/A	N/A
8404797	12/2012	Kawabe et al.	N/A	N/A
8454862	12/2012	Andino et al.	N/A	N/A
8470948	12/2012	Stiegman	N/A	N/A
8486055	12/2012	Knox et al.	N/A	N/A
8517534	12/2012	Sone et al.	N/A	N/A
8523354	12/2012	Haddock et al.	N/A	N/A
8529059	12/2012	Suzuki	N/A	N/A

8570485	12/2012	Ye et al.	N/A	N/A
8586664	12/2012	Buhler et al.	N/A	N/A
8611010	12/2012	Radcliffe et al.	N/A	N/A
8636358	12/2013	Binder	N/A	N/A
8681428	12/2013	Brown	N/A	N/A
8715345	12/2013	DeBoer et al.	N/A	N/A
8759414	12/2013	Muller-Lierheim et al.	N/A	N/A
8778450	12/2013	Zuyi et al.	N/A	N/A
8789943	12/2013	Sverdrup et al.	N/A	N/A
8789944	12/2013	Nishimoto et al.	N/A	N/A
8801177	12/2013	Archambeau et al.	N/A	N/A
8815378	12/2013	Gueneau et al.	N/A	N/A
8815388	12/2013	Yamazaki et al.	N/A	N/A
8834757	12/2013	Auciello et al.	N/A	N/A
8842370	12/2013	Jethmalani et al.	N/A	N/A
8846140	12/2013	Roisin et al.	N/A	N/A
8895233	12/2013	McLeod	N/A	N/A
8901190	12/2013	Smith et al.	N/A	N/A
8902487	12/2013	Ohnishi	N/A	N/A
8933143	12/2014	Boydston et al.	N/A	N/A
8944594	12/2014	McLeod et al.	N/A	N/A
8980431	12/2014	Mori et al.	N/A	N/A
9012566	12/2014	Buhler et al.	N/A	N/A
9019614	12/2014	DeVaul	N/A	N/A
9052436	12/2014	Jang et al.	N/A	N/A
9074040	12/2014	Turshani et al.	N/A	N/A
9107746	12/2014	Sahler et al.	N/A	N/A
9119710	12/2014	Grubbs et al.	N/A	N/A
9144491	12/2014	Knox et al.	N/A	N/A
9146407	12/2014	Clarke et al.	N/A	N/A
9150694	12/2014	Aoki et al.	N/A	N/A
9155614	12/2014	Blum et al.	N/A	N/A
9164206	12/2014	Valley et al.	N/A	N/A
11529230	12/2021	Rosen et al.	N/A	N/A
11564839	12/2022	Rosen et al.	N/A	N/A
11583388	12/2022	Rosen et al.	N/A	N/A
11583389	12/2022	Rosen et al.	N/A	N/A
11678975	12/2022	Rosen	N/A	N/A
11931296	12/2023	Rosen	N/A	A61F 9/00834
2001/0055094	12/2000	Zhang	N/A	N/A
2002/0016629	12/2001	Sandstedt et al.	N/A	N/A
2002/0031676	12/2001	Jonza et al.	N/A	N/A
2002/0093701	12/2001	Zhang et al.	N/A	N/A
2003/0007257	12/2002	Bell, Jr. et al.	N/A	N/A
2003/0017303	12/2002	Shindo et al.	N/A	N/A
2003/0038920	12/2002	Lin	N/A	N/A
2004/0117013	12/2003	Schachar	N/A	N/A

2004/0142185	12/2003	Takushima	N/A	N/A
2005/0090612	12/2004	Soane et al.	N/A	N/A
2005/0231677	12/2004	Meredith	N/A	N/A
2005/0254003	12/2004	Jani et al.	N/A	N/A
2005/0260388	12/2004	Lai	N/A	N/A
2006/0065989	12/2005	Druffel et al.	N/A	N/A
2006/0135952	12/2005	Curatu et al.	N/A	N/A
2006/0155093	12/2005	Kitahara	N/A	N/A
2006/0177638	12/2005	Shibuya et al.	N/A	N/A
2006/0204655	12/2005	Takahashi	N/A	N/A
2006/0227283	12/2005	Ooi et al.	N/A	N/A
2007/0097512	12/2006	Toyoda et al.	N/A	N/A
2007/0193987	12/2006	Bischoff	219/121.73	B23K 26/38
2007/0225466	12/2006	Matsumoto et al.	N/A	N/A
2007/0249794	12/2006	Evans et al.	N/A	N/A
2007/0255401	12/2006	Lang	N/A	N/A
2007/0273973	12/2006	Kursawe et al.	N/A	N/A
2008/0012850	12/2007	Keating, III	N/A	N/A
2008/0027537	12/2007	Gerlach et al.	N/A	N/A
2008/0137032	12/2007	Lawrence et al.	N/A	N/A
2008/0170487	12/2007	Kimura et al.	N/A	N/A
2008/0200582	12/2007	Craciun et al.	N/A	N/A
2008/0212023	12/2007	Bovet et al.	N/A	N/A
2008/0242965	12/2007	Norris et al.	N/A	N/A
2008/0268253	12/2007	Murai et al.	N/A	N/A
2008/0274352	12/2007	Hao et al.	N/A	N/A
2009/0029153	12/2008	Naito et al.	N/A	N/A
2009/0036880	12/2008	Bischoff et al.	N/A	N/A
2009/0066911	12/2008	Ishizaki et al.	N/A	N/A
2009/0078154	12/2008	Sasaki et al.	N/A	N/A
2009/0099329	12/2008	Ryu et al.	N/A	N/A
2009/0118828	12/2008	Altmann	N/A	N/A
2009/0169859	12/2008	Biteau et al.	N/A	N/A
2009/0174098	12/2008	Rouault De Coligny et al.	N/A	N/A
2009/0189303	12/2008	Diggins et al.	N/A	N/A
2009/0228101	12/2008	Zadno-Azizi	N/A	N/A
2009/0299345	12/2008	Bille et al.	N/A	N/A
2009/0316110	12/2008	Cano et al.	N/A	N/A
2010/0004741	12/2009	Gupta et al.	N/A	N/A
2010/0082017	12/2009	Zickler et al.	N/A	N/A
2010/0190919	12/2009	Kimura et al.	N/A	N/A
2010/0228345	12/2009	Bille	623/6.23	B23K 26/0624
2010/0245761	12/2009	Widman et al.	N/A	N/A
2010/0324408	12/2009	Klink et al.	N/A	N/A
2011/0071509	12/2010	Knox et al.	N/A	N/A
2011/0144747	12/2010	McGinniss et al.	N/A	N/A
2011/0164329	12/2010	Jiang et al.	N/A	N/A
2011/0172649	12/2010	Schuele et al.	N/A	N/A

2011/0190467	12/2010	Hughes et al.	N/A	N/A
2011/0242662	12/2010	Momoki et al.	N/A	N/A
2011/0245919	12/2010	Pettit	N/A	N/A
2012/0059439	12/2011	Yoon	N/A	N/A
2012/0141770	12/2011	Cadet et al.	N/A	N/A
2012/0172483	12/2011	Nakamura et al.	N/A	N/A
2012/0172854	12/2011	Raymond et al.	N/A	N/A
2012/0212696	12/2011	Trajkovska et al.	N/A	N/A
2012/0240939	12/2011	Kandulla	N/A	N/A
2012/0259411	12/2011	Hong et al.	N/A	N/A
2012/0296423	12/2011	Caffey et al.	N/A	N/A
2012/0310223	12/2011	Knox et al.	N/A	N/A
2012/0310340	12/2011	Knox et al.	N/A	N/A
2013/0035760	12/2012	Portney	N/A	N/A
2013/0218270	12/2012	Blanckaert et al.	N/A	N/A
2013/0222756	12/2012	Van Heugten	N/A	N/A
2013/0222913	12/2012	Tomoda et al.	N/A	N/A
2013/0231740	12/2012	Mentak	N/A	N/A
2013/0253159	12/2012	Benz et al.	N/A	N/A
2013/0273317	12/2012	Nakayama	N/A	N/A
2013/0289153	12/2012	Sandstedt et al.	N/A	N/A
2013/0308186	12/2012	Cathey, Jr. et al.	N/A	N/A
2013/0309453	12/2012	Biver et al.	N/A	N/A
2013/0337161	12/2012	Akimoto et al.	N/A	N/A
2014/0043584	12/2013	Blum	N/A	N/A
2014/0135920	12/2013	Sahler et al.	N/A	N/A
2014/0148899	12/2013	Fehr et al.	N/A	N/A
2014/0171612	12/2013	Bojkova et al.	N/A	N/A
2014/0192420	12/2013	Baer et al.	N/A	N/A
2014/0198296	12/2013	Kadowaki	N/A	N/A
2014/0241605	12/2013	Izatt et al.	N/A	N/A
2014/0276674	12/2013	Lee et al.	N/A	N/A
2014/0276680	12/2013	Dennison et al.	N/A	N/A
2014/0300857	12/2013	Cohen-Tannoudji et al.	N/A	N/A
2014/0316521	12/2013	McLeod et al.	N/A	N/A
2014/0327875	12/2013	Blum et al.	N/A	N/A
2014/0327884	12/2013	Buhren et al.	N/A	N/A
2014/0342016	12/2013	Raymond et al.	N/A	N/A
2014/0343541	12/2013	Scott et al.	N/A	N/A
2014/0347625	12/2013	Tomoda et al.	N/A	N/A
2015/0081016	12/2014	De Sio et al.	N/A	N/A
2015/0103313	12/2014	Sarver et al.	N/A	N/A
2015/0126979	12/2014	Knox et al.	N/A	N/A
2015/0166704	12/2014	Otani et al.	N/A	N/A
2015/0203635	12/2014	Tapsak	N/A	N/A
2015/0203710	12/2014	Feuillade et al.	N/A	N/A
2015/0234206	12/2014	Lee et al.	N/A	N/A
2015/0241714	12/2014	Allione et al.	N/A	N/A
2015/0258240	12/2014	Grubbs	N/A	N/A

2015/0277150	12/2014	Granger et al.	N/A	N/A
2015/0321991	12/2014	Ponrathnam et al.	N/A	N/A
2015/0351630	12/2014	Engelhardt et al.	N/A	N/A
2016/0074007	12/2015	Fedor	N/A	N/A
2016/0089271	12/2015	Zacharias	N/A	N/A
2016/0150952	12/2015	Raymond et al.	N/A	N/A
2016/0296662	12/2015	Stoy et al.	N/A	N/A
2017/0027437	12/2016	Neal et al.	N/A	N/A
2017/0156931	12/2016	Knox et al.	N/A	N/A
2018/0021172	12/2017	Zheleznyak et al.	N/A	N/A
2018/0110613	12/2017	Wortz et al.	N/A	N/A
2018/0200112	12/2017	Krampert et al.	N/A	N/A
2018/0243082	12/2017	Zheleznyak et al.	N/A	N/A
2018/0368972	12/2017	Rosen et al.	N/A	N/A
2018/0373060	12/2017	Knox et al.	N/A	N/A
2019/0000433	12/2018	Argenta et al.	N/A	N/A
2019/0004221	12/2018	Weeber et al.	N/A	N/A
2019/0004335	12/2018	Weeber et al.	N/A	N/A
2019/0021904	12/2018	Schuele et al.	N/A	N/A
2019/0060056	12/2018	Serdarevic et al.	N/A	N/A
2019/0142576	12/2018	Goldshleger et al.	N/A	N/A
2019/0239803	12/2018	Rosen et al.	N/A	N/A
2019/0307554	12/2018	Schuele et al.	N/A	N/A
2020/0197157	12/2019	Shmukler et al.	N/A	N/A
2020/0315782	12/2019	Rosen et al.	N/A	N/A
2020/0315783	12/2019	Rosen et al.	N/A	N/A
2020/0315848	12/2019	Rosen et al.	N/A	N/A
2020/0315849	12/2019	Rosen et al.	N/A	N/A
2021/0030531	12/2020	Ambati	N/A	N/A
2022/0031504	12/2021	Schuele et al.	N/A	N/A
2023/0123960	12/2022	Rosen et al.	N/A	N/A
2023/0200975	12/2022	Rosen	N/A	N/A
2023/0210654	12/2022	Rosen et al.	N/A	N/A
2023/0329858	12/2022	Rosen	N/A	N/A
2023/0404743	12/2022	Rosen	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
711538	12/1998	AU	N/A
712186	12/1998	AU	N/A
734097	12/2000	AU	N/A
774079	12/2003	AU	N/A
2003281672	12/2006	AU	N/A
2008201900	12/2007	AU	N/A
2006305319	12/2011	AU	N/A
2013228002	12/2012	AU	N/A
2014200799	12/2013	AU	N/A
2009278956	12/2014	AU	N/A
2050515	12/1991	CA	N/A

2059328	12/1991	CA	N/A
2150478	12/1993	CA	N/A
2291548	12/1999	CA	N/A
2563763	12/2004	CA	N/A
2722274	12/2008	CA	N/A
2752046	12/2009	CA	N/A
2802793	12/2011	CA	N/A
2824916	12/2011	CA	N/A
2837756	12/2011	CA	N/A
2859978	12/2012	CA	N/A
2858283	12/2012	CA	N/A
2888013	12/2013	CA	N/A
2895273	12/2013	CA	N/A
2411767	12/1999	CN	N/A
101107277	12/2007	CN	N/A
101564551	12/2008	CN	N/A
202004310	12/2010	CN	N/A
101321700	12/2011	CN	N/A
103698901	12/2013	CN	N/A
104151807	12/2013	CN	N/A
102015009610	12/2016	DE	N/A
0064812	12/1984	EP	N/A
0269288	12/1991	EP	N/A
0855993	12/2000	EP	N/A
0610310	12/2001	EP	N/A
1195623	12/2001	EP	N/A
1003795	12/2003	EP	N/A
1484352	12/2003	EP	N/A
1044097	12/2004	EP	N/A
1249716	12/2006	EP	N/A
2067613	12/2008	EP	N/A
2174966	12/2009	EP	N/A
2192932	12/2010	EP	N/A
2192934	12/2010	EP	N/A
2711741	12/2013	EP	N/A
2713950	12/2013	EP	N/A
2033021	12/2014	EP	N/A
2901965	12/2014	EP	N/A
2906970	12/2015	EP	N/A
2655842	12/1990	FR	N/A
2667073	12/1991	FR	N/A
2774998	12/1998	FR	N/A
2149804	12/1984	GB	N/A
2247538	12/1991	GB	N/A
2265367	12/1992	GB	N/A
2427169	12/2009	GB	N/A
S5541416	12/1979	JP	N/A
S638239	12/1987	JP	N/A
S63204229	12/1987	JP	N/A
S63279201	12/1987	JP	N/A

H06123856	12/1993	JP	N/A
H06261923	12/1993	JP	N/A
H10273887	12/1997	JP	N/A
2002156503	12/2001	JP	N/A
2002182002	12/2001	JP	N/A
2003222703	12/2002	JP	N/A
2004184933	12/2003	JP	N/A
2004309683	12/2003	JP	N/A
2005133131	12/2004	JP	N/A
2006189565	12/2005	JP	N/A
2006267561	12/2005	JP	N/A
2007046008	12/2006	JP	N/A
2007091921	12/2006	JP	N/A
2007163655	12/2006	JP	N/A
2007260192	12/2006	JP	N/A
2008096828	12/2007	JP	N/A
2008158513	12/2007	JP	N/A
2008239920	12/2007	JP	N/A
2009175658	12/2008	JP	N/A
2009227835	12/2008	JP	N/A
2009227836	12/2008	JP	N/A
2009234180	12/2008	JP	N/A
2009256275	12/2008	JP	N/A
2009256662	12/2008	JP	N/A
2010105229	12/2009	JP	N/A
2010202778	12/2009	JP	N/A
2010204456	12/2009	JP	N/A
2011038050	12/2010	JP	N/A
2011084817	12/2010	JP	N/A
2012082386	12/2011	JP	N/A
2012141407	12/2011	JP	N/A
2012234218	12/2011	JP	N/A
2012247741	12/2011	JP	N/A
2013010842	12/2012	JP	N/A
2013234127	12/2012	JP	N/A
5597780	12/2013	JP	N/A
20020027191	12/2001	KR	N/A
20080023016	12/2007	KR	N/A
20140122846	12/2013	KR	N/A
20150018006	12/2014	KR	N/A
9519748	12/1994	WO	N/A
9710527	12/1996	WO	N/A
9913361	12/1998	WO	N/A
0064956	12/1999	WO	N/A
0105578	12/2000	WO	N/A
0182815	12/2000	WO	N/A
2004023189	12/2003	WO	N/A
2004068202	12/2003	WO	N/A
2006043409	12/2005	WO	N/A
2007008666	12/2006	WO	N/A

2008055118	12/2007	WO	N/A
2008062903	12/2007	WO	N/A
2008070851	12/2007	WO	N/A
2009148454	12/2008	WO	N/A
2010016242	12/2009	WO	N/A
2010119755	12/2009	WO	N/A
2011080472	12/2010	WO	N/A
2011102502	12/2010	WO	N/A
2011109039	12/2010	WO	N/A
2011125956	12/2010	WO	N/A
2012034265	12/2011	WO	N/A
2012074742	12/2011	WO	N/A
2012112014	12/2011	WO	N/A
2012156081	12/2011	WO	N/A
2012166696	12/2011	WO	N/A
2013022065	12/2012	WO	N/A
2013169987	12/2012	WO	N/A
2014131879	12/2013	WO	N/A
2014140905	12/2013	WO	N/A
2014158615	12/2013	WO	N/A
2015000534	12/2014	WO	N/A
2015010119	12/2014	WO	N/A
2015015205	12/2014	WO	N/A
2015016363	12/2014	WO	N/A
2015038611	12/2014	WO	N/A
2015038614	12/2014	WO	N/A
2015038620	12/2014	WO	N/A
2015038623	12/2014	WO	N/A
2015068839	12/2014	WO	N/A
2015132605	12/2014	WO	N/A
2015164779	12/2014	WO	N/A
2015170133	12/2014	WO	N/A
2015170278	12/2014	WO	N/A
2016111851	12/2015	WO	N/A

OTHER PUBLICATIONS

Rosales P., et al., "Intraocular Lens Alignment From Purkinje and Scheimpflug Imaging," Clinical and Experimental Optometry, 2010, vol. 93(Issue-6), pp. 400-408. cited by applicant
Thurman S.T., "Method of Obtaining Wavefront Slope Data From Through-focus Point Spread Function Measurements," Journal of the Optical Society of America, Jan. 2011, vol. 28(1), pp. 1-7. cited by applicant

Primary Examiner: Bahena; Christie

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of and claims priority to U.S. Pat. No. 11,583,389, filed Apr. 1, 2020, which claims the benefit under

BACKGROUND

(1) Currently a range of factors can limit visual performance of a patient (also referred to herein as a “subject”) following corrective surgery (e.g., cataract surgery) in which an intraocular lens (IOL) is implanted in the patient's eye(s). These limiting factors can include: incorrect IOL power, which is commonly caused by incorrect IOL power calculations due to biometry accuracy; and uncorrected astigmatism, which can be caused by factors such as surgically induced astigmatism, effect of posterior corneal astigmatism, incorrect toric IOL power calculation, toric IOL rotation, or misplacement and use of non-toric IOLs in toric corneas. Additional limiting factors can include: spectacle dependence, which can be due to monofocal IOL implantation, as well as incorrect estimations of the most suitable presbyopia correcting IOLs for the patient; phone phenomena, such as halos, starburst and glare, for example in patients using presbyopia-correcting IOLs; negative dysphotopsia; peripheral aberration, and chromatic aberration. Replacing an implanted IOL that causes negative post-surgical visual outcomes for a patient can be a risky and complicated procedure. Therefore, among other needs, there exists a need to alleviate negative post-surgical visual outcomes without the need of IOL replacement.

SUMMARY

(2) Among other aspects, certain embodiments of the present disclosure relate to improving vision in a subject with an implanted intraocular lens (IOL) without the need to replace the IOL, through the use of refractive index writing (RIW).

(3) In one aspect, the present disclosure relates to a method for improving vision of a subject having an implanted intraocular lens (IOL). In one embodiment, the method includes determining at least one photic phenomenon experienced by the subject after implantation of the IOL; and applying a plurality of laser pulses to the IOL. The laser pulses can be configured to produce, by refractive index writing on the IOL, a phase shift in the IOL to compensate for the phone phenomenon.

(4) In some embodiments, applying the plurality of laser pulses includes applying a plurality of focused laser pulses, according to a predetermined pattern, to at least one selected area of the IOL to produce, by the refractive index writing on the IOL, the phase shift. The phone phenomenon can include a halo, starburst, and/or glare. In some embodiments, the phase shift can include a radially dependent phase shift. In some embodiments, the method can include verifying correction of the at least one photic phenomenon following the application of the laser pulses. Verifying the correction can be performed by incorporating subject feedback provided following the application of the laser pulses.

(5) In some embodiments, the IOL is a diffractive IOL or a refractive IOL and compensating for the photic phenomena includes at least partially compensating for the phase delay. In some embodiments, determining the photic phenomena can include measuring and mapping the phone phenomenon experienced by the subject. Determining the phase delay to compensate for at least one photic phenomena can include simulations of the optimal higher order aberrations induction based on pupil size analysis. The simulations of the optimal higher order aberrations induction can be based on subject response to photic phenomena.

(6) In some embodiments, compensating for the photic phenomenon includes refractive optimization, apodization, partial apodization, and/or profile reversion. The refractive optimization can include correcting, by the refractive index writing, at least one of defocus, astigmatism, and higher order aberrations. The apodization can include eliminating, by inverted phase delay, the diffractive or refractive IOL design in an outer part of the lens. The apodization phase delay can be determined using feedback from the subject relating to experiencing the phone phenomena. The apodization can include maintaining a central part of the diffractive design, where the peripheral

part is defined based on the specific photic phenomenon experienced by the subject.

(7) In some embodiments, the partial apodization includes modifying the percentage of light distributed between different foci of a multifocal IOL in an outer part of the lens. The profile reversion can include eliminating the full diffractive profile of the IOL.

(8) As an example, an adaptive optics (AO) system can be used to evaluate the level of higher-order aberrations that are needed to correct for the photic phenomenon, controlling the pupil size. The measurement of individual aberrations can be performed using, for example, wavefront sensors such as Hartmann-Shack sensors, and specialized software may be utilized to calculate an optimal phase map for the refractive index writing. In some embodiments, the simulations of the optimal higher order aberrations induction are based on subject response to photic phenomena.

(9) In some embodiments, correcting the higher order aberrations to compensate for the photic phenomenon can include performing an iterative, closed-loop correction process to correct one or more of the higher order aberrations of the subject. In some embodiments, the closed-loop correction process includes measuring the higher order aberrations associated with the vision of the subject and determining, based at least in part on the measurements, a target higher order aberration correction that can be at least one of: full correction of at least one of the higher order aberrations of the subject; partial correction of at least one of the higher order aberration of the subject; and induction of at least one higher order aberration. The method can also include applying a plurality of focused laser pulses to selected areas of the IOL, where the laser pulses are configured to produce, through refractive index writing, a target higher order aberration correction profile on the IOL.

(10) In some embodiments, the above-described closed-loop method also includes the steps of determining if the produced correcting profile meets the determined profile and, responsive to determining that the produced correcting profile does not meet the determined profile: measuring the difference between the higher order aberrations profile of the eye after the laser treatment and the target higher order aberrations correction and using this information to calculate the determined profile to achieve the target higher order aberration correction, and, based at least in part on the measured difference, applying a plurality of focused laser pulses to the IOL for refractive index writing, where the configuration of the laser pulses are modified from the prior applied laser pulses based on the measured difference, and repeating the above steps until the produced higher order aberration correcting profile meets the determined target higher order aberration correction.

(11) In another aspect, the present disclosure relates to a system for improving vision of a subject. In one embodiment, the system includes a pulsed laser system configured to apply laser pulses to an intraocular lens (IOL) implanted in an eye of a subject to change the refractive index of selected areas of the lens by refractive index writing. The system can also include a control system configured to receive data regarding a photic phenomenon of the eye of the subject after implantation of the IOL and use the received data to calculate a pattern of laser pulses and/or selected areas of the IOL to which the laser pulses are to be applied to produce a phase shift to compensate for the photic phenomenon. The control system can be coupled to the pulsed laser system and configured to control the pulsed laser system to apply the calculated pattern of laser pulses to the calculated selected areas of the IOL in order to produce, by refractive index writing on the IOL, the phase shift to compensate for the photic phenomenon. In some embodiments, the photic phenomenon can include a halo, starburst, and/or glare.

(12) In some embodiments, the control system can be configured to calculate the pattern of laser pulses and the selected areas of the IOL to produce a radially dependent phase shift. In some embodiments, the control system can be configured to calculate the pattern of laser pulses and the selected areas of the IOL to at least partially compensate for the phase delay of a diffractive IOL or a refractive IOL.

(13) In some embodiments, the system can also include at least one sensor coupled to the control system. The at least one sensor can be configured to collect data regarding the pupil size of the

subject and transmit the data regarding pupil size to the control system. The control system can be configured to compensate for the phase delay by using the data regarding pupil size to run simulations of optimal higher order aberrations to induce in the IOL to compensate for the photic phenomenon; and the control system can be configured to calculate the pattern of laser pulses and the selected areas of the IOL to induce the optimal higher order aberrations. In some embodiments, the simulations of the optimal higher order aberrations induced are based on subject response to photic phenomena.

(14) In some embodiments, compensating for the photic phenomenon can include: refractive optimization, apodization, partial apodization, and/or profile reversion. In some embodiments, the refractive optimization includes correcting, by the refractive index writing, at least one of defocus, astigmatism, and higher order aberrations.

(15) In some embodiments, the apodization can include eliminating, by inverted phase delay, the diffractive or refractive IOL design in an outer part of the lens. In some embodiments, the apodization can also include maintaining a central part of the diffractive design, wherein the peripheral part is defined based on the specific photic phenomenon experienced by the subject.

(16) In some embodiments, the partial apodization can include modifying the percentage of light distributed between different foci of a multifocal IOL in an outer part of the lens. In some embodiments, the profile reversion can include eliminating the full diffractive profile of the IOL.

(17) In some embodiments, the system can include at least one sensor coupled to the control system to measure higher order aberrations, and compensating for the photic phenomenon can include correcting the higher order aberrations. The control system can be configured to perform an iterative, closed-loop correction process to correct the higher order aberrations.

(18) Other aspects and features according to the present disclosure will become apparent to those of ordinary skill in the art, upon reviewing the following detailed description in conjunction with the accompanying figures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Reference will now be made to the accompanying drawings, which are not necessarily drawn to scale. Like reference numerals designate corresponding parts throughout the several views.

(2) FIG. 1A illustrates a side view of an eye containing a natural lens.

(3) FIG. 1B illustrates a side view of the eye shown in FIG. 1A with an implanted intraocular lens (IOL).

(4) FIG. 2 is a schematic diagram of an example optical system capable of implementing one or more aspects of the present disclosure in accordance with various embodiments.

(5) FIG. 3 shows is a diagram of an example computing system capable of performing various functions in accordance with one or more aspects and embodiments of the present disclosure.

(6) FIG. 4 illustrates phase addition of a presbyopia-correcting IOL and the phase addition needed to be introduced, by refractive index writing, to remove unwanted visual symptoms, in accordance with some embodiments of the present disclosure.

(7) FIG. 5A is an illustration of an IOL tilted with respect to the optical axis OA, and FIG. 5B is an illustration of an IOL decentered with respect to the optical axis OA.

(8) FIG. 6A illustrates a phase map (in waves of a 20 D monofocal IOL implanted in an average eye. FIG. 6B illustrates the phase map (in waves) induced by 5 degrees tilt of a 20 D monofocal IOL. FIG. 6C illustrates the phase map (in waves) induced by 0.5 mm decentration of a 20 D monofocal IOL.

(9) FIG. 7 plots the residual of a conventional phase profile with step size larger than a wavelength and its corresponding wrapped profile, in accordance with some embodiments of the present

disclosure.

(10) FIGS. **8A-8C** illustrate various aspects of phase wrapping in accordance with some embodiments of the present disclosure.

(11) FIGS. **9A** and **9B** illustrate aspects of vergence matching in accordance with some embodiments of the present disclosure.

(12) FIGS. **10A-10C** illustrate aspects of vergence matching with refractive index writing designs, in accordance with embodiments of the present disclosure.

(13) FIGS. **11** and **12** illustrate the radial dependence of the refractive index change for different thicknesses of the optical profile written inside the IOL, for power subtraction (FIG. **11**) and power addition (FIG. **12**), in accordance with embodiments of the present disclosure.

(14) FIGS. **13** and **14** illustrate the radial dependence of the refractive index change for different thicknesses of the optical profile written inside the IOL for spectacle independence, for negative added power (FIG. **13**) and positive added power (FIG. **14**), in accordance with embodiments of the present disclosure.

(15) FIG. **15** shows results of simulations in TCEM illustrating through frequency MTF with a comparison between an IOL with a refractive anterior and posterior surface (“refractive”), an IOL with refractive index writing without vergence matching (“grin_standard”), and an IOL with vergence matching according to some embodiments of the present disclosure (“refractive_grin_with_vergence_matching”).

(16) FIGS. **16** and **17** show the results of simulations in TCEM illustrating through frequency MTF (FIG. **16**) and through focus MTF at 50 c/mm (FIG. **17**), with a comparison between an IOL with a refractive anterior and posterior surface (“refractive”), an IOL with refractive index writing without vergence matching (“grin_standard”), an IOL like the grin_standard, but with the refractive index shrunk along the z axis in accordance with vergence matching in some embodiments described above (“grin_shrink”), and an IOL with refractive anterior and diffractive, elevated, posterior surface according to conventional diffractive IOLs (“diffractive sag”).

(17) FIGS. **18** and **19** show results illustrating a similar comparison for normalized polychromatic PSF (FIG. **18**) and polychromatic halo simulation (FIG. **19**).

(18) FIG. **20** shows simulated halo performance for a number of different designs: that of a standard refractive IOL (“refractive”), that of an extended depth of focus embodiment with vergence matching (“grin shrink”), that of an extended depth of focus embodiment IOL implemented with normal refractive index writing (“grin standard”), and the same extended depth of focus embodiment achieved by standard methods of elevated posterior surface (“diffractive sag”).

(19) FIG. **21** illustrates an IOL with multiple layers produced by refractive index writing according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

(20) Among other aspects, certain embodiments of the present disclosure relate to improving vision in a subject with an implanted intraocular lens (IOL) through the use of refractive index writing on the IOL. Refractive index writing (RIW) as described herein can utilize short pulses of focused irradiation focused on a selected area of an IOL in order to change the refractive index of the selected area and thereby modify optical performance of the IOL to correct post-surgical vision problems of the subject. For example, short and focused pulses of radiation from a visible or near-IR laser with a sufficient pulse energy can cause a nonlinear absorption of photons and lead to a change in the refractive index of the material at a focus point (in the selected area of the IOL) without affecting areas of the IOL outside of the selected area. Optical parameters of the pulsed radiation applied to the IOL, including the wavelength, pulse duration, frequency, and/energy can be configured to produce, by the refractive index writing, corrective patterns and/or structures on selected areas of the IOL to correct, e.g., to introduce a phase shift and modify the phase profile, of one or more portions of the IOL to improve vision in a subject. The pattern according to which the

pulses of radiation are applied can be in the form of a determined pulse sequence, for example, with the optical parameters as mentioned above incorporated

(21) According to some embodiments of the present disclosure, the starting point of a desired refractive index implementation is a phase map that has been shown to, for example, shift power, reduce residual astigmatism, improve near vision, improve spectacle independence, or reduce visual symptoms, among other undesired vision conditions and effects as described herein with respect to various embodiments. In some embodiments according to the present disclosure, calculations such as estimates and/or various measurements may be utilized in determining (e.g., designing) a phase map that corresponds to a pattern or other element(s) to be produced on a selected area (e.g., surface, interior portion) of an IOL in order to correct unwanted visual conditions and/or effects and reach a desired result in the modified IOL design. In accordance with some embodiments, a voxel-based treatment of the IOL is applied, wherein as one goes sequentially through each voxel, the desired shift in refractive index is applied, determined by total amount of light energy focused in the particular area and the duration of focus time.

(22) Although example embodiments of the present disclosure are explained in detail herein, it is to be understood that other embodiments are contemplated. Accordingly, it is not intended that the present disclosure be limited in its scope to the details of construction and arrangement of components set forth in the following description or illustrated in the drawings. The present disclosure is capable of other embodiments and of being practiced or carried out in various ways.

(23) It must also be noted that, as used in the specification and the appended claims, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise. By “comprising” or “containing” or “including” is meant that at least the named compound, element, particle, or method step is present in the composition or article or method, but does not exclude the presence of other compounds, materials, particles, method steps, even if the other such compounds, material, particles, method steps have the same function as what is named.

(24) In describing example embodiments, terminology will be resorted to for the sake of clarity. It is intended that each term contemplates its broadest meaning as understood by those skilled in the art and includes all technical equivalents that operate in a similar manner to accomplish a similar purpose. It is also to be understood that the mention of one or more steps of a method does not preclude the presence of additional method steps or intervening method steps between those steps expressly identified. Steps of a method may be performed in a different order than those described herein without departing from the scope of the present disclosure. Similarly, it is also to be understood that the mention of one or more components in a device or system does not preclude the presence of additional components or intervening components between those components expressly identified.

(25) Ranges may be expressed herein as from “about” one particular value, and/or to “about” another particular value. When such a range is expressed, an aspect includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another aspect. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint. As discussed herein, a “subject” or “patient” refers to any applicable human, animal, or other organism and may relate to specific components of the subject, in particular the eye of the subject and any applicable components such as various related muscles, tissues, and/or fluids.

(26) As used herein, the term “optical power” of a lens or optic means the ability of the lens or optic to converge or diverge light to provide a focus (real or virtual), and is specified in reciprocal meters or Diopters (D). As used herein the terms “focus” or “focal length” of a lens or optic is the reciprocal of the optical power. As used herein the term “power” of a lens or optic means optical power. Except where noted otherwise, optical power (either absolute or add power) of an intraocular lens or associated optic is from a reference plane associated with the lens or optic (e.g., a

principal plane of an optic).

(27) As used herein, the term “near vision” means vision produced by an eye that allows a subject to focus on objects that are at a distance of, for example 40 cm or closer to a subject, such as within a range of 25 cm to 33 cm from the subject, which corresponds to a distance at which a subject would generally place printed material for the purpose of reading. As used herein, the term “intermediate vision” means vision produced by an eye that allows a subject to focus on objects that are located, for example, between 40 cm and 2 meters from the subject. As used herein, the term “distant vision” means vision produced by an eye that allows a subject to focus on objects that are, for example at a distance that is greater than 2 meters, such as at a distance of about 5 meters from the subject, or at a distance of about 6 meters from the subject, or greater.

(28) Various aspects of the present disclosure will now be described, including aspects and embodiments discussed with reference to some example implementations and corresponding results, and the illustrations of FIGS. 1-21. Some experimental data are presented herein for purposes of illustration and should not be construed as limiting the scope of the present disclosure in any way or excluding any alternative or additional embodiments.

(29) Referring now to FIG. 1A, a cross-sectional view of a pseudo-phakic eye **10** containing the natural lens is shown, in which eye **10** includes a retina **12** that receives light in the form of an image produced when light from an object is focused by the combination of the optical powers of a cornea **14** and a natural lens **16**. The cornea **14** and lens **16** are generally disposed about an optical axis (OA). As a general convention, an anterior side is considered to be a side closer to the cornea **14**, while a posterior side is considered to be a side closer to the retina **12**.

(30) The natural lens **16** is enclosed within a capsular bag **20**, which is a thin membrane attached to a ciliary muscle **22** via zonules **24**. An iris **26**, disposed between the cornea **14** and the natural lens **16**, provides a variable pupil that dilates under lower lighting conditions (mesopic or scotopic vision) and constricts under brighter lighting conditions (photopic vision). The ciliary muscle **22**, via the zonules **24**, controls the shape and position of the natural lens **16**, allowing the eye **10** to focus on both distant and near objects. It is generally understood that distant vision is provided when the ciliary muscle **22** is relaxed, wherein the zonules **24** pull the natural lens **16** so that the capsular bag **20** and lens **16** are generally flatter and provide a longer focal length (lower optical power). It is generally understood that near vision is provided when the ciliary muscle contracts, thereby relaxing the zonules **24** and allowing the capsular bag **20** and lens **16** to return to a more rounded state that produces a shorter focal length (higher optical power).

(31) Referring now to FIG. 1B, a cross-sectional view of an eye **10'** is shown in which the natural crystalline lens **16** has been replaced by an intraocular lens (IOL) **100** according to one or more embodiments disclosed herein. The intraocular lens **100** can include an optic **102** and haptics **103**, the haptics **103** being configured to at least generally center the optic **102** within the capsular bag **20**, provide transfer of ocular forces to the optic **102**, and the like. Numerous configurations of haptics **103** relative to optic **102** are well known within the art, and the optics edge designs described herein can generally include any of these haptic configurations. Moreover, this disclosure contemplates that the methods described herein can be used to evaluate any IOL independently of the haptics configuration and/or optics design.

(32) Refractive Index Writing System

(33) FIG. 2 shows example of a system **200** capable of implementing one or more aspects of the present disclosure in accordance with various embodiments described in further detail throughout the present description. The example system of FIG. 2 includes a pulsed radiation system **202** including a light source configured to emit radiation such as laser pulses, a control system **204**, a relay unit **206**, eye with an implanted IOL **208**, and sensors **210**.

(34) In some embodiments, the light source of the pulsed radiation system **202** can be a femtosecond laser operating in the visible or near-infrared wavelength range, and pulsed according to a sequence (i.e., predetermined pattern of laser pulses having particular optical parameters as

mentioned in some examples described below) configured to produce a desired change in the IOL **208**. As some non-limiting examples, the optical parameters can include, for the emitted laser radiation pulses, a Gaussian or clipped beam profile, spot spacing between about 0.1 and 5 microns, and a pulse energy of up to about 500 nJ per pulse.

(35) In some embodiments, sensors **210** can include an optical coherence tomography (OCT) system for determining, for example, the IOL **208** location and position (x,y,z) and/or tilt or tip with respect to the direction of the emission of radiation from the pulsed radiation system **202**. The sensors **210** may alternatively or additionally include one or more of a wavefront sensor such as a Hartmann-Shack sensor, Aston Halometer, or Rostock Glare Perimeter, or other sensor(s) described herein in accordance with certain embodiments, that sense, detect, and/or measure attributes of the eye and/or IOL (**208**) associated with visual correction along the optical path of a subject's eye (e.g., eye **10** in FIGS. **1A** and **1B**) The relay unit **206**, in accordance with some embodiments, is configured to deliver the laser pulses to the IOL **208** and may be configured to collect and/or direct light, for example to collect OCT light for OCT images. The relay unit **206** may include one or more optical elements such as focusing lens(es) or mirrors to correctly direct the laser pulses to the intended points of the eye and/or IOL **208**

(36) Various aspects of refractive index changes required to achieve the correction, as sensed, detected and/or measured by the sensors **210**, for example, can be calculated by the use of a processor which may be, in some embodiments, included in the control system **204**. The processor may be the processing unit **302** shown in the computer **300** of FIG. **3**. The pulsed radiation can then be applied to the IOL at selected areas to achieve the determined correction, and the correction can subsequently be verified by the sensors **208**.

(37) In some embodiments, the control system **204** is configured to process sensed data from the sensors **210**, such as obtained OCT data, to control a scanning mirror for directing the pulsed radiation (e.g., laser pulses) according to a particular scan pattern, across one or more portions of the IOL **208**, and can control one or more through-focus optical elements. The control system **204**, in some embodiments, is configured to receive one or more treatment and control parameters (e.g. from sensors **210**) and to control the pulsed radiation system **202**, which can be a pulsed laser system.

(38) In some embodiments, the control system **204** can be configured to calculate, based on the treatment and control parameters, a pattern of laser pulses and/or selected areas of the IOL **208** to which the laser pulses are to be applied. The control system **204** can also be configured to control the pulsed laser system **202** to apply the calculated pattern of laser pulses to the calculated selected areas of the IOL **208** and thereby create a desired diffractive pattern in the IOL **208** (which can, in some embodiments, produce a phase shift). In some embodiments, the treatment and control parameters correspond to conditions (e.g., post-surgical states) and associated corrections that are needed to provide improved vision to the subject, for example residual spherical error, astigmatism, and others as described with respect to the various embodiments herein. In some embodiments, the cornea and/or anterior chamber are taken into account for the treatment and control parameters. For example, effects of refraction at the corneal surface may be taken into account to ensure that applied laser pulses are directed to an intended point within an IOL. In some embodiments, the treatment and control parameters may include specific attributes of the eye, for example the corneal topography.

(39) In various embodiments described herein, optical parameters of radiation applied to the IOL (as part of a calculated pattern, for example) can include, but are not limited to, the wavelength, pulse duration, frequency, energy, and/or other parameters can be specifically selected to produce, by the refractive index writing, a desired result, where the specific parameters depending upon the particular embodiments as described herein in which various types of corrections are needed to address various conditions to improve the vision of the subject. In describing some embodiments of the present disclosure below, particular operating parameters and other settings of a system such as

the system shown in FIG. 2 may be indicated.

(40) Example Computing System

(41) FIG. 3 is diagram showing a general computing system capable of implementing one or more embodiments of the present disclosure described herein. Computer **300** may be configured to perform one or more functions associated with embodiments described herein, for example embodiments illustrated in one or more of FIGS. 2 and/or 4-21. It should be appreciated that the computer **300** may be implemented within a single computing device or a computing system formed with multiple connected computing devices. For example, the computer **300** may be configured for a server computer, desktop computer, laptop computer, or mobile computing device such as a smartphone or tablet computer, or the computer **300** may be configured to perform various distributed computing tasks, which may distribute processing and/or storage resources among the multiple devices.

(42) As shown, the computer **300** includes a processing unit **302**, a system memory **304**, and a system bus **306** that couples the memory **304** to the processing unit **302**. The computer **300** further includes a mass storage device **312** for storing program modules. The program modules **314** may include modules executable to perform one or more functions associated with embodiments illustrated in one or more of FIGS. 2 and/or 4-21. For example, the program modules **314** may be executable to perform one or more of the functions for making determinations with respect to various optical attributes, performing calculations, and/or executing software (e.g., computer-executable instructions stored on non-transitory computer-readable media) as described herein with regard to specific embodiments. The mass storage device **312** further includes a data store **316**.

(43) The mass storage device **312** is connected to the processing unit **302** through a mass storage controller (not shown) connected to the bus **306**. The mass storage device **312** and its associated computer storage media provide non-volatile storage for the computer **300**. By way of example, and not limitation, computer-readable storage media (also referred to herein as “computer-readable storage medium” or “computer-storage media” or “computer-storage medium”) may include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-storage instructions, data structures, program modules, or other data. For example, computer-readable storage media includes, but is not limited to, RAM, ROM, EPROM, EEPROM, flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), HD-DVD, BLU-RAY, or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer **300**. Computer-readable storage media as described herein does not include transitory signals.

(44) According to various embodiments, the computer **300** may operate in a networked environment using connections to other local or remote computers through a network **318** via a network interface unit **310** connected to the bus **306**. The network interface unit **310** may facilitate connection of the computing device inputs and outputs to one or more suitable networks and/or connections such as a local area network (LAN), a wide area network (WAN), the Internet, a cellular network, a radio frequency network, a Bluetooth-enabled network, a Wi-Fi enabled network, a satellite-based network, or other wired and/or wireless networks for communication with external devices and/or systems. The computer **300** may also include an input/output controller **308** for receiving and processing input from a number of input devices. Input devices may include, but are not limited to, sensors (e.g., sensors **210**), keyboards, mice, stylus, touchscreens, microphones, audio capturing devices, or image/video capturing devices. An end user may utilize such input devices to interact with a user interface, for example a graphical user interface, for managing various functions performed by the computer **300**.

(45) The bus **306** may enable the processing unit **302** to read code and/or data to/from the mass storage device **312** or other computer-storage media. The computer-storage media may represent

apparatus in the form of storage elements that are implemented using any suitable technology, including but not limited to semiconductors, magnetic materials, optics, or the like. The program modules 314 may include software instructions that, when loaded into the processing unit 302 and executed, cause the computer 300 to provide functions associated with embodiments illustrated in FIGS. 2 and/or 4-21. The program modules 314 may also provide various tools or techniques by which the computer 300 may participate within the overall systems or operating environments using the components, flows, and data structures discussed throughout this description. In general, the program module 314 may, when loaded into the processing unit 302 and executed, transform the processing unit 302 and the overall computer 300 from a general-purpose computing system into a special-purpose computing system.

(46) As another example, the computer-storage media may be implemented using magnetic or optical technology. In such implementations, the program modules 314 may transform the physical state of magnetic or optical media, when the software is encoded therein. These transformations may include altering the magnetic characteristics of particular locations within given magnetic media. These transformations may also include altering the physical features or characteristics of particular locations within given optical media, to change the optical characteristics of those locations. Other transformations of physical media are possible without departing from the scope of the present disclosure.

(47) Correcting IOL Power

(48) Some aspects of the present disclosure relate to the use of refractive index writing to make negative or positive power additions to an implanted IOL to correct incorrect IOL power, which may be caused by pre-surgical incorrect IOL power calculations due to, for instance, limitations in biometry accuracy. Current post-surgical refractive conditions can include the need for both negative and positive power adjustment. In some embodiments, through the use of RIW to impose a phase pattern with a total phase addition of up to one lambda, with zone width calculated to achieve appropriate power change and the correct slope, both negative and positive additions can be made. Furthermore, alternative embodiments can include phase patterns with step height larger than one lambda which can achieve the desired monofocal shift.

(49) The process to adjust the power can be planned in advance. While adding positive diffractive power can reduce longitudinal chromatic aberrations (thereby increasing image quality), adding negative diffractive power can increase it. In accordance with certain embodiments, a postsurgical refractive index writing procedure is planned in the protocol, and therefore the power calculation for an IOL to be implanted in a subject can be intentionally set to leave the subject with a spherical error requiring an estimated positive addition. For example, IOL power can be calculated to leave a subject with a spherical error of +1.5D; with the range of expected spherical variation being 1.5 D, corrections can be made to improve a longitudinal chromatic aberration, and therefore, image quality.

(50) Spherical aberration (spherical error) of the added power can be controlled. While a default correction mode of solely adding power induces spherical aberration (the magnitude and sign of which depends on the spherical aberration that needs to be corrected), the correction factor, in accordance with some embodiments, does not alter the overall spherical aberration; this can be achieved by having the size of each zone in $r.\sup.2$ -space be non-uniform rather than fixed if the change in power is achieved with a diffractive phase pattern. Alternatively, spherical aberration can be combined with the spherical correction to modulate the refractive index change required along the r -space to create a refractive change in power. In some embodiments, some residual spherical aberration is left uncorrected, for example in cases where an extended depth of focus is desired.

(51) In some aspects of the present disclosure, according to one embodiment, an IOL is implanted in the eye of a subject, where the IOL is configured (pre-surgery) to, when implanted, leave a non-zero residual spherical error that requires an estimated diffractive power addition in the IOL. The IOL selected may be an IOL selected that would result in a particular average error, e.g., +2.5

diopters, according to, for instance, the Haigis formula. Furthermore, the estimation-calculation of the needed positive power addition can be performed based on several factors that are specific to a particular subject. For example, the calculations can be performed based on one or more of: estimated IOL power to target refraction, subject axial length, surgeon's optimized A constant or surgical factor, and/or effective lens position (ELP). The "A constant" refers to a personalized regression factor that accounts for individual differences in technique, and "axial length" refers to the distance between apex and the cornea and the retina.

(52) Regarding the refractive index writing, in some embodiments, a plurality of laser pulses are applied to selected area(s) of the implanted IOL, where the laser pulses are applied according to a predetermined pattern configured to produce, by the RIW, a positive diffractive power addition in the IOL that corrects for the residual spherical error and partially reduces or completely compensates for a longitudinal chromatic aberration of the eye. The applied laser pulses produce the positive diffractive power addition in the IOL in order to partially or fully correct for the longitudinal spherical chromatic aberration.

(53) In some embodiments, the power addition does not induce further spherical aberration or modify existing spherical aberration. In other embodiments, a spherical aberration change is induced by the RIW to change the size of diffractive profile zone(s) of the IOL in r.sup.2-space, such that there is non-uniform size of each zone in r.sup.2-space. In order to reduce spherical aberration there is higher spacing as high r.sup.2 values are approached, and in order to increase spherical aberration, there is lower spacing towards the high r.sup.2 values.

(54) In some embodiments, to compensate for the residual error(s) in the implanted IOL, a phase profile induced on the IOL by RIW is calculated based at least on the effective lens position (ELP). To create the profile, the postoperative refractive error in the spectacle plane needs to be converted to power shift on the IOL plane. In some embodiments, ELP measured during the refractive index writing procedure is utilized to calculate the correct conversion between spherical equivalent (SEQ) in the spectacle plane and power shift in the IOL plane for each individual subject using an average corneal eye or the subject's corneal power. The conversion can be implemented depending on the different eye models proposed. Refractive error is measured as, e.g., the optimal trial lenses to place outside the subject's eye to achieve emmetropia. In some embodiments, the RIW treatment can be personalized to account for ELP, rather than every subject receiving the same RIW treatment based on the size of the refractive error in diopters. The personalization can be calculated by various ways through implementing different IOL models, but have in common that they constitute a refractive calculation utilizing geometric optics or ray tracing simulation to achieve optimal focus on the retina.

(55) As table 1 (below) shows for an average eye, considering the ELP in the calculations with calculations of the estimated-desired power correction to be made in the IOL can significantly impact the outcomes.

(56) TABLE-US-00001 TABLE 1 Post-operative SEQ in Power shift in the IOL plane (D)
spectacle plane (D) ELP = 4.5 mm ELP = 4.7 mm -2 -2.72 -2.45 -1.5 -2.02 -1.74 -0.5 -0.68
-0.35 0.5 0.64 1.00 1.5 1.97 1.67 2 2.61 3.01

(57) One aspect of the present disclosure relates to a method for improving vision of a subject implanted with an intraocular lens (IOL) having a non-zero residual spherical error that requires an estimated diffractive power addition in the IOL. In one embodiment, the method can include applying a plurality of laser pulses to the IOL. The laser pulses can be configured to produce, by refractive index writing on the IOL, the estimated diffractive power addition to correct for the residual spherical error.

(58) In some embodiments, the power addition can be a positive diffractive power addition that at least partially reduces a longitudinal chromatic aberration of the eye. Applying the plurality of laser pulses can include applying a plurality of focused laser pulses according to a predetermined pattern to at least one selected area of the IOL, to produce the diffractive power addition. In some

embodiments, the estimated diffractive power addition fully compensates for the longitudinal chromatic aberration. The diffractive power addition can be estimated based at least in part on at least one of: estimated IOL power to target emmetropia; a subject's axial length; surgeon's optimized A constant; and/or effective lens position (ELP). In some embodiments, the laser pulses are configured and applied to the IOL such that the power addition does not induce further spherical aberration or modify existing spherical aberration.

(59) In some embodiments, control of the spherical aberration is performed at least in part by changing the phase profile of the IOL by refractive index writing. In some embodiments, control of the spherical aberration can be performed at least in part by changing, by the refractive index writing on the IOL, the size of diffractive profile zones in $r.\sup.2$ space. In some embodiments, a phase profile induced in the IOL to correct for residual errors is calculated based at least in part on effective lens position (ELP) measured during the refractive index writing.

(60) According to another aspect, the present disclosure relates to a method for improving vision of a subject implanted with an IOL that has a non-zero residual spherical error. In one embodiment, the method includes applying a plurality of laser pulses to the IOL. The laser pulses can be configured to produce, by refractive index writing on the IOL, an estimated positive diffractive power addition. A phase profile induced in the IOL to correct for residual errors can be calculated based at least in part on effective lens position (ELP) measured during the refractive index writing. In some embodiments, applying the plurality of laser pulses comprises applying a plurality of focused laser pulses to at least one selected area of the IOL to produce, by the refractive index writing on the IOL, the diffractive power addition in the IOL.

(61) In some embodiments, the diffractive power addition at least partially corrects a longitudinal chromatic aberration of the eye. The diffractive power addition can be estimated based at least in part on at least one of: estimated IOL power to target emmetropia; a subject's axial length; and surgeon's optimized A constant. In some embodiments, the laser pulses are configured and applied to the IOL such that the power addition does not induce further spherical aberration or modify existing spherical aberration. Control of the spherical aberration can be performed at least in part by changing, by the refractive index writing on the IOL, the size of diffractive profile zones in $r.\sup.2$ space.

(62) In another aspect, the present disclosure relates to a system for improving vision of a subject. In one embodiment, the system includes a pulsed laser system configured to apply laser pulses to an intraocular lens (IOL) implanted in an eye of a subject to change the refractive index of selected areas of the lens by refractive index writing. The system can also include a control system configured to receive data regarding a non-zero residual spherical error of the eye of the subject after implantation of the IOL and estimate a diffractive power addition to the IOL required to either partially or fully correct the non-zero residual spherical error. The control system can be coupled to the pulsed laser system and configured to control the pulsed laser system to apply a plurality of laser pulses to the IOL. The laser pulses can be configured to produce, by refractive index writing on the IOL, the estimated diffractive power addition.

(63) In some embodiments, the control system is configured to estimate the diffractive power addition such that the diffractive power addition reduces a longitudinal chromatic aberration of the eye. In some embodiments, the pulsed laser system is configured to apply a plurality of focused laser pulses to at least one selected area of the IOL to produce, by the refractive index writing on the IOL, the estimated diffractive power addition in the IOL. The estimated diffractive power addition can fully compensate for the longitudinal chromatic aberration of the eye. In some embodiments, the diffractive power addition can be estimated based at least in part on IOL power to achieve emmetropia. In some embodiments, the diffractive power addition is estimated based at least in part on the axial length of the subject's eye. In some embodiments, the diffractive power addition is estimated based at least in part on the effective lens position (ELP) of the IOL in the subject's eye.

(64) In some embodiments, the control system is configured to control the pulsed laser system to apply the plurality of laser pulses to the IOL such that the power addition does not induce further spherical aberration or modify existing spherical aberration of the IOL. In some embodiments, at least the control system is configured to control the pulsed laser system to control spherical aberration at least in part by changing, by the refractive index writing on the IOL, the size of diffractive profile zones in $r.\sup.2$ space. The control system can be configured to estimate, based at least in part on effective lens position (ELP) measured during the refractive index writing, the phase profile induced in the IOL. In some embodiments, the system can also include a sensor to measure the non-zero residual spherical error of the eye of the subject and transmit sensed data associated with the non-zero residual spherical error to the control system.

(65) Correcting Astigmatism

(66) Uncorrected astigmatism results in impaired contrast sensitivity and visual acuity, which has safety implications for subjects. Although a toric IOL can be implanted to correct for corneal astigmatism, residual astigmatism is common after cataract surgery due to different factors like surgically induced astigmatism, effect of posterior corneal astigmatism, incorrect toric IOL power determination, toric IOL rotation or misplacement, and/or use of non-toric IOLs in toric corneas. A conventional procedure to calculate the zone radii of full lambda phase shift to correct for a spherical error F is to use the formula:

$$(67) r = \sqrt{m^2 \frac{\lambda}{F}}$$

(68) where λ is the wavelength, m is a natural number (1, 2, 3, . . .) and F the power.

(69) In accordance with some embodiments of the present disclosure, the phase profile induction is modified to include an angular dependence; in some embodiments, the following calculation is utilized:

$$(70) r = \sqrt{m \frac{\lambda}{F_1 + (F_2 - F_1) \cdot \sin^2 \theta}} \quad (1)$$

where θ is the angle, and F1 and F2 the power to be corrected in the respective meridians. This can be used to correct the astigmatism of the subject.

(71) In some embodiments of the present disclosure, a method for improving vision of a subject having an implanted intraocular lens (IOL) includes the steps of: determined a modification of a phase profile on the IOL to correct an astigmatism; and applying a plurality of focused laser pulses to one or more selected areas of the IOL, where the laser pulses are configured to produce, by refractive index writing on the IOL, the determined modification of the phase profile on the IOL. Determining the modification of the phase profile includes calculating a radius of a phase shift for correcting for a residual spherical error, the radius being calculated according to factors that include an angular dependence. The radius of the phase shift can be calculated by the above-described equation (1) above.

(72) Spectacle Independence

(73) Spectacle dependence can be due to monofocal IOL implantation, for example, or incorrect selection of a suitable presbyopia-correcting IOL for a particular subject. Presbyopia-correcting intraocular lenses (PC IOLs) that make subjects spectacle independent can be highly desired. While spectacle independence is the expected result of cataract surgery with certain presbyopia-correcting IOLs, some subjects receiving those IOLs may still need to wear spectacles (i.e., they are still spectacle dependent) for the above-stated or other reasons. Parameters related to spectacle dependence include through-focus visual acuity of the subject, comfortable reading distance of the subject, subject biometry (such as at least one of axial length of the subject's eye IOL position, and corneal power), subject-specific reading habits (including reading distances), pupil size and subject-specific data indicating common lifestyle tasks performed by the subject and/or lighting conditions associated with respective tasks.

(74) In accordance with some embodiments of the present disclosure, subjects who have previously had monofocal IOLs surgically implanted can benefit from a refractive index writing (RIW) that

produces phase profiles similar to those in presbyopia-correcting IOLs, for example phase profiles shown and described in one or more of the following published patent applications, which are incorporated herein by reference: U.S. Patent Application Publication Nos. 2018-0368972; 2019/0004335; 2010/0004333; 2019/0004221. Certain embodiments provide for the specific application of many desired phase profiles in-vivo. Further, according to some embodiments, RIW can be used to convert a particular PC IOL treatment into another that may be more suitable for the subject. For example, if the subject gets an extended depth of focus IOL but after surgery is not satisfied with near vision, refractive index writing can be used to write another design that better suits the subject's spectacle independence needs. Alternatively, if the subject is not satisfied by the distance image quality or the intermediate performance provided by a particular design aimed to provide a higher degree of spectacle independence, refractive index writing can be used to write another design with a greater quality of vision or better intermediate vision.

(75) There is an important relationship between through focus visual acuity (VA) and rates of spectacle independence. While IOLs have an expected average through focus VA curve, which is related to expected rates of spectacle independence, individual through focus VA curves can radically differ from the expected curves, and as a result, individual subjects might need to wear spectacles. For instance, an individual subject might have a lower than expected VA at 30 cm, 40 cm, or 50 cm. In accordance with some embodiments of the present disclosure, a particular subject's through focus VA curve is measured, and the results are combined with an algorithm to predict spectacle independence from through focus VA. A multifocal addition produced by refractive index writing can be implemented to produce a certain phase change in the IOL which most optimally benefits spectacle independence for a particular subject's needs, for example improved VA at 30 cm, 40 cm, or 50 cm.

(76) Improving spectacle independence may include improving the subject's through-focus visual acuity at one or more first distances (optionally while maintaining the subject's through-focus visual acuity at one or more second distances), extending depth of focus of the IOL, providing the IOL with at least partial presbyopia correction, improving presbyopia correction of the IOL and adapting presbyopia correction of the IOL to subject-specific requirements such as subject biometry or subject-specific lifestyle data.

(77) Predicting the spectacle independence can, in some embodiments, utilize a Bayesian analysis method, involving calculating the probability of achieving spectacle independence for at least two IOLs based on at least one of: clinical data providing visual acuity at a second defocus position for the at least two IOLs in the population; standard deviation of pre-clinical visual acuity for the at least two IOLs at the first or the second defocus positions; clinical data providing minimum readable print size in mm in the population; modulation transfer function (MTF) at one or more frequencies at different distances for different pupil sizes; and/or area under the modulation transfer function at one or more frequencies at different distances for different pupil sizes.

(78) The Bayesian analysis method can be expanded to incorporate other characteristics of the subjects, such as age, gender, eye length, pupil size, ethnicity, corneal aberrations, life style or combinations thereof. The Bayesian analysis method of estimating spectacle independence for different parameters can be incorporated in an IOL design and/or manufacturing process. The parameter space of IOL design allows variation of IOL characteristics such as radii of curvature, diffraction power, diffraction step height, transition zones and IOL thickness. These characteristics can be used in a ray tracing simulation software to predict through focus MTF, which can predict VA. Using Bayesian analysis, the probability of spectacle independence can be calculated, and the IOL characteristics optimized such that the highest possible spectacle independence is achieved, in conjunction with other simulated and desired constraints such as distance image quality. Bayesian analysis can also be used to predict how suitable certain treatment techniques, such as making the subjects slightly myopic postoperatively can positively affect spectacle independence. Bayesian analysis to estimate spectacle independence can also be used to select an IOL for implantation in a

subject that would increase the chance of the subject to be spectacle independent for a variety of tasks such as reading, viewing a smartphone, computer use or combinations thereof.

(79) In some embodiments, diagnostics combined with customization of IOLs using RIW can provide customized results that take into account subject-specific individualized factors including one or more of: the subject's common reading behavior, for example his/her preferred reading distance; pupil size considerations along with the lighting conditions present during common tasks the subject performs in daily life; and/or aberrations of both eyes of the subject, for optimizing binocular vision by matching the aberrations in order to result in optimal (e.g., highest) depth perception.

(80) In one aspect, the present disclosure relates to a method for improving vision of a subject having an implanted intraocular lens (IOL). In one embodiment, the method includes applying a plurality of laser pulses to the IOL. The laser pulses can be configured to produce, by refractive index writing on the IOL, a predetermined change in phase profile of the IOL to increase spectacle independence. In some embodiments, applying the plurality of laser pulses includes applying a plurality of focused laser pulses according to a predetermined pattern to at least one selected area of the IOL to produce the predetermined change in phase profile.

(81) In some embodiments, the predetermined change in phase profile to improve spectacle independence can be determined by performing functions that include, prior to the application of the laser pulses to the IOL, acquiring measurements that include measurements associated with subject-specific through-focus visual acuity. The functions performed can also include predicting based at least in part on the acquired measurements, an estimated phase profile for increasing near vision for the subject while maintaining distance vision, or for the increasing of distance vision for the subject while maintaining near vision and intermediate vision. In some embodiments, the phase delay is estimated based at least in part on measurements associated with subject-specific through-focus visual acuity. In some embodiments, the IOL is a multifocal IOL and the refractive index writing produces a phase profile on the IOL that changes the add power of the multifocal IOL.

(82) In some embodiments, the change of the add power produced by the refractive index writing phase profile is calculated based on at least one of: through focus visual acuity of the subject; comfortable reading distance of the subject; and/or subject biometry. The subject biometry can include at least one of axial length of the subject's eye, IOL position, and/or corneal power.

(83) In some embodiments, the predetermined change in phase profile is determined, prior to the application of the laser pulses to the IOL, based at least in part on: subject-specific reading habits, including reading distances; pupil size; and/or subject-specific data indicating common lifestyle tasks performed by the subject and lighting conditions associated with respective tasks. In some embodiments, the IOL is a diffractive IOL or a multifocal refractive IOL. In some embodiments, the change in phase profile is estimated by calculating the phase difference between the existing phase profile of the implanted IOL and the desired phase profile expected after the refractive index writing.

(84) In another aspect, the present disclosure relates to a method for improving vision of a subject having an implanted intraocular lens. In one embodiment, the method can include applying a plurality of laser pulses to the IOL; the laser pulses can be configured to produce, by refractive index writing on the IOL, a predetermined change in phase profile of the IOL to increase spectacle independence. The predetermined change in phase profile can be determined at least in part on measurements associated with subject-specific through-focus visual acuity. The measurements can be acquired prior to the application of the laser pulses to the IOL. Applying the plurality of laser pulses can include applying a plurality of focused laser pulses according to a predetermined pattern to at least one selected area of the IOL to produce the predetermined change in phase profile.

(85) In some embodiments, the predetermined change in phase profile to improve spectacle independence can be determined by performing functions that include predicting, based at least in part on the acquired measurements, an estimated phase profile for increasing near vision for the

subject while maintaining distance vision, or the increasing of distance vision for the subject while maintaining near vision.

(86) In some embodiments, the predetermined change in phase profile to improve spectacle independence can be determined by performing functions that include predicting, based at least in part on the acquired measurements, an estimated phase profile for increasing intermediate vision for the subject while maintaining distance vision, or the increasing of distance vision for the subject while maintaining intermediate vision.

(87) In some embodiments, the predetermined change in phase profile to improve spectacle independence can be determined by performing functions that include predicting, based at least in part on the acquired measurements, an estimated phase profile for increasing intermediate vision for the patient while maintaining near vision, or the increasing of near vision for the patient while maintaining intermediate vision.

(88) In some embodiments, the phase delay can be estimated based at least in part on measurements associated with subject-specific through-focus visual acuity. In some embodiments, the IOL can be a multifocal IOL and the refractive index writing produces a phase profile to change the add power of the multifocal IOL. In some embodiments, the change of the add power produced by the refractive index writing of the phase profile can be calculated based on: through-focus visual acuity of the subject; comfortable reading distance of the subject; and/or subject biometry. The subject biometry can include axial length, IOL position, and/or corneal power.

(89) In some embodiments, the predetermined change in phase profile is determined, prior to the application of the laser pulses to the IOL, based at least in part on: subject-specific reading habits, including: reading distances; pupil size; and/or subject-specific data indicating common lifestyle tasks performed by the subject and lighting conditions associated with respective tasks.

(90) In some embodiments, the IOL can be a diffractive IOL or a multifocal refractive IOL. In some embodiments, the change in phase profile is estimated by calculating the phase difference between the existing phase profile of the implanted IOL and the desired phase profile expected after the refractive index writing.

(91) In another aspect, the present disclosure relates to a system for improving vision of a subject. In one embodiment, the system includes a pulsed laser system configured to apply a plurality of laser pulses to selected areas of an intraocular lens (IOL) implanted in an eye of a subject to change the refractive index of the selected areas by refractive index writing. The system can also include a control system configured to receive parameters related to spectacle dependence of the eye of the subject after implementation of the IOL and to calculate, based on the parameters, a pattern of laser pulses and selected areas of the intraocular lens to which the laser pulses are to be applied to provide a change in phase profile of the IOL to increase spectacle independence. The control system can be coupled to the pulsed laser system and configured to control the pulsed laser system to apply the calculated pattern of laser pulses to the calculated selected areas of the intraocular lens.

(92) In some embodiments, the parameters related to spectacle dependence can include measurements associated with subject-specific through-focus visual acuity. In some embodiments, the control system can be configured to determine the change in phase profile. In some embodiments, determining the change in phase profile can include predicting, based at least in part on the subject-specific through-focus visual acuity measurements, an estimated phase profile for increasing near vision for the subject while maintaining distance vision, or for increasing distance vision for the subject while maintaining near vision.

(93) In some embodiments, the parameters related to spectacle dependence include measurements associated with subject-specific through-focus visual acuity, wherein the control system is configured to determine the change in phase profile. Determining the change in phase profile can include predicting, based at least in part on the subject-specific through-focus visual acuity measurements, an estimated phase profile for increasing intermediate vision for the subject while maintaining distance vision, or increasing distance vision for the subject while maintaining

intermediate vision.

(94) In some embodiments, the parameters related to spectacle dependence include measurements associated with subject-specific through-focus visual acuity, wherein the control system is configured to determine the change in phase profile, and wherein determining the change in phase profile can include: predicting, based at least in part on the subject-specific through-focus visual acuity measurements, an estimated phase profile for increasing intermediate vision for the subject while maintaining near vision, or for increasing near vision for the subject while maintaining intermediate vision. In some embodiments, the control system can be configured to estimate phase delay based at least in part on measurements associated with subject-specific through-focus visual acuity. In some embodiments, the IOL can be a multifocal IOL and the refractive index writing can produce a phase profile on the IOL that changes the add power of the multifocal IOL.

(95) In some embodiments, the control system can be configured to calculate the change of the add power produced by the refractive index writing phase profile based on at least one of: through-focus visual acuity of the subject; comfortable reading distance of the subject; and/or subject biometry. In some embodiments, the subject biometry can include axial length of the subject's eye, IOL position, and/or corneal power.

(96) In some embodiments, the control system can be configured to determine the change in phase profile, prior to the application of the laser pulses to the IOL, based at least in part on: subject-specific reading habits, including reading distances; pupil size; and/or subject-specific data indicating common lifestyle tasks performed by the subject and/or lighting conditions associated with respective tasks. In some embodiments, the parameters related to spectacle dependence include: through-focus visual acuity of the subject; comfortable reading distance of the subject; subject biometry, such as at least one of axial length of the subject's eye, IOL position, and/or corneal power; subject-specific reading habits, including reading distances; pupil size; and/or subject-specific data indicating common lifestyle tasks performed by the subject and/or lighting conditions associated with respective tasks. In some embodiments, the IOL can be a diffractive IOL or a multifocal refractive IOL.

(97) In some embodiments, the change in phase profile can be estimated by calculating a phase difference between an existing phase profile of the implanted IOL and a desired phase profile expected after the refractive index writing. In some embodiments, improving spectacle independence includes one or more of: improving the subject's through-focus visual acuity at one or more distances; improving the subject's through-focus visual acuity at one or more first distances while maintaining the subject's through-focus visual acuity at one or more second distances; extending depth of focus of the IOL; providing the IOL with at least partial presbyopia correction; improving presbyopia correction of the IOL; and adapting presbyopia correction of the IOL to subject-specific requirements, such as subject biometry or subject-specific lifestyle data.

(98) Photoc Phenomenon

(99) Unwanted visual symptoms due to the presence of unwanted light for subjects, also referred to herein as "photoc phenomenon" include but are not limited to: halos, starbursts, and glare. Such unwanted visual symptoms tend to be more commonly experienced in subjects after the surgical implantation of a presbyopia-correcting intraocular lenses. For multifocal IOLs, the out of focus light can form a halo around the main image. The presence of unwanted visual symptoms strongly depends on the specific IOL design, but there is also a significant subjective component. For that reason, for two subjects with similar objective ocular conditions, one may not experience unwanted visual symptoms while the other may experience them and express complaints about the condition. Although medical professionals can make great efforts to select monofocal refractive IOLs for subjects with a high risk of experiencing unwanted post-surgical visual symptoms, such symptoms can be difficult to predict, particularly on a subject-by-subject basis.

(100) As mentioned above, while medical professionals can go to great length to ensure subject expectations are managed prior to IOL implantation surgery, some subjects nevertheless realize

after surgery that they would have preferred a monofocal IOLs or a lens that would provide a lower degree of photic phenomena. Rather than requiring the IOL to be surgically replaced, which can be a complicated and risky procedure, in accordance with some embodiments of the present disclosure refractive index writing is used to remove or substitute the optical design causing the unwanted visual symptoms. As shown in FIG. 4, according to one example implementation, the diffractive profile **402** introduces a radially dependent phase shift; this phase shift also creates unwanted visual symptoms. According to some embodiments, a radially dependent phase shift **404** is introduced to compensate, such that the IOL can be rendered monofocal, removing the unwanted visual symptoms. That is, in FIG. 4, the portion **402** illustrates phase addition of a presbyopia-correcting IOL, and the portion **404** illustrates the phase addition needed to be introduced, by refractive index writing, to remove the unwanted visual symptoms. In some embodiments of the presented disclosure, the phase delay introduced by a diffractive IOL is fully compensated. In other embodiments of the present disclosure, a partial compensation of the profile may be performed, or the creation of another profile that is expected to create less visual disturbances for a particular subject and therefore a better quality of vision.

(101) In some embodiments as discussed above, a phase-compensation technique by RIW is used to eliminate all visual symptoms of a diffractive and refractive IOL, by fully compensating the added phase. This can also eliminate the spectacle independence created by the IOL, however. In accordance with some embodiments, a subject-specific, personalized approach is taken that can enable certain subjects to receive a desirable compromise of reduced unwanted visual symptoms and maintained spectacle independence. In accordance with some embodiments of the present disclosure described below, this compromise-type approach can include: 1. a personalized diagnostic procedure mapping when intolerable levels of visual symptoms occur; 2. a personalized correction involving refractive optimization, apodization, and/or profile reversion; and 3. a diagnostic procedure verifying satisfactory reduction of unwanted visual symptoms.

(102) In some embodiments, the use of such approaches can be combined with simulated optical manipulations, including modulating the pupil size, and higher order aberrations. Certain pupil sizes and higher order aberrations interact with the diffractive design to exacerbate the visual symptoms, and this step would measure this on a personalized level.

(103) With respect to the above-mentioned personalized diagnostic procedure mapping when intolerable levels of visual symptoms occur, fully subjective, psychophysical, and/or objective approaches can be used for measuring and mapping unwanted visual symptoms, including halos, glare and starbursts. These may include one or more aspects and embodiments shown and described in U.S. patent application Ser. No. 16/271,648, entitled “Psychophysical Method to Characterize Visual Symptoms”, filed Feb. 8, 2019, which is hereby incorporated by reference. Fully subjective approaches include, for example, the use of questionnaires to solicit feedback from a particular subject in order to receive, for instance, descriptions and/or drawings that articulate the photic phenomena he/she is experiencing. Psychophysical approaches include, for example, use of commercially available devices such as an Aston Halometer and/or a Rostock Glare Perimeter, which can quantify halos. Objective approaches can include wavefront-based methods, such as the Objective Scatter Index.

(104) With respect to the above-mentioned personalized correction involving refractive optimization, apodization, and/or profile reversion, refractive optimization includes correcting one or more of defocus, astigmatism, and higher order aberrations. Regarding apodization, the peripheral part of the diffractive design, e.g., 4 mm and higher diameter, or 3 mm and higher diameter, can be eliminated, while the central part can be kept; additionally, multifocality can be modified in the peripheral part of the IOL to allow a different light distribution between the different foci, for example, to increase the amount of light that goes to the far focus and therefore, reducing the amount of light that goes to the near and/or focus. The diameter can be chosen based on individual results. In profile reversion, the full multifocal profile of the IOL is eliminated and a

monofocal profile created.

(105) With respect to the above-mentioned verification of satisfactory reduction of unwanted visual symptoms for the subject, through a diagnostic procedure, refractive optimization, apodization, and/or profile reversion can be done independently or sequentially to eliminate unwanted visual symptoms. Additionally, apodization can be performed using subject feedback by eliminating multifocality in the outer parts of the IOL and, if more reduction is desired, a further elimination of multifocality to a lower radius.

(106) In some embodiments, refractive index writing is implemented to provide a phase addition that simulations show would decrease the unwanted visual phenomenon. For example, if a subject complains about halo effects, then the added phase is configured such that it results in smaller magnitude of light outside the focus according to simulations. As another example, if a subject complained about experiencing rings and spiderwebs, then the simulation should result in lower variance in simulated light levels (light intensity going up and down as a function of radius).

According to some embodiments, this can be particularly useful to simulate on an individual basis to include the interaction effect between higher order aberrations and unwanted visual symptoms.

(107) In one aspect, the present disclosure relates to a method for improving vision of a subject having an implanted intraocular lens (IOL). In one embodiment, the method includes determining at least one photic phenomenon experienced by the subject after implantation of the IOL; and applying a plurality of laser pulses to the IOL. The laser pulses can be configured to produce, by refractive index writing on the IOL, a phase shift in the IOL to compensate for the phone phenomenon.

(108) In some embodiments, applying the plurality of laser pulses includes applying a plurality of focused laser pulses, according to a predetermined pattern, to at least one selected area of the IOL to produce, by the refractive index writing on the IOL, the phase shift. The phone phenomenon can include a halo, starburst, and/or glare. In some embodiments, the phase shift can include a radially dependent phase shift. In some embodiments, the method can include verifying correction of the at least one photic phenomenon following the application of the laser pulses. Verifying the correction can be performed by incorporating subject feedback provided following the application of the laser pulses.

(109) In some embodiments, the IOL is a diffractive IOL or a refractive IOL and compensating for the photic phenomena includes at least partially compensating for the phase delay. In some embodiments, determining the photic phenomena can include measuring and mapping the phone phenomenon experienced by the subject. Determining the phase delay to compensate for at least one photic phenomena can include simulations of the optimal higher order aberrations induction based on pupil size analysis. The simulations of the optimal higher order aberrations induction can be based on subject response to photic phenomena.

(110) In some embodiments, compensating for the photic phenomenon includes refractive optimization, apodization, partial apodization, and/or profile reversion. The refractive optimization can include correcting, by the refractive index writing, at least one of defocus, astigmatism, and higher order aberrations. The apodization can include eliminating, by inverted phase delay, the diffractive or refractive IOL design in an outer part of the lens. The apodization phase delay can be determined using feedback from the subject relating to experiencing the phone phenomena. The apodization can include maintaining a central part of the diffractive design, where the peripheral part is defined based on the specific photic phenomenon experienced by the subject.

(111) In some embodiments, the partial apodization includes modifying the percentage of light distributed between different foci of a multifocal IOL in an outer part of the lens. The profile reversion can include eliminating the full diffractive profile of the IOL.

(112) As an example, an adaptive optics (AO) system can be used to evaluate the level of higher-order aberrations that are needed to correct for the photic phenomenon, controlling the pupil size. The measurement of individual aberrations can be performed using, for example, wavefront sensors

such as Hartmann-Shack sensors, and specialized software may be utilized to calculate an optimal phase map for the refractive index writing. In some embodiments, the simulations of the optimal higher order aberrations induction are based on subject response to photic phenomena.

(113) In some embodiments, correcting the higher order aberrations to compensate for the phone phenomenon can include performing an iterative, closed-loop correction process to correct one or more of the higher order aberrations of the subject. In some embodiments, the closed-loop correction process includes measuring the higher order aberrations associated with the vision of the subject and determining, based at least in part on the measurements, a target higher order aberration correction that can be at least one of: full correction of at least one of the higher order aberrations of the subject; partial correction of at least one of the higher order aberration of the subject; and induction of at least one higher order aberration. The method can also include applying a plurality of focused laser pulses to selected areas of the IOL, where the laser pulses are configured to produce, through refractive index writing, a target higher order aberration correction profile on the IOL.

(114) In some embodiments, the above-described closed-loop method also includes the steps of determining if the produced correcting profile meets the determined profile and, responsive to determining that the produced correcting profile does not meet the determined profile: measuring the difference between the higher order aberrations profile of the eye after the laser treatment and the target higher order aberrations correction and using this information to calculate the determined profile to achieve the target higher order aberration correction, and, based at least in part on the measured difference, applying a plurality of focused laser pulses to the IOL for refractive index writing, where the configuration of the laser pulses are modified from the prior applied laser pulses based on the measured difference, and repeating the above steps until the produced higher order aberration correcting profile meets the determined target higher order aberration correction.

(115) In another aspect, the present disclosure relates to a system for improving vision of a subject. In one embodiment, the system includes a pulsed laser system configured to apply laser pulses to an intraocular lens (IOL) implanted in an eye of a subject to change the refractive index of selected areas of the lens by refractive index writing. The system can also include a control system configured to receive data regarding a photic phenomenon of the eye of the subject after implantation of the IOL and use the received data to calculate a pattern of laser pulses and/or selected areas of the IOL to which the laser pulses are to be applied to produce a phase shift to compensate for the photic phenomenon. The control system can be coupled to the pulsed laser system and configured to control the pulsed laser system to apply the calculated pattern of laser pulses to the calculated selected areas of the IOL in order to produce, by refractive index writing on the IOL, the phase shift to compensate for the photic phenomenon. In some embodiments, the photic phenomenon can include a halo, starburst, and/or glare.

(116) In some embodiments, the control system can be configured to calculate the pattern of laser pulses and the selected areas of the IOL to produce a radially dependent phase shift. In some embodiments, the control system can be configured to calculate the pattern of laser pulses and the selected areas of the IOL to at least partially compensate for the phase delay of a diffractive IOL or a refractive IOL.

(117) In some embodiments, the system can also include at least one sensor coupled to the control system. The at least one sensor can be configured to collect data regarding the pupil size of the subject and transmit the data regarding pupil size to the control system. The control system can be configured to compensate for the phase delay by using the data regarding pupil size to run simulations of optimal higher order aberrations to induce in the IOL to compensate for the phone phenomenon; and the control system can be configured to calculate the pattern of laser pulses and the selected areas of the IOL to induce the optimal higher order aberrations. In some embodiments, the simulations of the optimal higher order aberrations induced are based on subject response to photic phenomena.

(118) In some embodiments, compensating for the photic phenomenon can include: refractive optimization, apodization, partial apodization, and/or profile reversion. In some embodiments, the refractive optimization includes correcting, by the refractive index writing, at least one of defocus, astigmatism, and higher order aberrations.

(119) In some embodiments, the apodization can include eliminating, by inverted phase delay, the diffractive or refractive IOL design in an outer part of the lens. In some embodiments, the apodization can also include maintaining a central part of the diffractive design, wherein the peripheral part is defined based on the specific photic phenomenon experienced by the subject.

(120) In some embodiments, the partial apodization can include modifying the percentage of light distributed between different foci of a multifocal IOL in an outer part of the lens. In some embodiments, the profile reversion can include eliminating the full diffractive profile of the IOL.

(121) In some embodiments, the system can include at least one sensor coupled to the control system to measure higher order aberrations, and compensating for the photic phenomenon can include correcting the higher order aberrations. The control system can be configured to perform an iterative, closed-loop correction process to correct the higher order aberrations.

(122) Negative Dysphotopsia

(123) Negative dysphotopsia (ND) can be characterized by subjective reports and complaints from subjects having an intraocular lens (IOL) implanted, where the complaints describe the presence of a dark shadow in the far periphery. A number of subject factors, including small photopic pupil, high angle kappa and hyperopia, have been identified as increasing the risk of ND. The presence of ND is likely caused by absence of light in the retinal interval between light passing through and refracted by the IOL (e.g., at lower angles of incidence) and rays missing the IOL (e.g., at higher angles of incidence). While the light passing the IOL at the lower angles of incidence is refracted, changing its direction to a lower angle, the light at the higher angles miss the IOL and continue straight without deviation, thereby creating an angular interval on the retina that is not illuminated. The problem is partially alleviated at larger pupil sizes, since optical errors create larger deviations of rays at the pupil edge which partially hits the obscured part of the peripheral retina.

(124) As described above, negative dysphotopsia can result if there is a discontinuity in ray deviation between rays missing the IOL and rays being refracted by the IOL. In order to address this condition, in accordance with some embodiments of the present disclosure, a gradual outer phase prism is applied in the outermost part of the IOL (e.g., 0.5 mm from the edge of optic body) using refractive index writing procedure in subjects that complain of ND after IOL implantation. The result can be to gradually deviate the chief ray, bridging the gap between rays missing and rays being refracted by the IOL, eliminating or reducing the shadow. The phase prism can be defined based on the power of the IOL (e.g., from 5.0 to 34.0 D) and the extension of the prism (from the edge to the center of the IOL). The procedure can be independent of the IOL design (refractive or diffractive) and the IOL platform.

(125) Consistent with one or more aspects described above, and in accordance with some embodiments of the present disclosure, a method for improving vision of a subject having an implanted intraocular lens (IOL) can include determining parameters of a phase prism to be produced on the IOL to correct negative dysphotopsia, where the determining comprising defining the phase prism based on power of the IOL and extension of the prism from respective outer edges of the IOL to the center of the IOL. The method can also include applying a plurality of focused laser pulses to the IOL at the selected areas, where the laser pulses are configured to produce, through refractive index writing on the IOL, the phase prism having the determined parameters in at least one outermost portion proximate the outer edges of the IOL. In some embodiments, the phase prism, as produced by the RIW on the IOL, is configured to gradually deviate a chief ray to correct a discontinuity in ray deviation between rays missing the IOL and rays being refracted by the IOL.

(126) Personalized Correction of Higher Order Aberrations

(127) The average cornea has +0.27 μm spherical aberration at a 6 mm pupil. Correcting this average spherical aberration can increase contrast sensitivity and, among other benefits, improve a subject's driving safety. However, the average root mean square of higher order aberrations is around 0.5 μm . In accordance with some embodiments of the present disclosure, correcting for individual, subject-specific higher order aberrations can be accomplished through the use of refractive index writing on the IOL, since IOL placement is final and will not move.

(128) In accordance with some embodiments of the present disclosure, an iterative corrective approach is performed to address higher order aberrations. In some embodiments, the iterative approach includes the steps of: 1) measuring the subject's higher-order aberrations; 2) calculating the difference (from the current state) to a desired higher order aberration profile, and 3) producing the desired higher order aberration profile via refractive index writing. Steps 1 to 3 can be repeated until the desired profile is reached in a closed loop iteration. The step of measuring the higher-order aberrations, and the step of calculating the difference, can be performed at least in part using a wavefront sensor, for example a Hartmann-Shack wavefront sensor.

(129) In some embodiments, correction of circularly symmetric aberrations such as spherical aberration can be performed through selectively altering the zone width depending on radius and angle of the IOL position, and circularly asymmetric aberrations can be corrected by altering the zone width depending on angular location. As an example implementation, the correction of personalized higher order aberrations can significantly improve the visual outcomes subjects implanted with spherical IOLs (who tend to have large amounts of positive spherical aberrations).

(130) Consistent with one or more aspects described above, and in accordance with some embodiments of the present disclosure, a method for improving vision of a subject having an implanted intraocular lens (IOL) can include performing an iterative, closed-loop correction process to correct one or more of the higher order aberrations of the subject. In some embodiments, the closed-loop correction process includes measuring the higher order aberrations associated with the vision of the subject and determining, based at least in part on the measurements, a target higher order aberration correction that can be at least one of: full correction of at least one of the higher order aberrations of the subject; partial correction of at least one of the higher order aberration of the subject; and induction of at least one higher order aberration. The method also includes applying a plurality of focused laser pulses to selected areas of the IOL, where the laser pulses are configured to produce, through refractive index writing, a target higher order aberration correction profile on the IOL.

(131) In some embodiments, the method also includes a closed-loop method that includes the steps of determining if the produced correcting profile meets the determined profile and, responsive to determining that the produced correcting profile does not meet the determined profile: measuring the difference between the higher order aberrations profile of the eye after the laser treatment and the target higher order aberrations correction and using this information to calculate the determined profile to achieve the target higher order aberration correction, and, based at least in part on the measured difference, applying a plurality of focused laser pulses to the IOL for refractive index writing, where the configuration of the laser pulses are modified from the prior applied laser pulses based on the measured difference, and repeating the above steps until the produced higher order aberration correcting profile meets the determined target higher order aberration correction.

(132) Ocular Diseases

(133) Ocular diseases are often gradual and occur with advanced age, after cataract surgery has been performed. Ocular diseases can cause loss in central visual performance (e.g., age-related macular degeneration) or at more peripheral locations (e.g., glaucoma). In accordance with some aspects of the present disclosure, there are several treatment modalities utilizing refractive index writing to address ocular diseases.

(134) A common factor for many ocular diseases is an increased need for ocular contrast. There are different ways to improve the contrast in these subjects, using refractive index writing in

accordance with embodiments of the present disclosure. In some embodiments, these ways of improvement include one or more of inscribing correction of longitudinal chromatic correction through a diffractive pattern to increase contrast, and by correcting higher order aberrations.

(135) Macular degeneration is an ocular disease known to cause retinal damage. According to some embodiments of the present disclosure, refractive index writing is utilized to cause a yellowing of the IOL such that more harmful short wavelength light rays are absorbed, which is particularly beneficial for further preventing retinal damage caused macular degeneration. Subjects with macular degeneration can experience a positive magnification in vision that makes the world appear bigger. On the other hand, subjects with, for example glaucoma or hemianopia may benefit from a minification, making the world smaller, since they can suffer from a loss of outer peripheral vision which makes navigation more difficult, and a minified view of the world can fit more of the visual field within their functioning vision. It is known that wearing spectacles with a positive power results in a magnified view of the world, and that wearing negative spectacles results in a minified view of the world. In some embodiments of the present disclosure, refractive index writing is used to produce a refractive outcome needing either positive or negative spectacle correction, to have the desired effect for the refractive outcome and spectacle magnification. Subjects with certain ocular diseases may suffer from reduced quality of peripheral vision. In accordance with some embodiments of the present disclosure, gradient-index patterns can be applied to an implanted IOL by refractive index writing.

(136) According to one aspect, the present disclosure relates to a method for improving vision of a subject having an implanted intraocular lens (IOL). The method can include: determining visual needs of a subject that are associated with an ocular disease of the subject and determining a pattern of a plurality of pulses of radiation (e.g., plurality of focused laser pulses) to apply, by refractive index writing, to one or more selected areas of the IOL. The plurality of pulses can be configured to induce a change in the implanted IOL to adapt the optical performance of the IOL to at least one of the visual needs of the subject. The method can also include applying, according to the determined pattern, the plurality of pulses of radiation to the one or more selected areas of the IOL.

(137) In some embodiments, adapting the optical performance of the IOL to the visual needs of the subject can include increasing ocular contrast by inscribing a diffractive pattern in the IOL that is configured to correct longitudinal chromatic aberration. In some embodiments, adapting the optical performance of the IOL to the visual needs of the subject can include increasing ocular contrast by correcting a higher-order aberration.

(138) Adapting the optical performance of the IOL to the visual needs of the subject can additionally or alternatively include one or more of: producing a yellowing of at least a part of the IOL, wherein short wavelength light rays are absorbed; modifying the power of the IOL to correct for residual refractive errors (e.g., defocus and astigmatism); modifying the power of the IOL to improve vision for a given distance (e.g., far correction, near correction, intermediate correction); modifying the phase profile of the IOL to remove an existing diffractive or multifocal refractive profile in the IOL; modifying the phase profile of the IOL to redirect the light passing through the IOL to the subject-preferred retinal location (PRL); and/or inducing a gradient-index pattern on the IOL that is configured to improve peripheral vision of the subject.

(139) In some embodiments, the residual refractive error can be a residual spherical error associated with an uncorrected astigmatism, and determining the pattern of the plurality of pulses of radiation to apply can include calculating a radius of a phase shift for correcting for a residual spherical error. The radius can be calculated according to factors that include an angular dependence. The radius of the phase shift can be calculated, at least in part, according to:

$$(140) r = \sqrt{m \frac{2}{F_1 + (F_2 - F_1) \cdot \sin \theta}} \cdot \text{Math.}$$

where λ is the wavelength, m is a natural number, θ is the angle, and $F1$ and $F2$ the power to be corrected in the respective meridians.

(141) In some embodiments, adapting the optical performance of the IOL to the visual needs of the subject can include determining parameters of a phase prism to be produced on the IOL to correct negative dysphotopsia of the subject. Determining the parameters can include defining the phase prism based on power of the IOL and extension of the prism from respective outer edges of the IOL to the center of the IOL. Determining the pattern of a plurality of pulses of radiation to apply can include determining a pattern of a plurality of pulses of radiation to apply to produce, through refractive index writing on the IOL, wherein the phase prism has the determined parameters. In some embodiments, the one or more selected areas of the IOL include at least one outermost portion proximate the outer edges of the IOL. In some embodiments, the phase prism, as produced on the IOL, is configured to gradually deviate a chief ray to correct a discontinuity in ray deviation between rays missing the IOL and rays being refracted by the IOL.

(142) In another aspect, the present disclosure relates to a system for treating an ocular disease of a subject having an implanted intraocular lens (IOL). In some embodiments, the system can include a pulsed laser system configured to apply, according a determined pattern, a plurality of focused laser pulses to one or more selected areas of the IOL. The system can also include a control system coupled to the pulsed laser system and configured to control the pulsed laser system to apply the plurality of focused laser pulses. The control system can also be configured to: determine visual needs of a subject that are associated with an ocular disease of the subject; and determine the pattern of a plurality of laser pulses to apply, by refractive index writing, to the one or more selected areas of the IOL. The plurality of laser pulses can be configured to induce a change in the implanted IOL to adapt the optical performance of the IOL to the visual needs of the subject.

(143) In some embodiments, adapting the optical performance of the IOL to the visual needs can include increasing ocular contrast by inscribing a diffractive pattern in the IOL that is configured to correct longitudinal chromatic aberration. In some embodiments, adapting the optical performance of the IOL to the visual needs can include increasing ocular contrast by correcting a higher-order aberration. In some embodiments, adapting the optical performance of the IOL to the visual needs can include producing a yellowing of at least a part of the IOL, wherein short wavelength light rays are absorbed.

(144) In some embodiments, adapting the optical performance of the IOL to the visual needs can include modifying the power of the IOL to correct for at least one residual refractive error. The at least one residual refractive error can include defocus and/or astigmatism. In some embodiments, the at least one residual refractive error can be a residual spherical error associated with an uncorrected astigmatism.

(145) In some embodiments, determining the pattern of the plurality of laser pulses to apply can include calculating a radius of a phase shift for correcting for a residual spherical error. The radius can be calculated according to factors that include an angular dependence. In some embodiments, the radius of the phase shift can be calculated, at least in part, according to:

$$(146) \ r = \sqrt{m \frac{\lambda^2}{F_1 + (F_2 - F_1) \cdot \sin^2 \theta}}$$

where λ is the wavelength, m is a natural number, θ is the angle, and F_1 and F_2 the power to be corrected in the respective meridians.

(147) In some embodiments, adapting the optical performance of the IOL to the visual needs can include modifying the power of the IOL to improve vision for a given distance. In some embodiments, adapting the optical performance of the IOL to the visual needs can include modifying the phase profile of the IOL to remove an existing diffractive or multifocal refractive profile in the IOL. In some embodiments, adapting the optical performance of the IOL to the visual needs can include modifying the phase profile of the IOL to redirect light passing through the IOL to the subject's preferred retinal location (PRL). In some embodiments, adapting the optical performance of the IOL to the visual needs can include inducing a gradient-index pattern on the IOL that is configured to improve peripheral vision of the subject.

(148) In some embodiments, adapting the optical performance of the IOL to the visual needs can

include determining parameters of a phase prism to be produced on the IOL to correct negative dysphotopsia of the subject; the determining can include defining the phase prism based on power of the IOL and extension of the prism from respective outer edges of the IOL to the center of the IOL. Determining the pattern of laser pulses to apply can include determining a pattern of a plurality of laser pulses to apply to produce, through refractive index writing on the IOL, the phase prism having the determined parameters.

(149) In some embodiments, the one or more selected areas of the IOL can include at least one outermost portion proximate the outer edges of the IOL. In some embodiments, the phase prism, as produced on the IOL, can be configured to gradually deviate a chief ray to correct a discontinuity in ray deviation between rays missing the IOL and rays being refracted by the IOL.

(150) IOL Positioning

(151) The eye is not a perfectly centered optical system. The apex of the cornea, center of the pupil, center of the IOL and fovea does not always fall along a straight line. Furthermore, even if there is such a line, the optical elements can be tilted with respect to that line. These deviations from un-tilted straight-line optics have many names, depending on which of these deviations is taken as a reference point (e.g., center of pupil, fovea, or corneal apex) which include angle kappa, angle alpha, angle lambda and angle gamma. When the cornea, pupil, IOL, and fovea, all of which can be decentered and two of which have an optical impact of tilt (cornea and IOL), a large number of deviations can exist, and therefore even perfect positioning and tilt of the IOL during surgery may not result in optimal vision. FIG. 5A is an illustration of an eye of a subject with a tilted IOL (note the alignment along the dashed line, which is tilted with respect to the optical axis OA, rather than the optical axis), and FIG. 5B is an illustration of an eye of a subject with the IOL decentered with respect to the optical axis OA (note the vertical displacement of the IOL above the optical axis OA, as further indicated by the dashed line). In each of FIGS. 5A and 5B, like elements of the eye and IOL shown in FIG. 1B share the same reference numerals. FIG. 6A illustrates a phase map (in waves) of a 20 D monofocal IOL implanted in an average eye. FIG. 6B illustrates the phase map (in waves) induced by 5 degrees tilt of a 20 D monofocal IOL. FIG. 6C illustrates the phase map (in waves) induced by 0.5 mm decentration of a 20 D monofocal IOL.

(152) In accordance with some embodiments of the present disclosure, refractive index writing is used to optimize foveal vision by correcting for the effect of these deviations in position by inscribing phase pattern on the IOL that corrects and compensates for these errors. The position and tilt of each of the elements can be measured after surgery, and ray-tracing software can be used to calculate the optimal aberration pattern inscribed which corrects for these errors.

(153) Tilt and decentration can be altered by phase changes from refractive index writing. These can be measured using, for example, Purkinje imaging technology. Subsequently, the impact of tilt and decentration on IOLs can be simulated using ray tracing software, and adequate phase map compensation then calculated accordingly. This can be done once for a wide range of IOL models, tilt, and decentration, to provide automatic suggestion of phase changes following a measured tilt and decentration. Examples of ray-tracing software are Zemax and Oslo. In them, eye models can be implemented (such as the Navarro eye model). Normally, lenses are well-centered, but if the IOL is simulated to be decentered according to measured values, and subsequently a phase map is imposed, the software can optimize which phase map provides the best vision by optimizing for providing, for example, the best modulation transfer function (MTF).

(154) In one aspect, the present disclosure relates to a method for improving vision of a subject having an implanted intraocular lens (IOL). In one embodiment, the method can include determining a deviation in position of at least one optical element from a reference line corresponding to alignment of the apex of the cornea, center of the pupil, center of the IOL, and fovea, and/or determining a tilt of at least one of the optical elements relative to the reference line. The deviation(s) in position and the tilt produce an imperfection in foveal vision in the subject. The method can further include applying a plurality of focused laser pulses to a selected area of the

implanted IOL, using laser pulses that are applied according to a predetermined pattern and that are configured to produce, through refractive index writing, a phase change pattern on the IOL that is configured to compensate for the deviation(s) and/or tilt to improve the foveal vision of the subject. (155) The phase change pattern to be produced by RIW can be calculated, prior to the application of the plurality of focused laser pulses, based on at least one of: biometrics including one or more of IOL positioning, axial length, corneal power, and refraction. The biometrics associated with the IOL positioning include measurements of at least one of effective lens position, tilt, and decentration of the IOL. The biometrics associated with the corneal power can include keratometry and/or elevation maps.

(156) In some embodiments, determining the tilt and decentration can be performed using Purkinje imaging. In some embodiments, determining the tilt and decentration can be performed using optical coherence tomography (OCT). In some embodiments, determining the phase change pattern can include ray-tracing simulation.

(157) In some embodiments, the pattern according to which the pulses of radiation are applied can be calculated based at least in part on the at least one of the deviation in position and the tilt.

(158) In another aspect, the present disclosure relates to a system for improving vision of a subject. In one embodiment, the system includes at least one sensor that is configured to sense a deviation in position of at least one optical element from a reference line corresponding to alignment of the apex of the cornea, center of the pupil, center of the IOL, and fovea and/or a tilt of at least one optical element relative to the reference line. The deviation in position and/or the tilt produces an imperfection in foveal vision in the subject. The system also includes a control system operatively coupled to the at least one sensor and configured to receive associated sensed data corresponding to the deviation in position and/or the tilt. The control system is also configured to calculate, based at least on the sensed data, a phase change pattern to produce on the IOL, that is configured to compensate for the deviation and/or tilt to improve the foveal vision of the subject. The control system is also configured to calculate a pattern of a plurality of pulses of radiation to apply to the IOL to produce the phase change pattern and/or calculate one or more selected areas of the IOL to which the plurality of pulses are to be applied. The system also includes a pulsed radiation system operatively coupled to the control system. The pulsed radiation system can be configured to, based on control by the control system, apply the plurality of pulses of radiation to the IOL according to the pattern to produce, by refractive index writing on the IOL, the phase change pattern on the IOL that is configured to compensate for the deviation and/or tilt to improve the foveal vision of the subject. The at least one sensor can be configured to sense the deviation and tilt and the control system may be configured to receive data corresponding to both the deviation and the tilt.

(159) In some embodiments, the pulsed radiation system includes a pulsed laser and is configured to apply a plurality of laser pulses to the one or more selected areas of the IOL, according to the pattern of the plurality of pulses, to produce the phase change pattern. In some embodiments, the control system can be configured to determine the phase change pattern based at least in part on biometrics associated with at least one of: IOL positioning; axial length; corneal power; and refraction. In some embodiments, the biometrics associated with IOL positioning include measurements of at least one of effective lens position, tilt, and decentration of the IOL. In some embodiments, the biometrics associated with the corneal power include at least one of keratometry and elevation maps.

(160) In some embodiments, the system can be configured to determine the tilt and/or decentration using Purkinje imaging. In some embodiments, the system also includes an optical coherence tomography (OCT) system configured to determine the tilt and/or decentration. In some embodiments, the system is configured to determine the phase change pattern using, at least in part, ray-tracing simulation. In some embodiments, the control system can be configured to calculate the pattern according to which the pulses of radiation are applied based at least in part on the deviation in position and/or the tilt.

(161) Phase Wrapping

(162) Phase wrapping relates to, in the implementation of refractive index writing, that the maximum achievable optical path difference can be limited. For example, a refractive index writing system may not be able to easily shift the phase, e.g., 1.5 wavelengths, 2 wavelengths, or 3 wavelengths, at various locations in an intraocular lens (IOL), as there is a maximum possible shift in the absolute value of the refractive index over a volume. In some cases, the upper limit can be 1 wavelength, which may cause a challenge in implementing various phase maps. Phase wrapping in accordance with some embodiments of the present disclosure can overcome such challenges.

(163) The starting point of a desired refractive index implementation, including those described above in accordance with certain embodiments of the present disclosure, is a phase map that has been shown to, e.g., shift power, reduce residual astigmatism, improve near vision, improve spectacle independence or reduce visual symptoms. Such phase maps often contain values higher than one wavelength. In these implementations, such higher values can be modulated by subtracting the necessary number of whole wavelengths in the phase step such that the complete phase map has values in the range of zero to one wavelength.

(164) An example of the consequence of this implementation can be seen in FIG. 7. FIG. 7 plots the optical path difference of an implemented refractive index design with certain parts of the phase map having a phase addition higher than one wavelength. For the parts of the design that have a phase addition lower than one wavelength, no difference is seen. For the parts of the original design with a phase map value higher than one wavelength, however, a difference of exactly one wavelength (e.g. at 0.7 mm radius, at 1 mm radius, and at 1.3 mm radius) can be seen. Furthermore, the optical path difference impact of the transition between different zones can be seen. It should be understood that this example is purely for illustrative purposes, and any number of zones, and whole number of wavelengths can be phase wrapped.

(165) Benefits of the use of phase wrapping in accordance with some embodiments can be seen in the comparison of the illustrations of FIGS. 8A-8C. In each of FIGS. 8A-8C, three cases are compared: the design implemented using a sag profile (standard IOL technology), design using refractive index writing without the one wavelength limitation, and refractive index writing using phase wrapping. As is evident from the illustrations, phase wrapping successfully replicates the performance both of the sag profile and of the full refractive index writing profile.

(166) Consistent with one or more aspects described above, and in accordance with some embodiments of the present disclosure, a method for phase wrapping in refractive index writing of an intraocular lens (IOL) implanted in a subject includes: for at least one area of the IOL wherein there is a maximum possible shift in the absolute value of the refractive index over a particular volume, modulating the values of a corresponding phase map such that the phase map has values in a particular desired wavelength range. In some embodiments, the desired wavelength range is from about 0 to about 1 wavelength for a maximum possible shift in the absolute value of above 1 wavelength of the refractive index over the particular volume.

(167) Vergence Matching

(168) In refractive index writing, in some implementations phase maps may not be implemented in narrow layers, but rather wide layers of, e.g., 50 μm , 100 μm , 200 μm , or 300 μm . This is wider than for sag profiles. As a result, light that is incident at a vergence, which is the case in the eye, risks transitioning from one zone to the other. For example, at one zone the desired phase addition can be 1.5 wavelengths, and close by the desired phase addition can be 0 wavelengths. However, due to the vergence of the light, if the zone has a width of 300 μm , during the first 150 μm the light can pass the zone of 0 wavelengths phase addition, and during the last 150 μm the light can pass the zone of 1.5 wavelengths phase addition, with the result that the light has a phase addition of 0.75 wavelengths. This can result in undesirable outcomes for the subject.

(169) To address the above-mentioned concerns, in some embodiments of the present disclosure a vergence matching is implemented in the refractive index writing. A vergence matching starts with

a desired phase map, and initial depth position in the IOL, as well as the distance between the IOL and the retina. In some embodiments, the following steps are then performed: 1. creating a transformation function based on the vergence of the incident light; and 2. creating an angulated phase addition.

(170) In accordance with some embodiments, creating a transformation function based on the vergence of the incident light includes mapping, as a function of radius in the IOL, the shift in z direction necessary to match the spherical form of the idealized wave when inside the IOL. This can be calculated by: a) taking an object at infinity, b) imaging through the subject's individual cornea, c) propagating to the anterior surface of the desired IOL using the measured anterior chamber depth (ACD) of the subject, d) imaging through the anterior surface of the IOL, and e) propagating to the plane of the desired refractive index writing. The wave will have a vergence, and this vergence is matched with the baseline surface of where the zero-level of the refractive index pattern is written.

(171) In other embodiments, an average eye model (average cornea and/or average ACD) can be used to calculate the vergence. In other embodiments, a combination of measured and average data can be used to calculate vergence. Additionally, vergence matching can account for both rotationally and non-rotationally optical effects, by creating a 2D function, where vergence is determined by meridian.

(172) With regard to the above-mentioned step “2.” of creating an angulated phase addition, while the phase pattern can be written perpendicular to the apex of the IOL, in accordance with some embodiments of the present disclosure at each point in this new surface described at point 1, the phase map is instead written with a depth of, e.g., 50 μm , 100 μm , 200 μm , or 300 μm perpendicular to the vergence calculated above. The advantages of vergence matching according to some embodiments of the present disclosure can be seen in the comparison of simulations shown in FIGS. 9A and 9B, illustrating simulations with and without vergence matching, utilizing refractive index written designs.

(173) Consistent with one or more aspects described above, and in accordance with some embodiments of the present disclosure, a method for vergence matching in refractive index writing includes determining a desired phase map for producing, by refractive index writing, a phase change on an IOL, which can be an IOL implanted in the eye of a subject; determining the vergence of the wave after refraction on the anterior surface of the IOL for the design wavelength; propagating this wavefront to the plane of the refractive index writing within the IOL, and estimating the curvature in that plane. Based on this result, a desired phase map can be converted into a vergence-matched three-dimensional (3D) phase map such that the original flat phase map follows the curved vergence of the wavefront. Estimating the curvature in the plane of the refractive index writing can include calculating the curvature using ray tracing software (e.g., Zemax, Code V, Oslo), or other geometrical optics calculations (e.g., relating to wave propagation), some aspects of which will be described below.

(174) Propagation of the wavefront can be calculated by: taking an object at infinity; imaging through the individual cornea of the subject; propagating to the anterior surface of the IOL based on a measured distance between the cornea of the subject and the anterior surface of the IOL, the shape of the anterior surface of the IOL, and the refractive index of the IOL; imaging through the anterior surface of the IOL; and propagating to the plane inside the IOL to an area where the refractive index writing is to be performed. In some embodiments, the method includes matching the vergence with a baseline surface where the zero-level of the refractive index pattern is written. The vergence can be calculated using a model of an average cornea and/or average ACD. The vergence can be calculated using a model of an average IOL design for a particular power. The shape of the anterior surface of the IOL can be estimated using optical coherence tomography (OCT) imaging.

(175) In some embodiments, vergence matching accounts for rotational and non-rotational optical

effects by creating a two-dimensional function, wherein vergence is determined by meridian. In some embodiments, the method also includes creating an angulated phase addition, wherein at each point on a target surface of the IOL, a phase addition is written, by the refractive index writing, with a depth perpendicular to the calculated vergence. The phase addition can have a predetermined depth perpendicular to the calculated vergence. The refractive index writing can include applying a plurality of focused laser pulses to a selected area of the IOL.

(176) In another aspect, the present disclosure relates to a system for improving vision of a subject. In one embodiment, a pulsed radiation system can be configured to apply, by refractive index writing, a plurality of pulses of radiation to at least one selected area of an intraocular lens (IOL) implanted in an eye of a subject, according to a predetermined pattern. The system can also include a control system coupled to the pulsed radiation system and configured to control the pulsed radiation system and to perform functions that include: determining a desired phase map for producing, by refractive index writing, a phase change in an IOL implanted in an eye of a subject, the IOL having an anterior surface and a posterior surface; calculating vergence of a wave after refraction on the anterior surface of the IOL for a desired wavelength design; calculating propagation of a corresponding wavefront to the plane of the refractive index writing within the IOL; estimating curvature of the wavefront in the plane of the refractive index writing; and, based on the estimated curvature, converting an initial phase map into a vergence-matched three-dimensional (3D) phase map, such that the initial phase map follows the curved vergence of the wavefront; and

(177) In some embodiments, propagation of the wavefront can be calculated by performing functions that include: taking an object at infinity; imaging through the individual cornea of the patient; propagating the wavefront to the anterior surface of the IOL based on a measured distance between the cornea of the patient and the anterior surface of the IOL, the shape of the anterior surface of the IOL, and the refractive index of the IOL; imaging through the anterior surface of the IOL; and propagating the wavefront to the plane inside the IOL to an area where the refractive index writing is to be performed. The vergence can be matched with a baseline surface wherein the zero-level of the refractive index pattern is written.

(178) In some embodiments, a model of an average cornea and/or average anterior chamber depth (ACD) is used to calculate the vergence. In some embodiments, a model of an average IOL design for a particular power is used to calculate the vergence. In some embodiments, the shape of the anterior surface of the IOL can be estimated using optical coherence tomography (OCT) imaging. In some embodiments, the vergence matching accounts for rotational and non-rotational optical effects by creating a two-dimensional function, wherein vergence is determined by meridian.

(179) In some embodiments, the control system can be configured to control the pulsed radiation system to create an angulated phase addition, wherein at each point on a target surface of the IOL, a phase addition is written, by the refractive index writing, with a depth perpendicular to the calculated vergence. In some embodiments, the phase addition has a predetermined depth perpendicular to the calculated vergence.

(180) Vergence Matching of a Refractive Index Writing Design

(181) FIGS. 10A-C illustrate aspects of vergence matching of a refractive index writing design, in accordance with embodiments of the present disclosure. FIG. 10A shows a schematic of the pseudo-phakic eye (see, e.g. cornea 1002 and retina 1012) with rays entering the eye with zero vergence, as well as an intraocular lens (IOL) 1008 comprising an optical profile 1010 induced by refractive index writing, collectively 1000. FIGS. 10B and 10C show a zoomed in view of the optical profile 1010. In accordance with some embodiments of the present disclosure, to design a lens that considers the vergence of the wavefront 1004 (λ .sub.0), for the design wavelength, the direction ($\tan(\theta)$) of each ray is measured at a given radial coordinate. FIGS. 10B and 10C show also that the direction of the ray increases with the radial coordinates. In accordance with some embodiments, knowing the ray direction versus ray height and the value of the refractive index (RI)

at RI (z.sub.0, R.sub.0) (see FIG. 10B)), the refractive index is redesigned inside such that the RI at (z.sub.1, R.sub.1) is equal to the RI at (z.sub.0, R.sub.0) (see FIG. 10B). Accordingly, the z-dependence is achieved by making the RI at (z.sub.0, R.sub.0) equal to the RI at (z.sub.1, R.sub.1); this thereby “shrinks” or reduces the volume where the refractive index has been written. To keep the rays shown in FIG. 10B from deviating or changing direction, the optical profile 1010 is bent (see FIG. 10C, bent with reference to the initial orientation indicated by the dashed box) such that these rays have a zero incidence.

(182) Further stated, FIG. 10B shows that the output rays after the optical profile 1010 with vergence matching are parallel to the ray before entering the optical profile 1010 with an offset. This can cause an unwanted spherical aberration, longer optical path length than intended, and/or un-intended power shift, among other undesired effects. To cancel these undesirable effects, in accordance with some embodiments, the surfaces (anterior 1010a and posterior 1010) of the optical profile 1010 are bent such that the rays at the interface between the IOL 1008 and optical profile 1010 have a zero incidence, i.e., the rays are normal to the surface of the optical profile 1010 (see FIG. 10C). Therefore, the rays do not change their direction inside and outside the optical profile 1010 and add the intended optical path length.

(183) Consistent with aspects described above, and in accordance with some embodiments of the present disclosure, a method of vergence matching for an intraocular lens (IOL) having an optical profile induced by refractive index writing can include the steps of: determining the direction of a plurality of rays associated with a vergence of a wavefront; determining the ray direction and ray height of a plurality of rays entering a first location of the optical profile; and determining the refractive index of the optical profile at the first location. The method can also include, based on the determined ray direction, ray height, and refractive index at the first location, and by refractive index writing, specifying the volume and shape of each voxel to match the wavefront through the direction of propagation. The method can also include bending anterior and posterior surfaces of the optical profile such that rays inside a portion of the IOL changed by refractive index writing and outside a portion of the IOL changed by refractive index writing do not change direction; and determining a second location that, for each of the rays, corresponds to the location where the respective ray exits the optical profile changed by refractive index writing.

(184) In some embodiments, the volume and shape of each voxel match the wavefront through the direction of propagation such that the voxels decrease for converging wavefronts. In some embodiments, the volume and shape of each voxel match the wavefront through the direction of propagation such that the voxels increase for diverging wavefronts.

(185) In some embodiments, the anterior and posterior surfaces of the optical profile are bent such that rays at the interface of the respective surfaces of the optical profile with other portions of the lens have a zero incidence. The first location can correspond to a first plane parallel to a vertical axis of the lens and the second location can correspond to a second plane parallel to the first plane. The first location can be proximate to or correspond to the anterior surface of the lens and the second location can be proximate to or correspond to the posterior surface of the lens. In some embodiments, the bent anterior and posterior surfaces are bent to define a non-zero curvature about the optical axis. In some embodiments, the refractive index writing includes applying a plurality of pulses of radiation according to a predetermined pattern. The plurality of pulses of radiation can be focused laser pulses applied according to the predetermined pattern. In some embodiments, the IOL is implanted in an eye of a subject.

(186) In another aspect, in some embodiments a system for improving vision of a subject can include a pulsed laser system configured to apply a plurality of laser pulses to an intraocular lens (IOL) implanted in an eye of a subject and to change the refractive index of at least one selected area of the IOL by refractive index writing, wherein the IOL has an optical profile induced by refractive index writing. The system can also include a control system coupled to the pulsed laser system and configured to control the pulsed laser system to apply the plurality of laser pulses

according to calculated pattern. The control system can also be configured to perform functions that include determining the direction of a plurality of rays associated with a vergence of a wavefront; determining the ray direction and ray height of a plurality of rays entering a first location of the optical profile; determining the refractive index of the optical profile at the first location; and, based on the determined ray direction, ray height, and refractive index at the first location, and by refractive index writing using the pulsed laser system, specifying the volume and shape of each voxel to match the wavefront through the direction of propagation.

(187) In some embodiments, the control system can also be configured to calculate the pattern of laser pulses to apply. In some embodiments, anterior and posterior surfaces of the optical profile are bent such that rays inside a portion of the IOL changed by refractive index writing and outside a portion of the IOL changed by refractive index writing do not change direction. In some embodiments, the control system can be further configured to determine a second location that, for each of the rays, corresponds to the location where the respective ray exits the optical profile changed by refractive index writing. In some embodiments, the volume and shape of each voxel match the wavefront through the direction of propagation such that the voxels decrease for converging wavefronts. In some embodiments, the volume and shape of each voxel match the wavefront through the direction of propagation such that the voxels increase for diverging wavefronts.

(188) In some embodiments, the anterior and posterior surfaces of the optical profile are bent such that rays at the interface of the respective surfaces of the optical profile with other portions of the lens have a zero incidence. In some embodiments, the anterior and posterior surfaces are bent to define a non-zero curvature about the optical axis.

(189) In some embodiments, the first location can correspond to a first plane parallel to a vertical axis of the lens and the second location corresponds to a second plane parallel to the first plane. In some embodiments, the first location can be proximate to or corresponds to the anterior surface of the lens, and the second location can be proximate to or corresponds to the posterior surface of the lens.

(190) FIGS. **11** and **12** illustrate the radial dependence of the refractive index change for different thicknesses of the optical profile written inside the IOL, for power subtraction (FIG. **11**) and power addition (FIG. **12**), in accordance with embodiments of the present disclosure. FIGS. **13** and **14** illustrate the radial dependence of the refractive index change for different thicknesses of the optical profile written inside the IOL for spectacle independence, for negative added power (FIG. **13**) and positive added power (FIG. **14**), in accordance with embodiments of the present disclosure.

(191) FIG. **15** shows results of simulations in an anatomically correct eye model using ray tracing software (Zemax) illustrating through frequency MTF with a comparison between an IOL with a refractive anterior and posterior surface (“refractive”), an IOL with an anterior refractive surface with refractive index writing without vergence matching (“grin_standard”), and an IOL with vergence matching according to some embodiments of the present disclosure (“refractive_grin_with_vergence_matching”). “Polychromatic” and “4.5 mm stop” refers to a simulation condition of MTF for white light (polychromatic) and a 4.5 mm pupil diameter. FIG. **16** shows the results of simulations in TCEM illustrating through frequency MTF (FIG. **16**) and through focus MTF at 50 c/mm (FIG. **17**), with a comparison between an IOL with a refractive anterior and posterior surface (“refractive”), an IOL with refractive index writing without vergence matching (“grin_standard”), an IOL like the grin_standard, but with the refractive index shrunk along the z axis in accordance with vergence matching in some embodiments described above (“grin_shrink”), and an IOL with refractive anterior and diffractive, elevated, posterior surface (“diffractive sag”).

(192) FIGS. **18** and **19** show results illustrating a similar comparison for normalized polychromatic point spread function (PSF) (FIG. **18**) and polychromatic halo simulation (FIG. **19**). Rather than describing the optical quality, as measured by MTF, these Figures show simulated aspects of the

perception of visual symptoms (e.g., halo). As a PSF, an ideal would be to have all energy go to a single point, that of 0; it is desired to have a high up peak to the left of the curve, and then immediately the intensity going down; so for the rest of the curve, higher and higher up means a worse and worse perceived halo; “refractive” is lower than others. As further shown, “grin shrink” is particularly good in this aspect. FIG. 20 shows simulated halo performance for a number of different designs: that of a standard refractive IOL (“refractive”), that of an extended depth of focus embodiment with vergence matching (“grin shrink”), that of an extended depth of focus embodiment IOL implemented with normal refractive index writing (grin_standard), and the same extended depth of focus embodiment achieved by standard methods of elevated posterior surface (diffractive sag).

(193) Multi-Layer IOL

(194) According to certain aspects, the present disclosure relates to post-surgically improving vision in a subject with an implanted intraocular lens (IOL) through the use of refractive index writing and a flexible, multi-layered gradient index approach, such as to produce an effect like that produced by a GRIN lens. In some embodiments, the multi-layered approach is not diffractive; rather, it is purely refractive, without transition steps; the multi-layered approach can create a long series of transitions rather than a single surface. A power shift can occur not only at anterior and posterior sides of an IOL, but multiple times inside the lens, and without relying on diffractive aspects. In various embodiments, the multiple layers are induced inside the lens at different depths by focusing applied laser radiation at particular selected depths, through changing, e.g., settings and exposure times. The laser can be used to directly reach the desired state, going directly from a starting index of refraction to the desired index of refraction for a particular layer. Accordingly, there is not a restriction on a particular sequence in terms of depths or other progression that must be followed; for instance, one can start with an innermost layer, outermost, or any in between.

(195) In accordance with some embodiments, in order to induce a layer in the IOL, a voxel-based treatment of the IOL is applied, wherein as one goes sequentially through each voxel, the desired shift in refractive index is applied, determined by total amount of light energy focused in the particular area and the duration of focus time. Whereas in some other approaches, for each (x,y) coordinate on the IOL, a uniform shift in refractive index is created over the full range of z where it is applied (i.e., the depth, for example 100 microns, 200 microns, or 400 microns); instead, in accordance with aspects of the multi-layered approach according to embodiments of the present disclosure, there are uniform layers, but changes over z. The depth at which a uniform index of refraction change can be produced can be, for example 20 microns, 30 microns, or 50 microns.

(196) As discussed above in some detail, factors that can limit a subject's visual performance post surgery, for example after cataract surgery, can include: incorrect IOL power, uncorrected astigmatism, IOL placement error, higher order aberrations, spectacle dependence, negative dysphotopsia, peripheral aberrations, and chromatic aberrations.

(197) FIG. 21 illustrates a side, cross-sectional view of an IOL along an optical axis OA, showing the outline of an IOL 2100 (with an anterior side 2102a and posterior side 2102b), the index of refraction of the original IOL n.sub.1 several layers 2104, 2106, 2108, 2110 with various shapes, and their associated index of refraction (n.sub.1, n.sub.2, n.sub.3, and n.sub.4). In particular, the illustration of FIG. 21 shows the cross-section of the IOL 2100 with the solution being rotationally symmetric. The constructed layers can also be rotationally asymmetric, allowing the correction of astigmatism, higher order aberrations, and other asymmetric errors. The illustration shows four different refractive index values (n.sub.1, n.sub.2, n.sub.3, and n.sub.4). In some embodiments, the change in refractive index writing can be 0.2, such that up to 40 different such layers are achievable. For purposes of clarity in the illustrated embodiment of FIG. 21, four layers 2104, 2106, 2108, 2110 are shown.

(198) In some embodiments, the anterior and posterior sides can be of different shape, as is seen for the fourth layer 2110, wherein the anterior is curved and the posterior is flat. The thickness can be

close to zero over parts of or all of the layers, as is the case in the anterior side of the interface for the third index change (see left side of layer **2108** proximate the intersection with the optical axis OA). Further, the potential asymmetry is illustrated by the interface of the second layer **2106**, which is more curved on the left than on the right side. The described curves are convex. Alternatively, in some embodiments the curves can be concave as well, which induces a negative power change when the inner layers have a higher refractive index. Taken together, this multi-layered approach in refractive index writing allows control and alleviation of a number of the factors limiting post-surgical vision described above, and as will be specifically discussed below in further detail.

(199) Regarding incorrect IOL power, the multi-layer approach according to some embodiments, described above, allows power changes to be made without compromising aberration correction. Furthermore, if the induced layers follow a toric pattern, astigmatic errors of the patient can be corrected; these include: corneal astigmatism (anterior and posterior cornea); surgically induced astigmatism; and/or astigmatism from decentration, tilt, and angle kappa. Negative effects of incorrect IOL placement may also be corrected through the multi-layer approach according to some embodiments. In one embodiment, the implementation the IOL position and tilt is measured, and the desired multi-layer solution compensating for these errors is implemented with refractive index writing. In particular, the patient can receive compensation for the tilt of the IOL by induction of a left-right asymmetry in the multi-layers that have a prismatic effect. This prismatic effect also can be applied to the case when the patient suffers from strabismus; using an internal prism, this approach does not suffer from the limitations that make external prisms unworkable for strabismus patients. With respect to higher order aberrations, even if lenses could be customized with an exact measurement of the higher order aberrations of the patient, such corrections would not be used; even small amounts of decentration, within the range of normal uncertainty of IOL placement (e.g., 0.1 mm) would induce a mismatch between the correction and the original aberration, losing the benefits of the correction and potentially worsening it instead. In a postoperative multi-layered approach according to certain embodiments, the position is controlled with a high accuracy, overcoming this obstacle.

(200) Regarding spectacle independence, refractive multi-focal intraocular lenses are often not popular, as uptake is limited by the zonal nature of such designs. For example, if a lens has a high add power in the center, but a patient has a very small pupil, the entire pupil of the patient would have the add power, inducing a loss in distance vision. Diffractive lenses, on the other hand, are pupil-independent but suffer from visual phenomena. In a multi-layered refractive index writing approach to multifocal design in accordance with some embodiments, a measurement of pupil dynamics under different conditions would precede the algorithmic construction of the different layers. This allows for customization of where add power is created, ensuring near and distance vision for the patient under all lighting conditions.

(201) Some aspects of the present disclosure for construction of a peripheral attenuation zone that removes negative dysphotopsia have been described above. In some embodiments, such an attenuation zone, an outer peripheral area (e.g. the outer 0.5 mm) that gradually diminishes the deviation of the chief ray to zero, can be constructed using refractive index writing for the patients reporting negative dysphotopsia. A multi-layer gradient index approach according to some embodiments also allows the reduction of peripheral aberrations such as oblique astigmatism and coma. This may be a synergistic benefit, combined with the other approaches described above.

(202) Regarding chromatic aberrations, the normal human eye has approximately one diopter of longitudinal chromatic aberrations. While this can be reduced by diffractive designs, doing so can lower image quality. An alternative approach, in accordance with some embodiments, is to utilize refractive designs, using a number of different refracting elements and Abbe numbers. The different powers and Abbe numbers are realized in the multiple layers created by refractive index writing. A desired feature of the implemented total state is that $C/V_0 + F_1/V_1 + F_2/V_2 + F_3/V_3 + \dots = 0$, where C

is the corneal power, V_0 is the Abbe number of the cornea, ($F_1, F_2, F_3 \dots$) the power of the different layers and ($V_1, V_2, V_3 \dots$) the Abbe numbers.

(203) Consistent with aspects described above, and in accordance with some embodiments of the present disclosure, a method for improving vision in a subject having an implanted intraocular lens (IOL) can include determining at least one modification to be made to an IOL implanted in a subject to improve the vision of the subject, wherein the IOL has a first index of refraction. The method can also include, based on the determination, applying laser radiation to at least one selected area of the IOL to form, within the IOL, at least one additional layer having a different index of refraction than the first index of refraction and a particular shape within the IOL configured to improve the vision of the subject.

(204) In some embodiments, the applied laser radiation changes the index of refraction of the at least one selected area from the first refractive index to the different index of refraction in forming the at least one additional layer. The index of refraction of the at least one additional layer can be uniform throughout the respective layer. The at least one additional layer can be formed with a series of transitions within the IOL and/or formed to have a shape defined by portions having different depths within the IOL. The at least one additional layer can be formed to have a particular thickness and, when formed, at least one of the layers has a different thickness than another one of the layers.

(205) In some embodiments, applied laser radiation can include one or more selected optical energies focused in the at least one selected area and one or more selected durations of exposure of the focused optical energy in the at least one selected area, determined at least in part based on the determined at least one modification to be made to the IOL. In some embodiments, the at least one additional layer can include more than two additional layers, and each of the more than two additional layers can have a respective index of refraction and be formed with a particular shape within the IOL. The more than two additional layers can include at least two different shapes.

(206) In some embodiments, the at least one modification to be made to the IOL can correspond to correcting at least one of incorrect IOL power, uncorrected astigmatism, IOL placement error, higher order aberration, spectacle dependence, negative dysphotopsia, peripheral aberrations, and chromatic aberrations. Applying the laser radiation can include index writing with a plurality of focused laser pulses applied to the at least one selected area of the IOL according to a predetermined pattern. The predetermined pattern can be based at least in part on the determined at least one modification to be made to the IOL.

(207) In another aspect, in some embodiments a method for forming a multi-layered intraocular lens (IOL) can include determining at least one modification to be made to an IOL to improve the visual performance of the IOL, where the IOL has a first index of refraction and, based on the determination, applying laser radiation to the IOL to form, within the IOL, at least one additional layer having a different index of refraction than the first index of refraction and a particular shape within the IOL configured to improve the visual performance of the IOL.

(208) The applied laser radiation can change the index of refraction of the at least one selected area from the first refractive index to the different index of refraction in forming the at least one additional layer. The index of refraction of the at least one additional layer can be uniform throughout the respective layer. The at least one additional layer can be formed to have a shape defined by portions having different depths within the IOL, wherein at least one of the layers has a different thickness than another one of the layers.

(209) In some embodiments, the applied laser radiation can include one or more selected optical energies focused in the at least one selected area of the IOL and one or more selected durations of exposure of the focused optical energy in the at least one selected area, determined at least in part based on the determined at least one modification to be made to the IOL. Applying the laser radiation can include refractive index writing with a plurality of laser pulses applied to the at least one selected area of the IOL according to a predetermined pattern. The predetermined pattern can

be based at least in part on the determined at least one modification to be made to the IOL.

(210) In yet another aspect, in some embodiments a system for improving vision of a subject can include at least one sensor configured to determine a correction to be made to an intraocular lens (IOL) to improve the vision of a subject, wherein the IOL has a first index of diffraction. The system can also include a control system operatively coupled to the at least one sensor and configured to receive associated sensed data corresponding to the correction to be made to the IOL and to calculate, based on the sensed data, shape and/or index of refraction for at least one additional layer to be formed within the IOL. The additional layer can have a different index of refraction than the first index of refraction and a particular shape within the IOL configured to improve the vision of the subject. Additionally or alternatively, the control system can calculate parameters for a pattern of laser radiation to be applied to at least one selected area of the IOL to form the at least one additional layer; and a radiation system operatively coupled to the control system and configured to, based on control by the control system, apply focused laser radiation according to the parameters and pattern of laser radiation to be applied to at least one selected area of the IOL, to form, within the IOL, the at least one additional layer having the different index of refraction and the particular shape.

(211) The calculated parameters for the pattern of laser radiation can include one or more selected optical energies to be focused in the at least one selected area and one or more selected durations of exposure for the focused optical energy in the at least one selected area. The radiation system can be a pulsed laser system configured to apply the laser radiation by refractive index writing with a plurality of focused laser pulses applied to IOL according to the calculated parameters and pattern.

(212) In some embodiments, the at least one sensor corresponds to an optical coherence tomography (OCT) system configured to determine biometric data associated with the correction to be made to the IOL. The applied laser radiation can change the index of refraction of the at least one area of the IOL from the first refractive index to the different index of refraction in forming the at least one additional layer. The index of refraction of the formed at least one additional layer can be uniform throughout the respective layer. The at least one additional layer can be formed with a series of transitions within the IOL. The at least one additional layer can be formed to have a shape defined by portions having different depths within the IOL. The at least one additional layer can be formed to have a particular thickness, and wherein, when formed, at least one of the layers can have a different thickness than another one of the layers.

(213) The various embodiments described above are provided by way of illustration only and should not be construed to limit the scope of the present disclosure. Those skilled in the art will readily recognize that various modifications and changes may be made to the present disclosure without following the example embodiments and implementations illustrated and described herein, and without departing from the spirit and scope of the disclosure and claims here appended and those which may be filed in non-provisional patent application(s). Therefore, other modifications or embodiments as may be suggested by the teachings herein are particularly reserved.

Claims

1. A method for improving vision of a subject having an implanted intraocular lens (IOL), the method comprising: determining at least one photic phenomenon experienced by the subject after implantation of the IOL; and applying a plurality of laser pulses to the IOL, the laser pulses being configured to produce, by refractive index writing on the IOL, a phase shift in the IOL to compensate for the photic phenomenon, wherein the IOL is a diffractive IOL or a refractive IOL and compensating for the photic phenomena comprises at least partially compensating for a phase delay associated with the phase shift.

2. The method of claim 1, wherein applying the plurality of laser pulses comprises applying a plurality of focused laser pulses, according to a predetermined pattern, to at least one selected area

of the IOL to produce, by the refractive index writing on the IOL, the phase shift.

3. The method of claim 1 or 2, wherein the photic phenomenon is a halo, a starburst, or a glare.

4. The method of claim 1, wherein the phase shift in the IOL to compensate for the photic phenomenon comprises a radially dependent phase shift.

5. The method of claim 1, further comprising verifying correction of the at least one photic phenomenon following the application of the laser pulses.

6. The method of claim 5, wherein verifying the correction incorporates subject feedback provided following the application of the laser pulses.

7. The method of claim 1, wherein the determining at least one photic phenomena comprises measuring and mapping the photic phenomenon experienced by the subject.

8. The method of claim 1, further comprising determining a phase delay associated with the phase shift to compensate for at least one photic phenomena comprises simulations of the optimal higher order aberrations induction based on pupil size analysis.

9. The method of claim 8, wherein the simulations of the optimal higher order aberrations induction are based on subject response to photic phenomena.

10. The method of claim 1, wherein compensating for the photic phenomenon comprises refractive optimization, apodization, partial apodization, or profile reversion.

11. The method of claim 10, wherein the refractive optimization comprises correcting, by the refractive index writing, defocus, astigmatism, or higher order aberrations.

12. The method of claim 10, wherein the apodization comprises eliminating, by inverted phase delay, the diffractive or refractive IOL design in an outer part of the lens.

13. The method of claim 12, wherein apodization phase delay is determined using feedback from the subject relating to experiencing the photic phenomena.

14. The method of claim 12, wherein the apodization further comprises maintaining a central part of the diffractive design, wherein the peripheral part is defined based on the specific photic phenomenon experienced by the subject.

15. The method of claim 10, wherein the partial apodization comprises modifying the percentage of light distributed between different foci of a multifocal IOL in an outer part of the lens.

16. The method of claim 10, wherein the profile reversion comprises eliminating the full diffractive profile of the IOL.

17. The method of claim 11, wherein correcting higher order aberrations comprises performing an iterative, closed-loop correction process including: measuring the higher order aberrations; determining a target higher order aberration correction that exhibits one or more of: full correction of at least one of the higher order aberrations of the subject; partial correction of at least one of the higher order aberrations of the subject; or induction of at least one higher order aberration based on the measuring; applying, by refractive index writing, a plurality of pulses of radiation to one or more selected areas of the IOL, the plurality of pulses being configured to produce a target higher order aberration correction profile on the IOL; (a) determining if the produced correction profile meets the target higher order aberration correction profile; (b) responsive to determining that the produced correction profile does not meet the target higher order aberration correction profile: (i) measuring the difference between the higher order aberrations profile of the IOL after the prior application of the plurality of pulses of radiation and the target higher order aberrations correction and, based on the measured difference, calculating a profile to achieve the target higher order aberration correction, (ii) applying, by refractive index writing, a next plurality of pulses of radiation to the IOL, wherein the configuration of the pulses of radiation is modified based on the measured difference, and repeating the steps (i) and (ii) until the produced higher order aberration correcting profile meets the determined target higher order aberration correction.

18. A method for improving vision of a subject having an implanted intraocular lens (IOL), the method comprising: determining at least one photic phenomenon experienced by the subject after implantation of the IOL; and applying a plurality of laser pulses to the IOL, the laser pulses being

configured to produce, by refractive index writing on the IOL, a phase shift in the IOL to compensate for the photic phenomenon; and determining a phase delay associated with the phase shift to compensate for at least one photic phenomena comprises simulations of the optimal higher order aberrations induction based on pupil size analysis.

19. A method for improving vision of a subject having an implanted intraocular lens (IOL), the method comprising: determining at least one photic phenomenon experienced by the subject after implantation of the IOL; and applying a plurality of laser pulses to the IOL, the laser pulses being configured to produce, by refractive index writing on the IOL, a phase shift in the IOL to compensate for the photic phenomenon; and determining a phase delay associated with the phase shift to compensate for at least one photic phenomena comprises simulations of the optimal higher order aberrations induction based on pupil size analysis, wherein the simulations of the optimal higher order aberrations induction are based on subject response to photic phenomena.
