

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409378
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Shigeta; Yasushi

Card show apparatus and table game system

Abstract

A system includes a card shoe that includes a housing for housing cards and an opening through which the housed cards can be drawn. The system includes a computer to detect whether there is any of the following predefined arrangements: (1) for each of a predefined number of consecutively drawn cards, the respective rank of the respective card is larger or smaller by one than an immediately preceding one of the cards drawn from the card housing; (2) a respective rank of each of a predefined number of consecutively drawn cards is the same; (3) a respective suit of each of a predefined number of consecutively drawn cards is the same; or (4) a same sequence in which a predefined number of the cards are consecutively drawn is repeated.

Inventors:	Shigeta; Yasushi (Shiga, JP)
Applicant:	ANGEL GROUP CO., LTD. (Shiga, JP)
Family ID:	50296607
Assignee:	ANGEL GROUP CO., LTD. (Shiga, JP)
Appl. No.:	18/441442
Filed:	February 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240181332 A1	Jun. 06, 2024

Foreign Application Priority Data

JP	2012-227444	Sep. 25, 2012
WO	PCT/JP2012/006230	Sep. 28, 2012

Related U.S. Application Data

continuation parent-doc US 18103959 20230131 ABANDONED child-doc US 18441442
continuation parent-doc US 17230258 20210414 US 11596856 20230307 child-doc US 18103959
continuation parent-doc US 16409319 20190510 US 11007422 20210518 child-doc US 17230258
continuation parent-doc US 15456322 20170310 US 10335670 20190702 child-doc US 16409319
continuation parent-doc US 14431239 US 10124242 20181113 WO PCT/JP2013/004956
20130822 child-doc US 15456322

Publication Classification

Int. Cl.: **A63F1/14** (20060101); **A63F1/12** (20060101); **A63F1/18** (20060101); **A63F9/24** (20060101)

U.S. Cl.:

CPC **A63F1/14** (20130101); **A63F1/12** (20130101); **A63F1/18** (20130101); A63F2009/2419 (20130101); A63F2009/2451 (20130101); A63F2009/2457 (20130101); A63F2250/58 (20130101)

Field of Classification Search

CPC: A63F (1/14); A63F (1/12); A63F (1/18); A63F (2009/2419); A63F (2009/2451); A63F (2009/2457); A63F (2250/58); A63F (1/02); A63F (1/062)

USPC: 463/12; 463/11; 463/13

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4513696	12/1984	Fujii et al.	N/A	N/A
4513969	12/1984	Samsei, Jr.	N/A	N/A
4534562	12/1984	Cuff et al.	N/A	N/A
4586712	12/1985	Lorber et al.	N/A	N/A
4794239	12/1987	Allais	N/A	N/A
5067713	12/1990	Soules et al.	N/A	N/A
5166502	12/1991	Rendleman et al.	N/A	N/A
5169155	12/1991	Soules et al.	N/A	N/A
5259907	12/1992	Soules et al.	N/A	N/A
5331141	12/1993	Kaneko	N/A	N/A
5374061	12/1993	Albrecht	N/A	N/A
5669813	12/1996	Jairazbhoy et al.	N/A	N/A
5669816	12/1996	Garczynski et al.	N/A	N/A
5707287	12/1997	McCrea, Jr.	N/A	N/A
5722893	12/1997	Hill et al.	N/A	N/A
5779546	12/1997	Meissner	N/A	N/A
5814804	12/1997	Kostizak	N/A	N/A
5911626	12/1998	McCrea, Jr.	N/A	N/A
5941769	12/1998	Order	N/A	N/A
5989122	12/1998	Robledo	N/A	N/A

6039650	12/1999	Hill	N/A	N/A
6042150	12/1999	Daley	N/A	N/A
6066857	12/1999	Fanton et al.	N/A	N/A
6093103	12/1999	McCrea, Jr.	N/A	N/A
6098892	12/1999	Peoples, Jr.	N/A	N/A
6126166	12/1999	Lorson et al.	N/A	N/A
6217447	12/2000	Lofink et al.	N/A	N/A
6270406	12/2000	Sultan	N/A	N/A
6460848	12/2001	Soltys et al.	N/A	N/A
6527191	12/2002	Jannersten	N/A	N/A
6582301	12/2002	Hill	N/A	N/A
6588751	12/2002	Grauzer et al.	N/A	N/A
6629894	12/2002	Purton	N/A	N/A
6637622	12/2002	Robsinson	N/A	N/A
6638161	12/2002	Soltys et al.	N/A	N/A
7029009	12/2005	Grauzer et al.	N/A	N/A
7093130	12/2005	Kobayashi et al.	N/A	N/A
7172507	12/2006	Fujimoto et al.	N/A	N/A
7222852	12/2006	Soltys et al.	N/A	N/A
7422522	12/2007	Fujimoto et al.	N/A	N/A
7762889	12/2009	Shigeta	N/A	N/A
7946586	12/2010	Krenn et al.	N/A	N/A
7950663	12/2010	Schubert et al.	N/A	N/A
7967672	12/2010	Shigeta	N/A	N/A
8221244	12/2011	French	N/A	N/A
8309163	12/2011	Van Duren et al.	N/A	N/A
8490973	12/2012	Yoseloff et al.	N/A	N/A
8556262	12/2012	Shigeta	N/A	N/A
8590896	12/2012	Krenn et al.	N/A	N/A
8801516	12/2013	Shigeta	N/A	N/A
9649550	12/2016	Shigeta	N/A	N/A
10549178	12/2019	Shigeta	N/A	N/A
11845000	12/2022	Curley	N/A	A63F 1/12
2002/0017481	12/2001	Johnson et al.	N/A	N/A
2002/0063389	12/2001	Breeding et al.	N/A	N/A
2002/0068635	12/2001	Hill	N/A	N/A
2002/0155869	12/2001	Soltys et al.	N/A	N/A
2002/0163125	12/2001	Grauzer et al.	N/A	N/A
2002/0165029	12/2001	Soltys et al.	N/A	N/A
2003/0003997	12/2002	Vuong et al.	N/A	N/A
2003/0171142	12/2002	Kaji et al.	N/A	N/A
2003/0176209	12/2002	Soltys et al.	N/A	N/A
2003/0195025	12/2002	Hill	N/A	N/A
2004/0026636	12/2003	Shigeta	N/A	N/A
2004/0100026	12/2003	Haggard	N/A	N/A
2004/0259618	12/2003	Soltys	N/A	N/A
2005/0012270	12/2004	Schubert et al.	N/A	N/A
2005/0051955	12/2004	Schubert et al.	N/A	N/A
2005/0062226	12/2004	Schubert et al.	N/A	N/A
2005/0062227	12/2004	Grauzer et al.	N/A	N/A

2005/0104290	12/2004	Grauzer et al.	N/A	N/A
2005/0110210	12/2004	Soltys et al.	N/A	N/A
2005/0121852	12/2004	Soltys et al.	N/A	N/A
2005/0137005	12/2004	Soltys et al.	N/A	N/A
2006/0063577	12/2005	Downs, III et al.	N/A	N/A
2006/0247036	12/2005	Shigeta	N/A	N/A
2006/0279040	12/2005	Downs, III et al.	N/A	N/A
2007/0018389	12/2006	Downs, III	N/A	N/A
2007/0216092	12/2006	Fleckenstein	N/A	N/A
2007/0296151	12/2006	Kyrychenko	N/A	N/A
2008/0006997	12/2007	Scheper et al.	N/A	N/A
2008/0105750	12/2007	Shigeta	N/A	N/A
2008/0143048	12/2007	Shigeta	N/A	N/A
2008/0224394	12/2007	Shigeta	N/A	N/A
2009/0066021	12/2008	Shigeta	N/A	N/A
2009/0134575	12/2008	Dickenson et al.	N/A	N/A
2009/0140492	12/2008	Yoseloff	463/25	G07F 17/3293
2009/0224476	12/2008	Grauzer	N/A	N/A
2009/0224777	12/2008	Kim	702/58	G02F 1/1309
2009/0286597	12/2008	Shigeta	N/A	N/A
2010/0038849	12/2009	Scheper	273/149R	A63F 1/00
2010/0133754	12/2009	Shigeta	N/A	N/A
2010/0213667	12/2009	Grauzer et al.	N/A	N/A
2010/0276887	12/2009	Yoshida	N/A	N/A
2010/0289214	12/2009	Just	N/A	N/A
2010/0327525	12/2009	Shigeta	N/A	N/A
2011/0034243	12/2010	Shigeta	N/A	N/A
2011/0130185	12/2010	Walker	463/13	G07F 17/3202
2011/0148038	12/2010	Laughlin	N/A	N/A
2011/0198805	12/2010	Downs, III et al.	N/A	N/A
2011/0210175	12/2010	Shigeta	N/A	N/A
2011/0275432	12/2010	Lutnick et al.	N/A	N/A
2012/0091656	12/2011	Blaha et al.	N/A	N/A
2012/0306152	12/2011	Krishnamurty et al.	N/A	N/A
2013/0207344	12/2012	Shigeta	N/A	N/A
2013/0303277	12/2012	Shigeta	N/A	N/A
2014/0042697	12/2013	Berube et al.	N/A	N/A
2015/0014925	12/2014	Miller et al.	N/A	N/A
2015/0190707	12/2014	Shigeta	N/A	N/A
2015/0238849	12/2014	Shigeta	N/A	N/A
2015/0265908	12/2014	Shigeta	273/149R	A63F 1/18
2015/0328533	12/2014	Haushalter	273/149R	A63F 1/12
2015/0375095	12/2014	Shigeta	N/A	N/A
2016/0014351	12/2015	Blazevic	250/330	A63F 1/02
2017/0189792	12/2016	Shigeta	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013203307	12/2013	AU	N/A
2015202960	12/2014	AU	N/A
1525874	12/2003	CN	N/A
2772570	12/2005	CN	N/A
1933881	12/2006	CN	N/A
101099896	12/2007	CN	N/A
101437586	12/2008	CN	N/A
101484216	12/2008	CN	N/A
101541388	12/2008	CN	N/A
101584934	12/2008	CN	N/A
101588847	12/2008	CN	N/A
101678232	12/2009	CN	N/A
101711177	12/2009	CN	N/A
101732850	12/2009	CN	N/A
101804251	12/2009	CN	N/A
201537379	12/2009	CN	N/A
101884840	12/2009	CN	N/A
101920104	12/2009	CN	N/A
101959563	12/2010	CN	N/A
101972544	12/2010	CN	N/A
102307633	12/2011	CN	N/A
202398088	12/2011	CN	N/A
2380143	12/2002	GB	N/A
H05-000398	12/1992	JP	N/A
H05-020512	12/1992	JP	N/A
H09-215812	12/1996	JP	N/A
H09-144353	12/1996	JP	N/A
H10-508236	12/1997	JP	N/A
2000-327255	12/1999	JP	N/A
2001-222687	12/2000	JP	N/A
2002-165916	12/2001	JP	N/A
2002-224443	12/2001	JP	N/A
2002-282413	12/2001	JP	N/A
2003-052902	12/2002	JP	N/A
2003-070956	12/2002	JP	N/A
2003-144742	12/2002	JP	N/A
2003-250950	12/2002	JP	N/A
2004-215806	12/2003	JP	N/A
2005-198668	12/2004	JP	N/A
2005-267625	12/2004	JP	N/A
2005-296634	12/2004	JP	N/A
2007-236995	12/2006	JP	N/A
2008-161479	12/2007	JP	N/A
2008-188471	12/2007	JP	N/A
2009-213520	12/2008	JP	N/A
2012061023	12/2011	JP	N/A
4964037	12/2011	JP	N/A
2025060791	12/2024	JP	N/A

1996/14115	12/1995	WO	N/A
1999/043404	12/1998	WO	N/A
2001/056670	12/2000	WO	N/A
0205914	12/2001	WO	N/A
2002/064225	12/2001	WO	N/A
2002/094397	12/2001	WO	N/A
2003/026763	12/2002	WO	N/A
2003/078006	12/2002	WO	N/A
2003/078006	12/2002	WO	N/A
2009/069708	12/2008	WO	N/A
2009/126780	12/2008	WO	N/A
2010/019708	12/2009	WO	N/A
2010/055328	12/2009	WO	N/A
2010056562	12/2009	WO	N/A
2012035742	12/2011	WO	N/A
2012/053179	12/2011	WO	N/A
2012/166197	12/2011	WO	N/A
2013/116297	12/2012	WO	N/A
2014/049664	12/2013	WO	N/A
2010052573	12/2013	WO	N/A

OTHER PUBLICATIONS

Chinese Office Action, CN Patent Application No. 201610827326.0, mailed Mar. 1, 2019. cited by applicant

Japanese Office Action dated Oct. 8, 2019 for corresponding JP Application 2018-210439 cites the patent document above. cited by applicant

Chinese Office Action dated Dec. 25, 2019 for corresponding CN Application 201710188722.8 cites the patent document above. cited by applicant

Japanese Office Action dated May 11, 2020 for corresponding JP Application 2018-210439 cites the patent document above. cited by applicant

Filipino Office Action dated Jul. 13, 2020 for corresponding PH Application 1-2019-502270 cites the patent document above. cited by applicant

Malysian Office Action issued on Oct. 3, 2023 for MY Application No. PI2021001070. cited by applicant

Chinese Office Action dated Feb. 15, 2019 for CN application 201610830365.6. cited by applicant

Chinese Office Action, Chinese Patent Application No. 201380049993.5, issued Jan. 4, 2017. cited by applicant

Chinese Office Action, Chinese Patent Application No. 201280075345.2, issued Jan. 3, 2017. cited by applicant

Australian Patent Examination Report No. 1, Australian Patent Application No. 2013203307, mailed Oct. 15, 2014. cited by applicant

Australian Patent Examination Report No. 1, Australian Patent Application No. 2013203316, mailed Dec. 10, 2014. cited by applicant

International Search Report, International Application No. PCT/JP2013/004956, mailed Sep. 24, 2013. cited by applicant

Australian Examiner's First Report, Australian Patent Application No. 2008200596, mailed Nov. 6, 2009. cited by applicant

Australian Examiner's Report No. 2, Australian Patent Application No. 2010235931, mailed Jul. 11, 2011. cited by applicant

International Preliminary Report on Patentability, International Application No.

PCT/JP2005/003789, mailed Feb. 2, 2006. cited by applicant
International Search Report, International Application No. PCT/JP2005/003789, mailed Apr. 26, 2005. cited by applicant
International Search Report, International Application No. PCT/JP2012/006230, mailed Nov. 13, 2012. cited by applicant
Final Office Action, U.S. Appl. No. 10/542,073, mailed Apr. 14, 2010. cited by applicant
Non-Final Office Action, U.S. Appl. No. 11/884,021, mailed Dec. 8, 2010. cited by applicant
Non-Final Office Action, U.S. Appl. No. 11/929,727, mailed Oct. 1, 2010. cited by applicant
Non-Final Office Action, U.S. Appl. No. 11/929,727, mailed Mar. 7, 2011. cited by applicant
Non-Final Office Action, U.S. Appl. No. 12/231,657, mailed Mar. 19, 2010. cited by applicant
Final Office Action, U.S. Appl. No. 12/231,657, mailed Dec. 8, 2010. cited by applicant
Non-Final Office Action, U.S. Appl. No. 12/825,261, mailed Nov. 23, 2010. cited by applicant
New Zealand First Examination Report, NZ Patent Application No. 704620, mailed Jul. 31, 2015. cited by applicant
Chinese First Office Action, Chinese Patent Application No. 201310225940.6, mailed Dec. 3, 2015. cited by applicant
New Zealand First Examination Report, NZ Patent Application No. 706311 mailed Dec. 8, 2015. cited by applicant
Korean Office Action, Korean Patent Application No. 10-2015-7007553, mailed Mar. 28, 2016. cited by applicant
New Zealand First Examination Report, NZ Patent Application No. 716059, mailed May 6, 2016. cited by applicant
Australian Examination Report No. 1, Australian Patent Application No. 2015202960, mailed Jun. 9, 2016. cited by applicant
Korean Notice of Allowance, Korean Patent Application No. 10-2015-7007316, mailed Jun. 16, 2016. cited by applicant
Chinese Notice of Allowance, Chinese Patent Application No. 201310220992.4, mailed Jul. 4, 2016. cited by applicant
New Zealand First Examination Report, NZ Patent Application No. 720973, mailed Jul. 29, 2016. cited by applicant
International Search Report, European Patent Application No. 13842336.3, mailed Aug. 24, 2016. cited by applicant
Australian Examination Report No. 2 dated Jun. 17, 2018 for AU application 2016262639. cited by applicant
Australian Examination Report No. 1 dated Aug. 3, 2018 for AU application 2017225160. cited by applicant
US Notice of Allowance dated Jun. 8, 2018 for U.S. Appl. No. 14/431,239. cited by applicant
US Office Action dated Aug. 9, 2018 for U.S. Appl. No. 14/419,605. cited by applicant
Chinese Allowance dated Mar. 19, 2018 for corresponding Chinese application 201510315068.3. cited by applicant
Australian Office Action, Australian Patent Application No. 2016208351, issued May 11, 2017. cited by applicant
Australian Office Action, Australian Patent Application No. 2016208352, issued May 11, 2017. cited by applicant
Office Action mailed Aug. 29, 2017 for JP Application 2016-240958 (Japanese language). cited by applicant
Office Action mailed Sep. 6, 2017 for U.S. Appl. No. 14/431,239. cited by applicant
Australian Examination Report dated Jan. 19, 2018 for corresponding Australian application 2016262639. cited by applicant
New Zealand First Examination Report dated Dec. 4, 2017 for corresponding New Zealand

application 731453. cited by applicant

Filipino Substantive Examination Report dated May 2, 2019 for corresponding Philippine application No. 1-2015-502779. cited by applicant

Filipino Office Action dated Jan. 30, 2025, issued in PH Application No. 1-2019-502270. cited by applicant

Japanese Office Action dated Aug. 5, 2025 issued in JP Application 2023-062431. cited by applicant

Primary Examiner: Elisca; Pierre E

Attorney, Agent or Firm: NORTON ROSE FULBRIGHT US LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 18/103,959 filed Jan. 31, 2023, which is a continuation of U.S. patent application Ser. No. 17/230,258 filed Apr. 14, 2021 (now U.S. Pat. No. 11,596,856), which is a continuation of U.S. patent application Ser. No. 16/409,319 filed May 10, 2019 (now U.S. Pat. No. 11,007,422), which is a continuation of U.S. patent application Ser. No. 15/456,322 filed Mar. 10, 2017 (now U.S. Pat. No. 10,335,670), which is a continuation of U.S. patent application Ser. No. 14/431,239 filed Mar. 25, 2015 (now U.S. Pat. No. 10,124,242), which is a 35 USC 371 national-phase application of International Application PCT/JP2013/004956 filed Aug. 22, 2013, which claims priority to International Application PCT/JP2012/006230 filed Sep. 28, 2012 and JP Application 2012-227444 filed Sep. 25, 2012; each of the listed applications is incorporated herein by reference.

TECHNICAL FIELD

(1) The present invention relates to a card shoe apparatus and a table game system with a function of preventing cheating in a card game played with playing cards (hereinafter simply referred to as “cards”) such as baccarat.

BACKGROUND ART

(2) In poker, baccarat, bridge, blackjack, and other card games, a dealer sets one or more decks of playing cards in a card shoe or the like, and deals cards to game players by drawing out the cards one by one out of the card shoe or the like. In doing so, to ensure fairness in the games, the cards need to be dealt at random. Therefore, a game host has to sufficiently shuffle the playing cards randomly in order to ensure a random order of arrangement of the playing cards before they are set in the card shoe.

(3) A conventional card shuffling device for shuffling cards is disclosed in, for example, WO 2009/069708.

(4) The shuffled playing cards used in various card games such as poker, baccarat, bridge or blackjack include, ordinarily, 416 cards if eight decks of cards are used, and we cannot completely eliminate the possibility of the occurrence of a state in which such shuffled playing cards are arranged not in a random order but in a specific order instead (for example, a state of ten consecutive Ace cards) for some reason. If a set of cards that has not been sufficiently shuffled to be arranged in a random order is set in a card shoe or the like and used in a game, the fairness of the game may not be secured, which is a problem. In a card game, the arrangement order of the cards that are drawn during the game is important; the cards are drawn in such an order and the winner/loser of the game is also decided by the arrangement order.

(5) The present invention has been made in view of the above problems, and aims to provide a card

shoe and a table game system capable of detecting a state in which the shuffled playing cards to be used in a card game are not randomly arranged when the card shoe deals the cards onto the game table, thereby preventing the condition of an unfair game, and the dealing of cards of a card set arranged in a specific order, which thus, should not be dealt onto the game table, as well as a method therefor.

SUMMARY OF THE INVENTION

(6) One aspect of the present invention is a card shoe apparatus, and a card shoe apparatus for storing shuffled playing cards on a game table and manually dealing the cards housed in the card shoe apparatus one by one onto the game table, the card shoe apparatus comprising: a card housing unit for housing the shuffled playing cards; an opening unit for drawing out the cards from the card housing unit one by one; a card reading unit that reads, from a card, information provided in the card drawn from the card housing unit onto the game table; a control unit that stores rules of a card game, and determines the winner/loser of the card game according to said rules, based on the information of the cards read by the card reading unit; and an output unit that outputs a result of the winner/loser determined by the control unit, wherein the control unit has a shuffling checking function of storing the information of the cards read by the card reading unit for a predetermined number of cards, detecting and outputting an irregularity of the shuffled playing cards housed in the card housing unit based on the information of the cards read by the card reading unit, and outputting an irregularity alarm, the irregularity of the shuffled playing cards being at least one of the following cases: (1) a case where a state in which the rank of a card is larger or smaller by one than the card preceding that card continues for a predetermined number of cards; (2) a case where cards with the same rank continue for a predetermined number of cards; (3) a case where the same sequence is repeated throughout a predetermined number of cards; (4) a case where cards with the same suit continue for at least a predetermined number of cards; (5) a case where the arrangement order of a predetermined number of cards matches an arrangement order registered in advance; (6) a case where a state in which a card drawn has the same suit and rank as the card that precedes the card drawn by 52 cards continues for a plurality of cards; and (7) a case that corresponds to a case that has been registered in advance as an irregular case. (8) a case where cards with the same rank and suit are drawn for at least a predetermined number of cards.

(7) As explained hereinafter, there are other aspects in the present invention. Accordingly, this disclosure of the invention is intended to provide some aspects of the present invention, and is not intended to limit the scope of the invention described and claimed herein.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view schematically showing the entirety of a table game system according to an embodiment of the present invention.

(2) FIG. 2 is a perspective view of shuffled playing cards to be used in the table game system according to the embodiment.

(3) FIG. 3 is a plan view of a card according to the embodiment of the present invention.

(4) FIG. 4 is a diagram showing a general configuration of the card shoe apparatus.

(5) FIG. 5A is a plan view showing an example of an irregularity in the arrangement order of cards detected by the card shoe apparatus.

(6) FIG. 5B is a plan view showing another example of an irregularity in the arrangement order of cards.

(7) FIG. 6 is a plan view of a card guide of the card shoe apparatus in which main portions are enlarged and the card guide is partially broken.

(8) FIG. 7 is a diagram showing the relation between output waves from sensors and marks in the

card shoe apparatus.

(9) FIG. 8 is a diagram showing a general configuration of the card shoe apparatus.

(10) FIG. 9A is a diagram showing an embodiment of the card movement restriction means.

(11) FIG. 9B is a diagram showing another embodiment of the card movement restriction means.

DETAILED DESCRIPTION

(12) Detailed explanation of the present invention will be mentioned hereinafter. However, the following detailed explanation and accompanying drawings do not limit the invention.

(13) To solve the above conventional problems, the present invention provides a table game system including: shuffled playing cards made up of a predetermined number of cards, the cards having been shuffled in advance, each card with information representing a rank thereof as a code that is normally invisible; and, a card shoe apparatus for storing the shuffled playing cards on a game table and manually dealing the cards housed in the card shoe apparatus one by one onto the game table, wherein the card shoe apparatus includes: a card housing unit for housing the shuffled playing cards; an opening unit for drawing out the cards from the card housing unit one by one; a card reading unit that reads the code provided in the card drawn from the card housing unit onto the game table, a control unit that stores rules of a card game, and determines the winner/loser of the card game according to said rules, based on the information of the cards read by the card reading unit; and a output unit that outputs a result of the winner/loser determined by the control unit, and the control unit has a shuffling checking function of storing the information of the cards read by the card reading unit for a predetermined number of cards, detecting and outputting an irregularity of the shuffled playing cards housed in the card housing unit based on the information of the cards read by the card reading unit, the irregularity of the shuffled playing cards being at least one of the following cases: (1) a case where a state in which the rank of a card is larger (or smaller) by one than the card preceding that card continues for a predetermined number of cards (for example, 1, 2, 3, 4, - - -, K); (2) a case where cards with the same rank continue for a predetermined number of cards (for example, A, A, A, A, - - -); (3) a case where the same sequence is repeated throughout a predetermined number of cards (for example, A, Q, 10, A, Q, 10, - - -); (4) a case where cards with the same suit continue for at least a predetermined number of cards (for example, 13 consecutive cards with Hearts); (5) a case where the arrangement order of a predetermined number of cards matches an arrangement order registered in advance; (6) a case where a state in which a card drawn has the same suit and rank as the card that precedes the card drawn by 52 cards continues for a plurality of cards; (7) a case that corresponds to a case that has been registered in advance as an irregular case; and (8) a case where cards with the same rank and suit are drawn for at least a predetermined number of cards.

(14) With the present invention, it is possible to provide a table game system capable of detecting a state in which the shuffled playing cards to be used in a card game are not randomly arranged when a card shoe deals the cards onto a game table, thereby preventing the condition of an unfair game, and the dealing of a predetermined number or more of cards of a card set arranged in a specific order, which thus, should not be dealt.

(15) An embodiment of a table game system of the present invention will be described below. FIG. 1 is a perspective view schematically showing the entirety of a table game system according to the present embodiment. FIG. 2 is a perspective view of shuffled playing cards to be used in the table game system of the present embodiment. A shuffled playing card set is used in the table game system of the present embodiment is provided in a state in which cards 1 made up of a predetermined number of decks (normally, 6, 8 or 10 decks) have been shuffled and randomly arranged. On the game table, the shuffled playing card set 1s is housed in a card shoe apparatus 2 bundled with a band (B), and thereafter, the band (B) is undone and removed such that the cards 1 of the shuffled playing cards 1s can be dealt one by one. During a game, a dealer deals the cards 1 onto the game table out of the card shoe apparatus 2.

(16) A cut card 1c is inserted in the shuffled playing card set 1s before it is set in the card shoe

apparatus 2. The cut card 1c is inserted at any place within the latter half portion of the shuffled playing card set is when used in a game (in the last quarter or one-fifth of the shuffled playing card set 1s). The cut card 1c is used to end a game at the game table leaving about 20 to 40 cards 1 in the card shoe apparatus 2, so as to prevent any player from counting the ranks of the cards 1 dealt during a game to predict the ranks of the cards when the number of the cards that have not been dealt yet becomes small. FIG. 3 shows the cards 1 which form the shuffled playing cards. A figure is encoded and printed in UV ink or the like, which is invisible under normal conditions, on each card 1 that is used in table games such as baccarat. In FIG. 3, codes 3, each of which is configured with marks M, are provided in the upper and lower sides of the card 1 in a point-symmetric manner.

(17) In FIG. 4, the card shoe apparatus 2 of the table game system of the present embodiment includes a card guide unit 7 that guides the cards 1 that are drawn one by one out of a card housing unit 5 onto a game table 6, and a card reading unit 8 that reads from a card 1, when the card 1 is drawn from the card housing unit 5, the code 3 that indicates the figure (number, rank) of that card 1. The card shoe apparatus 2 further includes a control unit 12 that stores the rules of a card game for determining the winner/loser of the card game (in this example, the baccarat game), and determines the winner/loser based on the numbers (ranks) of the cards 1 read by the card reading unit 8. The control unit 12 stores the rules of a card game in a memory 13 to be described below, and determines the winner/loser between the player and the banker based on the total of the numbers (ranks) of their hands, each hand consisting of several cards 1 that were dealt. An output means 11 (configured from a plurality of lamps) displays the result of this determination.

(18) The control unit 12 includes the memory 13 that stores the information of a predetermined number of cards 1 read by the card reading unit 8, with which the control unit 12 stores the arrangement order of the cards of the shuffled playing cards 1s, and has a function of detecting any irregularity described below. Upon the detection of an irregularity in the arrangement order of the cards of the shuffled playing cards 1s housed in the card housing unit 5, the management division or the pit of the casino is notified thereof by an arrangement order irregularity alarm through an external output means 100. In addition, arrangement order irregularity lamps 101 and a liquid crystal display unit 102 exhibit the irregularity in the cards 1, thereby informing a dealer or the like thereof. A wired or wireless communication means is used as a means of outputting the irregularity alarm.

(19) Note that the irregularity alarm is given by a two-phase alarm system. In the first phase, an alarm is displayed in the liquid crystal display unit 102, which is a side display of the card shoe apparatus 2, upon the detection of an irregularity such that only the dealer who has the role of dealing the cards can know the irregularity. Next, in the second phase, the irregularity alarm is given as a final irregularity display at the end of the game during which the irregularity occurs. In this case, an arrangement order irregularity alarm is given to the management division or the pit of the casino through the external output means 100, and in addition, the arrangement order irregularity lamp(s) 101 is(are) lighted to indicate the irregularity in the arrangement order of the cards 1.

(20) Next, an irregularity in the arrangement order of the cards will be described. FIG. 5A and FIG. 5B each show a typical example of an irregularity in the arrangement order of the cards. FIG. 5A shows an example where the cards 1 drawn from the card housing unit 5 have the same suit (Clubs) with sequential figures (number, rank) beginning from Ace. FIG. 5B shows an example where the cards 1 drawn from the card housing unit 5 consist of 9 cards with the same rank (3). Generally, the cards of the shuffled playing cards 1s are shuffled by a random number generator or the like so as to be arranged in a random order. The arrangement order as shown in FIGS. 5A and 5B indicates an irregular shuffling of the shuffled playing card set 1s, which is thus determined to be irregular. Including the examples described above, possible examples of an irregularity in the arrangement order are listed below: (1) a case where a state in which the rank of a card is larger (or smaller) by

one than the card preceding that card continues for a predetermined number of cards (for example, 1, 2, 3, 4, - - -, K) (as shown in FIG. 5A); (2) a case where cards with the same rank continue for a predetermined number of cards (for example, A, A, A, A, - - -) (as shown in FIG. 5B); (3) a case where the same sequence is repeated throughout a predetermined number of cards (for example, A, Q, 10, A, Q, 10, - - -); (4) a case where cards with the same suit continue for at least a predetermined number of cards (for example, 13 consecutive cards with Hearts); and (5) a case where the arrangement order of a predetermined number of cards matches an arrangement order registered in advance (this is a case where the arrangement order used in a separate card manufacturing process appears, which case can also be considered irregular (shuffling failure)).

(21) These irregular patterns are stored in the memory **13** in advance, and the control unit **12** compares the information of the cards **1** read by the card reading unit **8** with such patterns. If the arrangement order of a predetermined number of cards **1** matches any of these irregular patterns, it is determined to be irregular.

(22) A sample case of an irregularity in the arrangement order of the shuffled playing cards described in (c) above, where the arrangement order of a predetermined number of cards matches an arrangement order that has been registered in advance, is a case where the state in which the suit and rank of a card drawn are the same as those of the card preceding it by 52 cards continues for a plurality of cards. This is to enable the detection of an irregular case where a shuffling of a plurality of decks has failed for some reason, and instead each of the 52 cards is arranged in the same arrangement order. Note that as another example of an irregularity in the arrangement order, the arrangement order of the cards used when manufacturing the cards, and which is unique to the card manufacturing process may be defined as an irregular case, and stored in advance.

(23) Further, as an example of an irregularity in the arrangement order of the shuffled playing cards, (7) a case that corresponds to a case that has been registered in advance as an irregular case and (8) a case where cards with the same rank and suit are drawn for at least a predetermined number of cards, can be considered. Regarding (7) a case that corresponds to a case that has been registered in advance as an irregular case, for example, the same arrangement order as the that of the rank and suit of each card (plurality of the cards) previously read by the card shoe apparatus **2** continue for a predetermined number of cards or a predetermined number of games in the set of cards currently read by the card shoe apparatus **2**. Regarding (8) a case where cards with the same rank and suit are drawn for at least a predetermined number of cards, for example, the shuffled playing cards is housed in the card housing unit **5** are consist of the predetermined number of decks of cards (usually 6, 8, 9 or 10 decks), and the cards the number of which is more than that number of decks (the 9^{sup}.th card of the same mark is drawn in the 8 decks of the shuffled playing cards) are not supposed to be housed in the card housing unit **5**, and if the cards the number of which is more than that number of decks are drawn, that means existence of irregularity.

(24) In this case, the card shoe apparatus **2** stores at least several sets ("8 decks" times "several sets") of the sequence of the suit and the rank in a result of reading cards previously.

(25) According to such an embodiment, the case where the cards which were previously used are not disposed and illegally reused (where the sequence of the cards which were previously read reappears) can be found as shuffle-irregular.

(26) An irregularity in the arrangement order of the shuffled playing cards refers to a case where an irregular state continues throughout a predetermined number of cards. It is further preferable that a preliminary alarm of irregularity is given, as a stage prior to the occurrence of an irregularity in the arrangement order, during the card that is several cards before the end of a predetermined number of cards. The preliminary alarm is given in a form different from the final alarm, for example, by characters, in a certain color, or with a different lamp. Also, since it is a preliminary alarm, if a state does not continue to be irregular throughout a predetermined number of cards and returns to a random state, then the preliminary alarm is cancelled.

(27) Next, the card reading unit **8** that reads the code **3** from a card **1** will be described in detail

with reference to FIG. 6. FIG. 6 is a plan view in which main portions of the card shoe apparatus 2 are enlarged. In FIG. 6, some portions are enlarged for the purpose of description, and thus FIG. 6 does not necessarily accurately reflect the relative scale. The card reading unit 8 is provided in the card guide unit 7 that guides the cards 1 drawn one by one from the opening 13 of the card housing unit 5 onto the game table 6, with the opening 13 provided in a front portion of the card housing unit 5. The card guide unit 7 is an inclined surface, and a card guide 14 is attached to a portion of the edge of each of both sides thereof, with the card guide 14 also serving as a sensor cover. Also, each of the two card guides 14 is configured to be attachable/detachable with screws or the like (not shown). When a card guide 14 is removed, a sensor group 15 of the card reading portion 8 is exposed. The sensor group 15 is composed of four sensors, including two ultraviolet reactive sensors (UV sensors) 20 and 21, and object detection sensors 22 and 23.

(28) The object detection sensors 22 and 23 are optical fiber sensors that each detect the presence of a card 1. The object detection sensor 22 is placed in the upstream side of the card guide unit 7 relative to the travel direction of the card 1, and the object detection sensor 23 is placed in the downstream side of the card guide unit 7 relative to the travel direction of the card 1. As shown in FIG. 6, the object detection sensors 22 and 23 are provided in the upstream and downstream sides of the UV sensors 20 and 21, respectively. Each of the UV sensors 20 and 21 includes an LED (UV LED) that emits an ultraviolet ray and a detector. The marks M are printed on the card 1 in UV luminescent ink that emits color when UV ray is applied. The card 1 is irradiated with the UV ray (black light), and the detector detects the light reflected by the marks M of the code 3 of the card 1. The UV sensors 20 and 21 are connected to the control unit 12 of the card reading unit 8 via a cable. In the card reading unit 8, the arrangement patterns of the marks M are determined based on the output signals of the detectors of the UV sensors 20 and 21, and the number (rank) corresponding to the code 3 is determined.

(29) In the card reading unit 8, the start and end of the reading performed by the UV sensors 20 and 21 are controlled by the control unit 12 based on the detection signals from the object detection sensors 22 and 23. Also, the control unit 12 determines whether the card 1 has normally passed through the card guide unit 7 based on the detection signals from the object detection sensors 22 and 23. As shown in FIG. 3, the rectangular marks M are arranged within a framework of two rows with four columns on each of the upper and bottom edges of the card 1, and the arrangement of such marks M indicates the rank (number) and the suit (Heart, Spade or the like) of the card 1. If the UV sensor(s) 20 and/or 21 detect(s) a mark M, such UV sensor(s) give(s) out an on signal. The card reading unit 8 determines the relative relation between the signals received from the two UV sensors 20 and 21. By this way, the card reading unit 8 identifies the code based on the relative difference or the like between the two marks M detected by the two UV sensors 20 and 21, thereby identifying the number (rank) and the type (suit) of the corresponding card 1.

(30) The relation between the code 3 and the output of the on signals of the two UV sensors 20 and 21 are shown in FIG. 7. It is possible to identify a predetermined arrangement pattern of the marks M based on the comparison results of the relative changes in the output of the on signals of the UV sensors 20 and 21. As a result, in two rows (the upper and lower rows), four types of arrangement patterns of the mark M are possible, and since patterns are printed in four columns, it is possible to form 256 types of codes ($4 \times 4 \times 4 \times 4$). Fifty two (52) different playing cards are each assigned to one of the 256 codes, and the relations of such assignment are stored in a memory or by a program as an association table. A configuration is thereby adopted in which the card reading unit 8 can, by identifying the code 3, identify the number (rank) and the type (suit) of the card 1 based on that predetermined association table (not shown). Also, 52 cards can be freely associated with 52 codes out of the 256 codes to be stored in the association table, and thus, there will be a variety of associations between them. Therefore, it is possible to change the associations between the 256 codes and the 52 cards depending on the time or place. Preferably, the code is printed with a paint material that becomes visible when irradiated with a UV ray, and placed in a position where it does

not overlap the indications of the card types or indexes **102**.

(31) Next, the configuration of the control unit **12** will be described in further detail. The control unit **12** and the like are achieved by a computer apparatus. For example, the process function of automatically determining the winner/loser of a game (in the control unit **12**) is achieved by installing in a computer a program for determining the winner/loser, and that program is executed by a processor of the computer. The numbers of the cards sequentially taken out onto the game table **6** are acquired using the UV sensors **20** and **21** in the card reading unit **8**, and the numbers of the cards thus acquired are stored sequentially in the memory **13**. At this point, information on which card **1** is dealt in what order to which player is also stored. The dealing order of the number and suit of the cards are stored. Although the cards of the shuffled playing card set is have generally been shuffled in advance by a random number generator or the like so as to be arranged in random, if any of the irregular patterns described above appears, it indicates the possibility of an irregular shuffling of the shuffled playing card set **1s**. The arrangement orders of the cards that should be determined as irregular patterns are stored in the memory **13** in advance or programmed such that the control unit **12** compares the information on the actual arrangement order of the cards **1** that were read by the card reading unit **8** and dealt with the irregular patterns, and if a predetermined number of the cards **1** are drawn in any irregular pattern, it is determined to be irregular.

(32) As shown in FIGS. **8**, **9A**, and **9B**, the card shoe apparatus **2** comprises the card movement restriction means **30** that restricts the movement of the card **1** to/from the card housing unit **5**. In FIG. **9A**, the card movement restriction means **30** is provided in the card guide **14** of the card guide unit **7** that guides the cards **1** taken out one by one from the opening **3**, which is provided in a front portion of the card housing unit **5**. The card movement restriction means **30** has a structure by which when a card **1** passes through a slot **33** between the card guide unit **7** and the card guide **14**, a lock member **34** presses the card **1** to prohibit the movement of the card **1** within the slot **33**. The lock member **34** is capable of moving in the direction indicated by the arrow M by a driving unit **35** composed of an electromagnetic solenoid, a piezoelectric device or the like, such that it can take two positions, namely, a position where the card **1** is pressed (restricted position) and a position where the card **1** is allowed to pass through. The driving unit **35** is controlled by the control apparatus **12**, and causes the lock member **34** to move to two positions, namely, a position where the card **1** is pressed and a position where the card **1** is allowed to pass through. The rules of the baccarat game are programmed and stored in advance in the control apparatus **12**.

(33) Next, an alternative embodiment of the card movement restriction means **30** will be described with reference to FIG. **9B**. According to this embodiment, a card movement restriction means **40** has a structure by which when a card **1** passes through the slot **33** between the card guide unit **7** and the card guide **14**, a lock member **36** protrudes into the slot **33** to prohibit movement of the card **1**. The lock member **36** is capable of moving in the direction indicated by the arrow M by a driving unit **37** composed of an electromagnetic solenoid, a piezoelectric device or the like, such that it can take two positions, namely, a position where movement of the card **1** is prohibited (restricted position) and a position where the card **1** is allowed to pass through. The driving unit **37** is controlled by the control apparatus **12**, and causes the lock member **36** to move to two positions, namely, a position where movement of the card **1** is prohibited and a position where the card **1** is allowed to pass through.

(34) The card movement restriction means **30** (**40**) is caused to function as a result of the driving unit **35** or **37** being controlled by the control apparatus **12** to prevent the fraudulent movement of the card **1**. The card movement restriction means **30** (**40**) is provided with the object detection sensors **22** and **23** as sensors for detecting movement of the card **1**, and has a function of detecting movement of the card **1** with these sensors **22** and **23** to restrict the movement of a card. The contents of control object as the fraudulent entry/exit of the card (programmed contents) includes at least the following 1) and 2).

(35) An error signal output unit **50**, which, upon the operation of the card entry/exit restriction unit **30 (40)**, gives an external signal regarding such operation (a lamp is illuminated and an alarm sound is emitted), is provided, and the operation of which is controlled by the control apparatus **12**.

(36) As a practical use of the above embodiment, it is applied to controlling the end of the game in the reading apparatus of the shuffled playing cards on the game table. As already explained, the cut card **1c** is inserted in the shuffled playing card set is before it is set in the card shoe apparatus **2**. The cut card **1c** may be inserted in a predetermined position of at the side or the like of the shuffled playing cards set is at the manufacturing of the shuffled playing cards set is in a factory or may be prepared separately, in any case, the cut card **1c** is inserted within the latter half portion of the shuffled playing card set is when used in a game (in the last quarter or one-fifth of the shuffled playing card set is). The cut card **1c** is used to end a game at the game table leaving about 20 to 40 cards **1** in the card shoe apparatus **2** to prevent any player and the like counting the ranks of the cards **1** dealt during a game to predict the ranks of the cards when the number of cards not yet dealt becomes small. Therefore, when the cut card **1c** is drawn onto the game table, use of the shuffled playing card set is currently in the card housing unit is stopped soon, or after that game or a few games thereafter.

(37) To implement this rule, the control unit **12** further has a cut card checking function of reading the cut card **1c** by the card reading unit **8** and memorizing the information that indicates the cut card **1c** is read in the memory **13** when the cut card is drawn onto the game table. When the cut card **1c** is drawn to the game table, use of the shuffled playing card set **1** s currently in the card housing is stopped soon, or after that game or a few games thereafter. The card entry/exit restriction unit **30 (40)** is caused to function as a result of the driving unit **35** or **37** being controlled by the program of the control apparatus **12** to prevent the further drawing of the card **1** for stopping further use of the shuffled playing card set **1s**. The end of the use of the shuffled playing card set is in the card housing **5** has determined, then the end of the use of the cards is reported to an administration section of the casino or pit via the outside output means **100**. Furthermore the control unit **12** is configured to have a function of informing the dealer or the like about the end by the display made by lamps or a liquid crystal display unit **102** separately. The cut card **1c** is normally colored in the black or the like in order to distinguish the other cards, and become recognizable. In addition, the code which is configured to be identified that it is the cut card itself is printed in UV ink or the like which is invisible under normal conditions. The code attached to the cut card **1c** which is drawn onto the game table is read by the card reading unit **8** in the same way as the above embodiment.

(38) Although the suitable embodiment of the present invention that can be considered at present has been explained hereinbefore, it is to be understood that various modifications can be made to the embodiment, and it is intended that accompanying claims include such all the modifications within the true spirit and the scope of the present invention.

Claims

1. A shuffle check system for shuffled playing cards, the shuffle check system comprising: a card reader that is configured to read rank or suit information from a card of the shuffled playing cards; and a computer including a memory, the computer configured to detect whether there is a special arrangement of the shuffle playing cards based on rank or suit information of one or more cards of the shuffled playing cards, wherein the special arrangement of the shuffle playing cards includes: a case where the rank goes up or down one by one in order for a predetermined number of cards, a case where the same rank continues at a predetermined number of cards, a case where the same suit continues at a predetermined number of cards, a case where the cards repeat the same sequence at a predetermined number of cards, or a case where the arrangement order of a predetermined number of cards matches an arrangement order registered in advance.

2. The shuffle check system according to claim 1, wherein an alarm is output when the special arrangement of the shuffle playing cards occur consecutively at a predetermined number of cards.
 3. The shuffle check system according to claim 2, wherein a wired or wireless communication means is used as a means to output the alarm.
-