

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411062
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Jiang; Ying et al.

Non-belt automatic mechanized sampling system for train

Abstract

Provided is a non-belt automatic mechanized sampling system for a train, including: a working platform provided with a slide rail; a sampling mechanism slidably arranged on the slide rail and configured to collect materials from the carriage of the train; an integrated sample preparation component including a discharging mechanism and a feeder, a crusher, a constant mass dividing machine and a sample retention barrel arranged from top to bottom. The feeder transports the material to the crusher. The crusher crushes the material and transports the crushed material to the constant mass dividing machine. The constant mass dividing machine divides the crushed material into samples to the sample retention barrel, and the discarded material to the discharging mechanism. The discharging mechanism transports the discarded materials to the carriage.

Inventors:	Jiang; Ying (Suzhou, CN), Luo; Yunfei (Suzhou, CN), Jiang; Guoning (Suzhou, CN), Zhang; Guoguang (Suzhou, CN)
Applicant:	LEON INTELLIGENCE & INFORMATION (SUZHOU) TECHNOLOGY CO., LTD. (Jiangsu, CN)
Family ID:	67016511
Assignee:	LEON INTELLIGENCE & INFORMATION (SUZHOU) TECHNOLOGY CO., LTD. (N/A, CN)
Appl. No.:	17/436864
Filed (or PCT Filed):	August 20, 2019
PCT No.:	PCT/CN2019/101641
PCT Pub. No.:	WO2020/220520
PCT Pub. Date:	November 05, 2020

Prior Publication Data

Foreign Application Priority Data

CN 201910350528.4 Apr. 28, 2019

Publication Classification

Int. Cl.: G01N1/28 (20060101); B02C13/14 (20060101); B02C13/286 (20060101); G01N1/04 (20060101); G01N1/08 (20060101); B61B1/00 (20060101)

U.S. Cl.:

CPC G01N1/286 (20130101); B02C13/14 (20130101); B02C13/286 (20130101); G01N1/04 (20130101); B02C2013/28609 (20130101); B02C2013/28672 (20130101); B61B1/00 (20130101)

Field of Classification Search

CPC: G01N (1/286); G01N (1/04); G01N (1/28); G01N (33/22); B02C (13/14); B02C (13/286); B02C (2013/28609); B02C (2013/28672); B61B (1/00); C10L (9/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4179929	12/1978	Redding	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2603393	12/2003	CN	G01N 35/00
202270570	12/2011	CN	N/A
103969079	12/2013	CN	N/A
104634607	12/2014	CN	N/A
108709763	12/2017	CN	N/A
108970720	12/2017	CN	B02C 13/14
109141994	12/2018	CN	N/A
109406192	12/2018	CN	N/A
109490042	12/2018	CN	N/A
109946113	12/2018	CN	N/A
209979260	12/2019	CN	N/A
20130087251	12/2012	KR	N/A
2016101909	12/2015	WO	N/A

OTHER PUBLICATIONS

China National Intellectual Property Administration, The International Search Report, Jan. 7, 2020, for International Application No. PCT/CN2019/101641. cited by applicant

Background/Summary

(1) This application is a U.S. National Stage Application of PCT Application Serial No. PCT/CN2019/101641, filed Aug. 20, 2019, which claims priority to Chinese Patent Application No. 201910350528. 4 filed April 28, 2019, the disclosures of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(2) This application relates to the technical field of bulk material quality inspection, such as a non-belt automatic mechanized sampling system for a train.

BACKGROUND

(3) As a mechanical device, the mechanized sampler can obtain a sample from a batch of materials, the test result of the sample can represent the whole materials. There are many kinds of samplers, different industries and places adopt different structural forms of samplers. Power plants, mines, wharves and gathering stations usually transport large quantities of minerals by train. The mechanized sampling system for train is one of the bulk mineral transportation systems, which is set up to sample solid minerals transported by automobile. The system is integrated with sampling, crushing, dividing, aggregating and discarding. It is widely used in the field of train transportation of solid minerals such as coal, coke and steel because of its reasonable structure, reliable and convenient operation. It can complete the sample collection and primary sample preparation of bulk solid mineral materials transported by train when entering or leaving the factory, which can provide representative samples that meet the weight specified in the corresponding national standard for the next laboratory sample preparation. Therefore, the representativeness of sampling samples is the core index to determine the performance of the mechanized sampling system for train.

SUMMARY

(4) The application provides a non-belt automatic mechanized sampling system for train, which can solve the problem of manual handling of discarded materials by the scraping divider.

(5) The application provides a non-belt automatic mechanized sampling system for a train. The system includes: a working platform provided with a slide rail; a sampling mechanism slidably arranged on the slide rail and configured to collect materials from the carriage of the train; an integrated sample preparation component, which includes a discharging mechanism and a feeder, crusher, a constant mass dividing machine and a sample retention barrel arranged from top to bottom. The feeder is configured to transport the material to the crusher. The crusher is configured to crush the material and transport the crushed material to the constant mass dividing machine. The constant mass dividing machine is configured to divide the crushed material into samples to the sample retention barrel, and the discarded material to the discharging mechanism. The discharging mechanism is configured to transport the discarded materials to the carriage.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is the structural diagram of the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(2) FIG. 2 is the structural diagram of the feeder in the non-belt automatic mechanized sampling

system for the train in the embodiment of the application;

(3) FIG. 3 is the structural diagram of the crusher in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(4) FIG. 4 is the structural diagram of the constant mass dividing machine in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(5) FIG. 5 is the structural diagram of the discharging mechanism in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(6) FIG. 6 is the partial structural diagram of the sampler in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(7) FIG. 7 is the structural diagram of the connection between the rotating driving part and the screw in the sampler of the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(8) FIG. 8 is the structural diagram of the vertical driving mechanism in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(9) FIG. 9 is the structural diagram of the horizontal driving mechanism in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(10) FIG. 10 is the structural diagram of the first driving device in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(11) FIG. 11 is the structural diagram of the first chute in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(12) FIG. 12 is the structural diagram of the second driving device in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(13) FIG. 13 is the structural diagram of the dividing part in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(14) FIG. 14 is the structural diagram of the multi bucket elevator in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(15) FIG. 15 is the structural diagram of the rotary discharger in the non-belt automatic mechanized sampling system for the train in the embodiment of the application;

(16) FIG. 16 is the structural diagram of the automatic filling mechanism in the non-belt automatic mechanized sampling system for the train in the embodiment of the application; and

(17) FIG. 17 is the structural diagram of the spare chute in the non-belt automatic mechanized sampling system for the train in the embodiment of the application.

IN THESE FIGURES

(18) **1**-working platform; **11**-slide rail; **12**-rail; **13**-carriage;

(19) **2**-sampling mechanism; **21**-frame; **22**-walking wheel; **23**-sampler; **231**-screw; **232**-barrel; **233**-rotary drive; **234**-sampling head; **24**-vertical driving mechanism; **241**-first electric motor; **242**-first active wheel; **243**-rack; **244**-sampling head hanger; **25**-horizontal driving mechanism; **251**-second electric motor; **252**-second active wheel; **2531**-first fixed plate; **2532**-second fixed plate; **2541**-first connecting shaft; **2542**-second connecting shaft;

(20) **100**-integrated sample preparation components; **3**-feeder; **4**-crusher; **5**-constant mass dividing machine;

(21) **31**-stock bin; **311**-sidewall; **3111**-cavity; **3112**-first inlet; **312**-floor; **3121**-first outlet; **32**-first rotating bearing; **33**-feeding component; **34**-discharge channel; **35**-first driving device; **351**-third electric motor; **352**-first driven wheel; **353**-second driven wheel;

(22) **41**-shell; **411**-second inlet; **412**-second outlet; **413**-crushing chamber; **42**-second rotating bearing; **43**-crushing mechanism; **431**-hammer plate; **432**-hammer; **44**-first chute; **45**-second driving device; **451**-fourth electric motor; **452**-third active wheel; **453**-second driven wheel; **454**-chain;

(23) **51**-box; **511**-dividing cavity; **512**-third inlet; **513**-discharge port;

(24) **52**-third driving device; **521**-fifth electric motor; **522**-transmission component;

- (25) **53**-sample retention channel; **54**-discharging channel;
- (26) **55**-dividing part; **551**-window;
- (27) **6**-discharging mechanism; **61**-horizontal transmission agency; **611**-outer shell; **612**-sixth electric motor; **62**-multi bucket elevator; **621**-cover; **63**-rotary discharger; **631**-rotary chute; **632**-fifth driving device;
- (28) **7**-sample retention barrel;
- (29) **81**-turntable; **82**-rotary driving device; **83**-lifting mechanism;
- (30) **9**-spare chute.

DETAILED DESCRIPTION

(31) In the description of the application, it should be noted that the orientation or position relationship indicated by the terms “center”, “up”, “down”, “left”, “right”, “vertical”, “horizontal”, “inside” and “outside” is based on the orientation or position relationship shown in the drawings, which is only for the convenience of describing the application and simplifying the description, rather than indicating or implying the device or element referred to must have a specific orientation, constructed and operated in a specific orientation. It cannot be understood as a limitation of the application. In addition, the terms “first” and “second” are used only for descriptive purposes and cannot be understood to indicate or imply relative importance. Among them, the terms “first position” and “second position” are two different positions.

(32) In the description of the application, it should be noted that, the terms “install”, “link” and “connect” should be understood broadly unless otherwise specified and limited. For example, they can be fixed connection, detachable connection or integrated connection; mechanical connection or electrical connection; direct connection or indirect connection through intermediate media, or internal connection between two components. For ordinary technicians in this field, the specific meaning of the above terms in the application can be understood in specific circumstances.

(33) From the perspective of function division, the mechanized sampling system for train is mainly divided into sampling mechanism and sample processing mechanism. The main function of the sampling mechanism is to collect samples of predetermined weight at the specified level and depth of the train carriage according to the setting of the automatic control program. The main function of the sample processing mechanism is to crush and divide the samples collected by the sampling mechanism according to the requirements of the national standard; and to prepare the retained samples with preset particle size and weight for laboratory use; meanwhile to pass the remaining samples to return to the specified location through pre-set mode.

(34) The sampling mechanism includes a drilling sampling head and a moving and lifting device of sampling head. The sample processing mechanism in related technology includes a crusher, dividing belt conveyor and a scraper divider. The crusher mostly adopts horizontal crusher with sieve plate. First the sample is extracted by the drilling sampler, then it falls into the receiving hopper of feeder, transported by closed feeding belt conveyor into the crusher (the crusher is usually located in the middle of the closed feeding belt conveyor) and the crushing of the sample is completed by the crusher. The crushed sample enters the dividing belt conveyor. The conveyor carries out the primary dividing at the same time of transportation. The scraper divider is used to divide and reserve the crushed samples again. The excess sample continues to be transported to the residual material treatment system through the belt conveyor, and then returned to the train carriage or directly discharged back to the mine by the treatment system. All materials are driven by belt in the whole sample preparation process.

(35) Taking coal or coke as an example, the following problems still exist in the actual use of the mechanical sampling system for train in related technology:

(36) 1) In the process of sample preparation, it is usually necessary to collect multiple increments. But if the feeder of mechanized sampling system in related technology gathers multiple increments, especially when the material moisture is large, it is easy to cause material bulking, which affects the subsequent sample collection accuracy.

(37) 2) In the horizontal crushing mode with sieve plate, the mesh of sieve plate is easy to block after long-time use, which affects the subsequent sample preparation accuracy.

(38) 3) It is easy to cause residue and mixing in different batches of samples by using belt as material conveying mode.

(39) 4) The horizontal crushing method with sieve plate can screen out the materials whose particle size is larger than the mesh of the sieve, which affects the representativeness of the subsequent samples to a certain extent.

(40) 5) In the process of dividing, the material above the upper surface height of the belt is scraped off by scraper, only the material below is retained. However, this dividing way easily leads to uneven dividing, resulting in large bias of the whole system.

(41) 6) All the materials are driven by belt in the whole process of sample preparation, the transportation distance is long and the moisture loss is large.

(42) 7) In the related technology, the samples after the dividing of the scraper are usually collected in the sample retention barrel, but the waste materials are usually piled up next to the scraper. When there are more wastes, it will be manually transported to other places.

(43) FIG. 1 is the structural diagram of the non-belt automatic mechanized sampling system for train in the embodiment. FIG. 2 is the structural diagram of the feeder in the non-belt automatic mechanized sampling system for train in the embodiment. FIG. 3 is the structural diagram of the crusher in the non-belt automatic mechanized sampling system for train in the embodiment. FIG. 4 is the structural diagram of the constant mass dividing machine in the non-belt automatic mechanized sampling system for train in the embodiment. FIG. 5 is the structural diagram of the discharging mechanism in the non-belt automatic mechanized sampling system for train in the embodiment of the application. As shown in FIG. 1-FIG. 17, this embodiment provides a non-belt automatic mechanized sampling system for train, which includes a working platform 1, a first frame 12, a first horizontal driving mechanism 15, a sampling mechanism 2 and an integrated sample preparation component 100.

(44) The working platform 1 is a steel truss structure. In this embodiment, the working platform 1 straddles over a train rail 12. The slide rail 11 is set on the working platform 1 and located above the train rail 12, straddled over the rail 12. The extension direction of the rail 12 is perpendicular to the extension direction of the slide rail 11.

(45) The sampling mechanism 2 is set to collect materials from the carriage 13. The carriage 13 of the train is on the rail 12. In the embodiment, the sampling mechanism 2 includes a second frame 21, a walking wheel 22, a sampler 23, a horizontal driving mechanism 25 and a vertical driving mechanism 24. The walking wheel 22 is rotated on the second frame 21 and slidably arranged on the slide rail 11. The sampler 23 slides on the second frame 21 and the sampler 23 is set to collect materials from the carriage 13. The horizontal driving mechanism 25 can drive the frame 21 to slide along the extension direction of the slide rail 11. The vertical driving mechanism 24 can drive the sampler 23 to move in the vertical direction. In the embodiment, the sampler 23 can collect materials in three directions perpendicular to each other and the collection range of the sampler 23 covers the whole carriage 13 by setting the horizontal driving mechanism 25 and the vertical driving mechanism 24, cooperating with the carriage 13 to move along the rail 12.

(46) As shown in FIG. 6 and FIG. 7, the sampler 23 includes a barrel 232, a rotary drive 233, a sampling head 234 and a screw 231. The barrel 232 is slidably arranged on the frame 21. The vertical driving mechanism 24 is connected with the barrel 232 and the vertical driving mechanism 24 can drive the barrel 232 to move in the vertical direction. The rotary drive 233 is fixed connected with the barrel 232. The sampling head 234 is installed at the bottom of the barrel 232. The sampling head 234 is conical so that the sampler 23 can be smoothly inserted into the material when sampling. The screw 231 is penetrated into the barrel 232 and bottom of the screw 231 is adjacent to the sampling head 234. In the embodiment, the rotary drive 233 is an electric motor. In other embodiments, the rotary drive 233 can also be a hydraulic motor. The screw 231 is driven to

rotate by the rotary drive **233** and the screw **231** gradually extrudes the material into the barrel **232** while rotating.

(47) As shown in FIG. 8, in this embodiment, the vertical driving mechanism **24** includes a first electric motor **241**, a first active wheel **242** connected with the output shaft of the first electric motor **241**, a rack **243** engaged with the first active wheel **242** and sampling head hanger **244**. The rack **243** is fixedly connected with the sampling head hanger **244**. The barrel **232** is connected with the sampling head hanger **244**. The first electric motor **241** is fixedly installed on the frame **21** and the first active wheel **242** is rotationally installed on the frame **21**. When the first electric motor **241** rotates, the sampling head hanger **244** is driven to rise and fall along the vertical direction through the rack **243**, thereby the barrel **232** and the rotary drive **233** fixed on the barrel **232** rise and fall along the vertical direction. In the embodiment, the sampling head hanger **244** is set to ensure that the direction of the barrel **232** is stable during lifting.

(48) In the embodiment, the horizontal driving mechanism **25** includes a second electric motor, a second active wheel connected to the output shaft of the second electric motor, a first driven wheel spaced with the second active wheel and belt mounted on the second active wheel and the first driven wheel. The second active wheel and the first driven wheel are rotatably arranged on the working platform **1**. The second electric motor is also mounted on the working platform **1**. The belt is fixed to the frame **21**. When the second electric motor turns, the sampler **23** moves along the slide rail **11** by the belt. As shown in FIG. 9, in the embodiment, the horizontal driving mechanism **25** includes a second electric motor **251**, a first fixed plate **2531**, a second fixed plate **2532**, a first connecting shaft **2541**, a second connecting shaft **2542** and a second active wheel **252** connected to the output shaft of the second electric motor **251**. Among them, the first fixed plate **2531** is arranged parallel to the second fixed plate **2532**, and the second electric motor **251** is fixed to the second fixing plate **2532**. The output shaft of the second electric motor **251** is connected with the second active wheel **252** after piercing the second fixed plate **2532**. The first connecting shaft **2541** is vertically connected between the first fixed plate **2531** and the second fixed plate **2532**. After passing through the first fixed plate **2531** and the second fixed plate **2532** at both ends of the first connecting shaft **2541**, a walking wheel **22** is connected to each other. The installation of the second connecting shaft **2542** is the same as that of the first connecting shaft, that is, four walking wheels **22** are provided in this embodiment. The walking wheel **22** connected with the second connecting shaft **2542** through the end of the second fixed plate **2532** is meshed with the second active wheel **252**. When the second electric motor **251** rotates, it drives the second active wheel **252** to rotate, the second active wheel **252** drives the second connecting shaft **2542** and the walking wheel **22** at both ends of the second connecting shaft **2542** to rotate at the same time, so as to drive the first connecting shaft **2541** and the walking wheel **22** at both ends of the first connecting shaft **2541** to rotate. Thus, four walking wheels **22** slide along the slide rail **11** simultaneously and to drive the sampler **23** to move along the slide rail **11**. In the embodiment, the second electric motor **251** adopts the frequency conversion control and it can realize the smooth start, operation and stop, which ensures that the sampler **23** driven by the frame **21** can accurately stop at any position within the operation range of the frame **21**. It should be noted that the second electric motor **251** can drive the frame **21** to move normally in the upwind direction when the wind speed is very high.

(49) The opening size of sampling head **234** is determined by the maximum nominal particle size of the collected material, and the opening size of the sampling head **234** is usually three times and more than three times of the maximum nominal particle size. In the embodiment, the sampling mechanism **2** is suitable for carriage **13** of train with height over 1.25 m. In order to prevent the failure of the first electric motor **241**, the first active wheel **242** is equipped with a handle, which is away from the center of the first active wheel **242**. Therefore, when the sampling head **234** dives to the carriage **13**, the first electric motor **241** fails and the sampling head **234** cannot be lifted automatically, the handle can be manually turned to drive the sampling head **234** to lift, which does not affect the normal traffic of the train.

(50) The integrated sample preparation component **100** is located on the side of the train rail **12**. It includes a discharging mechanism **6** and a feeder **3**, a crusher **4**, a constant mass dividing machine **5**, a sample retention barrel **7** driven from top to bottom. The feeder **3** is arranged to transport the material evenly and continuously to the crusher **4**. The crusher **4** is arranged to crush the material and transport the material after crushing to the constant mass dividing machine **5**. The constant mass dividing machine **5** is set to divide the crushed material into constant mass fractions. That is, the constant mass dividing machine **5** can divide the material into samples and discards. The constant mass dividing machine **5** transports the samples to the sample retention barrel **7**, then the samples can be retained. The discards are transported to the discharging mechanism **6**. The discards are transported to the storage place through the discharging mechanism **6**.

(51) In the embodiment, the feeder **3** includes a stock bin **31**, a first rotating bearing **32**, a first driving device **35** and a feeding component **33**. The inner part of the stock bin **31** is provided with a cavity **3111**. The upper and lower ends of the cavity **3111** are provided with a first inlet **3112** and a first outlet **3121** respectively. A sampling mechanism **2** can transport material to the stock bin **31**. The first rotating bearing **32** is arranged at the first outlet **3121**. The first end of the feeding component **33** is fixed to the first rotating bearing **32** and the second end is fitted to the inner wall of the stock bin **31**. The second end of the feeding component **33** can slide relative to the inner wall of the stock bin **31**. In the embodiment, a gap can also be arranged between the second end of the feeding component **33** and the inner wall of the stock bin **31**. The feeding component **33** is located at the bottom of the cavity **3111**. The first driving device **35** is arranged to drive the first rotating bearing **32** to rotate, so that the first rotating bearing **32** drives the feeding component **33** to rotate. When the feeding component **33** rotates, the material can be driven to move to the first outlet **3121**. In the embodiment, the axis of the first outlet **3121** coincides with the axis of the first rotating bearing **32**. When the feeding component **33** rotates, the material in contact with the feeding component **33** can be scraped from the inner wall of the stock bin **31** to the direction of the first outlet **3121**. The material can flow out from the first outlet **3121**, which ensures that the material in the stock bin **31** will not accumulate and the uniformity of the discharge. With the continuous rotation of the feeding component **33**, the material in the stock bin **31** will be reduced layer by layer, which can ensure the continuity and stability of the discharge, so as to ensure that there is no material accumulation and plugging in the subsequent sample preparation process and ensure the representativeness of the prepared samples.

(52) The feeder **3** also includes a first blowing device, and the first blowing device is connected with the external high-pressure gas source through the pipeline. The first blowing device is arranged to clean the material left in the inner wall of the cavity **3111** and the residual material on the surface of the feeding component **33**, so as to prevent material from remaining on the surface of cavity **3111** after material treatment. It can effectively improve the working environment, reduce the labor load of the operator and improve the working efficiency. Solenoid valve or manual control valve can be set on the pipeline, so the first blowing device can start and stop by manual control or by controller.

(53) The stock bin **31** includes an annular sidewall **311** and a floor **312** connected with the bottom of the sidewall **311**. The opening at the top of the sidewall **311** forms the first inlet **3112** and the first outlet **3121** is arranged on the floor **312**.

(54) As shown in FIG. **10**, the first driving device **35** includes a third electric motor **351** and a transmission component. The third electric motor **351** is connected with the first rotating bearing **32** through the transmission component and drives the first rotating bearing **32** to rotate. The transmission component includes a first driven wheel **352** and a second driven wheel **353** meshing with the first driven wheel **352**. The first driven wheel **352** is connected with the output shaft of the third electric motor **351**. The second driven wheel **353** is connected with the first rotating bearing **32**. In the embodiment, the rotation speed of the feeding component **33** is controlled by controlling the rotation speed of the third electric motor **351** to realize the control of the falling speed of the

material.

(55) In the embodiment, the feeder **3** supplies materials to crusher **4** through a first chute **44**. The structure of the first chute **44** is shown in FIG. **11**. In other embodiments, the first chute **44** can also be a downspouting, so that the feeder **3** can supply materials to crusher **4** through the downspouting. In the embodiment, the feeder **3** can also supply materials through discharge channel **34**. The top of the discharge channel **34** is connected to the floor **312** and to the first outlet **3121**. The discharge channel **34** is arranged outside the first rotating bearing **32** and it extends in the vertical direction or set at a non-zero angle with the vertical direction. The material flowing out of the first outlet **3121** is introduced into the crusher **4** through the discharge channel **34**. By setting the discharge channel **34**, the material can slide down to the crusher **4** by self-weight. The structure is simple and the material transmission is faster. It can effectively prevent the material from being exposed to the air for a long time, resulting in water loss and affecting the representativeness of the sample. The inner surface of the discharge channel **34** should be as smooth as possible, so that the material flows smoothly and not easy to adhere. it is easy to clean.

(56) The crusher **4** includes a shell **41**, a crushing mechanism **43** and a second driving device **45**. The inner part of the shell **41** is provided with a crushing chamber **413**. The upper and lower ends of the crushing chamber **413** are respectively provided with second inlet **411** and second outlet **412**. The second inlet **411** is connected with the feeder **3** through the discharge channel **34**. The second outlet **412** is connected with the constant mass dividing machine **5** through second chute. The second chute has the same structure as the first chute **44**. In other embodiments, the second chute can also be a downspouting. The second outlet **412** is connected with the constant mass dividing machine **5** through the downspouting. At least two crushing mechanisms **43** are arranged at intervals along the vertical direction. There is a gap between the crushing mechanism **43** and the inner wall of the crushing chamber **413**, and the size of the gap can be adjusted. The second driving device **45** is arranged to drive the crushing mechanism **43** to rotate. Driven by the second driving device **45**, the crushing mechanism **43** turns. The material falls down along the gap between the inner wall of the crushing mechanism **43** and the crushing chamber **413**. For materials with larger particle size than the gap, it is crushed under the extrusion of the crushing mechanism **43** and the inner wall of the crushing chamber **413**.

(57) A feeder **3**, a crusher **4** and a constant mass dividing machine **5** are connected by a chute or a downspouting, which can effectively improve the transmission efficiency of materials between devices, effectively prevent the material moisture loss and ensure the representativeness of the samples prepared.

(58) The crusher **4** also includes a second rotating bearing **42** partially located in the crushing chamber **413**. The second driving device **45** is arranged to drive the second rotating bearing **42** to rotate. The crushing mechanism **43** includes a hammer plate **431** fixed on the second rotating bearing **42** and a plurality of hammers **432** evenly distributed on the hammer plate **431**. The rotation axis of the hammer plate **431** coincides with the axis of the second rotating bearing **42**. The distance between the hammer **432** and the inner wall of the crushing chamber **413** is adjustable. For materials with larger particle size than the gap, it is crushed under the extrusion of the inner wall of the hammer **432** and the crushing chamber **413**.

(59) As shown in FIG. **12**, the second driving device **45** includes a fourth electric motor **451**, a third active wheel **452** fixed to the output shaft of the electric motor **451**, a second driven wheel **453** fixed to the top of the second rotating bearing **42**, and a chain **454** connecting the third active wheel **452** and the second driven wheel **453**. In other embodiments, the chain **454** may also be replaced with a belt.

(60) The crusher **4** also includes a second blowing device which is arranged on the shell **41** and connected with the external high pressure gas source through the pipeline. It can be set to blow the residual material in the crushing chamber **413**. Solenoid valve or manual valve can be set on the pipeline to control the start and stop of the second blowing device. Through the second blowing

device, the residual material on the inner wall of the crushing chamber **413** and the surface of the crushing mechanism **43** can be swept clean, which can avoid the mixing of different batches of materials, effectively improve the working environment, reduce the labor load of operators and improve the operation efficiency.

(61) The crusher **4** crushes the material through a plurality of crushing mechanisms **43** arranged from top to bottom. By adjusting the gap between the crushing mechanism **43** and the inner wall of the crushing chamber **413**, samples of different particle sizes can be made without sieve plate. By setting the second blowing device on the inner wall of the shell **41**, it can automatically clean the residual material on the inner wall of the crushing chamber **413** and the surface of the crushing mechanism **43**. It reduces the labor intensity of operators and improves the cleaning efficiency.

(62) As shown in FIG. **4** and FIG. **13**, the fixed constant mass dividing machine **5** includes a box **51**, a third driving device **52**, a dividing part **55** and a sample retention channel **53**. The box **51** is provided with a dividing cavity **511**, the top and bottom of the box **51** are respectively provided with a third inlet **512** and a discharge port **513** connected with the dividing cavity **511**. The third inlet **512** is connected with the crusher **4**. The third driving device **52** is installed on the box **51**. The dividing part **55** is located in the dividing cavity **511**, and is arranged to divide the material. There is a gap between the inner wall of the dividing part **55** and the dividing cavity **511**. The third driving device **52** is fixed to the dividing part **55** and the dividing part **55** is provided with window **551**. The dividing part **55** has the first position that enables the window **551** to completely overlap with the third inlet **512** in the vertical direction and the second position that completely not overlap. The third driving device **52** drives the dividing part **55** to rotate between the first position and the second position. In the embodiment, the third driving device **52** can drive the dividing part **55** to rotate continuously in the same direction. The top of the dividing part **55** is connected to the third driving device **52** and the bottom is adjacent to the bottom of the box **51**. The top of the sample retention channel **53** is provided with an opening, which is located in the dividing cavity **511** and directly below the third inlet **512**. The sample retention channel **53** is connected with the sample retention barrel **7**. The divided sample flows into the sample retention barrel **7** through the sample retention channel **53**.

(63) The fixed constant mass dividing machine **5** also includes a discharging channel **54**, the top of which is connected with the discharge port **513**. The sample retention channel **53** is threaded through the discarding channel **54**. The end of the discarding channel **54** is connected with the discharging mechanism **6**.

(64) In the embodiment, the material crushed by the crusher **4** enters into the dividing cavity **511** from the third inlet **512** through the second chute. The dividing part **55** rotates under the drive of the third driving device **52**. Whenever the window **551** turns below the third inlet **512**, the material entering the dividing cavity **511** can fall into the opening at the top of the sample retention channel **53** through the window **551**. And it can be imported into the sample retention barrel **7** through the sample retention channel **53** to complete a sample cutting process. When the window **551** turns to no overlap with the third inlet **512**, the material falls into the upper surface of the dividing part **55** and falls into the discharge port **513** through the gap between the inner wall of the dividing part **55** and the dividing cavity **511**. Then the material is discharged by the discharging channel **54** through the opening at the top of the discharging channel **54**.

(65) The fixed constant mass dividing machine **5** also includes a third blowing device. The third blowing device is installed on the box **51** and connected with the external high pressure gas source through a pipeline, which is arranged to blow the air into the dividing cavity **511**. Through the third blowing device, the residual material in the dividing cavity **511** and on the surface of the dividing part **55** can be blown clean, which can avoid the mixing of different batches of material, effectively improve the working environment, reduce the labor load of operators and improve the operation efficiency. The solenoid valve or manual valve can also be set on the pipeline connected with the external high pressure gas source, so that the automatic control or manual control of the third

blowing device can be realized.

(66) The third driving device **52** includes a fifth electric motor **521** and a first transmission component **522** connected to the output shaft of the fifth electric motor **521**. The first transmission component **522** is connected to the dividing part **55**. The fifth electric motor **521** drives the dividing part **55** rotation through the first transmission component **522**. The first transmission component **522** can be a belt, a chain or a gear transmission component. In the embodiment, the first transmission component **522** is a gear transmission component.

(67) In the embodiment, the discharging mechanism **6** includes a horizontal transmission agency **61**, multi bucket elevator **62** and a rotary discharger **63**. An inlet is arranged on the horizontal transmission agency **61**, and the discharging channel **54** is connected with the inlet through a pipeline. The horizontal transmission agency **61** can transport the material to the multi bucket elevator **62**. The multi bucket elevator **62** can transport the discards to the rotary discharger **63** and the rotary discharger **63** can transport the material to the carriage **13**.

(68) In the embodiment, the horizontal transmission agency **61** includes an outer shell **611**. A channel is set in the outer shell **611** and a feeding screw is set in the channel. One end of the feeding screw is connected with sixth electric motor **612** and the sixth electric motor **612** drives the feeding screw to rotate. The inlet of the horizontal transmission agency **61** is located at the first end of the channel and connected with the channel. After the discards enter from the inlet to the channel, the feeding screw rotates and pushes the discards to the second end of the channel under the drive of the sixth electric motor **612**. The outer shell **611** is provided with an outlet which is located at the bottom of the second end of the channel.

(69) The multi bucket elevator **62** includes a fourth driving device and a lifting bucket. The fourth driving device includes a fourth active wheel and a third driven wheel arranged along the vertical direction. The fourth active wheel and the third driven wheel are connected through a chain, and the fourth active wheel is connected with the seventh electric motor. The chain is fixedly connected with the lifting bucket so that the chain can drive the lifting bucket up and down in the vertical direction. In the embodiment, the chain is pivoted with the lifting bucket, when the lifting bucket passes through the highest point, it can rotate relative to the chain and unload the material. The number of lifting buckets in this embodiment is multiple. In the embodiment, as shown in FIG. **14**, the multi bucket elevator **62** also includes a cover **621**. The cover **621** sets the fourth driving device and the lifting bucket cover inside and the cover **621** is provided with a chute. The chute is located directly below the outlet on the outer shell **611** and located between the fourth active wheel and the third driven wheel. The lifting bucket can be located under the chute, so that the discards can enter into the lifting bucket through the chute.

(70) In the embodiment, the multi bucket elevator **62** also includes a transfer groove which is located on both sides of the fourth active wheel. The chute on the cover **621** is located on both sides of the third driven wheel. The transfer groove is close to the top of the fourth driving device. When the bucket passes through the highest point, the bucket turns over and the material in the bucket can be poured into the transfer groove.

(71) As shown in FIG. **15**, the rotary discharger **63** includes a rotary chute **631** and a fifth driving device **632**. The fifth driving device **632** is rotationally connected with the rotary chute **631**. The fifth driving device **632** can drive the rotary chute **631** to rotate relative to the cover **621**. The top of the rotary chute **631** is provided with a first opening that is located below the transfer groove. The bottom of the transfer groove is provided with a second opening. The first opening is larger than the second opening so that the transfer groove can transport the discards to the rotary chute **631**.

(72) The fifth driving device **632** includes an eighth electric motor, a fifth active wheel mounted on the eighth electric motor and a fourth driven wheel mounted on the rotary chute **631**. The fifth driving wheel and the fourth driven wheel are connected by a chain or a belt. The eighth electric motor is mounted on the cover **621**, so that the rotary chute **631** can be driven by the eighth electric motor. The axis of the first opening at the top of the rotary chute **631** coincides with the axis of the

rotary chute **631**. Thus, it can ensure that during the rotation of rotary chute **631**, the discards can flow into the rotary chute **631** through the transfer groove.

(73) In the embodiment, the discards storage place is the carriage **13**. In other embodiments, it may also be other locations away from the carriage **13**. By rotating the rotary chute **631**, the discards can be discharged into other carriage other than the carriage **13**.

(74) The discards after dividing of the constant mass dividing machine **5** is transported to the carriage **13** by the discharging mechanism **6**, which can replace the manual timing treatment of the discards and improve the operation efficiency.

(75) As shown in FIG. **16**, the non-belt automatic mechanized sampling system for train also includes an automatic filling mechanism. The automatic filling mechanism includes a turntable **81**, a rotary driving device **82** and a lifting mechanism **83**. A plurality of filling positions are arranged on the turntable **81** along the circumferential direction, and the filling position is set to place the sample retention barrel **7**. The rotary driving device **82** is set to drive the turntable **81** to rotate. One of the filling positions is located directly below the sample retention channel **53** in the turntable **81** rotation process. That is, in the turntable **81** rotation process, there is always a filling position can be located directly below the sample retention channel **53**, so that the sample retention barrel **7** can be filled through the sample retention channel **53**. The lifting mechanism **83** is installed on the turntable **81**, and the number of lifting mechanism **83** is equal to the number of filling position. And the lifting mechanism **83** and filling position are set one by one. The lifting mechanism **83** can drive the sample retention barrel **7** to rise and fall in the vertical direction. As shown in FIG. **4**, the sample retention channel **53** is arranged in a non-zero angle with the vertical direction, so as to facilitate the preset space between the sample and the discards, avoid interference with each other. And along the extension direction of the sample retention channel **53**, the pore size of the sample retention channel **53** is consistent. In other embodiments, the lower end of the sample retention channel **53** is bell-shaped and the opening of the sample retention channel **53** gradually increases from top to bottom. The top caliber of the sample retention barrel **7** is less than that of the bottom end of the sample retention channel **53**. The edge of the top opening of the sample retention barrel **7** can fit with the inner surface of the sample retention channel **53** to ensure that the material will not leak to the outside of the sample retention barrel **7** during filling, in which the upper and lower directions refer to the upper and lower directions in FIG. **4**.

(76) In the embodiment, the rotary driving device **82** is an electric motor or a hydraulic motor. The lifting mechanism **83** can be a cylinder or an electric push rod. By setting the automatic filling mechanism, the automatic filling of multiple sample retention barrel **7** can be realized, which can effectively save the working manpower. The sample retention barrel **7** and the sample retention channel **53** are tightly attached to each other which can effectively prevent the loss of material moisture.

(77) In the embodiment, the non-belt automatic mechanized sampling system for train also includes an automatic capping device. Along the rotation direction of the turntable **81**, the automatic capping device and the sample retention channel **53** are respectively located above the two adjacent filling positions. The filling position corresponding to the automatic capping device is located downstream of the filling position corresponding to the sample retention channel **53**. By setting the automatic capping device, the automatic operation can be realized, and the sample retention channel **53** can be automatically sealed after filling to avoid moisture loss.

(78) The working principle of the non-belt automatic mechanized sampling system for train is as follows:

(79) The controller of the non-belt automatic mechanized sampling system for train acquires the train information from the upper terminal to the train carriage **13** under the working platform **1**. The train information includes mineral information and acquisition mode.

(80) In the embodiment, the mineral information includes mineral type, mineral weight, mineral batch and the ore source, etc. According to the mineral information, the controller determines the

sampling frequency, the single sampling quantity, the sampling times and the backup sampling quantity. The sampling mechanism **2** collects materials according to the sampling frequency, and the weight of materials collected each time is equal to the single sampling amount. In the process of collecting materials by the sampling mechanism **2**, the controller also drives the sampler **23** to adjust the position on the slide rail **11** through the horizontal driving mechanism **25**, and adjusts the position of the working platform **1** on the rail **12** relative to the carriage **13**, so that the sampling range of the sampler **23** can cover the whole carriage **13**. In the range of sampling times, the sampler **23** transports the collected materials to the stock bin **31** of the feeder **3**. In the range of backup sampling times, the materials collected by the sampler **23** are manually retained.

(81) If the integrated sample preparation component **100** fails, the material collected by the sampling mechanism **2** can be transported directly to the sample retention barrel **7** through spare chute **9**. As shown in FIG. **17**, the spare chute **9** is fixed to the working platform **1**. When the integrated sample preparation component **100** fails, the sample retention barrel **7** is fixed below the spare chute **9**, and then the sampling mechanism **2** is moved to the top of the spare chute **9**. Thus, the material collected by the sampler **23** enters the sample retention barrel **7** through the spare chute **9**.

(82) There are two collection methods. The first is to collect multiple sub-samples at one time and then the whole sample is sampled through the integrated sample preparation component **100**. The second is to sample each sub-sample through the integrated sample preparation component **100**. When the first collection method is used, the sampler **23** transports all the collected materials to the stock bin **31**. The feeder **3**, the crusher **4** and the constant mass dividing machine **5** of the integrated sample preparation component **100** will feed, crush and constant mass divide in turn. The samples under constant mass divided are stored in the sample retention barrel **7**. The discards are transported to the storage place through the discharging mechanism **6**.

(83) When the second method is used, within the sampling times, the sampler **23** transports the collected material to the stock bin **31**. The integrated sample preparation component **100** prepares the samples for this time. After the sample preparation, the sampler **23** conveys the next batch of materials to the stock bin **31**. During the processing of two adjacent batches of materials by the integrated sample preparation component **100**, the first blowing device cleans the materials left on the inner wall of the cavity **3111** and the surface of the discharge channel **34**. The second blowing device is used to blow the residual materials in the inner wall of the crushing chamber **413** and the surface of the crushing mechanism **43**, and the third blowing device is used to blow the residual materials in the dividing cavity **511** and the surface of the dividing part **55**.

(84) The working principle of the integrated sample preparation component **100** is as follows:

(85) At the beginning of sample preparation, the constant mass dividing machine **5**, the crusher **4** and the feeder **3** are started in turn. And the first blowing device, the second blowing device and the third blowing device are opened in turn after the sample preparation is completed.

(86) After the feeder **3** starts, the first rotating bearing **32** drives the feeding component **33** to rotate, the feeding component **33** scrapes the material to the first outlet **3121**. The material flows evenly from the first outlet **3121** through the discharge channel **34** to the crushing chamber **413**. The second rotating bearing **42** drives the crushing mechanism **43** to rotate and crush the material through the hammer **432** on the crushing mechanism **43** and the inner wall of the crushing chamber **413**. The crushed material flows directly from the second outlet **412** to the constant mass dividing machine **5** without passing through the sieve plate. The divided sample flows into the sample retention barrel **7** through the sample retention channel **53** and remains. The divided discards flows into the discharging mechanism **6** through the discharging channel **54** and transported to the storage place through the discharging mechanism **6**.

(87) In the embodiment, the divide coefficient and the opening of the window **551** can be calculated according to the total mass of the crushed material and the mass of the required sample. The sample with the required mass can be divided by controlling the opening of the window **551**.

For the same batch of materials with different quality, it can meet the requirements that the materials with different quality are cut with the same numbers, so as to make the sample representative. The utility model has the advantages of simple design structure, uniform division, adjustable cutting speed, good stability of division ratio, and it can ensure the uniformity and representativeness of division.

(88) The non-belt automatic mechanized sampling system for train adopts non-belt, sampling and preparation integrated design scheme, which can effectively solve the problems of coal leakage, sticking, blocking and residual mixture in the sampling and sample preparation process of the automatic mechanized sampling system for train in related technology. It can reduce the water loss of coal sample and ensure the precision and bias of the whole sampling system meets the requirements of the national standard. It can complete the work of feeding, crushing, dividing and retaining samples from top to bottom at one time after collecting all sub samples in the sampling mechanism, and it can also continuously crush and reduce single sub sample in the sampling mechanism.

Claims

1. A non-belt automatic mechanized sampling system for a train, comprising: a working platform provided with a slide rail; a sampling mechanism slidably arranged on the slide rail and is configured to collect materials from a carriage of the train; an integrated sample preparation component comprising a discharging mechanism and a feeder, a crusher, a constant mass dividing machine and a sample retention barrel arranged from top to bottom, wherein the feeder is configured to convey the material to the crusher, the crusher is configured to crush the material and convey the crushed material to the constant mass dividing machine, the constant mass dividing machine is configured to divide the crushed material into samples and discards, then convey the samples to the sample retention barrel and discard to the discharging mechanism, and the discharging mechanism is configured to convey the discards to the carriage; and a controller connected to the sampling mechanism; wherein the sampling mechanism comprises: a frame slidably arranged on the slide rail; a walking wheel drivingly arranged on the frame and slidably arranged on the slide rail; a sampler slidably arranged on the frame, wherein the sampler is movable in a vertical direction and is configured to collect materials from the carriage; a horizontal driving mechanism configured to drive the frame to slide along the slide rail; and a vertical driving mechanism configured to drive the sampler to move in the vertical direction.
2. The non-belt automatic mechanized sampling system for the train according to claim 1, wherein the sampler comprises: a barrel slidably arranged on the frame, wherein the vertical driving mechanism is drivingly connected with the barrel; a rotary drive fixedly connected with the barrel; a sampling head installed at one end of the barrel, wherein the sampling head is conical; and a screw penetrated into the barrel, wherein one end of the screw is adjacent to the sampling head, and the rotary drive is drivingly connected with the screw.
3. The non-belt automatic mechanized sampling system for the train according to claim 1, wherein the feeder comprises a stock bin, a first rotating bearing, a first driving device and a feeding component, an inner part of the stock bin is provided with a cavity, a first end of the cavity is provided with a first inlet, a second end of the cavity is provided with a first outlet, and the sampling mechanism is configured to convey the material to the stock bin; the first rotating bearing is threaded through the first outlet; a first end of the feeding component is fixedly connected with the first rotating bearing, a second end of the feeding component is fitted with an inner wall of the stock bin, and the feeding component is configured to drive the material to flow out from the first outlet when the first driving device drives the first rotating bearing to drive the feeding component to rotate; and the first outlet is connected with the crusher.
4. The non-belt automatic mechanized sampling system for the train according to claim 3, wherein

the crusher comprises: a shell internally provided with a crushing chamber, wherein an upper end of the crushing chamber is provided with a second inlet, and a lower end of the crushing chamber is provided with a second outlet; a first chute, wherein the second inlet is connected with the first outlet through the first chute; at least two crushing mechanisms arranged at intervals along the vertical direction to crush materials, wherein a gap between each of the at least two crushing mechanisms and an inner wall of the crushing chamber is adjustable; and a second driving device configured to drive the at least two crushing mechanisms to rotate.

5. The non-belt automatic mechanized sampling system for the train according to claim 4, wherein the crusher further comprises a second rotating bearing drivingly arranged in the shell, the second driving device is configured to drive the second rotating bearing to rotate, the crushing mechanism comprises a hammer plate fixedly mounted on the second rotating bearing and a plurality of hammers uniformly distributed on the hammer plate, and the plurality of hammers are configured to crush the material.

6. The non-belt automatic mechanized sampling system for the train according to claim 5, wherein the constant mass dividing machine comprises: a box provided with a dividing cavity, wherein a top of the dividing cavity is provided with a third inlet, a bottom of the driving cavity is provided with a discharge port, and the third inlet is connected with the crusher; a third driving device installed on the box; a dividing part located in the dividing cavity, wherein a gap is arranged between the dividing part and an inner wall of the dividing cavity, a window is arranged on the dividing part, the window is arranged to have a first position completely overlapped with the third inlet and a second position completely not overlapped with the third inlet in the vertical direction, and the third driving device is configured to drive the dividing part to rotate between the first position and the second position; and a sample retention channel located directly below the third inlet and below the window, wherein the sample retention channel is connected with the sample retention barrel.

7. The non-belt automatic mechanized sampling system for the train according to claim 6, wherein the constant mass dividing machine further comprises a discharging channel, a top of the discarding channel is connected with the discharge port, a bottom of the discharge port is connected with the discharging mechanism, and the sample retention channel is threaded through the discarding channel.

8. The non-belt automatic mechanized sampling system for the train according to claim 7, wherein the discharging mechanism comprises a pipeline, a horizontal transmission agency, a multi bucket elevator and a rotary discharger, the horizontal transmission agency comprises an inlet, and the discharging channel is connected with the inlet through the pipeline; and the horizontal transmission agency is configured to transport the material to the multi bucket elevator, the multi bucket elevator is configured to transport the discards to the rotary discharger, and the rotary discharger is configured to transport the discards to the carriage.

9. The non-belt automatic mechanized sampling system for the train according to claim 6, further comprising an automatic filling mechanism, wherein the automatic filling mechanism comprises: a turntable provided with a plurality of filling positions evenly distributed on the turntable along a circumference of the turntable, wherein the plurality of filling positions are configured to place the sample retention barrel; a rotary driving device configured to drive the turntable to rotate, so that one of the plurality of filling positions is directly below the sample retention channel; and a plurality of lifting mechanisms installed on the turntable and located below the plurality of filling positions, wherein the plurality of lifting mechanism are in one-to-one correspondence to the plurality of filling positions, the lifting mechanism is configured to drive the sample retention barrel to rise and fall in the vertical direction, a bottom of the sample retention channel is bell shaped, a top of the sample retention channel is provided with an opening, and an edge of the opening fits with an inner surface of the sample retention channel.
