

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281717

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Brubaker; William et al.

BODY FLUID MOVEMENT SYSTEM WITH ONE OR MORE SENSORS AND ARTIFICIAL INTELLIGENCE

Abstract

A body fluid movement apparatus includes a body fluid movement apparatus tube with a lumen, a proximal end, a distal end and a balloon coupled to the proximal end. The balloon is configured to be positioned in an interior of a bladder. The proximal end is configured to provide flow of body fluid from the bladder through the lumen, with a draining bag collecting body fluid from the bladder through the lumen. The drainage bag has an inlet port for receiving body fluid and an outlet port for draining body fluid from the drainage bag. The urinary catheter tube includes the proximal end and the proximal end, with a plurality of body fluid draining holes that receive body fluid from the bladder and allow it to be transported to and through the body fluid movement apparatus tube. One or more sensors are positioned in an interior of the catheter tube and are in contact with the patient's urine. The one or more sensors provide sensor data, at least a portion of sensor data being noisy data that contains one or more of errors, outliers, and inconsistencies. Logic resources provide preprocessing of the noisy data to create cleaned sensor data used for one or more of: identification, cleaning, and transforming of noisy data for the machine learning algorithms to produce the cleaned sensor data. An artificial intelligence system coupled to or including an AI database. The AI engine, with a plurality of machine learning algorithms, provide analysis of the cleaned sensor data used for medical monitoring of one or more medical conditions of the patient by the machine learning algorithms, the analysis of the cleaned sensor data being used for the medical monitoring of the patient.

Inventors: Brubaker; William (Palo Alto, CA), Davis; Paul (Los Altos, CA)

Applicant: Brubaker; William (Palo Alto, CA); Davis; Paul (Los Altos, CA)

Family ID: 96948355

Appl. No.: 19/060990

Filed: February 24, 2025

Related U.S. Application Data

Publication Classification

Int. Cl.: **A61M25/00** (20060101); **A61B5/00** (20060101); **A61M25/10** (20130101); **G16H20/40** (20180101)

U.S. Cl.:

CPC **A61M25/0017** (20130101); **A61B5/6853** (20130101); **A61B5/7217** (20130101); **A61M25/10** (20130101); **G16H20/40** (20180101);

Background/Summary

BACKGROUND

Field of the Invention

[0001] This invention relates to body fluid movement systems catheters, and more specifically to body fluid movement apparatus coupled to or configured to be coupled to an AI system with preprocessing of noisy sensor data.

Description of the Related Art

[0002] Various developments have added diagnostic capabilities to Foley catheters, including pressure and temperature measurement capabilities. For example, Singer, Patent Document 1, discloses a catheter having an oxygen sensing function. Both Rhea and U.S. Pat. No. 5,057,059 and 1993, disclose pressure sensors associated with Foley catheters. U.S. Pat. No. 6,057,059 to Noda discloses a temperature sensor associated with a Foley type catheter.

[0003] Urinary catheters are medical devices that are widely used for the management of urinary retention and incontinence. These catheters are inserted into the bladder through the urethra to drain urine.

[0004] The kidneys make approximately 1.5 liters of urine daily and typical bladder capacity is 300 to 500 milliliters. When a person is unable to urinate, the problem can quickly become serious. As urine builds up in the bladder, it becomes uncomfortable, then painful. If the problem continues, the bladder can become overly full and urine can back up into a patient's kidneys, causing damage that can be permanent. When this happens, a sterile, flexible catheter tubes with lumens called a urinary catheter is inserted into the urethra (where urine leaves the body) and is gently pushed up until the end rests in a patient's bladder. The catheter then drains the urine, through attached tubing to a gravity drainage bag.

[0005] Urinary catheters are often used during surgery, as a patient cannot control its bladder while under anesthesia. For this purpose, a Foley catheter is typically placed prior to surgery and keeps the bladder empty throughout. It often remains in place until the surgery is completed, and a patient is awake and alert enough to begin urinating normally. A Foley catheter is a sterile urinary catheter that is intended to stay in place for an extended period of time.

[0006] A urinary catheter, regardless of type, increases the risk of a urinary tract infection. Even though sterile technique is used to insert them, the introduction of any foreign body into the urinary tract increases the risk of infection.

[0007] If pathogens enter the urinary tract, they may cause an infection. Many of the pathogens that cause a catheter-associated urinary tract infection are commonly found in a patient's intestines that do not usually cause an infection there. Pathogens can enter the urinary tract when the catheter is being put in or while the catheter remains in the bladder.

[0008] The longer a urinary catheter stays in the bladder, the greater the chance of infection. Infection is the most common problem. The catheter may let pathogens into a patient's body, where they can cause an infection of the bladder, urethra, urinary tract, or kidneys.

[0009] Artificial intelligence (AI) is the intelligence of machines or software, as opposed to the intelligence of human beings or animals. AI applications include advanced web search engines

[0010] It is the science and engineering of making intelligent machines, especially intelligent computer programs. It is related to the similar task of using computers to understand human intelligence. Artificial intelligence (AI) is a wide-ranging branch of computer science concerned with building smart machines capable of performing tasks that typically require human intelligence. While AI is an interdisciplinary science with multiple approaches, advancements in machine learning and deep learning.

[0011] Artificial intelligence systems can be improved by one or more of: adding new and fresh data; expanding the associated dataset; improving data collection; using synthetic data; improving the data; enriching the data; improving data quality; leveraging data augmentation; improve the architecture; and the like.

[0012] Currently, the common methods to monitor the individual health are still based on clinical observation and self-reported questionnaires for disease diagnosis and classification. Clinical observation is inefficient due to the heavy burden on physicians who must take care of several patients and the tendency to delay the diagnosis and treatment of patients. The self-reported questionnaires, on the other hand, requires a high level of patient attention, concentration, and mental state at the time. Prominent examples of these limitations include the elderly population, babies, and people with disabilities. These problems lead to a much higher rate of misdiagnosis, which not only affects the health of patients and increases their financial burden but also worsens the doctor-patient relationship. According to statistics, the misdiagnosis rate is as high as one in seven worldwide, which affects approximately 1.5 million people each year. Addressing misdiagnosis could free up 30% of the total global healthcare budget.

[0013] The combination of medical sensors and AI has attracted a wide range of interest. Medical sensors convert biomedical parameters into easily measurable signals such as electricity and light and can be divided into off-body detection and near-body monitoring. Off-body detection is mainly performed by medical liquid sensors, gas sensors, and imaging devices to detect body fluids (blood, saliva, urine, etc.), exhaled breath, and medical images for the efficiency and accuracy improvements of disease diagnosis. Near-body monitoring creates new opportunities for telemedicine and continuous monitoring mainly through wearable devices worn directly on the skin of different body parts to collect key information about the wearer's health in a timely manner. Due to the characteristics of continuity, minimally invasive, and multi-indicator, there are various application scenarios, including disease, motion, and mental status monitoring. To improve the efficiency and accuracy of medical sensors diagnosis and treatment, AI algorithms have made extensive progress. Common algorithms currently include support vector machine (SVM), principal component analysis (PCA), decision tree (DT), long short-term memory (LSTM), artificial neural network (ANN), recurrent neural network (RNN), and convolutional neural network (CNN). The large amount of data obtained from sensing devices analyzed by AI algorithms can lead to more opportunities for proactive, modernized, and personalized medicine. Therefore, the combination of accurate sensors and enhanced AI algorithms allows comprehensive information on disease characteristics through a sufficient number and variety of training samples. Systematic clinical assessment of health conditions can then be performed from multiple perspectives to improve the accuracy and efficiency of diagnosis.

[0014] Medical data is typically rich, rapidly growing, and relatively complex in structure. Machine learning (ML) techniques can combine medical datasets from millions of patients, such as diagnostic profiles, imaging records, and wearable information, to analyze the internal structure of the ocean of medical big data, identify patterns of disease conditions, and overcome the general

limitations on access to local datasets. Furthermore, the next-generation healthcare system supported by big data shifts from a centralized hospital-based mode to a parallel mode of monitoring at home, screening and detection at point-of-care testing (POCT), and monitoring during hospitalization, meanwhile, achieves doctor-patient interaction and data transferring via the cloud to ease healthcare resource crowding and facilitate personalized healthcare). Ultimately, systematic health status assessment from comprehensive individual information is used for clinical applications to achieve improved data processing capabilities and resource optimization in healthcare. In this perspective, we present the latest advances in AI in clinical diagnosis from three perspectives on off-body detection, near-body monitoring, disease prediction and CDSS. The challenges and opportunities of AI in personalized medicine in the future are deeply considered and discussed.

[0015] Sensor data from a catheter sensor can include noisy data.

[0016] There is also a need for urinary catheters with artificial intelligence and reduction or elimination of noisy data from the sensor data.

[0017] Thus, a need exists for an intelligent system that uses urine analysis data in a catheter system, with correction and/or elimination of noisy data from the sensor data.

SUMMARY

[0018] An object of the present invention is to provide body fluid movement apparatus coupled to AI systems with a reduction or elimination of noisy data in sensor data.

[0019] Another object of the present invention is to provide a body fluid movement apparatus coupled to AI systems configured to patient monitoring system and reduces or eliminates noisy data in sensor data.

[0020] Another object of the present invention is to provide body fluid movement apparatus with one or more sensors coupled to AI systems, wherein the one or more sensors are used for a patient's predictive information selected from one or more of: a diagnostic aid in dehydration, urinary tract infections, disorders of a urinary tract, kidney and metabolic disorders, cancers of kidneys and adjacent structures, and diagnose and monitor the progression of diabetes, and with a reduction or elimination of noisy data in sensor data.

[0021] A further object of the present invention is to provide body fluid movement apparatus with one or more sensors coupled to AI systems, wherein an artificial intelligence engine is configured to provide information selected from one or more of: a patient's ketone's bilirubin; nitrites; red blood cells; white blood cells; epithelial cells; bacteria; yeast; and parasites; and urinary casts, and with a reduction or elimination of noisy data in sensor data.

[0022] These and other objects of the present invention are achieved in a body fluid movement system. A body fluid movement apparatus includes a body fluid movement apparatus tube with a lumen, a proximal end, a distal end and a balloon coupled to the proximal end. The balloon is configured to be positioned in an interior of a bladder. The proximal end is configured to provide flow of body fluid from the bladder through the lumen, with a drainage bag collecting body fluid from the bladder through the lumen. The drainage bag has an inlet port for receiving body fluid and an outlet port for draining body fluid from the drainage bag. The urinary catheter tube includes the proximal end and the proximal end, with a plurality of body fluid draining holes that receive body fluid from the bladder and allow it to be transported to and through the body fluid movement apparatus tube. One or more sensors are included in the body fluid movement apparatus and positioned to be in contact with a patient's body fluid. An artificial intelligence engine is coupled to the one or more sensors to receive sensor data and make recommendations relative to a health of a patient. Noisy data in the sensor data is reduced and/or eliminated

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] FIGS. **1-5** illustrate one embodiment of a flexible catheter.

[0024] FIG. **6** illustrates one embodiment of a flexible catheter partially or wholly coiled to provided additional catheter length that is stretchable to provide movement.

[0025] FIG. **7** illustrates one embodiment of a flexible catheter made of a suitable material that can stretch when drainage bag moves in directions towards or away a drainage bag.

[0026] FIGS. **8** and **9** illustrates a proximal flexible catheter tube is inserted into a patient

[0027] FIG. **10** illustrates one embodiment of insertion of a proximal end of a flexible catheter inserted into the urethra to reach the bladder.

[0028] FIG. **11** illustrates a flexible catheter with only one tube extending from the bladder to the drainage bag.

[0029] FIG. **12** illustrates an outlet port sufficiently coupled to the inlet so that the two remain coupled when catheter moves or drain bag moves.

[0030] FIG. **13** illustrates a catheter with one or more sensors

[0031] FIG. **14** illustrates inlet and outlet ports remaining coupled irrespective of body movement.

[0032] FIG. **15** illustrates an embodiment with two ports with a locking mechanism.

[0033] FIG. **16** illustrates inlet and outlet ports each have a plurality of ridges that engage with each other to provide a locking arrangement.

[0034] FIG. **17** illustrates the inlet and output ports each having windings similar to a screw.

[0035] FIG. **18** illustrates a two-step locking mechanism, with a connector and lock.

[0036] FIGS. **19A** and **19B** illustrate one embodiment of a twist-lock, with male and female connectors.

[0037] FIG. **20** illustrates one embodiment of a snap-lock includes male and female connectors.

[0038] FIG. **21** illustrates one embodiment of a luer lock.

[0039] FIG. **22** illustrates one embodiment of a clamp lock.

[0040] FIGS. **23** and **24** illustrate one embodiment of an AI system used with the catheter.

[0041] FIG. **25** provides a schematic illustrating an AI system in accordance with some embodiments.

[0042] FIG. **26A** provides a schematic illustrating a mental model in accordance with some embodiments.

[0043] FIG. **26B** provides a schematic illustrating a mental model in accordance with some embodiments.

[0044] FIG. **27** provides a schematic illustrating an AI system in accordance with some embodiments.

[0045] FIG. **28A** provides a schematic illustrating an AI system in accordance with some embodiments.

[0046] FIG. **28B** provides a schematic illustrating an AI system in accordance with some embodiments.

[0047] FIGS. **29A** and **29B** a flow diagram of an embodiment of an AI database cooperating with a search engine and AI engine.

[0048] FIG. **30** provides one or more networks in accordance with some embodiments.

[0049] FIG. **31** provides one or more computing systems in accordance with some embodiments.

[0050] FIG. **32** is another flowchart of a method for patient monitoring, according to some embodiments of the present disclosure.

[0051] FIG. **33** illustrates a block diagram of an example computing device that may implement one or more aspects of the present disclosure, according to various embodiments of the present disclosure.

[0052] FIG. **34A** illustrates a network architecture **2800** for enabling remote management of patients, according to some embodiments of the present disclosure.

[0053] FIG. **34B** illustrates an extended architecture, supplementing the architecture of FIG. **28A**, according to some embodiments of the present disclosure.

[0054] FIG. **34C** illustrates a block diagram of the remote patient management system, according to some embodiments of the present disclosure.

[0055] FIG. **35** illustrates an example wireless sensor system, according to some embodiments of the present disclosure.

[0056] FIG. **36** illustrates noisy data in sensor data.

DETAILED DESCRIPTION

[0057] As illustrated in FIGS. **1-5**, in one embodiment, a flexible catheter **10** is provided that includes one or more a hollow, partially or fully flexible catheter tubes, generally **12**, that can be a single tube, multiple tubes **12(a)-(c)**, with lumens that collect urine from the bladder and leads to a drainage bag **14**. As a non-limiting example, drainage bag **14** can be expandable, flexible, be a urinary leg bag with top and bottom leg attachments that can be flexible, adjustable, and the like. In one embodiment, drainage bag **14** reduces fluid back pressure by avoiding the formation of dependent loops and can include low aspect ratio collection receptacles that rest on a flat surface to improve fluid flows and/or minimize back-pressures exerted by collected fluids. Flexible catheter **10** is kept in place by a bladder retention member that is deployed in the bladder to provide a retention of catheter **10** in the bladder. Flexible catheter with AI engine **65** is collectively (“system **10**”).

[0058] Catheter **10** includes a single flexible catheter tube **12**, multiple flexible catheter tubes **12(a)-(c)**. In one embodiment, flexible catheter tubes **12**, **12(a)-(c)** can be made of a stretched thermoplastic material. The thermoplastic material can be extrudable. As a non-limiting example, the thermoplastic material can be (a) from 40 to 70 percent by weight of an elastic composition which comprises: from 50 to 99.5 percent by weight of a block copolymer having thermoplastic rubber characteristics with a central, rubbery polyolefin block and terminal blocks of polystyrene, and optionally including up to about 45 percent by weight of polypropylene, plus from 0.5 to 10 percent by weight of a cross-linked organic silicone elastomer; and (b) from 30 to 60 percent by weight of a hydrophobic oil-type plasticizer to provide the desired degree of softness to said elastic composition.

[0059] In one embodiment, all or a portion, particularly the end section of flexible catheter **12** and/or **12(c)** can be partially or wholly coiled to provided additional catheter length that is stretchable to provide movement, see FIG. **6**. The coiled portion can readily extend and contract to relieve tension on the catheter **10**. In one embodiment, flexible catheter tube **12**, **12(a)-(c)** is movable with respect to drain bag **14**, see FIG. **6**. As a non-limiting example, distal end of **12(c)** can be coupled to drainage bag inlet port **22** with a flexible, expandable outlet port **26**. All or all of a portion of urinary catheter **10**, and the like and also made of a suitable material that is able to stretch when drainage bag moves in directions towards or away from outlet port **26**, see FIG. **7**.

[0060] Common indications for placing a urinary flexible catheter in a patient include: (i) acute or chronic urinary retention, both mechanical such as in the case of benign prostatic hypertrophy or non-mechanical such as in spastic bladder neck; (ii) the need to measure the urine output in critical care patients; (iii) incontinence; and (iv) patients post bladder or gynecological surgery.

[0061] As illustrated in FIGS. **8** and **9**, in one embodiment, proximal flexible catheter tube **12(a)** is inserted into a patient, in this embodiment, the penis, which can be held at a selected angle, for example 90 degrees. Catheter **12(a)** or a single flexible catheter tube is advanced into the patient's urinary meatus. There may be resistance at the urethral sphincter or the prostate. It is recommended that the advancement be paused to allow the sphincter to relax. The penis is then lower and the flexible catheter tube **12(a)** continues to advance.

[0062] Catheter **10** can be an indwelling catheter, a condom catheter, intermittent self-catheter, and the like. Dimensions of catheter **10** can be 10 Fr (3.3 mm) to 30 Fr (10 mm), and color-coded by size and have a solid color band on the outer end of the bladder retention member for easy size

identification. Size 12 Fr is large enough to relieve urinary obstruction in most adults, although practitioners typically choose size 14 to 16 Fr for initial catheterization. As a non-limiting example, suitable dimensions of catheter **10**, more particularly of flexible catheter tubes **12** can be as follows: TABLE-US-00001 Color Size French Size in Millimeter Light Green 6 2.0 mm Light Blue 8 2.7 mm Black 10 3.3 mm White 12 4.0 mm Green 14 4.7 mm Orange 16 5.3 mm Red 18 6.0 mm Yellow 20 6.7 mm Purple 22 7.3 mm Blue 24 8.0 mm Black 26 8.7 mm

[0063] In one embodiment a flexible catheter **10** is provided. Flexible catheter **10** can include an insertion tip **16**, FIG. **10**, that is advanced by a patient's urethra. In one embodiment, insertion tip **16** is a narrow proximal end of flexible catheter **10** that inserts into the urethra to reach the bladder **18**. Insertion tip **16** includes one or more draining holes/eyelets **20** in that receive fluids, including urine, from the bladder **18**. Draining holes **20** are small holes in proximal flexible catheter tube **12**, which are positioned on or very near insertion tip **16** to make urine draining easy. Flexible catheter drainage holes **20** are sometimes referred to as drainage holes or flexible catheter eyes **20**

[0064] As illustrated in FIG. **11**, a first flexible catheter tube **12(a)**, with lumen is provided. In various embodiments a plurality of flexible catheter tubes **12(a)-(c)**, with lumens, are included and can have one or more intermediate flexible catheter tubes **12(b)** with lumens, a distal flexible catheter tube **12(c)** with lumen and the like. Flexible catheter **10** can have only one flexible catheter tube **12**, extend from the bladder **18** to drainage bag **14**. It will be appreciated that all catheter tubes can be flexible, expandable, moveable, and the like. Flexibility reduces the occurrence of a catheter tube **12** from being in a kinked, non-flowing positioned, obstructed, and bent as to restrict urine flow

[0065] Drain bag **14** includes an inlet port **22** for coupling/attaching to a distal end of flexible distal catheter **12(c)**. Drain bag **14** also includes a drainage outlet port **24** for draining collected urine and the like from drainage bag **12**. Distal end of flexible distal catheter **12(c)** includes an outlet port **26** to couples to inlet port **22**. Outlet port **26** is sufficiently coupled to inlet port **22** so that the two remain coupled when catheter **10** moves or drain bag moves, FIG. **12**. They do not become disconnected from a patient's body motion and/or movement. This is more fully discussed below.

[0066] In one embodiment, flexible catheter **10** can be a straight intermittent flexible catheter, a closed system flexible catheter kit, and the like. As a non-limiting example, flexible catheter **10** can have a variety of insertion tips **16**, such as a straight tip, a crude tip and the like. The decision as to the type of insertion tip **12** to use is often made by the physician, the physician and patient, the nurse, physician's assistant, caregiver and the like. Insertion tip **16** can be at one end of first flexible catheter tubes with lumens **12(a)-12(c)** can be flexible and/or include a spiral. As a non-limiting example, flexible catheter **10** can include only the first tubes **12** with a lumen extending from the bladder to the draining bag **14**. Flexible catheter tubes **12(a)-(c)**, with lumens, as well as lumen **12** can be made of a variety of materials, including but not limited to: assorted polymers, polymer-metal composites polyamide (nylon), polyether block amide, polyurethane, polyethylene terephthalate, and polyimides.

[0067] In one embodiment, flexible catheter tubes **12**, which can be **12(a)-(c)** can be coated or impregnated with a variety of materials **29** for various purposes including but not limited to materials that provide: protect against infection, ease the discomfort of insertion, and the like. As a non-limiting example, tubes **12(a)-(c)** can include one or more lumens inside and outside lumen walls. These walls can be coated or impregnated on the inside and outside lumen walls with biomimetic surface **29** to prevent bacterial or other microbial growth. In another embodiment, the surfaces of the tubes **12** and/or lumen walls impregnated and/or coated with antibiotics, antibacterial or coated with biocompatible materials that prevent bacterial overgrowth, such as silver or copper.

[0068] In one embodiment, catheter **10** includes one or more sensors **28**, FIG. **13**.

[0069] In one embodiment, an introducer can be used to facilitate insertion of catheter **10** into the urinary tract.

[0070] In one embodiment, flexible catheter **10** is made more comfortable. This can be achieved by polishing and recessing drainage holes **20**, which can reduce friction and irritation in the delicate urethral tissues. As a non-limiting example, flexible catheter tubes **12** can be silicone-elastomer, coated after insertion, and the like.

[0071] As previously stated, and as illustrated in FIG. **14**, inlet and outlet ports **22** and **26** remain coupled irrespective of body movement. An infusion cleaning port **30** for cleaning distal end of flexible catheter **12(c)** for can included.

[0072] In one embodiment, ports **22** and **26** remain in a locked engagement and can have a locking mechanism **32**, FIG. **15**, positioned around exteriors or interiors of outlet ports **24** and **26**. This provides a closed system with a locking/tight/secure mechanism **32** that couples a urinary catheter **10** to attach/detach with drainage bag **14**.

[0073] In one embodiment, locking mechanism **32** provides a compression force to outlet ports **24** and **26**, but still allows passage of the fluid, urine, into drain bag **14**. A variety of locking mechanisms **32** can be used including but not limited to: a bore connector, a series-to-twist coupling, (SMC), luer, SMC connector that allows rotation and movement and prevents kinking, one or more series twist-to-connect couplings, twist lock, swivel-snap connectors, locking connectors, windings, brackets, flip locks, lockout locks, pop locks, telescopic tube locks, Locking & telescoping mechanisms for composite tubes Flip lock clamps & twist lock rings Button clips & ball lock pins, push button telescoping tube locks, telescoping tube clamps around telescoping tubing locks, tubular locks, micro-tube cap locks, telescoping tube adjusters, pin clips, lock nuts, and the like. As illustrated in FIG. **16**, in one embodiment, a hollow pipe **32** and a group of telescopic sleeves **34** are used for coupled. The telescopic tube can be a fixed sleeve fixedly arranged at an end part of the closed first end of the hollow tube to communicate the inner cavity of the hollow tube with the outside, and a sliding sleeve which is sleeved with the fixed sleeve in a sliding manner.

[0074] As a non-limiting example, locking mechanism **32** can be a twist-lock **32**, snap-lock **32**, luer-lock **32**, clamp-lock **32** and the like.

[0075] In various embodiments, locking mechanism **32** can be formed of any desired material, giving the locking mechanism **32** a desired amount of flexibility and/or compressibility. Locking mechanism **32** can be formed of silicone or other flexible polymeric material. Silicone provides rubber-like properties and can frictionally engage ports **22** and **26** with compression without interrupting the flow of urine. As a non-limiting example, locking mechanism **32** is coated with a material having a high coefficient of friction to enhance the frictional engagement.

[0076] In one embodiment, locking mechanism **32** can be in a first position in which the flexible catheter distal tube **12(c)** is free to move longitudinally via locking mechanism **32**. This movement reduces the chance that catheter distal tube **12(c)** disengages from inlet port **22** of drain bag **14**. In one embodiment, locking mechanism **32** can move to a second position in catheter distal tube **12(c)**. allowing movement and produces less stress on its engagement with drain bag **14**.

[0077] In one embodiment, illustrated in FIG. **17** inlet port **22** and outlet port **26** each have a plurality of ridges that engage with each other to provide a locking arrangement. In another embodiment, illustrated in FIG. **17**, inlet port **22** and outlet port **26** each have a plurality of windings, such as in a screw, and are coupled together with engagement of the windings. In other embodiments, the drain bag **14** is locked to catheter distal tube **12(c)** with bends notches, recesses, and the like.

[0078] As a non-limiting example, an improved locking mechanism **32** is provided that prevents leaks of urine, is easy for a patient or care giver to use, is compatible a variety of different drain bags **14** and urinary catheters **10** and the like. In one embodiment, locking mechanism **32** is positioned at a place at drain bag **14** so as not to cause any irritation to the patient's skin. Locking mechanism **32** can have a configuration that is substantially smooth, without any rough edges. Locking mechanism **32** can be made of the same material as tube **12(c)**.

[0079] As a non-limiting example, locking mechanism **32** can be a two-step lock **32** to provide greater engagement between urinary catheter **10** and drain bag **14**. This results in a reduction and/or elimination of urine leakage. In one embodiment, a connector **33** is used to couple and/or insert, urinary catheter **10** into drain bag **14**. In a second step, urinary catheter **10** then engages with connector **18** to lock in place, as illustrated in FIG. **18**. This is done by using locking mechanism **32** that ensures urinary catheter **10** does not become disconnected from drain bag **14**, partially when the patient moves.

[0080] In various embodiments, FIG. **18**, locking mechanism can be a twist-lock **36**, snap-lock **38**, clamp-lock **40**, luer lock **42**, and the like. Twist-lock **36** is configured to prevent over-twisting, and under-twisting when locking, and no or little damage to connector **33** and tube **12(c)**, more particularly inlet port **22** and outlet port **26**. Under-tightening results in inadequate coupling and causes leaking.

[0081] FIGS. **19A** and **19B** illustrate one embodiment of a twist-lock **32**, with male and female connectors **44** and **46**. Male connector **44** has a threaded end that is inserted into female connector **46**. Connectors **44** and **46** are then twisted together. This creates a seal.

[0082] As illustrated in FIG. **20**, snap-lock **32** includes male and female connectors **48** and **50**. Male connector **48** has a protruding tab or button **52** that snaps into a corresponding slot of female connector **50**. Connectors **48** and **50** are pushed together until tab or button **52** snaps, creating a seal.

[0083] Referring to FIG. **21**, luer-lock **32** includes male and female connectors **54** and **56**. Female connector **56** has a tapered opening with threads that match those on male connector **54**. The threads secure connectors **54** and **56**, creating a seal.

[0084] As illustrated in FIG. **22**, clamp lock **32** includes male and female connectors **58** and **60**. Male connector **58** is inserted into female connector **60**. Male connector **58** can include a tapered end. A sliding mechanism **62** is used for the coupling, creating a seal.

[0085] Locking mechanism **32** can be added to an existing catheter or be a part of catheter system **10**.

[0086] In various embodiments, system **10** can use AI (AI), as illustrated in FIGS. **23** and **24**. Examples of AI used include but are not limited to including linear regression, logistic regression, decision tree, SVM algorithm, Naive Bayes algorithm, KNN algorithm, K-means, random forest algorithm, dimensionality reduction, and the like.

[0087] As a non-limiting example, a k-means algorithm is used.

[0088] The one or more sensors **28** can be used for urine analysis data/information received from one or more sensors **28**. The one or more sensors **28** can be used to test and monitor urine to check a patient's overall health. The one or more sensors **28** can be used for urinalysis that is part of a routine medical exam, pregnancy checkup or pre-surgery preparation, and the like.

[0089] As non-limiting examples, the one or more sensors **28** can diagnose a medical condition, monitor a medical condition and the like.

[0090] It can help screen conditions related to kidneys and urinary tract. The test may be a diagnostic aid in dehydration, urinary tract infections, disorders of the urinary tract, kidney and metabolic disorders, cancers of kidneys and adjacent structures, etc. Kidney function and response to treatment may be monitored with the test. It is also used to diagnose and monitor the progression of diabetes. Urinalysis may also be advised before hospital admission and surgeries. A urine test can help assess a new pregnancy.

[0091] Urine monitoring with the one or more sensors **28** can be used for one or more of:

[0092] Urine pH level test: A urine pH test measures the acid-base (pH) level in your urine. A high urine pH may indicate conditions including kidney issues and a urinary tract infection (UTI). A low urine pH may indicate conditions including diabetes-related ketoacidosis and diarrhea.

[0093] Ketones urine test: Ketones build up when your body breaks down fats and fatty acids to use as fuel for energy. This is most likely to happen if your body does not get enough sugar or

carbohydrates as fuel. Healthcare providers most often use ketone urine tests to check for diabetes-related ketoacidosis.

[0094] Glucose urine test: A glucose urine test measures the amount of sugar (glucose) in your urine. Under regular circumstances, there should not be glucose in your urine, so the presence of glucose could be a sign of diabetes or gestational diabetes.

[0095] Bilirubin urine test: Bilirubin is a yellowish pigment found in bile; a fluid produced by your liver. Bilirubin in urine can indicate liver or bile duct issues.

[0096] Nitrite urine test: A positive nitrite test result can indicate a urinary tract infection (UTI). However, not all bacteria can convert nitrate (a substance that is normally in your urine) to nitrite, so you can still have a UTI despite a negative nitrite test.

[0097] Leukocyte esterase urine test: Leukocyte esterase is an enzyme that is present in most white blood cells. When this test is positive, it may indicate that there's inflammation in your urinary tract or kidneys. The most common cause for white blood cells in urine is a bacterial urinary tract infection (UTI).

[0098] Urine specific gravity test: A specific gravity test shows the concentration of all chemical particles in your urine. Abnormal results may indicate several different health conditions.

[0099] Microscopic tests that providers may include in a urinalysis include:

[0100] Red blood cell (RBC) urine test: An elevated number of RBCs indicates that there's blood in your urine. However, this test cannot identify where the blood is coming from. For example, contamination with blood from hemorrhoids or vaginal bleeding cannot be distinguished from a bleed somewhere in your urinary system. In some cases, higher-than-normal levels of red blood cells in your urine may indicate bladder, kidney or urinary tract issues.

[0101] White blood cell (WBC) urine test: An increased number of WBCs and/or a positive test for leukocyte esterase may indicate an infection or inflammation somewhere in your urinary tract.

[0102] Epithelial cells: Epithelial cells are cells that form the covering on all internal and external surfaces of your body and line body cavities and hollow organs. Your urinary tract is lined with epithelial cells. It is normal to have some epithelial cells in your urine, but elevated numbers of epithelial cells may indicate infection, inflammation and/or cancer in your urinary tract.

[0103] Bacteria, yeast and parasites: Sometimes, bacteria can enter your urethra and urinary tract, causing a urinary tract infection (UTI). The urine sample can also become contaminated with bacteria, yeast and parasites, especially for people with a vagina. Yeast can contaminate the sample for people who have a vaginal yeast infection. *Trichomonas vaginalis* is a parasite that may also be found in the urine of people who have a vagina. It is the cause of an STI called trichomoniasis.

[0104] Urinary casts: Casts are tiny tube-like particles that can sometimes be in your urine. They are formed from protein released by your kidney cells. Certain types of casts may indicate kidney issues, while others are completely normal.

[0105] In addition, an inside wall of an inner lumen can be coated with a material that has low friction to enhance urine flow. This material can include but is not limited to: plastic, PET, a naturally occurring latex, or synthetic latex material. As a non-limiting example, outer surface of tubes **12** can be coated with a material designed to reduce friction so that catheter **10** can be inserted easily without undue force or trauma to the urethra or the bladder or any other body part. In one embodiment, the tube lumens can be coated on the outer surface with a material that enhances mucosal growth.

[0106] In various embodiments AI is used with information derived from the one or more sensors **28**. The one or more sensors **28** convert biomedical parameters into easily measurable signals such as electricity and light and can be divided into off-body detection and near-body monitoring. Off-body detection is mainly performed by medical liquid one or more sensors **28**, gas sensors **28**, and imaging devices to detect body fluids (blood, saliva, urine, etc.), exhaled breath, and medical images for the efficiency and accuracy improvements of disease diagnosis. Near-body monitoring creates new opportunities for telemedicine and continuous monitoring mainly through wearable

devices worn directly on the skin of different body parts to collect key information about the wearer's health in a timely manner.

[0107] Due to the characteristics of continuity, minimally invasive, and multi-indicator, there are various application scenarios, including disease, motion, and mental status monitoring. To improve the efficiency and accuracy of medical sensor **28** diagnosis and treatment, AI algorithms have made extensive progress. Common algorithms currently include support vector machine (SVM), principal component analysis (PCA), decision tree (DT), long short-term memory (LSTM), artificial neural network (ANN), recurrent neural network (RNN), and convolutional neural network (CNN). The large amount of data obtained from sensing devices analyzed by AI algorithms can lead to more opportunities for proactive, modernized, and personalized medicine. Therefore, the combination of accurate sensor **28** and enhanced AI algorithms allows comprehensive information on disease characteristics through a sufficient number and variety of training samples. Systematic clinical assessment of health conditions can then be performed from multiple perspectives to improve the accuracy and efficiency of diagnosis.

[0108] Machine learning (ML) techniques can combine medical datasets from millions of patients, such as diagnostic profiles, imaging records, and wearable information, to analyze the internal structure of the ocean of medical big data, identify patterns of disease conditions, and overcome the general limitations on access to local datasets. Furthermore, the next-generation healthcare system supported by big data shifts from a centralized hospital-based mode to a parallel mode of monitoring at home, screening and detection at point-of-care testing (POCT), and monitoring during hospitalization, meanwhile, achieves doctor-patient interaction and data transferring via the cloud to ease healthcare resource crowding and facilitate personalized healthcare (FIG. **1**).

Ultimately, systematic health status assessment from comprehensive individual information is used for clinical applications to achieve improved data processing capabilities and resource optimization in healthcare. In this perspective, we present the latest advances in AI in clinical diagnosis from three perspectives on off-body detection, near-body monitoring, disease prediction and CDSS. The challenges and opportunities of AI in personalized medicine in the future are deeply considered and discussed.

[0109] Referring to FIGS. **23** and **24**, in one embodiment, a user can seek from system an artificial intelligence from the server and/or an artificial intelligence engine (AI) engine **65**. In one embodiment, the artificial intelligence engine **65** make one or more of the following recommendations: offer access to medical specialists; improve communication and coordination of care among health care team members and a person getting care; offer advice for self-management of health care; uploading data to a wearer's health care team, including recommendations regarding exercise, types of food, when to eat when to exercise, blood sugar levels, how to modify blood glucose levels, and the like. This artificial intelligence can be displayed at display **78**, FIG. **24**

[0110] In one embodiment, artificial intelligence engine **65** contains identifications and profiles of users who have posted recommendations/ratings, as well as profiles for users and usage feedback for videos and streamed media. In one embodiment, AI module/system, hereafter ("AI engine **65**") receives sensor information from one or more sensors **28**. A user seeking to use the artificial intelligence engine **65** is presented (at some time) with a set of questions or the system otherwise obtains data inputs defining the characteristics of the user. In this case, the user characteristics generally define the context which is used to interpret or modify the basic goal of the user, and therefore the reference-user(s) for the user, though the user may also define or modify the context at the time of use. Various considerations are used in a cluster analysis, in which recommendations relevant to the contexts may be presented, with a ranking according to the distance function from the "cluster definition." As discussed above, once the clustering is determined, advertisements may be selected as appropriate for the cluster, to provide a subsidy for operation of the system, and to provide relevant information for the user about available products.

[0111] Clustering algorithms partition data into a certain number of clusters (groups, subsets, or

categories). Important considerations include feature selection or extraction (choosing distinguishing or important features, and only such features); Clustering algorithm design or selection (accuracy and precision with respect to the intended use of the classification result; feasibility and computational cost; etc.); and to the extent different from the clustering criterion, optimization algorithm design or selection.

[0112] Finding nearest neighbors can require computing the pairwise distance between all points. However, clusters and their cluster prototypes might be found more efficiently. If the clustering distance metric reasonably includes close points, and excludes far points, then the neighbor analysis may be limited to members of nearby clusters, thus reducing the complexity of the computation.

[0113] There are many situations in which a point could reasonably be placed in more than one cluster, and these situations are better addressed by non-exclusive clustering. In the most general sense, an overlapping or non-exclusive clustering is used to reflect the fact that an object can simultaneously belong to more than one group (class). A non-exclusive clustering is also often used when, for example, an object is “between” two or more clusters and could reasonably be assigned to any of these clusters. In a fuzzy clustering, every object belongs to every cluster with a membership weight. In other words, clusters are treated as fuzzy sets. Similarly, probabilistic clustering techniques compute the probability with which each point belongs to each cluster.

[0114] In many cases, a fuzzy or probabilistic clustering is converted to an exclusive clustering by assigning each object to the cluster in which its membership weight or probability is highest. Thus, the inter-cluster and intra-cluster distance function is symmetric. However, it is also possible to apply a different function to uniquely assign objects to a particular cluster.

[0115] A well-separated cluster is a set of objects in which each object is closer (or more similar) to every other object in the cluster than to any object not in the cluster. Sometimes a threshold is used to specify that all the objects in a cluster must be sufficiently close (or similar) to one another. The distance between any two points in different groups is larger than the distance between any two points within a group. Well-separated clusters do not need to be spherical but can have any shape.

[0116] If the data is represented as a graph, where the nodes are objects and the links represent connections among objects, then a cluster can be defined as a connected component, i.e., a group of objects that are significantly connected to one another, but that have less connected to objects outside the group. This implies that each object in a contiguity-based cluster is closer to some other object in the cluster than to any point in a different cluster.

[0117] A density-based cluster is a dense region of objects that is surrounded by a region of low density. A density-based definition of a cluster is often employed when the clusters are irregular or intertwined, and when noise and outliers are present. DBSCAN is a density-based clustering algorithm that produces a partitional clustering, in which the number of clusters is automatically determined by the algorithm. Points in low-density regions are classified as noise and omitted; thus, DBSCAN does not produce a complete clustering.

[0118] A prototype-based cluster is a set of objects in which each object is closer (more similar) to the prototype that defines the cluster than to the prototype of any other cluster. For data with continuous attributes, the prototype of a cluster is often a centroid, i.e., the average (mean) of all the points in the cluster. When a centroid is not meaningful, such as when the data has categorical attributes, the prototype is often a medoid, i.e., the most representative point of a cluster. For many types of data, the prototype can be regarded as the most central point. These clusters tend to be globular. K-means is a prototype-based, partitional clustering technique that attempts to find a user-specified number of clusters (K), which are represented by their centroids. Prototype-based clustering techniques create a one-level partitioning of the data objects. There are several such techniques, but two of the most prominent are K-means and K-medoid. K-means defines a prototype in terms of a centroid, which is usually the mean of a group of points and is typically applied to objects in a continuous n-dimensional space. K-medoid defines a prototype in terms of a

medoid, which is the most representative point for a group of points and can be applied to a wide range of data since it requires only a proximity measure for a pair of objects. While a centroid almost never corresponds to an actual data point, a medoid, by its definition, must be an actual data point.

[0119] In the k-means clustering technique K initial centroids are selected, the number of clusters desired. Each point in the data set is then assigned to the closest centroid, and each collection of points assigned to a centroid is a cluster. The centroid of each cluster is then updated based on the points assigned to the cluster. We iteratively assign points and update until convergence (no point changes clusters), or equivalently, until the centroids remain the same. For some combinations of proximity functions and types of centroids, K-means always converges to a solution, i.e., K-means reaches a state in which no points are shifting from one cluster to another, and hence, the centroids do not change. Because convergence tends to be asymptotic, the end condition may be set as a maximum change between iterations. Because of the possibility that the optimization results in a local minimum instead of a global minimum, errors may be maintained unless and until corrected. Therefore, a human assignment or reassignment of data points into classes, either as a constraint on the optimization, or as an initial condition, is possible.

[0120] To assign a point to the closest centroid, a proximity measure is required. Euclidean (L2) distance is often used for data points in Euclidean space, while cosine similarity may be more appropriate for documents. However, there may be several types of proximity measures that are appropriate for a given type of data. For example, Manhattan (L1) distance can be used for Euclidean data, while the Jaccard measure is often employed for documents. Usually, the similarity measures used for K-means are relatively simple since the algorithm repeatedly calculates the similarity of each point to each centroid, and thus complex distance functions incur computational complexity. The clustering may be computed as a statistical function, e.g., mean square error of the distance of each data point according to the distance function from the centroid. Note that the K-means may only find a local minimum, since the algorithm does not test each point for each possible centroid, and the starting presumptions may influence the outcome. The typical distance functions for documents include the Manhattan (L1) distance, Bregman divergence, Mahalanobis distance, squared Euclidean distance and cosine similarity.

[0121] An optimal clustering can be obtained as long as two initial centroids fall anywhere in a pair of clusters, since the centroids will redistribute themselves, one to each cluster. As the number of clusters increases, it is increasingly likely that at least one pair of clusters will have only one initial centroid, and because the pairs of clusters are further apart than clusters within a pair, the K-means algorithm will not redistribute the centroids between pairs of clusters, leading to a suboptimal local minimum. One effective approach is to take a sample of points and cluster them using a hierarchical clustering technique. K clusters are extracted from the hierarchical clustering, and the centroids of those clusters are used as the initial centroids. This approach often works well but is practical only if the sample is relatively small, e.g., a few hundred to a few thousand (hierarchical clustering is expensive), and K is relatively small compared to the sample size. Other selection schemes are also available.

[0122] In the one embodiment, space requirements for K-means are modest because only the data points and centroids are stored. Specifically, the storage required is $O((m+K)n)$, where m is the number of points and n is the number of attributes. The time requirements for K-means are also modest-basically linear in the number of data points. In particular, the time required is $O(I \times K \times m \times n)$, where I is the number of iterations required for convergence. As mentioned, I is often small and can usually be safely bounded, as most changes typically occur in the first few iterations. Therefore, K-means is linear in m , the number of points, and is efficient as well as simple provided that K , the number of clusters, is significantly less than m .

[0123] In the one embodiment, outliers can unduly influence the clusters, especially when a squared error criterion is used. However, in some clustering applications, the outliers should not be

eliminated or discounted, as their appropriate inclusion may lead to important insights. In some cases, such as financial analysis, apparent outliers, e.g., unusually profitable investments, can be the most interesting points.

[0124] Hierarchical clustering techniques are a second important category of clustering methods. There are two basic approaches for generating a hierarchical clustering: Agglomerative and divisive. Agglomerative clustering merges close clusters in an initially high dimensionality space, while divisive splits large clusters. Agglomerative clustering relies upon a cluster distance, as opposed to an object distance. For example, the distance between centroids or medoids of the clusters, the closest points in two clusters, the further points in two clusters, or some average distance metric. Ward's method measures the proximity between two clusters in terms of the increase in the sum of the squares of the errors that results from merging the two clusters.

[0125] Agglomerative Hierarchical Clustering refers to clustering techniques that produce a hierarchical clustering by starting with each point as a singleton cluster and then repeatedly merging the two closest clusters until a single, all-encompassing cluster remains. Agglomerative hierarchical clustering cannot be viewed as globally optimizing an objective function. Instead, agglomerative hierarchical clustering techniques use various criteria to decide locally, at each step, which clusters should be merged (or split for divisive approaches). This approach yields clustering algorithms that avoid the difficulty of attempting to solve a hard combinatorial optimization problem. Furthermore, such approaches do not have problems with local minima or difficulties in choosing initial points. Of course, the time complexity of $O(m^2 \log m)$ and the space complexity of $O(m^2)$ are prohibitive in many cases. Agglomerative hierarchical clustering algorithms tend to make good local decisions about combining two clusters since they can use information about the pair-wise similarity of all points. However, once a decision is made to merge two clusters, it cannot be undone at a later time. This approach prevents a local optimization criterion from becoming a global optimization criterion.

[0126] In supervised classification, the evaluation of the resulting classification model is an integral part of the process of developing a classification model. Being able to distinguish whether there is non-random structure in the data is an important aspect of cluster validation.

[0127] In one embodiment, a k-means algorithm is used as follows:

[0128] The K Means Clustering algorithm finds observations in a dataset that are like each other and places them in a set. The process starts by randomly assigning each data point to an initial group and calculating the centroid for each one. A centroid is the center of the group. Note that some forms of the procedure allow you to specify the initial sets.

[0129] Then the algorithm continues as follows: it evaluates each observation, assigning it to the closest cluster. The definition of "closest" is that the Euclidean distance between a data point and a group's centroid is shorter than the distances to the other centroids.

[0130] When a cluster gains or loses a data point, the K means clustering algorithm recalculates its centroid. The algorithm repeats until it can no longer assign data points to a closer set.

[0131] When the K means clustering algorithm finishes, all groups have the minimum within-cluster variance, which keeps them as small as possible. Sets with minimum variance and size have data points that are as similar as possible. There is variability amongst the characteristics in each cluster, but the algorithm minimizes it.

[0132] In the one embodiment, the observations within a set should share characteristics. In some cases, the analysts might need to specify different numbers of groups to determine which value of K produces the most useful results.

[0133] In one embodiment, an artificial intelligence engine 65 is used to predict what will happen; or prescriptive, meaning sensor data, from the one or more sensors, uses the data to make suggestions about what action to take, As a nonlimiting example, AI provides predictive information about a user's health, including but not limiting to reminders what to eat, when to eat, when blue sugar is how and low, and the like. Artificial intelligence can also provide predictive

information about a user's other health parameters including but not limited to, oximetry, cardiac health, and like. In one embodiment, the predictive information can be sent by telemetry to a user's physicians, nurses, monitoring station, and the like.

[0134] As a non-limiting example, AI engine **65** is used for systems with a deep learning network with many layers. The layered network can process extensive amounts of data and determine the “weight” of each link in the network for example, in an image recognition system, some layers of the neural network might detect individual features of a face, like eyes, nose, or mouth, while another layer would be able to tell whether those features appear in a way that indicates a face.

[0135] In the one embodiment, there are many different AI engines **65** that can be trained to generate suitable output values for a range of input values; the neuro-fuzzy logic engine **65** is merely one embodiment.

[0136] In the one embodiment, measurement data, the information feeds, and the output parameters may be used to train an AI engine **65** to control the one or more devices in response to the measurement data and information feeds in one embodiment, AI engines **65** can be trained to recognize temporal patterns.

[0137] In one embodiment, sensor **68** measurement data, the information feeds, and the output parameters may be used to train an AI engine **65** to control the one or more devices in response to the measurement data and information feeds.

[0138] In the one embodiment, illustrated in FIGS. **23** and **24**, a computing system **64** includes a logic subsystem **66** and a storage subsystem **68**. Computing system **64** may further include an input subsystem **70**, an output subsystem **72**, a communication subsystem **74**, and/or other components not shown in FIGS. **23** and **24**.

[0139] In the one embodiment, logic subsystem **66** may include one or more physical logic devices configured to execute instructions. For example, the logic subsystem may be configured to execute instructions that are part of one or more applications, services, programs, routines, libraries, objects, components, data structures, or other logical constructs. Such instructions may be implemented to perform a task, implement a data type, transform the state of one or more components, achieve a technical effect, or otherwise arrive at a desired result.

[0140] In the one embodiment, logic subsystem **66** includes one or more processors (as an example of physical logic devices) configured to execute software instructions. Additionally, or alternatively, the logic subsystem may include one or more hardware and/or firmware logic machines (as an example of physical logic devices) configured to execute hardware or firmware instructions. Processors of the logic subsystem may be single-core or multi-core, and the instructions executed thereon may be configured for sequential, parallel, and/or distributed processing. Individual components of the logic subsystem may be distributed among two or more separate devices, which may be remotely located and/or configured for coordinated processing. Aspects of the logic subsystem may be virtualized and executed by remotely accessible, networked computing devices configured in a cloud-computing configuration.

[0141] In the one embodiment, storage subsystem **68** includes one or more physical, non-transitory memory devices configured to hold instructions executable by the logic subsystem in non-transitory form, to implement the methods and processes described herein. When such methods and processes are implemented, the state of storage subsystem **68** may be transformed. e.g., to hold different data. Storage subsystem **68** may include removable and/or built-in devices. Storage subsystem **68** may include optical memory devices, semiconductor memory devices, and/or magnetic memory devices, among other suitable forms. Storage subsystem **68** may include volatile, nonvolatile, dynamic, static, read/write, read-only, random-access, sequential-access, location-addressable, file-addressable, and/or content-addressable devices. Aspects of logic subsystem **66** and storage subsystem **68** may be integrated together into one or more hardware-logic components. While storage subsystem **68** includes one or more physical devices, aspects of the instructions described herein alternatively may be propagated by a communication medium (e.g., an

electromagnetic signal, an optical signal, etc.) that is not necessarily held by a physical device for a finite duration.

[0142] In the one embodiment, an AI database hosted on cloud platform **76** is configured to cooperate with AI engine **65**. In an embodiment, the AI database stores and indexes trained AI objects, and its class of AI objects have searchable criteria. The AI database cooperates with search engine **115** to utilize search criteria supplied from a user, from either or both 1) via scripted software code and 2) via data put into defined fields of a user interface. **S115** can search engine utilizes the search criteria in order for search engine **115** to retrieve one or more AI data objects that have already been trained as query results. The AI database is coupled to an AI engine to allow any of reuse, reconfigure ability, and recomposition of the one or more trained AI data objects from the AI database into a new trained AI model. These and other features of the design provided herein can be better understood with reference to the drawings, description, and claims, all of which form the disclosure of this patent application.

[0143] In general, AI database **114** stores and indexes trained AI objects, and its class of AI objects have searchable criteria. AI database **114** cooperates with search **115** engine to utilize search criteria supplied from a user to retrieve one or more AI data objects that have already been trained as query results. The AI database **114** is coupled to AI engine **65** to allow any of reuse, reconfigure ability, and recomposition of the one or more trained AI data objects from the AI database into a new trained AI model **106**.

[0144] FIG. **23** provides a schematic illustrating an AI system **65** in accordance with some embodiments of the present invention. In one embodiment, in response to received data from sensors **28** and/or users, the AI database **141** stores and indexes trained AI objects, and the class of AI objects have searchable criteria. The AI database **141** of searchable AI objects indexes parameters and characteristics known about the AI objects that allows searching of user supplied criteria from either or both 1) scripted code and 2) defined fields in a user interface.

[0145] In the one embodiment, engine **65** utilizes this search criteria supplied from the user or sensors **28**, from either or both 1) via scripted software code and 2) via data put into defined fields of a user interface, in order for AI engine **65** to find and retrieve relevant AI data objects that have already been trained as query results. In an embodiment, the AI database also stores a specification for a model and not the fully trained AI model itself, because the untrained model has not yet been trained. In the one embodiment, engine is **65** use of the user supplied search criteria from the user interfaces to find relevant trained AI objects stored in the AI data will be described in more detail later.

[0146] AI database can index AI objects corresponding to the main concept and the set of sub concepts making up a given trained AI model so that reuse, recomposition, and reconfiguration of all or part of a trained AI model is possible.

[0147] AI database **141** can be also coupled to engine **65** to allow any of reuse, reconfigure ability, and recomposition of the one or more trained AI data objects into a new trained AI model. As a non-limiting example, AI engine **65** can generates AI models, such as a first AI model. The AI database **141** may be part of and cooperate with various other modules of AI engine **65**. In one embodiment, AI engine **65** has a set of user interfaces **112** to import from either or both 1) scripted software code written in a pedagogical software programming language, such as Inkling, and/or 2) from the user interface **112** with defined fields that map user supply criteria to searchable criteria of the AI objects indexed in the AI database **141**

[0148] The AI database **141** can be part of cloud-based AI service. The AI database **141** can be hosted on cloud platform with the search engine **115** and AI engine **65**.

[0149] As a non-limiting example, The AI database **141** cooperates with AI engine **65**. AI engine **65** can further include an architect module **126**, an instructor module **124**, and a learner module **128**. In the one embodiment, architect module **126** creates and optimizes learning topologies of an AI object, such as the topology of a graph of processing nodes, for the AI objects. The instructor

module **124** carries out a training plan codified in a pedagogical software programming language. The learner module **128** carries out an actual execution of the underlying AI learning algorithms during a training session. The architect module **126**, when reconfiguring or recomposing the AI objects, composes one or more trained AI data objects into a new AI model and then the instructor module **124** and learner module **128** cooperate with one or more data sources to train the new AI model.

[0150] User interface, to the AI database **141** and search engine **115**, can be configured to present a population of known trained AI objects. In the one embodiment, search engine **115** cooperates with the AI database **141** is configured to search the population of known trained AI objects to return a set of one or more already trained AI objects similar to a problem trying to be solved by the user supplying the search criteria.

[0151] The database management system tracking and indexing trained AI objects corresponding to concepts is configured to make it easy to search past experiments, view results, share with others, and start new variants of a new trained AI model.

[0152] In the one embodiment, AI database **141** may be an object orientated database, a relational database, or other similar database, that stores a collection of AI objects (i.e., the trained main concept and sub concepts forming each trained AI model). The AI database **141** can be composed of a set of one or more databases in which each database has a different profile and indexing, where the set of databases are configured to operate in a parallel to then send back accurate, fast, and efficient returns of trained AI objects that satisfy the search query.

[0153] In the one embodiment, AI engine **65** generates a trained AI model **106** and can include one or more AI-generator modules selected from at least an instructor module **124**, an architect module **126**, and a learner module **128** as shown. The instructor module **324** can optionally include a hyperlearner module **125**, and which can be configured to select one or more hyperparameters for any one or more of a neural network configuration, a learning algorithm, a learning optimizer, and the like. The hyperlearner module **125** can optionally be contained in a different AI-generator module such as the architect module **126** or the learner module **128**, or the hyperlearner module **125** can be an AI-generator module itself. The learner module **1328** can optionally include a predictor module **129**, which can provide one or more predictions for a trained AI model. The predictor module **129** can optionally be contained in a different AI-generator module such as the instructor module **124** or the architect module **126**, or the predictor module **129** can be an AI-generator module itself. AI engine **65** can generate the trained AI model **106**, such as trained AI model **106**, from compiled scripted software code written in a pedagogical software programming language via one or more training cycles with AI engine **65**.

[0154] One or more clients **110** can make a submission to create a trained AI model. Once a Mental Model and Curricula have been coded in the pedagogical software programming language, then the code can be compiled and sent to the three main modules, the learner module **128**, the instructor module **124**, and the architect module **126** of AI engine **65** for training. One or more user interfaces **112**, such a web interface, a graphical user interface, and/or command line interface, will handle assembling the scripted code written in the pedagogical software programming language, as well as other ancillary steps like registering the line segments with AI engine **65**, together with a single command. However, each module—the AI compiler module **122**, the web enabled interface to AI engine **65**, the learner module **128** be used in a standalone manner, so if the author prefers to manually invoke the AI compiler module, manually perform the API call to upload the compiled pedagogical software programming language to the modules of AI engine **65**, and the like

[0155] As a non-limiting example, one or more clients **110** can send scripted code from a coder **112** or another user interface to AI compiler **122**. AI compiler **122** compiles the scripted software code written in a pedagogical software programming language. AI compiler **122** can send the compiled scripted code, similar to an assembly code, to the instructor module **124**, which, in turn, can send the code to the architect module **126**. In one embodiment, AI compiler **222** can send the compiled

scripted code in parallel to all of the modules needing to perform an action on the compiled scripted code. The architect module **126** can propose a vast array of machine learning algorithms, such as various neural network layouts, as well as optimize the topology of a network of intelligent processing nodes making up an AI object. The architect module **126** can map between concepts and layers of the network of nodes and send one or more instantiated AI objects to the learner module **128**. Once the architect module **126** creates the topological graph of concept nodes, hierarchy of sub concepts feeding parameters into that main concept (if a hierarchy exists in this layout) and learning algorithm for each of the main concept and sub concepts, then training by the learner module **128** and instructor module **124**, which can be coupled to a hyper learner **125**, can begin.

[0156] The instructor module **124** can request training data from the training data source **219**. Training can be initiated with an explicit start command in the pedagogical software programming language from the user to begin training. For training to proceed, the user needs to have already submitted compiled pedagogical software programming language code and registered all of their external data sources such as simulators (if any are to be used) via the user interfaces with the learner and instructor modules **124**, **126** of AI engine **65**.

[0157] The training data source **119** can send the training data to the instructor module **124** upon the request. The instructor module **124** can subsequently instruct the learner module **128** on training the AI object with pedagogical software programming language-based curricula for training the concepts into the AI objects. Training an AI model **106** can take place in one or more training cycles to yield a trained state of the AI model **106**. The instructor module **124** can decide what pedagogical software programming language-based concepts and streams should be actively trained in a mental model. The instructor module **124** can know what the terminating conditions are for training the concepts based on user criteria and/or known best practices. The learner module **128** or the predictor **129** can elicit a prediction from the trained AI model **106** and send the prediction to the instructor module **124**. The instructor module **124**, in turn, can send the prediction to the training data source **119** for updated training data based upon the prediction and, optionally, instruct the learner module **328** in additional training cycles. When the one or more training cycles are complete, the learner module **328** can save the trained state of the network of processing nodes in the trained AI model **106**. (Note a more detailed discussion of different embodiments of the components making up AI engine **65** occurs later.)

[0158] The AI database may consist of a storage layer which is configured to know how to efficiently store database objects, in this case AI objects, an indexing mechanism to speed retrieval of the stored AI objects, engine **115** to translate a query request into a retrieval strategy to retrieve AI objects that satisfy a query, and a query language which describes to the AI database what AI objects are desired to be retrieved.

[0159] As a non-limiting example, search engine **115** is configured to 1) parse scripted software code written in a pedagogical software programming language and then map that to one or more searchable criteria as well as 2) import the data put into defined fields of the user interface to use as searchable criteria to find relevant trained AI objects indexed in the AI database **341**. In an embodiment, the search engine **115** is configured to also be able to do a natural language search of a submitted description from a user to determine what a similar trained object would be by referencing the 1) indexed criteria and/or 2) signatures and/or 3) example models in the database.

[0160] In one embodiment, AI database **141** is indexed with keywords and problems solved about each stored AI object

[0161] In one embodiment, search engine **115** in query results will return relevant AI objects. The relevant AI objects can be evaluated and return based on several different weighting factors including number of resources consumed to train that concept learned by the AI object

[0162] In one embodiment, search engine **115** utilizes sensor **28** data for relevant trained AI objects. In an embodiment, search engine **343** refers to 1) the signatures of the stored AI objects as well as 2) any indexed parameters for the AI objects indexed by the AI database **141**.

[0163] In an embodiment, the AI database **141** and search engine **115** build an index of algorithms and parameters that have been tried in past.

[0164] FIGS. **24(a)** and **(b)** provide schematics illustrating mental models **200A** and **200B**.

[0165] In one embodiment, AI engine **65** takes in a description of a problem and how one would go about teaching concepts covering aspects of the problem to be solved, and AI engine **65** compiles the coded description into lower-level structured data objects that a machine can more readily understand, builds a network topology of the main problem concept and sub-concepts covering aspects of the problem to be solved, trains codified instantiations of the sub-concepts and main concept, and executes a trained AI model **106** containing one, two, or more neural networks.

[0166] In one embodiment, AI engine **65** can abstract away and automate the low-level mechanics of AI. AI engine **65** can manage and automate much of the lower-level complexities of working with AI. Each program developed in the pedagogical programming language can be fed into AI engine **65** in order to generate and train appropriate intelligence models.

[0167] AI engine **65** can abstract generation of a neural network topology for an optimal solution and faster training time with a curriculum and lessons to teach the neural network via recursive simulations and training sessions on each node making up the neural network.

[0168] In one embodiment, AI engine **65** can contain a vast array of machine learning algorithms, has logic for picking learning algorithms and guiding training, manages data streaming and data storage, and provides the efficient allocation of hardware resources. AI engine **65** can be built with an infrastructure that supports streaming data efficiently through the system. AI engine **65** can use a set of heuristics to make choices about which learning algorithms to use to train each BRAIN. The set of heuristics also make it possible for AI engine **65** to choose from any number of possible algorithms, topologies, and the like. be able to train a number of BRAINs in parallel and then pick the best result from all of the train BRAINs as the best trained AI model for that task.

[0169] FIG. **25** provides a schematic illustrating an AI system including an AI engine **65** in accordance with some embodiments.

[0170] The details for any given implementation of an AI engine **65** may vary substantially, but many have common architectural components such as the following six components: 1) an architect module **126**, 2) an instructor module **124**, 3) a learner module **128**, 4) a compiler module **122**, 5) a hyperlearner module **125**, and 6) one or more interfaces **112** exchanging communications into and out of AI engine **65**. The AI database **141** and search engine **115** may cooperate with the modules of AI engine **65** as discussed above.

[0171] In one embodiment, AI engine **65** is a cloud-hosted platform-as-a-service configured to manage complexities inherent to training AI networks. AI engine **65** can be accessible with one or more client-side interfaces **112**, GUI, CLI, and Web interfaces, to allow third parties to submit a description of a problem in a pedagogical programming language with possible sub concepts that factor in that problem and let the online AI **65** engine build and generate a trained intelligence model for one or more of the third parties.

[0172] In one embodiment, AI system includes the coder **112** on the one or more client systems and the following on the one or more server systems: the AI compiler module **122**; the AI-generator modules including the instructor module **124**, the architect module **126**, and the learner module **128**, the hyperlearner **125**, and the predictor **129** module. In addition to the foregoing, the AI system can include a training data loader **221** configured to load training data from a training data database **214a**, a simulator **614b**, and a streaming data server. The training data can be batched training data, streamed training data, or a combination thereof, and AI engine **65** can be configured to push or pull the training data from one or more training data sources selected from the simulator **214b**, a training data generator, the training data database **214a**, or a combination thereof. In some embodiments, a data stream manager can be configured to manage streaming of the streamed training data. FIG. **25** shows the architect module **126** configured to propose a neural network layout and the learner module **128** configured to save a trained state of a neural network such as the

trained AI model **106**.

[0173] In one embodiment, AI compiler module **122** automates conversion and compiling of the pedagogical programming language describing the problem (main concept) and sub-concepts factoring into the problem. Each statement recited in the code of the pedagogical programming language program submitted to AI engine **65** can be compiled into a structured data object's defined field, which can later be generated and instantiated into its own sub-concept node by the architect module **326**. Each node can have one or more inputs one or more neural networks to process the input data and a resulting output decision/action. The compiled statements, commands, and other codifications fed into the AI compiler can be transformed into a lower-level AI specification.

[0174] In one embodiment, architect module **126** is the component of the system responsible for proposing and optimizing learning topologies (e.g., neural networks) based on mental models.

[0175] Neural networks can be based on a large collection of neural units loosely modeling the way a biological brain solves problems with large clusters of biological neurons connected by axons. Each neural unit is connected with many others, and links can be enforcing or inhibitory in their effect on the activation state of connected neural units. Each individual neural unit can have, for example, a summation function, which combines the values of all its inputs together. There may be a threshold function or limiting function on each connection and on the unit itself such that it must surpass it before it can propagate to other neurons. These systems are self-learning and trained rather than explicitly programmed and excel in areas where the solution or feature detection is difficult to express in a traditional computer program.

[0176] Neural networks can consist of multiple layers or a cube design, and the signal path can traverse from front to back. The goal of the neural network is to solve problems in the same way that the human brain would, although several neural networks are much more abstract. Modern neural network projects typically work with a few thousand and up to a few million neural units and millions of connections.

[0177] In one embodiment, architect module **126** can take the codified mental model and pedagogy and then propose a set of candidate low-level learning algorithms, topologies of a main concepts and sub-concepts, and configurations thereof the architect module **126** believes will best be able to learn the concepts in the model. This is akin to the work that a data scientist does in the toolkit approach, or that the search system automates in the approach with statistical data analysis tools. In one embodiment, it is guided by the pedagogical program instead of being a broad search. The architect module **126** can employ a variety of techniques to identify such models. The architect module **126** can generate a directed graph of nodes. The architect module **126** can break down the problem to be solved into smaller tasks/concepts all factoring into the more complex main problem trying to be solved based on the software code and/or data in the defined fields of the user interface supplied from the user/client device. The architect module **126** can instantiate a main concept and layers of sub-concepts feeding into the main concept. Architect module **126** can generate each concept including the sub-concepts with a tap that stores the output action/decision and the reason why that node reached that resultant output (e.g., what parameters dominated the decision and/or other factors that caused the node to reach that resultant output). This stored output of resultant output and the reasons why the node reached that resultant output can be stored in the trained intelligence model. The tap created in each instantiated node allows explainability for each step on how a trained intelligence model produces its resultant output for a set of data input. The architect module **326** can reference a database of algorithms to use as well as a database of network topologies to utilize. The architect module **326** can reference a table or database of best suggested topology arrangements including how many layers of levels in a topology graph for a given problem, if available. Architect module **126** also has logic to reference similar problems solved by comparing signatures. If the signatures are close enough, the architect module **326** can try the topology used to optimally solve a problem stored in an archive database with a similar signature. Architect module **126** can also instantiate multiple topology arrangements all to be tested and

simulated in parallel to see which topology comes away with optimal results. The optimal results can be based on factors such as performance time, accuracy, computing resources needed to complete the training simulations, and the like

[0178] In some embodiments, architect module **126** can be configured to propose a number of neural networks and heuristically pick an appropriate learning algorithm from a number of machine learning algorithms in one or more databases for each of the number of neural networks. Instances of the learner module **128** and the instructor module **124** can be configured to train the number of neural networks in parallel. The number of neural networks can be trained in one or more training cycles with the training data from one or more training data sources. AI engine **65** can subsequently instantiate a number of trained AI models **106** based on the concepts learned by the number of neural networks in the one or more training cycles and then identify a best trained AI model (e.g., by means of optimal results based on factors such as performance time, accuracy, etc.) among the number of trained AI models **106**.

[0179] In one embodiment, the user can assist in building the topology of the nodes by setting dependencies for particular nodes. Architect module **126** can generate and instantiate neural network topologies for all of the concepts needed to solve the problem in a distinct two-step process. The architect module **326** can generate a description of the network concepts. The architect module **326** can also take the description and instantiate one or more topological shapes, layers, or other graphical arrangements to solve the problem description. The architect module **326** can select topology algorithms to use based on factors such as whether the type of output the current problem has either 1) an estimation output or 2) a discrete output and then factors in other parameters such as performance time to complete the algorithm, accuracy, computing resources needed to complete the training simulations, originality, number of attributes, and the like.

[0180] In one embodiment, instructor module **124** is a component of the system responsible for carrying out a training plan codified in the pedagogical programming language. Training can include teaching a network of intelligent processing nodes to get one or more outcomes, for example, on a simulator. To do so, instructor module **124** can form internal representations about the system's mastery level of each concept and adapt the execution plan based on actual performance during training. The directed graph of lessons can be utilized by instructor module **124** to determine an execution plan for training (e.g., which lessons should be taught in which order). The training can involve using a specific set of concepts, a curriculum, and lessons, which can be described in the pedagogical programming language file.

[0181] In one embodiment, instructor module **124** can train easier-to-understand tasks earlier than more complex tasks. Thus, the instructor module **324** can train sub-concept AI objects and then higher-level AI objects. The instructor module **124** can train sub-concept AI objects that are dependent on other nodes after those other AI objects are trained. However, multiple nodes in a graph may be trained in parallel. Instructor module **124** can run simulations on the AI objects with input data including statistics and feedback on results from the AI object being trained from learner module **128**. Learner module **128** and instructor module **124** can work with a simulator or other data source to iteratively train an AI object with different data inputs. The instructor module **124** can reference a knowledge base of how to train an AI object efficiently by different ways of flowing data to one or more AI objects in the topology graph in parallel, or, if dependencies exist, the instructor module **124** can train serially with some portions of lessons taking place only after earlier dependencies have been satisfied. The instructor module **324** can reference the dependencies in the topology graph, which the dependencies can come from a user specifying the dependencies and/or how the arrangement of AI objects in the topology was instantiated. Instructor module **124** can supply data flows from the data source such as a simulator in parallel to multiple AI objects at the same time where computing resources and a dependency check allows the parallel training.

[0182] In one embodiment, the instructor module **124** may flow data to train AI objects from many data sources including, but not limited to a simulator, a batch data source, a random-data generator,

and historical/guided performance form from past performance. A simulator can give data and get feedback from the instructor module **124** during the simulation that can create an iterative reactive loop from data inputs and data outputs from the AI objects. A batch data source can supply batched data from a database in at least one example. A random-data generator can generate random data based on user-input parameters.

[0183] When starting a training operation, instructor module **124** first generates an execution plan. This is the ordering it intends to use when teaching the concepts, and for each concept which lessons it intends to teach in what order. While the execution plan is executing, instructor module **124** may jump back and forth between concepts and lessons to optimize the learning rate.

[0184] In one embodiment, instructor module **124** looks to reuse similar training flows that have solved similar problems with similar signatures in the past.

[0185] In one embodiment, learner module **128** is a component of the system configured to carry out the actual execution of the low-level, underlying AI algorithms. In training mode, the learner module **328** can instantiate a system conforming to what was proposed by the architect module **326**, interface with instructor module **124** to carry out the computation and assess performance and then execute the learning algorithm itself. Learner module **128** can instantiate and execute an instance of the already trained system. Eventually, learner module **128** writes out network states for each trained sub-AI object and then a combination of the topological graph of the main node with all of the sub-nodes into a trained AI model **106**. Learner module **128** can also write the stored output of each node and why that node arrived at that output into the trained AI model, which gives explainability as to how and why the AI proposes a solution or arrives at an outcome.

[0186] In one embodiment, hyperlearner module **125** performs a comparison of a current problem to a previous problem in one or more databases. Hyperlearner module **125** can reference archived, previously built and trained intelligence models to help guide instructor module **124** to train the current model of nodes. Hyperlearner module **125** can parse an archive database of trained intelligence models, known past similar problems and proposed solutions, and other sources. Hyperlearner module **125** can compare previous solutions similar to the solutions needed in a current problem as well as compare previous problems similar to the current problem to suggest potential optimal neural network topologies and training lessons and training methodologies.

[0187] As a non-limiting example, when, the curriculum trains using a simulation or procedural generation, then the data for a lesson is not data to be passed to the learning system, but the data is to be passed to the simulator. The simulator can use this data to configure itself, and the simulator can subsequently produce a piece of data for the learning system to use for training. This separation permits a proper separation of concerns. The simulator is the method of instruction, and the lesson provides a way to tune that method of instruction, which makes it more or less difficult depending on the current level of mastery exhibited by the learning system. A simulation can run on a client machine and stream data to AI engine **65** for training. In such an embodiment, the client machine needs to remain connected to AI engine **65** while the BRAIN is training. However, if the client machine is disconnected from the server of AI engine **65**, it can automatically pick up where it left off when it is reconnected.

[0188] As a non-limiting example, a machine learning algorithm may have of a target/outcome variable (or dependent variable) which is to be predicted from a given set of predictors (independent variables). Using this set of variables, AI engine **65** generates a function that map inputs to desired outputs. The coefficients and weights plugged into the equations in the various learning algorithms are then updated after each epoch/pass of training session until a best set of coefficients and weights are determined for this particular concept. The training process continues until the model achieves a desired level of accuracy on the training data.

[0189] When in training mode architect module **126** of AI engine **65** is configured to i) instantiate the network of processing nodes in any layers of hierarchy conforming to concepts of the problem being solved proposed by the user and ii) then the learner module **128** and instructor module **124**

train the network of processing nodes in that AI model. To affect the foregoing, AI engine **65** can take compiled pedagogical programming language code and generate a BRAIN learning topology and proceed to follow the curricula to teach the concepts as specified. Depending on the model, training can potentially take substantial amounts of time. AI engine can provide interactive context on the status of training including, for example, showing which nodes are actively being trained, the current belief about each node's mastery of its associated concept, overall and fine-grained accuracy and performance, the current training execution plan, and/or an estimate of completion time. As such, in some embodiments, AI engine **65** can be configured to provide one or more training status updates on training a neural network selected from i) an estimation of a proportion of a training plan completed for the neural network, ii) an estimation of a completion time for completing the training plan, iii) the one or more concepts upon which the neural network is actively training, iv) mastery of the neural network on learning the one or more concepts, v) fine-grained accuracy and performance of the neural network on learning the one or more concepts, and vi) overall accuracy and performance of the neural network on learning one or more mental models.

[0190] Because the process of building pedagogical programs is iterative, AI engine **65** in training mode can also provide incremental training. That is to say, if the pedagogical programming language code is altered with respect to a concept that comes after other concepts that have already been trained, those antecedent concepts do not need to be retrained.

[0191] Additionally, in training mode, the user is able to specify what constitutes satisfactory training should the program itself permit indefinite training.

[0192] As a non-limiting example, a first step AI engine **65** can take is to pick an appropriate learning algorithm to train a mental model. AI engine **65** can have knowledge of many of the available learning algorithms, as well as a set of heuristics for picking an appropriate algorithm including an initial configuration to train from.

[0193] As a non-limiting example, the process of picking an appropriate algorithm, and the like, can be performed by a BRAIN that has been trained (and will continue to be trained) by AI engine, meaning the BRAIN will get better at building BRAINs each time a new one is built. A trained AI-engine neural network, such as a BRAIN, thereby provides enabling AI for proposing neural networks from assembly code and picking appropriate learning algorithms from a number of machine learning algorithms in one or more databases for training the neural networks. AI engine can be configured to continuously train trained AI-engine neural network in providing the enabling AI for proposing the neural networks and picking the appropriate learning algorithms thereby getting better at building BRAINs.

[0194] Architect module **126** can also use heuristics, mental model signatures, statistical distribution inference, and Meta-learning in topology and algorithm selection.

[0195] AI engine **100** and architect module **126** can be configured to heuristically pick an appropriate learning algorithm from a number of machine learning algorithms in one or more databases for training the neural network proposed by architect module **126**. Many heuristics regarding the mental model can be used to inform what types of AI and machine learning algorithms can be used. For example, the data types used have a large influence. For this reason, the pedagogical programming language contains rich native data types in addition to the basic data types. If architect module **126** sees, for example, that an image is being used, a convolutional deep learning neural network architecture might be appropriate. If architect module **126** sees data that is temporal in nature (e.g., audio data, sequence data, etc.), then a recursive deep-learning neural network architecture like a long short-term memory (“LSTM”) network might be more appropriate. The collection of heuristics can be generated by data science and machine learning/AI experts who work on architect module **126** codebase, and who attempt to capture the heuristics that they themselves use in practice.

[0196] As a non-limiting example, in addition to looking at the mental model, architect module **126**

can also consider the pedagogy provided in the pedagogical programming language code. It can, for example, look at the statistical distribution of any data sets being used; and, in the case of simulators, it can ask the simulator to generate substantial amounts of data so as to determine the statistics of data that will be used during training. These distribution properties can further inform the heuristics used.

[0197] In one embodiment, Meta-learning is an advanced technique used by architect module **126**. It is, as the name implies, learning about learning. What this means is that as architect module **126** can generate candidate algorithm choices and topologies for training, it can record this data along with the signature for the model and the resultant system performance. This data set can then be used in its own learning system. Thus, architect module **126**, by virtue of proposing, exploring, and optimizing learning models, can observe what works and what does not, and use that to learn what models it should try in the future when it sees similar signatures.

[0198] In one embodiment, AI engine can include a meta-learning module configured to keep a record such as a meta-learning record in one or more databases. The record can include i) the source code processed by AI engine, ii) mental models of the source code and/or signatures thereof, iii) the training data used for training the neural networks, iv) the trained AI models, v) how quickly the trained AI models were trained to a sufficient level of accuracy, and vi) how accurate the trained AI models became in making predictions on the training data.

[0199] In one embodiment, AI engine **65** will take is to pick an appropriate learning algorithm to train the Mental Model. This is a critical step in training AI. AI engine has knowledge of many of available learning algorithms and has a set of heuristics for picking an appropriate algorithm as well as an initial configuration to train from.

[0200] Once an algorithm is chosen, AI engine **65** can proceed with training BRAIN's Mental Model via Curricula. AI engine manages all of data streaming, data storage, efficient allocation of hardware resources, choosing when to train each concept, how much (or little) to train a concept given its relevance within Mental Model (i.e., dealing with common problems of overfitting and underfitting), and generally is responsible for producing a trained AI model based on given Mental Model and Curricula. As is case with picking an appropriate learning algorithm, guiding training—notably avoiding overfitting and underfitting—to produce an accurate AI solution is a task that requires knowledge and experience in training AIs. AI engine has an encoded set of heuristics manage this without user involvement. Similarly, process of guiding training is also a trained AI model that will only get smarter with each trained AI model it trains. AI engine is thus configured to make determinations regarding i) when to train AI model on each of one or more concepts and ii) how extensively to train AI model on each of one or more concepts. Such determinations can be based on relevance of each of one or more concepts in one or more predictions of a trained AI model based upon training data.

[0201] In one embodiment, AI engine can also determine when to train each concept, how much (or little) to train each concept based on its relevance, and, ultimately, produce a trained BRAIN. AI engine can utilize meta-learning. In meta-learning, AI engine keeps a record of each program it is seen, data it used for training, and generated AIs that it made. It also records how fast those AIs trained and how accurate y became. AI engine learns over that dataset.

[0202] In one embodiment, when training of an AI object occurs, hyper learner module **328** can be configured to save into AI database **141** two versions of an AI object. A first version of an AI object is a collapsed tensile flow representation of AI object. A second version of an AI object is representation left in its nominal non-collapsed state. When search engine **343** retrieves AI object in its nominal non-collapsed state, a programmer desiring to reuse AI object will be able to obtain outputs from non-collapsed graph of nodes with all its rich meta-data and a collapsed concept with a single discrete output. state of AI data objects can be in a non-collapsed state so trained AI object has its full rich data set, which n may be used by user for reuse, reconfigured, or recomposed into a subsequent trained AI model.

[0203] In one embodiment, database management system also indexes and tracks different AI objects with an indication of what version is this AI object. Later versions of an AI object may be better trained for particular task, but earlier versions of AI object may be more generally trained; and thus, reusable for wider range of related tasks, and further trained for that specific task.

[0204] In one embodiment, AI database **141** and or components in AI engine cooperate to allow migrations of learned state to reconfigure a trained AI object. When a system has undergone substantial training achieving a learned state, and a subsequent change to underlying mental models might necessitate retraining, it could be desirable to migrate learned state rather than starting training from scratch. AI engine can be configured to afford transitioning capabilities such that previously learned high dimensional representations can be migrated to appropriate, new, high dimensional representations. This can be achieved in a neural network by, for example, expanding width of an input layer to account for alterations with zero-weight connections to downstream layers. system can n artificially diminish weights on connections from input that are to be pruned until y hit zero and can n be fully pruned.

[0205] In one embodiment, once a trained AI model has been sufficiently trained, it can be deployed such that it can be used in a production application. interface for using a deployed trained AI model is simple: user submits data (of same type as trained AI model was trained with) to a trained AI model-server API and receives trained AI model's evaluation of that data.

[0206] In one embodiment, though a linear approach to building a trained AI model is presented in some embodiments, an author-train-deploy workflow does not have to be treated as a waterfall process. If user decides first refinement of a trained AI model **106** is needed, be it through additional training with existing data, additional training with new, supplemental data, or additional training with a modified version of mental model or curricula used for training, AI engine is configured to support versioning of BRAINs so that user can preserve (and possibly revert to) current state of a BRAIN while refining trained state of BRAIN until a new, more satisfactory state is reached.

[0207] In one embodiment, two or more AI objects can be merged for recomposition and into a new AI object that in one more session learn to work with each or to form a new trained AI model. Simulation time to fully train each of those two or more AI objects merged for recomposition is a much shorter time than starting from scratch and having to train two or more concepts and n having those two concepts having to figure out how to work with each or to achieve an optimal result.

[0208] In one embodiment, AI database **141**, AI engine **65**, and search engine **143** cooperate for storage and retrieval of a database of AI concepts, which can create a new subsequent AI trained object by essentially merging one or more stored trained AI objects with more AI objects in order to recompose to get a new trained AI model.

[0209] AI object may be reconfigured and trained with new coefficients for learning algorithm. Additionally, AI object may also be reused with same set of coefficients for its learning algorithm. Again, as an example, later different versions of an AI object may be better trained for particular task, but earlier versions of AI object may be more generally trained; and thus, reusable for wider range of related tasks, to n be first trained for that specific task.

[0210] FIG. **26A** provides a schematic illustrating an AI system **300A** in accordance with some embodiments.

[0211] In FIG. **26A** a user such as a software developer can interface with AI system **300(a)** through an online interface; however, user is not limited to online interface, and online interface is not limited to that shown in FIG. **26A** With this in mind, AI system **700A** of FIG. **32(a)** can enable a user to make API and web requests through a domain name system ("DNS"), which requests can be optionally filtered through a proxy to route API requests to an API load balancer and web requests to a web load balancer. API load balancer can be configured to distribute API requests among multiple BRAIN service containers running in a Docker network or containerization platform configured to wrap one or more pieces of software in a complete filesystem containing

everything for execution including code, runtime, system tools, system libraries, etc. web load balancer can be configured to distribute web requests among multiple web service containers running in Docker network. Docker network or Docker BRAIN network can include central processing unit (“CPU”) nodes and graphics processing unit (“GPU”) nodes, nodes of which Docker network can be auto scaled as needed. CPU nodes can be utilized for most BRAIN-service containers running on Docker network, and GPU nodes can be utilized for more computationally intensive components such as TensorFlow and learner. A BRAIN-service engineer can interface with AI system **300(a)** through virtual private cloud (“VPC”) gateway and a hardened bastion host configured to secure Docker network. An Elasticsearch-Logstash-Kibana (“ELK”) stack cluster can be shared among all production clusters for dedicated monitoring and logging.

[0212] FIG. **26B** provides a schematic illustrating an AI system **300B** in accordance with some embodiments.

[0213] Following on AI system **300(a)**, bastion host and one or more CPU nodes can be on a public subnet for bidirectional communication through an Internet gateway. One or more CPU nodes, as well as GPU nodes, can be on a private subnet communicatively coupled with public subnet by means of a subnet re between. one or more CPU nodes on public subnet can be utilized by compiler **222**, and architect module **126** of FIGS. **20** and **31**. One or more CPU nodes on private subnet can be utilized by instructor module **124**, and GPU nodes can be utilized by learner module **128** and predictor module **129**. As illustrated in FIG. **33(a)** private subnet can be configured to send outgoing communications to Internet through a network address translation (“NAT”) gateway.

[0214] As a non-limiting example, one or more methods of AI engine **65** can include, in some embodiments, compiling an assembly code, proposing a neural network, training neural network, and instantiating a trained AI model. assembly code can be compiled from a source code, wherein a compiler is configured to generate assembly code from source code written in a pedagogical programming language. source code can include a hierarchical mental model of one or more concepts to be learned by neural network using training data. source code can also include curricula of one or more lessons for training neural network on one or more concepts. neural network can be proposed by one or more AI-engine modules including an architect module **126** for proposing neural network from an assembly code. neural network can be trained by AI engine **65** in one or more training cycles with training data from one or more training data sources. Trained AI model can be instantiated by AI engine based on one or more concepts learned by neural network in one or more training cycles.

[0215] In one embodiment, AI engine **65** can include pushing or pulling training data. AI engine **65** can be configured for pushing or pulling training data from one or more training sources, each of which is selected from a simulator, a training data generator, a training data database, or a combination thereof. training data can be batched training data, streamed training data, or a combination thereof.

[0216] In one embodiment, AI engine **65** can include operating AI engine **65** in a training mode or a predicting mode during one or more training cycles. In the training mode, AI engine **65** can i) instantiate neural network conforming to neural network proposed by architect and ii) train neural network. In predicting mode, AI engine **65** can instantiate and execute trained AI model on training data through one or more API endpoints for one or more predictions in predicting mode.

[0217] In one embodiment, AI engine **65** can include heuristically picking an appropriate learning algorithm. AI engine can be configured for picking appropriate learning algorithm from a number of machine learning algorithms in one or more databases for training neural network proposed by architect.

[0218] In one embodiment, AI engine **65** can include proposing one or more additional neural networks to foregoing, initial neural network; heuristically picking an appropriate learning algorithm for each of one or more additional neural networks; training neural networks in parallel; instantiating one or more additional trained AI models **106**; and identifying a best trained AI model

among trained AI models. Architect module **126** can be configured for proposing one or more additional neural networks. AI engine **65** can be configured for heuristically picking appropriate learning algorithm from number of machine learning algorithms in one or more databases for each of one or more additional neural networks. AI engine **65** can be configured for training neural networks in parallel, wherein one or more additional neural networks can also be trained in one or more training cycles with training data from one or more training data sources. AI engine **65** can be configured to instantiate one or more additional trained AI models **106** based on concepts learned by one or more neural networks in one or more training cycles, and AI engine **65** can be configured to identify a best trained AI model among trained AI models **106**.

[0219] In one embodiment, AI engine **65** can first include providing enabling AI for proposing neural networks from assembly code and picking appropriate learning algorithms from number of machine learning algorithms in one or more databases for training neural networks. AI engine **65** can continuously train a trained AI-engine neural network to provide enabling AI for proposing neural networks and picking appropriate learning algorithms.

[0220] In such embodiments, AI engine **65** can include keeping a record in one or more databases with a meta-learning module. record can include i) source code processed by AI engine **65**, ii) mental models of source code, iii) training data used for training neural networks, iv) trained AI models **106**, v) how quickly trained AI models **106** were trained to a sufficient level of accuracy, and vi) how accurate trained AI models **106** became in making predictions on training data.

[0221] In such embodiments, AI engine **65** can include making certain determinations. Such determinations can include when to train neural network on each of one or more concepts. Such determinations can alternatively or additionally include how extensively to train neural network on each of one or more concepts. Determinations can be based on relevance of each of one or more concepts in one or more predictions of trained AI model **106** based upon training data.

[0222] In such embodiments, AI engine **65** can include providing one or more training status updates on training neural network.

[0223] FIGS. **27(a)** and **(b)** illustrate a flow diagram of an embodiment of an AI database cooperating with a search engine and AI engine **65**. In various embodiments, the example steps below need not be performed in sequential order and some of steps may be optional.

[0224] In step **402**, an AI database cooperates with a search engine and AI engine **65**.

[0225] In step **404**, AI database stores and indexes trained AI objects and its class of AI objects to have searchable criteria.

[0226] In step **405**, parts of a trained AI model are stored and indexed as a collection of trained AI objects corresponding to a main concept and a set of sub concepts feeding parameters into main concept so that reuse, recomposition, and reconfiguration of all or part of a trained AI model is possible.

[0227] In step **408**, a signature module calculates or concatenates a signature for a mental model of concepts in a trained AI model. For example, signature may in a form of hashing such that mental models of different trained AI models that have similar machine learning algorithmic characteristics have similar signatures.

[0228] In step **410**, search engine can have one or both 4) parse scripted software code written in a pedagogical software programming language with search engine and n mapping that to one or more searchable criteria as well as 2) import data put into defined fields of user interface to use as searchable criteria to find relevant trained AI objects indexed in AI database.

[0229] In step **412**, search engine **115** utilizes search criteria supplied from a user, from one or both 1) via scripted software code and 2) via data put into defined fields of a user interface, in order for search engine to retrieve one or more AI data objects that have already been trained as query results.

[0230] In step **414**, search engine utilizes user supplied criteria to query for relevant trained AI objects by referring to 1) signatures of stored AI objects as well as 2) any indexed parameters for

AI objects indexed by AI database.

[0231] In step **416**, a user interface presents a population of known trained AI objects; and searching population of known trained AI objects to return a set of one or more already trained AI objects similar to a problem trying to be solved by user supplying search criteria.

[0232] In step **418**, AI database is configured to be a set of one or more databases so that each database has a different profile and indexing. set of databases are configured to operate in a parallel to n send back accurate, fast, and efficient returns of trained AI objects that satisfy search query.

[0233] In step **420**, AI database cooperate with AI engine to supply one or more AI objects. AI engine includes an architect module configured to create and optimize learning topologies of neural networks for AI objects; an instructor module configured to carrying out a training plan codified in a pedagogical software programming language; and a learner module configured to carrying out an actual execution of underlying AI learning algorithms during a training session, where architect module, when reconfiguring or recomposing AI objects, composes one or more trained AI data objects into a new AI model and instructor module and learner module cooperate with one or more data sources to train new AI model.

[0234] In step **422**, AI database cooperates with an AI engine to cause any of reuse, reconfigure ability, and recomposition of one or more trained AI data objects into a new trained AI model.

[0235] FIGS. **28A** and **28B** illustrate one embodiment of present invention with a number of electronic systems and devices communicating with each or in a network environment in accordance with some embodiments. As a non-limiting example, network environment **500** has a communications network **520**. network **520** can include one or more networks selected from an optical network, a cellular network, Internet, a Local Area Network (“LAN”), a Wide Area Network (“WAN”), a satellite network, a fiber network, a cable network, and various combinations. In some embodiments, communications network **520**. As shown, re may be many server computing systems and many client computing systems connected to each or via communications network **520**. However, it should be appreciated that, for example, a single client computing system can also be connected to a single server computing system. As such, FIG. **30** illustrates any combination of server computing systems and client computing systems connected to each or via communications network **520**.

[0236] In one embodiment, communications network **520** can connect one or more server computing systems selected from at least a first server computing system **504A** and a second server computing system **504B** to each or and to at least one or more client computing systems as well. server computing system **504A** can be, for example, one or more server systems. Server computing systems **504A** and **504B** can respectively optionally include organized data structures such as databases **506A** and **506B**. Each of one or more server computing systems can have one or more virtual server computing systems, and multiple virtual server computing systems can be implemented by design. Each of one or more server computing systems can have one or more firewalls to protect data integrity.

[0237] In one embodiment, at least one or more client computing systems can be selected from a first mobile computing device **502A** (e.g., smartphone with an Android-based operating system), a second mobile computing device **502E** (e.g., smartphone with an iOS-based operating system), a first wearable electronic device **502C** (e.g., a smartwatch), a first portable computer **502B** (e.g., laptop computer), a third mobile computing device or second portable computer **502F** (e.g., tablet with an Android- or iOS-based operating system), a smart device or system incorporated into a first smart automobile **502D**, a smart device or system incorporated into a first smart bicycle **502G**, a first smart television **502H**, a first virtual reality or augmented reality headset **504C**, and like. client computing system **502B** can be, for example, one of one or more client systems **210**, and any one or more of or client computing system, (e.g., **502A**, **502C**, **502D**, **502E**, **502F**, **502G**, **502H**, and/or **504C**) can include, for example, software application or hardware-based system in which trained AI model can be deployed. Each of one or more client computing systems can have one or more

firewalls to protect data integrity.

[0238] In one embodiment, server computing systems can be a cloud provider. A cloud provider can install and operate application software in a cloud (e.g., network **520** such as Internet) and cloud users can access application software from one or more of client computing systems. Generally, cloud users that have a cloud-based site in cloud cannot solely manage a cloud infrastructure or platform where application software runs. Thus, server computing systems and organized data structures with shared resources, where each cloud user is given a certain amount of dedicated use of shared resources. Each cloud user's cloud-based site can be given a virtual amount of dedicated space and bandwidth in cloud. Cloud applications can be different from or applications in its scalability, which can be achieved by cloning tasks onto multiple virtual machines at run-time to meet changing work demand. Load balancers distribute work over set of virtual machines. This process is transparent to cloud user, who sees only a single access point.

[0239] Cloud-based remote access can be coded to utilize a protocol, such as Hypertext Transfer Protocol ("HTTP"), to engage in a request and response cycle with an application on a client computing system such as a web-browser application resident on client computing system. cloud-based remote access can be accessed by a smartphone, a desktop computer, a tablet, or any or client computing systems, anytime and/or anywhere. cloud-based remote access is coded to engage in 1) request and response cycle from all web browser-based applications, 3) request and response cycle from a dedicated on-line server, 4) request and response cycle directly between a native application resident on a client device and cloud-based remote access to one or more client computing system.

[0240] In an embodiment, server computing system **504A** can include a server engine, a web page management component, a content management component, and a database management component. server engine can perform basic processing and operating-system level tasks. web page management component can handle creation and display, or routing of web pages or screens associated with receiving and providing digital content and digital advertisements. Users (e.g., cloud users) can access one or more of server computing systems by means of a Uniform Resource Locator ("URL") associated therewith. Content management component can handle most of functions in embodiments described herein. database management component can include storage and retrieval tasks with respect to database, queries to database, and storage of data.

[0241] In some embodiments, a server computing system can be configured to display information in a window, a web page, or like. An application including any program modules, applications, services, processes, and or similar software executable when executed on, for example, server computing system **504A**, can cause server computing system **504A** to display windows and user interface screens in a portion of a display screen space. With respect to a web page, for example, a user via a browser on client computing system **502B** can interact with web page, and n supply input to query/fields and/or service presented by user interface screens. web page can be served by a web server, for example, server computing system **504A**, on any Hypertext Markup Language ("HTML") or Wireless Access Protocol ("WAP") enabled client computing system (e.g., client computing system **502B**) or any equivalent. Client computing system **502B** can host a browser and/or a specific application to interact with server computing system **504A**. Each application has a code scripted to perform functions that software component is coded to carry out such as presenting fields to take details of desired information. Algorithms, routines, and engines within, for example, server computing system **504A** can take information from presenting fields and put that information into an appropriate storage medium such as a database (e.g., database **506A**). A comparison wizard can be scripted to refer to a database and make use of such data. applications may be hosted on, for example, server computing system **504A** and served to specific application or browser of, for example, client computing system **502B**. applications n serve windows or pages that allow entry of details.

[0242] FIGS. **29A** and **29B** illustrates a computing system **600** that can be, wholly or partially, part of one or more of server or client computing devices in accordance with some embodiments.

Components of computing system **600** can include, but are not limited to, a processing unit **620** having one or more processing cores, a **6630**, and a system bus **621** that couples various system components including system memory **630** to processing unit **620**. system bus **621** may be any of several types of bus structures selected from a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures.

[0243] Computing system **600** typically includes a variety of computing machine-readable media. Computing machine-readable media can be any available media that can be accessed by computing system **600** and includes both volatile and nonvolatile media, and removable and non-removable media. By way of example, and not limitation, computing machine-readable media use includes storage of information, such as computer-readable instructions, data structures, or executable software or roof data. Computer-storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or roof memory technology, CD-ROM, digital versatile disks (DVD) or roof optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or roof magnetic storage devices, or any or tangible medium which can be used to store desired information and which can be accessed by computing device **600**. Transitory media such as wireless channels are not included in machine-readable media. Communication media typically embody computer readable instructions, data structures, or executable software, or roof transport mechanism and includes any information delivery media. As an example, some client computing systems on network **620** need not have optical or magnetic storage. [0244] system memory **630** includes computer storage media in form of volatile and/or nonvolatile memory such as read only memory (ROM) **631** and random access memory (RAM) **632**. A basic input/output system **633** (BIOS) containing basic routines that help to transfer information between elements within computing system **600**, such as during start-up, is typically stored in ROM **631**. RAM **632** typically contains data and/or software that are immediately accessible to and/or presently being operated on by processing unit **620**. By way of example, and not limitation, FIG. **31** illustrates that RAM **632** can include a portion of operating system **634**, application programs **635**, or executable software **636**, and program data **637**. [0245] computing system **600** can also include or removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. **31** illustrates a solid-state memory **641**. Or removable/non-removable, volatile/nonvolatile computer storage media that can be used in example operating environment include, but are not limited to, USB drives and devices, flash memory cards, solid state RAM, solid state ROM, and like. solid-state memory **641** is typically connected to system bus **621** through a non-removable memory interface such as interface **640**, and USB drive **651** is typically connected to system bus **621** by a removable memory interface, such as interface **650**.

[0246] Drives and/or associated computer storage media discussed above, provide storage of computer readable instructions, data structures, or executable software and or data for computing system **600**. In FIG. **31**, for example, solid state memory **641** is illustrated for storing operating system **644**, application programs **645**, or executable software **646**, and program data **647**.

Operating system **644**, application programs **645**, or executable software **646**, and program data **647** are given different numbers here to illustrate that, at a minimum, y are different copies.

[0247] A user may enter commands and information into computing system **600** through input devices such as a keyboard, touchscreen, or software or hardware input buttons **662**, a microphone **663**, a pointing device and/or scrolling input component, such as a mouse, trackball or touch pad. microphone **663** can cooperate with speech recognition software. se and or input devices are often connected to processing unit **620** through a user input interface **660** that is coupled to system bus **621** but can be connected by or interface and bus structures, such as a parallel port, game port, or a universal serial bus (USB). A display monitor **691** or ear type of display screen device is also connected to system bus **621** via an interface, such as a display interface **690**. In addition to monitor **691**, computing devices may also include or peripheral output devices such as speakers **697**, a vibrator **699**, and or output devices, which may be connected through an output peripheral

interface **695**. [0248] computing system **600** can operate in a networked environment using logical connections to one or more remote computers/client devices, such as a remote computing system **680**. remote computing system **680** can be a personal computer, a hand-held device, a server, a router, a network PC, a peer device or any common network node, and typically includes many or all of the elements described above relative to computing system **600**. logical connections can include a personal area network ("PAN") **672** (e.g., Bluetooth®), a local area network ("LAN") **671** (e.g., Wi-Fi), and a wide area network ("WAN") **673** (e.g., cellular network), but may also include other networks. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets and Internet. A browser application may be resident on computing device and stored in memory.

[0249] When used in a LAN networking environment, computing system **600** is connected to LAN **671** through a network interface or adapter **670**, which can be, for example, a Bluetooth® or Wi-Fi adapter. When used in a WAN networking environment (e.g., Internet), computing system **600** typically includes some means for establishing communications over WAN **673**. With respect to mobile telecommunication technologies, for example, a radio interface, which can be internal or external, can be connected to system bus **621** via network interface **670**, or any appropriate mechanism. In a networked environment, or software depicted relative to computing system **600**, or portions thereof, may be stored in remote memory storage device. By way of example, and not limitation, illustrates remote application programs **685** as residing on remote computing device **680**. It will be appreciated that network connections shown are examples and other means of establishing a communications link between computing devices may be used.

[0250] As discussed, computing system **600** can include a processor **620**, a memory (e.g., ROM **631**, RAM **632**, etc.), a built-in battery to power computing device, an AC power input to charge battery, a display screen, a built-in Wi-Fi circuitry to wirelessly communicate with a remote computing device connected to network.

[0251] It should be noted that present design can be carried out on a computing system such as that described with respect to. However, present design can be carried out on a server, a computing device devoted to message handling, or on a distributed system in which different portions of present design are carried out on different parts of distributed computing system.

[0252] Another device that may be coupled to bus **621** is a power supply such as a DC power supply (e.g., battery) or an AC adapter circuit. As discussed above, DC power supply may be a battery, a fuel cell, or similar DC power source that needs to be recharged on a periodic basis. A wireless communication module can employ a Wireless Application Protocol to establish a wireless communication channel. wireless communication module can implement a wireless networking standard.

[0253] In some embodiments, software used to facilitate algorithms discussed herein can be embodied onto a non-transitory machine-readable medium. A machine-readable medium includes any mechanism that stores information in a form readable by a machine (e.g., a computer). For example, a non-transitory machine-readable medium can include read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; flash memory devices; Digital Versatile Disc (DVD's), EPROMs, EEPROMs, FLASH memory, magnetic or optical cards, or any type of media suitable for storing electronic instructions.

[0254] Note, an application described herein includes but is not limited to software applications, mobile apps, and programs that are part of an operating system application. Some portions of this description are presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are means used by those skilled in the data processing arts to convey substance of work most effectively to one skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps leading to a desired result. steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take form of electrical or magnetic signals capable of being

stored, transferred, combined, compared, and manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to signals as bits, values, elements, symbols, characters, terms, numbers, or like. se algorithms can be written in a number of different software programming languages such as C, C+, or similar languages. Also, an algorithm can be implemented with lines of code in software, configured logic gates in software, or a combination of both. In an embodiment, logic consists of electronic circuits that follow rules of Boolean Logic, software that contain patterns of instructions, or any combination of both.

[0255] Many functions performed by electronic hardware components can be duplicated by software emulation. Thus, a software program written to accomplish those same functions can emulate functionality of hardware components in input-output circuitry.

[0256] Each of following references is expressly incorporated herein by reference in its entirety:

[0257] Abraham, Ittai, et al. "Low-distortion inference of latent similarities from a multiplex social network." *SIAM Journal on Computing* 44.3 (2015): 617-668. [0258] Aldenderfer, M. S., and R. K. Blashfield. *Cluster Analysis*. Sage Publications, Los Angeles, 1985. [0259] Anderberg, M. R. (1973). *Cluster Analysis for Applications*. Academic Press, New York. [0260] Anderson, E. (1957). A semi-graphical method for analysis of complex problems. *Proc. Nat. Acad. Sci. USA* 43923-927. [0261] Anderson, T. W. (1958). *An Introduction to Multivariate Statistical Analysis*. Wiley, New York. [0262] Anderson, T. W., and Bahadur, R. R. (1962). classification into two multivariate normal distributions with different covariance matrices. *Ann. Math. Statist.* 33420-431. [0263] Andrews, D. F. (1972). Plots of high-dimensional data. *Biometrics* 28 125-136. [0264] Ankerst, M., M. M. Breunig, H. P. Kriegel, and J. Sander. OPTICS: Ordering Points To Identify Clustering Structure. In *Proc. of 1999 ACM-SIGMOD Intl. Conf. on Management of Data*, pages 49-60, Philadelphia, Pa., June 1999. ACM Press. [0265] Arabie, P. (1977). clustering representations of group overlap. *J. Math. Soc.* 5 112-128. [0266] Arabie, P. and Carroll, J. D. (1980). MAPCLUS: A mamatical programming approach to fitting to ADCLUS model. *Psychometrika* 45211-235. [0267] Arabie, P., L. Hubert, and G. D. Soete. An overview of combinatorial data analysis. In P. [0268] Arabie, L. Hubert, and G. D. Soete, editors, *Clustering and Classification*, pages 188-217. World Scientific, Singapore, January 1996. [0269] Art, D., Gnanadesikan, R., and Kettenring, J. R. (1982). Data-based metrics for cluster analysis. *Utilitas Mamatica* 31A 75-99. [0270] Asimov, D. (1985). The grand tour. *SLAM J. Sci. Statist. Corn-put.* 6 128-143. [0271] Auffarth, Benjamin, Yasumasa Muto, and Yasuharu Kunii. "An artificial system for visual perception in autonomous Robots." *Proceedings of IEEE International Conference on Intelligent Engineering Systems*. 2005. [0272] Babu, B. Hari, N. Subash Chandra, and T. Venu Gopal. "Clustering Algorithms For High Dimensional Data—A Survey Of Issues And Existing Approaches." [0273] Baker, F. B. (1974). Stability of two hierarchical grouping techniques, Case I: Sensitivity to data errors. *J. Amer. Statist. Assoc.* 69440-445. [0274] Ball, G., and D. Hall. A Clustering Technique for Summarizing Multivariate Data. *Behavior Science*, 12:153-155, March 1967. [0275] Banerjee, A., S. Merugu, I. S. Dhillon, and J. Ghosh. Clustering with Bregman Divergences. In *Proc. of 2004 SIAM Intl. Conf. on Data Mining*, pages 234-245, Lake Buena Vista, Fla., April 2004. [0276] Baraglia, R., Dazzi, P., Mordacchini, M., & Ricci, L. (2013). A peer-to-peer recommender system for self-emerging user communities based on gossip overlays. *Journal of Computer and System Sciences*, 79 (2), 291-308. [0277] Baragliaa, R., Dazzia, P., Mordacchinib, M., & Riccic, L. A Peer-to-Peer Recommender System for self-emerging user communities based on Gossip Overlays. (2012) [0278] Beck, Carolyn, et al. "Dynamic Coverage and Clustering: A Maximum Entropy Approach." *Distributed Decision Making and Control*. Springer London, 2012. 215-243. [0279] Becker, P. (1968). *Recognitions of Patterns*. Polyteknisk, Copenhagen. [0280] Bell, P. A. and Korey, J. L. (1975). *QUICLSTR: A FORTRAN program for hierarchical cluster analysis with a large number of subjects*. *Behavioral Research Methods and Instrumentation* 7575. [0281] Berg, Mikko. "Human abilities to perceive, understand, and manage multi-dimensional information with visualizations." (2012). [0282] Birkin, P. *Survey Of Clustering Data Mining Techniques*. Technical report, Accrue

Software, San Jose, Calif., 2002. [0283] Bhat, Sajid Yusuf, and Muhammad Abolish. "A density-based approach for mining overlapping communities from social network interactions." Proceedings of 2nd International Conference on Web Intelligence, Mining and Semantics. ACM, 2012. [0284] Binder, D. A. (1978). Comment on 'Estimating mixtures of normal distributions and switching regressions'. J Amer. Statist. Assoc. 73:746-747. [0285] Blashfield, R. K., Aldenderfer, M. S. and Morey, L. C. (1982). cluster analysis literature on validation. In *Classifying Social Data*. (H. Hudson, ed.) 167-176. Jossey-Bass, San Francisco. [0286] Bock, H. H. (1985). On significance tests in cluster analysis. J. Classification 2:77-108. [0287] Boley, D. Principal Direction Divisive Partitioning. *Data Mining and Knowledge Discovery*, 2 (4): 325-344, 1998. [0288] Bosley, Daniel, and Vivian Borst. "A General Unsupervised Clustering Tool for Unstructured Data." *matrix* 100:2. [0289] Boratto, Ludovico. "Group artificial intelligence with automatic detection and classification of groups." (2012). [0290] Bradley, P. S. and U. M. Fayyad. Refining Initial Points for K-Means Clustering. In *Proc. of 15th Intl. Conf. on Machine Learning*, pages 91-99, Madison, Wis., July 1998. Morgan Kaufmann Publishers Inc. [0291] Breiman, L. Meisel, W. S., and Purcell, E. (1977). Variable kernel estimates of multivariate densities and its calibration. *Technometrics* 19 135-144. [0292] Brineman, L., Friedman, J. H., Olshen, R. A., and Stone, C. J. (1984). *Classification and Regression Trees*. Wadsworth, Belmont, Calif. [0293] Broadbent, S. R. and Hammersley, J. M. (1957). Percolation Processes, I: Crystals and Mazes. *Proc. Cambridge Philos. Soc.* 53:629-641. [0294] Bu, Yingyi, et al. "HaLoop approach to large-scale iterative data analysis." *VLDB Journal—International Journal on Very Large Data Bases* 21.2 (2012): 169-190. [0295] Buja, A., Hurley, C. and McDonald, J. A. (1986). A data viewer for multivariate data. *Computer Science and Statistics: Proceedings of 18th Symposium on Interface* 171-174. [0296] Cacoullos, T. (1966). Estimation of a multivariate density. *Ann. Math. Statist.* 18 179-189. [0297] Cal, Rui, et al. "Scalable music artificial intelligence by search." *Proceedings of 15th international conference on Multimedia*. ACM, 2007. [0298] Carrizosa, Emilio, and Dolores Romero Morales. "Supervised classification and mathematical optimization." *Computers & Operations Research* 40.1 (2013): 150-165. [0299] Chang, Chin-Chun, and Hsin-Yi Chen. "Semi-supervised clustering with discriminative random fields." *Pattern Recognition* 45.12 (2012): 4402-4413. [0300] Chen, H., Gnanadesikan, R., and Kettenring, J. R. (1974). Statistical methods for grouping corporations. *Sankhya B* 36 1-28. [0301] Chen, Yen Hung. "k Partition-Distance Problem." *Journal of Computational Biology* 19.4 (2012): 404-417. [0302] Cheng, Hong, et al. "Clustering large attributed information networks: an efficient incremental computing approach." *Data Mining and Knowledge Discovery* 25.3 (2012): 450-477. [0303] Chernoff, H. (1972). selection of effective attributes for deciding between hypotheses using linear discriminant functions. In *Frontiers of Pattern Recognition*. (S. Watanabe, ed.) 55-60. Academic Press, New York. [0304] Chernoff, H. (1973a). Some measures for discriminating between normal multivariate distributions with unequal covariance matrices. In *Multivariate Analysis III*. (P. R. Krishnaiah, ed.) 337-344. Academic Press, New York. [0305] Chernoff, H. (1973b). use of faces to represent points in k-dimensional space graphically. *J Amer. Statist. Assoc.* 68 361-368. [0306] Cherubini, Umberto, and Agnese Sironi. *Bond Trading, Market Anomalies and Neural Networks: An Application with Kohonen Nets*. No. 012. Society for Computational Economics. [0307] Christou, Ioannis T., George Gekas, and Anna Kyrikou. "A classifier ensemble approach to TV-viewer profile adaptation problem." *International Journal of Machine Learning and Cybernetics* 3.4 (2012): 313-326. [0308] Clunies-Ross, C. W. and Riffenburgh, R. H. (1960). Geometry and linear discrimination. *Biometrika* 47:185-189. [0309] Cormack, R. M. (1971). A review of classification (with discussion). *J Roy. Statist. Soc. A* 134:321-367. [0310] Cover, T. M. (1968). Estimation by nearest neighbor rule. *IEEE Transactions Information Theory* IT-14 50-55. [0311] Cover, T. M. and Hart, P. E. (1967). Nearest neighbor pattern classification. *IEEE Transactions, Information Theory* IT-13 21-27. [0312] Dallal, G. E. (1975) A user's guide to J. A. Hartigan's clustering algorithms. (unpublished manuscript) Yale University. [0313] Day, N. E. (1969). Estimating components of a mixture of normal distributions.

Biometrika 56463-474. [0314] Day, N. E., and Kerridge, D. F., (1967). A general maximum likelihood discriminant. Biometrics 23313-323. 94 [0315] de Master, Trabajo Fin. "Novelty and Diversity Enhancement and Evaluation in Recommender Systems." (2012). [0316] Defays, D. (1977). An efficient algorithm for a complete link method. Computer Journal 20364-366. [0317] Derrac, Joaquín, Isaac Triguero, Salvador García, and Francisco Herrera. "Integrating instance selection, instance weighting, and feature weighting for nearest neighbor classifiers by coevolutionary algorithms."

[0318] As illustrated in FIG. 32, at block 814, it can be determined whether on-site care is required.

[0319] At block 816, on-site care can be executed. At block 818, patient data and/or user interface(s) can be presented. In one embodiment, the software application provided to a care provider can enable the care provider to view the patient's physiological parameters (such as, but not limited to, blood oxygen saturation and/or temperature measurements) over the monitoring period.

[0320] At block 820, a patient can be diagnosed and/or treated for a health condition. For example, a clinician can review and/or a system can process the patient data and decide whether a health condition is present. For example, a preliminary indication of whether a patient has the coronavirus can be determined based on physiological parameters such as blood oxygen saturation and/or temperature measurements. A clinician can treat the patient based on the patient's physiological parameters (such as blood oxygen saturation and/or the temperature measurements) over the monitoring period. In some embodiments, a system can make a treatment recommendation based on the physiological parameters for review by a clinician. Treating the patient can include those disorders listed above regarding analysis of urine.

[0321] In some embodiments, the method and system 800 can be used to establish a monitoring environment for a user suspected of having a contagious respiratory infection. As described herein, the user can be monitored remotely from a care provider. The monitoring environment can include one or more sensors worn by the user, a wearable device worn by the user configured to communicate with the one or more sensors and to process information responsive to output from the one or more sensors. The monitoring environment can further include a user computing device configured to wirelessly communicate with the wearable device and to communicate with a remote care provider system over a network. The care provider system can be configured to be monitored by the care provider.

[0322] As non-limiting examples, any of the systems or methods described herein can also be applied to and/or used in conjunction with a health monitoring system that can assist organizations to manage infectious diseases. As described herein, additional health monitoring systems and use cases are described in the health monitoring application. For example, any of the systems or methods described herein can also be applied to and/or used in conjunction with risk states and/or proximity data

[0323] FIG. 31 illustrates one embodiment of block diagram that illustrates components of a computing device 900. The computing device 900 can implement aspects of the present disclosure, and, in particular, aspects of the patient management and 111, including but not limited to a frontend server, a patient data service, the patient care management service, and/or the patient monitoring service. The computing device 900 can communicate with other computing devices.

[0324] The computing device 900 can include a hardware processor 902, a data storage device 904, a memory device 906, a bus 908, a display 912, and one or more input/output devices 914. A processor 902 can also be implemented as a combination of computing devices, e.g., a combination of a digital signal processor and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a digital signal processor, or any other such configuration. The processor 902 can be configured, among other things, to process data, execute instructions to perform one or more functions, such as process one or more physiological signals to obtain one or more measurements, as described herein. The data storage device 904 can include a magnetic disk,

optical disk, or flash drive, etc., and is provided and coupled to the bus **908** for storing information and instructions. The memory **906** can include one or more memory devices that store data, including without limitation, random access memory (RAM) and read-only memory (ROM). The computing device **900** may be coupled via the bus **908** to a display **912**, such as an LCD display or touch screen, for displaying information to a user, such as a clinician. The computing device **900** may be coupled via the bus **908** to one or more input/output devices **914**. The input device **914** can include, but is not limited to, a keyboard, mouse, digital pen, microphone, touch screen, gesture recognition system, voice recognition system, imaging device (which may capture eye, hand, head, or body tracking data and/or placement), gamepad, accelerometer, or gyroscope.

[0325] In various embodiments, patient remote monitoring system **800** can be designed to help clinicians care for patients remotely over a period of time. The patient management system can include non-clinical spaces into advanced care environments with the one or more sensors **28**, and vital signs monitors.

[0326] In one embodiment, illustrated in **34(a)**, a network architecture **1000** for enabling remote management of patients. The network architecture **1000** can include a wireless sensor system **1010** that is capable of transmitting data to a mobile computing device **1012** enabled smartphones or another mobile computing device via a wireless link **1014**. In some examples, the wireless link **1014** is a Bluetooth link. Other wireless links, such as NFC or WiFi can also be used for connection between the wireless sensor system **1010** and the mobile computing device **1012**. The mobile computing device **1012** may communicate with a remote patient management system (RPMS) **1050** (see FIG. **34C**) that can display the collected data from wireless sensor system **1010** in a format that is readable by a patient or a user of the mobile computing device **1012**. The RPMS **1050** can generate customized user interfaces as shown in more detail below. The mobile computing device **1012** in combination with the RPMS **1050** may enable transmission of the collected data to a server **1016** via a network connection link **1018**. In some examples, the network connection link **1018** can include WiFi or other wireless broadband communication systems.

[0327] As non-limiting examples, the mobile computing device **1012** can be replaced with a connectivity hub that enables data collection from the wireless sensor system **1010** and transmits the collected data to the server **1016** via the communication link **1018**. Not all users have access to a smart phone or mobile computing devices

[0328] In one embodiment, patient remote monitoring system **1020** can access the collected data from the server **1016**. The care provider monitoring system **1020** can include a computing system associated with a hospital, a caregiver (such as a primary provider), or a user (friends or family) that have permission to access the patient's data.

[0329] As illustrated in FIG. **34A** the wireless sensor system **1010** can collect physiological data. In some instances, the wireless sensor system **1010** can store 96 hours of data. This data can be streamed directly to the mobile computing device **1012**. In some instances, when the mobile computing device **1012** is offline or not in the vicinity, data can be transferred when the mobile computing device **1012** is connected back with the wireless sensor system **1010**. Accordingly, the wireless sensor system **1010** can keep monitoring and transmit when the mobile computing device **1012** is available.

[0330] As a non-limiting example, mobile computing device **1012** can associate the collected physiological data with patient identification information and transmit the data to the server **1016** as discussed above with respect to FIG. **34A**. In one embodiment, a connectivity hub can also transmit the collected data to the server **1016**. In some instances, the database is part of the server **1016**, that it is located within same networking environment. The clinicians can access the collected patient data with a web browser. The clinicians can monitor one patient or multiple patients in a dashboard. The clinicians can access trend chart of the patients. Moreover, clinicians can obtain patient alerts via email. In some instances, patient data may be replicated on clinician's mobile computing device.

[0331] In various embodiments 32A and 32B show a cloud-based system, in some instances, connectivity between the wireless sensor system **1010** may be enabled inside the hospital using a network system. During a contagion management situation, it may be ideal for caregivers to not come in close contact with patients on frequent basis. In one embodiment, remote monitoring system can be created at the hospital. The wireless sensor system shown in FIG. 35) can be paired with a receiver. In some examples, the receiver can enable transmission of data to a patient monitor which in turn transmits the data to a hospital server. In other examples, the receiver is a communication hub that can directly transmit the data to the hospital server. Accordingly, caregivers can monitor multiple patients from a central location or even outside of a particular patient's hospital room, thereby limiting the interactions. This can also be useful in field hospitals that are set up on demand. A central monitoring station can be set up to monitor many patients through a local ad-hoc network.

[0332] In one embodiment, illustrated in FIG. 35(c) illustrates a block diagram of the RPMS **1050**. The RPMS **1050** can be a software application including multiple engines that can be implemented across multiple devices, such as the mobile computing device **1012**, the server **1016**, and patient remote monitoring system **1020**. The RPMS **1050** can collect data from multiple wireless sensor systems associated with a patient. The RPMS **1050** can further collect data from multiple patients that are monitored in different locations. The RPMS **1050** can collect data periodically for transmission to the server **1016**. The RPMS **1050** can generate user interfaces for presenting the collected data and reports associated with the collected data. FIGS. 4A-34C illustrates an example wireless sensor system **1010**.

[0333] RPMS **1050** can additionally or alternatively include a different wireless sensor system from the system shown in FIG. 35. In some instances, multiple wireless sensors systems **1010** can be part of a network architecture. For example, additional wireless sensors systems **1010** can include a temperature system, an ECG monitoring system, a blood pressure monitoring system, an acoustic sensor monitoring system, and any other physiological monitoring system capable of communication using the wireless link **1014**.

[0334] In one embodiment, wireless sensor system(s) **1010** may include a pulse oximetry sensor with respiration rate monitoring. The pulse oximetry sensor can provide continuous respiration rate and oxygen saturation monitoring. The pulse oximetry sensor can also monitor the patient's pulse rate, variability index, perfusion, index, among other physiological parameters. Alternatively, or additionally, the wireless sensor system(s) **1010** may include a temperature monitoring system worn on the patient's body for measuring temperature.

[0335] In one embodiment, the remote monitoring system may include a digital discussion platform that may incorporate questions and possible answers to direct a patient consultation.

[0336] In some implementations, the patient remote monitoring management system may incorporate a secured data sharing to allow the remote patient surveillance system to share patient physiological data with others, for example, care providers, without the surveillance system gaining access to data. The secured data sharing may incorporate multiple layers of encryption with multiple entry points to some of the layers

[0337] In one embodiment, RPMS **1050** may offer care providers a single-platform solution that couples a secure, cloud-based monitoring platform with patient sensors that can monitor blood oxygen saturation (SpCh), pulse rate, perfusion index, variability index, and respiration rate, and the like. Sensor **28** monitoring can be continuous or periodic.

[0338] Patients can be sent home with catheter **10** and one or more sensors **28** along with access to a secure, home-based, remote patient surveillance system. In some examples, patients may receive a multi-day supply of sensors. The RPMS **1050** can provide a dashboard user interface for a care provider to monitor multiple patients simultaneously. In some instances, the patients can be monitored for respiratory distress. Further, in some instances, the patients can be monitored during vims outbreaks. The RPMS **1050** may generate alerts when the patient may need urgent attention,

including admission in the hospital based on monitoring a trend in physiological parameters. [0339] In some implementations, the RPMS **1050** may offer programs or regimes that are digital replacement for traditional home-care plans and may be delivered to patients' smartphones. Programs can include for example, contagious disease monitoring, glucose monitoring, blood pressure monitoring, and other health condition monitoring and compliance. The programs can be predefined and selectable by the clinicians. The programs can be dynamically modified by changing government guidelines. The RPMS **1050** can actively remind patients to follow their regimen, automatically capture monitoring data from the wireless sensor system, and securely push (or transmit) the data to clinicians at the hospital for evaluation. In some implementations, the digital home-care plan may follow CDC and WHO guidance for monitoring suspected COVID-19 or other communicable disease subjects, which can be easily updated at any time to accommodate evolving guidance or hospital protocol. The patient management system can provide support during a surge in demand for medical care. The system can expand the ability of healthcare professionals to monitor conditions of patients that need non-urgent medical care (for example, patients with mild or moderate symptoms) and care for those patient remotely, while saving the limited hospital beds and urgent care facilities (for example, the intensive care units) for patients who are in more critical conditions, such as needing intubation and/or assisted breathing. Conditions of the patients who are experiencing mild or moderate symptoms, or suspected of having been infected by virus or bacteria can be more accurately and/or more timely monitored using the patient management system, for example, as compared to asking the patient to self-report breathlessness, fever, or other medical conditions. In times of an epidemic or pandemic, patients who otherwise need their vital signs monitored by a healthcare professional can also receive medical care using the patient management system. The reduction in need for patients to visit the hospital or other clinical setting unless in urgent situations can also facilitate in reducing cross contamination (among patients, healthcare professionals, and other care takers) during epidemics or pandemics.

[0340] In one embodiment, RPMS **1050** may collect other physiological data, for example, temperature, heart rate, and the like from user inputs via interactive user interfaces.

[0341] In one embodiment, the RPMS **1050** may include a secured online portal that may allow care providers to easily track patient compliance, helping the care providers to identify when intervention may be needed, as well as providing insight to prioritize patients. With advanced automation features, institutions can more easily deploy home care monitoring at scale while ensuring clinicians stay informed of important developments in a patient's condition. In some implementations, the RPMS **1050** can be fully customizable to accommodate each institution's protocols, each patient's needs, and any changes in guidance. Additionally, and/or optionally, the remote patient surveillance system can be updated through the cloud by providers even after being deployed, for maximum flexibility as situations evolve.

[0342] In one embodiment of the present invention, and referring to FIG. **36**, at least a portion of the sensor data may contain noisy data, including errors, outliers, and inconsistencies. System **10** provides functionality for identifying, cleaning, and transforming such noisy data to optimize its use in machine learning algorithms. The system includes a preprocessing module, which may be integrated into the system or implemented as a separate component and employs advanced techniques such as rule-based filters, machine learning algorithms, or heuristic methods to detect and address anomalies or inconsistencies. For example, it can identify missing values, duplicate records, or formatting errors and either correct these issues based on predefined rules or remove the problematic records entirely. Additionally, the module can leverage external data sources or context-aware algorithms to validate and enrich the data, enhancing its quality and relevance. The preprocessing functionality is highly adaptable, allowing customization to suit specific dataset requirements or applications. It supports both real-time and batch processing workflows, enabling efficient handling of large-scale data while ensuring data integrity, reliability, and usability for downstream analytics, modeling, or other processes. Further, the system can detect incomplete,

incorrect, or inaccurate data and then replace, modify, or delete the affected records. Data cleansing can be performed interactively using data wrangling tools or through batch processing, often implemented via scripts or a data quality firewall, to maintain consistent and reliable datasets. [0343] As a non-limiting example, system **10** provides for data cleaning, also referred to as data scrubbing or data cleansing, that is the process of preparing data for analysis by identifying and correcting errors, inconsistencies, and inaccuracies. This can be achieved in the AI module/engine and/or in a separate preprocessing module.

[0344] In one embodiment, system **10** provides for sensor data preprocessing that transforms raw, unstructured, or noisy data into a clean, structured format suitable for analysis. As stated previously, raw sensor data may contain missing values, outliers, inconsistencies, or redundant information, all of which can adversely impact the performance of machine learning algorithms. In one embodiment, system **10** provides systematic data preprocessing.

[0345] In one embodiment, system **10** gathers relevant data for sensor data, the sensor data is cleaned and optionally splitting it into training and testing sets. The training set is used to train, while the testing set evaluates its performance

[0346] As a non-limiting example, system **10** can preprocess sensor data and to eliminate or reduce noise. This can include but is not limited to the following types of sensor data noise: Feature Noise that refers to superfluous or irrelevant features present in the dataset that might cause confusion and impede the process of learning; Systematic Noise: Recurring biases or mistakes in measuring or data collection procedures that cause data to be biased or incorrect; Random Noise: unpredictable fluctuations in data brought on by variables such as measurement errors or ambient circumstances; Background noise: information in the sensor data that is unnecessary or irrelevant and could distract the model from the learning job, and the like.

[0347] As a non-limiting example, noise can include measuring errors, anomalies, or discrepancies in the sensor data. Handling noise is important because it might result in AI machine learning algorithm that are unreliable and forecasts that are not correct.

[0348] As a non-limiting example, system **10** preprocesses at least of sensor data by a preprocessing module that can be include with or separate from AI module. It can include methods to improve the quality of the sensor data and lessen noise from errors or inconsistencies, such as data cleaning, normalization, and outlier elimination. Sensor data can be preprocessed with the use of Fourier Transform which can be a mathematical technique used to transform signals from the time or spatial domain to the frequency domain. In the context of noise removal, it can help identify and filter out noise by representing the signal as a combination of different frequencies. Relevant frequencies can be retained while noise frequencies can be filtered out.

[0349] In one embodiment, constructive learning involves training a machine learning model to distinguish between clean and noisy data instances. This can require labeled data where the noise level is known. The model learns to classify instances as either clean or noisy, allowing for the removal of noisy data points from the dataset.

[0350] Autoencoders can be utilized, with autoencoders being neural network architectures that can include an encoder and a decoder. The encoder compresses the input data into a lower-dimensional representation, while the decoder reconstructs the original data from this representation. Autoencoders can be trained to reconstruct clean signals while effectively filtering out noise during the reconstruction process.

[0351] As a non-limiting example, principal component analysis (PCA) can be used by system **10** to reduce and/or eliminate noisy data. PCA is a dimensionality reduction technique that identifies the principal components of a dataset, which are orthogonal vectors that capture the maximum variance in the data. By projecting the data onto a reduced set of principal components, PCA can help reduce noise by focusing on the most informative dimensions of the data while discarding noise-related dimensions.

[0352] As a non-limiting example, noisy data cross-validation and ensemble models can be used to

eliminate or reduce noisy data. Cross-validation is a resampling technique used to assess how well a predictive model generalizes to an independent dataset. It involves partitioning the dataset into complementary subsets, performing training on one subset (training set) and validation on the other (validation set). This process is repeated multiple times with different partitions of the data. Common cross-validation methods include k-fold cross-validation and leave-one-out cross-validation. By training on different subsets of data, cross-validation helps in reducing the impact of noise in the data. It also aids in avoiding overfitting by providing a more accurate estimate of the model's performance. Ensemble learning involves combining multiple individual models to improve predictive performance compared to any single model alone. Ensemble models work by aggregating the predictions of multiple base models, such as decision trees, neural networks, or other machine learning algorithms. Popular ensemble techniques include bagging (bootstrap aggregating), boosting, and stacking. By combining models trained on different subsets of the data or using different algorithms, ensemble models can mitigate the impact of noise in the data. Ensemble methods are particularly effective when individual models may be sensitive to noise or may overfit the data. They help in improving robustness and generalization performance by reducing the variance of the predictions.

[0353] As a non-limiting example, system **10** provides for the removable and/or adding the following: missing values that are missing entries that arise due to incomplete data collection or errors during data entry. Inconsistencies; differences in data formats, units, or encoding that can create confusion and errors during processing; outliers which can be extreme or anomalous values that skew results, leading to incorrect insights or predictions; redundancy that can include non-relevant duplicate records which inflate dataset size and misrepresent actual trends; irrelevance with features that are unrelated to target variable can introduce noise and hinder model performance.

[0354] Patient health information is collected in real-time data and can be used to improve disease monitoring and management. Additionally, it is used for early disease detection and prevention. The Health Information Technology for Economic and Clinical Health Act (HITECH Act), enacted as part of the American Recovery and Reinvestment Act of 2009, (ARRA) contains provisions that strengthen the privacy and security protections for certain health information established under HIPAA. From blockchain-based solutions to artificial intelligence-powered threat detection systems, system **10** can include resources to mitigate the risks associated with cyber threats and protect the integrity of medical devices including but not limited to surgical robot system **10**.

[0355] As a non-limiting example, system **10** provides logic resource cybersecurity in response to one or more of regulations and frameworks in the health care industry selected from one or more of: NIST, HIPAA, CIS, COBIT, ISO/IEC 27001, and HITRUST.

[0356] In one embodiment, system **10** cyber security resources are included that minimize hacking of patient data in compliance with HIPAA.

[0357] In one embodiment cryptography algorithms function by: encrypting data into ciphertext, making it unreadable to unauthorized users; ensuring secure communication by encrypting data during transit; allowing decryption with the correct key to reveal the true contents of a message, and the like. In one embodiment, machine learning algorithms and AI help identify and prevent cyberthreats by: using supervised learning models with labeled data to train a system and; identifying patterns in unlabeled data through unsupervised learning, detecting advanced or emerging cyberthreats.

[0358] It is to be understood that present disclosure is not to be limited to specific examples illustrated and that modifications and or examples are intended to be included within scope of appended claims. Moreover, although foregoing description and associated drawings describe examples of present disclosure in context of certain illustrative combinations of elements and/or functions, it should be appreciated that different combinations of elements and/or functions may be provided by alternative implementations without departing from scope of appended claims.

Accordingly, parenthetical reference numerals in appended claims are presented for illustrative purposes only and are not intended to limit scope of claimed subject matter to specific examples provided in present disclosure.

Claims

1. A urinary catheter, comprising: a catheter with a urinary catheter tube with a lumen, a proximal end, a distal end and a balloon coupled to proximal end, the balloon configured to be positioned in an interior of a bladder, the catheter tube configured to provide flow of urine from bladder through the catheter lumen; a drainage bag configured for collecting urine from the bladder through the catheter lumen, the drainage bag having an inlet port for receiving urine; the urinary catheter tube including the proximal end, having a plurality of urine draining holes that receive urine from bladder and allow urine to be transported through the urinary catheter tube to the drainage bag; one or more sensors positioned in an interior of the catheter tube and positioned to be in contact with patient's urine, the one or more sensors provide sensor data relative to a health of a patient, at least a portion of sensor data being noisy data that contains one or more of errors, outliers, and inconsistencies; an artificial intelligence system including an AI engine with a plurality of machine learning algorithms that provide analysis the sensor data, the AI engine coupled to the one or more sensors to receive the sensor data, and in response to the analysis of the sensor data by the machine learning algorithms make recommendations relative to a health of a patient; and wherein the system provides preprocessing sensor data for identification, cleaning, and/or transforming of noisy data for machine learning algorithms.
2. The system of claim 1, wherein at least a portion of sensor data can be noisy data contains one or more of: errors, outliers, and inconsistencies.
3. The system of claim 1, wherein the system provides one or more of: identification, cleaning, and transforming noisy data for the machine learning algorithms.
4. The system of claim 1, wherein the system includes a module, that is included with or is a separate preprocessing module to execute a process of one or more of: identifying and correcting or removing) corrupt, inaccurate, or irrelevant records from a dataset, table, or database.
5. The system of claim 4, wherein the module is configured to provide one of more of: detecting incomplete, incorrect, or inaccurate parts of the data, followed by replacement modification and deletion affected data.
6. In one embodiment, at least a portion of raw sensor data is noisy data that contains one or more of errors, outliers, and inconsistencies,
7. The system of claim 1, wherein the includes logic resources for preprocessing of the noisy data to create cleaned sensor data that is preprocessed sensor data used for one or more of: identification; cleaning; and transforming noisy data for the machine learning algorithms to produce the cleaned sensor data.
8. The system of claim 1, wherein all of a portion of raw sensor data is collected from the sensor data.
9. The system of claim 8, wherein the raw sensor data is preprocessed to clean and transform it into a suitable format and extracts relevant features from sensor data.
10. The system of claim 9, wherein the relevant features are used for medical monitoring of one or more medical conditions of the patient. In one embodiment, sensor data preprocessing transforms raw, unstructured, or noisy data into a clean, structured format (preprocessed data) suitable for analysis.
11. The system of claim 1, wherein the system provides for data cleaning that is a process of preparing sensor data for analysis by identifying and correcting errors, inconsistencies, and inaccuracies.
12. As a non-limiting example, system 10 provides for the cleansing to be performed interactively

- using data wrangling tools, or through batch processing often via scripts or a data quality firewall.
- 13.** The system of claim 1, wherein raw sensor data includes one or more of: missing values; outliers; inconsistencies, and: redundant information all of which can adversely impact a performance of the machine learning algorithms. In one embodiment, system **10** provides systematic data preprocessing.
- 14.** The system of claim 1, wherein the sensor data is cleaned and split into training and testing sets.
- 15.** The system of claim 1, wherein the noisy includes one or more of feature noise with superfluous or irrelevant features present in the dataset that might cause confusion and impede the process of learning; systematic noise with biases or mistakes in measuring or data collection procedures that cause the sensor data to be biased or incorrect; random noise with unpredictable fluctuations in data brought on by variables, and background noise: where information in the sensor data is unnecessary.
- 16.** The system of claim 1, wherein sensor data is preprocessed with the use of Fourier Transform
- 17.** The system of claim 1, wherein sensor data is preprocessed with the use of autoencoders.
- 18.** The system of claim 1, wherein one or more of: data cross-validation and ensemble models are used to reduce noisy data.
- 19.** The system of claim 18, wherein the data cross-validation is a resampling technique used to assess how well a predictive model generalizes to an independent dataset.
- 20.** The system of claim 18, wherein the data cross-validation provides for partitioning the dataset into complementary subsets.
-