

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286488

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

OISHI; Ryohei

CONTROLLER, METHOD, AND NON-TRANSITORY COMPUTER READABLE MEDIUM FOR DRIVE SYSTEM

Abstract

A controller includes a feedback controller and a state feedback controller. The feedback controller performs feedback control using a d-axis current value and a d-axis current command value, and feedback control using a q-axis current value and a q-axis current command value, and calculates a d-axis voltage command value and a q-axis voltage command value. The state feedback controller calculates a d-axis voltage value and a q-axis voltage value, obtained by state feedback control of a d-axis current value and a q-axis current value, by performing rotational conversion at a rotation angle determined by the characteristics of the motor, which is correlated with a rotation speed of a motor using a rotation matrix, to calculate a d-axis voltage correction value and a q-axis voltage correction value.

Inventors: OISHI; Ryohei (Kariya-city, JP)

Applicant: DENSO CORPORATION (Kariya-city, JP)

Family ID: 92500748

Appl. No.: 19/220749

Filed: May 28, 2025

Foreign Application Priority Data

JP 2023-026477

Feb. 22, 2023

Related U.S. Application Data

parent WO continuation PCT/JP2024/002268 20240125 PENDING child US 19220749

Publication Classification

Int. Cl.: H02P21/22 (20160101); H02P21/05 (20060101); H02P27/08 (20060101)

U.S. Cl.:

CPC H02P21/22 (20160201); H02P21/05 (20130101); H02P27/08 (20130101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation application of International Patent Application No. PCT/JP2024/002268 filed on Jan. 25, 2024, which designated the U.S. and claims the benefit of priority from Japanese Patent Application No. 2023-026477 filed on Feb. 22, 2023. The entire disclosures of all of the above applications are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates to a controller, a method, and a non-transitory computer readable medium for a drive system.

BACKGROUND

[0003] A controller may rotate an electric rotating machine. The controller may calculate a feedback manipulated variable for controlling the rotation speed of a motor to which a cooling fan is attached to a target value.

SUMMARY

[0004] The present disclosure describes a controller, a method and a non-transitory computer readable medium, each of which is adapted to a drive system in which an inverter converts DC power of a DC power supply into three-phase AC power and the three-phase AC power is supplied to a rotating electric machine.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0005] FIG. 1 is a block diagram showing a schematic configuration of a drive system.

[0006] FIG. 2 is a diagram showing a schematic configuration of a state feedback controller.

[0007] FIG. 3 is a diagram showing a schematic configuration of a feedback controller and a state feedback controller according to a modified example.

[0008] FIG. 4 is a graph showing the rotation speed characteristics of $K_{sub.SFB}$.

[0009] FIG. 5 is a graph showing the rotation speed characteristics of $\theta_{sub.SFB}$.

[0010] FIG. 6 is a graph showing the rotation speed characteristics of $K_{sub.FBC}$.

[0011] FIG. 7 is a graph showing the rotation speed characteristics of $\theta_{sub.FBC}$.

[0012] FIG. 8A is an explanatory diagram for explaining effects.

[0013] FIG. 8B is an explanatory diagram for explaining effects.

[0014] FIG. 9 is a graph showing a torque ripple reduction effect.

DETAILED DESCRIPTION

[0015] A controller may calculate a feedback manipulated variable for controlling the rotation speed of a motor to which a cooling fan is attached to a target value. Further, based on the rotation speed, a load operation amount is calculated, which is a feedforward operation amount equivalent to a load torque that increases as the rotation speed of the motor increases. Then, the inverter is operated based on a command manipulated variable, which is a value obtained by adding a load manipulated variable to a feedback manipulated variable.

[0016] Incidentally, in a system including an inverter, harmonic ripples may occur due to variations

in the dead time of the inverter. It is conceivable that this dead time variation can be suppressed by state feedback control. However, state feedback control has an issue in that the control period is slow and the control system becomes unstable when the motor rotates at high speed.

[0017] A controller described herein is for a drive system in which an inverter converts DC power of a DC power supply into three-phase AC power and the three-phase AC power is supplied to a rotating electric machine. The controller calculates a voltage command to be output to the inverter by performing vector control. The controller includes a command value output unit, a conversion unit, a feedback controller, a state feedback controller, and a control unit. The command value output unit outputs a d-axis current command value and a q-axis current command value. The conversion unit converts phase currents flowing through respective phases of the rotating electric machine into a d-axis current value and a q-axis current value. The feedback controller calculates a d-axis voltage command value and a q-axis voltage command value by performing feedback control based on the d-axis current value and the d-axis current command value, and feedback control based on the q-axis current value and the q-axis current command value. The state feedback controller calculates a d-axis voltage correction value and a q-axis voltage correction value by performing state feedback control of the d-axis current value and the q-axis current value to acquire a d-axis voltage value and a q-axis voltage value, and rotation conversion of the d-axis voltage value and the q-axis voltage value at an angle by using a rotation matrix. The angle is correlated to a rotational speed of the rotatory electric machine and determined based on a characteristics of the rotating electric machine. The control unit outputs to the inverter a value as the voltage command obtained by performing uvw conversion of a d-axis corrected command value and a q-axis corrected command value. The d-axis corrected command value is a value obtained by subtracting the d-axis voltage correction value from either the d-axis voltage command value or a correlated value correlated to the d-axis voltage command value. The q-axis corrected command value is a value obtained by subtracting the q-axis voltage correction value from either the q-axis voltage command value or a correlated value correlated to the q-axis voltage command value.

[0018] In this way, the controller uses the rotation matrix to perform rotational conversion at an angle that is correlated with the rotation speed of the rotating electric machine and is determined by the characteristics of the rotating electric machine, and calculates the d-axis voltage correction value and the q-axis voltage correction value. Then, the controller calculates a d-axis corrected command value and a q-axis corrected command value using the d-axis voltage correction value and the q-axis corrected command value, and outputs the uvw converted values of the d-axis corrected command value and the q-axis corrected command value as voltage commands to the inverter. Therefore, the controller can suppress instability caused by state feedback control when the control period is slow and the rotation speed is high. Therefore, the controller can stably control the inverter when the control period is slow and the rotating electric machine rotates at high speed.

[0019] An embodiment for carrying out the present disclosure is hereinafter described with reference to the drawings.

[0020] In this embodiment, as an example, a drive system **100** is applied to a cooling system. The cooling system includes the drive system **100**, a radiator that dissipates heat from the cooling water flowing through an engine (not shown), a cooling fan **50** that air-cools the cooling water flowing through the radiator, and a motor **30** that rotates the cooling fan **50**. The radiator is connected to the engine via a cooling water passage (not shown) that includes an inlet flow path and an outlet flow path.

[0021] The motor **30** is an AC-driven rotating electric machine having U-, V- and W-phase coils **31**, **32** and **33**, respectively. The cooling fan **50** is attached to the rotating shaft of the motor **30**. The cooling fan **50** is rotated by the motor **30** depending on whether the vehicle is stopped or traveling at a low speed.

[0022] The drive system **100** includes a controller **10** and an inverter **20** (INV). The inverter **20** is connected to positive and negative terminals of a battery **70**. The inverter **20** is connected to the

motor **30** via wirings **L1** to **L3**. The inverter **20** converts the DC power supplied from the battery **70** into three-phase AC power of U, V, and W, and supplies it to the motor **30**. The battery **70** corresponds to a DC power supply.

[0023] The inverter **20** has a set of series-connected switching elements for each of the U, V, and W-phases, and is configured by connecting the series-connected sets in parallel. The connection points of the switching elements of each phase are connected to the U-, V-, and W-phase coils **31** to **33** of the motor **30** via the wirings **L1**, **L2**, and **L3**. The switching elements are turned on and off by an operation signal (voltage command) output from the controller **10**, thereby supplying power to the coils **31** to **33** of each phase via the wirings **L1** to **L3**. The switching element may be, for example, a MOSFET or an IGBT.

[0024] A current detection unit **40** is provided on the wirings **L1** to **L3**. The current detection unit **40** includes three phase detection units **41** to **43** that detect the phase currents flowing through the respective phase coils **31** to **33**. The U-phase detection unit **41** is provided on the wiring **L1** that connects the inverter **20** and the U-phase coil **31**. The U-phase detection unit **41** detects the phase current flowing through the U-phase coil **31** as a U-phase current I_u .

[0025] The V-phase detection unit **42** is provided on the wiring **L2** that connects the inverter **20** and the V-phase coil **32**. The V-phase detection unit **42** detects the phase current flowing through the V-phase coil **32** as a V-phase current I_v .

[0026] The W-phase detection unit **43** is provided on the wiring **L3** that connects the inverter **20** and the W-phase coil **33**. The W-phase detection unit **43** detects the current flowing through the W-phase coil of the first winding set **180** as the W-phase current I_{w1} . The phase currents I_u to I_w are provided to a three-to-two phase conversion unit **15**, which will be described later.

[0027] In this embodiment, a shunt resistor is used as an example of each of the phase detection units **41** to **43**. However, in the present disclosure, Hall ICs or the like can be used as each of the phase detection units **41** to **43**.

[0028] The motor **30** is provided with a resolver **60** that detects the electrical angle θ_r of the motor **30**. The electrical angle θ_r is provided to a two-to-three phase conversion unit **13**, a three-to-two phase conversion unit **15** and a rotation speed calculation unit **16**, which will be described later. The current detection unit **40** and the resolver **60** may be included in the drive system **100**.

[0029] The controller **10** is a device that calculates an operation signal to be output to the inverter **20** by vector control. The controller **10** mainly includes a microcomputer and a control IC. The controller **10** may include, for example, a processing device such as a CPU, a memory device including a ROM and a RAM, and an interface such as an I/O circuit. The controller **10** executes control by, for example, software recorded in a physical memory device and a computer that executes the software, hardware, or a combination of these components.

[0030] As shown in FIG. **1**, the controller **10** includes a command value calculation unit **11**, a feedback controller **12**, the two-to-three phase conversion unit **13**, a PWM control unit **14**, the three-to-two phase conversion unit **15**, the rotation speed calculation unit **16**, and a state feedback controller **17**. Furthermore, the controller **10** includes a first d-axis calculator **18a**, a first q-axis calculator **18b**, a second d-axis calculator **18c**, and a second q-axis calculator **18d**. In the drawing, the command value calculation unit **11** is indicated as CVC, the feedback controller **12** is indicated as FBC, the two-to-three phase conversion unit **13** is indicated as 2-3CVT, and the PWM control unit **14** is indicated as PWMC. In addition, the three-to-two phase conversion unit **15** is described as a 3-2CVT, the rotation speed calculation unit **16** as an RPMC, and the state feedback controller **17** as an SFB.

[0031] The command value calculation unit **11** calculates a feedback manipulated variable based on an externally input command value and the rotation speed w of the motor **30** calculated by the rotation speed calculation unit **16**. The command value calculation unit **11** calculates, as feedback manipulated variables, a d-axis current command value I_d^* and a q-axis current command value I_q^* , which are values on the dq coordinate system. The command value calculation unit **11** outputs

the calculated d-axis current command value I_d^* and q-axis current command value I_q^* . The command value calculation unit **11** corresponds to a command value output unit.

[0032] Here, among the axes defining the d-q coordinates, the d-axis is the axis of the ineffective current component, that is, the exciting current component which is a current contributing to the rotation magnetic field accompanying the rotation of the motor **30**. On the other hand, the q-axis is the axis of the active current component, that is, the torque current component which is the current that contributes to the torque of the motor **30**.

[0033] The feedback controller **12** performs feedback control using a d-axis current value I_{dr} and a d-axis current command value I_d^* , and also performs feedback control using a q-axis current value I_{qr} and a q-axis current command value I_q^* . In this way, the feedback controller **12** calculates a d-axis voltage command value V_d^* and a q-axis voltage command value V_q^* . The d-axis current value I_{dr} and the q-axis current value I_{qr} are output from a three-to-two phase conversion unit **15**, which will be described later.

[0034] More specifically, the feedback controller **12** receives outputs from a first d-axis calculator **18a**, a first q-axis calculator **18b**, and the rotation speed calculation unit **16**. The first d-axis calculator **18a** calculates a d-axis current deviation ΔI_d by subtracting the d-axis current value I_{dr} from the d-axis current command value I_d^* . The first q-axis calculator **18b** calculates a q-axis current deviation ΔI_q by subtracting the q-axis current value I_{qr} from the q-axis current command value I_q^* . The rotation speed calculation unit **16** outputs the rotation speed ω of the motor **30**, as will be described later. The feedback controller **12** receives the d-axis current deviation ΔI_d and the q-axis current deviation ΔI_q . The feedback controller **12** calculates a d-axis voltage command value V_d^* so that the d-axis current deviation ΔI_d becomes zero, and calculates a q-axis voltage command value V_q^* so that the q-axis current deviation ΔI_q becomes zero. Then, the feedback controller **12** improves the current response performance by eliminating the interference component using the rotation speed ω .

[0035] The two-to-three phase conversion unit **13** receives outputs from a second d-axis calculator **18c** and a second q-axis calculator **18d**. The second d-axis calculator **18c** calculates a value obtained by subtracting the d-axis voltage correction value V_{d1} from the d-axis voltage command value V_d^* as the d-axis corrected command value V_d . The second q-axis calculator **18d** calculates a q-axis corrected command value V_q by subtracting the q-axis voltage correction value V_{q1} from the q-axis voltage command value V_q^* . The d-axis corrected command value V_d can also be called a d-axis voltage deviation, which is the deviation between the d-axis voltage command value V_d^* and the d-axis voltage correction value V_{d1} . The q-axis corrected command value V_q can also be called a q-axis voltage deviation, which is the deviation between the q-axis voltage command value V_q^* and the q-axis voltage correction value V_{q1} . The d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} are output from a state feedback controller **17**, which will be described later.

[0036] The two-to-three phase conversion unit **13** performs uvw conversion on the d-axis corrected command value V_d and the q-axis corrected command value V_q using the electrical angle θ_r of the motor **30**. That is, the two-to-three phase conversion unit **13** performs uvw conversion on the d-axis corrected command value V_d and the q-axis corrected command value V_q into a U-phase command voltage V_u , a V-phase command voltage V_v , and a W-phase command voltage V_w .

[0037] In this manner, the controller **10** corrects the d-axis voltage command value V_d^* using the d-axis voltage correction value V_{d1} calculated by the state feedback controller **17**. In addition, the controller **10** corrects the q-axis voltage command value V_q^* using the q-axis voltage correction value V_{q1} calculated by the state feedback controller **17**.

[0038] The PWM control unit **14** calculates operation signals GS_u , GS_v , GS_w for operating the U-, V-, and W-phase semiconductor switches of the inverter **20** based on the U-phase command voltage V_u , the V-phase command voltage V_v , and the W-phase command voltage V_w . In other words, the PWM control unit **14** generates PWM waveform signals (voltage designated value signals) GS_u ,

GSv, and GSw to perform switching control of each switch of the inverter **20**.

[0039] The operation signal GSu is a signal for operating the U-phase switch of the inverter **20**. The operation signal GSv is a signal for operating the V-phase switch of the inverter **20**. The operation signal GSw is a signal for operating the W-phase switch of the inverter **20**. Then, the PWM control unit **14** outputs the operation signals GSu, GSv, and GSw to the inverter **20**. In this manner, the controller **10** controls the inverter **20**. The two-to-three phase conversion unit **13** and the PWM control unit **14** correspond to a control unit.

[0040] The three-to-two phase conversion unit **15** performs dq axis conversion of each phase current I_u to I_w into a d-axis current value I_{dr} and a q-axis current value I_{qr} based on the electrical angle θ_r . That is, the three-to-two phase conversion unit **15** converts each of the phase currents I_u to I_w into a d-axis current value I_{dr} and a q-axis current value I_{qr} , which are values on the dq coordinate system. The three-to-two phase conversion unit **15** corresponds to a conversion unit. The rotation speed ω of the motor **30** is calculated by the rotation speed calculation unit **16**. The rotation speed calculation unit **16** calculates the rotation speed ω by differentiating the electrical angle θ_r .

[0041] The state feedback controller **17** will be described with reference to FIG. 2. The state feedback controller **17** includes a rotation matrix calculation unit **170** and gain compensators **171** to **173**. The d-axis gain compensator **171** calculates the d-axis voltage value V_{dr} by performing state feedback control of the d-axis current value I_{dr} with a state feedback gain $K_{sub.SFB}$. The q-axis gain compensator **172** calculates the q-axis voltage value V_{qr} by performing state feedback control on the q-axis current value I_{qr} with a state feedback gain $K_{sub.SFB}$. In this manner, the state feedback controller **17** calculates the d-axis voltage value V_{dr} and the q-axis voltage value V_{qr} by performing state feedback control on the d-axis current value I_{dr} and the q-axis current value I_{qr} .

[0042] The state feedback gain $K_{sub.SFB}$ is a value that is set in advance based on manufacturing variations, control periods, and the like. In this embodiment, as an example, the same state feedback gain $K_{sub.SFB}$ is used on the d-axis side and the q-axis side. However, the state feedback gain $K_{sub.SFB}$ may have different values on the d-axis side and the q-axis side.

[0043] The ω gain compensator **173** calculates the rotation angle $\theta_{sub.SFB}$ by multiplying the rotation speed ω by a state feedback angle gain $K_{\theta.sub.SFB}$. The state feedback angle gain $K_{\theta.sub.SFB}$ is a value that is set in advance based on the characteristics of the motor **30**. The characteristics of the motor **30** are parameters such as the resistance value and inductance of the motor **30**. The rotation angle $\theta_{sub.SFB}$ is an angle that correlates with the rotation speed ω of the motor **30** and is determined by the characteristics of the motor **30**. In this embodiment, as an example, a rotation angle $\theta_{sub.SFB}$ proportional to the rotation speed ω is adopted. That is, the rotation angle $\theta_{sub.SFB}$ is a value that is proportional to the rotation speed ω . The rotation angle $\theta_{sub.SFB}$ can also be called the rotation angle of a state feedback control system or a state feedback rotation angle.

[0044] The rotation matrix calculation unit **170** receives the d-axis voltage value V_{dr} , the q-axis voltage value V_{qr} , and the rotation angle $\theta_{sub.SFB}$. The rotation matrix calculation unit **170** calculates the rotation matrix shown in FIG. 2. The rotation matrix calculation unit **170** performs rotation transformation on the d-axis voltage value V_{dr} and the q-axis voltage value V_{qr} by a rotation angle $\theta_{sub.SFB}$ (angle) using a rotation matrix to calculate a d-axis voltage correction value V_{d1} and a q-axis voltage correction value V_{q1} . That is, the rotation matrix calculation unit **170** calculates the d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} by rotating the d-axis voltage value V_{dr} and the q-axis voltage value V_{qr} in the opposite direction by the rotation angle $\theta_{sub.SFB}$. The rotation matrix calculation unit **170** can also be considered as a calculator of a state feedback control system or a phase compensator of the state feedback control system.

[0045] The controller **10** is designed in a discrete system rather than a continuous system. In the case of a discrete system, it is necessary to compensate for the interference between the d-axis and

the q-axis in state feedback control. The more precisely the inter-axis interference is compensated for, the more stable the control becomes. However, there is a possibility that the calculation will become unstable due to the time required for the calculation. Therefore, the controller **10** calculates the d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} for compensating for the inter-axis interference by the rotation matrix calculation unit **170**.

[0046] As described above, the controller **10** uses a rotation matrix to perform a rotation transformation at the rotation angle $\theta_{\text{sub.SFB}}$ that is correlated with the rotation speed ω of the motor **30** and determined by the characteristics of the motor **30**, and calculates the d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} . Then, the controller **10** calculates the d-axis corrected command value V_d and the q-axis corrected command value V_q using the d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} . Furthermore, the controller **10** calculates operation signals GS_u , GS_v , GS_w from values V_u to V_w obtained by uvw conversion of the d-axis corrected command value V_d and the q-axis corrected command value V_q , and outputs them to the inverter.

[0047] Therefore, the controller **10** can suppress instability caused by state feedback control when the control period is slow and the motor **30** is rotating at high speed. Therefore, the controller **10** can stably control the inverter **20** when the control period is slow and the rotation speed is high. Furthermore, the controller **10** can stably control the inverter **20** while suppressing harmonic ripples. It can also be said that the controller **10** can stably control the drive of the motor **30** via the inverter **20** when the control period is slow and the motor is rotating at high speed.

[0048] That is, in the drive system **100**, harmonic ripples occur due to the dead time variation of the inverter **20**. In the drive system **100**, abnormal noise (audible noise) occurs when the harmonic ripple coincides with the resonant frequency of the cooling system. This dead time variation is a voltage disturbance. In order to suppress this voltage disturbance, it is conceivable to use state feedback control.

[0049] However, in the state feedback control, when the control period of the controller **10** is slow and the rotation speed is high, the control system may become unstable. Therefore, the controller **10** calculates the d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} using the rotation matrix as described above, and calculates the d-axis corrected command value V_d and the q-axis corrected command value V_q using the d-axis voltage correction value V_{d1} and the q-axis voltage correction value V_{q1} . This allows the controller **10** to stabilize the control of the inverter **20** as described above, and suppress harmonic ripples through state feedback control. The control system includes the drive system **100**, the cooling fan **50**, and the motor **30** that rotates the cooling fan **50**. In other words, the control system can be rephrased as a cooling system.

[0050] In addition, the stability of the motor **30** against parameter variations was confirmed using the contour diagram shown in FIGS. **8A** and **8B**. FIG. **8A** shows the results for a comparative controller that does not use a rotation matrix. FIG. **8B** shows the results for the controller **10** using a rotation matrix. In addition, in FIGS. **8A** and **8B**, the unstable regions are hatched. The black dots in FIGS. **8A** and **8B** indicate nominal parameters (design values). The parameters of the motor **30** include the resistance value and the inductance.

[0051] As shown in FIG. **8A**, in the comparative control unit, the unstable region is close to the nominal parameters, and the control system is easily destabilized by parameter fluctuations. On the other hand, as shown in FIG. **8B**, in the controller **10**, the unstable region is far from the nominal parameters, and the control system can be stabilized. In other words, the control system of the controller **10** is unlikely to become unstable even if the parameters fluctuate.

[0052] Furthermore, the above-mentioned abnormal noise is caused by the secondary ripple component of the electrical angle. Therefore, the effect was confirmed by torque ripple as shown in FIG. **9**. FIG. **9** is a graph showing the torque ripple reduction effect. More specifically, FIG. **9** shows the results of a simulation showing the relationship between the electrical angle order and the torque ripple. The solid line in FIG. **9** is a simulation result for the controller **10** equipped with

the state feedback controller **17**. On the other hand, the solid line in FIG. **9** represents the simulation results for a comparative controller that does not include the state feedback controller **17**. As shown in FIG. **9**, it was confirmed that the controller **10** can reduce the torque ripple of the electrical angle second order by approximately 33%.

[0053] As in a modified example shown in FIG. **3**, the controller **10** may be provided with a rotation matrix calculation unit **124** on the output side of the feedback controller **12**. The rotation matrix calculation unit **124** can also be said to be a calculator of a feedback control system or a phase compensator of a feedback control system. The rotation matrix calculation unit **124** corresponds to a correlation value calculation unit.

[0054] The rotation matrix calculation unit **124** receives the d-axis voltage command value V_d^* , the q-axis voltage command value V_q^* , and the rotation angle $\theta_{\text{sub.FBC}}$. The rotation matrix calculation unit **124** calculates the rotation matrix shown in FIG. **3**. The rotation angle $\theta_{\text{sub.FBC}}$ is calculated by the w gain compensator **123**. The rotation speed ω is input to the w gain compensator **123**, and a feedback angle gain $K\theta_{\text{sub.FBC}}$ is set.

[0055] The rotation matrix calculation unit **170** performs a rotational conversion on the d-axis voltage command value V_d^* and the q-axis voltage command value V_q^* at a rotation angle $\theta_{\text{sub.FBC}}$ using a rotation matrix to calculate a d-axis correlation value V_{d1}^* that is correlated with the d-axis voltage command value V_d^* and a q-axis correlation value V_{q1}^* that is correlated with the q-axis voltage command value V_q^* . That is, the rotation matrix calculation unit **170** calculates the d-axis correlation value V_{d1}^* and the q-axis correlation value V_{q1}^* by rotating the d-axis voltage command value V_d^* and the q-axis voltage command value V_q^* in the opposite direction by the rotation angle $\theta_{\text{sub.FBC}}$.

[0056] In the configuration of the modified example, the second d-axis calculator **18c** calculates a value obtained by subtracting the d-axis voltage correction value V_{d1} from the d-axis correlation value V_{d1}^* as the d-axis corrected command value V_d . The second q-axis calculator **18d** calculates a value obtained by subtracting the q-axis voltage correction value V_{q1} from the q-axis correlation value V_{q1}^* as the q-axis corrected command value V_q .

[0057] FIGS. **4**, **5**, **6**, and **7** show the rotation speed characteristics of the state feedback gain $K_{\text{sub.SFB}}$, the rotation angle $\theta_{\text{sub.SFB}}$, the feedback gain $K_{\text{sub.FBC}}$, and the rotation angle $\theta_{\text{sub.FBC}}$. In each drawing, the theoretical values are shown by solid lines. The controller **10** according to the modified example performs calculation processing using theoretical values to control the inverter **20**. Therefore, the controller **10** according to the modified example can appropriately control the inverter **20**.

[0058] However, the processing load of the controller **10** of the modified example increases by using the theoretical values shown in FIGS. **4**, **5**, **6**, and **7**. Therefore, in the above embodiment, as shown by the dashed lines in FIGS. **4**, **5**, **6** and **7**, the state feedback gain $K_{\text{sub.SFB}}$, the feedback gain $K_{\text{sub.FBC}}$, and the rotation angle $\theta_{\text{sub.FBC}}$ are approximated as being constant values, and the rotation angle $\theta_{\text{sub.SFB}}$ is proportional to the rotation speed ω . This allows the controller **10** of the above embodiment to have a lower processing load than the modified example.

[0059] However, the present disclosure is not only limited to the above example. It is also conceivable that the theoretical value of the rotation angle $\theta_{\text{sub.SFB}}$ changes linearly depending on the range of the rotation speed ω . In this case, the rotation angle $\theta_{\text{sub.SFB}}$ is a value that correlates with the rotation speed ω , and is determined by changing the slope and intercept of a linear function according to the rotation speed ω .

[0060] The preferred embodiment of the present disclosure has been described above. However, the present disclosure is not limited to the above embodiment. Various modifications may be made without departing from the scope and spirit of the present disclosure.

[0061] Although the present disclosure has been described in accordance with the embodiments, it is understood that the present disclosure is not limited to the embodiments or the structures. The present disclosure encompasses various modifications and variations within the scope of

equivalents. In addition, while various combinations and modes are described in the present disclosure, other combinations and modes including only one element, more elements, or less elements therein are also within the scope and spirit of the present disclosure.

Claims

1. A controller for a drive system, the drive system configured to convert DC power of a DC power supply into three-phase AC power through an inverter and supply the three-phase AC power to a rotating electric machine, the controller comprising: a command value output unit configured to output a d-axis current command value and a q-axis current command value; a conversion unit configured to convert phase currents into a d-axis current value and a q-axis current value through dq-axis transformation, the phase currents being currents flowing through respective phases of the rotating electric machine; a feedback controller configured to calculate a d-axis voltage command value and a q-axis voltage command value by performing feedback control based on the d-axis current value and the d-axis current command value, and feedback control based on the q-axis current value and the q-axis current command value; a state feedback controller configured to calculate a d-axis voltage correction value and a q-axis voltage correction value by performing state feedback control of the d-axis current value and the q-axis current value to acquire a d-axis voltage value and a q-axis voltage value, and rotation conversion of the d-axis voltage value and the q-axis voltage value at an angle by using a rotation matrix, the angle being correlated to a rotational speed of the rotating electric machine and determined based on a characteristic of the rotating electric machine; and a control unit configured to output to the inverter a value as a voltage command that is calculated through vector control in which uvw conversion of a d-axis corrected command value and a q-axis corrected command value is performed, the d-axis corrected command value being a value obtained by subtracting the d-axis voltage correction value from either the d-axis voltage command value or a correlated value correlated to the d-axis voltage command value, the q-axis corrected command value being a value obtained by subtracting the q-axis voltage correction value from either the q-axis voltage command value or a correlated value correlated to the q-axis voltage command value.
2. The controller according to claim 1, further comprising: a correlated value calculation unit configured to calculate the correlated value correlated to the d-axis voltage command value and the correlated value correlated to the q-axis voltage command value by performing rotation conversion of the d-axis voltage command value and the q-axis voltage command value at an angle by using a rotation matrix, the angle being correlated to the rotational speed of the rotating electric machine and determined based on a characteristic of the feedback controller and a characteristic of the state feedback controller.
3. The controller according to claim 1, wherein the angle determined based on the characteristic of the rotating electric machine is proportional to the rotational speed of the rotating electric machine.
4. A method for a drive system, the drive system configured to convert DC power of a DC power supply into three-phase AC power through an inverter and supply the three-phase AC power to a rotating electric machine, the method comprising: outputting a d-axis current command value and a q-axis current command value; converting phase currents into a d-axis current value and a q-axis current value through dq-axis transformation, the phase currents being currents flowing through respective phases of the rotating electric machine; calculating a d-axis voltage command value and a q-axis voltage command value by performing feedback control based on the d-axis current value and the d-axis current command value, and feedback control based on the q-axis current value and the q-axis current command value; calculating a d-axis voltage correction value and a q-axis voltage correction value by performing state feedback control of the d-axis current value and the q-axis current value to acquire a d-axis voltage value and a q-axis voltage value, and rotation conversion of the d-axis voltage value and the q-axis voltage value at an angle by using a rotation

matrix, the angle being correlated to a rotational speed of the rotating electric machine and determined based on a characteristic of the rotating electric machine; and outputting to the inverter a value as a voltage command that is calculated through vector control in which uvw conversion of a d-axis corrected command value and a q-axis corrected command value is performed, the d-axis corrected command value being a value obtained by subtracting the d-axis voltage correction value from either the d-axis voltage command value or a correlated value correlated to the d-axis voltage command value, the q-axis corrected command value being a value obtained by subtracting the q-axis voltage correction value from either the q-axis voltage command value or a correlated value correlated to the q-axis voltage command value.

5. A non-transitory computer readable medium for a drive system, the drive system configured to convert DC power of a DC power supply into three-phase AC power through an inverter and supply the three-phase AC power to a rotating electric machine, the non-transitory computer readable medium storing a computer program comprising instructions configured to, when executed by at least one processor, cause the at least one processor to: output a d-axis current command value and a q-axis current command value; convert phase currents into a d-axis current value and a q-axis current value through dq-axis transformation, the phase currents being currents flowing through respective phases of the rotating electric machine; calculate a d-axis voltage command value and a q-axis voltage command value by performing feedback control based on the d-axis current value and the d-axis current command value, and feedback control based on the q-axis current value and the q-axis current command value; calculate a d-axis voltage correction value and a q-axis voltage correction value by performing state feedback control of the d-axis current value and the q-axis current value to acquire a d-axis voltage value and a q-axis voltage value, and rotation conversion of the d-axis voltage value and the q-axis voltage value at an angle by using a rotation matrix, the angle being correlated to a rotational speed of the rotating electric machine and determined based on a characteristic of the rotating electric machine; and output to the inverter a value as a voltage command that is calculated through vector control in which uvw conversion of a d-axis corrected command value and a q-axis corrected command value is performed, the d-axis corrected command value being a value obtained by subtracting the d-axis voltage correction value from either the d-axis voltage command value or a correlated value correlated to the d-axis voltage command value, the q-axis corrected command value being a value obtained by subtracting the q-axis voltage correction value from either the q-axis voltage command value or a correlated value correlated to the q-axis voltage command value.
