

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403304
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kim; Jong Won et al.

High frequency and ultrasonic fusion treatment device

Abstract

Proposed is a high frequency wave and ultrasonic wave fusion treatment device used for skin treatment and improvement that includes a housing, a tip disposed at one end of the housing, a plurality of high frequency wave transfer parts disposed on the tip and configured to transfer high frequency wave energy to skin in a pulsed manner, an ultrasonic wave transfer part disposed on the tip, but spaced apart from the high frequency wave transfer parts, and configured to transfer generated ultrasonic wave energy through an ultrasonic wave irradiation surface provided on the tip to the skin, and a movement part disposed inside the housing or the tip and configured to move the ultrasonic wave transfer part along the ultrasonic wave irradiation surface.

Inventors: Kim; Jong Won (Seongnam-si, KR), Kim; Jung Hyun (Seongnam-si, KR), Seo; Young Seok (Sejong-si, KR), Kim; Young Sik (Daejeon, KR)

Applicant: WONTECH Co., Ltd. (Daejeon, KR)

Family ID: 88393144

Assignee: WONTECH CO., LTD. (Daejeon, KR)

Appl. No.: 18/059382

Filed: November 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230338730 A1	Oct. 26, 2023

Foreign Application Priority Data

KR	10-2022-0049602	Apr. 21, 2022
----	-----------------	---------------

Publication Classification

Int. Cl.: A61N1/06 (20060101); A61N1/32 (20060101); A61N7/00 (20060101)

U.S. Cl.:

CPC A61N1/06 (20130101); A61N1/328 (20130101); A61N7/00 (20130101);
A61N2007/0034 (20130101)

Field of Classification Search

CPC: A61N (1/06); A61N (1/328); A61N (2007/0034); A61N (2007/0091); A61N (2007/025);
A61N (7/00); A61N (7/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0254008	12/2008	Shields, Jr.	601/3	A61N 7/00
2016/0038771	12/2015	Jung	601/3	A61N 7/02
2017/0333705	12/2016	Schwarz	N/A	A61N 1/328
2021/0393992	12/2020	Ji	N/A	A61N 1/403

Primary Examiner: Demie; Tigist S

Attorney, Agent or Firm: Harvest IP Law, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) The present application claims priority to Korean Patent Application No. 10-2022-0049602, filed on Apr. 21, 2022, the entire contents of which is incorporated herein for all purposes by this reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) The present disclosure relates to a device and, more particularly, to a high frequency wave and ultrasonic wave fusion treatment device used for skin treatment and improvement.

Description of the Related Art

(3) Recently, energy is provided to the skin using various energy sources, whereby a technique for treating the skin has been widely applied by transforming the tissue state of the skin or improving tissue characteristics. Skin treatment devices using various energy sources such as laser beams, flash lamps, ultrasonic waves, and the like have been developed, and recently, research on skin treatment devices using RF high frequency wave energy has been actively conducted. When high frequency wave energy is provided to the skin surface, each time a direction of a high frequency wave current is changed, molecules constituting skin tissue vibrate and rub against each other, and deep heat is generated by rotational motion, twisting motion, or collision motion. Such deep heat may increase the temperature of skin tissue to reorganize a collagen layer, thereby improving wrinkles and enhancing skin elasticity.

(4) In addition, when ultrasonic wave energy is provided to the skin surface, high intensity ultrasonic wave energy is focused in one place, whereby high heat is generated. Using the heat

generated by focused ultrasonic waves, specific subcutaneous tissue such as tumors in the skin and the like may be burned and removed, or degeneration and regeneration of the skin tissue may be caused, thereby improving wrinkles.

(5) The foregoing is intended merely to aid in the understanding of the background of the present disclosure and is not intended to mean that the present disclosure falls within the purview of the related art that is already known to those skilled in the art.

SUMMARY OF THE INVENTION

(6) Accordingly, the present disclosure has been made keeping in mind the above problems occurring in the related art, and an objective of the present disclosure is to provide a high frequency wave and ultrasonic wave fusion treatment device in order to treat and improve the skin by transferring high frequency wave energy and ultrasonic wave energy to the skin without continuous handpiece movement.

(7) The objective of the present disclosure is not limited to the above-mentioned objective, and other objectives not mentioned may be clearly understood by those skilled in the art from the description below.

(8) In order to achieve the above objective, according to one embodiment of the present disclosure, there may be provided a high frequency wave and ultrasonic wave fusion treatment device, the device including: a housing; a tip disposed at one end of the housing; a plurality of high frequency wave transfer parts disposed on the tip and configured to transfer high frequency wave energy to skin in a pulsed manner; an ultrasonic wave transfer part disposed on the tip, but spaced apart from the high frequency wave transfer parts, and configured to transfer generated ultrasonic wave energy through an ultrasonic wave irradiation surface provided on the tip to the skin; and a movement part disposed inside the housing or the tip and configured to move the ultrasonic wave transfer part along the ultrasonic wave irradiation surface.

(9) In the one embodiment of the present disclosure, the plurality of high frequency wave transfer parts may be arranged symmetrically on opposite sides with the ultrasonic wave irradiation surface as a center.

(10) In the one embodiment of the present disclosure, the high frequency wave transfer parts may be provided with one cover layer disposed on a surface of one side thereof facing the skin.

(11) In the one embodiment of the present disclosure, the device may further include a controller configured to control at least one of the high frequency wave transfer parts, the ultrasonic wave transfer part, and the movement part.

(12) In the one embodiment of the present disclosure, the controller may be configured to control the high frequency wave transfer parts and the ultrasonic wave transfer part so that the high frequency wave energy and the ultrasonic wave energy are emitted at the same time or at different times, respectively.

(13) In the one embodiment of the present disclosure, the controller may be configured to control an emission sequence and an emission time point of the high frequency wave energy of each of the high frequency wave transfer parts on the basis of an arrangement order of the plurality of high frequency wave transfer parts.

(14) In the one embodiment of the present disclosure, the controller may be configured to control at least one pair of the high frequency wave transfer parts disposed symmetrically with each other with respect to the ultrasonic wave irradiation surface among the plurality of high frequency wave transfer parts to simultaneously emit high frequency wave energy.

(15) In the one embodiment of the present disclosure, the controller may be configured to group the plurality of high frequency wave transfer parts into a plurality of groups and control emission of the high frequency wave energy for each group.

(16) In the one embodiment of the present disclosure, the controller may be configured to control an emission sequence and an emission time point of the high frequency wave energy on the basis of an arrangement order of the plurality of groups.

- (17) In the one embodiment of the present disclosure, the controller may be configured to control a movement distance and a movement time of the movement part on the basis of the emission sequence and emission time point of the high frequency wave energy.
- (18) In the one embodiment of the present disclosure, the controller may be configured to control movement of the movement part so that the ultrasonic wave transfer part emits ultrasonic wave energy at a position staggered with the high frequency wave transfer part emitting high frequency wave energy among the plurality of high frequency wave transfer parts.
- (19) As described above, according to an embodiment of the present disclosure, a thermal effect can be maximized by irradiating skin with high frequency wave energy and ultrasonic wave energy simultaneously or alternately.
- (20) In addition, even when the skin is irradiated with high frequency wave energy and ultrasonic wave energy simultaneously, damage to the skin can be avoided.
- (21) Effects of the present disclosure are not limited to the above effects and should be understood to include all effects that can be inferred from the description of the present disclosure or the configuration of the invention described in the claims.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objectives, features, and other advantages of the present disclosure will be more clearly understood from the following detailed description when taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a view showing a high frequency wave and ultrasonic wave fusion treatment device according to an embodiment of the present disclosure;
- (3) FIG. 2 is a view showing a tip end portion to which a Flexible Printed Circuit Board (FPCB) is attached according to the embodiment of the present disclosure;
- (4) FIG. 3 is a view showing a handpiece having a cover and a cover layer according to the embodiment of the present disclosure;
- (5) FIG. 4 is a sectional view showing a tip provided in a handpiece according to the embodiment of the present disclosure;
- (6) FIG. 5 is a block diagram schematically showing a control signal of a controller according to the embodiment of the present disclosure;
- (7) FIG. 6 is a view showing a movement part according to the embodiment of the present disclosure;
- (8) FIG. 7 shows operation patterns of the high frequency wave and ultrasonic wave fusion treatment device according to the embodiments of the present disclosure;
- (9) FIG. 8 is sectional views showing a tip provided in a handpiece according to another embodiment of the present disclosure;
- (10) FIG. 9 is a sectional view showing a tip provided in the handpiece according to another embodiment of the present disclosure; and
- (11) FIG. 10 is a sectional view showing a tip provided in the handpiece according to still another embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

- (12) Hereinbelow, the present disclosure will be described with reference to the accompanying drawings. However, the present disclosure may be embodied in many different forms and, therefore, is not limited to embodiments described herein. In addition, in order to clearly explain the present disclosure in the drawings, parts irrelevant to the description are omitted, and similar reference numerals are attached to similar parts throughout the specification.
- (13) Throughout the specification, when a part is said to be “connected (accessed, contacted,

coupled”) with another part, this includes not only “directly connected”, but also “indirectly connected” with another member in between. In addition, when a part “includes” a certain component, it means that it may further include other components without excluding other components unless otherwise stated.

(14) Terms used in the present specification are only used to describe specific embodiments and are not intended to limit the present disclosure. Singular expressions include plural expressions unless the context clearly dictates otherwise.

(15) In the present specification, terms such as “include”, “have”, and the like are intended to designate that features, numbers, steps, operations, components, parts, or combinations thereof described in the specification exist and are to be understood such that presence or addition of one or more other features, numbers, steps, operations, components, parts, or combinations thereof is not precluded.

(16) Hereinafter, the embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

(17) FIG. 1 is a view showing a high frequency wave and ultrasonic wave fusion treatment device 1 according to an embodiment of the present disclosure, FIG. 2 is a view showing a tip end portion 220 to which a Flexible Printed Circuit Board (FPCB) is attached according to the embodiment of the present disclosure, FIG. 3 is a view showing a handpiece 10 having a cover 240 and a cover layer 250 according to the embodiment of the present disclosure, FIG. 4 is a sectional view showing a tip 200 provided in the handpiece 10 according to the embodiment of the present disclosure, FIG. 5 is a block diagram schematically showing a control signal of a controller 600 according to the embodiment of the present disclosure, FIG. 6 is a view showing a movement part 500 according to the embodiment of the present disclosure, a part (a) of FIG. 7 shows a first operation pattern of the high frequency wave and ultrasonic wave fusion treatment device 1 according to the embodiment of the present disclosure, a part (b) of FIG. 7 shows a second operation pattern of the high frequency wave and ultrasonic wave fusion treatment device 1, and a part (c) of FIG. 7 shows a third operation pattern of the high frequency wave and ultrasonic wave fusion treatment device 1, FIG. 8 is sectional views showing a tip 200 provided in a handpiece 10 according to another embodiment of the present disclosure, FIG. 9 is a sectional view showing a tip 200 provided in the handpiece 10 according to another embodiment of the present disclosure, and FIG. 10 is a sectional view showing a tip 200 provided in the handpiece 10 according to still another embodiment of the present disclosure.

(18) With reference to FIGS. 1 to 10, the high frequency wave and ultrasonic wave fusion treatment device 1 may be a system in order to treat (improve) patient's skin using high frequency wave energy and/or ultrasonic wave energy. The high frequency wave and ultrasonic wave fusion treatment device 1 may include a handpiece and a main body 20.

(19) The main body 20 is connected to the handpiece 10 and may generate high frequency wave energy and ultrasonic wave energy according to input information input by a user and transfer same to the handpiece 10. The main body 20 may include a display part 21, a high frequency wave generator 310, and an ultrasonic wave generator 410.

(20) The display part 21 may display an image to the outside. The image displayed by the display part 21 may represent input information such as intensity of high frequency wave and ultrasonic wave energy, adjustment of pulse interval, or the like. The display part 21 may be disposed on an upper portion of the main body 20 so that the screen and the user face each other so as to be easily touched by the user. The display part 21 may decide input information about the high frequency wave energy and ultrasonic wave energy transferred to the handpiece 10 by a user touching a screen and an image.

(21) The display unit 21 may be located on an outer surface of the main body 20. The display part 21 may be disposed on an upper portion of the main body 20 so that the screen and the user face each other so as to be easily touched by the user.

(22) The high frequency wave generator **310** and the ultrasonic wave generator **410** will be described together with the handpiece **10** below.

(23) The handpiece **10** may transfer high frequency wave energy and/or ultrasonic wave energy to patient's skin. The handpiece **10** may include a housing **100**, a tip **200**, a high frequency wave transfer part **320**, an ultrasonic wave transfer part **420**, and the movement part **500**. In addition, the handpiece **10** may further include the controller **600**.

(24) The housing **100** is a part that a user grips when skin treatment is performed using the handpiece **10** and may be provided in a handheld type to improve convenience of user manipulation. For example, such a housing may have a rear end, which is an end of a side opposite to a front end, having a width wider than the front end at which the tip is disposed. At this time, a boundary portion between the front end and the rear end of the housing **100** is provided in a curved surface that is an incurvated shape, so the user may comfortably and stably hold the housing **100**. The housing **100** may include a detachable portion **110** and a cable **120**.

(25) The detachable portion **110** may detach the tip **200** from the housing **100**. More specifically, the detachable portion **110** may be selectively coupled to the tip **200**. As one embodiment, one end of the detachable portion **110** may protrude to the outside of the housing **100** and an opposite end (not shown) may be accommodated inside the housing **100**. At this time, the opposite end of the detachable portion **110** may be detachably coupled to the rear end (not shown) of the tip **200** (for example, the end portion opposite to the tip end portion **220** to be described later). In this case, when the user presses the detachable portion **110**, the opposite end of the detachable portion **110** is separated from the rear end of the tip **200**, whereby the tip **200** may be separated from the housing **100**.

(26) The cable **120** may be connected to the main body **20** and transfer power generated from the main body **20** to the handpiece **10**. In addition, the cable **120** may transfer a high frequency wave signal and an ultrasonic wave signal to the handpiece **10**.

(27) The tip **200** may transmit both high frequency wave energy and ultrasonic wave energy to the patient's skin. In addition, the tip **200** may transmit the high frequency wave energy or the ultrasonic wave energy, respectively. Tip **200** may be disposed in the housing **100**. In the one embodiment, the tip **200** may be disposed to face a bottom surface at the front end portion of the housing **100**.

(28) The tip **200** may be detachably coupled to the housing **100**. As described above, the tip **200** is detachably coupled to the detachable portion **110** and may be separated from the housing **100** by, for example, an operation pressing the detachable portion **110**. At this time, the tip **200** may include a tip body **210**, the tip end portion **220**, and an ultrasonic wave irradiation surface **230**.

(29) When coupled with the detachable portion **110**, the tip body **210** may be a part that directly contacts one end of the detachable portion **110**. The tip body **210** has a flat and angular cross section so as to be easily gripped by the user, thereby being allowed to be easily attached to and detached from the handpiece **10**.

(30) The tip end portion **220** may transfer ultrasonic wave energy and/or high frequency wave energy to the patient's skin during skin treatment using the handpiece **10**. With reference to FIG. 2, the FPCB may be attached to the tip end portion **220**. The FPCB is a non-conductive board, is a film of a synthetic resin material having flexibility, and may have various sizes and shapes depending on an area to be treated. However, the FPCB may have a shape that matches a shape of the tip end portion **220** as shown in FIG. 4. In one embodiment, with reference to FIG. 3, the FPCB may be provided with a cover **240** so as to be prevented from being separated from the tip end portion **220**. The tip end portion **220** may be disposed to face the patient's skin during skin treatment.

(31) The high frequency wave signal and the ultrasonic wave signal transferred through the cable **120** may be converted into high frequency wave energy and ultrasonic wave energy, thereby being subjected to irradiation through the tip end portion **220**. At this time, the handpiece **10** may transfer

the high frequency wave energy and/or ultrasonic wave energy with the tip end portion **220** in a state of being brought into contact with the skin. Meanwhile, as another embodiment, the tip end portion **220** may transfer the high frequency wave energy and ultrasonic wave energy in a non-contact state with the skin, but hereinafter, an embodiment in which the tip end portion **220** is brought into contact with the skin will be mainly described.

(32) When the tip end portion **220** is brought into contact with the skin to be treated, the high frequency wave and ultrasonic waves may be simultaneously or alternately transferred to the skin being brought into contact with the tip. Details on this will be described later. The ultrasonic wave irradiation surface **230** may be a portion that the outside is irradiated with ultrasonic wave energy, having been generated from the ultrasonic wave transfer part **420**, passing therethrough. When water is contained inside the tip **200**, the ultrasonic wave irradiation surface **230** may prevent water from being discharged to the outside. In this case, the water is an ultrasonic wave energy transfer medium and may allow the ultrasonic wave energy to be smoothly generated and emitted in the ultrasonic wave transfer part **420**. Such an ultrasonic wave irradiation surface **230** is disposed on the tip end portion **220** and may have a length the same as a length of a guide shaft **520** to be described later or a maximum moving distance of the ultrasonic wave transfer part **420**.

(33) As an embodiment, the ultrasonic wave irradiation surface **230** may extend from one side of the tip end portion **220** up to an opposite side facing thereto. At this time, when viewed from a direction parallel to the YZ plane, the ultrasonic wave irradiation surface **230** may pass through the center of the tip end portion **220** and extend in a direction parallel to a width direction (Y axis direction). The ultrasonic wave irradiation surface **230** may have a length the same as a moving distance of the ultrasonic wave transfer part **420**. In this case, the ultrasonic wave transfer part **420** may transfer ultrasonic wave energy to the skin through a portion of the ultrasonic wave irradiation surface **230** while moving along the ultrasonic wave irradiation surface **230**, which will be described in detail later.

(34) A high frequency wave module **300** may generate high frequency wave energy and provide it to the skin. The high frequency wave module **300** may include the high frequency wave generator **310** and the high frequency wave transfer part **320**.

(35) The high frequency wave generator **310** may receive a control signal from the controller **600** to be described later and generate various types of high frequency wave energy on the basis of a received control signal. For example, the high frequency wave generator **310** may generate various types of high frequency wave energy having various specific time points, frequencies, and intensities. The high frequency wave generator **310** may transfer generated high frequency wave energy to the high frequency wave transfer part **320** inside the housing **100** through the cable **120**.

(36) The high frequency wave generator **310** may be disposed inside the main body **20**. In such a case, the high frequency wave generator **310** may provide the generated high frequency wave energy to the handpiece **10** through the cable **120**. Meanwhile, the present disclosure is not limited thereto, and as another embodiment, the high frequency wave generator **310** may also be disposed inside the housing **100**.

(37) The high frequency wave transfer part **320** may be connected to the high frequency wave generator **310** and transfer the high frequency wave energy generated by the high frequency wave generator **310** to the skin. The high frequency wave transfer part **320** may be, for example, a radio frequency (RF) electrode. In this case, when a plurality of high frequency wave transfer parts **320** is provided, high frequency wave energy having various frequencies and intensities may be transferred.

(38) The high frequency wave transfer part **320** may be disposed on the tip **200**. More specifically, the high frequency wave transfer part is disposed on the tip end portion **220** and may face the skin during skin treatment using the handpiece **10**.

(39) Meanwhile, as an embodiment, with reference to FIG. 3, the high frequency wave transfer part **320** may include a cover layer **250**. The cover layer **250** may be a dielectric substance. When the

dielectric substance is applied to an entire surface of the high frequency wave transfer part **320**, during skin treatment, the high frequency wave transfer part **320** may transfer the high frequency wave energy by capacitive coupling with the skin. At this time, when the dielectric substance includes, for example, a thermally conductive material such as polyimide, polyurethane, polyethylene, and the like, the high frequency wave transfer part **320** may increase the heat efficiency transferred to the skin in a process in which the high frequency wave energy is transferred to the skin. Accordingly, the cover layer **250** may prevent skin damage caused by a spark caused by direct contact of the high frequency wave transfer part **320** with the skin or a rise in temperature due to an increase in resistance components.

(40) At this time, the cover layer **250** may be applied on an outer surface of the high frequency wave transfer part **320**. In this case, the high frequency wave transfer part **320** may transfer the high frequency wave energy to the skin through the cover layer **250** without directly contacting the skin.

(41) At least one high frequency wave transfer part **320** may be provided. As one embodiment, a plurality of high frequency wave transfer parts **320** may be provided. In this case, the plurality of high frequency wave transfer parts **320** may be symmetrically arranged on opposite sides with the ultrasonic wave irradiation surface **230** as a center.

(42) Specifically, the plurality of high frequency wave transfer parts **320** may be arranged in a pair of rows, and the high frequency wave transfer parts **320** of the pair of rows have the ultrasonic wave irradiation surface **230** therebetween and may be arranged side by side in the longitudinal direction (Y axis direction).

(43) As exemplarily shown in the drawing, each row may include eight high frequency wave transfer parts **320**, but the present disclosure is not limited thereto. However, for convenience of description, the following description will be made focusing on an embodiment in which eight high frequency wave transfer parts **320** are included in each row. In such a case, the eight high frequency wave transfer parts **320** included in any one of the pair of rows may be arranged symmetrically one to one with the eight high frequency wave transfer parts **320** included in another one of the pair of rows. In addition, the high frequency wave transfer parts **320** included in each row may be spaced apart from each other by a predetermined distance.

(44) The ultrasonic wave module **400** may generate and transfer ultrasonic wave energy to the skin. The ultrasonic wave module **400** may include an ultrasonic wave generator **410** and an ultrasonic wave transfer part **420**.

(45) The ultrasonic wave generator **410** may receive a control signal from the controller **600** to be described later and transfer a received control signal to the ultrasonic wave transfer part **420**. An ultrasonic wave may be, for example, high intensity focused ultrasound (HIFU).

(46) As the one embodiment, the ultrasonic wave generator **410** may be disposed inside the main body **20**. In such a case, the ultrasonic wave generator **410** may transfer control signals such as frequency, intensity, and the like input by the user to the ultrasonic wave transfer part **420** inside the tip **200**. On the other hand, as another embodiment, the ultrasonic wave generator **410** is disposed inside the housing **100**, or as yet another embodiment, provided with the ultrasonic wave transfer part **420** and placed inside the housing **100**.

(47) The ultrasonic wave transfer part **420** may receive a control signal from the ultrasonic wave generator **410** and generate ultrasonic wave energy to transfer to the skin. The ultrasonic wave transfer part **420** may provide ultrasonic wave energy to the skin through at least a portion of the ultrasonic wave irradiation surface **230**. The ultrasonic wave transfer part **420** may be disposed inside the tip body **210**. At this time, the ultrasonic wave transfer part **420** is disposed at a position facing the ultrasonic wave irradiation surface **230** inside the tip body **210**, whereby the ultrasonic wave energy emitted from the ultrasonic wave transfer part **420** penetrates the ultrasonic wave irradiation surface **230** and may be transferred to the skin being brought into contact with the ultrasonic wave irradiation surface **230**.

(48) The ultrasonic wave transfer part **420** may be disposed to be linearly movable along the ultrasonic wave irradiation surface **230**. At this time, the ultrasonic wave transfer part **420** may reciprocate and linearly move along the longitudinal direction (Y axis direction) of the ultrasonic wave irradiation surface **230** by the movement part **500** and change a position where the ultrasonic wave energy is emitted.

(49) The movement part **500** may be disposed inside the handpiece **10** to move the ultrasonic wave transfer part **420**.

(50) The movement part **500** may include a motor **510**, the guide shaft **520**, and a connection member **530**.

(51) The motor **510** may provide a driving force for moving the ultrasonic wave transfer part **420** and the connection member **530**. The motor **510** may be, for example, a linear motor. The ultrasonic wave transfer part **420** and the connection member **530** may be linearly moved by the motor.

(52) The motor **510** may be located inside the housing **100**. The motor **510** is disposed above the guide shaft **520** and the connection member **530** but may be connected to the connection member **530**, thereby moving the connection member **530**.

(53) The guide shaft **520** may guide the movement paths of the ultrasonic wave transfer part **420** and the connection member **530**. By the guide shaft **520**, the ultrasonic wave transfer part **420** and the connection member **530** may be linearly moved one way or reciprocally along the longitudinal direction (Y axis direction or -Y axis direction) of the ultrasonic wave irradiation surface **230**. In addition, the guide shaft **520** is coupled to the connection member **530** and, when the connection member **530** moves linearly by the motor **510**, may provide stability so that the connection member **530** may move without being shaken.

(54) The guide shaft **520** may be located inside the tip **200**. The guide shaft **520** is disposed between the motor **510** and the connection member **530** so that the ultrasonic wave transfer part **420** and the connection member **530** may linearly move along the ultrasonic wave irradiation surface **230**. The guide shaft **520** may have a length the same as the ultrasonic wave irradiation surface **230**.

(55) The connection member **530** may be connected to the ultrasonic wave transfer part **420** and the guide shaft **520**, thereby linearly moving the ultrasonic wave transfer part **420**. In addition, the connection member **530** may be coupled in a shape surrounding an outer surface of the ultrasonic wave transfer part **420**, thereby protecting the ultrasonic wave transfer part **420**.

(56) The connection member **530** may be disposed between the ultrasonic wave transfer part **420** and the guide shaft **520**, at the inside of the tip **200**. As the motor **510** operates, the connection member **530** linearly moves along the guide shaft **520**, and the ultrasonic wave transfer part **420** connected to the connection member **530** may also linearly move and emit ultrasonic wave energy.

(57) Whether to move/stop, a moving direction, and a moving time for the movement part **500** may be controlled on the basis of a control signal transferred from the controller **600**, which will be described in detail later.

(58) The controller **600** may control the high frequency wave module **300**, the ultrasonic wave module **400**, and the movement part **500**. At this time, the controller **600** may be implemented in a form of, for example, a circuit board mounted on a computer for controlling the handpiece **10**, a computer chip mounted on a circuit board, software embedded in a computer chip or embedded in a control computer, or the like.

(59) The controller **600** may include a user interface. The controller **600** may receive input information such as whether to generate high frequency wave energy and ultrasonic wave energy, emission time point, frequency and intensity, a pulse interval, and the like from the user. The controller **600** may control the high frequency wave module **300** and the ultrasonic wave module **400** according to input information provided by the user and control generation and emission of the high frequency wave energy and ultrasonic wave energy.

(60) The controller **600** may control a transfer method of the high frequency wave energy emitted from the high frequency wave transfer part **320** with one of bipolar and monopolar. The present disclosure is not limited thereto, and as another embodiment, a high frequency wave energy transfer method may be unipolar or multipolar.

(61) The bipolar method may be a method in which high frequency wave energy emitted from one high frequency wave transfer part **320** enters another high frequency wave transfer part **320**. The high frequency wave transfer parts **320** are at least two, and therethrough, the controller **600** may allow transfer and recovery of the high frequency wave energy to be performed.

(62) The monopolar method may be a method in which high frequency wave energy from the high frequency wave transfer part **320** passes through the patient's body and enters a ground patch. In this case, the handpiece **10** may include one ground patch. At this time, the ground patch is attached to a portion of a patient's skin surface, and the controller **600** may transfer high frequency wave energy through the high frequency wave transfer part **320**.

(63) The controller **600** may control an emission sequence of the high frequency wave energy from a plurality of high frequency wave transfer parts **320**.

(64) For example, as described above, eight high frequency wave transfer parts **320** may be provided, and for convenience of explanation, the eight high frequency wave transfer parts **320** will be referred to as a first high frequency wave transfer part **320a**, a second high frequency wave transmission part **320b**, a third high frequency wave transfer part **320c**, a fourth high frequency wave transfer part **320d**, a fifth high frequency wave transfer part **320e**, a sixth high frequency wave transfer part **320f**, a seventh high frequency wave transfer part **320g**, and an eighth high frequency wave transfer part **320h**. At this time, the first to eighth high frequency wave transfer parts **320a**, **320b**, **320c**, **320d**, **320e**, **320f**, **320g**, and **320h** may be sequentially disposed on the tip end portion **220** along the longitudinal direction (Y axis direction) of the ultrasonic wave irradiation surface **230**.

(65) As one embodiment, the controller **600** may control the high frequency wave energy to be emitted according to an arrangement order of the high frequency wave transfer parts **320**. Specifically, the controller **600** may control the high frequency wave energy to be sequentially emitted at the second to eighth high frequency wave transfer parts **320b**, **320c**, **320d**, **320e**, **320f**, **320g**, and **320h** after the first high frequency wave transfer part **320a** emits the high frequency wave energy for the first time.

(66) At this time, the controller **600** may control the emission time point of the high frequency wave energy of each high frequency wave transfer part **320**. For example, with reference to a part (a) of FIG. 7, the controller **600** may control the high frequency wave energy to be continuously emitted without a delay time Dt in between pulses of each high frequency wave transfer part **320**. More specifically, the controller **600** may control the pulse of the second high frequency wave transfer part **320b** to start at a time point when the pulse of the first high frequency wave transfer part **320a** ends. The pulses of the third to eighth high frequency wave transfer parts **320c**, **320d**, **320e**, **320f**, **320g**, and **320h** may operate the same as the pulse of the first high frequency wave transfer part **320a** and the pulse of the second high frequency wave transfer part **320b**.

(67) As another example, with reference to a part (b) of FIG. 7, the controller **600** may control a delay time to occur in between pulses of each high frequency wave transfer part **320**. More specifically, the controller **600** may control such that pulse generation is delayed for a specific time from a time point when the pulse of the first high frequency wave transfer part **320b** ends to a time point when the pulse of the second high frequency wave transfer part **320b** starts. The pulses of the third to eighth high frequency wave transfer parts **320c**, **320d**, **320e**, **320f**, **320g**, and **320h** may operate the same as the pulse of the first high frequency wave transfer part **320a** and the pulse of the second high frequency wave transfer part **320b**.

(68) As still another example, with reference to a part (c) of FIG. 7, the controller **600** may control the pulses of the high frequency wave transfer parts **320** not to have a delay time in between but to

overlap each other. More specifically, the controller **600** may control the pulse of the second high frequency wave transfer part **320b** to start before the pulse of the first high frequency wave transfer part **320a** ends so that the pulses partially overlap each other. The pulses of the third to eighth high frequency wave transfer parts **320c**, **320d**, **320e**, **320f**, **320g**, and **320h** may operate the same as the pulse of the first high frequency wave transfer part **320a** and the pulse of the second high frequency wave transfer part **320b**.

(69) As shown in FIG. 7, while each high frequency wave transfer part **320** emits high frequency wave energy, the ultrasonic wave transfer part **420** may also linearly move and allow the ultrasonic wave energy to be sequentially irradiated. At this time, the skin may be simultaneously irradiated with high frequency wave energy and ultrasonic wave energy.

(70) As another embodiment, with reference to FIG. 8, when the same high frequency wave transfer parts **320** are disposed on opposite sides with the horizontal center line **221** as a reference, respectively, the controller **600** may control the same high frequency wave transfer parts **320** to emit high frequency wave energy at the same time.

(71) At this time, when the controller **600** controls the high frequency wave energy transfer method of the high frequency wave transfer part **320** in a bipolar manner, high frequency wave energy may be emitted and recovered by the same high frequency wave transfer parts **320** themselves. For example, the high frequency wave energy emitted from the first high frequency wave transfer part **320a** may be recovered by the symmetrical first high frequency wave transfer part **320a**.

(72) The controller **600** may control the skin to be irradiated with high frequency wave energy and ultrasonic wave energy at the same time or at different times, respectively. In this case, for example, while the ultrasonic wave transfer part **420** emits ultrasonic wave energy during moving in the direction from left to right (Y axis direction) on the drawing as shown in a part (b) of FIG. 8, the controller **600** may control such that one high frequency wave transfer part emits high frequency wave energy and another high frequency wave transfer part **320** neighboring the one high frequency wave transfer part recovers the high frequency wave energy. At this time, when the high frequency wave transfer part **320** is present at an irradiation point of the ultrasonic wave energy, the high frequency wave energy and ultrasonic wave energy may be transferred to the skin at the same time, or only one of the high frequency wave energy and ultrasonic wave energy may be transferred to the skin. As another example, while the ultrasonic wave transfer part **420** emits ultrasonic wave energy during moving in the direction from left to right (Y axis direction) on the drawing as shown in a part (b) of FIG. 8, the controller **600** controls such that high frequency wave energy is emitted in the order from the eighth high frequency wave transfer part **320h** to the first high frequency wave transfer part **320a**, but the high frequency wave energy of each of the high frequency wave transfer parts is recovered by another high frequency wave transfer part **320** neighboring the one high frequency wave transfer part. Accordingly, emission orders of the ultrasonic wave energy and high frequency wave energy are opposite, so the skin may be irradiated with the high frequency wave energy and the ultrasonic wave energy at different times. At this time, when the high frequency wave transfer part **320** is present at an irradiation point of the ultrasonic wave energy, the high frequency wave energy and ultrasonic wave energy may be transferred to the skin at the same time, or only one of the high frequency wave energy and ultrasonic wave energy may be transferred to the skin.

(73) Through this, it is possible to prevent burns from occurring due to an increase in temperature of the skin irradiated with ultrasonic wave energy and high frequency wave energy, maximize the effect of treatment, and shorten the treatment time.

(74) The controller **600** may control the emission and recovery of high frequency wave energy between the same high frequency wave transfer parts **320**. For example, the high frequency wave energy emitted from the first high frequency wave transfer part **320a** is recovered with another first high frequency wave transfer part **320a**, and the high frequency wave energy emitted from the second high frequency wave transfer part **320b** may be recovered with another second high

frequency wave transfer part **320b**. The third to eighth high frequency wave transfer parts **320c**, **320d**, **320e**, **320f**, **320g**, and **320h** may operate in the same way as the first high frequency wave transfer part **320a** and the second high frequency wave transfer part **320b**.

(75) As still another embodiment, the high frequency wave transfer parts **320** may disposed to be the same on left and right sides, respectively, with a vertical center line **222** as a reference. For example, with reference to FIG. **9**, the first to fourth high frequency wave transfer parts **320a**, **320b**, **320c**, and **320d**, each of which consists in a pair, may be disposed to be equal on the left and right sides with the vertical center line **222** as the reference. In this case, the controller **600** may control such that the same high frequency wave transfer parts **320** emit high frequency wave energy having the same frequency and energy.

(76) In addition, when the ultrasonic wave energy is emitted while the ultrasonic wave transfer part **420** moves in the direction from left to right in FIG. **9** (Y axis direction), the same high frequency wave transfer parts **320** each emit high frequency wave energy. At this time, the controller **600** may control such that the high frequency wave transfer parts **320** located on a rear side row output high frequency wave energy prior to ultrasonic wave energy. On the other hand, when the ultrasonic wave transfer part **420** is individually located in each high frequency wave transfer part **320**, the controller **600** may control high frequency wave energy and ultrasonic wave energy to be irradiated at the same time.

(77) The controller **600** may group and control a plurality of high frequency wave transfer parts **320**. The controller **600** may control an operation of each group and may also individually control the operation of each of the high frequency wave transfer parts **320** in each group. For example, with reference to FIG. **10**, it may be divided such that the first to fourth high frequency wave transfer parts **320a**, **320b**, **320c**, and **320d** are a first group G1, and the fifth to eighth high frequency wave transfer parts **320e**, **320f**, **320g**, and **320h** are a second group G2. In this case, with a direction, which faces the right from the left, as a reference, the high frequency wave transfer parts **320** may be arranged and grouped to be the same each other on opposite sides. The controller **600** may allow the first group to emit high frequency wave energy or only the first high frequency wave transfer parts **320a** of the first group to emit high frequency wave energy.

(78) Although the controller **600** controls the plurality of high frequency wave transfer parts **320** by dividing the same into two groups, this is only one embodiment of the present disclosure, and the controller **600** may allow the groups of the high frequency wave transfer parts **320** to be configured in various ways to be controlled.

(79) As described above, the handpiece **10** according to the embodiments of the present disclosure includes: a housing **100**; a tip **200** disposed at one end of the housing **100**; a plurality of high frequency wave transfer parts **320** disposed on the tip **200** and configured to transfer high frequency wave energy to skin in a pulsed manner; an ultrasonic wave transfer part **420** disposed on the tip **200**, but spaced apart from the high frequency wave transfer parts **320**, and configured to transfer generated ultrasonic wave energy through an ultrasonic wave irradiation surface **230** provided on the tip **200** to the skin; and a movement part **500** disposed inside the housing **100** or the tip **200** and configured to move the ultrasonic wave transfer part **420** along the ultrasonic wave irradiation surface **230**. Accordingly, the handpiece **10** may allow the high frequency wave energy and ultrasonic wave energy to be transferred to the skin with one handpiece **10** without continuous movement of the handpiece **10**.

(80) Through this, the skin is treated and improved by maximizing the thermal effect of the high frequency wave energy and ultrasonic wave energy transferred to the skin, and damage to the skin may not be applied even when the skin is irradiated with the high frequency energy and the ultrasonic energy at the same time.

(81) The above description of the present disclosure is for illustrative purposes, and those skilled in the art will be able to understand that it may be easily modified into other specific forms without changing the technical spirit or essential features of the present disclosure. Therefore, the

embodiments described above should be understood as illustrative in all respects and not limiting. For example, each component described as a single type may be implemented as being distributed, and similarly, components described as having been distributed may be implemented in a combined form.

(82) The scope of the present disclosure is indicated by the following claims, and all changes or modifications derived from the meaning and scope of the claims and equivalent concepts should be interpreted as being included in the scope of the present disclosure.

Claims

1. A high frequency wave and ultrasonic wave fusion treatment device, the device comprising: a housing; a tip disposed at one end of the housing; a plurality of high frequency wave transfer parts disposed on the tip and configured to transfer high frequency wave energy to skin in a pulsed manner; an ultrasonic wave transfer part disposed on the tip, but spaced apart from the high frequency wave transfer parts, and configured to transfer generated ultrasonic wave energy through an ultrasonic wave irradiation surface provided on the tip to the skin, the ultrasonic wave irradiation surface having an elongated shape elongated in an extension direction; and a movement part disposed inside the housing or the tip and configured to move the ultrasonic wave transfer part along the extension direction of the ultrasonic wave irradiation surface; and a controller configured to control at least one of the high frequency wave transfer parts, the ultrasonic wave transfer part, and the movement part, wherein the controller is configured to control an emission sequence of the high frequency wave energy of each of the high frequency wave transfer parts based on a movement direction of the ultrasonic wave transfer part in the extension direction.
2. The device of claim 1, wherein the plurality of high frequency wave transfer parts is arranged symmetrically on opposite sides with the ultrasonic wave irradiation surface as a center.
3. The device of claim 1, wherein the high frequency wave transfer parts are provided with one cover layer disposed on a surface of one side thereof facing the skin, wherein the one cover layer includes a thermally conductive material selected from a group consisting of polyimide, polyurethane, and polyethylene.
4. The device of claim 1, wherein the controller is configured to control the high frequency wave transfer parts and the ultrasonic wave transfer part so that the high frequency wave energy and the ultrasonic wave energy are emitted at the same time or at different times, respectively.
5. The device of claim 1, wherein the controller is configured to control the emission sequence and an emission time point of the high frequency wave energy of each of the high frequency wave transfer parts on the basis of an arrangement order of the plurality of high frequency wave transfer parts.
6. The device of claim 5, wherein the controller is configured to control at least one pair of the high frequency wave transfer parts disposed symmetrically with each other with respect to the ultrasonic wave irradiation surface among the plurality of high frequency wave transfer parts to simultaneously emit high frequency wave energy.
7. The device of claim 5, wherein the controller is configured to control a movement distance and a movement time of the movement part such that the emission sequence and emission time point of the high frequency wave energy correspond to the movement distance and the movement time of the movement part according to a predetermined correspondence relationship.
8. The device of claim 7, wherein the controller is configured to control movement of the movement part so that the ultrasonic wave transfer part emits ultrasonic wave energy at a position staggered with the high frequency wave transfer part emitting high frequency wave energy among the plurality of high frequency wave transfer parts.
9. The device of claim 1, wherein the controller is configured to group the plurality of high frequency wave transfer parts into a plurality of groups and control emission of the high frequency

wave energy for each group.

10. The device of claim 9, wherein the controller is configured to control an emission sequence and an emission time point of the high frequency wave energy on the basis of an arrangement order of the plurality of groups.

11. The device of claim 1, wherein the high frequency wave transfer parts are arranged at both sides of the elongated shape and include a first pair of high frequency wave transfer parts from among the plurality of the high frequency wave transfer parts located adjacent to one end of the elongated shape and a second pair of high frequency wave transfer parts from among the plurality of the high frequency wave transfer parts located adjacent to an opposite end of the elongated shape, wherein the controller is configured to control such that the high frequency wave energy is emitted in an order of a direction either from the first pair of high frequency wave transfer parts toward the second pair of high frequency wave transfer parts or from the second pair of high frequency wave transfer parts toward the first pair of high frequency wave transfer parts, based on the movement direction of the ultrasonic wave transfer part in the extension direction of the elongated shape.
