

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404067
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hammersten; Noah

Expandable bottle

Abstract

Collapsible bottles and methods of use are disclosed in which the bottle is fabricated, collapsed at a body section including circular or spiral folds, provided with a condensed or concentrated substance, and sealed. Subsequently, the bottle may be unsealed, expanded, provided with a liquid, sealed, and mixed to bring the substance to a desired concentration or consistency.

Inventors:	Hammersten; Noah (Studio City, CA)
Applicant:	Hammersten; Noah (Studio City, CA)
Family ID:	88700371
Appl. No.:	18/316478
Filed:	May 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230365287 A1	Nov. 16, 2023

Related U.S. Application Data

us-provisional-application US 63341349 20220512

Publication Classification

Int. Cl.: B65D1/02 (20060101); B65D21/02 (20060101); B65D41/04 (20060101); B65D43/16 (20060101)

U.S. Cl.:

CPC **B65D1/0292** (20130101); **B65D1/0246** (20130101); **B65D1/0276** (20130101);
B65D21/0213 (20130101); **B65D41/04** (20130101); **B65D43/169** (20130101);
B65D2543/00092 (20130101)

Field of Classification Search

CPC: B65D (21/0234); B65D (21/0233); B65D (21/086); B65D (1/0292); B65D (1/0207);
B65D (1/0246); B65D (2543/00092); B65D (2543/00972); B65D (2501/0018); Y10S
(215/90); Y10S (220/907); A45F (2003/205); A45F (3/20); B29C (49/4283)

USPC: 215/382; 215/10; 215/900; 220/666; 220/8

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2886084	12/1958	Davison	220/666	B65D 21/086
5209372	12/1992	Norwood	220/666	B65D 1/0292
5348173	12/1993	Norwood	N/A	N/A
5584413	12/1995	Jung	220/666	B65D 1/0292
2017/0320611	12/2016	Shen	N/A	N/A
2018/0155209	12/2017	Cohen	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2765556	12/1998	FR	N/A
2015127248	12/2014	JP	N/A
9415846	12/1993	WO	N/A
2015076362	12/2014	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Nov. 2, 2023. cited by applicant

Written Opinion of the International Searching Authority dated Nov. 2, 2023. cited by applicant

Primary Examiner: Chu; King M

Attorney, Agent or Firm: Dergosits & Noah LLP

Background/Summary

CROSS-REFERENCE TO RELATED CASES (1) This application claims priority to U.S. Provisional Patent Application No. 63/341,349, entitled “Expandable Bottle,” filed on May 12, 2022, which is hereby incorporated by reference.

BACKGROUND

(1) Typical bottled products include a volume of a liquid, e.g., water. This liquid is often relatively heavy. In addition, the volume adds a spatial requirement to shipping, storage, and display

considerations.

(2) Thus, a bottle is needed that provides for reduced weight and space considerations.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The embodiments are illustrated by way of example and not limitation in the accompanying drawings, in which like references indicate similar elements, and in which.

(2) FIG. 1A is side view illustrating an embodiment of a collapsible bottle;

(3) FIG. 1B is a side view illustrating the embodiment of FIG. 1 collapsed;

(4) FIG. 1C is a side view illustrating the embodiment of FIG. 1 stacked;

(5) FIG. 2A is a side view illustrating a use case for the embodiment of FIG. 1 collapsed;

(6) FIG. 2B is a side view illustrating the use case for the embodiment of FIG. 1 expanded;

(7) FIG. 2C is a side view illustrating the use case for the embodiment of FIG. 1 expanded and filled;

(8) FIG. 2D is a side view illustrating the use case for the embodiment of FIG. 1 expanded, filled, and mixed;

(9) FIG. 3A is a side view illustrating an embodiment of a collapsible bottle;

(10) FIG. 3B is a side view illustrating the embodiment of FIG. 3A collapsed;

(11) FIG. 3C is a side view illustrating a detail of an embodiment;

(12) FIG. 3D is a side view illustrating the detail of FIG. 3C;

(13) FIG. 4A is a side view illustrating an embodiment of a collapsible bottle;

(14) FIG. 4B is a side view illustrating the embodiment of FIG. 4A partially expanded;

(15) FIG. 4C is a side view illustrating the embodiment of FIG. 4A stacked

(16) FIG. 5A is a perspective view is a side view illustrating an embodiment of a collapsible bottle in a collapsed state;

(17) FIG. 5B is a side view illustrating the embodiment of a collapsible bottle of FIG. 5A in an expanded state;

(18) FIG. 6A-FIG. 6F are side views illustrating steps in an embodiment of a method of use of an embodiment of a collapsible bottle;

(19) FIG. 7A-FIG. 7H are side views illustrating steps in an embodiment of a method of use of an embodiment of a collapsible bottle;

(20) FIG. 8A is a side view illustrating an embodiment of a collapsible bottle;

(21) FIG. 8B is a side view illustrating an embodiment of a collapsible bottle;

(22) FIG. 9A is a perspective view is a side view illustrating an embodiment of a collapsible bottle in a collapsed state;

(23) FIG. 9B is a side view illustrating the embodiment of a collapsible bottle of FIG. 9A in a partially expanded state; and

(24) FIG. 10 is a side view illustrating the embodiment of a collapsible bottle of FIG. 9A.

DETAILED DESCRIPTION

(25) Embodiments described within disclose a vehicle for the sale of single-serving dehydrated foodstuffs in an expandable bottle. The foodstuff may include, e.g., baby formula, protein powder, powdered meal replacement, or the like. Embodiments may also be vehicles for containing condensed or dehydrated materials for later dilution or rehydration, including both foodstuffs and non-foodstuffs.

(26) In a use case, an embodiment is distributed or sold with the material added and the bottle collapsed. In such an embodiment, a consumer may purchase the bottle individually or in bulk. When the ready to consume the product, the consumer opens the bottle, expands it, fills it with water or other liquid, and mixes the material and the liquid.

(27) The expandability allows for the convenience of a liquid bottled product with the shelf-space, weight, and cost savings more similar to a dry product bought in a tub or bag.

(28) Embodiments may also be stackable.

(29) In an embodiment, the walls of the bottle may be bi-stable so the bottle remains in either of a fully collapsed or a fully extended position. For example, regarding the shape of the folds, in an embodiment, like a measuring tape which will happily coil, or when straightened remain rigid, the body of the bottle will remain in a collapsed or extended position, with force required to transition between. In a position mid-way between collapsed and extended, the outer edge of each fold will be stretched, or otherwise deformed, slightly, creating an over-center condition. In other words, when transitioning from collapsed to extended, as the neck is moved away from the bottom, for each fold, an outer apex of a fold follows an arc. Initially, the apex is relatively closer to a center axis of the bottle and, as the bottle is expanded, the apex arcs up and away from the center axis. At a mid-way point in the expansion, the arc of the apex is furthest from the bottle center axis. With further expansion, the apex travels further along the arc, becoming closer to the center axis along the way. In an embodiment, when expanding, for the apex of each fold (both circular and spiral) to arc away from the center axis requires a slight stretch of the bottle material. Similarly, compression requires a stretch of the bottle material for the apex to make the return arc. Thus, without effort being exerted to expand or compress the bottle and stretch the material in the process, the material will not, on its own or by the force of gravity, make the transition to the other state. Thus, the need to stretch the material to change states results in the bottle being bi-stable.

(30) In an embodiment with a spiral fold, when expanding or compressing the bottle, the top section of the bottle twists relative to the bottom section. When the spiral is oriented with the spiral in a left-hand orientation (as shown in FIG. 5B), the top section rotates counter clockwise (viewed from above) when expanding to feel like the opening of a normal threaded cap.

(31) In an embodiment, the walls of the bottle may be expandable, but after being expanded, are not readily collapsible. In an embodiment, the body of the bottle may be configured to assume the extended position by default, with force required to compress the folds of the body, much that that required to compress a spring. The bottle may then be held in the collapsed position by vacuum when sealed. When the seal is breached, the folds would spring open and the bottle would return to the extended position.

(32) In an embodiment, the wall of the body of the bottle, which contains the folds that provide for the expansion, For example, may have a thickness that is uniform at all locations of the fold, e.g., a spiral or pleat.

(33) In an embodiment, a mesh or filter may be included in a bottle cap. In an embodiment, an arm may be attached to the cap to be inserted into the bottle and used in mixing the ingredients within the bottle.

(34) In an embodiment, because the bottle is holding dry goods instead of water, the material from which the bottle is constructed is less robust than if the bottle were to be sold with the volume of liquid that will eventually be added to the dry goods. For example, less robust bottles may be more biodegradable and constructed of, e.g., bio-plastics (PHA), corn or mycelium plastic alternatives, etc.

(35) Generally, embodiments are directed to collapsible bottles that may be or are provided with a dry food sealed within, and that may be expanded to allow the dry food within to be rehydrated or otherwise diluted. In addition, embodiments are directed to collapsible bottles that may be or are provided with a concentrated substance sealed within, and that may be expanded to allow the substance to be rehydrated or otherwise diluted.

(36) FIG. 1A is side view illustrating an embodiment of a collapsible bottle **10**. In FIG. 1A, collapsible bottle **10** includes a cap **12** sealing an opening (not shown) within a neck **35** (FIG. 3A), an upper section **14**, an expandible body **16** (shown expanded), a base **18**, and a punt **20**. Punt **20** is configured to accommodate cap **12** and upper section **14**. As shown, expandable body **16** is

expandable in an accordion or folded fashion with each fold being a continuous spiral from base **18** to next **14**. In embodiment, expandable body **16** may be expandable in an accordion or folded fashion in which each fold makes a single circle (see body **36** of FIGS. **3A** and **3B**). In an embodiment, a spiral fold may be selected for improved mixing, with the continuity of the spiral, which provides a single, continuous groove from bottle bottom to top, promoting fluid motion more than a circular fold, which may function something like a series of dams or fluid speed bumps.

(37) FIG. **1B** is a side view illustrating the embodiment of FIG. **1** collapsed. In FIG. **1B**, expandible body **16** is shown collapsed.

(38) FIG. **1C** is a side view illustrating the embodiment of FIG. **1** stacked. In FIG. **1C**, multiple collapsed bottles **10a** . . . **10c** are shown stacked, with caps **12b**, **12c** received within punts **20a**, **20b**. In an embodiment, punts **20** and caps **12** may be configured such that a press-fit is formed between them when stacked as shown in FIG. **1C**. Such a press-fit may be desired for maintaining the stack during loading, shipment, storage, and display.

(39) FIG. **2A** is a side view illustrating a use case for collapsible bottle **10**. In FIG. **2A** bottle **10** is provided with a dehydrated or condensed food or substance **22**. In FIG. **2B**, body section **16** has been expanded, e.g., by removing cap **12**, or unscrewing it enough to break the seal, and pulling upper section **14** away from bottom **18**. In FIG. **2C**, a liquid **24**, e.g., water, has been added to body section **16**. In FIG. **2D**, condensed food or substance **22** and liquid **24** have been mixed to create a re-hydrated or diluted food or substance **26**.

(40) FIG. **3A** is a side view illustrating an embodiment of a collapsible bottle **30**. In FIG. **3A**, collapsible bottle **30** includes a cap **32** about a neck **35**, an upper section **34**, an expandible body **36** (shown expanded), a base **38**, and a punt **40**. In the embodiment, punt **40** is configured to accommodate upper section **34**. Neck **35** includes threads **42**. As shown, expandable body **36** is expandable in an accordion or folded fashion with each fold making single circle about body **36**, but body **36** may be expandable in the spiral fashion shown in FIG. **1A** as well. In embodiments, punt **40** may be configured to accommodate cap **32** and upper section **34**.

(41) FIG. **3B** is a side view illustrating the embodiment of FIG. **3A** collapsed and with cap **32** opened to allow access to an opening **50**. In the configuration of FIG. **3B**, and with cap **32** removed, or with just arm **49** removed and punt **40** configured to receive cap **32**, bottle **30** may be stacked to save space, similar to the stacking shown in FIG. **1C**.

(42) FIG. **3C** is a side view illustrating detail of cap **32**. Cap **32** includes threads **44**, which cooperate with threads **42** to attach cap **32** to neck **35**. Cap **32** includes a lip **45** above threads **44**. A press-fit or partial press-fit of lip **45** within cap **32** at inner diameter **46** helps keep cap **32** closed. Cap **32** includes a flange (or edge) **47** that defines opening **50**. An outer diameter **48** of a post **52** of cap **32** is received within flange **47** to also help keep cap **32** closed. In an embodiment, cap **32** may include an arm **49**. Arm **49** may be leveraged to cause cap **32** to pivot about a hinge **54** and withdraw post **52** from opening **50**. With cap **32** detached from threads **42**, arm **49** may be used to stir the contents the bottle.

(43) FIG. **3D** is a side view illustrating the detail of FIG. **3C** in an open configuration that allows access to opening **50**.

(44) FIG. **4A** is a side view illustrating an embodiment of a collapsible bottle **60**. In FIG. **4A**, collapsible bottle **60** includes an upper section **64**, a neck **65**, an expandible body **66** (shown collapsed), a base **68**, and a punt **70**. Punt **70** is configured to accommodate a cap **62**, an insert **76**, and neck **65** when upper section **64** is in a retracted position (FIG. **4A**). Neck **65** is received within insert **76**, which includes threads **78**. Threads **74** of cap **62** cooperate with threads **78** to seal bottle **60**. In some embodiments, insert **76** may include a filter or mesh **80**. In other embodiments, the area shown occupied by mesh **80** may be solid or open. In some embodiments, threads **78** may be formed directly into neck **65** with insert **76** not extending past the outside diameter of neck **65**. In an embodiment, insert **76**, threads **78**, and mesh **80** may be one unit and welded into position on

neck **65**. In an embodiment, threads **78** may be provided in on neck **65** conventionally, and mesh **80** welded in place, without insert **76**.

(45) In FIG. **4A** bottle **60** is provided with a dehydrated or condensed food or substance **72** to be rehydrated or diluted as discussed with regard to FIGS. **2A** . . . **2D**. As before, expandable body **66** may be expandable in an accordion or folded fashion with each fold making single circle about body **36**, or in the spiral fashion shown in FIG. **1A** as well.

(46) FIG. **4B** is a side view illustrating the embodiment of FIG. **4A** partially expanded such that upper section **64** is popped up, or extended. The ability of upper section **64** to pop, by itself and with body **66** remaining compressed, between a collapsed or retracted state (FIG. **4A**) and an expanded or extended state (FIG. **4C**) allows for bottle **60** to stack compactly, as shown in FIG. **4C**. It is envisioned that bottle **60** may be used efficiently for relatively small servings of foodstuffs.

(47) FIG. **5A** is a perspective view is a side view illustrating an embodiment **100** of a collapsible bottle in a collapsed state. In FIG. **5A**, collapsible bottle **100** includes a cap **112**, an upper section **114** (shown retracted), an expandible body **116** (shown compressed), a base **118**, and a punt **120** (FIG. **6A**). Body **116** is compressed between upper section **114** and base **118**. Punt **120** is configured to accommodate cap **112** and neck **145** (FIG. **6A**) when upper section **114** is retracted. As shown, expandable body **116** is expandable in an accordion or folded fashion with each fold being a continuous spiral from base **118** to upper section **114**. Spiral **117** indicates the longitudinal distance gained by one complete spiral in the compressed state. In an embodiment, expandable body **116** may be expandable in an accordion or folded fashion in which each fold makes a single circle (see body **136** of FIG. **8**).

(48) FIG. **5B** is a side view illustrating the embodiment of a collapsible bottle of FIG. **5A** in an expanded state. In the expanded state, each spiral **117** has been expanded and upper section **114** extended as well from being concave in FIG. **5A** to convex in FIG. **5B**.

(49) FIG. **6A**-FIG. **6F** are side views illustrating steps in an embodiment of a method of use of an embodiment of a collapsible bottle. FIG. **6A** further illustrates that cap **112** includes threads **144**, which cooperate with threads **142** to attach cap **112** to neck **65** and seal opening **150**.

(50) In FIG. **6A**, in a first step of a method, bottle **100** and cap **112** are manufactured. In FIG. **6B**, upper section **114** and body **116** are compressed, separately or at the same time. In FIG. **6C**, compressed bottle **100** is filled with a substance **122**, e.g., a dehydrated or condensed material, such as a foodstuff. In FIG. **6D**, bottle **100** is capped. In FIG. **6E**, bottle **100** may receive a label **123**. And in FIG. **6F**, after multiple bottles have undergone the steps of FIG. **6A**-FIG. **6E**, the bottles may be stacked, with cap **112** being received within punt **120**, e.g., for packaging, shipment, and/or display. In an embodiment, it is envisioned that the steps illustrated by FIG. **6A**-FIG. **6F** would be performed by a manufacturer or other commercial entity.

(51) In an embodiment, the volume of compressed bottle **100** (FIG. **6B**) and the volume of expanded bottle **100** (FIG. **6A**) may be both be predetermined volumes such that, for a particular substance **112**, when compressed bottle **100** is filled with the substance, and the bottle **100** is subsequently expanded, filling expanded bottle **100** with a designated fluid brings the particular substance **112** to a predetermined concentration or consistency.

(52) FIG. **7A**-FIG. **7H** are side views illustrating steps in an embodiment of a method of use of an embodiment of a collapsible bottle. In FIG. **7A**, a bottle **100** is obtained that has completed the method of FIG. **6A**-FIG. **6F**. In FIG. **7B**, body section **116** has been expanded, e.g., by removing cap **112**, or unscrewing it enough to break the seal, and pulling upper section **114** away from bottom **118**. In FIG. **7C**, bottle **100** is uncapped and both upper section **114** and body **116** are fully expanded. In FIG. **7D**, a liquid **124** is added, e.g., to the fill line **146**. In FIG. **7E**, bottle **100** is re-capped and shaken to mix. In FIG. **7F**, the mixing is shown to result in a reconstituted substance **126**. In FIG. **7G**, reconstituted substance **126** is used, e.g., consumed or applied. And in FIG. **7H**, empty bottle may be recycled or re-used. In an embodiment, it is envisioned that the steps illustrated by FIG. **7A**-FIG. **7H** would be performed by a manufacturer or other commercial entity.

(53) FIG. 8A is a side view illustrating an embodiment of a collapsible bottle **130** including an upper section **114**, a body **136**, and a bottom section **138**. Body **136** includes a number of folds **137**, each fold **137** making a single circle about body **136**. Upper section **114** is the same for both bottle **100** and bottle **130**.

(54) FIG. 8B is a side view illustrating an embodiment of collapsible bottle **100**, which, when compared to bottle **130** of FIG. 8A, illustrates the similarity of upper sections **114** and the differences between bodies **116**, **136**, and between bottom section **118**, **138**.

(55) FIG. 9A is a perspective view is a side view illustrating bottle **100** in a collapsed state. FIG. 9B is a side view illustrating bottle **100** in a partially expanded state. FIG. 9A and FIG. 9B illustrate that flexible section **134** of upper section **114** may be pulled and extended with respect to the lower outer perimeter of upper section **114** to go from the concave orientation of FIG. 9A to the convex orientation of FIG. 9B.

(56) FIG. 10 is a side view illustrating the embodiment of collapsible bottle **100** of FIG. 9A. In FIG. 10, cap **112** is shown to include an undercut **132**, which facilitates grasping cap **112** and pulling to expand bottle **100**.

(57) The previous description is provided to enable any person skilled in the art to practice the various aspects described herein. In the embodiments, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but are to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” Unless specifically stated otherwise, the term “some” refers to one or more. Pronouns in the masculine (e.g., his) include the feminine and neuter gender (e.g., her and its) and vice versa. Headings and subheadings, if any, are used for convenience only and do not limit the subject disclosure.

(58) A phrase such as an “aspect” does not imply that such aspect is essential to the subject technology or that such aspect applies to all configurations of the subject technology. A disclosure relating to an aspect may apply to all configurations, or one or more configurations. A phrase such as an aspect may refer to one or more aspects and vice versa. A phrase such as a “configuration” does not imply that such configuration is essential to the subject technology or that such configuration applies to all configurations of the subject technology. A disclosure relating to a configuration may apply to all configurations, or one or more configurations. A phrase such as a configuration may refer to one or more configurations and vice versa.

(59) All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims.

Claims

1. A bottle comprising: a pliant material; a top section including a first opening; a bottom section; and a body including at least one fold completely traversing a perimeter of the bottle and including a first side and a second side and an angle between the first and second sides, wherein: the bottle has a compressed state in which the angle is relatively smaller and an expanded state in which the angle is relatively larger; when the bottle is in the compressed state the at least one fold is exposed; and when the bottle is in the compressed state, a first perimeter of the top section and a second perimeter of the bottom section are greater than a maximum perimeter of the exposed at least one fold such that the first perimeter and second perimeter may be grasped to pull the bottle from the compressed state to the expanded state.

2. The bottle of claim 1, wherein either: the at least one fold includes a plurality of folds and each fold traverses the perimeter of the bottle from an initial point such that as the fold is followed about the perimeter of the bottle the fold returns to the initial point; or the at least one fold includes a single spiral that traverses the perimeter of the bottle a plurality of times and, as the spiral is followed about the perimeter of the bottle, the longitudinal position of the spiral changes.
3. The bottle of claim 1, wherein the bottom section is configured to receive the top section when the top section is fitted with a cap such that a first bottle may be stacked atop a second bottle identical to the first.
4. The bottle of claim 3, wherein the bottom section and cap are configured such that there is a first press fit between the bottom section and the cap when the top section is received by the bottom section.
5. The bottle of claim 3 in the compressed state, further including a substance, wherein the substance is brought to a predetermined concentration when the bottle is expanded to the expanded state and filled with a liquid.
6. The bottle of claim 3, wherein: the top section includes the first opening; and a perimeter of the cap increases as the cap extends away from the body such that the increasing perimeter facilitates grasping the cap to pull the bottle from the compressed state to the expanded state.
7. The bottle of claim 1, further comprising a cap including: a second opening with an inner edge; a first flange around the second opening; a lid including: an inner edge and a post having an outer edge; and a hinge connecting the cap and the lid, wherein: the second opening is sealed by a second press fit between the inner edge and the post when the lid pivots about the hinge and the post enters the second opening; and a third press fit between the first flange and the inner edge is formed when the lid pivots about the hinge and the post enters the second opening, the third press fit assisting in maintaining the post within the second opening.
8. The bottle of claim 1, wherein the top section includes a flexible cone section between the first opening and a periphery of the top section, the flexible cone section flexing between a first retracted position relatively toward the body and an extended position relatively away from the body, the retracted position and the extended position being possible regardless of whether the bottle is in the compressed state or expanded state.
9. The bottle of claim 1, further comprising a filter configured to be received within the first opening.
10. The bottle of claim 9, wherein the filter is provided within an insert configured to receive a neck of the bottle, the insert including threads configured to cooperate with threads of a cap.
11. The bottle of claim 1, wherein the at least one fold is bi-stable such that force is required to change the bottle from the compressed state to the expanded state, or from the expanded state to the compressed state, and not required to maintain the bottle in either the compressed state or the expanded state.
12. The bottle of claim 11, wherein force required to change the bottle from the compressed state to the expanded state, or from the expanded state to the compressed state, is required to deform the pliant material as an apex of the at least one fold moves away from a center axis of the bottle.
13. A method of using a collapsible bottle comprising: obtaining the collapsible bottle in a compressed state and provided with a substance, the collapsible bottle including: a pliant material, a top section including a first opening, a bottom section, a cap configured to seal the first opening, and a body including at least one fold completely traversing a perimeter of the bottle and including a first side and a second side and an angle between the first and second sides, wherein: the bottle has the compressed state in which the angle is relatively smaller and an expanded state in which the angle is relatively larger; when the bottle is in the compressed state the at least one fold is exposed; and when the bottle is in the compressed state, a first perimeter of the top section and a second perimeter of the bottom section are greater than a maximum perimeter of the exposed at least one fold such that the first perimeter and second perimeter may be grasped to pull the bottle from the

compressed state to the expanded state: expanding the collapsible bottle to the expanded state; adding a liquid to the expanded collapsible bottle; and mixing the liquid with the substance to dilute the substance a pre-determined amount or to obtain a pre-determined consistency.

14. The method of claim 13, wherein the mixing the liquid with the compressed substance to dilute the compressed substance a pre-determined amount or to obtain a pre-determined consistency further comprises: moving the collapsible bottle about an axis parallel to a center axis of the bottle, the movement causing at least some of the liquid to move about the center axis and within a groove defined by the at least one fold.

15. The method of claim 14, wherein the at least one fold includes a spiral that traverses the perimeter of the bottle a plurality of times such that the groove is continuous, the moving the collapsible bottle about an axis parallel to a center axis of the bottle further causing at least some of the liquid to have a component of movement along the center axis.

16. A method of using a first collapsible bottle comprising: obtaining the first collapsible bottle in an expanded state; the first collapsible bottle including: a pliant material, a top section including a first opening, a bottom section, a cap configured to seal the first opening, and a body including at least one fold completely traversing a perimeter of the bottle and including a first side and a second side and an angle between the first and second sides, wherein: the bottle has the compressed state in which the angle is relatively smaller and an expanded state in which the angle is relatively larger; when the bottle is in the compressed state the at least one fold is exposed; and when the bottle is in the compressed state, a first perimeter of the top section and a second perimeter of the bottom section are greater than a maximum perimeter of the exposed at least one fold such that the first perimeter and second perimeter may be grasped to pull the bottle from the compressed state to the expanded state: compressing the first collapsible bottle to the compressed state; adding a substance to the first compressed collapsible bottle; and, after the addition, capping the first compressed collapsible bottle.

17. The method of claim 16, further comprising: stacking a second capped compressed collapsible bottle atop the first capped compressed collapsible bottle.

18. The method of claim 17, wherein a press fit is created between the cap of the first capped compressed collapsible bottle and a bottom of the second capped compressed collapsible bottle.

19. The method of claim 16, further comprising: flexing a flexible cone surrounding the first opening from an extended position to a retracted position; and stacking a second capped compressed collapsible bottle atop the first capped compressed collapsible bottle, wherein a height of the stacked bottles is less with the flexible cone in the retracted position than possible when the flexible cone remains in the extended position.
