

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405505
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hsiang; Jui-Chieh et al.

Display device

Abstract

A display device including a first substrate, a second substrate, a first electrode, a second electrode and a display medium layer is provided. The first electrode entirely covers a surface of the first substrate and is provided with a first voltage input terminal, a second voltage input terminal and a third voltage input terminal. The first voltage input terminal and the second voltage input terminal are respectively located on two opposite side edges of the first electrode. The third voltage input terminal is located between the first voltage input terminal and the second voltage input terminal. The second electrode entirely covers a surface of the second substrate and is provided with a fourth voltage input terminal and a fifth voltage input terminal. The fourth voltage input terminal and the fifth voltage input terminal are respectively located on two opposite side edges of the second electrode.

Inventors: Hsiang; Jui-Chieh (New Taipei, TW), Chen; Chih-Chiang (New Taipei, TW)

Applicant: Acer Incorporated (New Taipei, TW)

Family ID: 88513032

Assignee: Acer Incorporated (New Taipei, TW)

Appl. No.: 17/964858

Filed: October 12, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230350265 A1	Nov. 02, 2023

Foreign Application Priority Data

TW	111116363	Apr. 29, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: G02F1/1676 (20190101); G02F1/1343 (20060101); G02F1/16756 (20190101);
G02F1/1685 (20190101)

U.S. Cl.:

CPC G02F1/1676 (20190101); G02F1/134345 (20210101); G02F1/16756 (20190101);
G02F1/1685 (20190101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6108067	12/1999	Okamoto	349/149	G02F 1/133382
6812911	12/2003	Makishima	345/92	G09G 3/3655
8692971	12/2013	Chiu	349/200	G02B 30/27
10048547	12/2017	Ho	N/A	G02F 1/133707
10866465	12/2019	Pan	N/A	G02F 1/13439
11087644	12/2020	Paolini, Jr. et al.	N/A	N/A
11366346	12/2021	Huang	N/A	G02F 1/1343
2005/0088582	12/2004	Park	349/43	G02F 1/134309
2007/0052909	12/2006	Chou	349/155	G02F 1/1339
2009/0015737	12/2008	Jung	349/200	G02B 30/28
2009/0185125	12/2008	Hida	349/141	G02F 1/134363
2010/0201900	12/2009	Lee	349/40	G02F 1/13452
2011/0102698	12/2010	Wang	349/54	G02F 1/13338
2011/0317086	12/2010	Wang	349/73	G02F 1/1362
2015/0002779	12/2014	Joten	349/59	G02F 1/133308
2019/0278146	12/2018	He	N/A	G02F 1/136286
2021/0223619	12/2020	Zhou	N/A	G02F 1/13338

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
113759630	12/2020	CN	N/A
699605	12/2019	TW	N/A

Primary Examiner: Tzeng; Fred

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of Taiwan application serial no. 111116363, filed on Apr. 29, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Field of the Disclosure

(2) The present disclosure relates to a display device, and more particularly, to a display device having a radiation gradient grayscale display effect.

DESCRIPTION OF RELATED ART

(3) A bistable display is a display that uses a bistable medium for display, and the technologies for achieving bistable display include electronic ink (E-Ink) display, cholesteric liquid crystal display (ChLCD), electro-phoretic display (EPD), electrowetting display (EWD) or quick response-liquid powder display (QR-LPD).

(4) Compared with mainstream displays (such as liquid crystal displays or light-emitting diode displays), bistable display has lower operating power consumption and better flexibility. In addition to being suitable for applications in portable electronic products (such as e-paper or e-book), bistable display may also be applied to the casing of various electronic products or car body to achieve the effect of changing visual appearance. However, limited by the existing driving method, the bistable display cannot produce the radiation gradient grayscale display effect.

SUMMARY OF THE DISCLOSURE

(5) The present disclosure provides a display device that may achieve a radiation gradient grayscale display effect.

(6) A display device of the disclosure includes a first substrate, a second substrate, a first electrode, a second electrode and a display medium layer. The first substrate and the second substrate are disposed opposite to each other. The first electrode entirely covers a surface of the first substrate and is provided with a first voltage input terminal, a second voltage input terminal and a third voltage input terminal. The first voltage input terminal and the second voltage input terminal are respectively located on two opposite side edges of the first electrode. The third voltage input terminal is located between the first voltage input terminal and the second voltage input terminal. The second electrode entirely covers a surface of the second substrate and is provided with a fourth voltage input terminal and a fifth voltage input terminal. The fourth voltage input terminal and the fifth voltage input terminal are respectively located on two opposite side edges of the second electrode. The display medium layer is disposed between the first electrode and the second electrode.

(7) In an embodiment of the present disclosure, the first voltage input terminal, the second voltage input terminal, the third voltage input terminal, the fourth voltage input terminal and the fifth voltage input terminal of the display device are respectively used for inputting the first voltage, the second voltage, the third voltage, the fourth voltage and the fifth voltage. The third voltage is greater or less than the first voltage and the second voltage, and the fourth voltage is different from the fifth voltage.

(8) In an embodiment of the present disclosure, the display device further includes a third electrode and a first insulating layer. The third electrode is disposed on one side of the first electrode facing away from the second electrode. The third electrode has a first end portion and a first extension portion. The first end portion is a third voltage input terminal. The first extension portion extends from the first end portion to a side edge of the first substrate. The first insulating layer is disposed between the first extension portion and the first electrode.

(9) In an embodiment of the present disclosure, the third electrode and the first insulating layer of the display device are located between the first substrate and the first electrode. The first insulating layer covers the third electrode, and the first end portion penetrates through the first insulating layer

to electrically contact the first electrode.

(10) In an embodiment of the present disclosure, the third electrode and the first insulating layer of the display device are located on one side of the first substrate facing away from the first electrode. The first insulating layer is located between the first substrate and the first extension portion, and the first end portion of the third electrode is electrically coupled to the first electrode.

(11) In an embodiment of the present disclosure, the first electrode, the third electrode and the first insulating layer of the display device are located on one side of the first substrate facing away from the display medium layer, and the first end portion of the third electrode is in electrical contact with the first electrode.

(12) In an embodiment of the present disclosure, the display device further includes a fourth electrode and a second insulating layer. The fourth electrode is disposed on one side of the second electrode facing away from the first electrode. The fourth electrode has a second end portion and a second extension portion. The second extension portion extends from the second end portion to a side edge of the second substrate. The second insulating layer is disposed between the second extension portion and the second electrode. The second electrode is further provided with a sixth voltage input terminal located between the fourth voltage input terminal and the fifth voltage input terminal, and the second end portion of the fourth electrode is the sixth voltage input terminal.

(13) In an embodiment of the present disclosure, the first voltage input terminal, the second voltage input terminal, the third voltage input terminal, the fourth voltage input terminal, the fifth voltage input terminal and the sixth voltage input terminal of the display device are respectively used for inputting the first voltage, the second voltage, the third voltage, the fourth voltage, the fifth voltage and the sixth voltage. The third voltage is greater or less than the first voltage and the second voltage, and the sixth voltage is greater or less than the fourth voltage and the fifth voltage.

(14) In an embodiment of the present disclosure, the display device further includes a first flexible circuit board and a second flexible circuit board. The second electrode is further provided with a sixth voltage input terminal located between the fourth voltage input terminal and the fifth voltage input terminal. The first substrate, the first electrode and the display medium layer have openings. The opening exposes the sixth voltage input terminal of the second electrode. The first flexible circuit board is electrically connected to the third voltage input terminal. The second flexible circuit board is electrically connected to the sixth voltage input terminal through the opening.

(15) In an embodiment of the present disclosure, the opening of the display device further exposes the third voltage input terminal of the first electrode, and the first flexible circuit board is electrically connected to the third voltage input terminal through the opening.

(16) In an embodiment of the present disclosure, the first electrode of the display device is disposed on one side of the first substrate facing away from the display medium layer.

(17) In an embodiment of the present disclosure, the first substrate, the display medium layer and the first electrode of the display device have openings. The display device further includes a light guide structure, a light source and a patterned ink layer. The patterned ink layer is disposed on the second substrate and overlaps the opening. The light guide structure extends into the opening and is adapted to guide light from the light source to pass through the patterned ink layer.

(18) In an embodiment of the present disclosure, the material of the display medium layer of the display device includes a bistable material.

(19) Based on the above, in the display device of an embodiment of the present disclosure, two surfaces of two substrates facing each other are entirely covered with two electrodes respectively, and the two opposite side edges of the two electrodes are respectively provided with two voltage input terminals. By arranging another independently controllable voltage input terminal between two voltage input terminals of one of the electrodes, the display medium layer interposed between the two electrodes may achieve the radiation gradient grayscale display effect.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic top view of a display device according to a first embodiment of the present disclosure.
- (2) FIG. 2 is a schematic cross-sectional view of the display device of FIG. 1.
- (3) FIG. 3 is an equivalent circuit diagram of the display device of FIG. 2.
- (4) FIG. 4 is a schematic cross-sectional view of the display device of a second embodiment of the present disclosure.
- (5) FIG. 5 is a schematic cross-sectional view of a display device according to a third embodiment of the present disclosure.
- (6) FIG. 6 is a schematic cross-sectional view of a display device according to a fourth embodiment of the present disclosure.
- (7) FIG. 7 is an equivalent circuit diagram of the display device of FIG. 6.
- (8) FIG. 8 is a schematic top view of a display device according to a fifth embodiment of the present disclosure.
- (9) FIG. 9 is a schematic cross-sectional view of the display device of FIG. 8.
- (10) FIG. 10 is a schematic cross-sectional view of a display device according to a sixth embodiment of the present disclosure.
- (11) FIG. 11 is a schematic top view of a display device according to a seventh embodiment of the present disclosure.
- (12) FIG. 12 is a schematic cross-sectional view of the display device of FIG. 11.

DESCRIPTION OF EMBODIMENTS

(13) In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. It should be understood that when an element such as a layer, film, region or substrate is referred to as being “on” or “connected to” another element, it can be directly on or connected to the other element, or an intermediate element may also be present. In contrast, when an element is referred to as being “directly on” or “directly connected to” another element, there are no intermediate elements therebetween. As used herein, “connected” may refer to a physical and/or electrical connection. Furthermore, the “electrical connection” may refer to the existence of other elements between two elements.

(14) Reference will now be made in detail to exemplary embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numerals are used in the drawings and description to refer to the same or like parts.

(15) FIG. 1 is a schematic top view of a display device according to a first embodiment of the present disclosure. FIG. 2 is a schematic cross-sectional view of the display device of FIG. 1. FIG. 3 is an equivalent circuit diagram of the display device of FIG. 2. FIG. 2 corresponds to the sectional line A-A' of FIG. 1. Referring to FIG. 1 and FIG. 2, the display device 10 includes a first substrate 101, a second substrate 102, a first electrode 110, a second electrode 120 and a display medium layer 200. The first substrate 101 and the second substrate 102 are disposed opposite to each other. The first electrode 110 entirely covers a surface of the first substrate 101. The second electrode 120 entirely covers a surface of the second substrate 102. The display medium layer 200 is disposed between the first substrate 101 and the second substrate 102. In this embodiment, the first electrode 110 and the second electrode 120 are respectively disposed on two opposite surfaces 101s1 and 102s1 of the first substrate 101 and the second substrate 102, but the disclosure is not limited thereto.

(16) The materials of the first substrate 101 and the second substrate 102 may include glass, quartz, high molecular polymers (such as polyimide, polycarbonate or polyethylene terephthalate), or other flexible plates with high light-transmittance. The first electrode 110 and the second electrode 120

are, for example, light-transmitting electrodes, and the material of the light-transmitting electrodes includes metal oxides, such as indium tin oxide, indium zinc oxide, aluminum tin oxide, aluminum zinc oxide oxides, or other suitable oxides, or a stacked layer of at least two of the above, but the disclosure is not limited thereto. In some embodiments, the material of the first electrode **110** and/or the second electrode **120** may also be selected from metal materials (e.g., molybdenum, aluminum, copper, etc.).

(17) The display medium layer **200** may include a plurality of microcapsules **210** and an electronic ink **220** filled in the microcapsules **210**. The electronic ink **220** may optionally include a plurality of white particles **221**, a plurality of black particles **222** and a transparent liquid **223**, and one of the white particles **221** and the black particles **222** may be positively charged and the other negatively charged. That is, in this embodiment, the material of the display medium layer **200** may be an electrophoretic display (EPD) material.

(18) However, the present disclosure is not limited thereto. According to other embodiments, the display medium layer may also be a Liquid Powder Display (LPD) material, a Cholesteric Liquid-Crystal (CLC) material, Microelectromechanical Systems (MEMS), an Electrochromic Display (ECD) material, a Polymer-Dispersed Liquid Crystal (PDLC) material, or other suitable bistable medium.

(19) Further, the first electrode **110** and the second electrode **120** may be provided with a plurality of voltage input terminals. For example, the two opposite side edges **110e1** and **110e2** of the first electrode **110** may be provided with a voltage input terminal **110in1**, a voltage input terminal **110in2**, a voltage input terminal **110in3** and a voltage input terminal **110in4**, and two opposite side edges **120e1** and **120e2** of the second electrode **120** may be provided with a voltage input terminal **120in1**, a voltage input terminal **120in2**, a voltage input terminal **120in3** and a voltage input terminal **120in4**.

(20) In this embodiment, the display device **10** may further include a third electrode **130** disposed on one side of the first electrode **110** facing away from the second electrode **120**. The third electrode **130** has an end portion **131** and an extension portion **133**. The end portion **131** may be substantially disposed on the first substrate **101** and at a position away from the edge of the substrate, such as a geometric center of the first substrate **101** (as shown in FIG. 1) or other positions deviated from the geometric center and away from the edge of the substrate.

(21) On the other hand, the extension portion **133** may extend from the end portion **131** to the side edge **101e** of the first substrate **101**, and an insulating layer **115** is provided between the extension portion **133** of the third electrode **130** and the first electrode **110**. In order to reduce the capacitive coupling effect between the extension portion **133** of the third electrode **130** and the first electrode **110**, the material of the insulating layer **115** may be selected from an insulating material with a high dielectric constant. For example, in this embodiment, the third electrode **130** and the insulating layer **115** are located between the first substrate **101** and the first electrode **110**, the insulating layer **115** covers the third electrode **130**, and the end portion **131** of the third electrode **130** penetrates through the insulating layer **115** to electrically contact the first electrode **110**, but the disclosure is not limited thereto.

(22) Since the end portion **131** of the third electrode **130** is in electrical contact with the first electrode **110** at the geometric center of the first substrate **101**, the end portion **131** may serve as the geometric center of the first electrode **110** at the first substrate **101** or another voltage input terminal in the proximity thereof. Please also refer to FIG. 3, for example, the voltage input terminal **110in1** (or the voltage input terminal **110in3**) located on the side edge **110e1** of the first electrode **110** may be used as a first voltage input terminal for inputting the first voltage **V1**. The voltage input terminal **110in2** (or the voltage input terminal **110in4**) located at another side edge **110e2** of the first electrode **110** may be used as a second voltage input terminal for inputting the second voltage **V2**. The end portion **131** of the third electrode **130** located between the first voltage input terminal and the second voltage input terminal may serve as a third voltage input terminal for

inputting the third voltage V3.

(23) Similarly, the voltage input terminal **120in1** (or the voltage input terminal **120in3**) located at the side edge **120e1** of the second electrode **120** may be used as the fourth voltage input terminal for inputting the fourth voltage V4. The voltage input terminal **120in2** (or the voltage input terminal **120in4**) located at another side edge **120e2** of the second electrode **120** may be used as the fifth voltage input terminal for inputting the fifth voltage V5.

(24) In this embodiment, when the display device **10** is enabled to display, the third voltage V3 input to the first electrode **110** may be greater or less than the first voltage V1 and the second voltage V2, and the fourth voltage V4 input to the second electrode **120** is different from the fifth voltage V5. That is to say, the potential distribution on the first electrode **110** gradually increases or decreases from the third voltage input terminal (i.e., the end portion **131** of the third electrode **130**) to the first voltage input terminal and the second voltage input terminal on both side edges, and the potential distribution on the second electrode **120** gradually increases or decreases from the fourth voltage input terminal at one side edge **120e1** to the fifth voltage input terminal at another side edge **120e2**. Accordingly, the display medium layer **200** sandwiched between the first electrode **110** and the second electrode **120** may achieve the radiation gradient grayscale display effect.

(25) As shown in FIG. 1, the display grayscale of the display device **10** may exhibit a gradient effect increasing from the end portion **131** of the third electrode **130** (i.e., the third voltage input terminal of the first electrode **110**) as the center to the periphery, that is, radiation grayscale gradient effect. It should be noted that, by adjusting the relative magnitude relationship of the third voltage V3 with respect to the first voltage V1 and the second voltage V2, the display grayscale of the display device **10** may also exhibit a radiation display effect that reduces gradually from the end portion **131** (or the geometric center of first substrate **101**) of the third electrode **130** as the center to the periphery.

(26) In this embodiment, the display device **10** further includes a flexible circuit board **311**, a flexible circuit board **312**, a flexible circuit board **313**, and a flexible circuit board **314**. For example, each of these flexible circuit boards may have two sets of bonding pins, one of which may be electrically connected to a voltage input terminal of the first electrode **110**, and the other set may be electrically connected to a voltage input terminal of the second electrode **120**. For example, one set of bonding pins of the flexible circuit board **311** is electrically connected to the voltage input terminal **110in1** on the first electrode **110**, and the other set of bonding pins is electrically connected to the voltage input terminal **120in1** on the second electrode **120** and so on, but the disclosure is not limited thereto.

(27) Other embodiments will be listed below to describe the present disclosure in detail, and the same components will be marked with the same symbols, and the description of the same technical content will be omitted. For omitted parts, please refer to the foregoing embodiments, which will not be repeated below.

(28) FIG. 4 is a schematic cross-sectional view of the display device of a second embodiment of the present disclosure. Referring to FIG. 4, the only difference between the display device **10A** of the present embodiment and the display device **10** of FIG. 2 is that the configuration of the third electrode and the insulating layer is different. Specifically, the third electrode **130A** and the insulating layer **115A** of the display device **10A** are disposed on one side of the first substrate **101** facing away from the first electrode **110**, and the insulating layer **115A** is located between the first substrate **101** and the extension portion **133** of the third electrode **130A**. It should be noted that, in this embodiment, the end portion **131** of the third electrode **130A** is not directly in electrical contact with the first electrode **110**, but is electrically coupled to the first electrode **110**. That is, the end portion **131** of the third electrode **130A** changes the charge distribution of the first electrode **110** near the end portion **131** through the capacitive coupling effect, thereby changing the electric potential at the position.

(29) FIG. 5 is a schematic cross-sectional view of a display device according to a third embodiment

of the present disclosure. Referring to FIG. 5, the only difference between the display device **10B** of this embodiment and the display device **10A** of FIG. 4 is that the configuration of the first electrode is different. Specifically, the first electrode **110A**, the third electrode **130A** and the insulating layer **115A** of the display device **10B** are disposed on one side of the first substrate **101** facing away from the display medium layer **200**. Unlike the third electrode **130A** in FIG. 4 that is electrically coupled to the first electrode **110**, the end portion **131** of the third electrode **130A** in this embodiment is in direct electrical contact with the first electrode **110A** also located outside the first substrate **101**.

(30) FIG. 6 is a schematic cross-sectional view of a display device according to a fourth embodiment of the present disclosure. FIG. 7 is an equivalent circuit diagram of the display device of FIG. 6. Referring to FIG. 6 and FIG. 7, the only difference between the display device **10C** of this embodiment and the display device **10** of FIG. 2 is that the display device **10C** further includes a fourth electrode **140** and an insulating layer **125**. The fourth electrode **140** is disposed on one side of the second electrode **120** facing away from the first electrode **110**, and has an end portion **141** and an extension portion **143**. Similar to the third electrode **130**, the end portion **141** of the fourth electrode **140** may be substantially disposed on the second substrate **102** and at a position away from the edge of the substrate, such as the geometric center of the second substrate **102** (as shown in FIG. 6) or other positions deviated from the geometric center and away from the edge of the substrate.

(31) On the other hand, the extension portion **143** may extend from the end portion **141** to the side edge **102e** of the second substrate **102**, and an insulating layer **125** is provided between the extension portion **143** of the fourth electrode **140** and the second electrode **120**. In order to reduce the capacitive coupling effect between the extension portion **143** of the fourth electrode **140** and the second electrode **120**, the material of the insulating layer **125** may be selected from an insulating material with a high dielectric constant. For example, in this embodiment, the fourth electrode **140** and the insulating layer **125** are located between the second substrate **102** and the second electrode **120**, the insulating layer **125** covers the fourth electrode **140**, and the end portion **141** of the fourth electrode **140** penetrates through the insulating layer **125** to be in electrical contact with the second electrode **120**, but the disclosure is not limited thereto.

(32) Since the end portion **141** of the fourth electrode **140** is in electrical contact with the second electrode **120** at the geometric center of the second substrate **102**, the end portion **141** may serve as the geometric center of the second electrode **120** at the second substrate **102** or another voltage input terminal in the proximity thereof. For example, the end portion **141** of the fourth electrode **140** located between the fourth voltage input terminal and the fifth voltage input terminal may be used as a sixth voltage input terminal for inputting the sixth voltage **V6** (as shown in FIG. 7).

(33) In the present embodiment, when the display device **10C** is enabled to display, the third voltage **V3** input to the first electrode **110** may be greater than or less than the first voltage **V1** and the second voltage **V2**, and the sixth voltages **V6** input to the second electrode **120** may be greater or less than the fourth voltage **V4** and the fifth voltage **V5**. That is to say, the potential distribution on the first electrode **110** gradually increases or decreases from the third voltage input terminal (i.e., the end portion **131** of the third electrode **130**) to the first voltage input terminal and the second voltage input terminal on both side edges, and the potential distribution on the second electrode **120** gradually increases or decreases from the sixth voltage input terminal (i.e., the end portion **141** of the fourth electrode **140**) to the fourth voltage input terminal and the fifth voltage input terminal on both side edges. Accordingly, the display medium layer **200** sandwiched between the first electrode **110** and the second electrode **120** may achieve the radiation gradient grayscale display effect.

(34) FIG. 8 is a schematic top view of a display device according to a fifth embodiment of the present disclosure. FIG. 9 is a schematic cross-sectional view of the display device of FIG. 8. FIG. 10 is a schematic cross-sectional view of a display device according to a sixth embodiment of the

present disclosure. FIG. 9 corresponds to the sectional line B-B' of FIG. 8.

(35) Please refer to FIG. 8 and FIG. 9, the difference between the display device **20** of this embodiment and the display device **10** of FIG. 1 and FIG. 2 is that the first substrate **101A**, the first electrode **110B** and the display medium layer **200A** of the display device have openings OP. The opening OP may be substantially located at or near the geometric center of the first substrate **101A**, and expose the voltage input terminal **110in5** (i.e., the third voltage input terminal) of the first electrode **110B** and the voltage input terminal **120in5** (i.e., the sixth voltage input terminal) of the second electrode **120**. It should be noted that, in this embodiment, the display device **20** is not provided with the third electrode **130** and the fourth electrode **140** as shown in FIG. 6 to serve as the third voltage input terminal of the first electrode **110B** and the sixth voltage input terminal of the second electrode **120**.

(36) In addition, the display device **20** further includes a flexible circuit board **321** (i.e., a first flexible circuit board) and a flexible circuit board **322** (i.e., a second flexible circuit board). In this embodiment, the two flexible circuit boards are electrically connected to the third voltage input terminal and the sixth voltage input terminal respectively through the opening OP. However, the present disclosure is not limited thereto. As shown in FIG. 10, in the display device **20A** of another embodiment, the first electrode **110C** and its voltage input terminal **110in5** may also be disposed on one side of the first substrate **101A** facing away from the display medium layer **200A**. Therefore, in this embodiment, the flexible circuit board **321** may be electrically connected to the voltage input terminal **110in5** without extending into the opening OP.

(37) Except for the above-mentioned differences, since the display device **20** in FIG. 8 and FIG. 9 and other components and their configuration relationships in the display device **20A** of FIG. 10 are similar to the display device **10** of FIG. 2, detailed descriptions may be derived from the relevant paragraphs of the foregoing embodiments, which will not be repeated here.

(38) FIG. 11 is a schematic top view of a display device according to a seventh embodiment of the present disclosure. FIG. 12 is a schematic cross-sectional view of the display device of FIG. 11. FIG. 12 corresponds to the sectional line C-C' of FIG. 11. Referring to FIG. 11 and FIG. 12, in the display device **30** of this embodiment, the first substrate **101A**, the first electrode **110B** and the display medium layer **200A** have openings OP'', and the openings OP'' may be substantially located at or near the geometric center of the first substrate **101A**.

(39) Different from the foregoing embodiments, the display device **30** further includes a light guide structure **410**, a light source **420** and a patterned ink layer **430**. The patterned ink layer **430** is disposed on the second substrate **102** and overlaps the opening OP''. For example, the display device **30** may further include a transparent cover plate **410**, and the patterned ink layer **430** may be directly printed on the transparent cover plate **410**, but the disclosure is not limited thereto.

(40) The light guide structure **410** extends into the opening OP'' and is adapted to guide the light LB from the light source **420** to pass through the patterned ink layer **430**. In detail, the light guide structure **410** may include a light guide plate **411** and a light guide column **413**. The light guide column **413** is connected to the light emitting surface **410es** of the light guide plate **411** facing the patterned ink layer **430**. The light source **420** is arranged on one side of the light incident surface **410is** of the light guide plate **411** and may be controlled by the flexible circuit board **450**.

(41) For example, in the present embodiment, the flexible circuit board **321A** and the flexible circuit board **322A** connected to the first substrate **101A** near the opening OP'' may be optionally electrically connected to the third voltage input terminal (not shown) of the first electrode **110B** and/or the sixth voltage input terminal (not shown) of the second electrode **120** through a suitable conductive structure (not shown), so as to realize the radiation gradation effect of display grayscales (as shown in FIG. 11). It should be noted that the configuration of the voltage input terminals of the first electrode **110B** and/or the second electrode **120** at the geometric center of the first substrate **101A** in this embodiment may also adopt the configuration described in any of the foregoing embodiments. Therefore, for the detailed description, please refer to the relevant

paragraphs of the foregoing embodiments, which will not be repeated here.

(42) As shown in FIG. 11, by arranging the light guide structure **410** and the patterned ink layer **430** in the radiation center of the gradient display grayscale to display a predetermined pattern, the optimal visual effect for highlighting, for example, a brand logo may be achieved.

(43) To sum up, in the display device of an embodiment of the present disclosure, two surfaces of two substrates facing each other are entirely covered with two electrodes respectively, and the two opposite side edges of the two electrodes are respectively provided with two voltage input terminals. By arranging another independently controllable voltage input terminal between two voltage input terminals of one of the electrodes, the display medium layer interposed between the two electrodes may achieve the radiation gradient grayscale display effect.

Claims

1. A display device, comprising: a first substrate and a second substrate, which are disposed opposite to each other; a first electrode, which entirely covers a surface of the first substrate and is provided with a first voltage input terminal, a second voltage input terminal and a third voltage input terminal, wherein the first voltage input terminal and the second voltage input terminal are respectively located on two opposite side edges of the first electrode, the third voltage input terminal is located between the first voltage input terminal and the second voltage input terminal; a second electrode, which entirely covers a surface of the second substrate and is provided with a fourth voltage input terminal and a fifth voltage input terminal, wherein the fourth voltage input terminal and the fifth voltage input terminal are respectively located on two opposite side edges of the second electrode; and a display medium layer, which is disposed between the first electrode and the second electrode.
2. The display device according to claim 1, wherein the first voltage input terminal, the second voltage input terminal, the third voltage input terminal, the fourth voltage input terminal and the fifth voltage input terminal are respectively used for inputting a first voltage, a second voltage, a third voltage, a fourth voltage and a fifth voltage, the third voltage is greater or less than the first voltage and the second voltage, and the fourth voltage is different from the fifth voltage.
3. The display device according to claim 1, further comprising: a third electrode, which is disposed on one side of the first electrode facing away from the second electrode, wherein the third electrode has a first end portion and a first extension portion, the first end portion is the third voltage input terminal, the first extension portion extends from the first end portion to a side edge of the first substrate; and a first insulating layer, which is disposed between the first extension portion and the first electrode.
4. The display device according to claim 3, wherein the third electrode and the first insulating layer are located between the first substrate and the first electrode, the first insulating layer covers the third electrode, and the first end portion penetrates through the first insulating layer to electrically contact the first electrode.
5. The display device according to claim 3, wherein the third electrode and the first insulating layer are located on one side of the first substrate facing away from the first electrode, the first insulating layer is located between the first substrate and the first extension portion, and the first end portion of the third electrode is electrically coupled to the first electrode.
6. The display device according to claim 3, wherein the first electrode, the third electrode and the first insulating layer are located on one side of the first substrate facing away from the display medium layer, and the first end portion of the third electrode is in electrical contact with the first electrode.
7. The display device according to claim 3, further comprising: a fourth electrode, which is disposed on one side of the second electrode facing away from the first electrode, wherein the fourth electrode has a second end portion and a second extension portion, the second extension

portion extends from the second end portion to a side edge of the second substrate; and a second insulating layer, which is disposed between the second extension portion and the second electrode, wherein the second electrode is further provided with a sixth voltage input terminal located between the fourth voltage input terminal and the fifth voltage input terminal, and the second end portion of the fourth electrode is the sixth voltage input terminal.

8. The display device according to claim 7, wherein the first voltage input terminal, the second voltage input terminal, the third voltage input terminal, the fourth voltage input terminal, the fifth voltage input terminal and the sixth voltage input terminal are respectively used for inputting a first voltage, a second voltage, a third voltage, a fourth voltage, a fifth voltage and a sixth voltage, the third voltage is greater or less than the first voltage and the second voltage, and the sixth voltage is greater or less than the fourth voltage and the fifth voltage.

9. The display device according to claim 1, further comprising: a first flexible circuit board and a second flexible circuit board, wherein the second electrode is further provided with a sixth voltage input terminal located between the fourth voltage input terminal and the fifth voltage input terminal, the first substrate, the first electrode and the display medium layer have an opening, the opening exposes the sixth voltage input terminal of the second electrode, the first flexible circuit board is electrically connected to the third voltage input terminal, and the second flexible circuit board is electrically connected to the sixth voltage input terminal through the opening.

10. The display device according to claim 9, wherein the opening further exposes the third voltage input terminal of the first electrode, and the first flexible circuit board is electrically connected to the third voltage input terminal through the opening.

11. The display device according to claim 10, wherein the first voltage input terminal, the second voltage input terminal, the third voltage input terminal, the fourth voltage input terminal and the fifth voltage input terminal are respectively used for inputting a first voltage, a second voltage, a third voltage, a fourth voltage and a fifth voltage, the third voltage is greater or less than the first voltage and the second voltage, and the fourth voltage is different from the fifth voltage.

12. The display device according to claim 9, wherein the first electrode is disposed on one side of the first substrate facing away from the display medium layer.

13. The display device according to claim 12, wherein the first voltage input terminal, the second voltage input terminal, the third voltage input terminal, the fourth voltage input terminal and the fifth voltage input terminal are respectively used for inputting a first voltage, a second voltage, a third voltage, a fourth voltage and a fifth voltage, the third voltage is greater or less than the first voltage and the second voltage, and the fourth voltage is different from the fifth voltage.

14. The display device according to claim 1, wherein the first substrate, the display medium layer and the first electrode have an opening, the display device further comprises a light guide structure, a light source and a patterned ink layer, the patterned ink layer is disposed on the second substrate and overlaps the opening, the light guide structure extends into the opening and is adapted to guide a light from the light source to pass through the patterned ink layer.

15. The display device according to claim 14, wherein the light guide structure includes a light guide plate and a light guide column, the light guide column is connected to a light emitting surface of the light guide plate facing the patterned ink layer, and the light source is arranged on one side of a light incident surface of the light guide plate.

16. The display device according to claim 14, wherein the second electrode is further provided with a sixth voltage input terminal located between the fourth voltage input terminal and the fifth voltage input terminal, the opening exposes the sixth voltage input terminal of the second electrode.

17. The display device according to claim 16, further comprising: a first flexible circuit board and a second flexible circuit board, which are connected to the first substrate, wherein one of the first flexible circuit board and the second flexible circuit board is electrically connected to the sixth voltage input terminal of the second electrode through the opening.

18. The display device according to claim 14, wherein the first voltage input terminal, the second

voltage input terminal, the third voltage input terminal, the fourth voltage input terminal and the fifth voltage input terminal are respectively used for inputting a first voltage, a second voltage, a third voltage, a fourth voltage and a fifth voltage, the third voltage is greater or less than the first voltage and the second voltage, and the fourth voltage is different from the fifth voltage.

19. The display device according to claim 1, wherein a material of the display medium layer comprises a bistable medium.

20. The display device according to claim 1, wherein a material of the first electrode and the second electrode includes metal oxides.
