

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent

12406183

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Councill; Peter et al.

---

### Accelerated model training from disparate and heterogeneous sources using a meta-database

---

#### Abstract

A system for training a model from a subset of data representing decentrally stored source databases. A key variable repository module operably couples the databases and includes an AI program with a scanner algorithm and a profiler algorithm. The scanner algorithm receives the training data from a source interface, compresses the training data, and synchronizes the training data with the meta-data using a meta-database interface. The profiler algorithm receives the meta-data from the meta-database interface, generates granular data types for the meta-data, determines training variables indicative of the meta-data, generates variable probability distributions, produces training variable associations, and modifies the meta-database to include the probability distributions and associations using the meta-data interface. The key interface allows for searching the meta-database for training variables, variable probability distributions, and/or variable associations. A model of the system may be trained in less time with a subset of data associated with the training variable.

---

**Inventors:** Councill; Peter (Richmond, VA), Cluff; Kenneth William (Powhatan, VA), Nofsinger; Glenn Thomas (Reva, VA), Xu; James (Raleigh, NC), Li; Qing (Cary, NC)

**Applicant:** Truist Bank (Charlotte, NC)

**Family ID:** 88699123

**Assignee:** TRUIST BANK (Charlotte, NC)

**Appl. No.:** 17/663122

**Filed:** May 12, 2022

#### Prior Publication Data

**Document Identifier**

**Publication Date**

US 20230368013 A1

Nov. 16, 2023

---

Publication Classification

Int. Cl.: G06N3/08 (20230101)

U.S. Cl.:

CPC G06N3/08 (20130101);

Field of Classification Search

CPC: G06N (3/08)

References Cited

U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name   | U.S. Cl. | CPC          |
|--------------|-------------|-----------------|----------|--------------|
| 6865567      | 12/2004     | Oommen          | N/A      | N/A          |
| 8046749      | 12/2010     | Owen            | N/A      | N/A          |
| 9904579      | 12/2017     | Shear           | N/A      | N/A          |
| 10664381     | 12/2019     | Walters         | N/A      | N/A          |
| 10884894     | 12/2020     | Walters         | N/A      | N/A          |
| 2009/0240366 | 12/2008     | Kaushal         | N/A      | N/A          |
| 2010/0138026 | 12/2009     | Kaushal         | N/A      | N/A          |
| 2011/0131162 | 12/2010     | Kaushal         | N/A      | N/A          |
| 2013/0311517 | 12/2012     | Kementsietsidis | N/A      | N/A          |
| 2013/0346409 | 12/2012     | Welinder        | 707/737  | G06F 18/2185 |
| 2015/0379430 | 12/2014     | Dirac           | N/A      | N/A          |
| 2016/0034305 | 12/2015     | Shear           | N/A      | N/A          |
| 2018/0011739 | 12/2017     | Pothula         | N/A      | N/A          |
| 2019/0303434 | 12/2018     | Methner         | N/A      | N/A          |
| 2020/0012657 | 12/2019     | Walters         | N/A      | N/A          |
| 2020/0012902 | 12/2019     | Walters         | N/A      | N/A          |
| 2020/0250071 | 12/2019     | Walters         | N/A      | N/A          |
| 2021/0081261 | 12/2020     | Walters         | N/A      | N/A          |
| 2021/0200745 | 12/2020     | Bui             | N/A      | N/A          |
| 2021/0248496 | 12/2020     | Verhoeven       | N/A      | N/A          |
| 2023/0059750 | 12/2022     | Beale           | N/A      | H04L 1/0026  |
| 2023/0177024 | 12/2022     | Anand           | N/A      | N/A          |
| 2024/0135329 | 12/2023     | Hinton          | N/A      | G06Q 10/1053 |
| 2025/0061290 | 12/2024     | Gardner         | N/A      | G06F 16/345  |

Primary Examiner: Leroux; Etienne P

Attorney, Agent or Firm: Shumaker, Loop & Kendrick, LLP

Background/Summary

## FIELD

(1) This invention relates generally to the field of data science, and more particularly embodiments of the invention relate to model training utilizing a meta-database to identify variables, distributions, and casualty of the data included in separate or distinct sources.

## BACKGROUND

(2) AI systems, algorithms, statistical models and the like can generally be used to predict a subsequent outcome based on previous events. For instance, data representing or associated with various events (e.g., events already taken place) may be fed into an AI system, and the AI system may be configured to determine a characteristic with respect to a subsequent outcome. AI systems are typically utilized to model data including a large number of parameters, values, and the like. In many situations, a larger amount of data relevant to the subsequent outcome may increase the accuracy of a generated output from the AI system. Further, AI systems may provide particular benefit when it is unknown which values within a large amount of data are relevant or most relevant to determining a characteristic of the subsequent outcome. Some AI algorithms include machine learning, in which the AI algorithm may alter internal parameters based on training data in order to increase fidelity with respect to a prediction of a characteristic of a subsequent outcome. Machine learning algorithms are typically more accurate when the data used to train the algorithm includes a large amount of data relevant to the subsequent outcome. Generally, additional input data provided to an AI system is associated with increased processing time, an increase in algorithm training time, greater computing power consumption, and/or a reduction in available processing power for executing other computer-readable instructions.

(3) Improvement in the processing time, training time, and required processing power can typically be realized by reducing the input data or training data provided to the AI system and/or associated algorithm. However, a user may have difficulty identifying important data relative or variables useful to modeling, and it may be cumbersome to locate recognizable data within extensive storage architectures. Often, data useful for modeling, such as in conjunction with AI algorithms or statistical modeling, is stored in distinct and separate digital locations (e.g., separate databases). Such data is not typically stored or associated with one memory location or programming interface. Thus, it is difficult to ascertain what data is most relevant to producing an accurate inference and/or to accurately train a model. Even knowing what type of data is relevant to an important variable, value, or the like may not alleviate these matters, as the user may not know where all such data is stored when considering voluminous amounts of data, databases, data repositories, and the like.

(4) In view of the circumstances described above, there is a need for a system to help identify key variables and associated data that may reduce processing time and power required for modeling and statistical analysis.

## BRIEF SUMMARY

(5) Embodiments of the present invention address the above needs and/or achieve other advantages by providing systems, apparatuses, and methods that produce a meta-database including a summary of data stored across multiple, distinct databases or sources. The meta-database may, via use of an associated key interface, allow a user to search the meta-database during pre-processing to determine variables that are important or critical for modeling and ascertain relationships between types of data stored in the source databases. In various embodiments, the system may include a computer implementing computer instructions including AI algorithms trained to identify important variables, data associated with the variables, and produce associations for the same. Generally, the system may include a program or subprogram to scan source databases and summarize the data within the meta-database. Scanning source databases may include implementing AI instructions in order to initially categorize and group similar sampled data. The system may further include a program or subprogram to profile the meta-data produced in the meta-database during the scanning process. Profiling the meta-data may include implementing AI instructions to identify important

variables and associated data in the source databases, generating associations between variables, or generating probability distributions for the identified variables. In some embodiments, AI instructions associated with profiling the meta-data may determine a causal relationship between two or more variables.

(6) Aspects of the present subject matter are directed to a system for training a model from a subset of training data representing data from a plurality of source databases. The system includes a computer including one or more processor and at least one of a memory device and a non-transitory storage device. The one or more processor executes a source programming interface, a meta-database programming interface, a key training variable repository module, and key interface, and model. The source programming interface allows for interfacing with the source databases, which include training data associated with the training variables. The meta-database programming interface allows for interfacing with the meta-database. The key training variable repository module operably couples the source databases and the meta-database. The key training variable repository module includes an artificial intelligence program including a scanner algorithm and a profiler algorithm. The scanner algorithm includes a number of steps. One step of the scanner algorithm is to communicate with the source programming interface to receive the training data of the source databases. Another step of the scanner algorithm is to compress the training data of the source databases. Another step of the scanner algorithm is to communicate with the meta-database programming interface and synchronize the meta-database with the compressed training data of the source databases. The profiler algorithm also includes a number of steps. One step of the profiler algorithm is to communicate with the meta-database programming interface to receive the training data of the meta-database. Another step of the profiler algorithm is to generate, based on the training data of the meta-database, granular training data types for at least a portion of the training data of the meta-database. A further step of the profiler algorithm is to determine a plurality of training variables indicative of at least a portion of the training data of the meta-database and generate, for each training variable, a probability distribution. Another step of the profiler algorithm is to produce at least one association between at least two training variables of the plurality of training variables. An additional step of the profiler algorithm is to communicate with the meta-database programming interface to modify the meta-database to include the probability distribution generated for each training variable and the at least one association produced between the at least two training variables. The key interface allows for searching the meta-database, based on a communicated user input, for at least one of a training variable, a probability distribution for a training variable, or a produced association between training variables. The model uses artificial intelligence programming and inference data to generate an inference, after required training of the model. As such, using a subset of training data from the source databases and associated with the at least one training variable reduces the time required to train the model to generate the inference.

(7) In another aspect, the present subject matter is directed to a system for training a model from a subset of training data representing training data from a plurality of source databases. The system includes a computer including one or more processor and at least one of a memory device and a non-transitory storage device. The one or more processor executes a number of artificial intelligence computer-readable instructions. One instruction is to receive training data representative of the plurality of source databases. Another instruction is to identify a representative set of training data for each database of the plurality of source databases. Each representative set of training data substantially represents the training data of the respective source database. Another instruction is to generate, in a training meta-database, the representative training data sets for the plurality of source databases. An additional instruction is to generate granular training data types for at least a portion of the training data of the training meta-database. A further instruction is to determine a plurality of training variables indicative of at least a portion of the training data of the training meta-database. Another instruction is to generate a probability distribution for each training variable of the plurality of training variables. One instruction includes to produce at least

one association between at least two training variables of the plurality of training variables. One instruction includes to search, based on a user communicated input, the training data of the training meta-database for at least one training variable, probability distributions for at least one training variable, or associations between at least two training variables. A further instruction includes to identify a subset of training data from the source databases associated with the at least one training variable. A further instruction includes to train the model utilizing the subset of training data from the source databases associated with the at least one training variable. The model includes artificial intelligence programming configured to generate an inference in response to data input, and the subset of training data reduces the time required to train the model to generate the inference.

(8) In at least one embodiment, one or more of the steps to identify the representative set of training data for each source database, to generate granular training data types for at least a portion of the training data of the training meta-database, to determine the plurality of training variables indicative of at least a portion of the training data of the training meta-database, or to produce at least one association between at least two training variables may be included in instructions associated with a machine learning algorithm. In an additional or alternative embodiment, the machine learning algorithm may use a neural network. Additionally or alternatively, the one or more processor may execute instructions to generate, in the training meta-database, the probability distribution generated for each training variable and the at least one association between the at least two training variables.

(9) In some embodiments, the one or more processor may execute instructions to search, based on a user input, a subset of the training data of the training meta-database for at least one training variable, probability distributions for at least one training variable, or associations between at least two training variables. The subset of training data may represent a subset of databases of the plurality of source databases. In at least one additional or alternative embodiment, the one or more processor may execute instructions to produce at least one interactive visualization of at least one training variable of the plurality of training variables, a probability distributions for at least one training variable, or an association between at least two training variables. Additionally or alternatively, the one or more processor may execute instructions to communicate, based on at least one training variable identified by a user, a subset of the plurality of source databases including training data relevant to the at least one training variable identified by the user.

(10) In an additional or alternative embodiment, the instruction to identify the representative training data for each database of the plurality of source databases may include instructions to compress the training data represented in each source database of the plurality of source databases. Additionally or alternatively, the instruction to generate, in the training meta-database, the representative training data for the plurality of source databases includes instructions to synchronize the training data of training meta-database with the representative training data for the plurality of source databases. In some embodiments, the one or more processor may further execute instructions to collect information about the completeness of training data relevant to a training variable and, when the completeness of the training data is less than a predetermined threshold, eliminate the training data relevant to the training variable from the training meta-database.

(11) In an additional or alternative embodiment, the instruction to generate granular training data types for at least a portion of the training data of the training meta-database may include utilizing a field-by-field analysis. Additionally or alternatively, the instruction to generate granular training data types for at least a portion of the training data of the training meta-database may include instructions to analyze properties of the training data of the training meta-database stored as at least one of integer, floating point, date, or text to detect at least one of categorical training variables, binary training variables, dates with and without times, timestamps with and without dates, numerically encoded categorical training variables, true floating point and integer values, ID numbers, strings, zip codes, phone numbers, or IP addresses. In some embodiments, the instruction to generate a probability distribution for each training variable of the plurality of training variables

may include instructions to apply a function of the granular training data type for at least one training variable, the function including at least one of a density estimate, discrete distribution, or sample.

(12) Additionally or alternatively, the instruction to produce at least one association between at least two training variables may include instructions to determine or estimate a causal relationship between the at least two training variables. In some embodiments, the instruction to produce at least one association between at least two training variables may include instructions to determine or estimate at least one of a parametric correlation between the at least two training variables, a non-parametric correlation between the at least two training variables, a Pearson correlation between the at least two training variables, a Spearman correlation between the at least two training variables, a Kendall's Tau correlation between the at least two training variables, mutual information between the at least two training variables, or an uncertainty coefficient between the at least two training variables.

(13) In some further or alternative embodiments, the training meta-database may be stored on a first portion of the at least one of the memory device and the non-transitory storage device, and the plurality of source databases may be stored on a second portion of the at least one of a memory device and a non-transitory storage device. Furthermore, the first portion may be allocated to substantially less memory space of the at least one of the memory device and the non-transitory storage device than the second portion.

(14) In another aspect, the present subject matter is directed to a for training a model from a subset of training data representing a plurality of source databases. The method includes communicating, from a source programming interface, training data representative of a plurality of source databases to an artificial intelligence program. The method further includes compressing the training data representative of the plurality of source databases. Further, the method includes communicating, to a training meta-database programming interface, the compressed training data and synchronizing the training data of the training meta-database with the compressed training data. The method also includes generating, utilizing the artificial intelligence program, granular training data types for at least a portion of the training data of the training meta-database. Further, the method includes determining, utilizing the artificial intelligence program, a plurality of training variables indicative of at least a portion of the training data of the training meta-database. The method further includes generating, utilizing the artificial intelligence program, a probability distribution for each training variable of the plurality of training variables. The method additionally includes producing, utilizing the artificial intelligence program, at least one association between at least two training variables of the plurality of training variables. Furthermore, the method includes communicating, to the training meta-database programming interface, the compressed training data and modifying the training meta-database to include the probability distribution generated for each training variable and the at least one association produced between the at least two training variables. The method includes receiving a user communicated input and searching the training meta-database, based on the user communicated input, for at least one of a training variable, a probability distribution for a training variable, or a produced association between training variables. The method further includes identifying a searched subset of the training data from the source databases associated with the at least one training variable searched for based on the user input.

(15) In one embodiment, the method may further include training the model utilizing the searched subset of training data from the source databases. The model may include artificial intelligence programming configured to generate an inference in response to data input. Thus, the searched subset of training data may reduce the time required to train the model to generate the inference. Additionally or alternatively, the method may include determining, utilizing the artificial intelligence program and the plurality of source databases, that at least a portion of the training data of the training meta-database is outdated.

(16) The features, functions, and advantages that have been discussed may be achieved

independently in various embodiments of the present invention or may be combined in yet other embodiments, further details of which can be seen with reference to the following description and drawings.

---

## Description

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) Having thus described embodiments of the invention in general terms, reference will now be made to the accompanying drawings, wherein:

(2) FIG. 1 illustrates an enterprise system, and environment thereof, according to at least one embodiment.

(3) FIG. 2A is a diagram of a feedforward network, according to at least one embodiment, utilized in machine learning.

(4) FIG. 2B is a diagram of a convolution neural network, according to at least one embodiment, utilized in machine learning.

(5) FIG. 2C is a diagram of a portion of the convolution neural network of FIG. 2B, according to at least one embodiment, illustrating assigned weights at connections or neurons.

(6) FIG. 3 is a diagram representing an exemplary weighted sum computation in a node in an artificial neural network.

(7) FIG. 4 is a diagram of a Recurrent Neural Network RNN, according to at least one embodiment, utilized in machine learning.

(8) FIG. 5 is a schematic logic diagram of an artificial intelligence program including a front-end and a back-end algorithm.

(9) FIG. 6 is a flow chart representing a method, according to at least one embodiment, of model development and deployment by machine learning.

(10) FIG. 7 illustrates one embodiment of a system for maintaining a meta-database representing data from multiple source databases, in accordance with aspects of the present subject matter.

(11) FIG. 8 illustrates one embodiment of a method for maintaining a meta-database representing data from multiple source databases, in accordance with aspects of the present subject matter.

(12) FIG. 9 illustrates one embodiment of a method for training a model from a subset of training data representing data from multiple source databases, in accordance with aspects of the present subject matter.

### DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

(13) Embodiments of the present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all, embodiments of the invention are shown. Indeed, the invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout. Unless described or implied as exclusive alternatives, features throughout the drawings and descriptions should be taken as cumulative, such that features expressly associated with some particular embodiments can be combined with other embodiments. Unless defined otherwise, technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which the presently disclosed subject matter pertains.

(14) The exemplary embodiments are provided so that this disclosure will be both thorough and complete, and will fully convey the scope of the invention and enable one of ordinary skill in the art to make, use, and practice the invention.

(15) The terms “coupled,” “fixed,” “attached to,” “communicatively coupled to,” “operatively coupled to,” and the like refer to both (i) direct connecting, coupling, fixing, attaching, communicatively coupling; and (ii) indirect connecting coupling, fixing, attaching,

communicatively coupling via one or more intermediate components or features, unless otherwise specified herein. “Communicatively coupled to” and “operatively coupled to” can refer to physically and/or electrically related components.

(16) Embodiments of the present invention described herein, with reference to flowchart illustrations and/or block diagrams of methods or apparatuses (the term “apparatus” includes systems and computer program products), will be understood such that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a particular machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create mechanisms for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

(17) These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer readable memory produce an article of manufacture including instructions, which implement the function/act specified in the flowchart and/or block diagram block or blocks.

(18) The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions, which execute on the computer or other programmable apparatus, provide steps for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks. Alternatively, computer program implemented steps or acts may be combined with operator or human implemented steps or acts in order to carry out an embodiment of the invention.

(19) While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of, and not restrictive on, the broad invention, and that this invention not be limited to the specific constructions and arrangements shown and described, since various other changes, combinations, omissions, modifications and substitutions, in addition to those set forth in the above paragraphs, are possible. Those skilled in the art will appreciate that various adaptations, modifications, and combinations of the herein described embodiments can be configured without departing from the scope and spirit of the invention. Therefore, it is to be understood that, within the scope of the included claims, the invention may be practiced other than as specifically described herein.

(20) FIG. 1 illustrates a system **100** and environment thereof, according to at least one embodiment, by which a user **110** benefits through use of services and products of an enterprise system **200**. The user **110** accesses services and products by use of one or more user devices, illustrated in separate examples as a computing device **104** and a mobile device **106**, which may be, as non-limiting examples, a smart phone, a portable digital assistant (PDA), a pager, a mobile television, a gaming device, a laptop computer, a camera, a video recorder, an audio/video player, radio, a GPS device, or any combination of the aforementioned, or other portable device with processing and communication capabilities. In the illustrated example, the mobile device **106** is illustrated in FIG. 1 as having exemplary elements, the below descriptions of which apply as well to the computing device **104**, which can be, as non-limiting examples, a desktop computer, a laptop computer, or other user-accessible computing device.

(21) Furthermore, the user device, referring to either or both of the computing device **104** and the mobile device **106**, may be or include a workstation, a server, or any other suitable device, including a set of servers, a cloud-based application or system, or any other suitable system, adapted to execute, for example any suitable operating system, including Linux, UNIX, Windows, macOS, iOS, Android and any other known operating system used on personal computers, central



computing systems, phones, and other devices.

(22) The user **110** can be an individual, a group, or any entity in possession of or having access to the user device, referring to either or both of the mobile device **104** and computing device **106**, which may be personal or public items. Although the user **110** may be singly represented in some drawings, at least in some embodiments according to these descriptions the user **110** is one of many such that a market or community of users, consumers, customers, business entities, government entities, clubs, and groups of any size are all within the scope of these descriptions.

(23) The user device, as illustrated with reference to the mobile device **106**, includes components such as, at least one of each of a processing device **120**, and a memory device **122** for processing use, such as random access memory (RAM), and read-only memory (ROM). The illustrated mobile device **106** further includes a storage device **124** including at least one of a non-transitory storage medium, such as a microdrive, for long-term, intermediate-term, and short-term storage of computer-readable instructions **126** for execution by the processing device **120**. For example, the instructions **126** can include instructions for an operating system and various applications or programs **130**, of which the application **132** is represented as a particular example. The storage device **124** can store various other data items **134**, which can include, as non-limiting examples, cached data, user files such as those for pictures, audio and/or video recordings, files downloaded or received from other devices, and other data items preferred by the user or required or related to any or all of the applications or programs **130**.

(24) The memory device **122** is operatively coupled to the processing device **120**. As used herein, memory includes any computer readable medium to store data, code, or other information. The memory device **122** may include volatile memory, such as volatile Random Access Memory (RAM) including a cache area for the temporary storage of data. The memory device **122** may also include non-volatile memory, which can be embedded and/or may be removable. The non-volatile memory can additionally or alternatively include an electrically erasable programmable read-only memory (EEPROM), flash memory or the like.

(25) The memory device **122** and storage device **124** can store any of a number of applications which comprise computer-executable instructions and code executed by the processing device **120** to implement the functions of the mobile device **106** described herein. For example, the memory device **122** may include such applications as a conventional web browser application and/or a mobile P2P payment system client application. These applications also typically provide a graphical user interface (GUI) on the display **140** that allows the user **110** to communicate with the mobile device **106**, and, for example a mobile banking system, and/or other devices or systems. In one embodiment, when the user **110** decides to enroll in a mobile banking program, the user **110** downloads or otherwise obtains the mobile banking system client application from a mobile banking system, for example enterprise system **200**, or from a distinct application server. In other embodiments, the user **110** interacts with a mobile banking system via a web browser application in addition to, or instead of, the mobile P2P payment system client application.

(26) The processing device **120**, and other processors described herein, generally include circuitry for implementing communication and/or logic functions of the mobile device **106**. For example, the processing device **120** may include a digital signal processor, a microprocessor, and various analog to digital converters, digital to analog converters, and/or other support circuits. Control and signal processing functions of the mobile device **106** are allocated between these devices according to their respective capabilities. The processing device **120** thus may also include the functionality to encode and interleave messages and data prior to modulation and transmission. The processing device **120** can additionally include an internal data modem. Further, the processing device **120** may include functionality to operate one or more software programs, which may be stored in the memory device **122**, or in the storage device **124**. For example, the processing device **120** may be capable of operating a connectivity program, such as a web browser application. The web browser application may then allow the mobile device **106** to transmit and receive web content, such as, for

example, location-based content and/or other web page content, according to a Wireless Application Protocol (WAP), Hypertext Transfer Protocol (HTTP), and/or the like.

(27) The memory device **122** and storage device **124** can each also store any of a number of pieces of information, and data, used by the user device and the applications and devices that facilitate functions of the user device, or are in communication with the user device, to implement the functions described herein and others not expressly described. For example, the storage device may include such data as user authentication information, etc.

(28) The processing device **120**, in various examples, can operatively perform calculations, can process instructions for execution, and can manipulate information. The processing device **120** can execute machine-executable instructions stored in the storage device **124** and/or memory device **122** to thereby perform methods and functions as described or implied herein, for example by one or more corresponding flow charts expressly provided or implied as would be understood by one of ordinary skill in the art to which the subject matters of these descriptions pertain. The processing device **120** can be or can include, as non-limiting examples, a central processing unit (CPU), a microprocessor, a graphics processing unit (GPU), a microcontroller, an application-specific integrated circuit (ASIC), a programmable logic device (PLD), a digital signal processor (DSP), a field programmable gate array (FPGA), a state machine, a controller, gated or transistor logic, discrete physical hardware components, and combinations thereof. In some embodiments, particular portions or steps of methods and functions described herein are performed in whole or in part by way of the processing device **120**, while in other embodiments methods and functions described herein include cloud-based computing in whole or in part such that the processing device **120** facilitates local operations including, as non-limiting examples, communication, data transfer, and user inputs and outputs such as receiving commands from and providing displays to the user.

(29) The mobile device **106**, as illustrated, includes an input and output system **136**, referring to, including, or operatively coupled with, user input devices and user output devices, which are operatively coupled to the processing device **120**. The user output devices include a display **140** (e.g., a liquid crystal display or the like), which can be, as a non-limiting example, a touch screen of the mobile device **106**, which serves both as an output device, by providing graphical and text indicia and presentations for viewing by one or more user **110**, and as an input device, by providing virtual buttons, selectable options, a virtual keyboard, and other indicia that, when touched, control the mobile device **106** by user action. The user output devices include a speaker **144** or other audio device. The user input devices, which allow the mobile device **106** to receive data and actions such as button manipulations and touches from a user such as the user **110**, may include any of a number of devices allowing the mobile device **106** to receive data from a user, such as a keypad, keyboard, touch-screen, touchpad, microphone **142**, mouse, joystick, other pointer device, button, soft key, and/or other input device(s). The user interface may also include a camera **146**, such as a digital camera.

(30) Further non-limiting examples include, one or more of each, any, and all of a wireless or wired keyboard, a mouse, a touchpad, a button, a switch, a light, an LED, a buzzer, a bell, a printer and/or other user input devices and output devices for use by or communication with the user **110** in accessing, using, and controlling, in whole or in part, the user device, referring to either or both of the computing device **104** and a mobile device **106**. Inputs by one or more user **110** can thus be made via voice, text or graphical indicia selections. For example, such inputs in some examples correspond to user-side actions and communications seeking services and products of the enterprise system **200**, and at least some outputs in such examples correspond to data representing enterprise-side actions and communications in two-way communications between a user **110** and an enterprise system **200**.

(31) The mobile device **106** may also include a positioning device **108**, which can be for example a global positioning system device (GPS) configured to be used by a positioning system to determine a location of the mobile device **106**. For example, the positioning system device **108** may include a

GPS transceiver. In some embodiments, the positioning system device **108** includes an antenna, transmitter, and receiver. For example, in one embodiment, triangulation of cellular signals may be used to identify the approximate location of the mobile device **106**. In other embodiments, the positioning device **108** includes a proximity sensor or transmitter, such as an RFID tag, that can sense or be sensed by devices known to be located proximate a merchant or other location to determine that the consumer mobile device **106** is located proximate these known devices.

(32) In the illustrated example, a system intraconnect **138**, connects, for example electrically, the various described, illustrated, and implied components of the mobile device **106**. The intraconnect **138**, in various non-limiting examples, can include or represent, a system bus, a high-speed interface connecting the processing device **120** to the memory device **122**, individual electrical connections among the components, and electrical conductive traces on a motherboard common to some or all of the above-described components of the user device. As discussed herein, the system intraconnect **138** may operatively couple various components with one another, or in other words, electrically connects those components, either directly or indirectly—by way of intermediate component(s)—with one another.

(33) The user device, referring to either or both of the computing device **104** and the mobile device **106**, with particular reference to the mobile device **106** for illustration purposes, includes a communication interface **150**, by which the mobile device **106** communicates and conducts transactions with other devices and systems. The communication interface **150** may include digital signal processing circuitry and may provide two-way communications and data exchanges, for example wirelessly via wireless communication device **152**, and for an additional or alternative example, via wired or docked communication by mechanical electrically conductive connector **154**. Communications may be conducted via various modes or protocols, of which GSM voice calls, SMS, EMS, MMS messaging, TDMA, CDMA, PDC, WCDMA, CDMA2000, and GPRS, are all non-limiting and non-exclusive examples. Thus, communications can be conducted, for example, via the wireless communication device **152**, which can be or include a radio-frequency transceiver, a Bluetooth device, Wi-Fi device, a Near-field communication device, and other transceivers. In addition, GPS (Global Positioning System) may be included for navigation and location-related data exchanges, ingoing and/or outgoing. Communications may also or alternatively be conducted via the connector **154** for wired connections such by USB, Ethernet, and other physically connected modes of data transfer.

(34) The processing device **120** is configured to use the communication interface **150** as, for example, a network interface to communicate with one or more other devices on a network. In this regard, the communication interface **150** utilizes the wireless communication device **152** as an antenna operatively coupled to a transmitter and a receiver (together a “transceiver”) included with the communication interface **150**. The processing device **120** is configured to provide signals to and receive signals from the transmitter and receiver, respectively. The signals may include signaling information in accordance with the air interface standard of the applicable cellular system of a wireless telephone network. In this regard, the mobile device **106** may be configured to operate with one or more air interface standards, communication protocols, modulation types, and access types. By way of illustration, the mobile device **106** may be configured to operate in accordance with any of a number of first, second, third, fourth, fifth-generation communication protocols and/or the like. For example, the mobile device **106** may be configured to operate in accordance with second-generation (2G) wireless communication protocols IS-136 (time division multiple access (TDMA)), GSM (global system for mobile communication), and/or IS-95 (code division multiple access (CDMA)), or with third-generation (3G) wireless communication protocols, such as Universal Mobile Telecommunications System (UMTS), CDMA2000, wideband CDMA (WCDMA) and/or time division-synchronous CDMA (TD-SCDMA), with fourth-generation (4G) wireless communication protocols such as Long-Term Evolution (LTE), fifth-generation (5G) wireless communication protocols, Bluetooth Low Energy (BLE) communication protocols such as

Bluetooth 5.0, ultra-wideband (UWB) communication protocols, and/or the like. The mobile device **106** may also be configured to operate in accordance with non-cellular communication mechanisms, such as via a wireless local area network (WLAN) or other communication/data networks.

(35) The communication interface **150** may also include a payment network interface. The payment network interface may include software, such as encryption software, and hardware, such as a modem, for communicating information to and/or from one or more devices on a network. For example, the mobile device **106** may be configured so that it can be used as a credit or debit card by, for example, wirelessly communicating account numbers or other authentication information to a terminal of the network. Such communication could be performed via transmission over a wireless communication protocol such as the Near-field communication protocol.

(36) The mobile device **106** further includes a power source **128**, such as a battery, for powering various circuits and other devices that are used to operate the mobile device **106**. Embodiments of the mobile device **106** may also include a clock or other timer configured to determine and, in some cases, communicate actual or relative time to the processing device **120** or one or more other devices. For further example, the clock may facilitate timestamping transmissions, receptions, and other data for security, authentication, logging, polling, data expiry, and forensic purposes.

(37) System **100** as illustrated diagrammatically represents at least one example of a possible implementation, where alternatives, additions, and modifications are possible for performing some or all of the described methods, operations and functions. Although shown separately, in some embodiments, two or more systems, servers, or illustrated components may be utilized. In some implementations, the functions of one or more systems, servers, or illustrated components may be provided by a single system or server. In some embodiments, the functions of one illustrated system or server may be provided by multiple systems, servers, or computing devices, including those physically located at a central facility, those logically local, and those located as remote with respect to each other.

(38) The enterprise system **200** can offer any number or type of services and products to one or more users **110**. In some examples, an enterprise system **200** offers products. In some examples, an enterprise system **200** offers services. Use of “service(s)” or “product(s)” thus relates to either or both in these descriptions. With regard, for example, to online information and financial services, “service” and “product” are sometimes termed interchangeably. In non-limiting examples, services and products include retail services and products, information services and products, custom services and products, predefined or pre-offered services and products, consulting services and products, advising services and products, forecasting services and products, internet products and services, social media, and financial services and products, which may include, in non-limiting examples, services and products relating to banking, checking, savings, investments, credit cards, automatic-teller machines, debit cards, loans, mortgages, personal accounts, business accounts, account management, credit reporting, credit requests, and credit scores.

(39) To provide access to, or information regarding, some or all the services and products of the enterprise system **200**, automated assistance may be provided by the enterprise system **200**. For example, automated access to user accounts and replies to inquiries may be provided by enterprise-side automated voice, text, and graphical display communications and interactions. In at least some examples, any number of human agents **210**, can be employed, utilized, authorized or referred by the enterprise system **200**. Such human agents **210** can be, as non-limiting examples, point of sale or point of service (POS) representatives, online customer service assistants available to users **110**, advisors, managers, sales team members, and referral agents ready to route user requests and communications to preferred or particular other agents, human or virtual.

(40) Human agents **210** may utilize agent devices **212** to serve users in their interactions to communicate and take action. The agent devices **212** can be, as non-limiting examples, computing devices, kiosks, terminals, smart devices such as phones, and devices and tools at customer service

counters and windows at POS locations. In at least one example, the diagrammatic representation of the components of the user device **106** in FIG. **1** applies as well to one or both of the computing device **104** and the agent devices **212**.

(41) Agent devices **212** individually or collectively include input devices and output devices, including, as non-limiting examples, a touch screen, which serves both as an output device by providing graphical and text indicia and presentations for viewing by one or more agent **210**, and as an input device by providing virtual buttons, selectable options, a virtual keyboard, and other indicia that, when touched or activated, control or prompt the agent device **212** by action of the attendant agent **210**. Further non-limiting examples include, one or more of each, any, and all of a keyboard, a mouse, a touchpad, a joystick, a button, a switch, a light, an LED, a microphone serving as input device for example for voice input by a human agent **210**, a speaker serving as an output device, a camera serving as an input device, a buzzer, a bell, a printer and/or other user input devices and output devices for use by or communication with a human agent **210** in accessing, using, and controlling, in whole or in part, the agent device **212**.

(42) Inputs by one or more human agents **210** can thus be made via voice, text or graphical indicia selections. For example, some inputs received by an agent device **212** in some examples correspond to, control, or prompt enterprise-side actions and communications offering services and products of the enterprise system **200**, information thereof, or access thereto. At least some outputs by an agent device **212** in some examples correspond to, or are prompted by, user-side actions and communications in two-way communications between a user **110** and an enterprise-side human agent **210**.

(43) From a user perspective experience, an interaction in some examples within the scope of these descriptions begins with direct or first access to one or more human agents **210** in person, by phone, or online for example via a chat session or website function or feature. In other examples, a user is first assisted by a virtual agent **214** of the enterprise system **200**, which may satisfy user requests or prompts by voice, text, or online functions, and may refer users to one or more human agents **210** once preliminary determinations or conditions are made or met.

(44) A computing system **206** of the enterprise system **200** may include components such as, at least one of each of a processing device **220**, and a memory device **222** for processing use, such as random access memory (RAM), and read-only memory (ROM). The illustrated computing system **206** further includes a storage device **224** including at least one non-transitory storage medium, such as a microdrive, for long-term, intermediate-term, and short-term storage of computer-readable instructions **226** for execution by the processing device **220**. For example, the instructions **226** can include instructions for an operating system and various applications or programs **230**, of which the application **232** is represented as a particular example. The storage device **224** can store various other data **234**, which can include, as non-limiting examples, cached data, and files such as those for user accounts, user profiles, account balances, and transaction histories, files downloaded or received from other devices, and other data items preferred by the user or required or related to any or all of the applications or programs **230**.

(45) The computing system **206**, in the illustrated example, includes an input/output system **236**, referring to, including, or operatively coupled with input devices and output devices such as, in a non-limiting example, agent devices **212**, which have both input and output capabilities.

(46) In the illustrated example, a system intraconnect **238** electrically connects the various above-described components of the computing system **206**. In some cases, the intraconnect **238** operatively couples components to one another, which indicates that the components may be directly or indirectly connected, such as by way of one or more intermediate components. The intraconnect **238**, in various non-limiting examples, can include or represent, a system bus, a high-speed interface connecting the processing device **220** to the memory device **222**, individual electrical connections among the components, and electrical conductive traces on a motherboard common to some or all of the above-described components of the user device.

(47) The computing system **206**, in the illustrated example, includes a communication interface **250**, by which the computing system **206** communicates and conducts transactions with other devices and systems. The communication interface **250** may include digital signal processing circuitry and may provide two-way communications and data exchanges, for example wirelessly via wireless device **252**, and for an additional or alternative example, via wired or docked communication by mechanical electrically conductive connector **254**. Communications may be conducted via various modes or protocols, of which GSM voice calls, SMS, EMS, MMS messaging, TDMA, CDMA, PDC, WCDMA, CDMA2000, and GPRS, are all non-limiting and non-exclusive examples. Thus, communications can be conducted, for example, via the wireless device **252**, which can be or include a radio-frequency transceiver, a Bluetooth device, Wi-Fi device, Near-field communication device, and other transceivers. In addition, GPS (Global Positioning System) may be included for navigation and location-related data exchanges, ingoing and/or outgoing. Communications may also or alternatively be conducted via the connector **254** for wired connections such as by USB, Ethernet, and other physically connected modes of data transfer.

(48) The processing device **220**, in various examples, can operatively perform calculations, can process instructions for execution, and can manipulate information. The processing device **220** can execute machine-executable instructions stored in the storage device **224** and/or memory device **222** to thereby perform methods and functions as described or implied herein, for example by one or more corresponding flow charts expressly provided or implied as would be understood by one of ordinary skill in the art to which the subjects matters of these descriptions pertain. The processing device **220** can be or can include, as non-limiting examples, a central processing unit (CPU), a microprocessor, a graphics processing unit (GPU), a microcontroller, an application-specific integrated circuit (ASIC), a programmable logic device (PLD), a digital signal processor (DSP), a field programmable gate array (FPGA), a state machine, a controller, gated or transistor logic, discrete physical hardware components, and combinations thereof.

(49) Furthermore, the computing device **206**, may be or include a workstation, a server, or any other suitable device, including a set of servers, a cloud-based application or system, or any other suitable system, adapted to execute, for example any suitable operating system, including Linux, UNIX, Windows, macOS, iOS, Android, and any known other operating system used on personal computer, central computing systems, phones, and other devices.

(50) The user devices, referring to either or both of the mobile device **104** and computing device **106**, the agent devices **212**, and the enterprise computing system **206**, which may be one or any number centrally located or distributed, are in communication through one or more networks, referenced as network **258** in FIG. 1.

(51) Network **258** provides wireless or wired communications among the components of the system **100** and the environment thereof, including other devices local or remote to those illustrated, such as additional mobile devices, servers, and other devices communicatively coupled to network **258**, including those not illustrated in FIG. 1. The network **258** is singly depicted for illustrative convenience, but may include more than one network without departing from the scope of these descriptions. In some embodiments, the network **258** may be or provide one or more cloud-based services or operations. The network **258** may be or include an enterprise or secured network, or may be implemented, at least in part, through one or more connections to the Internet. A portion of the network **258** may be a virtual private network (VPN) or an Intranet. The network **258** can include wired and wireless links, including, as non-limiting examples, 802.11a/b/g/n/ac, 802.20, WiMax, LTE, and/or any other wireless link. The network **258** may include any internal or external network, networks, sub-network, and combinations of such operable to implement communications between various computing components within and beyond the illustrated environment **100**. The network **258** may communicate, for example, Internet Protocol (IP) packets, Frame Relay frames, Asynchronous Transfer Mode (ATM) cells, voice, video, data, and other

suitable information between network addresses. The network **258** may also include one or more local area networks (LANs), radio access networks (RANs), metropolitan area networks (MANs), wide area networks (WANs), all or a portion of the internet and/or any other communication system or systems at one or more locations.

(52) Two external systems **202** and **204** are expressly illustrated in FIG. **1**, representing any number and variety of data sources, users, consumers, customers, business entities, banking systems, government entities, clubs, and groups of any size are all within the scope of the descriptions. In at least one example, the external systems **202** and **204** represent automatic teller machines (ATMs) utilized by the enterprise system **200** in serving users **110**. In another example, the external systems **202** and **204** represent payment clearinghouse or payment rail systems for processing payment transactions, and in another example, the external systems **202** and **204** represent third party systems such as merchant systems configured to interact with the user device **106** during transactions and also configured to interact with the enterprise system **200** in back-end transactions clearing processes.

(53) In certain embodiments, one or more of the systems such as the user device **106**, the enterprise system **200**, and/or the external systems **202** and **204** are, include, or utilize virtual resources. In some cases, such virtual resources are considered cloud resources or virtual machines. Such virtual resources may be available for shared use among multiple distinct resource consumers and in certain implementations, virtual resources do not necessarily correspond to one or more specific pieces of hardware, but rather to a collection of pieces of hardware operatively coupled within a cloud computing configuration so that the resources may be shared as needed.

(54) As used herein, an artificial intelligence engine (e.g., an artificial intelligence system, artificial intelligence algorithm, artificial intelligence module, program, and the like) generally refer to computer implemented programs that are suitable to simulate intelligent behavior (i.e., intelligent human behavior) and/or computer systems and associated programs suitable to perform tasks that typically require a human to perform, such as tasks requiring visual perception, speech recognition, decision-making, translation, and the like. An artificial intelligence engine may include, for example, at least one of a series of associated if-then logic statements, a statistical model suitable to map raw sensory data into symbolic categories and the like, or a machine learning program. A machine learning program, machine learning algorithm, or machine learning module, as used herein, is generally a type of artificial intelligence including one or more algorithms that can learn and/or adjust parameters based on input data provided to the algorithm. In some instances, machine learning programs, algorithms, and modules are used at least in part in implementing artificial intelligence (AI) functions, systems, and methods.

(55) Artificial Intelligence and/or machine learning programs may be associated with or conducted by one or more processors, memory devices, and/or storage devices of a computing system or device. It should be appreciated that the AI algorithm or program may be incorporated within the existing system architecture or be configured as a standalone modular component, controller, or the like communicatively coupled to the system. An AI program and/or machine learning program may generally be configured to perform methods and functions as described or implied herein, for example by one or more corresponding flow charts expressly provided or implied as would be understood by one of ordinary skill in the art to which the subjects matters of these descriptions pertain.

(56) A machine learning program may be configured to implement stored processing, such as decision tree learning, association rule learning, artificial neural networks, recurrent artificial neural networks, long short term memory networks, inductive logic programming, support vector machines, clustering, Bayesian networks, reinforcement learning, representation learning, similarity and metric learning, sparse dictionary learning, genetic algorithms, k-nearest neighbor (KNN), and the like. In some embodiments, the machine learning algorithm may include one or more image recognition algorithms suitable to determine one or more categories to which an input,

such as data communicated from a visual sensor or a file in JPEG, PNG or other format, representing an image or portion thereof, belongs. Additionally or alternatively, the machine learning algorithm may include one or more regression algorithms configured to output a numerical value given an input. Further, the machine learning may include one or more pattern recognition algorithms, e.g., a module, subroutine or the like capable of translating text or string characters and/or a speech recognition module or subroutine. In various embodiments, the machine learning module may include a machine learning acceleration logic, e.g., a fixed function matrix multiplication logic, in order to implement the stored processes and/or optimize the machine learning logic training and interface.

(57) One type of algorithm suitable for use in machine learning modules as described herein is an artificial neural network or neural network, taking inspiration from biological neural networks. An artificial neural network can, in a sense, learn to perform tasks by processing examples, without being programmed with any task-specific rules. A neural network generally includes connected units, neurons, or nodes (e.g., connected by synapses) and may allow for the machine learning program to improve performance. A neural network may define a network of functions, which have a graphical relationship. As an example, a feedforward network may be utilized, e.g., an acyclic graph with nodes arranged in layers.

(58) A feedforward network (see, e.g., feedforward network **260** referenced in FIG. 2A) may include a topography with a hidden layer **264** between an input layer **262** and an output layer **266**. The input layer **262**, having nodes commonly referenced in FIG. 2A as input nodes **272** for convenience, communicates input data, variables, matrices, or the like to the hidden layer **264**, having nodes **274**. The hidden layer **264** generates a representation and/or transformation of the input data into a form that is suitable for generating output data. Adjacent layers of the topography are connected at the edges of the nodes of the respective layers, but nodes within a layer typically are not separated by an edge. In at least one embodiment of such a feedforward network, data is communicated to the nodes **272** of the input layer, which then communicates the data to the hidden layer **264**. The hidden layer **264** may be configured to determine the state of the nodes in the respective layers and assign weight coefficients or parameters of the nodes based on the edges separating each of the layers, e.g., an activation function implemented between the input data communicated from the input layer **262** and the output data communicated to the nodes **276** of the output layer **266**. It should be appreciated that the form of the output from the neural network may generally depend on the type of model represented by the algorithm. Although the feedforward network **260** of FIG. 2A expressly includes a single hidden layer **264**, other embodiments of feedforward networks within the scope of the descriptions can include any number of hidden layers. The hidden layers are intermediate the input and output layers and are generally where all or most of the computation is done.

(59) Neural networks may perform a supervised learning process where known inputs and known outputs are utilized to categorize, classify, or predict a quality of a future input. However, additional or alternative embodiments of the machine learning program may be trained utilizing unsupervised or semi-supervised training, where none of the outputs or some of the outputs are unknown, respectively. Typically, a machine learning algorithm is trained (e.g., utilizing a training data set) prior to modeling the problem with which the algorithm is associated. Supervised training of the neural network may include choosing a network topology suitable for the problem being modeled by the network and providing a set of training data representative of the problem.

Generally, the machine learning algorithm may adjust the weight coefficients until any error in the output data generated by the algorithm is less than a predetermined, acceptable level. For instance, the training process may include comparing the generated output produced by the network in response to the training data with a desired or correct output. An associated error amount may then be determined for the generated output data, such as for each output data point generated in the output layer. The associated error amount may be communicated back through the system as an



error signal, where the weight coefficients assigned in the hidden layer are adjusted based on the error signal. For instance, the associated error amount (e.g., a value between  $-1$  and  $1$ ) may be used to modify the previous coefficient, e.g., a propagated value. The machine learning algorithm may be considered sufficiently trained when the associated error amount for the output data is less than the predetermined, acceptable level (e.g., each data point within the output layer includes an error amount less than the predetermined, acceptable level). Thus, the parameters determined from the training process can be utilized with new input data to categorize, classify, and/or predict other values based on the new input data.

(60) An additional or alternative type of neural network suitable for use in the machine learning program and/or module is a Convolutional Neural Network (CNN). A CNN is a type of feedforward neural network that may be utilized to model data associated with input data having a grid-like topology. In some embodiments, at least one layer of a CNN may include a sparsely connected layer, in which each output of a first hidden layer does not interact with each input of the next hidden layer. For example, the output of the convolution in the first hidden layer may be an input of the next hidden layer, rather than a respective state of each node of the first layer. CNNs are typically trained for pattern recognition, such as speech processing, language processing, and visual processing. As such, CNNs may be particularly useful for implementing optical and pattern recognition programs required from the machine learning program. A CNN includes an input layer, a hidden layer, and an output layer, typical of feedforward networks, but the nodes of a CNN input layer are generally organized into a set of categories via feature detectors and based on the receptive fields of the sensor, retina, input layer, etc. Each filter may then output data from its respective nodes to corresponding nodes of a subsequent layer of the network. A CNN may be configured to apply the convolution mathematical operation to the respective nodes of each filter and communicate the same to the corresponding node of the next subsequent layer. As an example, the input to the convolution layer may be a multidimensional array of data. The convolution layer, or hidden layer, may be a multidimensional array of parameters determined while training the model.

(61) An exemplary convolutional neural network CNN is depicted and referenced as **280** in FIG. 2B. As in the basic feedforward network **260** of FIG. 2A, the illustrated example of FIG. 2B has an input layer **282** and an output layer **286**. However where a single hidden layer **264** is represented in FIG. 2A, multiple consecutive hidden layers **284A**, **284B**, and **284C** are represented in FIG. 2B. The edge neurons represented by white-filled arrows highlight that hidden layer nodes can be connected locally, such that not all nodes of succeeding layers are connected by neurons. FIG. 2C, representing a portion of the convolutional neural network **280** of FIG. 2B, specifically portions of the input layer **282** and the first hidden layer **284A**, illustrates that connections can be weighted. In the illustrated example, labels **W1** and **W2** refer to respective assigned weights for the referenced connections. Two hidden nodes **283** and **285** share the same set of weights **W1** and **W2** when connecting to two local patches.

(62) Weight defines the impact a node in any given layer has on computations by a connected node in the next layer. FIG. 3 represents a particular node **300** in a hidden layer. The node **300** is connected to several nodes in the previous layer representing inputs to the node **300**. The input nodes **301**, **302**, **303** and **304** are each assigned a respective weight **W01**, **W02**, **W03**, and **W04** in the computation at the node **300**, which in this example is a weighted sum.

(63) An additional or alternative type of feedforward neural network suitable for use in the machine learning program and/or module is a Recurrent Neural Network (RNN). An RNN may allow for analysis of sequences of inputs rather than only considering the current input data set. RNNs typically include feedback loops/connections between layers of the topography, thus allowing parameter data to be communicated between different parts of the neural network. RNNs typically have an architecture including cycles, where past values of a parameter influence the current calculation of the parameter, e.g., at least a portion of the output data from the RNN may be used as

feedback/input in calculating subsequent output data. In some embodiments, the machine learning module may include an RNN configured for language processing, e.g., an RNN configured to perform statistical language modeling to predict the next word in a string based on the previous words. The RNN(s) of the machine learning program may include a feedback system suitable to provide the connection(s) between subsequent and previous layers of the network.

(64) An example for a Recurrent Neural Network RNN is referenced as **400** in FIG. 4. As in the basic feedforward network **260** of FIG. 2A, the illustrated example of FIG. 4 has an input layer **410** (with nodes **412**) and an output layer **440** (with nodes **442**). However, where a single hidden layer **264** is represented in FIG. 2A, multiple consecutive hidden layers **420** and **430** are represented in FIG. 4 (with nodes **422** and nodes **432**, respectively). As shown, the RNN **400** includes a feedback connector **404** configured to communicate parameter data from at least one node **432** from the second hidden layer **430** to at least one node **422** of the first hidden layer **420**. It should be appreciated that two or more and up to all of the nodes of a subsequent layer may provide or communicate a parameter or other data to a previous layer of the RNN network **400**. Moreover and in some embodiments, the RNN **400** may include multiple feedback connectors **404** (e.g., connectors **404** suitable to communicatively couple pairs of nodes and/or connector systems **404** configured to provide communication between three or more nodes). Additionally or alternatively, the feedback connector **404** may communicatively couple two or more nodes having at least one hidden layer between them, i.e., nodes of nonsequential layers of the RNN **400**.

(65) In an additional or alternative embodiment, the machine learning program may include one or more support vector machines. A support vector machine may be configured to determine a category to which input data belongs. For example, the machine learning program may be configured to define a margin using a combination of two or more of the input variables and/or data points as support vectors to maximize the determined margin. Such a margin may generally correspond to a distance between the closest vectors that are classified differently. The machine learning program may be configured to utilize a plurality of support vector machines to perform a single classification. For example, the machine learning program may determine the category to which input data belongs using a first support vector determined from first and second data points/variables, and the machine learning program may independently categorize the input data using a second support vector determined from third and fourth data points/variables. The support vector machine(s) may be trained similarly to the training of neural networks, e.g., by providing a known input vector (including values for the input variables) and a known output classification. The support vector machine is trained by selecting the support vectors and/or a portion of the input vectors that maximize the determined margin.

(66) As depicted, and in some embodiments, the machine learning program may include a neural network topography having more than one hidden layer. In such embodiments, one or more of the hidden layers may have a different number of nodes and/or the connections defined between layers. In some embodiments, each hidden layer may be configured to perform a different function. As an example, a first layer of the neural network may be configured to reduce a dimensionality of the input data, and a second layer of the neural network may be configured to perform statistical programs on the data communicated from the first layer. In various embodiments, each node of the previous layer of the network may be connected to an associated node of the subsequent layer (dense layers). Generally, the neural network(s) of the machine learning program may include a relatively large number of layers, e.g., three or more layers, and are referred to as deep neural networks. For example, the node of each hidden layer of a neural network may be associated with an activation function utilized by the machine learning program to generate an output received by a corresponding node in the subsequent layer. The last hidden layer of the neural network communicates a data set (e.g., the result of data processed within the respective layer) to the output layer. Deep neural networks may require more computational time and power to train, but the additional hidden layers provide multistep pattern recognition capability and/or reduced output

error relative to simple or shallow machine learning architectures (e.g., including only one or two hidden layers).

(67) Referring now to FIG. 5 and some embodiments, an AI program **502** may include a front-end algorithm **504** and a back-end algorithm **506**. The artificial intelligence program **502** may be implemented on an AI processor **520**, such as the processing device **120**, the processing device **220**, and/or a dedicated processing device. The instructions associated with the front-end algorithm **504** and the back-end algorithm **506** may be stored in an associated memory device and/or storage device of the system (e.g., memory device **124** and/or memory device **224**) communicatively coupled to the AI processor **520**, as shown. Additionally or alternatively, the system may include one or more memory devices and/or storage devices (represented by memory **524** in FIG. 5) for processing use and/or including one or more instructions necessary for operation of the AI program **502**. In some embodiments, the AI program **502** may include a deep neural network (e.g., a front-end network **504** configured to perform pre-processing, such as feature recognition, and a back-end network **506** configured to perform an operation on the data set communicated directly or indirectly to the back-end network **506**). For instance, the front-end program **504** can include at least one CNN **508** communicatively coupled to send output data to the back-end network **506**.

(68) Additionally or alternatively, the front-end program **504** can include one or more AI algorithms **510**, **512** (e.g., statistical models or machine learning programs such as decision tree learning, associate rule learning, recurrent artificial neural networks, support vector machines, and the like). In various embodiments, the front-end program **504** may be configured to include built in training and inference logic or suitable software to train the neural network prior to use (e.g., machine learning logic including, but not limited to, image recognition, mapping and localization, autonomous navigation, speech synthesis, document imaging, or language translation). For example, a CNN **508** and/or AI algorithm **510** may be used for image recognition, input categorization, and/or support vector training. In some embodiments and within the front-end program **504**, an output from an AI algorithm **510** may be communicated to a CNN **508** or **509**, which processes the data before communicating an output from the CNN **508**, **509** and/or the front-end program **504** to the back-end program **506**. In various embodiments, the back-end network **506** may be configured to implement input and/or model classification, speech recognition, translation, and the like. For instance, the back-end network **506** may include one or more CNNs (e.g., CNN **514**) or dense networks (e.g., dense networks **516**), as described herein.

(69) For instance and in some embodiments of the AI program **502**, the program may be configured to perform unsupervised learning, in which the machine learning program performs the training process using unlabeled data, e.g., without known output data with which to compare. During such unsupervised learning, the neural network may be configured to generate groupings of the input data and/or determine how individual input data points are related to the complete input data set (e.g., via the front-end program **504**). For example, unsupervised training may be used to configure a neural network to generate a self-organizing map, reduce the dimensionality of the input data set, and/or to perform outlier/anomaly determinations to identify data points in the data set that falls outside the normal pattern of the data. In some embodiments, the AI program **502** may be trained using a semi-supervised learning process in which some but not all of the output data is known, e.g., a mix of labeled and unlabeled data having the same distribution.

(70) In some embodiments, the AI program **502** may be accelerated via a machine learning framework **520** (e.g., hardware). The machine learning framework may include an index of basic operations, subroutines, and the like (primitives) typically implemented by AI and/or machine learning algorithms. Thus, the AI program **502** may be configured to utilize the primitives of the framework **520** to perform some or all of the calculations required by the AI program **502**. Primitives suitable for inclusion in the machine learning framework **520** include operations associated with training a convolutional neural network (e.g., pools), tensor convolutions, activation functions, basic algebraic subroutines and programs (e.g., matrix operations, vector

operations), numerical method subroutines and programs, and the like.

(71) It should be appreciated that the machine learning program may include variations, adaptations, and alternatives suitable to perform the operations necessary for the system, and the present disclosure is equally applicable to such suitably configured machine learning and/or artificial intelligence programs, modules, etc. For instance, the machine learning program may include one or more long short-term memory (LSTM) RNNs, convolutional deep belief networks, deep belief networks DBNs, and the like. DBNs, for instance, may be utilized to pre-train the weighted characteristics and/or parameters using an unsupervised learning process. Further, the machine learning module may include one or more other machine learning tools (e.g., Logistic Regression (LR), Naive-Bayes, Random Forest (RF), matrix factorization, and support vector machines) in addition to, or as an alternative to, one or more neural networks, as described herein.

(72) FIG. 6 is a flow chart representing a method 600, according to at least one embodiment, of model development and deployment by machine learning. The method 600 represents at least one example of a machine learning workflow in which steps are implemented in a machine learning project.

(73) In step 602, a user authorizes, requests, manages, or initiates the machine-learning workflow. This may represent a user such as human agent, or customer, requesting machine-learning assistance or AI functionality to simulate intelligent behavior (such as a virtual agent) or other machine-assisted or computerized tasks that may, for example, entail visual perception, speech recognition, decision-making, translation, forecasting, predictive modelling, and/or suggestions as non-limiting examples. In a first iteration from the user perspective, step 602 can represent a starting point. However, with regard to continuing or improving an ongoing machine learning workflow, step 602 can represent an opportunity for further user input or oversight via a feedback loop.

(74) In step 604, data is received, collected, accessed, or otherwise acquired and entered as can be termed data ingestion. In step 606 the data ingested in step 604 is pre-processed, for example, by cleaning, and/or transformation such as into a format that the following components can digest. The incoming data may be versioned to connect a data snapshot with the particularly resulting trained model. As newly trained models are tied to a set of versioned data, preprocessing steps are tied to the developed model. If new data is subsequently collected and entered, a new model will be generated. If the preprocessing step 606 is updated with newly ingested data, an updated model will be generated. Step 606 can include data validation, which focuses on confirming that the statistics of the ingested data are as expected, such as that data values are within expected numerical ranges, that data sets are within any expected or required categories, and that data comply with any needed distributions such as within those categories. Step 606 can proceed to step 608 to automatically alert the initiating user, other human or virtual agents, and/or other systems, if any anomalies are detected in the data, thereby pausing or terminating the process flow until corrective action is taken.

(75) In step 610, training test data such as a target variable value is inserted into an iterative training and testing loop. In step 612, model training, a core step of the machine learning work flow, is implemented. A model architecture is trained in the iterative training and testing loop. For example, features in the training test data are used to train the model based on weights and iterative calculations in which the target variable may be incorrectly predicted in an early iteration as determined by comparison in step 614, where the model is tested. Subsequent iterations of the model training, in step 612, may be conducted with updated weights in the calculations.

(76) When compliance and/or success in the model testing in step 614 is achieved, process flow proceeds to step 616, where model deployment is triggered. The model may be utilized in AI functions and programming, for example to simulate intelligent behavior, to perform machine-assisted or computerized tasks, of which visual perception, speech recognition, decision-making, translation, forecasting, predictive modelling, and/or automated suggestion generation serve as

non-limiting examples.

(77) With reference to the general architecture, features, and function of AI engines as described above, such as neural networks and other machine learning algorithms, the present subject matter is also directed to applications for creating, maintaining, and utilizing a meta-database formed from data stored in multiple, separate, or distinct source databases. Generally, the meta-database and/or associated hardware and software allow for a user to efficiently determine parameters useful for modeling from the source databases. It should be appreciated that, in various embodiments disclosed herein, a user may be able to ascertain such parameters and which databases of the source databases include data relevant to such parameters without directly opening or interfacing with the source databases. In some embodiments, the parameters determined from the meta-database may be particularly suitable to efficiently utilize an AI model (e.g., generating an inference from an AI algorithm) and/or to more efficiently train the AI model.

(78) In an exemplary embodiment and as illustrated schematically with reference to FIG. 7, a system architecture **700** is generally suitable to initially generate and/or subsequently maintain a meta-database **708** representing data from a plurality of source databases **702**. In the embodiment of FIG. 7, two databases (i.e., first database **704** and second database **706**) are illustrated for the purposes of ease of discussion. However, it should be appreciated that the system **700** may be configured to interface with any number of additional source databases **702**. Particularly, several embodiments herein may be utilized with a large number of source databases **702**, such as hundreds, thousands, tens-of-thousands, or more.

(79) Furthermore, the size, aspect ratio, number of circles (indicating one or more data points or database elements) in the source databases **702** generally represent the amount of data stored in the respective source databases **702** and the configuration of such data. For instance and as illustrated, a size of the schematic box associated with the first database **702** is larger than a size of the box associated with the second source database **706**. However, it should be appreciated that the source databases **702** may include more than the illustrated, exemplary data. Particularly, the one or more of the source databases **702** may include voluminous amounts of data that may be useful for modeling purposes. Additionally or alternatively, the source databases **702** may be designated by an administrator of the system **700**. In some embodiments, a user of the system **700** may add one or more additional databases or remove one or more administrator selected databases from the source databases **702**. In some embodiments, all of the source databases **702** may be selected by a user of the system **700**.

(80) The system **700** may include a source programming interface **712** for interfacing with the source databases **702**. The source databases **702** generally include data representing a number of variables (some of which are useful for modeling, statistical analysis, or the like for both general and for particular applications). The meta-database programming interface **714** allows for interfacing with the meta-database **708**. A key variable repository module (KVR module **710**) operably couples the source databases and the meta-database. For example, source data from the source databases **702** may be communicated to the KVR module **710**, and the KVR module **710** may generate data or update corresponding data in the meta-database **708**. The KVR module **710** may generally include or be associated with one or more AI programs (e.g., a scanner algorithm **716** and profiler algorithm **717**). The AI programs may be used to generate the meta-database **708** one or variables, probability distributions for the variables, or associations between the variables. More particularly, the AI programs may be configured to implement a number of AI algorithm instructions (such as a portion of the associated instruction to all of the associated instructions), AI subroutines, and the like as described herein and in more detail below. A key interface **732** allows for searching the meta-database for at least one of a variable, a probability distribution for a variable, or a produced association between variables.

(81) Thus, FIG. 7 illustrates a system architecture of the exemplary system **700** with programs, subprograms, and related or associated programs that are suitable for implementing various of the

elements of methods, steps, instructions, and the like discussed herein. However, the following discussion is equally applicable to other suitable configurations of systems. In various embodiments, one or more of the schematic elements may be combined or arranged alternatively. For example, the interface programs **712**, **714** and/or the key interface **732** or a portion thereof may be included in the key variable repository module **710** and/or the databases **702**, **708**. Further, any of the interface **712**, **714**, **732** may be formed together as a single program or may be arranged as a subsystem or assembly including multiple subroutines, programs, and the like.

(82) As shown in FIG. 7, the meta-database **708** may utilize less storage space than the storage space used to store the source databases **702**. This can be realized by comparing the areas of the schematic box associated with the first database **704** and the schematic box associated with the second database **706** with the area of the schematic box associated with meta-database **708**. This relationship is further represented by the difference in the number of data-representing circles included in the source databases (28 circles) and the number of data-representing circles included in the meta-database (16 elements, with only 8 data-representing circles equivalent to the data included within the source databases **702**). For example and in several embodiments, the meta-database **708** may be stored on a first portion of a memory device(s) and/or a non-transitory storage device(s) associated with the system **700**, and the source databases **702** may be stored on a second portion the memory device(s) and/or the non-transitory storage device(s). Furthermore, the first portion (e.g., meta-data) may be allocated to substantially less space of the memory device(s) and/or the non-transitory storage device(s) than space allocated to the second portion (e.g., source data).

(83) For instance, various embodiments of the system **700** may be suitable to summarize source data (e.g., columns and rows of elements, numbers, strings and the like) of a source databases associated with 100 s of megabytes (MB) or even gigabytes (GB) into a few MB. Additionally or alternatively, the system **700** may form or maintain the meta-database **708** that summarizes the source data of the source databases **702** (e.g., data associated multiple, individual source databases **702**). For example, source data associated with 100 s of GB or even terabytes (TB) across a few or numerous source databases **702** may be summarized in 100 s of MB.

(84) Thus, the system **700** or components thereof (such as the meta-database **708**, the KVR module **710**, and/or key interface **732**) are able to reduce the amount of data requiring processing and/or consideration for modeling or statically analysis of some or all of the source databases **702** themselves, as explained below with reference to the scanner algorithm **716**. Furthermore, embodiments of the system **700** may identify variables particularly suitable for modeling or statistical analysis of the source data, the source databases **702**, and/or portions thereof, as explained below with reference to the profiler algorithm **717**. As such, the system **700** or components thereof may provide increased efficiency in the selection of data (e.g., one or more source databases **702**) or variables (portions of the source database(s) **702**, e.g., particular columns of data) for subsequent statistical analysis, modeling, or model training in a future process, represented by schematic block **740**. It should be appreciated that the identifying which source databases **702** or portions thereof include data useful for future processing reduces the time required and/or computational power necessary to run the future process **740**. In various embodiments, the future process **740** may include a machine learning program, and the identified source databases and/or variables may be input used to producing an inference from the machine learning program and/or train the same, as generally explained herein. Further, a user of the system **700** is not required to download and open the source databases **702** or initially examine the associated data, elements, and the like to determine where useful data for modeling/analysis is located. Thereby, several embodiments disclosed herein may reduce ancillary bandwidth usage in pre-processing and/or selecting input data or databases for future modeling or model training, e.g., in one or more future processes **740**.

(85) It should be appreciated that the system **700**, meta-database **708**, and/or key interface **732** may

provide the user(s) a single place or application to determine what useful variables the source databases **702** are associated with and/or if there are conditional relationships or correlations between various variables. For instance and when determine what data to input into a future process **740**, e.g., an AI algorithm, a user does not have to theorize or guess the connections between data and what portions of the data may be useful. A user may thereby avoid unnecessarily operating the future process **740** on data that is unlikely to produce accurate or desired results. In many embodiments, determining the ideal source databases **702** or elements thereof for use with the future process **40** may increase the computational speed of the future process, may reduce the computational power required by the future process **40**, may increase the accuracy of the output or inference of the future process **40**, and/or may increase the computation power available for other processes utilizing processing components shared with the future process **740**.

(86) In some embodiments, the system **700**, meta-database **708**, and/or key interface **732** may provide the user(s) a single place or application to determine what useful variables the source databases **702** are associated with for training and/or if there are conditional relationships or correlations between various training variables. Additionally or alternatively, the AI algorithm **740** may require or be capable of being trained utilizing training data (e.g., previous input data, versions of source databases, and the like associated with known outputs, acceptable outputs, and the like). In some embodiments, the AI algorithm may include a machine learning algorithm requiring training or configured such that the machine algorithm may be trained to increase an accuracy, efficiency, or processing speed when used to generate an inference. In some embodiments, the AI algorithm **740** may include at least one of a deep neural network, a CNN, a front-end algorithm, a back-end algorithm, statistical models or machine learning programs such as decision tree learning, associate rule learning, recurrent artificial neural networks, support vector machines, and the like.

(87) In various embodiments, the meta-database **708** and/or key interface **732** may be processed on one or more servers, processing devices, controllers, and other suitable hardware that is independent from the component(s) utilized to open or interface with the source databases **702**. Thus, the risk of a user submitting a bad query, request, instruction, etc. to the programs used in association with the source databases **802** is substantially reduced, thereby also lowering the risk of crashing, slowing down, or otherwise impacting the processing components associated with the source databases **702** and potentially other process of the enterprise system **200**, associated systems, or local devices (e.g., the mobile device **104**, computing device **106**, the agent devices **212**, and/or the enterprise computing system **206**).

(88) In some embodiments, the KVR module **710**, the scanner algorithm **716**, and/or the profiler algorithm **717** may be associated with instruction related to one or more a deep neural network, a CNN, a front-end algorithm, a back-end algorithm, statistical models or machine learning programs such as decision tree learning, associate rule learning, recurrent artificial neural networks, support vector machines, and the like as described herein. While exemplary embodiments of suitable AI configurations are discussed below, other embodiments of the KVR module **710**, the scanner algorithm **716**, and/or the profiler algorithm **717** may include other, suitable configurations of AI programs such as configurations of an AI system similar to the basic feedforward network **260**, the RNN **400**, the AI program **502**, the front-end algorithm **504**, and/or the back-end algorithm **506** of FIGS. 2A, 2B, 4, & 5, respectively. It should be appreciated that different AI systems generally suitable to perform the required task of the program and/or instructions thereof may produce more accurate or faster results and/or reduce the processing power required to perform the task (e.g., AI systems generally suitable for data type recognition and summarization may be particularly suitable for use with the scanner algorithm **716**, and AI systems generally suitable for categorization of data types, pattern recognition, statistical modeling, and/or determining correlation or causation may be particularly suitable for use with the profiler algorithm **717**). As an example, a machine learning algorithm may be utilized in the profiler algorithm **717** to recognize the type of data of each element in the meta-database **708**, determine variables, and/or determine associations between

variables, as machine learning algorithms can be trained to recognize patterns).

(89) Certain types of AI programs suitable for use with the KVR module **710**, the scanner algorithm **716**, and/or the profiler algorithm **717** generally require training, e.g., machine learning algorithms, support vector machines, and the like. An exemplary procedure for training a machine learning algorithm for recognizing variables of the meta-database **708** is described below (e.g., a portion of the instructions associated with the profiler algorithm). However, it should be appreciated that a similar procedure may be utilized with respect to training other AI systems to perform the same task, similar tasks, or alternative tasks associated with one or more of the KVR module **710**, the scanner algorithm **716**, and/or the profiler algorithm **717**, as described herein.

(90) The machine learning algorithm may be trained to identify important variables in the meta-database **708**, and thus the plurality of databases **702**, using real modeling, statistical analysis, and/or the like (e.g., prior identification of variables and data of the plurality of databases for use in the same). In some embodiments, significant and/or important variables used for such purposes (e.g., in a previous or historical model) may be identified as correct or favorable variable candidates for the purposes of training the machine learning algorithm. If the variables were not useful or not used in the previous model, such variables may be identified as incorrect or unfavorable variable candidates for the purposes of training the machine learning algorithm.

Furthermore, the input for training the machine learning algorithm can include a version, historical record, or the like of the source databases **702** or a portion thereof. It should be appreciated that version of the source databases **702** may be the same as used when producing the previous model or an approximation of the same (e.g., a version of the source databases **702** or a portion thereof at approximately the same time and/or including substantially the same data). The version of the source databases **702** used for training the machine learning algorithm may be supplemented with additional data needed to perform supervised learning. Supervised learning is a machine learning training approach that is defined by its use of labeled datasets. These datasets are designed to train or “supervise” algorithms into classifying data or predicting outcomes accurately. Using labeled inputs and outputs, the machine learning algorithm can measure its accuracy and learn over time. Both satisfactory and unsatisfactory outcome examples may be included in training, as the machine learning algorithm learns from both types of scenarios. Furthermore, ongoing training may be periodically performed on the machine learning algorithm using new or additional examples, such as user provided feedback (positive and/or negative) with respect to inferences (i.e., variables determined from the meta-database) during use. Thus, periodic ongoing training can further improve the efficiency and effectiveness of the machine learning algorithm for user interaction.

(91) In some embodiments, at least a portion of the system **700** and/or the KVR module **710** may be implemented on the processing device **120**, the processing device **220**, the AI processor **520**, and/or one or more dedicated processing device or processing devices associated with the system **700**. In some embodiments, various instructions associated with the KVR module **710**, such as the scanner algorithm **716** and/or the profiler algorithm **717** may be implemented on the AI processor **520**, and/or one or more dedicated processing device or processing devices associated with the system **700**. In various embodiments, instructions associated with the system **700** and/or components or subprograms thereof may be stored in an associated memory device and/or storage device of the system (e.g., memory device **124** and/or memory device **224**) communicatively coupled to the associated processor(s). Additionally or alternatively, the system **700** may include one or more memory devices and/or storage devices for processing use and/or including one or more instructions necessary for operation of the system **700**, the KVR module **710**, the scanner algorithm **716**, and/or the profiler algorithm **717**.

(92) Referring now to FIG. **8**, an exemplary embodiment of a method **800** is illustrated for maintaining a meta-database representing a plurality of source databases. Maintaining, as used herein and in reference to a meta-database, includes the initial creation of unless otherwise specified. The method **800** may be utilized with the system **700**, similarly, or suitably configured



systems to generate the meta-database **708** or an equivalent centralized repository for the storage of such data. In various embodiments, the method **800** may include elements, steps, instructions, etc. that are associated with one or more AI algorithms. For instance, method elements generally associated with tasks suitable for one or more machine learning algorithms (e.g., identifying representative data from the source database(s), generating granular data types for at least a portion of the data of the meta-database, determining variables indicative of the data and/or a portion the data of the meta-database, and/or producing an association between variables) may be included in the instructions of programs and subprograms corresponding to such tasks in the system architecture, e.g., the schematic logic flow for the corresponding system. In some embodiments and also in reference to FIG. 7, such method elements associated with the AI algorithm(s) may correspond to instructions for one or more of the KVR module **710**, the scanner algorithm **716**, and/or the profiler algorithm **717**. However, the method **800** of FIG. 8 is equally applicable to other system architectures capable, suitable, etc. of performing or executing such method elements.

(93) As shown in FIG. 8, the method may include (method element **852**) communicating, from a source programming interface, data representative of a plurality of source databases to an artificial intelligence program. With reference also to exemplary system **700** of FIG. 7, the source programming interface **712** may include one or more subprograms and/or be associated with instructions allowing the KVR module **710** to communicate with each of the source database **102**. For instance, the source programming interface **712** may include one or more drivers suitable or capable of interfacing with each application and/or storage format of the respective source database **702**. It should be appreciated that as used here, and without, the data representative of the source databases **702**, compressed data, and meta-data as well as variables, parameters, and the like produced from the meta-data may include information relative to, be associated with, or somehow linked to the source database(s) **702** containing the original data. For example, if the system **700** indicates that source data **720** is useful as input to the future process **740**, information associated with identifying at least the first database **704**, the second database **706**, and the position of source data **720** within the respective databases **704**, **706** may be provided to the user and/or stored with such elements of the meta-database **708** (e.g., database element location information may generally be propagated with the individual data points throughout various transformation, manipulations, and the like described herein).

(94) Method element **854** may include compressing the data representative of the plurality of source databases. In one embodiment, the scanner algorithm **716** may include one or more subprograms and/or be associated with instructions allowing the scanner algorithm **716** to identify a representative set of data for each database (e.g., first database **704** and second database **706**) of the source databases **702**. Thus, compressing the data of the source databases, as used herein, may generally include summarizing the data of the source databases **702** by identifying a subset of data points that will be recorded in the meta-database **708**. The subset of data produced in the meta-database **708** generally or substantially represents the data of each respective source database (e.g., first and second databases **704** and **706**).

(95) Compressing the data of the source databases **702** and/or the scanner algorithm **716** may be associated with instructions to initially oversample data from each of the source databases **702**. For instance, data may be sampled from each of the source databases **702** from all applicable time periods represented within the source databases **702**. Once the data has been sampled, the scanner algorithm **716** may be configured to establish scanning categoricals and organize the oversampled input data into the respective scanning categoricals including similar data. For instance, the scanning algorithm may place data including similar significant features within an associated scanning categorical. For instance, individual scanning categoricals may include numbers within significant ranges (e.g., 0-10, 10-20), numbers with having a significant number of digits (e.g., numbers capable of being telephone numbers, numbers that may represent money with two significant figures following a decimal point such as 500.00, numbers suitable for time stamps,

etc.), numbers and/or character strings having features associated identification indicators (e.g., strings with numbers and letters, dashes, internal divisions, etc.), strings including digital communication characteristics (e.g., strings including “.com,” “.net,” “@,” etc.), and the like.

(96) In various embodiments, the scanning algorithm **716** may utilize an AI program(s) in order to establish some or all of the scanning categoricals of the scanner algorithm **716** and/or sort the oversampled data into the appropriate scanning categoricals (e.g., categoricals determined by the AI program, categoricals determined by the administrator of the system **700**, and/or categoricals received as input from a user of the key interface **732**). Suitable AI programs for use with the scanner algorithm **716** may include one or more machine learning programs, neural networks, CNNs, support vector algorithms, deep neural networks, decision tree learning, associate rule learning, or AI programs capable of establishing some or all of the scanning categoricals of the scanner algorithm **716** and/or sort the oversampled data into the appropriate scanning categoricals. In some embodiments, the input data from the source database may be sampled (e.g., oversampled) numerous times, such as 5 or more, 10 or more, or 20 or more times. The scanning algorithm **716** and/or an AI program thereof may be configured to form the compressed data from each of the individual samples. For example, numbers suitable to averaging may be averages, a representative element may be chosen for strings, etc.

(97) In some embodiments, system **700** may be configured to run the scanner algorithm **716** autonomously or semi-autonomously. For instance, when a time since the system **700** has implemented the scanner algorithm **716** at least one of the source databases **702** is greater than a predetermined update interval, the system **700** automatically run the scanner algorithm. Additionally or alternatively, a user of the key interface **732** may communicate a signal or cause a signal to be communicated which deploys the scanner algorithm **716**.

(98) Referring still to the embodiment of FIG. **8**, and for some embodiments FIG. **7**, method element **856** may include communicating, to a meta-database programing interface, the compressed data and synchronizing the data of the meta-database with the compressed data. For example, the meta-database programing interface **714** may include one or more subprograms and/or be associated with instructions allowing the KVR module **710** and/or the meta-database programing interface **714** to communicate with the meta-database **708**. For instance, the meta-database programing interface **714** may include one or more drivers suitable or capable of interfacing with the application and/or storage format of the meta-database **708** such that the meta-database programing interface **714** generates the compressed data and/or data representative of the source databases **702**. Such compressed data may generally be determined and communicated from the scanner algorithm **716**. Generally, synchronizing data of the meta-database (meta-data) with the compressed data may include adding newly discovered database elements, removing old meta-data from the previous operation of the scanner algorithm associated with elements now missing from the associated source database(s) **702**. In some embodiment, the meta-database programing interface **714** and/or scanner algorithm **716** may designate or otherwise flag significant changes to previously identified elements and/or meta-data. In some embodiments, the meta-database programing interface **714** and/or meta-database **708** may include or be associated with a Python script or the like, which allows user and administrator web and server functionality.

(99) The method may include generating, utilizing the artificial intelligence program, granular data types for at least a portion of the data of the meta-database (e.g., method element **858**). As illustrated with reference to the example of FIG. **7**, the profiler algorithm **717** may include one or more subprograms and/or be associated with instructions allowing the profiler algorithm **717** to generate, based on the meta-data, granular data types for at least a portion of the meta-data. Generally, the profiler algorithm **717** may communicate with the meta-database programing interface **714** to receive the data of the meta-database **708** for subsequent processing. Thus, the system **700** allows for the scanner algorithm **716** that generates meta-data and the profiler algorithm **717** that analyzes the meta-database **708** to be ran sequentially and/or at the option of the

administrator or user. Thus, instructions that require substantial processing power (e.g., any steps requiring AI programming) may be scheduled for implementation at times that are convenient. In some embodiments, the scanner algorithm **716** may directly communicate the compressed data to the profiler algorithm **717** (where the compressed data is further processed) and the compressed data (meta-data) may be subsequently communicated from the profiler algorithm **717** to the meta-database programming interface **714** along with parameters determined by instructions associated with the profiler algorithm **717**.

(100) The method **800** may include (see, e.g., method element **858**) generating, utilizing the AI program, granular data types for at least a portion of the meta-data. In several embodiments, the profiler algorithm **717** may include one or more subprograms and/or be associated with instructions that, when implemented, generate the granular data types and associate such data types with the appropriate meta-data. In various embodiments, the profiler algorithm **717** may utilize an AI program(s) in order to determine at least a portion of the granular data types and/or sort or associate the meta-data with the appropriate granular data types. In some embodiments, suitable granular data types may represent, for example, types of devices associated with telephone numbers (e.g., landline, mobile phone, web-browser telephone application, local PC telephone application, etc.), different types of statistically significant profile distributions associated with portions of the metadata (e.g., Bernoulli distributions, uniform distributions, binomial distributions, normal distributions, Poisson distributions, exponential distributions, and the like), physical addresses; virtual locations or associations (e.g., an IP address, hash, email, etc.), names (e.g., first, last, middle, full, aliases, etc.), database element characteristics (e.g., signed floating point real numbers, zero-inflated signed floating point real numbers, integers, strings, etc.). While the above granular data types are provided for example, it should be appreciated that the granular data types may generally be determined or associated with characteristics of the source databases **702** and/or the future process **740**.

(101) Suitable AI programs for use with the profiler algorithm **717** may include one or more machine learning programs, neural networks, CNNs, support vector algorithms, deep neural networks, decision tree learning, associate rule learning, or a similar AI algorithm capable of establishing some or all of the granular data types and/or associate the meta-data with the appropriate granular data types. Additionally or alternatively, generating the granular data types and associated the meta-data with the same may include or be associated with instructions representing a field-by-field analysis. Additionally or alternatively, the instruction to generate granular data types for at least a portion of the data of the meta-database may include instructions to analyze properties of the data of the meta-database stored as at least one of integer, floating point, date, or text to detect at least one of categorical variables, binary variables, dates with and without times, timestamps with and without dates, numerically encoded categorical variables, true floating point and integer values, ID numbers, strings, zip codes, phone numbers, or IP addresses.

(102) Method element **860** may include determining, utilizing the artificial intelligence program, a plurality of variables indicative of at least a portion of the data of the meta-database. In several embodiments, the profiler algorithm **717** may include one or more subprograms and/or be associated with instructions that, when implemented, generate the variables (variables depicted as triangles **726**, **728**, **730**, **734**) from the meta-data. Particularly, the identified variables are generally produced or linked from portions of the meta-data (associated with the data of source databases **702**) having the most use for future processing, e.g., a reduction in the time required and/or computational power necessarily associated with running the future process **740**. Thus, the system may indicate that source data **718**, **720**, **722**, and **724** may be useful as part of the input to the future process **740**. For instance, at least one of, such as all of source data **718**, **720**, **722**, and **724** may include a superset of functional column types/data of the source databases **702** that are more useful to data scientists. Additionally or alternatively, the profiler algorithm **717** may be configured to generate a warning communication if the data associated with a variable categorized as important

changes to a substantial degree, as compared to meta-data utilized to generate such variable previously.

(103) In various embodiments, the profiler algorithm **717** may utilize an AI program(s) in order to determine at least a portion of the variables and/or sort or associate the meta-data with the appropriate variables. Suitable AI programs for use with the profiler algorithm **717** may include one or more machine learning programs, neural networks, CNNs, support vector algorithms, deep neural networks, decision tree learning, associate rule learning, or, similar AI algorithms capable of determining some or all of the variables and/or associate the meta-data with the appropriate variable(s).

(104) For instance and as shown in FIG. 7, variable **728** may be determined from (e.g., may be the same value, approximately the same value, and/or the result of one or more operations performed) on meta-data **722** representing source data **722** of the source databases **702**. Similarly, variable **730** may be determined from meta-data **724**. With respect to variable **726**, the profiler algorithm **717** may be configured to indicate one of source data **718** and **720**, which may be heavily inter-correlated, are redundant for the purposes of determining variable **726**. Such result may indicate to a user of the system **700** that source data **718** or source data **720** may be excluded from the future process **740** without substantially reducing the accuracy of the inference and/or training. Particularly, the elimination of redundant data in the input to the future process **740** may improve the efficiency of the same.

(105) In some embodiments, the profiler algorithm **717** may be configured to indicate portions, fields, columns, etc. of the source databases that include blank entries, are missing entries, and/or contain data that is mostly incomplete. For example, the profiler algorithm **717** may be associated with instructions to collect information about the completeness of meta-data (e.g., meta-data **725** representing source data **725**) relevant to a potential variable and, when the completeness of the meta-data is less than a predetermined threshold, eliminate the meta-data relevant to the potential variable from the meta-database **708**. Thus, the profiler algorithm **717** may be configured to remove meta-data **725** (e.g., via the meta-database interface **714**) from the meta-database. Thus, subsequent processes performed on the meta-database **708** may be faster or require less computational resources due to the reduction in elements of the meta-database.

(106) In some embodiments, the profiler algorithm **717** may be configured to determine one or more combined variables, each combined variable representing data associated with two or more distinct variables. Particularly, various combined variables determined by the profiler algorithm **717** may require input from sparse portions of the source database(s) **702** relevant to the distinct variables. In various embodiments, the profiler algorithm **717** may recognize when distinct meta-data variables are related from the training of the associated AI algorithm(s). As an example, variable **728** may represent data indicating or otherwise associated with a time zone, and variable **730** may represent data indicating or otherwise associated with a latitude within the United States. Based on prior training of the AI program(s), an inference may be produced identifying a state represented by the combination of variables (e.g., combined variable **734** of the meta-database **708** of FIG. 7). In a different situation, the source databases **702** may already include source data relevant to each of variables **728**, **730**, and **734**. Thus, additionally or alternatively, the profiler algorithm **717** may be configured to produce one or more associations between variables. For example, the profiler algorithm **717** may identify relationship **736** between variable **728** and variable **734** and/or may identify relationship **738** between variable **730** and variable **734**. For example, an AI program(s) associated with the profiler algorithm **717** may produce an inference of the association(s) **736**, **738** based at least in part on adequate training of the model.

(107) In some embodiments, an association produced between two or more variables (e.g., association **736** and/or association **738**) represents or approximates a causal relationship between such variables. Such casual relationships may be determined between variables associated with a single source database **702** or data stored across multiple source databases **702**. In some

embodiments, determining such a causal relationship may include instructions associated with determining at least one parametric correlation between at least two variables, a non-parametric correlation between at least two variables, a Pearson correlation between at least two variables, a Spearman correlation between at least two variables, a Spearman correlation between at least two variables, a Kendall's Tau correlation between at least two variables, mutual information between at least two variables, or an uncertainty coefficient between at least two variables. In some embodiments, an AI program(s) of the profiler algorithm **717** may be used in the process of determining a causal relationship between variables. For example, a deep neural network may be trained to determine or approximate such a causal relationship and/or coefficients for determining the same, such as some or all of the proceeding. It should be appreciated that the AI program may be capable of approximating the causal relationship and/or coefficients or parameters representing the relationship or used to establish the relationship faster and/or require less computing power than the traditional mathematical operations to determine the same. Thus, the profiler algorithm **717** may expedite representing or approximating causal relationships between variables of the meta-database **708** in a pre-processing stage. Other AI programs that may be used, at least in part, by the profiler algorithm **717** to determine casual relationships between variables include machine learning programs, neural networks, CNNs, support vector algorithms, decision tree learning, associate rule learning, or, similar AI algorithms suitable for producing causal inferences based on input data.

(108) In some embodiments, the profiler algorithm **717** may generate a probability distribution for the meta-data associated with at least one variable, such as all of the variables identified by the profiler algorithm **717** and/or included in the meta-database **708**. In some embodiments, the profiler algorithm **717** may utilize an appropriate AI program(s) in order to produce or approximate probability distributions for the meta-data associated with variable(s) of the meta-database. Additionally or alternatively, generating the probability distribution for each variable may be associated with instruction to apply a function of the granular data type for the variable, such as a function including at least one of a density estimate, discrete distribution, or sample.

(109) As shown in FIG. **8**, method element **866** may include communicating, to the meta-database programming interface, the compressed data and modifying the meta-database to include the probability distribution generated for each variable and the at least one association produced between the at least two variables. For example, the profiler algorithm **717** may communicate the meta-data to the meta-database interface **714** to update the meta-data. More particularly, the meta-database interface **714** may alter the meta-data to reflect any changes that are indicated by the profiler algorithm **717**. For example, mostly empty meta-data **725** may be removed from the meta-database **708** (see crossed-out circles **725** at the bottom, left of FIG. **7**). In some embodiments, the profiler algorithm **717** may be configured to communicate to the meta-database interface **714** any variables, associations between variables, probability distributions, casual relationships, and the like determined using the steps associated with the profiler algorithm **717**.

(110) As shown in FIG. **7**, the system **700** may include the key interface program (key interface **732**) associated with instructions allowing a user to search the meta-database **708** for at least one of a variable, a probability distribution for a variable, or a produced association between variables. In some embodiments, a user may be able to alter the source databases **702** available to the KVR module **710** module for processing or specify portions, columns, etc. of source databases **702** to summarize and other portions to exclude. Thus, key interface **732** may be communicatively coupled to the KVR module **710** in order to communicate and/or alter such parameters. Further, the key interface **732** may communicate a signal or otherwise cause system **700** to implement the scanner algorithm **716** and/or profiler algorithm **717** with the user specified parameters.

(111) Generally, a user may interact and/or enter search queries within the key interface **732** and receive information indicating where data relevant to such queries are stored in the source databases **702**. For example, a user may review the variables identified by the KVR module **710**

and input a variable(s) of interest. The key interface **732** may be configured (e.g., via associated computer implementable instructions) to indicate a subset of the source databases **702** and or portions of the same including data relevant to the variable(s) of interest. In some embodiments, the key interface **732** may execute instructions to produce one or more interactive visualizations of the meta-data indicative of the variable(s) of interest, the association(s) between variables of interest, and/or the probability distribution of the variable(s) of interest. In some embodiments, the key interface **732** may be configured to receive weight coefficients from the user in order to alter the visual representation produced by the key interface **732** and/or associated instruction implemented by the same. For example, a user may increase a gain in order to better visualize certain parameters.

(112) Referring now to FIG. **9**, an exemplary embodiment of a method **900** is illustrated for reducing the time to train a model, such as an artificial intelligence program, a machine learning algorithm, or the like, which require or could benefit from training. In general, method **900** may include the same or similar steps as explained above and in reference to FIG. **8**. For example, method elements **952-966** generally correspond to method elements **852-866**. However, with reference to FIG. **9** and in some examples, the plurality of source databases may be utilized to train an AI algorithm (e.g., AI algorithm **740**). Thus, embodiments of the present disclosure may additionally or alternatively include generating a training meta-database that represents training data from the plurality of source databases and using the same to determine important training variables and associated probability distributions, associations between variables, and/or interactive graphical interfaces between variables. In such embodiments, data in the plurality of source databases may include training data, and such training data may be compressed and stored in the training meta-database. Generally, training variables, probability distributions, and associations for the same may be produced and stored in the training meta-database, as described above with respect to the meta-database and method of FIG. **8**.

(113) Thus, some or all of the steps of FIG. **9**, may be utilized to train an AI algorithm with a suitable system (e.g., to train the AI algorithm **740** using a system the same, similar to, etc. system **700**). Additionally or alternatively, as shown in method element **968**, the method **900** may include receiving a user communicated input and searching the training meta-database, based on the user communicated input, for at least one of a training variable, a probability distribution for a training variable, or a produced association between training variables. For example, a user may communicate with the key interface **732** and search for variables, probability distributions, and associations, as described herein, useful for training the AI algorithm **740**. In some embodiments, the method **900** may include identifying a searched subset of the training data from the source databases associated with the at least one training variable searched for based on the user input (e.g., method element **970**). In additional or alternative embodiments, the method **900** may include training the model utilizing the searched subset of training data from the source databases. Thus, the searched subset of training data may reduce the time required to train the AI algorithm **740**.

(114) Particular embodiments and features have been described with reference to the drawings. It is to be understood that these descriptions are not limited to any single embodiment or any particular set of features. Similar embodiments and features may arise or modifications and additions may be made without departing from the scope of these descriptions and the spirit of the appended claims.

## Claims

1. A system for training a model from a subset of training data representing a plurality of source databases: the system comprising: a computer including one or more processor and at least one of a memory device and a non-transitory storage device, wherein the one or more processor executes: a source programming interface configured for interfacing with the plurality of source databases, the plurality of source databases including training data associated with a plurality of training variables, wherein a decentralized storage of the training data results in increased time required to

train the model using the training data; a meta-database programming interface configured for interfacing with a meta-database; a key variable repository module configured to operably couple the plurality of source databases and the meta-database, the key variable repository module including an artificial intelligence program comprising: a scanner algorithm configured to perform steps including: communicate with the source programming interface to receive the training data of the source databases; compress the training data of the source databases; communicate with the meta-database programming interface and synchronize the meta-database with the compressed training data of the source databases; a profiler algorithm configured to perform steps including: communicate with the meta-database programming interface to receive the training data of the meta-database; generate, based on the training data of the meta-database, granular data types for at least a portion of the training data of the meta-database; determine a plurality of training variables indicative of at least a portion of the training data of the meta-database and generate, for each training variable, a probability distribution; produce at least one association between at least two training variables of the plurality of training variables; and communicate with the meta-database programming interface to modify the meta-database to include the probability distribution generated for each training variable and the at least one association produced between the at least two training variables; and a key interface configured to, based on a communicated user input, search the meta-database for at least one of a training variable, a probability distribution for a training variable, or a produced association between training variables; and a model configured to, using artificial intelligence programming and inference data, generate an inference, wherein the model requires training prior to generating the inference, and wherein using a subset of training data from the source databases and associated with the at least one training variable reduces the time required to train the model to generate the inference.

2. A system for training a model from a subset of training data representing a plurality of source databases, the system comprising: a computer including one or more processor and at least one of a memory device and a non-transitory storage device, wherein the one or more processor executes artificial intelligence computer-readable instructions to: receive the training data representative of the plurality of source databases; identify a representative set of training data for each source database of the plurality of source databases, wherein each set of training data represents the training data of the respective source database; generate, in a training meta-database, the representative training data sets for the plurality of source databases; generate granular data types for at least a portion of the training data of the training meta-database; determine a plurality of training variables indicative of at least a portion of the training data of the training meta-database; generate a probability distribution for each training variable of the plurality of variables; produce at least one association between at least two training variables of the plurality of training variables; based on a communicated user input, search the training meta-database for at least one of a training variable, a probability distribution for a training variable, or a produced association between training variables; identify a subset of training data from the source databases associated with the at least one training variable; and train the model utilizing the subset of training data from the source databases associated with the at least one training variable, the model including artificial intelligence programming configured to generate an inference in response to data input, wherein the subset of training data reduces the time required to train the model to generate the inference.

3. The system of claim 2, wherein at least one of the steps to identify the representative set of training data for each source database, to generate granular data types for at least a portion of the training data of the training meta-database, to determine the plurality of training variables indicative of at least a portion of the data of the meta-database, or to produce at least one association between at least two training variables are included in instructions associated with a machine learning algorithm.

4. The system of claim 3, wherein the machine learning algorithm uses a neural network.

5. The system of claim 2, wherein the one or more processor further executes instructions to:

generate, in the training meta-database, the probability distribution generated for each training variable and the at least one association between the at least two training variables.

6. The system of claim 5, wherein the one or more processor further executes instructions to: search, based on a user input, a subset of the training data of the training meta-database for at least one training variable, a probability distribution for at least one training variable, or an association between at least two training variables, wherein the subset of training data represents a subset of databases of the plurality of source databases.

7. The system of claim 2, wherein the one or more processor further executes instructions to: produce at least one interactive visualization of at least one training variable of the plurality of training variables, a probability distribution for at least one variable, or an association between at least two training variables.

8. The system of claim 2, wherein the one or more processor further executes instructions to: communicate, based on at least one training variable identified by a user, a subset of the plurality of source databases including training data relevant to the at least one training variable identified by the user.

9. The system of claim 2, wherein the instruction to identify the representative training data for each database of the plurality of source databases includes instructions to: compress the training data represented in each source database of the plurality of source databases.

10. The system of claim 2, wherein the instruction to generate, in the training meta-database, the representative training data for the plurality of source databases includes instructions to: synchronize the training data of training meta-database with the representative training data for the plurality of source databases.

11. The system of claim 2, wherein the one or more processor further executes instructions to: collect information about the completeness of training data relevant to a variable and, when the completeness of the training data is less than a predetermined threshold, eliminates the training data relevant to the variable from the meta-database.

12. The system of claim 2, wherein the instruction to generate granular data types for at least a portion of the training data of the training meta-database includes utilizing a field-by-field analysis.

13. The system of claim 2, wherein the instruction to generate granular data types for at least a portion of the training data of the training meta-database includes instructions to: analyze properties of the training data of the training meta-database stored as at least one of integer, floating point, date, or text to detect at least one of categorical variables, binary variables, dates with and without times, timestamps with and without dates, numerically encoded categorical variables, true floating point and integer values, ID numbers, strings, zip codes, phone numbers, or IP addresses.

14. The system of claim 2, wherein the instruction to generate a probability distribution for each training variable of the plurality of training variables includes instructions to: apply a function of the granular data type for at least one training variable, the function including at least one of a density estimate, discrete distribution, or sample.

15. The system of claim 2, wherein the instruction to produce at least one association between at least two training variables includes instructions to: determine or estimate a causal relationship between the at least two training variables.

16. The system of claim 2, wherein the instruction to produce at least one association between at least two training variables includes instructions to: determine or estimate at least one of a parametric correlation between the at least two training variables, a non-parametric correlation between the at least two training variables, a Pearson correlation between the at least two training variables, a Spearman correlation between the at least two training variables, a Spearman correlation between the at least two training variables, a Kendall's Tau correlation between the at least two training variables, mutual information between the at least two training variables, or an uncertainty coefficient between the at least two training variables.

17. The system of claim 2, wherein the training meta-database is stored on a first portion of the at



least one of the memory device and the non-transitory storage device, and the plurality of source databases is stored on a second portion of the at least one of a memory device and a non-transitory storage device, and wherein the first portion is allocated to substantially less memory space of the at least one of a memory device and a non-transitory storage device than the second portion.

18. A method for training a model from a subset of training data representing a plurality of source databases, the method comprising: communicating, from a source programming interface, training data representative of a plurality of source databases to an artificial intelligence program; compressing the training data representative of the plurality of source databases; communicating, to a training meta-database programming interface, the compressed training data and synchronizing training data of the training meta-database with the compressed training data; generating, utilizing the artificial intelligence program, granular data types for at least a portion of the training data of the training meta-database; determining, utilizing the artificial intelligence program, a plurality of training variables indicative of at least a portion of the training data of the training meta-database; generating, utilizing the artificial intelligence program, a probability distribution for each training variable of the plurality of training variables; producing, utilizing the artificial intelligence program, at least one association between at least two training variables of the plurality of training variables; communicating, to the training meta-database programming interface, the compressed training data and modifying the training meta-database to include the probability distribution generated for each training variable and the at least one association produced between the at least two training variables; receiving a user communicated input and searching the training meta-database, based on the user communicated input, for at least one of a training variable, a probability distribution for a training variable, or a produced association between training variables; identifying a searched subset of the training data from the source databases associated with the at least one training variable searched for based on the user input.

19. The method of claim 18, further comprising: training the model utilizing the searched subset of training data from the source databases, the model including artificial intelligence programming configured to generate an inference in response to data input, wherein the searched subset of training data reduces the time required to train the model to generate the inference.

20. The method of claim 18, further comprising: determining, utilizing the artificial intelligence program and the plurality of source databases, that at least a portion of the training data of the training meta-database is outdated.

---