

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407138
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Miller; Keith Edwin et al.

Contact and shield configuration for ground current optimization

Abstract

An electrical connector and a ground system which includes ground contacts and ground shields positioned proximate the ground contacts. The ground contacts have receiving sections, securing sections and mounting sections. The receiving sections have first engagement portions and second engagement portions. The ground shields have a nonplanar configuration, with portions of the ground shields passing between signal contacts. Surfaces of the securing sections of the ground contacts are positioned in mechanical and electrical engagement with surfaces of the ground shields, providing first ground contact areas across which ground currents may flow. The first engagement portions of the ground contacts are provided in electrical and mechanical engagement with the surfaces of the ground shields, providing second ground contact areas across which the ground currents may flow. The second ground contact areas are spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground shields.

Inventors: Miller; Keith Edwin (Manheim, PA), Walton; Scott Eric (Mount Joy, PA), Gingrich, III; Charles Raymond (Mechanicsburg, PA), Smith; Rodney T. (Hummelstown, PA)

Applicant: TE Connectivity Solutions GmbH (Schaffhausen, CH)

Family ID: 88517968

Assignee: TE Connectivity Solutions GmbH (N/A, CH)

Appl. No.: 18/050523

Filed: October 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240146003 A1	May. 02, 2024

Publication Classification

Int. Cl.: H01R13/6596 (20110101); H01R13/6467 (20110101)

U.S. Cl.:

CPC H01R13/6596 (20130101); H01R13/6467 (20130101);

Field of Classification Search

CPC: H01R (13/646); H01R (13/6461); H01R (13/6467); H01R (13/6469); H01R (13/6471); H01R (13/658); H01R (13/6581); H01R (13/6591); H01R (13/6596)

USPC: 439/607.28

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10003144	12/2017	Sharf	N/A	N/A
10424860	12/2018	Okuyama et al.	N/A	N/A
10993314	12/2020	Charbonneau et al.	N/A	N/A
10998678	12/2020	Miller et al.	N/A	N/A
11025014	12/2020	Miller et al.	N/A	N/A
11031734	12/2020	Miller et al.	N/A	N/A

OTHER PUBLICATIONS

European Search Report, EP App. No. 23206086 International Filing Date Oct. 26, 2023. cited by applicant

Primary Examiner: Le; Thanh Tam T

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to a contact and shield configuration for ground current optimization to provide adequate shielding from crosstalk between signal lines in a connector.

BACKGROUND OF THE INVENTION

(2) Due to the increasing complexity of electronic components, it is desirable to fit more components in less space on a circuit board or other substrate. Consequently, the spacing between electrical terminals within connectors has been reduced, while the number of electrical terminals housed in the connectors has increased, thereby increasing the need in the electrical arts for electrical connectors that are capable of handling higher and higher speeds and to do so with greater and greater pin densities. It is desirable for such connectors to have not only reasonably constant impedance levels, but also acceptable levels of impedance and crosstalk, as well as other acceptable electrical and mechanical characteristics. Therefore, there remains a need to provide appropriate shielding to preserve signal integrity and to minimize crosstalk as speeds of signals

increase and the footprint of the connector maintains or increases density of signal pairs.

(3) It would, therefore, be beneficial to provide a connector with ground contacts and ground shield which provides for adequate ground currents for proper shielding from crosstalk between signal lines in a connector. It would also be beneficial to provide a system with a robust, manufacturable connection without requiring additional components or complicated features in the shield component.

SUMMARY OF THE INVENTION

(4) An embodiment is directed to a ground system for use in an electrical connector. The ground system includes ground contacts and ground shields. The ground contacts have receiving sections, securing sections and mounting sections. The receiving sections have first engagement portions and second engagement portions. The ground shields are positioned proximate the ground contacts. The ground shields have a nonplanar configuration, with portions of the ground shields passing between signal contacts. Surfaces of the securing sections of the ground contacts are positioned in mechanical and electrical engagement with surfaces of the ground shields, providing first ground contact areas across which ground currents may flow. The first engagement portions of the ground contacts are provided in electrical and mechanical engagement with the surfaces of the ground shields, providing second ground contact areas across which the ground currents may flow. The second ground contact areas are spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground shields.

(5) An embodiment is directed to an electrical connector which controls cross talk and signal radiation. The electrical connector includes a housing having a mating end and a mounting end. Signal contacts are positioned in the housing. The signal contacts extend between the mating end and the mounting end and are arranged in pairs to carry differential signals. Ground contacts are positioned in the housing and extend between the mating end and the mounting end. Respective ground contacts of the ground contacts are positioned adjacent to respective signal contacts of the signal contacts. The ground contacts have receiving sections and securing sections, with the receiving sections having first engagement portions and second engagement portions. Ground shields are positioned proximate the ground contacts. Portions of the ground shields pass between the signal contacts. Surfaces of the securing sections of the ground contacts are positioned in mechanical and electrical engagement with surfaces of the ground shields, providing first ground contact areas across which ground currents may flow. The first engagement portions of the ground contacts are provided in electrical and mechanical engagement with the surfaces of the ground shields, providing second ground contact areas across which the ground currents may flow. The second ground contact areas are spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground shields. The ground contacts and the ground shields entirely peripherally surround pairs of signal contacts to provide electrical shielding for the pairs of signal contacts.

(6) An embodiment is directed to an electrical connector which controls cross talk and signal radiation. The electrical connector has a housing having a mating end and a mounting end. Signal contacts are positioned in the housing and are arranged in pairs to carry differential signals. Ground contacts are positioned in the housing and extend between the mating end and the mounting end. Respective ground contacts of the ground contacts are positioned adjacent to respective signal contacts of the signal contacts. The ground contacts have first engagement portions and second engagement portions. Ground shields are positioned proximate the ground contacts. Portions of the ground shields pass between the signal contacts. First ground contact areas where surfaces of the ground contacts are positioned in mechanical and electrical engagement with surfaces of the ground shields provide first paths across which ground currents may flow. The first ground contact areas are provided proximate the mounting end of the housing. Second ground contact areas where the first engagement portions of the ground contacts are provided in electrical and mechanical engagement with the surfaces of the ground shields provide second paths across which the ground

currents may flow. The second ground contact areas are provided proximate the mating end of the housing.

(7) Other features and advantages of the present invention will be apparent from the following more detailed description of the illustrative embodiment, taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a front perspective view of an illustrative connector system shown in an assembled position, with a backplane connector mated to a mating daughtercard connector.

(2) FIG. 2 is an enlarged front perspective view of the backplane connector of FIG. 1.

(3) FIG. 3 is an enlarged bottom perspective view of the backplane connector of FIG. 1.

(4) FIG. 4 is a cross-sectional view of the daughtercard connector mated with the backplane connector, taken along line 4-4 of FIG. 1.

(5) FIG. 5 is a perspective view of an illustrative ground contact of the present invention.

(6) FIG. 6 is a perspective view of a ground shield of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

(7) The description of illustrative embodiments according to principles of the present invention is intended to be read in connection with the accompanying drawings, which are to be considered part of the entire written description. In the description of embodiments of the invention disclosed herein, any reference to direction or orientation is merely intended for convenience of description and is not intended in any way to limit the scope of the present invention. Relative terms such as “lower,” “upper,” “horizontal,” “vertical,” “above,” “below,” “up,” “down,” “top” and “bottom” as well as derivative thereof (e.g., “horizontally,” “downwardly,” “upwardly,” etc.) should be construed to refer to the orientation as then described or as shown in the drawing under discussion. These relative terms are for convenience of description only and do not require that the apparatus be constructed or operated in a particular orientation unless explicitly indicated as such. Terms such as “attached,” “affixed,” “connected,” “coupled,” “interconnected,” and similar refer to a relationship wherein structures are secured or attached to one another either directly or indirectly through intervening structures, as well as both movable or rigid attachments or relationships, unless expressly described otherwise.

(8) Moreover, the features and benefits of the invention are illustrated by reference to the preferred embodiments. Accordingly, the invention expressly should not be limited to such embodiments illustrating some possible non-limiting combination of features that may exist alone or in other combinations of features, the scope of the invention being defined by the claims appended hereto.

(9) FIG. 1 illustrates an illustrative electrical connector system **10** having a backplane connector **12** and a daughtercard connector **14** that are used to electrically connect a backplane circuit board (not shown) and a daughtercard circuit board (not shown). While the electrical connector system **10** is described herein with reference to backplane connectors **12** and daughtercard connectors **14**, it is realized that the subject matter herein may be utilized with different types of electrical connectors other than a backplane connector or a daughtercard connector. The backplane connector **12**, and the daughtercard connector **14** are merely illustrative of an electrical connector system **10**.

(10) In the illustrative embodiment shown, the daughtercard connector **14** constitutes a right angle connector wherein a mating interface **16** and mounting interface **18** of the daughtercard connector **14** are oriented perpendicular to one another. The daughtercard connector **14** is mounted to the daughtercard circuit board at the mounting interface **18**. Other orientations of the interfaces **16**, **18** are possible in alternative embodiments.

(11) The daughtercard connector **14** includes a housing **20**, made of one or more components,

holding a plurality of circuit board wafers **22** therein. The circuit board wafers **22** have pairs of individual signal pathways or traces (not shown) that extend between the mating interface **16** and the mounting interface **18**. The signal traces have signal conductive pads **24** (FIG. **4**) provided proximate the mating interface **16**. The circuit board wafers **22** have individual ground pathways or traces (not shown) that extend between the mating interface **16** and the mounting interface **18**. The ground traces have ground conductive pads **26** (FIG. **4**) provided proximate the mating interface **16**. The circuit board wafers **22** also have ground pathways or traces **28** (FIG. **1**) on opposite sides of the circuit board wafers **22** from the ground traces. The ground traces **28** extend between the mating interface **16** and the mounting interface **18**. In alternative embodiments, the circuit board wafers **22** may be contact modules, the signal traces may be mating signal contacts and the ground traces may be ground contacts.

(12) In the illustrated embodiment, the backplane connector **12** constitutes a header connector mounted to the backplane circuit board. However, other types of connectors may be used. When the backplane connector **12** is mated to the daughtercard connector **14**, the daughtercard circuit board is oriented generally perpendicular with respect to the backplane circuit board.

(13) As is shown in FIG. **2**, the backplane connector **12** includes a mating end **30** and a mounting end **32** that are oriented generally parallel to one another. The backplane connector **12** is mounted to the backplane circuit board at the mounting end **32**. Other orientations of the mating end **30** and the mounting end **32** are possible in alternative embodiments.

(14) The backplane connector **12** includes a housing **34** which includes a plurality of individual housings or modules **36**. Each of the modules **36** extends from the mating end **30** to the mounting end **32**. Each of the modules **36** holds a plurality of individual signal contacts **42** that extend between the mating end **30** and the mounting end **32**. In the exemplary embodiment, the signal contacts **42** are arranged in pairs carrying differential signals. However, in other configurations, the signal contacts **42** may not be arranged in pairs for carrying other signals. Each of the modules **36** holds a plurality of ground contacts **44** that extend between the mating end **30** and the mounting end **32**. In the illustrative embodiment shown, the ground contacts **44** are electrically connected to ground shields or plates **46** that extend between the mating end **30** and the mounting end **32**.

(15) As shown in FIGS. **2** through **4**, each of the modules **36** includes a plurality of signal cavities or channels **48** which extends between the mating end **30** and the mounting end **32**. Each of the modules **36** includes a plurality of ground cavities or channels **54** which extend between the mating end **30** and the mounting end **32** and ground slots **56** which extend between the mating end **30** and the mounting end **32**.

(16) Any number of ground channels **54** may be provided. The ground channels **54** may be provided at any locations within the modules **36**. In an exemplary embodiment, the ground channels **54** are generally positioned between pairs of signal channels **48**. The ground slots **56** are sized and shaped to receive the ground shields or plates **46**.

(17) In the illustrative embodiment shown, the connector **12** has four modules **36** which are positioned adjacent to each other. However, other number of modules may be provided, such as, but not limited to, 8 modules or 16 modules. Circuit board receiving slots **60** are provided between adjacent modules **36**. Each circuit board receiving slot **60** extends from the mating end **30** of the connector **12** toward the mounting end **32**. In other illustrative embodiments, the housing **34** of connector **12** may be a one piece housing, eliminating the need for individual modules.

(18) As shown in FIGS. **2** and **3**, each signal contact **42** has a receiving section **62**, a securing section **64** and circuit board mounting section **66**. In the illustrative embodiment shown, the receiving section **62** includes two resilient arms **68** with lead in portions **70** and engagement portions **72**. In the embodiment shown, first resilient arms **68a** have a different configuration than the second resilient arms **68b**. The resilient arms **62** are configured to press against the signal conductive pads **24** of the signal traces of the daughter card connector **14** when the daughter card connector **14** is mated to the backplane connector **12**. The securing section **64** has retention

members **74**, which may be, but are not limited to barbs or projections, which extend from side surfaces of the securing section **64**. The circuit board mounting section **66** has a compliant portion **76**, such as an eye of the needle pin, although other configurations may be used. The configuration of the signal contact **42** is meant to be illustrative as other embodiments of the signal contact may be used. For example, the signal contacts **42** may have asymmetrical or other configurations which allows for optimal performance under different conditions.

(19) As shown in FIGS. **3** through **5**, each ground contact **44** has a receiving section **82**, a securing section **84** and circuit board mounting section **86**. In the illustrative embodiment shown, the receiving section **82** includes two contact beams or resilient arms **88** with first engagement portions **91** on lead in portions **90** and second engagement portions **92**. In the embodiment shown, first resilient arms **88a** has the same configuration as the second resilient arms **88b**. However, the resilient arms **88** can be made with contact beam geometries that are slightly different from each other so that the ground contacts **44** can fully function with components made within a larger tolerance range than designs that use identical contact beam geometries. The ground contacts **44** may have asymmetrical or other configurations which allows for optimal performance under different conditions.

(20) The resilient arms **82** are configured to cause the second engagement portions **92** to press against the ground conductive pads **26** of the ground traces of the daughter card connector **14** and the first engagement portions **91** to press against the ground shields or plates **46** when the daughter card connector **14** is mated to the backplane connector **12**. The securing section **84** has retention members **94**, which may be, but are not limited to barbs or projections, which extend from side surfaces of the securing section **84**. The circuit board mounting section **86** has a compliant portion **96**, such as an eye of the needle pin, although other configurations may be used.

(21) The ground shields or plates **46** have a non-planar, wavy configuration to pass between and along pairs of signal contacts **42**. The ground shields **46** may be shaped to be positioned generally equidistant from adjacent signal contacts **42**.

(22) In various embodiments, the ground shields **46** may be located as far from the signal contacts **42** as possible. For example, the ground shields **46** may be shaped to be positioned generally equidistant from adjacent signal contacts **42**.

(23) The ground shields **46** have first sections **100** and second sections **102** which are positioned in a different plane than the first sections **100**. Transition sections **104** extend between the first sections **100** and the second sections **102**. In the illustrative embodiment, the transition sections **104** are angled with respect to the first sections **100** and the second sections **102**. Alternatively, the transition sections **104** may be curved or radiused rather than angled.

(24) FIG. **3** is a bottom perspective view of the backplane connector **12** with the ground shields **46** shown to illustrate the layout of the signal contacts **42**, the ground contacts **44** and ground shields **46**. The ground contacts **44** and the ground shields **46** entirely peripherally surround the pairs of signal contacts **42** to provide electrical shielding for the pairs of signal contacts **42**. Gaps or spaces, which could allow EMI leakage between pairs of signal contacts **42**, are minimized through or between the ground contacts **44** and the ground shields **46**.

(25) The ground shields **46** extend along multiple pairs of signal contacts **42**. The ground shields **46** engage the ground contacts **44** to electrically common the ground contacts **44** and the ground shields **46** together. The ground contacts **44** and the ground shields **46** form cavities **106** (FIG. **3**) around the pairs of signal contacts **42**. The cavities **106** may have any shape depending on the shapes of the ground contacts **44** and the ground shields **46**. In the illustrated embodiments, the cavities **106** have a hexagonal prism shape.

(26) When assembled, the ground contacts **44** are positioned in the ground cavities or channels **54** and the ground shields **46** are positioned in the ground slots **56**, as shown in FIG. **4**. In this position, the retention members **94** of the securing sections **84** of the ground contacts **44** cooperate with the walls of the channels **54** of the housing **34** to secure and retain the ground contacts **44** in the

channels **54**. The ground shields **46** are also retained and secured in position in the ground slots **56**. (27) As shown in FIG. **4**, when properly inserted, surfaces **95** of the securing sections **84** of the ground contacts **44** are placed in mechanical and electrical engagement with surfaces **93** of the ground shields **46**. This provides first ground contact areas **81** across which ground currents may flow. The surfaces **95** may be placed in engagement with the surfaces **93** by welding, pressure or some other means.

(28) In addition to the electrical connection between the ground contacts **44** and the ground shields **46** at the first ground contact area **81**, the ground contacts **44** and the ground shields **46** are also placed in mechanical and electrical engagement at a second ground contact areas **83**. At the second ground contact areas **83**, the first engagement portions **91** of the ground contacts **44** are provided in electrical and mechanical engagement with the surfaces **93** of the ground shields **46**. The second ground contact areas **83** are provided proximate the mating end **30** of the housing **34** of the backplane connector **12** which is spaced from the first ground contact area **81** positioned proximate the mounting end **32**. The positioning of the first ground contact areas **81** and the second ground contact areas **83** at opposite ends of the ground shields **46** allows the ground current to properly flow through the entire ground shields, without creating gaps in the effectiveness of the ground shields **46**.

(29) As first ends of the resilient arms **88** of the receiving sections **82** are fixed by the securing sections **84** and as the opposed second ends of the resilient arms **88** engage the ground shields, the resilient arms **88** function as a double supported leaf spring. This ensures that proper electrical and mechanical connections are provided and maintained at the first ground contact areas **81** and the second ground contact areas **83**.

(30) Upon mating of the daughtercard connector **14** to the backplane connector **12**, the circuit board wafers **22** of the daughter card connector **14** are positioned in the circuit board receiving slots **60**. In this position, the signal contacts **42** physically and electrically engage the signal conductive pads **24** of the signal traces of the circuit board wafers **22**. In addition, the ground contacts **44** are also placed in physical and electrical engagement with the ground conductive pads **26** of the ground traces of the circuit board wafers **22**. As this occurs, the second engagement portions **92** of the ground contacts **44** are resiliently deformed inward toward a respective ground shield **46**, causing the resilient arms **88** to deform. This resilient deformation of the resilient arms **88** causes the first engagement portions **91** of the ground contacts **44** to apply additional force to the surfaces **93** of the ground shields **46**, thereby ensuring that the first engagement portions **91** of the ground contacts **44** are retained in electrical and mechanical engagement with the surfaces **93** of the ground shields **46**.

(31) With the connector **12** properly assembled, the ground contacts **44** and the ground shields **46** extend about the periphery of the pairs of signal contacts **42** and surround the pairs of signal contacts **42** to provide electrical shielding for the pairs of signal contacts **42**. In an exemplary embodiment, entire, 360 degree shielding is provided by the ground contacts **44** and the ground shields **46** along the length of the signal contacts **42**. The ground contacts **44** and the ground shields **46** surround portions of the mating signal traces when the connectors **12**, **14** are mated. The ground contacts **44** and the ground shields **46** provide shielding along the entire mating interface with the signal conductive pads **24** of the mating signal traces. The ground contacts **44** and the ground shields **46** may control electrical characteristics at the mating interface **16** and throughout the connector **12**, such as by controlling cross talk, signal radiation, impedance or other electrical characteristics.

(32) While the invention has been described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the spirit and scope of the invention as defined in the accompanying claims. One skilled in the art will appreciate that the invention may be used with many modifications of structure, arrangement, proportions, sizes, materials and components and otherwise used in the practice of the invention, which are particularly adapted to

specific environments and operative requirements without departing from the principles of the present invention. The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being defined by the appended claims, and not limited to the foregoing description or embodiments.

Claims

1. A ground system for use in an electrical connector, the ground system comprising: ground contacts having receiving sections, securing sections and mounting sections, the receiving sections having first engagement portions and second engagement portions, each of the receiving sections has one or more contact beams with the first engagement portions and the second engagement portions provided thereon, first ends of the one or more contact beams are fixed by the securing sections and opposed second ends of the one or more contact beams engage ground shields causing the contact beams to function as a double supported leaf spring; the ground shields positioned proximate the ground contacts, the ground shields having a nonplanar configuration; surfaces of the securing sections of the ground contacts positioned in mechanical and electrical engagement with surfaces of the ground shields, providing first ground contact areas across which ground currents may flow; the first engagement portions of the ground contacts provided in electrical and mechanical engagement with the surfaces of the ground shields, providing second ground contact areas across which the ground currents may flow, the second ground contact areas spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground shields.
2. The ground system as recited in claim 1, wherein the one or more contact beams are two contact beams which have the same configuration.
3. The ground system as recited in claim 1, wherein the one or more contact beams are two contact beams have different configurations.
4. The ground system as recited in claim 1, wherein the securing sections have retention members and the mounting sections have compliant portions.
5. The ground system as recited in claim 1, wherein the ground shields have first sections and second sections which are positioned in a different plane than the first sections, transition sections extend between the first sections and the second sections.
6. The ground system as recited in claim 1, wherein the ground contacts and the ground shields entirely peripherally surround pairs of signal contacts to provide electrical shielding for the pairs of signal contacts.
7. The ground system as recited in claim 1, wherein first ground contact areas and the second ground contact areas engage the ground shields at opposite ends of the ground shields.
8. A ground system for use in an electrical connector, the ground system comprising: ground contacts having receiving sections, securing sections and mounting sections, the receiving sections having first engagement portions and second engagement portions; ground shields positioned proximate the ground contacts, the ground shields having a nonplanar configuration, portions of the ground shields pass between signal contacts, the ground shields have first sections and second sections which are positioned in a different plane than the first sections, transition sections extend between the first sections and the second sections, the transition sections are angled with respect to the first sections and the second sections; surfaces of the securing sections of the ground contacts positioned in mechanical and electrical engagement with surfaces of the ground shields, providing first ground contact areas across which ground currents may flow; the first engagement portions of the ground contacts provided in electrical and mechanical engagement with the surfaces of the ground shields, providing second ground contact areas across which the ground currents may flow, the second ground contact areas spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground shields.

9. An electrical connector which controls cross talk and signal radiation, the electrical connector comprising: a housing having a mating end and a mounting end; signal contacts positioned in the housing, the signal contacts extending between the mating end and the mounting end, the signal contacts being arranged in pairs to carry differential signals; ground contacts positioned in the housing, the ground contacts extending between the mating end and the mounting end, respective ground contacts of the ground contacts being positioned adjacent to respective signal contacts of the signal contacts, the ground contacts having receiving sections and securing sections, the receiving sections having first engagement portions and second engagement portions, wherein each of the receiving sections has one or more contact beams with the first engagement portions and the second engagement portions provided thereon, first ends of the one or more contact beams are fixed by the securing sections and opposed second ends of the one or more contact beams engage ground shields, causing the one or more contact beams to function as a double supported leaf spring; the ground shields positioned proximate the ground contacts, portions of the ground shields pass between the signal contacts; surfaces of the securing sections of the ground contacts positioned in mechanical and electrical engagement with surfaces of the ground shields, providing first ground contact areas across which ground currents may flow; the first engagement portions of the ground contacts provided in electrical and mechanical engagement with the surfaces of the ground shields, providing second ground contact areas across which the ground currents may flow, the second ground contact areas spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground shields; wherein the ground contacts and the ground shields entirely peripherally surround pairs of signal contacts to provide electrical shielding for the pairs of signal contacts.

10. The electrical connector as recited in claim 9, wherein the first ground contact areas and the second ground contact areas engage the ground shields at opposite ends of the ground shields.

11. The electrical connector as recited in claim 9, wherein the one or more contact beams are two contact beams which have the same configuration.

12. The electrical connector as recited in claim 9, wherein the one or more contact beams are two contact beams have different configurations.

13. The electrical connector as recited in claim 9, wherein the securing sections have retention members to retain the ground contacts in the housing.

14. The electrical connector as recited in claim 9, wherein the ground shields have first sections and second sections which are positioned in a different plane than the first sections, transition sections extend between the first sections and the second sections.

15. The electrical connector as recited in claim 14, wherein the transition sections are angled with respect to the first sections and the second sections.

16. An electrical connector which controls cross talk and signal radiation, the electrical connector comprising: a housing having a mating end and a mounting end; signal contacts positioned in the housing, the signal contacts being arranged in pairs to carry differential signals; ground contacts positioned in the housing, the ground contacts extending between the mating end and the mounting end, respective ground contacts of the ground contacts being positioned adjacent to respective signal contacts of the signal contacts, the ground contacts having receiving sections and securing sections, the receiving sections having one or more contact beams with first engagement portions provide at free ends and second engagement portions; ground shields positioned proximate the ground contacts, portions of the ground shields pass between the signal contacts; first ground contact areas where surfaces of the securing sections of the ground contacts are positioned in mechanical and electrical engagement with surfaces of the ground shields provide first paths across which ground currents may flow, the first ground contact areas provided proximate the mounting end of the housing; second ground contact areas where the first engagement portions of the one or more contact beams of the receiving sections of the ground contacts are provided in electrical and mechanical engagement with the surfaces of the ground shields provide second paths across which

the ground currents may flow, the second ground contact areas provided proximate the mating end of the housing; wherein the second ground contact areas are spaced from the first ground contact areas to allow the ground currents to properly flow through the entire ground contacts and the entire ground shields.
