

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408219
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Cheong; Gupil et al.

Electronic device and method for adaptive communication in wireless environment

Abstract

An electronic device includes a processor configured to: obtain a Connected Isochronous Group (CIG) event including a first Connected Isochronous Stream (CIS) event and a second CIS event at least partially overlapped with at least a part of the first CIS event; identify first data indicating a quality of a first link (with a first external device) for the first CIS event and second data indicating a quality of a second link (with a second external device) for the second CIS event; transmit, based on the first data and the second data either a first packet to the first external device or a second packet to the second electronic device.

Inventors: Cheong; Gupil (Suwon-si, KR), Kang; Doosuk (Suwon-si, KR), Kim; Gibeom (Suwon-si, KR), Seo; Hocheol (Suwon-si, KR), Yoo; Hyungseoung (Suwon-si, KR), Cho; Siejoon (Suwon-si, KR), Jin; Juyeon (Suwon-si, KR), Choi; Junsu (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 88835466

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/113931

Filed: February 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240023177 A1	Jan. 18, 2024

Foreign Application Priority Data

KR	10-2022-0062240	May. 20, 2022
KR	10-2022-0069169	Jun. 07, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/002148 20230214 PENDING child-doc US 18113931

Publication Classification

Int. Cl.: H04W76/14 (20180101)
U.S. Cl.:
CPC H04W76/14 (20180201);

Field of Classification Search

CPC: H04W (76/14)
USPC: 455/41.2

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10856297	12/2019	Chen	N/A	N/A
2019/0045304	12/2018	Bhalla	N/A	H04R 3/12
2020/0260322	12/2019	Chen	N/A	H04L 1/16
2020/0260448	12/2019	Chen	N/A	H04W 72/0453
2021/0306103	12/2020	Young	N/A	H04L 1/1887
2022/0039041	12/2021	Zhu	N/A	G06F 3/165
2022/0078541	12/2021	Zhu	N/A	H04W 4/38
2022/0124471	12/2021	Chen	N/A	H04L 1/1874
2023/0071138	12/2022	Cheong	N/A	H04W 88/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112740728	12/2021	CN	N/A
4 383 768	12/2023	EP	N/A
10-2023-0036955	12/2022	KR	N/A
2020/124610	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion (PCT/ISA/210 and PCT/ISA/237) dated May 12, 2023, issued by International Searching Authority for International Application No. PCT/KR2023/002148. cited by applicant
Communication issued on May 19, 2025 by the European Patent Office for European Patent Application No. 23807739.0. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a by-pass continuation application of International Application No. PCT/KR2023/002148, filed on Feb. 14, 2023, which based on and claims priority to Korean Patent Application Nos. 10-2022-0062240, filed on May 20, 2022 and 10-2022-0069169, filed on Jun. 7, 2022, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) One or more embodiments relate to an electronic device and a method for adaptive communication in a wireless environment.

2. Description of Related Art

(2) Compared to legacy Bluetooth® (or classical Bluetooth), Bluetooth Low Energy (BLE) may provide reduced power consumption and at least a similar, or often greater, communication range between connected devices. The BLE may be provided on an Industrial, Scientific, and Medical (ISM) radio band.

SUMMARY

(3) An electronic device is described. The electronic device may include a communication circuit and a processor. The processor may be configured to obtain a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event and a second CIS event at least partially overlapped with at least a part of the first CIS event. The processor may be configured to identify first data indicating quality of a first link for the first CIS event and second data indicating quality of a second link for the second CIS event, the first link between the electronic device and a first external electronic device, the second link between the electronic device and a second external electronic device. The processor may be configured to transmit, by using the communication circuit, a first packet to the first external electronic device via a sub event of the first CIS event in a time interval where the first CIS event and the second CIS event are overlapped or transmit, by using the communication circuit, a second packet to the second external electronic device via a sub event of the second CIS event in the time interval where the first CIS event and the second CIS event are overlapped, based on the first data and the second data.

(4) A method for an electronic device including a communication circuit is described. The method may comprise obtaining a connected isochronous group (CIG) event including a first connected isochronous stream (CIS) event and a second CIS event at least partially overlapped with at least a part of the first CIS event. The method may comprise identifying first data indicating quality of a first link for the first CIS event and second data indicating quality of a second link for the second CIS event, the first link between the electronic device and a first external electronic device, the second link between the electronic device and a second external electronic device. The method may comprise transmitting, by using the communication circuit, a first packet to the first external electronic device via a sub event of the first CIS event in a time interval where the first CIS event and the second CIS event are overlapped or transmitting, by using the communication circuit, a second packet to the second external electronic device via a sub event of the second CIS event in the time interval where the first CIS event and the second CIS event are overlapped, based on the first data and the second data.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 illustrates an electronic device in a network environment according to one or more embodiments;
- (3) FIG. 2 illustrates an example of a wireless environment including an electronic device;
- (4) FIG. 3 illustrates an exemplary method of adaptively transmitting a packet through a Connected Isochronous Group (CIG) event having a hybrid arrangement through first data and second data;
- (5) FIGS. 4A to 4C illustrate an exemplary CIG event having a hybrid arrangement.
- (6) FIG. 5A illustrates an example in which first data and second data are applied to a CIG event;
- (7) FIG. 5B illustrates an example in which first data and second data are applied to a sub event;
- (8) FIG. 6 illustrates an exemplary method of adaptively transmitting a packet through a CIG event having a hybrid arrangement based on first data indicating a number of at least one Protocol Data Unit (PDU) in a first buffer and second data indicating a number of at least one PDU in a second buffer;
- (9) FIG. 7 illustrates an exemplary method of adaptively transmitting a packet through a CIG event having a hybrid arrangement based on first data indicating remaining lifetime of a first packet and a second data indicating remaining lifetime of a second packet;
- (10) FIG. 8 illustrates examples of a first packet, a second packet, a third packet, and a fourth packet;
- (11) FIG. 9A illustrates an exemplary method of allocating all of a time interval in which a first CIS (connected isochronous stream) event and a second CIS event overlap in a CIG event having a hybrid arrangement, based on quality of a first link and quality of a second link, to one CIS event of the first event and second CIS event.
- (12) FIG. 9B illustrates an exemplary method of allocating all of a time interval in which a first CIS event and a second CIS event overlap in a CIG event having a hybrid arrangement, based on quality of a first link and quality of a second link, to one CIS event of the first event and second CIS event.
- (13) FIG. 10A illustrates an exemplary method of executing an allocation corresponding to a reference range including a difference between first data and second data for a CIG event with a hybrid arrangement.
- (14) FIG. 10B illustrates an example of a plurality of predetermined allocations corresponding respectively to a plurality of reference ranges.
- (15) FIG. 11A illustrates an exemplary method of transmitting a packet through a CIG event having a hybrid arrangement according to a scheme corresponding to a state of a wireless environment among a plurality of schemes.
- (16) FIG. 11B illustrates an example of candidate states of a wireless environment.

DETAILED DESCRIPTION

- (17) FIG. 1 illustrates an electronic device **101** in a network environment **100** according to one or more embodiments. In FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network).
- (18) According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module

160, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a Subscriber Identification Module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(19) For example, the processor **120** may execute software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a Central Processing Unit (CPU) or an Application Processor (AP)), or an auxiliary processor **123** (e.g., a Graphics Processing Unit (GPU), a Neural Processing Unit (NPU), an Image Signal Processor (ISP), a sensor hub processor, or a Communication Processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**.

(20) For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(21) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the NPU) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**).

(22) Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a Deep Neural Network (DNN), a Convolutional Neural Network (CNN), a Recurrent Neural Network (RNN), a Restricted Boltzmann Machine (RBM), a Deep Belief Network (DBN), a Bidirectional Recurrent Deep Neural Network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(23) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related to the data. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**. The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

- (24) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).
- (25) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.
- (26) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.
- (27) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.
- (28) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.
- (29) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a High Definition Multimedia Interface (HDMI), a Universal Serial Bus (USB) interface, a Secure Digital (SD) card interface, or an audio interface.
- (30) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).
- (31) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.
- (32) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, ISPs, or flashes.
- (33) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a Power Management Integrated Circuit (PMIC).
- (34) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.
- (35) The communication module **190** may support establishing a direct (e.g., wired)

communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more CPs that are operable independently from the processor **120** (e.g., the AP) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a Global Navigation Satellite System (GNSS) communication module) or a wired communication module **194** (e.g., a Local Area Network (LAN) communication module or a Power Line Communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, Wireless-Fidelity (Wi-Fi) direct, or Infrared Data Association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or Wide Area Network (WAN))).

(36) These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., International Mobile Subscriber Identity (IMSI)) stored in the SIM **196**.

(37) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced Mobile Broadband (eMBB), massive Machine Type Communications (mMTC), or Ultra-Reliable And Low-Latency Communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive Multiple-Input and Multiple-Output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(38) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a Printed Circuit Board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a Radio Frequency Integrated Circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(39) According to various embodiments, the antenna module **197** may form an mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(40) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, General Purpose Input And Output (GPIO), Serial Peripheral Interface (SPI), or Mobile Industry Processor Interface (MIPI)).

(41) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**.

(42) The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, Mobile Edge Computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra-low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an Internet-of-Things (IoT) device.

(43) The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(44) An electronic device may transmit data (or a packet) including information on multimedia content to each of a plurality of external electronic devices by using isochronous logical transport referred to as Connected Isochronous Stream (CIS) via an isochronous link between each of the plurality of external electronic devices and the electronic device. For example, the CIS may be configured as a Connected Isochronous Group (CIG) event including a plurality of CIS events. For example, resources for the CIG event for communication with each of the plurality of external electronic devices may be limited.

(45) The quality of the link between each of the plurality of external electronic devices and the electronic device for communication through the CIG event may be changed due to a change in a state of a wireless environment including the electronic device and the plurality of external electronic devices. Therefore, based on the change in the quality of the link caused while the communication through the CIG event is performed using limited resources, a method for adaptively performing the communication for the CIG event may be required.

(46) FIG. 2 illustrates an example of a wireless environment including an electronic device.

(47) Referring to FIG. 2, the wireless environment **200** may include an electronic device **101**, a first external electronic device **201**, and a second external electronic device **202**.

(48) The electronic device **101** in the wireless environment **200** may be an audio source device such as a smartphone, a laptop computer, a desktop computer, or a tablet PC. For example, the electronic device **101** may transmit data on audio played in the electronic device **101** to each of the first external electronic device **201** and the second external electronic device **202**.

(49) For example, the data may be usable in each of the first external electronic device **201** and the second external electronic device **202** to output the audio from each of the first external electronic device **201** and the second external electronic device **202**. For example, the electronic device **101** may transmit a request to the first external electronic device **201** and the second external electronic device **202**, respectively, in order to receive data on audio (obtained by the first external electronic device **201** and the second external electronic device **202**) from the first external electronic device **201** and the second external electronic device **202**, respectively.

(50) For example, the electronic device **101** may receive the data on the audio from the first external electronic device **201** and the second external electronic device **202** in response to the request. In an embodiment, the electronic device **101** may be referred to as a central device, a primary device, or a main device.

(51) The first external electronic device **201** and the second external electronic device **202** in the wireless environment **200** may be audio sink devices such as earbuds or earphones. For example, the first external electronic device **201** and the second external electronic device **202** may be configured as a pair. However, it is not limited thereto. For example, each of the first external electronic device **201** and the second external electronic device **202** may receive data on audio from the electronic device **101** and output the audio through speakers of each of the first external electronic device **201** and the second external electronic device **202**, based on the data. For example, the data may be usable for reproduce the audio in the electronic device **101**. In an embodiment, each of the first external electronic device **201** and the second external electronic device **202** may be referred to as a peripheral device, a secondary device, or a sub device.

(52) The electronic device **101**, the first external electronic device **201**, and the second external electronic device **202** may support multi-stream audio. For example, synchronized, independent, multiple audio streams may be transmitted between the electronic device **101** and the first external electronic device **201** and/or between the electronic device **101** and the second external electronic device **202**. For example, a Connected Isochronous Group CIG **203** including Connected Isochronous Streams (CIS) may be used to support the multi-stream audio.

(53) For example, the CIG **203** may include two or more CISs having the same isochronous (ISO) interval. For example, the CIG **203** may include a first CIS **204** and a second CIS **205**. For example, each of the first CIS **204** and the second CIS **205** may be a logical transport that causes the first external electronic device **101**, the first external electronic device **201**, and the second external electronic device **202** to transfer uni-directionally (or bi-directionally) isochronous data. For example, each of the first CIS **204** and the second CIS **205** may be related to an asynchronous connection (ACL). For example, each of the first CIS **204** and the second CIS **205** may support variable-sized packets and may support transmitting one or more packets within an isochronous event.

(54) For example, the first CIS **204** may be used to transmit at least one packet from the electronic device **101** to the first external electronic device **201**. For example, the at least one packet may be used to output audio played in the electronic device **101** through a speaker of the first external electronic device **201**. For example, the first CIS **204** may be used to transmit an acknowledgement signal for the at least one packet or a non-acknowledgement signal for the at least one packet from the first external electronic device **201** to the electronic device **101**.

(55) For example, the acknowledgement signal may be transmitted from the first external electronic device **201** to the electronic device **101** through the first CIS **204** to indicate that the first external electronic device **201** successfully receives the at least one packet, and wherein the non-acknowledgement signal may be transmitted from the first external electronic device **201** to the

electronic device **101** through the first CIS **204** to indicate that the first external electronic device **201** fails to receive the at least one packet.

(56) For example, the first CIS **204** may be used to transmit at least one packet from the electronic device **101** to the first external electronic device **201**. For example, the at least one packet may be used to obtain audio played in the electronic device **101** from the first external electronic device **201**. For example, the at least one packet may be a dummy packet or a null packet. For example, the first CIS **204** may be used to transmit a response packet for the at least one packet from the first external electronic device **201** to the electronic device **101**, the response packet including data on the audio. For example, the response packet may cause the electronic device **101** to play at least a part of the audio.

(57) For example, the second CIS **205** may be used to transmit at least one packet from the electronic device **101** to the second external electronic device **202**. For example, the at least one packet may be used to output audio played in the electronic device **101** through a speaker of the second external electronic device **202**. For example, the audio output through the speaker of the first external electronic device **201** and the audio output through the speaker of the second external electronic device **202** may provide stereophonic sound. However, it is not limited thereto. For example, the second CIS **205** may be used to transmit an acknowledgement signal for the at least one packet or a non-acknowledgement signal for the at least one packet from the second external electronic device **202** to the electronic device **101**.

(58) For example, the second CIS **205** may be used to transmit at least one packet from the electronic device **101** to the second external electronic device **202**. For example, the at least one packet may be used to obtain audio played in the electronic device **101** from the second external electronic device **202**. For example, the at least one packet may be a dummy packet or a null packet. For example, the second CIS **205** may be used to transmit a response packet for the at least one packet from the second external electronic device **202** to the electronic device **101**, a response packet including data on the audio. For example, the response packet may cause the electronic device **101** to play at least a part of the audio.

(59) For example, the audio obtained through the response packet received from the first external electronic device **201** and the audio obtained through the response packet received from the second external electronic device **202** may be provided together to provide stereophonic sound or directional sound. However, it is not limited thereto.

(60) FIG. 3 illustrates an exemplary method of adaptively transmitting a packet through a connected isochronous group (CIG) event having a hybrid arrangement through first data and second data. The method may be executed by the electronic device **101** or the processor **120** of the electronic device **101** illustrated in FIG. 1.

(61) In FIG. 3, in operation **302**, the processor **120** may obtain a CIG event. For example, the processor **120** may obtain the CIG event including a first CIS event and a second CIS event at least partially overlapped with a part of the first CIS event.

(62) For example, the processor **120** may schedule, allocate, obtain, configure, identify, or set the CIG event (e.g., the event of CIG **203** illustrated in FIG. 2) that includes the first CIS event for the first external electronic device **201** (e.g., the event of the first CIS **204** illustrated in FIG. 2) and the second CIS event for the second external electronic device **202** (e.g., the event of the second CIS **205** illustrated in FIG. 2) to transmit data or at least one packet to each of the first external electronic device **201** and the second external electronic device **202**.

(63) For example, the processor **120** may schedule, allocate, obtain, compose, identify, or configure the CIG event that includes the first CIS event for the first external electronic device **201** and the second CIS event for the second external electronic device **202** to receive data or at least one packet from each of the first external electronic device **201** and the second external electronic device **202**.

(64) For example, the CIG event including the first CIS event and the second CIS event may

initiate at a start timing of an initial sub event of the initially scheduled CIS and end at an end timing of the last sub event within an ISO interval. For example, an anchor point of the CIG event may occur simultaneously with an anchor point of the initial CIS event within the CIG event.

(65) For example, each of the first CIS event and the second CIS event may include one or more sub events. For example, a sub event within the first CIS event may be used to transmit a packet from the electronic device **101** and to transmit a response packet (e.g., the acknowledgement signal defined in the description of FIG. 2, the non-acknowledgement signal defined in the description of FIG. 2, or the response packet defined in the description of FIG. 2) from the first external electronic device **201**. For example, a sub event within the second CIS event may be used to transmit a packet from the electronic device **101** and a response packet from the second external electronic device **202**.

(66) For example, the first CIS event and the second CIS event may be scheduled in a hybrid arrangement within the CIG event. For example, the processor **120** may obtain, configure, identify, or set the CIG event by scheduling the second CIS event at least partially overlapped with at least a part of the first CIS event, to adaptively change the number of times of at least one transmission through the first CIS event and the number of times of at least one transmission through the second CIS event.

(67) For example, the processor **120** may obtain, configure, identify, or set the CIG event by scheduling the second CIS event at least partially overlapped with the first CIS event, to adaptively change the number of times of at least one reception through the first CIS event and the number of times of at least one reception through the second CIS event. For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event at least partially overlapped with the first CIS event, by scheduling an anchor point of the second CIS event in the first CIS event.

(68) For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event including sub event at least partially overlapped with at least a part of sub event of the first CIS event. For example, the hybrid arrangement may indicate that it has both characteristics of a sequential arrangement and an interleave arrangement defined within a standard for Bluetooth ca Low Energy (BLE) according to overlapping at least a part of the first CIS event and at least a part of the second CIS event.

(69) For example, the processor **120** may obtain the CIG event including the first CIS event and the second CIS event in a hybrid arrangement of one type among various types of hybrid arrangements. For example, the hybrid arrangement of the type may be identified based on the service type or characteristics provided through the CIG event. However, it is not limited thereto. For example, the hybrid arrangements of various types may be illustrated in the description of FIGS. 4A to 4C.

(70) FIGS. 4A to 4C illustrate an exemplary CIG event having a hybrid arrangement.

(71) For example, in FIG. 4A, as illustrated in the chart **400**, the processor **120** may set or obtain a CIG event **401** including a first CIS event **402** and a second CIS event **403** partially overlapped with a part of the first CIS event **402**.

(72) For example, the processor **120** may set or obtain the CIG event **401** by scheduling the first CIS event **402** and the second CIS event **403** so that each of the k th sub event **402-k** to the n th sub event **402-n** in the first CIS event **402** overlaps each of the first sub event **403-1** to the $n-k+1$ th sub event **430-(n-k+1)** in the second CIS event **403** (herein, k is a natural number greater than 1 and less than n). The number of times a packet can be transmitted through the first CIS event **402** may be $k-1$ times to n times, since the first CIS event **402** includes k th sub event **402-k** to n th sub event (**402-n**) overlapped respectively with the first sub event **403-1** to the $n-k+1$ th sub event **403-(n-k+1)** and the first sub event **402-1** to the $k-1$ th sub event **402-(k-1)** that do not overlap with the second CIS event **403**.

(73) As illustrated in the chart **400** of FIG. 4A, since the second CIS event **403** includes the first sub event **403-1** to the $n-k+1$ th sub event **403-(n-k+1)** overlapped respectively with the k th sub

event **402-k** to the n th sub event **402-n** and the $n-k+2$ th sub event **403-(n-k+2)** to the n th sub event **403-n** that do not overlap with the first CIS event **402**, the number of times a packet can be transmitted through the second CIS event **403** may be $k-1$ times to n times in the second CIS event **403**. For example, the processor **120** may be configured to transmit a packet **405** for the first external electronic device **201** through at least a part of the time interval of the first CIS event **402**, which does not overlap with the second CIS event **403** (e.g., the first sub event **402-1** to the $k-1$ th sub event **402-(k-1)**), transmit one of the packet **405** for the first external electronic device **201** and a packet **406** for the second external electronic device **202** through at least a part of the time interval (e.g., the k th sub event **402-k** to the n th sub event **402-n**) of the first CIS event **402** overlapping the second CIS event **403** or the time interval (e.g., the first sub event **403-1** to the $n-k+1$ th sub event **403-(n-k+1)**) of the second CIS event **403** overlapping the first CIS event **402**, and transmit a packet **406** for the second external electronic device **202** through at least a part of the time interval (e.g., $n-k+2$ th sub event **403-(n-k+2)** to n th sub event **403-n**) of the second CIS event **403**, which does not overlap the first CIS event **402**.

(74) For example, since the time interval in which the first CIS event **402** and the second CIS event **403** overlap includes all of the first sub event **403-1** to the $n-k+1$ th sub event **403-(n-k+1)** of the second CIS event **403** that are overlapped respectively with the k th sub event **402-k** to the n th sub event **402-n** of the first CIS event **402** and the k th sub event **402-k** to the n th sub event **402-n** of the first CIS event **402**, the time interval may be a time interval capable of adaptively selecting a transmission from a transmission to the first external electronic device **201** and another transmission to the second external electronic device **202**, for each sub event of the first CIS event **402** or sub event of the second CIS event **403**.

(75) FIG. 4A illustrates an example in which the length of each of the first sub event **402-1** to the n th sub event **402-n** in the first CIS event **402** is the same as the length of each of the first sub event **403** to the n th sub event **403-n** in the second CIS event **403**.

(76) For example, each anchor points of at least a part (e.g., the k th sub event **402-k** to the n th sub event **402-n**) of the first sub event **402-1** to the n th sub event **402-n** within the first CIS event **402** corresponds to each anchor points of at least a part (e.g., the first sub event **403-1** to the $n-k+1$ sub event **403-(n-k+1)**) of the first sub event **403-1** to the n th sub event **403-n** in the second CIS event **403**. Even if the length of each of the first sub event **402-1** to the n th sub event **402-n** in the first CIS event **402** and the length of each of the first sub event **403-1** to the n th sub event **403-n** in the second CIS event **403** are different, the processor **120** may obtain the CIG event **401** that includes the first CIS event **402** and the second CIS event **403** at least partially overlapped with at least a part of the first CIS event **402**.

(77) For example, an interval between anchor points of the first sub event **402-1** to the n th sub event **402-n** within the first CIS event **402** is a multiple of an interval between anchor points of the first sub event **403-1** to the n th sub event **403-n** within the second CIS event **403**. Further, an offset of an anchor point of each of the first sub event **402-1** to the n th sub event **402-n** within the first CIS event **402** matches an offset of an anchor point of the first sub event **403-1** to the n th sub event **403-n** within the second CIS event **403**. Then, the processor **120** may obtain the CIG event **401** that includes the first CIS event **402** and the second CIS event **403** at least partially overlapped with at least a part of the first CIS event **402**.

(78) For example, an interval between anchor points of the first sub event **403-1** to the n th sub event **403-n** within the second CIS event **403** is a multiple of an interval between anchor points of the first sub event **402-1** to the n th sub event **402-n** within the first CIS event **402**. Further, an offset of an anchor point of each of the first sub event **402-1** to the n th sub event **402-n** within the first CIS event **402** matches an offset of an anchor point of the first sub event **403-1** to the n th sub event **403-n** within the second CIS event **403** and a distance between anchor points of the first sub event **402-1** to the n th sub event **402-n** within the first CIS event **402** is a multiple of a distance between anchor points of the first sub event **403-1** to the n th sub event **403-n** within the second CIS event

403. Then, the processor **120** may obtain the CIG event **401** that includes the first CIS event **402** and the second CIS event **403** at least partially overlapped with at least a part of the first CIS event **402**.

(79) For example, in FIG. **4B**, as shown in the chart **450**, the processor **120** may obtain CIG event **451** that includes a first CIS event **452** and a second CIS event **453** completely overlapped with the first CIS event **452**. For example, the processor **120** may obtain the CIG event **451** by scheduling the first CIS event **452** and the second CIS event **453** so that each of the first sub event **452-1** to the fourth sub event **452-4** of the first CIS event **452** overlaps the first sub event **453-1** to the fourth sub event **453-4** of the second CIS event **453**.

(80) Since the first CIS event **452** and the second CIS event **453** are completely overlapped within the CIG event **451**, the processor **120** may adaptively change the number of times capable of transmitting a packet through the first CIS event **452** and the number of times a capable of transmitting a packet through the second CIS event **453**. For example, since the time interval for the CIG event **451** includes both the first sub event **452-1** to the fourth sub event **452-4** and the first sub event **453-1** to the fourth sub event **453-4** that are overlapped respectively with the first sub event **452-1** to the fourth sub event **452-4**, the time interval for the CIG event **451** may be a time interval capable of adaptively selecting a transmission from a transmission to the first external electronic device **201** and another transmission to the second external electronic device **202**, for each sub event of the first CIS event **452** or sub event of the second CIS event **453**.

(81) FIG. **4B** illustrates an example in which the length of each of the first sub event **452-1** to the fourth sub event **452-4** in the first CIS event **452** is the same as the length of each of the first sub event **453-1** to the fourth sub event **453-4** in the second CIS event **453**.

(82) For example, each anchor points of the anchor points of each of the sub events of the first CIS event **452** correspond to the anchor points of each of the sub events of the second CIS event **453**, even if the length of each of the sub events of the first CIS event **452** is different from the length of each of the sub events of the second CIS event **453**. Then, the processor **120** may obtain the CIG event **451** including the first CIS event **452** and the second CIS event **453** overlapped with the first CIS event **452**.

(83) For example, an interval between anchor points of the first CIS event **452** is a multiple of an interval between anchor points of the second CIS event **453**. Further, an offset of each of anchor points of the sub events of the first CIS event **452** match an offset of each of the anchor points of the sub events of the second CIS event **453**. Then, the processor **120** may obtain the CIG event **451** that includes the first CIS event **452** and the second CIS event **453** overlapped with the first CIS event **452**. For example, the CIG event **451** will be illustrated in the description of FIG. **4C**.

(84) For example, an interval between anchor points of the second CIS event **453** is a multiple of an interval between anchor points of the first CIS event **452** and an offset of each of an anchor points of the sub events of the first CIS event **452** match an offset of each of the anchor points of the sub events of the second CIS event **453**. Then, the processor **120** may obtain the CIG event **451** that includes the first CIS event **452** and the second CIS event **453** overlapped with the first CIS event **452**.

(85) For example, in FIG. **4C**, as illustrated in the chart **470**, a CIG event **471** may include a first CIS event **472** and a second CIS event **473** completely overlapped with the first CIS event **472**. For example, the processor **120** may obtain the CIG event **471** by scheduling the first CIS event **472** and the second CIS event **473** so that the first sub event **472-1** of the first CIS event **472** overlaps the first sub event **473-1** and the second sub event **473-2** of the second CIS event **473**, the second sub event **472-2** of the first CIS event **472** overlaps the third sub event **473-3** and the fourth sub event **473-4** of the second CIS event **473**, the third sub event **472-3** of the first CIS event **472** overlaps the fifth sub event **473-5** and the sixth sub event **473-6** of the second CIS event **473**, and the fourth sub event **472-4** of the first CIS event **472** overlaps the seventh sub event **473-7** and the eighth sub event **473-8** of the second CIS event **473**.

(86) For example, unlike the CIG event **401** and the CIG event **451** illustrated respectively in FIGS. **4A** and **4B**, the number of sub events of the first CIS event **472** of the CIG event **471** may be different from the number of sub events of the second CIS event **473** of the CIG event **471**. For example, unlike the CIG event **401** and the CIG event **451** illustrated respectively in FIGS. **4A** and **4B**, an interval between anchor points of the sub events of the first CIS event **472** of the CIG event **471** may be longer than an interval between anchor points of the sub events of the second CIS event **473** of the CIG event **471**.

(87) For example, unlike the CIG event **401** and the CIG event **451** illustrated respectively in FIGS. **4A** and **4B**, the number of times capable of transmitting a packet through the first CIS event **472** may be different from the number of times capable of transmitting a packet through the second CIS event **473**. For example, the interval between the anchor points of the sub events of the first CIS event **472** of the CIG event **471** may be a multiple of the interval between the anchor points of the sub events of the second CIS event **473** of the CIG event **471**.

(88) For example, the offset of each anchor point of each of the sub events of the first CIS event **472** of the CIG event **471** may be the same as the offset of each anchor point of each of the sub events of the second CIS event **473** of the CIG event **471**. For example, the position of the anchor point of the first sub event **472-1** of the first CIS event **472** may be the same as the position of the anchor point of the first sub event **473-1** of the second CIS event **473**. The position of the anchor point of the second sub event **472-2** of the first CIS event **472** may be the same as the position of the anchor point of the third sub event **473-3** of the second CIS event **473**. The position of the anchor point of the third sub event **472-3** of the first CIS event **472** may be the same as the position of the anchor point of the fifth sub event **473-5** of the second CIS event **473**. The position of the anchor point of the fourth sub event **472-4** of the first CIS event **472** may be the same as the position of the anchor point of the seventh sub event **473-7** of the second CIS event **473**.

(89) For example, the anchor point of the second sub event **473-2** of the second CIS event **473** may be within the first sub event **472-1** of the first CIS event **472**. The anchor point of the fourth sub event **473-4** of the second CIS event **473** may be within the second sub event **472-2** of the first CIS event **472**. The anchor point of the sixth sub event **473-6** of the second CIS event **473** may be within the third sub event **472-3** of the first CIS event **472**. The anchor point of the eighth sub event **473-8** of the second CIS event **473** may be in the fourth sub event **472-4** of the first CIS event **472**. For example, the sub events of the first CIS event **472** may be synchronized with the sub events of the second CIS event **473**.

(90) For example, since the interval between the anchor points of the sub events of the first CIS event **472** within the time interval for the CIG event **471** is longer than the interval between the anchor points of the sub events of the second CIS event **473** within the time interval, the time interval may be capable of adaptively selecting a transmission between a transmission to the first external electronic device **201** and another transmission to the second external electronic device **202**, for each sub event of the first CIS event **472**.

(91) Referring back to FIG. **3**, in operation **304**, the processor **120** may identify (read and recognize) first data indicating the quality of the first link for the first CIS event and second data indicating the quality of the second link for the second CIS event. For example, the first link may be a link between the electronic device **101** and the first external electronic device **201**, and the second link may be a link between the electronic device **101** and the second external electronic device **202**.

(92) For example, the first data may indicate the quality of the first link and may be data on the state of the first buffer for the first CIS event. For example, the first data may indicate the number of at least one Protocol Data Unit (PDU) stored in the first buffer, at least temporarily. For example, the at least one PDU may be a PDU not transmitted to the first external electronic device **201** through the first CIS event among PDUs identified based on a Burst Number (BN) (e.g., BN defined within the standard) and a Flush Timeout (FT) (e.g., FT defined within the standard).

However, it is not limited thereto.

(93) For example, the second data may indicate the quality of the second link and may be data on the state of the second buffer for the second CIS event. For example, the second data may indicate the number of at least one protocol data unit (PDU) stored in the second buffer at least temporarily. For example, the at least one PDU may be a PDU not transmitted to the second external electronic device **202** through the second CIS event among PDUs identified based on a burst number (BN) and a flush timeout (FT). However, it is not limited thereto.

(94) For example, the first data may indicate the remaining lifetime of a packet (e.g., the first packet to be illustrated in the description of operation **306**) to be transmitted through the sub event of the first CIS event. For example, the remaining lifetime may indicate a flush point of the packet. For example, the flush point may indicate a timing or in-time at which the packet is deleted by a link layer. For example, the packet may be retransmitted until an acknowledgment signal for the packet is received or until the flush point is reached.

(95) For example, the remaining lifetime may indicate a time until a timing corresponding to the flush point of the packet. However, it is not limited thereto. For example, since the remaining lifetime of the packet may be relatively long on a condition that the quality of the first link is relatively high, and the remaining lifetime of the packet may be relatively short on a condition that the quality of the first link is relatively low, the first data indicating the remaining lifetime of the packet may indicate the quality of the first link. However, it is not limited thereto.

(96) For example, the second data may indicate the remaining lifetime of a packet (e.g., the second packet to be illustrated in the description of operation **306**) to be transmitted through the sub event of the second CIS event overlapped with the sub event of the first CIS event. For example, the remaining lifetime may indicate a flush point of the packet. For example, the flush point may indicate a timing or in-time at which the packet is deleted by a link layer. For example, the packet may be retransmitted until an acknowledgment signal for the packet is received or until the flush point is reached. For example, the remaining lifetime may indicate a time until a timing corresponding to the flush point of the packet. However, it is not limited thereto.

(97) For example, since the remaining lifetime of the packet may be relatively long on a condition that the quality of the second link is relatively high, and the remaining lifetime of the packet may be relatively short on a condition that the quality of the second link is relatively low, the second data indicating the remaining lifetime of the packet may indicate the quality of the second link. However, it is not limited thereto.

(98) For example, the first data may indicate a retransmission rate (or a state of retransmission) of at least one packet transmitted through the first CIS event. For example, since the retransmission rate is relatively low on the condition that the quality of the first link is relatively high, and the retransmission rate may be relatively high on the condition that the quality of the first link is relatively low, the first data indicating the retransmission rate may indicate the quality of the first link. However, it is not limited thereto.

(99) For example, the second data may indicate a retransmission rate (or a state of retransmission) of at least one packet transmitted through the second CIS event. For example, since the retransmission rate is relatively low on the condition that the quality of the second link is relatively high, and the retransmission rate may be relatively high on the condition that the quality of the second link is relatively low, the second data indicating the retransmission rate may indicate the quality of the second link. However, it is not limited thereto.

(100) For example, the first data may indicate a retransmission rate of at least one packet transmitted through a CIS event for the first external electronic device **201** in the first CIS event and another CIG event including the second CIS event. For example, the second data may indicate a retransmission rate of at least one packet transmitted through a CIS event for the second external electronic device **202** within the other CIG event.

(101) For example, the first data may indicate a Packet Error Rate (PER) of transmission through

the first CIS event. For example, the second data may indicate PER of transmission through the second CIS event.

(102) For example, the first data may indicate the reception intensity of a signal transmitted from the electronic device **101** to the first external electronic device **201** through the first CIS event. For example, the first data may indicate reception intensity of a signal transmitted from the first external electronic device **201** to the electronic device **101** through the first CIS event.

(103) For example, the second data may indicate the reception intensity of a signal transmitted from the electronic device **101** to the second external electronic device **202** through the second CIS event. For example, the second data may indicate reception intensity of a signal transmitted from the second external electronic device **202** to the electronic device **101** through the second CIS event. However, it is not limited thereto.

(104) For example, the first data may indicate a Signal-to-Noise Ratio (SNR), a Signal to Interference and Noise Ratio (SINR), and/or a Bit Error Rate (BER) for communication through the first CIS event. For example, the second data may indicate SNR, SINR, and/or BER for communication through the second CIS event. For example, a timing of identifying the first data and the second data may vary according to embodiments.

(105) For example, the processor **120** may identify the first data and the second data before starting a transmission through another sub event next to the sub event after terminating a transmission through the sub event of the first CIS event or the second CIS event. For example, the other sub event may be a sub event within a time interval in which the first CIS event and the second CIS event overlap. For example, the processor **120** may identify the first data and the second data for a transmission through the next sub event at termination of transmission through the sub event. However, it is not limited thereto.

(106) For example, the processor **120** may identify the first data and the second data before transmissions through the CIG event are initiated in a state terminating (or completing) transmissions through another CIG events, the other CIG event prior to the CIG event including the first CIS event and the second CIS event.

(107) For example, the processor **120** may identify the first data and the second data for a transmission through the next CIG event at the end of one CIG event. The processor **120** may identify the first data and the second data for transmission through the next CIG event at each end of a CIG event. However, it is not limited thereto.

(108) For example, the section to which the first data and the second data are applied may vary according to embodiments. For example, the first data and the second data may be applied with respect to a CIG event. Such an example may be illustrated in FIG. 5A.

(109) FIG. 5A illustrates an example in which first data and second data are applied to a CIG event. For example, in FIG. 5A, the processor **120** may identify the first data **504** and the second data **505** based on the result (or state) of previous transmissions including the transmissions performed through the first CIG event **500** including the first CIS event **501** and the second CIS event **502** in the hybrid arrangement.

(110) The processor **120** may apply the first data **504** and the second data **505** with respect to transmissions to be performed through the time interval **513** in the second CIG event **510** in which the first CIS event **511** and the second CIS event **512** overlap. A method of applying the first data **504** and the second data **505** to the transmissions will be illustrated in the following descriptions.

(111) For example, the processor **120** may identify the first data **514** and the second data **515** based on the result (or state) of previous transmissions including transmissions performed through the second CIG event **510**. The processor **120** may apply the first data **514** and the second data **515** with respect to transmissions to be performed through time interval **523** in the third CIG event **520** in which the first CIS event **521** and the second CIS event **522** overlap each other.

(112) A method of applying the first data **514** and the second data **515** to the transmissions will be illustrated in the following descriptions. Referring back to FIG. 3, the first data and the second data

may be applied with respect to one sub event. Such an example may be illustrated in the description of FIG. 5B.

(113) FIG. 5B illustrates an example in which first data and second data are applied to a sub event. For example, in FIG. 5B, the processor **120** may identify the first data **561** and the second data **562** based on the result (or state) of previous transmissions including transmissions performed through the first sub event **551-1** of the first CIS event **551** within the CIG event **550** having the hybrid arrangement. The processor **120** may apply the first data **561** and the second data **562** to a transmission to be performed through a time interval **553** in which the second sub event **551-2** of the first CIS event **551** and the first sub event **552-1** of the second CIS event **552** overlap. A method of applying the first data **561** and the second data **562** to the transmission will be illustrated in the following descriptions.

(114) For example, the processor **120** may identify the first data **571** and the second data **572** based on the result (or state) of previous transmissions including a transmission performed through the time interval **553**. The processor **120** may apply the first data **571** and the second data **572** to a transmission to be performed through the time interval **554** in which the third sub event **551-3** of the first CIS event **551** and the second sub event **552-2** of the second CIS event **552** overlap each other. A method of applying the first data **571** and the second data **572** to the transmission will be illustrated in the following descriptions.

(115) For example, the processor **120** may identify the first data **581** and the second data **582** based on the result (or state) of previous transmissions including a transmission performed through the time interval **554**. The processor **120** may apply the first data **581** and the second data **582** with respect to a transmission to be performed through a time interval **555** in which the fourth sub event **551-4** of the first CIS event **551** and the third sub event **552-3** of the second CIS event **552** overlap each other. A method of applying the first data **581** and the second data **582** to the transmission will be illustrated in the following descriptions.

(116) Referring back to FIG. 3, in operation **306**, the processor **120** may transmit a first packet or a second packet based on the first data and the second data. For example, the processor **120** may transmit the first packet to the first external electronic device **201** through the sub event of the first CIS event within the time interval in which the first CIS event and the second CIS event overlap, based on the first data and the second data, and transmit the second packet to the second external electronic device through the sub event of the second CIS event in the time interval in which at least a part of the sub event of the first CIS event is partially overlapped. For example, the processor **120** may identify a packet to be transmitted within a time interval in which at least a part of the sub event of the first CIS event and at least a part of the sub event of the second CIS event overlap among the first packet and the second packet, based on the first data and the second data. The processor **120** may transmit the identified packet.

(117) In one example, the processor **120** may refrain from transmitting the first packet through the sub event of the first CIS event while the processor **120** may transmit the second packet through the sub event of the second CIS event based on the quality of the first link, which is higher than the quality of the second link. For example, the processor **120** may transmit the first packet through the sub event of the first CIS event, while the processor **120** may refrain from transmitting the second packet through the sub event of the second CIS event based on the quality of the first link, which is lower than the quality of the second link.

(118) For example, the processor **120** may transmit the first packet or the second packet based on the first data indicating the number of at least one PDU temporarily stored in the first buffer and the second data indicating the number of at least one PDU temporarily stored in the second buffer. For example, the processor **120** may transmit the first packet through the sub event of the first CIS event based on the number of at least one PDU temporarily stored in the first buffer being greater than the number of at least one PDU temporarily stored in the second buffer. For example, the processor **120** may transmit the second packet through the sub event of the second CIS event based

on the number of the at least one PDU at least temporarily stored in the first buffer being smaller than the number of at least one PDU at least temporarily stored in the second buffer.

(119) For example, the processor **120** may transmit a packet through a sub event of a CIS event corresponding to a buffer storing a larger amount of data among the first buffer and the second buffer, for balance between the quality of service provided through the first CIS event and the quality of service provided through the second CIS event. For example, the processor **120** may transmit a packet through another CIS event distinguished from the CIS event used for previous transmission under a condition that the number of the at least one PDUs at least temporarily stored in the second buffer is equal to the number of the at least one PDUs at least temporarily stored in the first buffer, for the balance between the quality of the service provided through the first CIS event and the quality of the service provided through the second CIS event for the balance between the quality of the service provided through the first CIS event and the quality of the service provided through the second CIS event.

(120) For example, the number of at least one PDU temporarily stored in the second buffer is equal to the number of at least one PDU temporarily stored in the first buffer, and the processor **120** may transmit a packet through a sub event of the second CIS event under a condition that the previous transmission was performed through the first CIS event. For example, the number of at least one PDU temporarily stored in the second buffer is equal to the number of at least one PDU temporarily stored in the first buffer, the processor **120** may transmit a packet through a sub event of the first CIS event under conditions that the previous transmission was performed through the first CIS event. For example, such transmission may be illustrated in FIG. 6.

(121) FIG. 6 illustrates an exemplary method of adaptively transmitting a packet through a CIG event having a hybrid arrangement based on first data indicating a number of at least one protocol data unit (PDU) in a first buffer and second data indicating a number of at least one PDU in a second buffer. In FIG. 6, the first CIG event **600-1** may include the first CIS event **601** and the second CIS event **602** in the hybrid arrangement, the second CIG event **600-2** may include the first CIS event **603** and the second CIS event **604** in the hybrid arrangement, and the third CIG event **600-3** may include the first CIS event **605** and the second CIS event **606** in the hybrid arrangement. For example, in FIG. 6, each of the first CIS event **601** and the second CIS event **602**; the first CIS event **603** and the second CIS event **604**; the first CIS event **605** and the second CIS event **606** may include 10 sub events. For example, BN of each of the first CIS event **601**, the second CIS event **602**, the first CIS event **603**, the second CIS event **604**, the first CIS event **605**, and the second CIS event **606** may be 2. For example, FT of each of the first CIS event **601**, the second CIS event **602**, the first CIS event **603**, the second CIS event **604**, the first CIS event **605**, and the second CIS event **606** may be 3.

(122) For example, each of the length of the time interval in which the first CIS event **601** and the second CIS event **602** overlap, the length of the time interval in which the first CIS event **603** and the second CIS event **604** overlap, and the length of the time interval in which the first CIS event **605** and the second CIS event **606** overlap may be identified based on the number (NSE defined within the standard) of sub events of the CIS event and the BN of the CIS event. For example, the number of sub events of the first CIS event **601** overlapped with the second CIS event **602**, the number of sub events of the first CIS event **603** overlapped with the second CIS event **604**, and the number of first CIS event **605** overlapping the second CIS event **606** may be 8, which is obtained by subtracting BN (e.g., 2) from NSE (e.g., 10). However, it is not limited thereto.

(123) For example, packets scheduled or allocated for transmissions through the first CIS event **601** may be packet A1 and packet A2, packets scheduled or allocated for transmissions through the first CIS event **603** may be packet A3 and packet A4, packets scheduled or allocated for transmissions through the first CIS event **605** may be packet A5 and packet A6, packets scheduled or allocated for transmissions through the second CIS event **602** may be packet B1 and packet B2, packets scheduled or allocated for transmissions through the second CIS event **604** may be packet B3 and

packet B4, and packets scheduled or allocated for transmissions through the second CIS event **606** may be packet B5 and packet B6.

(124) For example, the processor **120** may transmit the packet A1 through each of the first sub event **601-1** of the first CIS event **601** and the second sub event **601-2** of the first CIS event **601**. For example, the processor **120** may not receive an acknowledgement signal for the packet A1 from the first external electronic device **201** or may receive a non-acknowledgement signal for the packet A1 from the first external electronic device **201** through each of the first sub event **601-1** of the first CIS event **601** and the second sub event **601-2** of the first CIS event **601**.

(125) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 2 and the second data indicating that the number of the at least one PDU in the second buffer is 2, before initiating transmission through the third sub event **601-3** of the first CIS event **601** or the second CIS event **602**. In a state where the number indicated by the first data (e.g., 2) and the number indicated by the second data (e.g., 2) are the same, the processor **120** may transmit the packet A1 through the third sub event **601-3** of the first CIS event **601** among the third sub event **601-3** of the first CIS event **601** and the first sub event **602-1** of the second CIS event **602**.

(126) For example, since the remaining number (e.g., 8) of transmissions through the first CIS event **601** is less than the remaining number (e.g., 10) of transmissions through the second CIS event **602**, and thus the processor **120** may perform the transmission of the packet A1 through the third sub event **601-3** of the first CIS event **601**. However, it is not limited thereto. Meanwhile, the processor **120** may receive an acknowledgment signal with respect to the packet A1 from the first external electronic device **201** through the third sub event **601-3** of the first CIS event **601**.

(127) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of the at least one PDU in the second buffer is 2, before initiating transmission through the fourth sub event **601-4** of the first CIS event **601** or the second sub event **602-2** of the second CIS event **602**. The processor **120** may transmit packet B1 through the second sub event **602-2** of the second CIS event **602**, among the fourth sub event **601-4** of the first CIS event **601** and the second sub event **602-2** of the second CIS event **602**, based on the number (e.g., 1) indicated by the first data less than the number (e.g., 2) indicated by the second data. For example, the processor **120** may not receive an acknowledgement signal for the packet B1 from the second external electronic device **202**, or may receive a non-acknowledgement signal for the packet B1 from the second external electronic device **202**, through the second sub event **602-2** of the second CIS event **602**.

(128) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of the at least one PDU in the second buffer is 2, before initiating transmission through the fifth sub event **601-5** of the first CIS event **601** or the third sub event **602-3** of the second CIS event **602**. The processor **120** may transmit the packet B1 through the third sub event **602-3** of the second CIS event **602**, among the fifth sub event **601-5** of the first CIS event **601** and the third sub event **602-3** of the second CIS event **602**, based on the number (e.g., 1) indicated by the first data less than the number (e.g., 2) indicated by the second data. For example, the processor **120** may receive an acknowledgement signal for the packet B1 from the second external electronic device **202** through the third sub event **602-3** of the second CIS event **602**.

(129) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of the at least one PDU in the second buffer is 1, before initiating transmission through the sixth sub event **601-6** of the first CIS event **601** or the fourth sub event **602-4** of the second CIS event **602**. The processor **120** may transmit the packet A2 through the sixth sub event **601-6** of the first CIS event **601**, among the sixth sub event **601-6** of the first CIS event **601** and the fourth sub event **602-4** of the second CIS event **602**, within a state in which the number indicated by the second data (e.g., 1) is the same as

the number indicated by the first data (e.g., 1).

(130) For example, the number indicated by the first data is the same as the number indicated by the second data, but the remaining number of transmissions through the first CIS event **601** (e.g., 5) is less than the remaining number of transmissions through the second CIS event **602** (e.g., 7), so that the processor **120** may execute the transmission through the sixth sub event **601-6** of the first CIS event **601**. However, it is not limited thereto. The processor **120** may not receive an acknowledgement signal for the packet A2 from the first external electronic device **201** through the sixth sub event **601-6** of the first external electronic device **201** or may receive a non-acknowledgement signal for the packet A2 from the first external electronic device **201**.

(131) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of the at least one PDU in the second buffer is 1, before initiating transmission through the seventh sub event **601-7** of the first CIS event **601** or the fifth sub event **602-5** of the second CIS event **602**. The processor **120** may transmit the packet B2 through the fifth sub event **602-5** of the second CIS event **602**, among the seventh sub event **601-7** of the first CIS event **601** and the fifth sub event **602-5** of the second CIS event **602**, within a state in which the number indicated by the second data (e.g., 1) is the same as the number indicated by the first data (e.g., 1).

(132) For example, the number indicated by the first data is the same as the number indicated by the second data, but the packet A2 was transmitted through the sixth sub event **601-6** of the first CIS event **601** in the previous transmission, so that the processor **120** execute the transmission of the packet B2 through the fifth sub event **602-5** of the second CIS event **602**. For example, the remaining number of transmissions through the first CIS event **601** (e.g., 4) is less than the remaining number of transmissions through the second CIS event **602** (e.g., 6), but the packet A2 was transmitted through the sixth sub event **601-6** of the first CIS event **601** in the previous transmission, so that the processor **120** may execute the transmission of the packet B2 through the fifth sub event **602-5** of the second CIS event **602**. However, it is not limited thereto. The processor **120** may not receive an acknowledgement signal for the packet B2 from the second external electronic device **202** through the fifth sub event **602-5** of the second CIS event **602**, or may receive a non-acknowledgement signal for the packet B2 from the second external electronic device **202**.

(133) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of at the least one PDU in the second buffer is 1, before initiating transmission through the eighth sub event **601-8** of the first CIS event **601** or the sixth sub event **602-6** of the second CIS event **602**. The processor **120** may transmit the packet A2 through the eighth sub event **601-8** of the first CIS event **601**, among the eighth sub event **601-8** of the first CIS event **601** and the sixth sub event **602-6** of the second CIS event **602**, within a state in which the number indicated by the second data (e.g., 1) is the same as the number indicated by the first data (e.g., 1).

(134) For example, the number indicated by the first data is equal to the number indicated by the second data, but the packet B2 was transmitted through the fifth sub event **602-5** of the second CIS event **602** in the previous transmission, so that the processor **120** may execute the transmission of the packet A2 through the eighth sub event **601-8** of the first CIS event **601**. However, it is not limited thereto. The processor **120** may not receive an acknowledgement signal for the packet A2 from the first external electronic device **201** through the eighth sub event **601-8** of the first CIS event **601**, or may receive a non-acknowledgement signal for the packet A2 from the first external electronic device **201**.

(135) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of the at least one PDU in the second buffer is 1, before initiating transmission through the ninth sub event **601-9** of the first CIS event **601** or the seventh sub event **602-7** of the second CIS event **602**. The processor **120**

may transmit the packet B2 through the seventh sub event **602-7** of the second CIS event **602**, among the ninth sub event **601-9** of the first CIS event **601** and the seventh sub event **602-7** of the second CIS event **602**, within a state in which the number indicated by the second data (e.g., 1) is the same as the number indicated by the first data (e.g., 1).

(136) For example, the number indicated by the first data is equal to the number indicated by the second data, but the packet A2 was transmitted through the eighth sub event **601-8** of the first CIS event **601** in the previous transmission, so that the processor **120** may execute the transmission of the packet B2 through the seventh sub event **602-7** of the second CIS event **602**. However, it is not limited thereto. The processor **120** may not receive an acknowledgement signal for the packet B2 from the second external electronic device **202** through the seventh sub event **602-7** of the second CIS event **602**, or may receive a non-acknowledgement signal for the packet B2 from the second external electronic device **202**.

(137) The processor **120** may identify the first data indicating that the number of the at least one PDU in the first buffer is 1, and the second data indicating that the number of the at least one PDU in the second buffer is 1, before initiating transmission through the tenth sub event **601-10** of the first CIS event **601** or the eighth sub event **602-8** of the second CIS event **602**. The processor **120** may transmit the packet A2 through the tenth sub event **601-10** of the first CIS event **601**, among the tenth sub event **601-10** of the first CIS event **601** and the eighth sub event **602-8** of the second CIS event **602**, within a state in which the number indicated by the second data (e.g., 1) is the same as the number indicated by the first data (e.g., 1). For example, the number indicated by the first data is equal to the number indicated by the second data, but the packet B2 was transmitted through the seventh sub event **602-7** of the second CIS event **602** in the previous transmission, so that the processor **120** may execute the transmission of the packet A2 through the tenth sub event **601-10** of the first CIS event **601**. However, it is not limited thereto. The processor **120** may not receive an acknowledgement signal for the packet A2 from the first external electronic device **201** through the tenth sub event **601-10** of the first CIS event **601**, or may receive a non-acknowledgement signal for the packet A2 from the first external electronic device **201**.

(138) The processor **120** may transmit the packet B2 through the ninth sub event **602-9** of the second CIS event **602**. For example, the processor **120** may not receive an acknowledgement signal for the packet B2 from the second external electronic device **202** through the ninth sub event **602-9** of the second CIS event **602**, or may receive a non-acknowledgement signal for the packet B2 from the second external electronic device **202**. The processor **120** may transmit the packet B2 through the tenth sub event **602-10** of the second CIS event **602**. For example, the processor **120** may not receive an acknowledgement signal for the packet B2 from the second external electronic device **202** through the tenth sub event **602-10** of the second CIS event **602**, or may receive a non-acknowledgement signal for the packet B2 from the second external electronic device **202**.

(139) The processor **120** may execute transmissions within a time interval in which the third sub event **603-3** to the tenth sub event **603-10** of the first CIS event **603** in the second CIG event **600-2** and the first sub event **604-1** to the eighth sub event **604-8** of the second CIS event **604** in the second CIG event **600-2** overlap each other, as a method corresponding to executing transmissions within a time interval in which the third sub event **601-3** to the tenth sub event **601-10** of the first CIS event **601** in the first CIG event **600-1** and the first sub event **602-1** to the eighth sub event **602-8** of the second CIS event **602** in the first CIG event **600-1** overlap each other.

(140) The processor **120** may execute transmissions within a time interval in which the third sub event **603-5** to the tenth sub event **603-10** of the first CIS event **605** in the third CIG event **600-3** and the first sub event **606-1** to the eighth sub event **606-8** of the second CIS event **606** in the second CIG event **600-3** overlap each other, as a method corresponding to executing transmissions within a time interval in which the third sub event **601-3** to the tenth sub event **601-10** of the first CIS event **601** in the first CIG event **600-1** and the first sub event **602-1** to the eighth sub event **602-8** of the second CIS event **602** in the first CIG event **600-1** overlap each other. The FT of the

first CIS event **601**, the first CIS event **603**, and the first CIS event **605** is 3, and the acknowledgement signal for the packet A2 was not received until the end of the first CIS event **605** in the third CIG event **600-3**, so that the packet A2 may be flushed in response to the end of the first CIS event **605** or the end of the third CIG event **600-3**.

(141) As described above, the number (e.g., 8) of transmissions through the first CIS event **605** in the third CIG event **600-3** may be different from the number (e.g., 6) of transmissions through the first CIS event **601** in the first CIG event **600-1** and the number (e.g., 6) of transmissions through the first CIS event **603** in the second CIG event **600-2**, respectively. For example, based on the quality of the first link and the quality of the second link, the electronic device **101** may adaptively change the number of transmissions through the first CIS event (e.g., the first CIS event **601**, the first CIS event **603**, or the first CIS event **605**) and the number of transmissions through the second CIS event (e.g., the second CIS event **602**, the second CIS event **604**, or the second CIS event **606**).

(142) For example, the electronic device **101** may execute such an adaptive change using the hybrid arrangement to balance the quality of a service provided through the first CIS event and the quality of a service provided through the second CIS event. For example, the electronic device **101** may adaptively change the number of transmissions through the first CIS event and the number of transmissions through the second CIS event by using the hybrid arrangement based on the quality of the first link and the quality of the second link, unlike the sequential arrangement and the interleave arrangement, where the number of transmissions of the first CIS event and the number of transmissions of the second CIS event are fixed regardless of the quality of the first link and the quality of the second link.

(143) As described above, the position of at least a part of the time resources used for transmissions through the first CIS event **601** in the first CIG event **600-1** may be different from the position of at least a part of the time resources used for transmissions through the first CIS event **603** in the second CIG event **600-2**, and the position of at least a part of the time resources used for transmissions through the first CIS event **605** in the third CIG event **600-3**, respectively. For example, the electronic device **101** may adaptively change the position of time resources used for transmissions through the first CIS event and the position of time resources used for transmissions through the second CIS event by using the hybrid arrangement based on the quality of the first link and the quality of the second link, unlike the sequential arrangement and interleave arrangement, where the position of the time resources used for transmissions through the first CIS event and the position of the time resources used for transmissions through the second CIS event are fixed regardless of the change in the quality of the first link and the change in the quality of the second link.

(144) For example, in a case that a service provided through the CIG event including the first CIS event and the second CIS event in the hybrid arrangement is a service that provides music using the first external electronic device **201** and the second external electronic device **202**, the electronic device **101** may provide enhanced synchronization between the first audio output through the first external electronic device **201** and the second audio output through the second external electronic device **202**, rather than the sequential arrangement and interleave arrangement.

(145) Referring back to FIG. 3, the processor **120** may transmit the first packet or the second packet based on the first data indicating the remaining lifetime of the first packet and the second data indicating the remaining lifetime of the second packet. For example, the processor **120** may identify the first data indicating the remaining lifetime of the first packet and the second data indicating the remaining lifetime of the second packet, after transmitting a packet to the first external electronic device **201** or the second external electronic device **202**, through one of another sub event of the first CIS event previous to the sub event of the first CIS event that can be (or is capable of being) used for transmission of the first packet, or another sub event of the second CIS event previous to the sub event of the second CIS event that can be (or is capable of being) used for transmission of the second packet. For example, the packet transmitted through the other sub event

of the first CIS event or the other sub event of the second CIS event may be the first packet, the second packet, or a different packet from the first packet and the second packet.

(146) For example, the processor **120** may transmit the second packet through the sub event of the second CIS event based on the remaining lifetime of the first packet longer than the remaining lifetime of the second packet. For example, the processor **120** may transmit the first packet through the sub event of the first CIS event based on the remaining lifetime of the first packet shorter than the remaining lifetime of the second packet. For example, such transmission may be illustrated in FIG. 7.

(147) FIG. 7 illustrates an exemplary method of adaptively transmitting a packet through a CIG event having a hybrid arrangement based on first data indicating remaining lifetime of a first packet and a second data indicating remaining lifetime of a second packet.

(148) In FIG. 7, the CIG event **700** may include the first CIS event **701** and the second CIS event **702** in the hybrid arrangement. For example, the first CIS event **701** may include a first sub event **701-1** to a fourth sub event **701-4**. For example, the second CIS event **702** may include a first sub event **702-1** to a fourth sub event **702-4**. For example, the second sub event **701-2** to the fourth sub event **701-4** may overlap the first sub event **702-1** to the third sub event **702-3**, respectively. For example, the BN of each of the first CIS event **701** and the second CIS event **702** may be 2. For example, the FT of each of the first CIS event **701** and the second CIS event **702** may be 3.

(149) For example, the processor **120** may transmit the packet A1 to the first external electronic device **201** through the first sub event **701-1** of the first CIS event **701**. For example, the processor **120** may not receive an acknowledgement signal for the packet A1 from the first external electronic device **201** through the first sub event **701-1** of the first CIS event **701**, or may receive a non-acknowledgement signal for the packet A1 from the first external electronic device **201**.

(150) The processor **120** may identify the first data indicating that the remaining lifetime of the packet A1 to be transmitted through the second sub event **701-2** of the first CIS event **701** is 1, and the second data indicating that the remaining lifetime of the packet B1 to be transmitted through the first sub event **702-1** of the second CIS event **702** is 2, before initiating transmission through the second sub event **701-2** of the first CIS event **701** or the first sub event **702-1** of the second CIS event **702**. For example, if the remaining lifetime of the packet A1 is 1, it may indicate that the packet A1 is flushed in response to the end of the first CIS event **701** or the end of the CIG event **700**.

(151) For example, if the remaining lifetime of packet B1 is 2, it may indicate that packet B1 is flushed in response to the end of a CIG event next to the CIG event **700**, or the end of the second CIS event in the CIG event next to the CIG event **700**. For example, the processor **120** may transmit the packet A1 to the first external electronic device **201** through the second sub event **701-2** of the first CIS event **701**, among the second sub event **701-2** of the first CIS event **701** and the first sub event **702-1** of the second CIS event **702**, based on the remaining lifetime of the packet A1 shorter than the remaining lifetime of the packet B1. For example, the processor **120** may receive an acknowledgement signal for the packet A1 from the first external electronic device **201** through the second sub event **701-2** of the first CIS event **701**.

(152) The processor **120** may identify the first data indicating that the remaining lifetime of the packet A2 to be transmitted through the third sub event **701-3** of the first CIS event **701** is 3, and the second data indicating that the remaining lifetime of the packet B1 to be transmitted through the second sub event **702-2** of the second CIS event **702** is 2, before initiating transmission through the third sub event **701-3** of the first CIS event **701**, or the second sub event **702-2** of the second CIS event **702**.

(153) For example, the processor **120** may transmit the packet B1 to the second external electronic device **202** through the second sub event **702-2** of the second CIS event **702**, among the third sub event **701-3** of the first CIS event **701** and the second sub event **702-2** of the second CIS event **702**, based on the remaining lifetime of the packet A2 longer than the remaining lifetime of packet B1.

For example, the processor **120** may not receive an acknowledgement signal for the packet B1 from the second external electronic device **202** through the second sub event **702-2** of the second CIS event **702**, or may receive a non-acknowledge signal for the packet B1 from the second external electronic device **202** through the second sub event **702-2** of the second CIS event **702**.

(154) The processor **120** may identify the first data indicating that the remaining lifetime of the packet A2 to be transmitted through the fourth sub event **701-4** of the first CIS event **701** is 3, and the second data indicating that the remaining lifetime of the packet B1 to be transmitted through the third sub event **702-3** of the second CIS event **702** is 2, before initiating transmission through the fourth sub event **701-4** of the first CIS event **701** or the third sub event **702-3** of the second CIS event **702**.

(155) For example, the processor **120** may transmit the packet B1 to the second external electronic device **202** through the third sub event **702-3** of the second CIS event **702**, among the fourth sub event **701-4** of the first CIS event **701** and the third sub event **702-3** of the second CIS event **702**, based on the remaining lifetime of the packet A2 longer than the remaining lifetime of packet B1. For example, the processor **120** may receive an acknowledgement signal for the packet B1 from the second external electronic device **202** through the third sub event **702-3** of the second CIS event **702**.

(156) The processor **120** may transmit the packet B2 to the second external electronic device **202** through the fourth sub event **702-4** of the second CIS event **702**. The processor **120** may receive an acknowledgment signal for the packet B2 from the second external electronic device **202** through the fourth sub event **702-4** of the second CIS event **702**.

(157) The processor **120** may identify one sub event of the sub event of the first CIS event **701** and the sub event of the second CIS event **702** through different conditions (or different standard), based on identifying that the remaining lifetime of the packet to be transmitted through the sub event of the first CIS event **701** is the same as the remaining lifetime of the packet to be transmitted through the sub event of the second CIS event **702**.

(158) For example, the processor **120** may identify one sub event of the sub event of the first CIS event **701** and the sub event of the second CIS event **702**, based on the other standards illustrated in the description of FIG. 6. For example, the processor **120** may identify one sub event of the sub event of the first CIS event **701** and the sub event of the second CIS event **702**, based on the comparison between the remaining number of transmissions through the first CIS event **701** and the remaining number of transmissions through the second CIS event **702**. For example, the processor **120** may identify one sub event of the sub event of the first CIS event **701** and the sub event of the second CIS event **702**, based on whether the sub event used for the previous transmission is another sub event of the first CIS event **701** or another sub event of the second CIS event **702**. However, it is not limited thereto.

(159) As described above, the electronic device **101** may compare the remaining lifetime of the packet to be transmitted through the first CIS event with the remaining lifetime of the packet to be transmitted through the second CIS event. By this comparison, the electronic device **101** may reduce flushing of packets transmitted to the first external electronic device **201** and flushing of packets transmitted to the second external electronic device **202**. For example, the electronic device **101** may execute the comparison so that the number of times a packet is transmitted through a link having a relatively low quality increases.

(160) Referring back to FIG. 3, the first packet and the second packet may vary according to embodiments. For example, as illustrated in the description of FIGS. 6 to 7, each of the first packet and the second packet may include data to be used within each of the first external electronic device **201** and the second external electronic device **202**. For example, each of the first packet and the second packet may be a packet for transmitting audio data or a packet for retransmitting the audio data.

(161) For example, each of the first packet and the second packet may be a dummy packet or a null

packet. For example, the first packet, which is the null packet, may request the electronic device **101** to transmit a third packet including data to be used in the electronic device **101** or to request the electronic device **101** to retransmit the third packet. For example, the data in the third packet may be audio data obtained through a microphone of the first external electronic device **201**.

However, it is not limited thereto.

(162) For example, the second packet, which is the null packet, may request the electronic device **101** to transmit a fourth packet including data to be used in the electronic device **101** or to request the electronic device **101** to retransmit the fourth packet. For example, the data in the fourth packet may be audio data obtained through the microphone of the second external electronic device **202**. However, it is not limited thereto. For example, the first packet that is the null packet, the second packet that is the null packet, the third packet, and the fourth packet may be exemplified in the description of FIG. **8**.

(163) FIG. **8** illustrates examples of a first packet, a second packet, a third packet, and a fourth packet. In FIG. **8**, the first packet **801**, which is a null packet, may replace packets A1 to A6 exemplified in the description of FIG. **6**. For example, in a case that the electronic device **101** obtains data from the first external electronic device **201**, the processor **120** may transmit packets such as a first packet **801** to the first external electronic device **201** instead of packets A1 to A6. The first packet **801**, which is the null packet, may replace the packet A1 and the packet A2 illustrated in the description of FIG. **7**. For example, in a case that the electronic device **101** obtains data from the first external electronic device **201**, the processor **120** may transmit a packet such as the first packet **801** to the first external electronic device **201** instead of packets A1 and A2.

(164) The second packet **802**, which is the null packet, may replace packets B1 to B6 illustrated in the description of FIG. **6**. For example, in a case that the electronic device **101** obtains data from the second external electronic device **202**, the processor **120** may transmit a packet such as a second packet **802** to the second external electronic device **202** instead of packets B1 to B6. The second packet **802**, which is the null packet, may replace the packet B1 and the packet B2 illustrated in the description of FIG. **7**. For example, in a case that the electronic device **101** obtains data from the second external electronic device **202**, the processor **120** may transmit a packet such as the second packet **802** to the second external electronic device **202** instead of packets B1 and B2.

(165) The third packet **803** is a response packet for a request through the first packet **801**, and may include data obtained by the first external electronic device **201**. For example, the third packet **803** may replace the acknowledgment signal illustrated in the description of FIG. **6**. For example, the first external electronic device **201** may transmit the third packet **803** to the electronic device **101** in response to the first packet **801** received from the electronic device **101**. For example, the third packet **803** may replace the acknowledgment signal illustrated in the description of FIG. **7**. For example, the first external electronic device **201** may transmit the third packet **803** to the electronic device **101** in response to the first packet **801** received from the electronic device **101**.

(166) The fourth packet **804** is a response packet for a request through the second packet **802**, and may include data obtained by the second external electronic device **202**. For example, the fourth packet **804** may replace the acknowledgment signal illustrated in the description of FIG. **6**. For example, the second external electronic device **202** may transmit the fourth packet **804** to the electronic device **101** in response to the second packet **802** received from the electronic device **101**. For example, the fourth packet **804** may replace the acknowledgment signal illustrated in the description of FIG. **7**. For example, the second external electronic device **202** may transmit the fourth packet **804** to the electronic device **101** in response to the second packet **802** received from the electronic device **101**.

(167) The above-described examples and examples below illustrate that the electronic device **101** provides data to each of the first external electronic device **201** and second external electronic device **202** within a CIG event including a first CIS event, and a second CIS event at least partially overlapped with at least a part of the first CIS event, and that each of the first external electronic

device **201** and the second external electronic device **202** provides data to the electronic device **101** within a CIG event including a first CIS event, and a second CIS event at least partially overlapped with at least a part of the first CIS event.

(168) In an embodiment, the electronic device **101** (or the processor **120**) may execute providing data to each of the first external electronic device **201** and the second external electronic device **202**, or obtaining data from each of the first external electronic device **201** and the second external electronic device **202** within a CIG event including a first CIS event, and a second CIS event at least partially overlapped with at least a part of the first CIS event. For example, the processor **120** may execute an adaptive transmission through the CIG event, based on a number of at least one packet in the buffer to be transmitted to the first external electronic device **201**, the remaining lifetime of the packet to be received from the first external electronic device **201**, a number of at least one packet in the buffer to be transmitted to the second external electronic device **202**, and the remaining lifetime of the packet to be received from the second external electronic device **202**. However, it is not limited thereto.

(169) FIG. **9A** illustrates an exemplary method of allocating all of a time interval in which a first CIS event and a second CIS event overlap in a CIG event having a hybrid arrangement, based on quality of a first link and quality of a second link, to one CIS event of the first event and second CIS event. The method may be executed by the electronic device **101** or the processor **120** of the electronic device **101** illustrated in FIG. **1**. In an embodiment, operations **902** to **906** of FIG. **9A** may be included in operation **306** of FIG. **3**. In an embodiment, operations **902** to **906** of FIG. **9A** may be an example of operation **306** of FIG. **3**.

(170) In FIG. **9A**, in operation **902**, the processor **120** may compare the quality of the first link with the quality of the second link. For example, the processor **120** may compare the quality of the first link with the quality of the second link by comparing the first data with the second data. For example, the processor **120** may execute operation **904** on a condition that the quality of the first link is higher than the quality of the second link. For example, the processor **120** may execute operation **906** on a condition that the quality of the first link is lower than the quality of the second link.

(171) In operation **904**, the processor **120** may allocate or schedule all of the time intervals in the CIG event where the first CIS event and the second CIS event overlap to the first CIS event among the first CIS event and the second CIS event, based on the quality of the first link higher than the quality of the second link. For example, in a case that a service with an FT of 1 is provided through the CIG event including the first CIS event and the second CIS event, such as a telephone call, or in a case that a service is provided that requires reducing packet missing through the CIG event including the first CIS event and the second CIS event, even when an imbalance between the first CIS event and the second CIS event occurs, the processor **120** may allocate all of the time intervals to the first CIS event based on identifying (by the processor **120**) that the quality of the first link is higher than the quality of the second link.

(172) The processor **120** may transmit at least one packet including the first packet through at least a part of the sub events of the first CIS event in the time interval based on the allocation. Allocating all of the time intervals to the first CIS event may be illustrated in the description of FIG. **9B**.

(173) FIG. **9B** illustrates an exemplary method of allocating all of a time interval in which a first CIS event and a second CIS event overlap in a CIG event having a hybrid arrangement, based on quality of a first link and quality of a second link, to one CIS event of the first event and second CIS event.

(174) In FIG. **9B**, the CIG event **950** may include the first CIS event **951** and the second CIS event **952** in the hybrid arrangement. For example, the first CIS event **951** may include a first sub event **951-1** to a tenth sub event **951-10** and the second CIS event **952** may include a first sub event **952-1** to a tenth sub event **952-10**. For example, the third sub event **951-3** to the tenth sub event **951-10** of the first CIS event **951** may overlap the first sub event **952-1** to the eighth sub event **952-8** of the

second CIS event **952**, respectively.

(175) For example, the processor **120** may identify that the quality of the first link is higher than the quality of the second link based on the state (or result) of transmissions through another CIG event previous to the CIG event **950**. Based on the identification, the processor **120** may allocate all of the time intervals **953** in which the first CIS event **951** and the second CIS event **952** overlap each other to the third sub event **951-3** to the tenth sub event **951-10** of the first CIS event **951**. For example, the processor **120** may transmit the at least one packet including the first packet through at least a part of the third sub event **951-3** to the tenth sub event **951-10** of the first CIS event **951**.

(176) In an embodiment, when all packets targeted to be transmitted through the first CIS event **951** are transmitted before end of the first CIS event **951**, the processor **120** may use the remaining part of the time interval **953** for transmission through the second CIS event **952**. For example, when transmissions of all the packets are completed through transmissions through the sixth sub event **951-6** of the first CIS event **951**, the processor **120** may transmit at least one packet including the second packet to the second external electronic device **202** through the fifth sub event **952-5** to the eighth sub event **952-8** of the second CIS event **952** overlapping with the seventh sub event **951-7** to the tenth sub event **951-10** of the first CIS event **951**, respectively. However, it is not limited thereto.

(177) Referring back to FIG. **9A**, in operation **906**, the processor **120** may allocate or schedule all of the time intervals in the CIG event in which the first CIS event and the second CIS event overlap to the second CIS event, among the first CIS event and the second CIS event, based on the quality of the first link lower than the quality of the second link. For example, in case that a service with an FT of 1 is provided through the CIG event including the first CIS event and the second CIS event, such as a telephone call, or in case that a service is provided that requires reducing packet missing through the CIG event including the first CIS event and the second CIS event, even when an imbalance between the first CIS event and the second CIS event occurs, the processor **120** may allocate all of the time intervals to the second CIS event, based on identifying that the quality of the second link is higher than the quality of the first link.

(178) The processor **120** may transmit at least one packet including the second packet through at least a part of the sub events of the second CIS event in the time interval based on the allocation. Allocating all of the time intervals to the second CIS event may be illustrated in the description of FIG. **9B**.

(179) In FIG. **9B**, the CIG event **960** may include the first CIS event **961** and the second CIS event **962** in the hybrid arrangement. For example, the first CIS event **961** may include a first sub event **961-1** to a tenth sub event **961-10** and the second CIS event **962** may include a first sub event **962-1** to a tenth sub event **962-10**. For example, the third sub event **961-3** to the tenth sub event **961-10** of the first CIS event **961** may overlap the first sub event **962-1** to the eighth sub event **962-8** of the second CIS event **962**, respectively.

(180) For example, the processor **120** may identify that the quality of the second link is higher than the quality of the first link, based on a state (or a result) of transmissions through another CIG event previous to the CIG event **960**. Based on the identification, the processor **120** may allocate all of the time intervals **963** in which the first CIS event **961** and the second CIS event **962** overlap to the first sub event **962-1** to the eighth sub event **962-8** of the second CIS event **962**. For example, the processor **120** may transmit the at least one packet including the second packet through at least a part of the first sub event **962-1** to the eighth sub event **962-8** of the second CIS event **962**.

(181) In an embodiment, when all packets targeted for transmission through the second CIS event **962** are transmitted through at least one sub event (e.g., at least one of the first sub event **962-1** to the tenth sub event **962-10**) of the second CIS event **962** included in a part of the time interval **963**, the processor **120** may use the remaining part of the time intervals **963** for transmission through the first CIS event **961**. For example, when transmissions of all the packets are completed through transmissions in the third sub event **962-3** of the second CIS event **962**, the processor **120** may

transmit at least one packet including the first packet to the first external electronic device **201** through the sixth sub event **961-6** to the tenth sub event **961-10** of the first CIS event **961** overlapping with the fourth sub event **962-4** to the eighth sub event **962-8** of the second CIS event **962**, respectively. However, it is not limited thereto.

(182) The processor **120** may allocate the time interval in which the first CIS event and the second CIS event overlap, on a condition that the quality of the first link corresponds to the quality of the second link, based on another condition. For example, the processor **120** may allocate the time interval, based on a state of the first buffer and a state of the second buffer, a remaining lifetime of the first packet and a remaining lifetime of the second packet, a remaining number of times of transmission through the first CIS event and a remaining number of times of transmission through the second CIS event, and/or the CIS event used in the previous transmission.

(183) As described above, when it is required to reduce missing packets, even if an imbalance occurs between the quality of service provided through the first CIS event and the quality of service provided through the second CIS event, the electronic device **101** may increase the number of times of transmissions through a link having a high quality among the first link and the second link, by using the hybrid arrangement.

(184) FIG. **10A** illustrates an exemplary method of executing an allocation corresponding to a reference range including a difference between first data and second data for a CIG event with a hybrid arrangement. The method may be executed by the electronic device **101** or the processor **120** of the electronic device **101** illustrated in FIG. **1**. In an embodiment, operations **1002** to **1006** of FIG. **10A** may be included in operation **306** of FIG. **3**.

(185) In FIG. **10A**, in operation **1002**, the processor **120** may identify a difference between the first data and the second data. For example, the processor **120** may identify the difference between the first data and the second data to adaptively execute a method of allocating a time interval in which the first CIS event and the second CIS event overlap, according to a difference between the quality of the first link and the quality of the second link.

(186) In operation **1004**, the processor **120** may identify a reference range including the difference among a plurality of reference ranges. For example, the plurality of reference ranges may be expressed as shown in Table 1 below.

(187) TABLE-US-00001 TABLE 1 In a case that quality of first link is greater than or equal to quality Kth reference range a1~a2 of second link mth reference range a2~a3 In a case that quality of first link is less than quality of second link lth reference range a1~a2 nth reference range a2~a3

(188) In Table 1, k may be a natural number of 1 or more, m may be a natural number greater than k, 1 may be a natural number of 1 or more, and n may be a natural number greater than 1. In Table 1, each of a1, a2, and a3 may be a real number.

(189) For example, the processor **120** may identify the mth reference range illustrated in Table 1 as the reference range on a condition that the quality of the first link is higher than the quality of the second link and the difference is between a2 and a3. For example, the processor **120** may identify the 1th reference range illustrated in Table 1 as the reference range on a condition that the quality of the first link is lower than the quality of the second link and the difference is a value between a1 and a2. However, it is not limited thereto.

(190) In operation **1006**, the processor **120** may execute allocation corresponding to the identified reference range. For example, the processor **120** may execute the allocation corresponding to the reference range among a plurality of predetermined respectively allocations defined for the plurality of reference ranges. For example, the allocation may be illustrated in FIG. **10B**.

(191) FIG. **10B** illustrates an example of a plurality of predetermined allocations corresponding respectively to a plurality of reference ranges. In FIG. **10B**, a CIG event **1050** may include a first CIS event **1051** including a first sub event **1051-1** to a tenth sub event **1051-10** and a second CIS event **1052** including a first sub event **1052-1** to tenth sub event **1052-10** in the hybrid arrangement.

For example, the third sub event **1051-3** to the tenth sub event **1051-10** of the first CIS event **1051** may overlap the first sub event **1052-1** to the eighth sub event **1052-8** of the second CIS event **1052**, respectively.

(192) For example, the processor **120** may identify a first allocation **1061** corresponding to a first reference range among a plurality of predetermined allocations **1060**, on a condition that the reference range including the identified difference is the first reference range. For example, the first allocation **1061** may be to allocate the first part **1071** of the time interval **1053** to the third sub event **1051-3** to the sixth sub event **1051-6** of the first CIS event **1051**, and the second part **1072** of the time interval **1053** to the fifth sub event **1052-5** to the eighth sub event **1052-8** of the second CIS event **1052**. However, it is not limited thereto.

(193) For example, the processor **120** may identify a second allocation **1062** corresponding to a second reference range among the plurality of predetermined allocations **1060**, on a condition that the reference range including the identified difference is the second reference range. For example, the second allocation **1062** may allocate the third part **1073** of the time interval **1053** to the third sub event **1051-3** to the fourth sub event **1051-4** of the first CIS event **1051**, and the fourth part **1074** of the time interval **1053** to the third sub event **1052-3** to the eighth sub event **1052-8** of the second CIS event **1052**. However, it is not limited thereto.

(194) For example, the processor **120** may identify a third allocation **1063** corresponding to a third reference range among the plurality of predetermined allocations **1060**, on a condition that the reference range including the identified difference is the third reference range. For example, the third allocation **1063** may be to allocate the fifth part **1075** of the time interval **1053** to the third sub event **1051-3** to the eighth sub event **1051-8** of the first CIS event **1051**, and the sixth part **1076** of the time interval **1053** to the seventh sub event **1052-7** to the eighth sub event **1052-8** of the second CIS event **1052**. However, it is not limited thereto.

(195) For example, the processor **120** may identify a fourth allocation **1064** corresponding to a fourth reference range among the plurality of predetermined allocations **1060**, on a condition that the reference range including the identified difference is the fourth reference range. For example, the fourth allocation **1064** may allocate all (**1077**) of the time interval **1053** to the third sub event **1051-3** to the tenth sub event **1051-10** of the first CIS event **1051**. However, it is not limited thereto.

(196) For example, the processor **120** may identify a fifth allocation **1065** corresponding to a fifth reference range among the plurality of predetermined allocations **1060**, on a condition that the reference range including the identified difference is the fifth reference range. For example, the fifth allocation **1065** may be to allocate all (**1078**) of the time interval **1053** to the first sub event **1052-1** to the eighth sub event **1052-8** of the second CIS event **1052**. However, it is not limited thereto.

(197) As described above, the electronic device **101** may adaptively execute transmissions through the CIG event including the first CIS event and the second CIS event according to the state of the first link and the state of the second link, by identifying an allocation corresponding to a difference between the first data and the second data among the predetermined allocations.

(198) FIG. **11A** illustrates an exemplary method of transmitting a packet through a CIG event having a hybrid arrangement according to a scheme corresponding to a state of a wireless environment among a plurality of schemes. The method may be executed by the electronic device **101** or the processor **120** of the electronic device **101** illustrated in FIG. **1**. In an embodiment, operations **1102** to **1106** of FIG. **11A** may be included in operation **306** of FIG. **3**.

(199) In FIG. **11A**, in operation **1102**, the processor **120** may identify the state of the wireless environment including the first external electronic device and the second external electronic device based on the first data and the second data. For example, the first data may indicate a change in the quality of the first link, and the second data may indicate a change in the quality of the second link. For example, the state of the wireless environment may be identified among candidate states

defined in the electronic device **101**. For example, the candidate states may be illustrated in FIG. **11B**.

(200) FIG. **11B** illustrates an example of candidate states of a wireless environment. In FIG. **11B**, the candidate states **1150** may include a first state **1151**, a second state **1152**, a third state **1153**, and a fourth state **1154**.

(201) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the first state **1151**, corresponds to the second state **1152**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the first state **1151** to the second state **1152**, based on the first data and the second data indicating that a retransmission rate is 50%.

(202) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the first state **1151**, corresponds to the third state **1153**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the first state **1151** to the third state **1153**, based on the first data and the second data indicating that both the first buffer and the second buffer are empty.

(203) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the second state **1152**, corresponds to the third state **1153**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the second state **1152** to the third state **1153**, based on the first data and the second data indicating that the retransmission rate is 40%.

(204) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the second state **1152**, corresponds to the first state **1151**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the second state **1152** to the first state **1151**, based on the first data and the second data indicating that the retransmission rate is 55%.

(205) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the second state **1152**, corresponds to the fourth state **1154**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the second state **1152** to the fourth state **1154**, based on the first data and the second data indicating that both the first buffer and the second buffer are empty.

(206) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the third state **1153**, corresponds to the fourth state **1154**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the third state **1153** to the fourth state **1154**, based on the first data and the second data indicating that the retransmission rate is 30%.

(207) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the third state **1153**, corresponds to the second state **1152**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the third state **1153** to the second state **1152**, based on the first data and the second data indicating that the retransmission rate is 45%.

(208) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the third state **1153**, corresponds to the first state **1151**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the third state **1153** to the first state **1151** based on the first data and the second data indicating that packets are continuously flushed.

(209) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the fourth state **1154**, corresponds to the third state **1153**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the fourth state **1154** to the third state **1153** based on the first data and the second data indicating that the retransmission rate is 35%.

(210) For example, the processor **120** may identify that the state of the wireless environment, which was identified as the fourth state **1154**, corresponds to the second state **1152**, based on the first data and the second data. For example, the processor **120** may identify that the state of the wireless environment is changed from the fourth state **1154** to the second state **1152**, based on the first data and the second data indicating that packets are continuously flushed.

(211) Referring back to FIG. **11A**, in operation **1104**, the processor **120** may identify a scheme corresponding to the identified state among a plurality of scheme defined for the candidate states. For example, the plurality of schemes may include first schemes that allocate a next transmission to the first CIS event or the second CIS event each time a packet is transmitted within the time interval. For example, the first schemes may include a scheme illustrated in the description of FIG. **6**, a scheme illustrated in the description of FIG. **7**, and/or a scheme illustrated in the description of FIG. **9A**. However, it is not limited thereto.

(212) For example, the plurality of schemes may include second schemes that allocate at least a part of the time interval to the first CIS event and at least another part of the time interval to the second CIS event before transmitting a packet within the time interval. For example, the second schemes may include a scheme illustrated in the description of FIG. **10A**. However, it is not limited thereto.

(213) In operation **1106**, the processor **120** may execute the allocation corresponding to the identified reference range. For example, the processor **120** may allocate at least a part of the time interval in which the first CIS event and the second CIS event overlap each other to at least one of the first CIS event and the second CIS event, based on the scheme illustrated in the description of FIG. **6**, the scheme illustrated in the description of FIG. **7**, the scheme illustrated in the description of FIG. **9A**, and/or the scheme illustrated in the description of FIG. **10A**.

(214) As described above, the electronic device **101** may adaptively change a transmission method of the time interval in which the first CIS event and the second CIS event overlap based on a change in the wireless environment. The electronic device **101** may provide an enhanced service by such change.

(215) Although FIGS. **11A** and **11B** illustrate an example of adaptively changing the allocation of the time interval according to the state of the wireless environment, the processor **120** may adaptively change the allocation of the time interval, instead of the state of the wireless environment, based on the type of service provided through the electronic device **101**, the first external electronic device **201**, and the second external electronic device **202**.

(216) For example, the processor **120** may change the allocation corresponding to the first type of service to the allocation corresponding to the second type of service, in response to identifying that services provided through the electronic device **101**, the first external electronic device **201**, and the second external electronic device **202** are changed from the first type of service to the second type of service.

(217) In one embodiment, the electronic device and the method can provide a robust service by identifying time resources for communication between the first external electronic device and the second external electronic device based on quality of a first link between the electronic device and a first external electronic device and quality of a second link between the electronic device and a second external electronic device.

(218) As described above, in one embodiment, an electronic device (e.g., the electronic device **101**) may comprise a communication circuit (e.g., the wireless communication module **192** of FIG. **1**), and a processor (e.g., the processor **120**) operably coupled with the communication circuit.

(219) In one embodiment, the processor may be configured to obtain a CIG event including a first CIS event and a second CIS event at least partially overlapped with at least a part of the first CIS event.

(220) In one embodiment, the processor may be configured to identify first data indicating quality of a first link for the first CIS event and second data indicating quality of a second link for the

second CIS event, the first link between the electronic device and a first external electronic device, the second link between the electronic device and a second external electronic device.

(221) In one embodiment, the processor may be configured to transmit, by using the communication circuit, a first packet to the first external electronic device via a sub event of the first CIS event in a time interval where the first CIS event and the second CIS event are overlapped or transmit, by using the communication circuit, a second packet to the second external electronic device via a sub event of the second CIS event in the time interval where the first CIS event and the second CIS event are overlapped, based on the first data and the second data.

(222) In one embodiment, the processor may be configured to refrain from transmitting the first packet via the sub event of the first CIS event and transmit the second packet via the sub event of the second CIS event by using the communication circuit, based on the quality of the first link higher the quality of the second link.

(223) In one embodiment, the processor may be configured to transmit the first packet via the sub event of the first CIS event by using the communication circuit and refrain from transmitting the second packet via the sub event of the second CIS event, based on the quality of the first link lower than the quality of the second link.

(224) In one embodiment, the processor may be configured to identify the first data and the second data, after transmitting a packet to one of the first external electronic device and the second external electronic device via one of another sub event of the first CIS event and another sub event of the second CIS event, the other sub event of the first CIS event previous to the sub event of the first CIS event, the other sub event of the second CIS event previous to the sub event of the second CIS event.

(225) In one embodiment, the processor may be configured to transmit the first packet via the sub event of the first CIS event by using the communication circuit or transmit the second packet via the sub event of the second CIS event, based on the first data and the second data.

(226) In one embodiment, the processor may be configured to identify the first data by identifying a state of a first buffer for the first CIS event.

(227) In one embodiment, the processor may be configured to identify the second data by identifying a state of a second buffer for the second CIS event.

(228) In one embodiment, the processor may be configured to identify the first data indicating a number of at least one PDU at least temporarily stored in the first buffer and the second data indicating a number of at least one PDU at least temporarily stored in the second buffer, after transmitting the packet via the other sub event of the first CIS event.

(229) In one embodiment, the processor may be configured to transmit the first packet via the sub event of the first CIS event by using the communication circuit, based on the number of the at least one PDU, at least temporarily stored in the first buffer, greater than the number of the at least one PDU at least temporarily stored in the second buffer.

(230) In one embodiment, the processor may be configured to transmit the second packet via the sub event of the second CIS event by using the communication circuit, based on the number of the at least one PDU, at least temporarily stored in the first buffer, smaller than the number of the at least one PDU at least temporarily stored in the second buffer.

(231) In one embodiment, the processor may be configured to transmit the second packet via the sub event of the second CIS event by using the communication circuit, based on the number of the at least one PDU, at least temporarily stored in the first buffer, equal to the number of the at least one PDU at least temporarily stored in the second buffer.

(232) In one embodiment, the processor may be configured to allocate all of the time intervals to sub events of the first CIS event in the time interval among the sub events of the first CIS event and sub events of the second CIS event in the time interval, and transmit at least one packet including the first packet via at least a part of the sub events of the first CIS event in all of the time intervals by using the communication circuit based on the quality of the first link higher than the quality of

the second link.

(233) In one embodiment, the processor may be configured to allocate all of the time intervals to the sub events of the second CIS event among the sub events of the first CIS event and the sub events of the second CIS event, and transmit at least one packet including the second packet via at least a part of the sub events of the second CIS event in all of the time intervals by using the communication circuit, based on the quality of the first link lower than the quality of the second link.

(234) In one embodiment, the processor may be configured to allocate a first part of the time interval corresponding to the first reference range for the first CIS event, transmit at least one packet including the first packet via at least one sub event of the first CIS event in the first part of the time interval by using the communication circuit, and transmit at least one packet including the second packet via at least one sub event of the second CIS event in a second part of the time interval different from the first part of the time interval by using the communication circuit, based on difference of the first data and the second data that is within first reference range.

(235) In one embodiment, the processor may be configured to allocate a third part of the time interval corresponding to the second reference range for the first CIS event, transmit at least one packet including the first packet via at least one sub event of the first CIS event in the third part of the time interval by using the communication circuit, and transmit at least one packet including the second packet via at least one sub event of the second CIS event in a fourth part of the time interval different from the third part of the time interval by using the communication circuit, the third part of the time interval having length different from length of the first part of the time interval, based on the difference in second reference range different from the first reference range.

(236) In one embodiment, the first data may be data identified with respect to the first link based on a transmission via another CIG event, previous to the CIG event, including a third CIS event for the first link and a fourth CIS event for the second link at least partially overlapped with at least a part of the third CIS event.

(237) In one embodiment, the second data may be data identified with respect to the second link based on a transmission via another CIG event, previous to the CIG event, including a third CIS event for the first link and a fourth CIS event for the second link at least partially overlapped with at least a part of the third CIS event.

(238) In one embodiment, the processor may be configured to transmit the first packet to the first external electronic device via the sub event of the first CIS event by using the communication circuit or transmit the second packet to the second external electronic device via the sub event of the second CIS event by using the communication circuit, further based on type of a service provided through the CIG event.

(239) In one embodiment, each of the first packet and the second packet may be a packet for transmitting audio data or re-transmitting the audio data.

(240) In one embodiment, each of the first packet and the second packet may be a dummy packet or a null packet.

(241) In one embodiment, the first packet may be a packet for requesting that the first external electronic device transmits a third packet to the electronic device.

(242) In one embodiment, the second packet may be a packet for requesting that the second external electronic device transmits a fourth packet to the electronic device.

(243) In one embodiment, the processor may be further configured to receive, as a response to the first packet, the third packet via the sub event of the first CIS event from the first external electronic device by using the communication circuit, or receive, as a response to the second packet, the fourth packet via the sub event of the second CIS event from the second external electronic device by using the communication circuit.

(244) In one embodiment, identify the first data indicating remaining lifetime of the first packet scheduled to be transmitted via the sub event of the first CIS event and the second data indicating

remaining lifetime of the second packet scheduled to be transmitted via the sub event of the second CIS event, after transmitting a packet to one of the first external electronic device and the second external electronic device via one of another sub event of the first CIS event and another sub event of the second CIS event, the other sub event of the first CIS event previous to the sub event of the first CIS event, the other sub event of the second CIS event previous to the sub event of the second CIS event.

(245) In one embodiment, the processor may be configured to transmit the second packet via the sub event of the second CIS event by using the communication circuit and refrain from transmitting the first packet via the sub event of the first CIS event, based on the remaining lifetime of the first packet longer than the remaining lifetime of the second packet.

(246) In one embodiment, the processor may be configured to transmit the first packet via the sub event of the first CIS event by using the communication circuit and refrain from transmitting the second packet via the sub event of the second CIS event, based on the remaining lifetime of the first packet shorter than the remaining lifetime of the second packet.

(247) In one embodiment, the processor may be configured to identify a scheme from a first scheme allocating next transmission to the first CIS event or the second CIS event every transmitting of a packet in the time interval and a second scheme allocating at least a part of the time interval to the first CIS event and allocating at least another part of the time interval to the second CIS event before transmitting a packet in the time interval, based on the first data and the second data.

(248) In one embodiment, the processor may be configured to transmit the first packet via the sub event of the first CIS event or transmit the second packet via the sub event of the second CIS event, according to the identified scheme.

(249) The electronic device according to one or more embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. In one embodiment of the disclosure, the electronic devices are not limited to those described above.

(250) It should be appreciated that one or more embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(251) As used in connection with one or more embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, in one embodiment, the module may be implemented in a form of an Application-Specific Integrated Circuit (ASIC).

(252) One or more embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(253) In one embodiment, an operational procedure according to one or more embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., Compact Disc Read Only Memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(254) According to one or more embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to one or more embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to one or more embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to one or more embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device comprising: a communication circuit; and a processor, operably coupled with the communication circuit, configured to: obtain a Connected Isochronous Group (CIG) event including a first Connected Isochronous Stream (CIS) event and a second CIS event at least partially overlapped with at least a part of the first CIS event; identify first data indicating a quality of a first link for the first CIS event and second data indicating a quality of a second link for the second CIS event, the first link being established between the electronic device and a first external electronic device, the second link being established between the electronic device and a second external electronic device; and transmit, based on the first data and the second data by using the communication circuit, a first packet to the first external electronic device via a sub event of the first CIS event in time intervals where the first CIS event and the second CIS event are overlapped or transmit, based on the first data and the second data by using the communication circuit, a second packet to the second external electronic device via a sub event of the second CIS event in the time intervals where the first CIS event and the second CIS event are overlapped.

2. The electronic device of claim 1, wherein the processor is further configured to: refrain, based on the quality of the first link higher the quality of the second link, from transmitting the first packet via the sub event of the first CIS event or transmitting the second packet via the sub event of the second CIS event; and transmit, based on the quality of the first link lower than the quality of the second link, the first packet via the sub event of the first CIS event and refrain from transmitting the second packet via the sub event of the second CIS event.
3. The electronic device of claim 1, wherein the processor is further configured to: identify the first data and the second data, after transmitting a packet to one of the first external electronic device and the second external electronic device via one of another sub event of the first CIS event and another sub event of the second CIS event, the other sub event of the first CIS event being prior to the sub event of the first CIS event, the other sub event of the second CIS event being prior to the sub event of the second CIS event; and transmit, based on the first data and the second data, the first packet via the sub event of the first CIS event or transmit, based on the first data and the second data, the second packet via the sub event of the second CIS event.
4. The electronic device of claim 3, wherein the processor is further configured to: identify the first data by identifying a state of a first buffer for the first CIS event; and identify the second data by identifying a state of a second buffer for the second CIS event.
5. The electronic device of claim 4, wherein the processor is further configured to: identify the first data indicating a number of at least one Protocol Data Unit (PDU) at least temporarily stored in the first buffer and the second data indicating a number of at least one PDU at least temporarily stored in the second buffer, after transmitting the packet via the other sub event of the first CIS event; transmit the first packet via the sub event of the first CIS event, based on the number of the at least one PDU, at least temporarily stored in the first buffer, which is greater than the number of the at least one PDU at least temporarily stored in the second buffer; transmit the second packet via the sub event of the second CIS event, based on the number of the at least one PDU at least temporarily stored in the first buffer, which is smaller than the number of the at least one PDU at least temporarily stored in the second buffer; and transmit the second packet via the sub event of the second CIS event, based on the number of the at least one PDU at least temporarily stored in the first buffer, which is equal to the number of the at least one PDU at least temporarily stored in the second buffer.
6. The electronic device of claim 1, wherein the processor is further configured to: based on the quality of the first link, which is higher than the quality of the second link, allocate all of the time intervals to sub events of the first CIS event in the time intervals among the sub events of the first CIS event and sub events of the second CIS event in the time intervals and transmit at least one packet including the first packet via at least a part of the sub events of the first CIS event in all of the time intervals; and based on the quality of the first link, which is lower than the quality of the second link, allocate all of the time intervals to the sub events of the second CIS event among the sub events of the first CIS event and the sub events of the second CIS event and transmit at least one packet including the second packet via at least a part of the sub events of the second CIS event in all of the time intervals.
7. The electronic device of claim 1, wherein the processor is further configured to: based on a difference of the first data and the second data that is within a first reference range, allocate a first part of the time intervals corresponding to the first reference range for the first CIS event, transmit at least one packet including the first packet via at least one sub event of the first CIS event in the first part of the time intervals, and transmit at least one packet including the second packet via at least one sub event of the second CIS event in a second part of the time intervals different from the first part of the time intervals; and based on a difference in second reference range different from the first reference range, allocate a third part of the time intervals corresponding to the second reference range for the first CIS event, transmit at least one packet including the first packet via at least one sub event of the first CIS event in the third part of the time intervals, and transmit at least

one packet including the second packet via at least one sub event of the second CIS event in a fourth part of the time intervals different from the third part of the time intervals, the third part of the time intervals having length different from length of the first part of the time intervals.

8. The electronic device of claim 7, wherein the first data is identified with respect to the first link based on a transmission via another CIG event, prior to the CIG event, including a third CIS event for the first link and a fourth CIS event for the second link at least partially overlapped with at least a part of the third CIS event, and wherein the second data is identified with respect to the second link based on a transmission via another CIG event, prior to the CIG event, including a third CIS event for the first link and a fourth CIS event for the second link at least partially overlapped with at least a part of the third CIS event.

9. The electronic device of claim 1, wherein the processor is further configured to transmit the first packet to the first external electronic device via the sub event of the first CIS event or transmit the second packet to the second external electronic device via the sub event of the second CIS event, further based on a type of a service provided through the CIG event.

10. The electronic device of claim 1, wherein each of the first packet and the second packet transmits audio data.

11. The electronic device of claim 1, wherein each of the first packet and the second packet is a dummy packet or a null packet, wherein the first packet requests that the first external electronic device transmits a third packet to the electronic device, wherein the second packet requests that the second external electronic device transmits a fourth packet to the electronic device, and wherein the processor is further configured to: receive, as a response to the first packet, the third packet via the sub event of the first CIS event from the first external electronic device; or receive, as a response to the second packet, the fourth packet via the sub event of the second CIS event from the second external electronic device.

12. The electronic device of claim 1, wherein the processor is further configured to: identify the first data indicating a remaining lifetime of the first packet scheduled to be transmitted via the sub event of the first CIS event and the second data indicating a remaining lifetime of the second packet scheduled to be transmitted via the sub event of the second CIS event, after transmitting a packet to one of the first external electronic device and the second external electronic device via one of another sub event of the first CIS event and another sub event of the second CIS event, the other sub event of the first CIS event being prior to the sub event of the first CIS event, the other sub event of the second CIS event being prior to the sub event of the second CIS event; transmit the second packet via the sub event of the second CIS event and refrain from transmitting the first packet via the sub event of the first CIS event, based on the remaining lifetime of the first packet, which is longer than the remaining lifetime of the second packet; and transmit the first packet via the sub event of the first CIS event and refrain from transmitting the second packet via the sub event of the second CIS event, based on the remaining lifetime of the first packet, which is shorter than the remaining lifetime of the second packet.

13. The electronic device of claim 1, wherein the processor is further configured to: identify a scheme from a first scheme allocating a next transmission to the first CIS event or the second CIS event transmitting of a packet in the time intervals and a second scheme allocating at least a part of the time intervals to the first CIS event and allocating at least another part of the time intervals to the second CIS event before transmitting a packet in the time intervals, based on the first data and the second data; and transmit the first packet via the sub event of the first CIS event or transmit the second packet via the sub event of the second CIS event, based on the identified scheme.

14. A method for an electronic device, the method comprising: obtaining a Connected Isochronous Group (CIG) event including a first Connected Isochronous Stream (CIS) event and a second CIS event at least partially overlapped with at least a part of the first CIS event; identifying first data indicating a quality of a first link for the first CIS event and second data indicating a quality of a second link for the second CIS event, the first link being established between the electronic device

and a first external electronic device, the second link being established between the electronic device and a second external electronic device; and transmitting, based on the first data and the second data, a first packet to the first external electronic device via a sub event of the first CIS event in time intervals where the first CIS event and the second CIS event are overlapped or transmitting, based on the first data and the second data, a second packet to the second external electronic device via a sub event of the second CIS event in the time intervals where the first CIS event and the second CIS event are overlapped.

15. The method of claim 14, wherein transmitting, based on the first data and the second data, the first packet or transmitting, based on the first data and the second data, the second packet comprises: refraining, based on the quality of the first link higher the quality of the second link, from transmitting the first packet via the sub event of the first CIS event and transmitting, based on the quality of the first link higher the quality of the second link, the second packet via the sub event of the second CIS event; and transmitting, based on the quality of the first link lower than the quality of the second link, the first packet via the sub event of the first CIS event and refraining, based on the quality of the first link lower than the quality of the second link, from transmitting the second packet via the sub event of the second CIS event.

16. The method of claim 14, wherein transmitting, based on the first data and the second data, the first packet or transmitting, based on the first data and the second data, the second packet comprises: identifying the first data and the second data, after transmitting a packet to one of the first external electronic device and the second external electronic device via one of another sub event of the first CIS event and another sub event of the second CIS event, the other sub event of the first CIS event being prior to the sub event of the first CIS event, the other sub event of the second CIS event being prior to the sub event of the second CIS event; and transmitting, based on the first data and the second data, the first packet via the sub event of the first CIS event or transmitting, based on the first data and the second data, the second packet via the sub event of the second CIS event.

17. The method of claim 16, wherein identifying the first data and the second data comprises: identifying the first data by identifying a state of a first buffer for the first CIS event; and identifying the second data by identifying a state of a second buffer for the second CIS event.

18. The method of claim 17, wherein identifying the first data and the second data comprises identifying the first data indicating a number of at least one Protocol Data Unit (PDU) at least temporarily stored in the first buffer and the second data indicating a number of at least one PDU at least temporarily stored in the second buffer, after transmitting the packet via the other sub event of the first CIS event, and wherein transmitting the first packet or the second packet based on the first data and the second data comprises: transmitting the first packet via the sub event of the first CIS event, based on the number of the at least one PDU, at least temporarily stored in the first buffer, which is greater than the number of the at least one PDU at least temporarily stored in the second buffer; transmitting the second packet via the sub event of the second CIS event, based on the number of the at least one PDU, at least temporarily stored in the first buffer, which is smaller than the number of the at least one PDU at least temporarily stored in the second buffer; and transmitting the second packet via the sub event of the second CIS event, based on the number of the at least one PDU, at least temporarily stored in the first buffer, which is equal to the number of the at least one PDU at least temporarily stored in the second buffer.

19. The method of claim 14, wherein transmitting, based on the first data and the second data, the first packet or transmitting, based on the first data and the second data, the second packet comprises: based on the quality of the first link, which is higher than the quality of the second link, allocating all of the time intervals to sub events of the first CIS event in the time intervals among the sub events of the first CIS event and sub events of the second CIS event in the time intervals and transmitting at least one packet including the first packet via at least a part of the sub events of the first CIS event in all of the time intervals; and based on the quality of the first link, which is

lower than the quality of the second link, allocating all of the time intervals to the sub events of the second CIS event among the sub events of the first CIS event and the sub events of the second CIS event and transmitting at least one packet including the second packet via at least a part of the sub events of the second CIS event in all of the time intervals.

20. The method of claim 14, wherein transmitting, based on the first data and the second data, the first packet or transmitting, based on the first data and the second data, the second packet comprises: based on difference of the first data and the second data that is within a first reference range, allocating a first part of the time intervals corresponding to the first reference range for the first CIS event, transmitting at least one packet including the first packet via at least one sub event of the first CIS event in the first part of the time intervals, and transmitting at least one packet including the second packet via at least one sub event of the second CIS event in a second part of the time intervals different from the first part of the time intervals; and based on a difference in a second reference range different from the first reference range, allocating a third part of the time intervals corresponding to the second reference range for the first CIS event, transmitting at least one packet including the first packet via at least one sub event of the first CIS event in the third part of the time intervals, and transmitting at least one packet including the second packet via at least one sub event of the second CIS event in a fourth part of the time intervals different from the third part of the time intervals, the third part of the time intervals having length different from length of the first part of the time intervals.
